

Moscow ML Library Documentation

Version 2.00 of June 2000

Sergei Romanenko, Russian Academy of Sciences, Moscow, Russia
Claudio Russo, Cambridge University, Cambridge, United Kingdom
Peter Sestoft, Royal Veterinary and Agricultural University, Copenhagen, Denmark

This document

This manual describes the Moscow ML library, which includes parts of the SML Basis Library and several extensions. The manual has been generated automatically from the commented signature files.

Alternative formats of this document

Hypertext on the World-Wide Web

The manual is available at <http://www.dina.kvl.dk/~sestoft/mosmlib/> for online browsing.

Hypertext in the Moscow ML distribution

The manual is available for offline browsing at [mosml/doc/mosmlib/index.html](http://www.dina.kvl.dk/~sestoft/mosmlib/doc/mosmlib/index.html) in the distribution.

On-line help in the Moscow ML interactive system

The manual is available also in interactive mosml sessions. Type `help "lib"`; for an overview of built-in function libraries. Type `help "fromstring"`; for help on a particular identifier, such as `fromString`. This will produce a menu of all library structures which contain the identifier `fromstring` (disregarding the lowercase/upercase distinction):

| | | | | | |
|--|-------|--|-----|-------------------|--|
| | 1 | | val | Bool.fromString | |
| | 2 | | val | Char.fromString | |
| | 3 | | val | Date.fromString | |
| | 4 | | val | Int.fromString | |
| | 5 | | val | Path.fromString | |
| | 6 | | val | Real.fromString | |
| | 7 | | val | String.fromString | |
| | 8 | | val | Time.fromString | |
| | 9 | | val | Word.fromString | |
| | 10 | | val | Word8.fromString | |
| | ----- | | | | |

Choosing a number from this menu will invoke the help browser on the desired structure, e.g. `Int`.

CONTENTS

Contents

| | |
|-----------------|-----|
| AppleScript | 2 |
| Array | 3 |
| Array2 | 5 |
| ArraySlice | 8 |
| Arraysort | 11 |
| BinIO | 12 |
| Binarymap | 15 |
| Binaryset | 16 |
| Bool | 18 |
| Byte | 19 |
| Callback | 20 |
| Char | 23 |
| CharArray | 26 |
| CharArraySlice | 27 |
| CharVector | 28 |
| CharVectorSlice | 29 |
| CommandLine | 30 |
| Date | 31 |
| Dynarray | 34 |
| Dynlib | 35 |
| FileSys | 37 |
| Gdbm | 40 |
| Gdimage | 42 |
| General | 45 |
| Help | 49 |
| Int | 50 |
| Intmap | 52 |
| Inset | 53 |
| Lexing | 55 |
| List | 57 |
| ListPair | 59 |
| Listsort | 61 |
| Location | 62 |
| Math | 64 |
| Meta | 66 |
| Mosml | 70 |
| Mosmlegi | 71 |
| Mosmlcookie | 74 |
| Msp | 75 |
| Mysql | 81 |
| NJ93 | 85 |
| Nonsdio | 87 |
| OS | 88 |
| Option | 89 |
| PP | 90 |
| Parsing | 93 |
| Path | 95 |
| Polygdbm | 98 |
| Polyhash | 100 |
| Postgres | 102 |
| Process | 106 |
| Random | 107 |
| Real | 108 |
| Regex | 110 |
| SML90 | 114 |
| Signal | 115 |

| | |
|------------------|-----|
| Socket | 117 |
| Splaymap | 122 |
| Splayset | 123 |
| String | 125 |
| StringCvt | 128 |
| Substring | 130 |
| Susp | 134 |
| TextIO | 135 |
| Time | 138 |
| Timer | 140 |
| Unix | 141 |
| Vector | 142 |
| VectorSlice | 144 |
| Weak | 146 |
| Word | 149 |
| Word8 | 152 |
| Word8Array | 155 |
| Word8ArraySlice | 156 |
| Word8Vector | 157 |
| Word8VectorSlice | 158 |
| Index | 159 |

Module AppleScript

```
AppleScript -- Apple MacOS scripting
type OSASID
type OSMerr = int
exception AppleScriptErr of OSASerr * string
val as_compile      : string -> OSASID
val as_dispose      : OSASID -> unit
val as_run_script   : OSASID -> string
val as_run_text     : string -> string
```

These Mac specific functions provide the capability to compile and run AppleScript programs.

The exception AppleScriptErr is raised in the event of an error.

[as_compile str] compiles AppleScript source code text, returning an abstract token of type OSASID. This token may be used to run the script. The token may be used repeatedly until it is returned with as_dispose or until mosml exits.

[as_dispose tok] disposes of the resources associated with the OSASID token so that they may be reused by the AppleScript system. AppleScriptErr is raised upon any attempt to reuse a disposed token.

[as_run_script tok] runs the script associated with the token. This typically involves AppleEvent communication with other programs running on the Mac, or networked Macs. The AppleScript result is returned as a string.

[as_run_text str] compiles and runs the AppleScript source code text, disposing all resources allocated in the process, and returns the AppleScript result as a string.

References:

Inside Macintosh: Interapplication Communication, Chapter 10
AppleScript Language Guide English Edition,
available at <http://applescript.apple.com/support.html>

Module Array

```
Array -- SML Basis Library
prim_EQType 'a array
val maxLen   : int
val array    : int * 'a -> 'a array
val tabulate : int * (int -> 'a) -> 'a array
val fromList : 'a list -> 'a array
val length   : 'a array -> int
val sub      : 'a array * int -> 'a
val update   : 'a array * int * 'a -> unit
val vector   : 'a array -> 'a Vector.vector
val copy     : {src: 'a array, dst: 'a array, di: int} -> unit
val copyVec  : {src: 'a vector, dst: 'a array, di: int} -> unit
val find     : ('a -> bool) -> 'a array -> 'a option
val exists   : ('a -> bool) -> 'a array -> bool
val all      : ('a -> bool) -> 'a array -> bool
val app      : ('a -> unit) -> 'a array -> unit
val foldl    : ('a * 'b -> 'b) -> 'b -> 'a array -> 'b
val foldr    : ('a * 'b -> 'b) -> 'b -> 'a array -> 'b
val modify   : ('a -> 'a) -> 'a array -> unit
val findi    : (int * 'a -> bool) -> 'a array -> (int * 'a) option
val appi     : (int * 'a -> unit) -> 'a array -> unit
val foldli   : (int * 'a * 'b -> 'b) -> 'b -> 'a array -> 'b
val foldri   : (int * 'a * 'b -> 'b) -> 'b -> 'a array -> 'b
val modifyi  : (int * 'a -> 'a) -> 'a array -> unit
val collate  : ('a * 'a -> order) -> 'a array * 'a array -> order
```

['ty array] is the type of one-dimensional, mutable, zero-based constant-time-access arrays with elements of type 'ty. Type 'ty array admits equality even if 'ty does not. Arrays a1 and a2 are equal if both were created by the same call to a primitive (array, tabulate, fromList).

Functions working on a slices (contiguous subsequence) of an array are found in the ArraySlice structure.

[maxLen] is the maximal number of elements in an array.

[array(n, x)] returns a new array of length n whose elements are all x. Raises Size if n<0 or n>maxLen.

[tabulate(n, f)] returns a new array of length n whose elements are f 0, f 1, ..., f (n-1), created from left to right. Raises Size if n<0 or n>maxLen.

[fromList xs] returns an array whose elements are those of xs. Raises Size if length xs > maxLen.

[length a] returns the number of elements in a.

[sub(a, i)] returns the i'th element of a, counting from 0. Raises Subscript if i<0 or i>=length a. To make 'sub' infix, use the declaration

infix 9 sub

[update(a, i, x)] destructively replaces the i'th element of a by x. Raises Subscript if i<0 or i>=length a.

[copy(src, dst, di)] destructively copies the array src to dst, starting at index di. Raises Subscript if di<0, or if di + length src > length dst.

```
[copyVec(src, dst, di)] destructively copies the vector to dst,
starting at index di.
Raises Subscript if di<0, or if di + Vector.length src > length dst.
```

```
[find p a] applies p to each element x of a, from left to right,
until p(x) evaluates to true; returns SOME x if such an x exists,
otherwise NONE.
```

```
[exists p a] applies p to each element x of a, from left to right,
until p(x) evaluates to true; returns true if such an x exists,
otherwise false.
```

```
[all p a] applies p to each element x of a, from left to right,
until p(x) evaluates to false; returns false if such an x exists,
otherwise true.
```

```
[foldl f e a] folds function f over a from left to right. That is,
computes f(a[len-1], f(a[len-2], ..., f(a[1], f(a[0], e)) ...),
where len is the length of a.
```

```
[foldr f e a] folds function f over a from right to left. That is,
computes f(a[0], f(a[1], ..., f(a[len-2], f(a[len-1], e)) ...),
where len is the length of a.
```

```
[app f a] applies f to a[j] for j=0,1,...,length a-1.
```

```
[modify f a] applies f to a[j] and updates a[j] with the result
f(a[j]) for j=0,1,...,length a-1.
```

The following iterators generalize the above ones by passing also the index *j* to the function being iterated.

```
[findi p a] applies f to successive pairs (j, a[j]) for j=0,1,...,n-1,
until p(j, a[j]) evaluates to true; returns SOME (j, a[j]) if such
a pair exists, otherwise NONE.
```

```
[foldli f e a] folds function f over the array from left to right.
That is, computes f(n-1, a[n-1], f(..., f(1, a[1], f(0, a[0], e)) ...).
```

```
[foldri f e a] folds function f over the array from right to left.
That is, computes f(0, a[0], f(1, a[1], ..., f(n-1, a[n-1], e) ...).
```

```
[appi f a] applies f to successive pairs (j, a[j]) for j=0,1,...,n-1.
```

```
[modifiy f a] applies f to (j, a[j]) and updates a[j] with the
result f(j, a[j]) for j=0,1,...,n-1.
```

```
[collate cmp (xs, ys)] returns LESS, EQUAL or GREATER according as
xs precedes, equals or follows ys in the lexicographic ordering on
arrays induced by the ordering cmp on elements.
```

Module Array2

Array2 -- *SML Basis Library*

eqtype 'a array

datatype traversal = RowMajor | ColMajor

```
val array      : int * int * 'a -> 'a array
val fromList   : 'a list list -> 'a array
val tabulate   : traversal -> int * int * (int * int -> 'a) -> 'a array
```

```
val dimensions : 'a array -> int * int
val nCols     : 'a array -> int
val nRows     : 'a array -> int
```

```
val sub        : 'a array * int * int -> 'a
val update     : 'a array * int * int * 'a -> unit
val row        : 'a array * int -> 'a Vector.vector
val column     : 'a array * int -> 'a Vector.vector
```

```
type 'a region = { base : 'a array, row : int, col : int,
                    nRows : int option, nCols : int option}
```

```
val copy       : { src : 'a region, dst : 'a array,
                  dst_row : int, dst_col : int } -> unit
```

```
val app        : traversal -> ('a -> unit) -> 'a array -> unit
val modify     : traversal -> ('a -> 'a) -> 'a array -> unit
val fold       : traversal -> ('a * 'b -> 'b) -> 'b -> 'a array -> 'b
```

```
val appi       : traversal -> (int * int * 'a -> unit) -> 'a region -> unit
val modifiy    : traversal -> (int * int * 'a -> 'a) -> 'a region -> unit
val foldi      : traversal -> (int * int * 'a * 'b -> 'b) -> 'b
                  -> 'a region -> 'b
```

[*'ty* array] is the type of two-dimensional, mutable, zero-based constant-time-access arrays with elements of type *'ty*. Type *'ty* array admits equality even if *'ty* does not. Arrays *a1* and *a2* are equal if both were created by the same call to one of the primitives `array`, `fromList`, and `tabulate`.

[`traversal`] is the type of traversal orders: `row major` or `column major`.

[`RowMajor`] specifies that an operation must be done in row-major order, that is, one row at a time, from top to bottom, and from left to right within each row. Row-major traversal visits the elements of an (*m*,*n*)-array with *m* rows and *n* columns in this order:

```
order:  (0,0), (0,1), (0,2), ..., (0,n-1),
        (1,0), (1,1), (1,2), ..., (1,n-1),
        ...
```

that is, in order of lexicographically increasing (*i*, *j*). In Moscow ML, row-major traversal is usually faster than column-major traversal.

[`ColMajor`] specifies that an operation must be done in column-major order, that is, one column at a time, from left to right, and from top to bottom within each column. Column-major traversal visits the elements of an (*m*,*n*)-array with *m* rows and *n* columns in this order:

```
order:  (0,0), (1,0), (2,0), ..., (m-1,0),
        (0,1), (1,1), (2,1), ..., (m-1,1),
        ...
```

that is, in order of lexicographically increasing (*j*, *i*).

[`array(m, n, x)`] returns a new *m* * *n* matrix whose elements are all *x*. Raises `Size` if *n*<0 or *m*<0.

[`fromList xss`] returns a new array whose first row has elements

```

xs1, second row has elements xs2, ..., where xss = [xs1,xs2,...,xsm].
Raises Size if the lists in xss do not all have the same length.

[tabulate RowMajor (m, n, f)] returns a new m-by-n array whose
elements are f(0,0), f(0,1), ..., f(0, n-1),
f(1,0), f(1,1), ..., f(1, n-1),
...
f(m-1,0), ..., f(m-1, n-1)
created in row-major order: f(0,0), f(0,1), ..., f(1,0), f(1,1), ...
Raises Size if n<0 or m<0.

[tabulate ColMajor (m, n, f)] returns a new m-by-n array whose
elements are as above, but created in the column-major order:
f(0,0), f(1,0), ..., f(0, 1), f(1, 1), ... Raises Size if n<0 or m<0.

[dimensions a] returns the dimensions (m, n) of a, where m is the
number of rows and n the number of columns.

[nCols a] returns the number of n of columns of a.

[nRows a] returns the number of m of rows of a.

[sub(a, i, j)] returns the i'th row's j'th element, counting from 0.
Raises Subscript if i<0 or j<0 or i>=m or j>=n
where (m,n) = dimensions a.

[update(a, i, j, x)] destructively replaces the (i,j)'th element of a
by x. Raises Subscript if i<0 or j<0 or i>=m or j>=n
where (m,n) = dimensions a.

[row (a, i)] returns a vector containing the elements of the ith
row of a. Raises Subscript if i < 0 or i >= height a.

[column (a, j)] returns a vector containing the elements of the jth
column of a. Raises Subscript if j < 0 or j >= width a.

[app RowMajor f a] applies f to the elements a[0,0], a[0,1], ...,
a[0,n-1], a[1,0], ..., a[m-1, n-1] of a, where (m, n) = dimensions a.

[app ColMajor f a] applies f to the elements a[0,0], a[1,0], ...,
a[n-1,0], a[0,1], a[1,1], ..., a[m-1, n-1] of a, where (m, n) =
dimensions a.

[modify RowMajor f a] applies f to the elements a[0,0], a[0,1],
..., a[0,n-1], a[1,0], ..., a[m-1, n-1] of a, updating each element
with the result of the application, where (m, n) = dimensions a.

[modify ColMajor f a] applies f to the elements a[0,0], a[1,0],
..., a[n-1,0], a[0,1], a[1,1], ..., a[m-1, n-1] of a, updating each
element with the result of the application, where (m, n) =
dimensions a.

[fold RowMajor f b a] folds f left-right and top-down over the
elements of a in row-major order. That is, computes
f(a[m-1, n-1], f(a[m-1, n-2], ..., f(a[0,1], f(a[0,0], b)) ...))
where (m, n) = dimensions a.

[fold ColMajor f b a] folds f left-right and top-down over the
elements of a in column-major order. That is, computes
f(a[m-1, n-1], f(a[m-2, n-1], ..., f(a[1,0], f(a[0,0], b)) ...))
where (m, n) = dimensions a.

```

The following iterators generalize the above ones in two ways:

- * the indexes i and j are also being passed to the function;
- * the iterators work on a region (submatrix) of a matrix.

[region] is the type of records { base, row, col, nrows, ncols }
determining the region or submatrix of array base whose upper left
corner has index (row, col).

```

If nrows = SOME r, then the region has r rows: row, row+1, ..., row+r-1.
If nrows = NONE, then the region extends to the bottom of the matrix.
The field ncols similarly determines the number of columns.

A region is valid for an array with dimensions (m, n) if
(1) either nrows = NONE and 0 <= row <= m
    or nrows = SOME r and 0 <= row <= row + r <= m
and (2) either ncols = NONE and 0 <= col <= n
    or ncols = SOME c and 0 <= col <= col + c <= n.

[appi RowMajor f reg] applies f to (i, j, a[i, j]) in order of
lexicographically increasing (i, j) within the region reg. Raises
Subscript if reg is not valid. Note that appi tr f a is equivalent
to appi tr (f o #3) {base=a, row=0, col=0, nrows=NONE, ncols=NONE}

[appi ColMajor f reg] applies f to (i, j, a[i, j]) in order of
lexicographically increasing (j, i) within the region reg. Raises
Subscript if reg is not valid.

[foldi RowMajor f b a] folds f over (i, j, a[i, j]) in row-major
order within the region reg, that is, for lexicographically
increasing (i, j) in the region. Raises Subscript if reg is not
valid.

[foldi ColMajor f b a] folds f over (i, j, a[i, j]) in column-major
order within the region reg, that is, for lexicographically
increasing (j, i) in the region. Raises Subscript if reg is not
valid.

[copy { src, dst, dst_row, dst_col }] copies the region determined
by src to array dst such that the upper leftmost corner of src is
copied to dst[dst_row, dst_col]. Works correctly even when src and
dst are the same and the source and destination regions overlap.
Raises Subscript if the src region is invalid, or if src translated
to (dst_row, dst_col) is invalid for dst.

```

Module ArraySlice

ArraySlice -- *SML Basis Library*

```

type 'a slice

val length : 'a slice -> int
val sub : 'a slice * int -> 'a
val update : 'a slice * int * 'a -> unit
val slice : 'a Array.array * int * int option -> 'a slice
val full : 'a Array.array -> 'a slice
val subslice : 'a slice * int * int option -> 'a slice
val base : 'a slice -> 'a Array.array * int * int
val vector : 'a slice -> 'a Vector.vector
val copy : {src: 'a slice, dst: 'a Array.array, di: int} -> unit
val copyVec : {src: 'a VectorSlice.slice, dst: 'a Array.array, di: int}
-> unit
val isEmpty : 'a slice -> bool
val getItem : 'a slice -> ('a * 'a slice) option

val find : ('a -> bool) -> 'a slice -> 'a option
val exists : ('a -> bool) -> 'a slice -> bool
val all : ('a -> bool) -> 'a slice -> bool

val app : ('a -> unit) -> 'a slice -> unit
val foldl : ('a * 'b -> 'b) -> 'b -> 'a slice -> 'b
val foldr : ('a * 'b -> 'b) -> 'b -> 'a slice -> 'b
val modify : ('a -> 'a) -> 'a slice -> unit

val findi : (int * 'a -> bool) -> 'a slice -> (int * 'a) option
val appi : (int * 'a -> unit) -> 'a slice -> unit
val foldli : (int * 'a * 'b -> 'b) -> 'b -> 'a slice -> 'b
val foldri : (int * 'a * 'b -> 'b) -> 'b -> 'a slice -> 'b
val modifyi : (int * 'a -> 'a) -> 'a slice -> unit

val collate : ('a * 'a -> order) -> 'a slice * 'a slice -> order

```

[*'ty slice*] is the type of array slices, that is, sub-arrays. The slice (*a*, *n*) is valid if $0 \leq i \leq i+n \leq \text{size } s$, or equivalently, $0 \leq i$ and $0 \leq n$ and $i+n \leq \text{size } s$. A valid slice *sli* = (*a*, *n*) represents the sub-array *ali*...*i+n-1*, so the elements of *sli* are *ali*, *ali+1*, ..., *ali+n-1*, and *n* is the length of the slice. Only valid slices can be constructed by the functions below.

[*length sli*] returns the number *n* of elements in *sli* = (*s*, *n*).

[*sub (sli, k)*] returns the *k*'th element of the slice, that is, *a*[*k*] where *sli* = (*a*, *n*). Raises Subscript if $k < 0$ or $k \geq n$.

[*update (sli, k, x)*] destructively replaces the *k*'th element of *sli* by *x*. That is, replaces *a*[*k*+1] by *x*, where *sli* = (*a*, *n*). Raises Subscript if $k < 0$ or $k \geq n$.

[*slice (a, i, SOME n)*] creates the slice (*a*, *i*, length *a*-*i*), consisting of the tail of *a* starting at *i*. Raises Subscript if $i < 0$ or $i \geq \text{Array.length } a$. Equivalent to *slice (a, i, SOME(Array.length a - i))*.

[*slice (a, i, SOME n)*] creates the slice (*a*, *i*, *n*), consisting of the sub-array of *a* with length *n* starting at *i*. Raises Subscript if $i < 0$ or $n < 0$ or $i+n > \text{Array.length } a$.

| slice | meaning |
|---|----------------------------|
| (<i>a</i> , 0, NONE) | the whole array |
| (<i>a</i> , 0, SOME <i>n</i>) | a left sub-array (prefix) |
| (<i>a</i> , <i>i</i> , NONE) | a right sub-array (suffix) |
| (<i>a</i> , <i>i</i> , SOME <i>n</i>) | a general slice |

[*full a*] creates the slice (*a*, 0, length *a*).

ARRAYSLICE

Equivalent to *slice(a,0,NONE)*

[*subslice (sli, i', NONE)*] returns the slice (*a*, *i*+*i'*, *n*-*i'*) when *sli* = (*a*, *n*). Raises Subscript if $i' < 0$ or $i' > n$.

[*subslice (sli, i', SOME n')*] returns the slice (*a*, *i*+*i'*, *n'*) when *sli* = (*a*, *n*). Raises Subscript if $i' < 0$ or $n' < 0$ or $i'+n' > n$.

[*base sli*] is the concrete triple (*a*, *i*, *n*) when *sli* = (*a*, *i*, *n*).

[*vector sli*] creates and returns a vector consisting of the elements of the slice, that is, *a*[*i*..*i+n*-1] when *sli* = (*a*, *i*, *n*).

[*copy (src, dst, di)*] copies the elements of slice *src* = (*a*, *i*, *n*), that is, *a*[*i*..*i+n*-1], to the destination segment *dst*[*di*..*di+n*-1]. Raises Subscript if $di < 0$ or if $di+n > \text{length } dst$. Works also if the array underlying *sli* is the same as *dst*, and the slice overlaps with the destination segment.

[*copyVec (src, dst, di)*] copies the elements of the vector slice *src* = (*v*, *i*, *n*), that is, *v*[*i*..*i+n*-1], to *dst*[*di*..*di+n*-1]. Raises Subscript if $di < 0$, or if *len*=NONE and $di + n > \text{length } dst$.

[*isEmpty sli*] returns true if the slice *sli* = (*a*, *i*, *n*) is empty, that is, if *n*=0.

[*getItem sli*] returns *SOME(x, rst)* where *x* is the first element and *rst* the remainder of *sli*, if *sli* is non-empty; otherwise returns NONE.

[*find p sli*] applies *p* to each element *x* of *sli*, from left to right, until *p*(*x*) evaluates to true; returns *SOME x* if such an *x* exists, otherwise NONE.

[*exists p sli*] applies *p* to each element *x* of *sli*, from left to right, until *p*(*x*) evaluates to true; returns true if such an *x* exists, otherwise false.

[*all p sli*] applies *p* to each element *x* of *sli*, from left to right, until *p*(*x*) evaluates to false; returns false if such an *x* exists, otherwise true.

[*app f sli*] applies *f* to all elements of *sli* = (*a*, *i*, *n*), from left to right. That is, applies *f* to *a*[*j*+1] for $j=0,1,\dots,n$.

[*foldl f e sli*] folds function *f* over *sli* = (*a*, *i*, *n*) from left to right. That is, computes *f*(*a*[*i*+*n*-1], *f*(*a*[*i*+*n*-2], ..., *f*(*a*[*i*], *e*))....).

[*foldr f e sli*] folds function *f* over *sli* = (*a*, *i*, *n*) from right to left. That is, computes *f*(*a*[*i*], *f*(*a*[*i*+1], ..., *f*(*a*[*i*+*n*-2], *f*(*a*[*i*+*n*-1], *e*))....).

[*modify f sli*] modifies the elements of the slice *sli* = (*a*, *i*, *n*) by function *f*. That is, applies *f* to *a*[*j*] and updates *a*[*j*] with the result *f*(*a*[*j*]) for $j=0,1,\dots,n$.

The following iterators generalize the above ones by also passing the index into the array *a* underlying the slice to the function being iterated.

[*findi p sli*] applies *p* to the elements of *sli* = (*a*, *i*, *n*) and the underlying array indices, and returns the least (*j*, *a*[*j*]) for which *p*(*j*, *a*[*j*]) evaluates to true, if any; otherwise returns NONE. That is, evaluates *p*(*j*, *a*[*j*]) for $j=i, \dots, i+n-1$ until it evaluates to true for some *j*, then returns *SOME*(*j*, *a*[*j*]); otherwise returns NONE.

[*appi f sli*] applies *f* to the slice *sli* = (*a*, *i*, *n*) and the underlying array indices. That is, applies *f* to successive pairs (*j*, *a*[*j*]) for $j=i, i+1, \dots, i+n-1$.

[*foldli f e sli*] folds function *f* over the slice *sli* = (*a*, *i*, *n*) and the underlying array indices from left to right. That is, computes *f*(*i*+*n*-1, *a*[*i*+*n*-1], *f*(..., *f*(*i*+1, *a*[*i*+1], *f*(*i*, *a*[*i*], *e*)) ...).

```
[foldri f e sli] folds function f over the slice sli = (a,i,n) and
the underlying array indices from right to left. That is, computes
f(i, a[i], f(i+1, a[i+1], ..., f(i+n-1, a[i+n-1], e) ...)).

[modifiy f sli] modifies the elements of the slice sli = (a,i,n) by
applying function f to the slice elements and the underlying array
indices. That is, applies f to (j, a[j]) and updates a[j] with the
result f(j, a[j]) for j=i+1,...,i+n-1.

[collate cmp (sli1, sli2)] returns LESS, EQUAL or GREATER according
as sli1 precedes, equals or follows sli2 in the lexicographic
ordering on slices induced by the ordering cmp on elements.
```

Module Arraysort

```
Arraysort -- Quicksort for arrays, from SML/NJ library

val sort   : ('a * 'a -> order) -> 'a Array.array -> unit
val sorted : ('a * 'a -> order) -> 'a Array.array -> bool

[sort order arr] sorts array arr in-place, using ordering relation order.

[sorted order arr] returns true if the elements of array arr is
appear in (weakly) increasing order, according to ordering order.
```

Module BinIO

BinIO -- SML Basis Library

```
type elem = Word8.word
type vector = Word8Vector.vector
```

Binary input

```
type instream
```

```
val openIn      : string -> instream
val closeIn    : instream -> unit
val input      : instream -> vector
val inputAll   : instream -> vector
val inputNoBlock : instream -> vector option
val input1     : instream -> elem option
val inputN     : instream * int -> vector
val eofOfStream : instream -> bool
val lookahead   : instream -> elem option
```

Binary output

```
type ostream
```

```
val openOut      : string -> ostream
val openAppend   : string -> ostream
val closeOut     : ostream -> unit
val output       : ostream * vector -> unit
val output1      : ostream * elem -> unit
val flushOut     : ostream -> unit
```

This structure provides input/output functions on byte streams. The functions are state-based: reading from or writing to a stream changes the state of the stream. The streams are buffered: output to a stream may not immediately affect the underlying file or device.

[instream] is the type of state-based byte input streams.

[ostream] is the type of state-based byte output streams.

[elem] is the type Word8.word of bytes.

[vector] is the type of Word8Vector.vector (byte vectors).

BYTE INPUT:

[openIn s] creates a new instream associated with the file named s. Raises Io.Io if file s does not exist or is not accessible.

[closeIn istr] closes stream istr. Has no effect if istr is closed already. Further operations on istr will behave as if istr is at end of stream (that is, will return "" or NONE or true).

[input istr] reads some elements from istr, returning a vector v of those elements. The vector will be empty (size v = 0) if and only if istr is at end of stream or is closed. May block (not return until data are available in the external world).

[inputAll istr] reads and returns the vector v of all bytes remaining in istr up to end of stream.

[inputNoBlock istr] returns SOME(v) if some elements v can be read without blocking; returns SOME("") if it can be determined without blocking that istr is at end of stream; returns NONE otherwise. If istr does not support non-blocking input, raises Io.NonblockingNotSupported.

[input1 istr] returns SOME(e) if at least one element e of istr is

available; returns NONE if istr is at end of stream or is closed; blocks if necessary until one of these conditions holds.

[inputN(istr, n)] returns the next n bytes from istr as a vector, if that many are available; returns all remaining bytes if end of stream is reached before n bytes are available; blocks if necessary until one of these conditions holds.

[eofOfStream istr] returns false if any elements are available in istr; returns true if istr is at end of stream or closed; blocks if necessary until one of these conditions holds.

[lookahead istr] returns SOME(e) where e is the next element in the stream; returns NONE if istr is at end of stream or is closed; blocks if necessary until one of these conditions holds. Does not advance the stream.

BYTE OUTPUT:

[openOut s] creates a new ostream associated with the file named s. If file s does not exist, and the directory exists and is writable, then a new file is created. If file s exists, it is truncated (any existing contents are lost).

[openAppend s] creates a new ostream associated with the file named s. If file s does not exist, and the directory exists and is writable, then a new file is created. If file s exists, any existing contents are retained, and output goes at the end of the file.

[closeOut ostr] closes stream ostr; further operations on ostr (except for additional close operations) will raise exception Io.Io.

[output(ostr, v)] writes the byte vector v on ostream ostr.

[output1(ostr, e)] writes the byte e on ostream ostr.

[flushOut ostr] flushes the ostream ostr, so that all data written to ostr becomes available to the underlying file or device.

The functions below are not yet implemented:

[setPosIn(istr, i)] sets istr to the position i. Raises Io.Io if not supported on istr.

[getPosIn istr] returns the current position of istr. Raises Io.Io if not supported on istr.

[endPosIn istr] returns the last position of istr.

[getPosOut ostr] returns the current position in stream ostr. Raises Io.Io if not supported on ostr.

[endPosOut ostr] returns the ending position in stream ostr. Raises Io.Io if not supported on ostr.

[setPosOut(ostr, i)] sets the current position in stream to ostr to i. Raises Io.Io if not supported on ostr.

[mkInstream sistr] creates a state-based instream from the functional instream sistr.

[getInstream istr] returns the functional instream underlying the state-based instream istr.

[setInstream(istr, sistr)] redirects istr, so that subsequent input is taken from the functional instream sistr.

[mkOutstream sostr] creates a state-based ostream from the ostream sostr.

```
[getOutstream ostr] returns the outstream underlying the
state-based outstream ostr.

[setOutstream(ostr, sostr)] redirects the outstream ostr so that
subsequent output goes to sostr.
```

Module Binarymap

Binarymap -- applicative maps as balanced ordered binary trees
From SML/NJ lib 0.2, copyright 1993 by AT&T Bell Laboratories
Original implementation due to Stephen Adams, Southampton, UK

```
type ('key, 'a) dict
exception NotFound

val mkDict    : ('key * 'key -> order) -> ('key, 'a) dict
val insert    : ('key, 'a) dict * 'key * 'a -> ('key, 'a) dict
val find      : ('key, 'a) dict * 'key -> 'a dict
val peek      : ('key, 'a) dict * 'key -> 'a option
val remove    : ('key, 'a) dict * 'key -> ('key, 'a) dict * 'a
val numItems  : ('key, 'a) dict -> int
val listItems : ('key, 'a) dict -> ('key * 'a) list
val app       : ('key * 'a -> unit) -> ('key, 'a) dict -> unit
val revapp    : ('key * 'a -> unit) -> ('key, 'a) dict -> unit
val foldr     : ('key * 'a * 'b -> 'b) -> 'b -> ('key, 'a) dict -> 'b
val foldl     : ('key * 'a * 'b -> 'b) -> 'b -> ('key, 'a) dict -> 'b
val map       : ('key * 'a -> 'b) -> ('key, 'a) dict -> ('key, 'b) dict
val transform : ('a -> 'b) -> ('key, 'a) dict -> ('key, 'b) dict
```

[('key, 'a) dict] is the type of applicative maps from domain type 'key to range type 'a, or equivalently, applicative dictionaries with keys of type 'key and values of type 'a. They are implemented as ordered balanced binary trees.

[mkDict odr] returns a new, empty map whose keys have ordering odr.

[insert(m, i, v)] extends (or modifies) map m to map i to v.

[find (m, k)] returns v if m maps k to v; otherwise raises NotFound.

[peek(m, k)] returns SOME v if m maps k to v; otherwise returns NONE. [remove(m, k)] removes k from the domain of m and returns the modified map and the element v corresponding to k. Raises NotFound if k is not in the domain of m.

[numItems m] returns the number of entries in m (that is, the size of the domain of m).

[listItems m] returns a list of the entries (k, v) of keys k and the corresponding values v in m, in order of increasing key values.

[app f m] applies function f to the entries (k, v) in m, in increasing order of k (according to the ordering odr used to create the map or dictionary).

[revapp f m] applies function f to the entries (k, v) in m, in decreasing order of k.

[foldl f e m] applies the folding function f to the entries (k, v) in m, in increasing order of k.

[foldr f e m] applies the folding function f to the entries (k, v) in m, in decreasing order of k.

[map f m] returns a new map whose entries have form (k, f(k,v)), where (k, v) is an entry in m.

[transform f m] returns a new map whose entries have form (k, f v), where (k, v) is an entry in m.

Module Binaryset

Binaryset -- sets implemented by ordered balanced binary trees
From SML/NJ lib 0.2, copyright 1993 by AT&T Bell Laboratories
Original implementation due to Stephen Adams, Southampton, UK

```
type 'item set
exception NotFound

val empty      : ('item * 'item -> order) -> 'item set
val singleton  : ('item * 'item -> order) -> 'item -> 'item set
val add        : 'item set * 'item -> 'item set
val addlist    : 'item set * 'item list -> 'item set
val retrieve    : 'item set * 'item -> 'item
val peek       : 'item set * 'item -> 'item option
val isEmpty    : 'item set -> bool
val equal      : 'item set * 'item set -> bool
val isSubset   : 'item set * 'item set -> bool
val member     : 'item set * 'item -> bool
val delete     : 'item set * 'item -> 'item set
val numItems   : 'item set -> int
val union      : 'item set * 'item set -> 'item set
val intersection : 'item set * 'item set -> 'item set
val difference  : 'item set * 'item set -> 'item set
val listItems  : 'item set -> 'item list
val app        : ('item -> unit) -> 'item set -> unit
val revapp     : ('item -> unit) -> 'item set -> unit
val foldr      : ('item * 'b -> 'b) -> 'b -> 'item set -> 'b
val foldl      : ('item * 'b -> 'b) -> 'b -> 'item set -> 'b
val find       : ('item -> bool) -> 'item set -> 'item option

['item set] is the type of sets of ordered elements of type 'item.
The ordering relation on the elements is used in the representation
of the set. The result of combining two sets with different
underlying ordering relations is undefined. The implementation
uses ordered balanced binary trees.

[empty ordx] creates a new empty set with the given ordering
relation.

[singleton ordx i] creates the singleton set containing i, with the
given ordering relation.

[add(s, i)] adds item i to set s.

[addlist(s, xs)] adds all items from the list xs to the set s.

[retrieve(s, i)] returns i if it is in s; raises NotFound otherwise.

[peek(s, i)] returns SOME i if i is in s; returns NONE otherwise.

[isEmpty s] returns true if and only if the set is empty.

[equal(s1, s2)] returns true if and only if the two sets have the
same elements.

[isSubset(s1, s2)] returns true if and only if s1 is a subset of s2.

[member(s, i)] returns true if and only if i is in s.

[delete(s, i)] removes item i from s. Raises NotFound if i is not in s.

[numItems s] returns the number of items in set s.

[union(s1, s2)] returns the union of s1 and s2.

[intersection(s1, s2)] returns the intersection of s1 and s2.

[difference(s1, s2)] returns the difference between s1 and s2 (that
is, the set of elements in s1 but not in s2).
```

```
[listItems s] returns a list of the items in set s, in increasing
order.

[app f s] applies function f to the elements of s, in increasing
order.

[revapp f s] applies function f to the elements of s, in decreasing
order.

[foldl f e s] applies the folding function f to the entries of the
set in increasing order.

[foldr f e s] applies the folding function f to the entries of the
set in decreasing order.

[find p s] returns SOME i, where i is an item in s which satisfies
p, if one exists; otherwise returns NONE.
```

Module Bool

```
Bool -- SML Basis Library

datatype bool = datatype bool

val not      : bool -> bool
val toString : bool -> string
val fromString : string -> bool option
val scan : (char, 'a) StringCvt.reader -> (bool, 'a) StringCvt.reader
```

[bool] is the type of Boolean (logical) values: true and false.

[not b] is the logical negation of b.

[toString b] returns the string "false" or "true" according as b is false or true.

[fromString s] scans a boolean b from the string s, after possible initial whitespace (blanks, tabs, newlines). Returns (SOME b) if s has a prefix which is either "false" or "true"; the value b is the corresponding truth value; otherwise NONE is returned.

[scan getc src] scans a boolean b from the stream src, using the stream accessor getc. In case of success, returns SOME(b, rst) where b is the scanned boolean value and rst is the remainder of the stream; otherwise returns NONE.

Module Byte

```
Byte -- SML Basis Library

val byteToChar      : Word8.word -> Char.char
val charToByte      : Char.char -> Word8.word
val bytesToString   : Word8Vector.vector -> String.string
val stringToBytes    : String.string -> Word8Vector.vector
val unpackStringVec : Word8Vector.vector * int * int option -> string
val unpackString     : Word8Array.array * int * int option -> string
val packString       : Word8Array.array * int * Substring.substring -> unit
```

Conversions between bytes and characters, and between byte vectors and strings (character vectors).

[byteToChar w] is the character corresponding to the byte w.

[charToByte c] is the byte corresponding to character c.

[bytesToString v] is the string whose character codes are the bytes from vector v.

[stringToBytes s] is the byte vector of character codes of the string s.

In Moscow ML, all the above operations take constant time. That is, no copying is done.

[unpackStringVec (v, i, NONE)] is the string whose character codes are the bytes of v[i..length v-1]. Raises Subscript if i<0 or i>length v.

[unpackStringVec (v, i, SOME n)] is the string whose character codes are the bytes of v[i..i+n-1]. Raises Subscript if i<0 or i+n>length v.

[unpackString (a, i, NONE)] is the string whose character codes are the bytes of a[i..length a-1]. Raises Subscript if i<0 or i>length a.

[unpackString (a, i, SOME n)] is the string whose character codes are the bytes of a[i..i+n-1]. Raises Subscript if i<0 or n<0 or i+n>length a.

[packString (a, i, ss)] copies the character codes of substring ss into the subarray a[i..i+n-1] where n = Substring.size ss. Raises Subscript if i<0 or i+n > length a.

Module Callback

Callback -- registering ML values with C, and accessing C values from ML

Registering ML values for access from C code:

```
val register      : string -> 'a -> unit
val unregister   : string -> unit
val isRegistered : string -> bool
```

Accessing C variables and functions from ML:

```
type cptr

val getcptr : string -> cptr
val var     : cptr -> 'b
val app1    : cptr -> 'a1 -> 'b
val app2    : cptr -> 'a1 -> 'a2 -> 'b
val app3    : cptr -> 'a1 -> 'a2 -> 'a3 -> 'b
val app4    : cptr -> 'a1 -> 'a2 -> 'a3 -> 'a4 -> 'b
val app5    : cptr -> 'a1 -> 'a2 -> 'a3 -> 'a4 -> 'a5 -> 'b
```

REGISTERING ML VALUES FOR ACCESS FROM C CODE

This example shows how to register the ML function (fn n => 2*n) so that it may be called from C code.

- (0) The ML side registers the function:
 Callback.register "myfun" (fn n => 2*n)
- (1) The C side first obtains an ML value pointer:
 valueptr mvp = get_valueptr("myfun");
- (2) The C side then uses the ML value pointer to obtain an ML value, and uses it:
 callback(get_value(mvp), Val_long(42));

Operation (1) involves a callback to ML, and hence may be slow. Calling get_valueptr may cause the garbage collector to run; hence other live ML values must be registered as GC roots. The garbage collector will never move the ML value pointer; hence it need not be registered as a GC root in the C code.

Operation (2) is very fast. If the garbage collector is invoked between the call of get_value() and the use of the ML value, then the value must be registered as a GC root. However, the idiom
 callback(get_value(mvp), arg1);
is safe provided the evaluation of arg1 does not provoke a garbage collection (e.g. if arg1 is a variable).

The C function get_valueptr returns NULL if nam is not registered.

The C function get_value returns NULL if nam has been unregistered (and not reregistered) since mvp was obtained; it raises exception Fail if mvp itself is NULL. Every access to the ML value from C code should use the ML valueptr and get_valueptr, otherwise the C code will not know when the value has been unregistered and possibly deallocated.

```
The C functions (in mosml/src/runtime/callback.c)
void registervalue(char* nam, value mval)
void unregistervalue(char* nam)
can be used just as Callback.register and Callback.unregister.
```

The C functions
 value callbackptr (valueptr mvp, value arg1)
 value callbackptr2(valueptr mvp, value arg1, value arg2)
 value callbackptr3(valueptr mvp, value arg1, value arg2, value arg3)
can be used for callback via an ML value pointer; they will raise

exception Fail if the ML function indicated by mvp has been unregistered.

[register nam v] registers the ML value v, so that it can be retrieved from C code under the name nam. If nam has previously been registered and then unregistered, it will be reregistered with the new value. The new value immediately becomes visible to the C side, both via get_valueptr(nam) and via any ML value pointer previously obtained for nam. Raises exception Fail if nam has been registered and not yet unregistered.

[unregister nam] deletes the registration. This prevents C code from obtaining an ML value pointer for nam and from using an ML value pointer already obtained (but does not prevent C from attempting to use a stored ML value previously obtained with the help of the ML value pointer, which is unsafe anyway). Does nothing if nam is already unregistered. Raises exception Fail if nam has never been registered.

[isRegistered nam] returns true if nam has been registered and not yet unregistered.

ACCESSING REGISTERED C VARIABLES AND FUNCTIONS FROM ML

This example shows how to register the C function

```
value silly_cfuns(value v)
{ return copy_double(42.42 * Double_val(v)); }
```

so that it may be called from ML.

- (0) The C side registers the function:
 registercptr("mycfun", sillycfun);
- (1) The ML side obtains a C pointer and defines an ML function via that pointer:
 val sillycfun = app1 (getcptr "mycfun") : real -> real
 The type ascription is needed to ensure any type safety whatsoever. Mistakes in the types will lead to crashes, as usual with C.
- (2) To the ML side, the new ML function is indistinguishable from other ML functions
 val result = sillyfun(3.4)

The C function (in mosml/src/runtime/callback.c)
 void registercptr(char* nam, void* cptr);

is used to register C pointers for access from ML. Only pointers to static C variables, and C functions, should be registered. There is no way to unregister a C pointer.

[cptr] is the type of pointers to C variables and C functions.

[getcptr nam] returns a pointer to the C variable or function registered (by the C side) under the name nam. Raises exception Fail if the name nam has not been registered.

[var cptr] returns the value of the C variable associated with cptr.

[app1 cptr arg1] applies the C function associated with cptr to arg1.

[app2 cptr arg1 arg2] applies the C function associated with cptr to (arg1, arg2).

[app3 cptr arg1 arg2 arg3] applies the C function associated with cptr to (arg1, arg2, arg3).

[app4 cptr arg1 arg2 arg3 arg4] applies the C function associated with cptr to (arg1, arg2, arg3, arg4).

[app5 optr arg1 arg2 arg3 arg4 arg5] applies the C function associated with optr to (arg1, arg2, arg3, arg4, arg5).

Module Char

Char -- SML Basis Library

type char = char

val minChar : char
val maxChar : char
val maxOrd : int

val chr : int -> char
val ord : char -> int
val succ : char -> char
val pred : char -> char
May raise Chr
May raise Chr
May raise Chr

val isLower : char -> bool
val isUpper : char -> bool
val isDigit : char -> bool
val isAlpha : char -> bool
val isHexDigit : char -> bool
val isAlphaNum : char -> bool
val isPrint : char -> bool
val isSpace : char -> bool
val isPunct : char -> bool
val isGraph : char -> bool
val isAscii : char -> bool
val isCntrl : char -> bool
contains "abcdefghijklmnopqrstuvwxyz"
contains "ABCDEFGHIJKLMNOPQRSTUVWXYZ"
contains "0123456789"
isUpper orelse isLower
isDigit orelse isLower
isAlpha orelse isDigit
any printable character (incl. # " ")
contains "\t\r\n\v\f"
printable, not space or alphanumeric
(not isSpace) and also isPrint
ord c < 128
control character

val toLower : char -> char
val toUpper : char -> char

val fromString : string -> char option
val toString : char -> string
ML escape sequences
ML escape sequences

val fromCString : string -> char option
val toCString : char -> string
C escape sequences
C escape sequences

val contains : string -> char -> bool
val notContains : string -> char -> bool

val < : char * char -> bool
val <= : char * char -> bool
val > : char * char -> bool
val >= : char * char -> bool
val compare : char * char -> order

[char] is the type of characters.

[minChar] is the least character in the ordering <.

[maxChar] is the greatest character in the ordering <.

[maxOrd] is the greatest character code; equals ord(maxChar).

[chr i] returns the character whose code is i. Raises Chr if i < 0 or i > maxOrd.

[ord c] returns the code of character c.

[succ c] returns the character immediately following c, or raises Chr if c = maxChar.

[pred c] returns the character immediately preceding c, or raises Chr if c = minChar.

[isLower c] returns true if c is a lowercase letter (a to z).

[isUpper c] returns true if c is an uppercase letter (A to Z).

[isDigit c] returns true if c is a decimal digit (0 to 9).

```

[isAlpha c] returns true if c is a letter (lowercase or uppercase).
[isHexDigit c] returns true if c is a hexadecimal digit (0 to 9 or a to f or A to F).
[isAlphaNum c] returns true if c is alphanumeric (a letter or a decimal digit).
[isPrint c] returns true if c is a printable character (space or visible)
[isSpace c] returns true if c is a whitespace character (blank, newline, tab, vertical tab, new page).
[isGraph c] returns true if c is a graphical character, that is, it is printable and not a whitespace character.
[isPunct c] returns true if c is a punctuation character, that is, graphical but not alphanumeric.
[isCtrl c] returns true if c is a control character, that is, if not (isPrint c).
[isAscii c] returns true if 0 <= ord c <= 127.
[toLowerCase] returns the lowercase letter corresponding to c, if c is a letter (a to z or A to Z); otherwise returns c.
[toUpperCase] returns the uppercase letter corresponding to c, if c is a letter (a to z or A to Z); otherwise returns c.
[contains s c] returns true if character c occurs in the string s; false otherwise. The function, when applied to s, builds a table and returns a function which uses table lookup to decide whether a given character is in the string or not. Hence it is relatively expensive to compute val p = contains s but very fast to compute p(c) for any given character.
[notContains s c] returns true if character c does not occur in the string s; false otherwise. Works by construction of a lookup table in the same way as the above function.
[fromString s] attempts to scan a character or ML escape sequence from the string s. Does not skip leading whitespace. For instance, fromString "\\065" equals #A".
[toString c] returns a string consisting of the character c, if c is printable, else an ML escape sequence corresponding to c. A printable character is mapped to a one-character string: bell, backspace, tab, newline, vertical tab, form feed, and carriage return are mapped to the two-character strings "\a", "\b", "\t", "\n", "\v", "\f", and "\r"; other characters with code less than 32 are mapped to three-character strings of the form "\\>z", and characters with codes 127 through 255 are mapped to four-character strings of the form "\\ddd", where ddd are three decimal digits representing the character code. For instance,
toString #A" equals "A"
toString #"\" equals "\"
toString #\" equals "\"
toString (chr 0) equals "\\0"
toString (chr 1) equals "\\A"
toString (chr 6) equals "\\F"
toString (chr 7) equals "\\a"
toString (chr 8) equals "\\b"
toString (chr 9) equals "\\t"
toString (chr 10) equals "\\n"
toString (chr 11) equals "\\v"
toString (chr 12) equals "\\f"
toString (chr 13) equals "\\r"
toString (chr 14) equals "\\N"
toString (chr 127) equals "\\127"
toString (chr 128) equals "\\128"

```

```

[fromCString s] attempts to scan a character or C escape sequence from the string s. Does not skip leading whitespace. For instance, fromCString "\\065" equals #A".
[toCString c] returns a string consisting of the character c, if c is printable, else an C escape sequence corresponding to c. A printable character is mapped to a one-character string: bell, backspace, tab, newline, vertical tab, form feed, and carriage return are mapped to the two-character strings "\a", "\b", "\t", "\n", "\v", "\f", and "\r"; other characters are mapped to four-character strings of the form "\\ooo", where ooo are three octal digits representing the character code. For instance,
toString #A" equals "A"
toString #"\" equals "\"
toString #"\" equals "\"
toString (chr 0) equals "\\000"
toString (chr 1) equals "\\001"
toString (chr 6) equals "\\006"
toString (chr 7) equals "\\a"
toString (chr 8) equals "\\b"
toString (chr 9) equals "\\t"
toString (chr 10) equals "\\n"
toString (chr 11) equals "\\v"
toString (chr 12) equals "\\f"
toString (chr 13) equals "\\r"
toString (chr 14) equals "\\016"
toString (chr 127) equals "\\177"
toString (chr 128) equals "\\200"

[<]
[<=]
[>]
[>=] compares character codes. For instance, c1 < c2 returns true if ord(c1) < ord(c2), and similarly for <=, >, >=.
[compare(c1, c2)] returns LESS, EQUAL, or GREATER, according as c1 is precedes, equals, or follows c2 in the ordering Char.< .

```

Module CharArray

CharArray -- *SML Basis Library*

```

eqtype array = Char.char
type elem   = CharVector.vector
type vector = CharVector.vector

val maxLen  : int

val array      : int * elem -> array
val tabulate  : int * (int -> elem) -> array
val fromList  : elem list -> array

val length    : array -> int
val sub       : array * int -> elem
val update    : array * int * elem -> unit
val vector    : array -> vector

val copy      : {src: array, dst: array, di: int} -> unit
val copyVec   : {src: vector, dst: array, di: int} -> unit

val find      : (elem -> bool) -> array -> elem option
val exists    : (elem -> bool) -> array -> bool
val all       : (elem -> bool) -> array -> bool

val app       : (elem -> unit) -> array -> unit
val foldl     : (elem * 'b -> 'b) -> 'b -> array -> 'b
val foldr     : (elem * 'b -> 'b) -> 'b -> array -> 'b
val modify    : (elem -> elem) -> array -> unit

val findi     : (int * elem -> bool) -> array -> (int * elem) option
val appi      : (int * elem -> unit) -> array -> unit
val foldli    : (int * elem * 'b -> 'b) -> 'b -> array -> 'b
val foldri    : (int * elem * 'b -> 'b) -> 'b -> array -> 'b
val modifyi   : (int * elem -> elem) -> array -> unit

val collate   : (elem * elem -> order) -> array * array -> order

```

[array] is the type of one-dimensional, mutable, zero-based constant-time-access arrays with elements of type Char.char, that is, characters. Arrays a1 and a2 are equal if both were created by the same call to a primitive, or if both are empty.

All operations are as for Array.array.

Module CharArraySlice

CharArraySlice -- *SML Basis Library*

```

type elem = char
type array = CharArray.array
type vector = CharVector.vector
type vector_slice = CharVectorSlice.slice

type slice

val length    : slice -> int
val sub       : slice * int -> elem
val update    : slice * int * elem -> unit
val slice     : array * int * int option -> slice
val full      : array -> slice
val subslice  : slice * int * int option -> slice
val base      : slice -> array * int * int
val vector     : slice -> vector
val copy      : {src: slice, dst: array, di: int} -> unit
val copyVec   : {src: vector_slice, dst: array, di: int} -> unit
val isEmpty   : slice -> bool
val getItem   : slice -> (elem * slice) option

val find      : (elem -> bool) -> slice -> elem option
val exists    : (elem -> bool) -> slice -> bool
val all       : (elem -> bool) -> slice -> bool

val app       : (elem -> unit) -> slice -> unit
val foldl     : (elem * 'b -> 'b) -> 'b -> slice -> 'b
val foldr     : (elem * 'b -> 'b) -> 'b -> slice -> 'b
val modify    : (elem -> elem) -> slice -> unit

val findi     : (int * elem -> bool) -> slice -> (int * elem) option
val appi      : (int * elem -> unit) -> slice -> unit
val foldli    : (int * elem * 'b -> 'b) -> 'b -> slice -> 'b
val foldri    : (int * elem * 'b -> 'b) -> 'b -> slice -> 'b
val modifyi   : (int * elem -> elem) -> slice -> unit

val collate   : (elem * elem -> order) -> slice * slice -> order

```

[slice] is the type of CharArray slices, that is, sub-arrays of CharArray.array values.

The slice (a,i,n) is valid if 0 ≤ i ≤ i+n ≤ size s, or equivalently, 0 ≤ i and 0 ≤ n and i+n ≤ size s. A valid slice sli = (a,i,n) represents the sub-array a[i..i+n-1], so the elements of sli are a[i], a[i+1], ..., a[i+n-1], and n is the length of the slice. Only valid slices can be constructed by the functions below.

All operations are as for ArraySlice.slice.

Module CharVector

CharVector -- SML Basis Library

```
type vector = string
type elem = Char.char

val maxLen : int

val fromList : elem list -> vector
val tabulate : int * (int -> elem) -> vector

val length : vector -> int
val sub : vector * int -> elem
val update : vector * int * elem -> vector
val concat : vector list -> vector

val find : (elem -> bool) -> vector -> elem option
val exists : (elem -> bool) -> vector -> bool
val all : (elem -> bool) -> vector -> bool

val app : (elem -> unit) -> vector -> unit
val map : (elem -> elem) -> vector -> vector
val foldl : (elem * 'b -> 'b) -> 'b -> vector -> 'b
val foldr : (elem * 'b -> 'b) -> 'b -> vector -> 'b

val findi : (int * elem -> bool) -> vector -> (int * elem) option
val appi : (int * elem -> unit) -> vector -> unit
val mapi : (int * elem -> elem) -> vector -> vector
val foldli : (int * elem * 'b -> 'b) -> 'b -> vector -> 'b
val foldri : (int * elem * 'b -> 'b) -> 'b -> vector -> 'b

val collate : (elem * elem -> order) -> vector * vector -> order
```

[vector] is the type of one-dimensional, immutable, zero-based constant-time-access vectors with elements of type Char.char, that is, characters. Type vector admits equality, and vectors v1 and v2 are equal if they have the same length and their elements are equal. The type vector is the same as String.string.

All operations are as for Vector.vector.

Module CharVectorSlice

CharVectorSlice -- SML Basis Library

```
type elem = Char.char
type vector = CharVector.vector

type slice = Substring.substring

val length : slice -> int
val sub : slice * int -> elem
val slice : vector * int * int option -> slice
val full : vector -> slice
val subSlice : slice * int * int option -> slice
val base : slice -> vector * int * int
val vector : slice -> vector
val concat : slice list -> vector
val isEmpty : slice -> bool
val getItem : slice -> (elem * slice) option

val find : (elem -> bool) -> slice -> elem option
val exists : (elem -> bool) -> slice -> bool
val all : (elem -> bool) -> slice -> bool

val app : (elem -> unit) -> slice -> unit
val map : (elem -> elem) -> slice -> vector
val foldl : (elem * 'b -> 'b) -> 'b -> slice -> 'b
val foldr : (elem * 'b -> 'b) -> 'b -> slice -> 'b

val findi : (int * elem -> bool) -> slice -> (int * elem) option
val appi : (int * elem -> unit) -> slice -> unit
val mapi : (int * elem -> elem) -> slice -> vector
val foldli : (int * elem * 'b -> 'b) -> 'b -> slice -> 'b
val foldri : (int * elem * 'b -> 'b) -> 'b -> slice -> 'b

val collate : (elem * elem -> order) -> slice * slice -> order
```

[slice] is the type of CharVector slices, that is, sub-vectors of CharVector.vector values. Since a CharVector.vector is a string, a slice is the same as a substring, and slices may be processed using the functions defined as well as those in structure Substring.

The slice (a,i,n) is valid if 0 <= i <= i+n <= size s, or equivalently, 0 <= i and 0 <= n and i+n <= size s. A valid slice sli = (a,i,n) represents the sub-vector a[i..i+n-1], so the elements of sli are a[i], a[i+1], ..., a[i+n-1], and n is the length of the slice. Only valid slices can be constructed by these functions.

All operations are as for VectorSlice.slice.

Module CommandLine

CommandLine -- SML Basis Library

```
val name      : unit -> string
val arguments : unit -> string list
```

[name ()] returns the name used to start the current process.

[arguments ()] returns the command line arguments of the current process.
Hence List.nth(arguments (), 0) is the first argument.

Module Date

Date -- SML Basis Library

```
datatype weekday = Mon | Tue | Wed | Thu | Fri | Sat | Sun
```

```
datatype month = Jan | Feb | Mar | Apr | May | Jun
               | Jul | Aug | Sep | Oct | Nov | Dec
```

type date

exception Date

```
val date : {
  year   : int,           e.g. 1999
  month  : month,         Jan, Feb, ...
  day    : int,           1-31
  hour   : int,           0-23
  minute : int,           0-59
  second : int,           0-61, permitting leap seconds
  offset : Time.time option time zone west of UTC
} -> date
```

```
val year      : date -> int
val month     : date -> month
val day       : date -> int
val hour      : date -> int
val minute    : date -> int
val second    : date -> int
val weekday   : date -> weekday
val yearDay   : date -> int
val isDST     : date -> bool option
val offset    : date -> Time.time option
```

```
val compare   : date * date -> order
```

```
val toString  : date -> string
val fmt       : string -> date -> string
val fromString : string -> date option
val scan      : (char, 'a) StringCvt.reader -> (date, 'a) StringCvt.reader
```

```
val fromTimeLocal : Time.time -> date
val fromTimeUniv  : Time.time -> date
val toTime        : date -> Time.time
val localOffset   : unit -> Time.time
```

These functions convert times to dates and vice versa, and format and scan dates.

[date] is the type of points in time in a given time zone. If the offset is NONE, then the date is in the local time zone. If the offset is SOME t, then t is the offset of the main timezone (ignoring daylight savings time) west of UTC.

When 0 hours <= t < 12 hours, the represented time is to the west of UTC and the local time is UTC-t.
When 12 hours <= t < 23 hours, the represented time is to the East of UTC and the local time is UTC+(24-t).

[date { year, month, day, hour, minute, second, offset }] returns a canonical date value. Seconds outside the range 0..59 are converted to the equivalent minutes and added to the minutes argument; leap seconds are ignored. Similarly, excess minutes are converted to hours, hours to days, days to months, and months to years. Then the weekday and day number in the year are computed. Leap years are assumed in accordance with the Gregorian calendar, for any year after year 0 A.D.

If the offset is greater than one day (24 hours), then the excess days are added to the days, and the offset modulo 24 hours is used.


```
[year dt] returns the year of dt, e.g. 1999.
[month dt] returns the month of dt.
[day dt] returns the day of dt
[hour dt] returns the hour of dt.
[minute dt] returns the minute of dt.
[second dt] returns the second of dt.
[weekDay dt] returns the weekday of dt.
[yearDay dt] returns the number of the day in the year of dt.
January 1 is day 0, and December 31 is day 364 (and 365 in leap years).
[isdst dt] returns SOME(true) if daylight savings time is in effect
at the date dt; returns SOME(false) if not; and returns NONE if
this information is unavailable.
[offset dt] returns NONE if the date dt is in the local time zone;
returns SOME t where t is the offset west of UTC otherwise. Thus
SOME(Time.zeroTime) is UTC.
[compare(dt1, dt2)] returns LESS, EQUAL, or GREATER, according as
date dt1 precedes, equals, or follows dt2 in time.
Lexicographically compares the dates. Ignores timezone offset and
DST. Does not detect invalid dates.
[toString dt] returns a 24 character string representing the date dt
in the following format:
      Wed Mar  8 19:06:45 1995
The result may be wrong if the date is not representable as a
Time.time value. Raises Date if dt is an invalid date.
Corresponds to the ANSI C function 'asctime'.
[fmt fmtstr dt] formats the date dt according to the format string
fmtstr. The format string has the same meaning as with the ANSI C
function 'strftime'. These ANSI C format codes should work on all
platforms:
%a abbreviated weekday name (e.g. "Mon")
%A full weekday name (e.g. "Monday")
%b abbreviated month name (e.g. "Oct")
%B full month name (e.g. "October")
%c date and time (e.g. "Dec 2 06:55:15 1979")
%d day of month (01..31)
%H hour (00..23)
%i hour (01..12)
%j day of year (001..366)
%m month number (01..12)
%M minutes (00..59)
%p locale's equivalent of a.m./p.m.
%S seconds (00..61, allowing for leap seconds)
%U week number (00..53), with Sunday as the first day of week 01
%w day of week, with 0 representing Sunday (0..6)
%W week number (00..53), with Monday as the first day of week 01
%x locale's appropriate date representation
%Y year of century (00..99)
%y year including century (e.g. 1997)
%Z time zone name if it exists; otherwise the empty string
%% the percent character
```

Example: The current local date in ISO format (e.g. 1998-04-06) can be obtained by using:

```
fmt "%Y-%m-%d" (fromTimeLocal (Time.now ()))
```

[fromString s] scans a 24-character date from the string s, after possible initial whitespace (blanks, tabs, newlines). The format of the string must be as produced by toString. The fields isdst and offset in the resulting date will be NONE. No check of the

consistency of the date (weekday, date in the month, ...) is performed.

[scan getc src] scans a 24-character date from the stream src, using the stream accessor getc. Otherwise works as fromString. In case of success, returns SOME(date, rst) where date is the scanned date and rst is the remainder of the stream; otherwise returns NONE.

[fromTimeLocal t] returns the local date at (UTC) time t. The resulting date will have offset = NONE. The fields year, month, day, hour, minute, and second are as expected. The resulting isdst may be NONE if the system cannot determine whether daylight savings time is in effect at the given time. Corresponds to the ANSI C function 'localtime'.

[fromTimeUniv t] is similar to fromTime, but returns the UTC date at (UTC) time t. The resulting date will have offset = SOME Time.zeroTime. Corresponds to the ANSI C function 'gmtime'.

[toTime dt] returns the (UTC) time corresponding to the date dt. Uses the isdst time field if it is present (SOME _) and cannot be calculated from the given date. May raise Date if the given date is invalid. Raises Time.time if the Date cannot be represented as a Time.time value. At least the dates in the interval 1970-2030 can be represented as Time.time values. Corresponds to the ANSI C function 'mktime'.

[localOffset ()] is the local time zone offset west of UTC. It holds that 0 hours <= localOffset () < 24 hours.

Module Dynarray

Dynarray -- polymorphic dynamic arrays a la SML/NJ library

```
type 'a array
val array : int * 'a -> 'a array
val subarray : 'a array * int * int -> 'a array
val fromList : 'a list * 'a -> 'a array
val tabulate : int * (int -> 'a) * 'a -> 'a array
val sub : 'a array * int -> 'a
val update : 'a array * int * 'a -> unit
val default : 'a array -> 'a
val bound : 'a array -> int

['ty array] is the type of one-dimensional, mutable, zero-based
unbounded arrays with elements of type 'ty. Type 'ty array does
not admit equality.

[array(n, d)] returns a dynamic array, all of whose elements are
initialized to the default d. The parameter n is used as a hint of the
upper bound on non-default elements. Raises Size if n < 0.

[subarray(a, m, n)] returns a new array with the same default
value as a, and whose values in the range [0..n-m] equal the
values in a in the range [m..n]. Raises the exception Size if n < m.

[fromList(xs, d)] returns an array whose first elements are
those of [xs], and the rest are the default d.

[tabulate(n, f, d)] returns a new array whose first n elements
are f 0, f 1, ..., f (n-1), created from left to right, and whose
remaining elements are the default d. Raises Size if n < 0.

[sub(a, i)] returns the i'th element of a, counting from 0.
Raises Subscript if i < 0.

[update(a, i, x)] destructively replaces the i'th element of a by x.
Raises Subscript if i < 0.

[default a] returns the default value of the array a.

[bound a] returns an upper bound on the indices of non-default values.
```

Module Dynlib

Dynlib -- dynamic linking with foreign functions

```
type dHandle
type symHandle
exception Closed
datatype flag = RTLD_LAZY | RTLD_NOW
val dlopen : { lib : string, flag : flag, global : bool } -> dHandle
val dlsym : dHandle -> string -> symHandle
val dlclose : dHandle -> unit
val var : symHandle -> 'b
val appl : symHandle -> 'a1 -> 'b
val app2 : symHandle -> 'a1 -> 'a2 -> 'b
val app3 : symHandle -> 'a1 -> 'a2 -> 'a3 -> 'b
val app4 : symHandle -> 'a1 -> 'a2 -> 'a3 -> 'a4 -> 'b
val app5 : symHandle -> 'a1 -> 'a2 -> 'a3 -> 'a4 -> 'a5 -> 'b
```

Structure Dynlib provides dynamic loading and calling of C functions, using the dlopen interface. A dynamic library is a collection of symbols (C variables and functions).

An ML value passed to or returned from a symbol has type 'value' as defined in src/runtime/mlvalues.h. The C functions should use the macros defined there to access and produce ML values. When writing a C function, remember that the garbage collector may be activated whenever you allocate an ML value. Also, remember that the garbage collector may move values from the young heap to the old one, so that a C pointer pointing into the ML heap may need to be updated. Use the Push_roots and Pop_roots macros to achieve this.

[dHandle] is the type of dynamic library handles. A dynamic library handle is created by opening a dynamic library using dlopen. This will load the library into the runtime system. The dynamic library handle is used for accessing symbols in that library. The library may be closed and removed from the runtime system using dlclose.

The same library may be opened more than once, resulting in different library handles. The physical library will be loaded only once, though, and will remain in the runtime system until all handles to the library have been closed.

[symHandle] is the type of symbol handles. A symbol handle is used to access a symbol (variable or function) in the dynamic library, using the functions var, appl, app2, ..., app5. Type safety is the responsibility of the programmer; the runtime system performs no type checking. Hence you are advised to add explicit types whenever you define an ML function in terms of var, appl, ..., app5.

How to create a dynamically loadable library

To compile xyz.c into xyz.o and then create a dynamic library libxyz.so from xyz.o:

```
Under Linux and OSF/1 (Digital Unix):
gcc -c -o xyz.o xyz.c
ld -shared -o libxyz.so xyz.o
Under Solaris (ignore the warnings from ld):
gcc -c -o xyz.o xyz.c
ld -G -B symbolic -z nodefs -o libxyz.so xyz.o
Under HP-UX:
gcc -fPIC -c -o xyz.o xyz.c
ld -b -B symbolic -E -o libxyz.so xyz.o
```

If "xyz.o" depends on another library "libc.a" you may link the required functions into libxyz.so just by adding -libc or libc.a to the above linker command.

If "xyz.o" depends on another dynamic library "libc.so" you may specify this by adding -libc to the above linker command. Then Dynlib.dlopen will automatically load libc.so before libxyz.so.

[dlopen { lib, flag, global }] will load and open the library in file 'lib', returning a handle to it. Libraries are usually specified just by file name, leaving out the directory path. Linux/Unix-specific information: Libraries are searched for in those directories mentioned in LD_LIBRARY_PATH, those mentioned in /etc/ld.so.cache, in /usr/lib and /lib. (Note that /etc/ld.so.cache is created from /etc/ld.so.conf by running ldconfig; you must be superuser to do that!).

If 'global' is true, then the library's global symbols are made available for other libraries subsequently loaded.

[flag] is the type of library loading modes: RTLD_LAZY and RTLD_NOW.

[RTLD_LAZY] specifies that only symbol relocations will be performed when calling dlopen, whereas function relocations will be performed later when a function is invoked for the first time (if ever). This is the normal situation.

[RTLD_NOW] specifies that all function relocations must be performed immediately, also for functions that will never be called. This checks that all functions are defined, but may waste some time.

[disym dlh nam] returns a symbol handle for the symbol called 'nam' in the library associated with dlh. Raises Closed if dlh has been closed.

[dclose dlh] closes the library handle and deallocates the library if there are no more open handles to this library.

The following functions raise Closed if the associated handle has been closed.

- [var sym] returns the value of the C variable associated with sym.
- [app1 sym arg1] applies the C function associated with sym to arg1.
- [app2 sym arg1 arg2] applies the C function associated with sym to (arg1, arg2).
- [app3 sym arg1 arg2 arg3] applies the C function associated with sym to (arg1, arg2, arg3).
- [app4 sym arg1 arg2 arg3 arg4] applies the C function associated with sym to (arg1, arg2, arg3, arg4).
- [app5 sym arg1 arg2 arg3 arg4 arg5] applies the C function associated with sym to (arg1, arg2, arg3, arg4, arg5).

Module FileSys

OS.FileSys -- SML Basis Library

type dirstream

```
val opendir      : string -> dirstream
val readDir     : dirstream -> string option
val rewindDir   : dirstream -> unit
val closeDir    : dirstream -> unit

val chdir       : string -> unit
val getDir      : unit -> string
val mkDir       : string -> unit
val rmdir       : string -> unit
val isDir       : string -> bool

val realPath    : string -> string
val fullPath   : string -> string
val isLink      : string -> bool
val readLink    : string -> string

val modTime     : string -> Time.time
val setTime     : string * Time.time option -> unit
val remove      : string -> unit
val rename      : {old: string, new: string} -> unit

datatype access = A_READ | A_WRITE | A_EXEC
val access      : string * access list -> bool

val fileSize    : string -> int

val tmpName     : unit -> string

eqtype file_id
val fileId      : string -> file_id
val hash        : file_id -> word
val compare     : file_id * file_id -> order
```

These functions operate on the file system. They raise OS.SysErr in case of errors.

[openDir p] opens directory p and returns a directory stream for use by readDir, rewindDir, and closeDir. Subsequent calls to readDir will return the directory entries in some unspecified order.

[readDir dstr] returns SOME(s), consuming an entry s from the directory stream if it is non-empty; returns NONE if it is empty (when all directory entries have been read). Only entries distinct from the parent arc and the current arc (that is, .. and . in Unix, DOS, and Windows; see the Path structure) will be returned.

[rewindDir dstr] resets the directory stream as if it had just been opened.

[closeDir dstr] closes the directory stream. All subsequent operations on the stream will raise OS.SysErr.

[chdir p] changes the current working directory to p. This affects calls to the functions use, load, compile in the interactive system, as well as all functions defined in this library. If p specifies a volume name, then this command also changes the current volume (relevant under DOS, Windows, OS/2, etc.).

[getDir ()] returns the name of the current working directory.

[mkDir p] creates directory p on the file system.

[rmdir p] removes directory p from the file system.

```

[isDir p] tests whether p is a directory.

[fullPath p] returns a canonical form of path p, where all
occurrences of the arcs ".", ".", ".", "." have been expanded or
removed, and (under Unix) symbolic links have been fully expanded.
Raises SysErr if a directory on the path, or the file or directory
named, does not exist or is not accessible, or if there is a link
loop.

[realPath p] behaves as fullPath(p) if p is absolute. If p is
relative and on the same volume as the current working directory,
it returns a canonical path relative to the current working
directory, where superfluous occurrences of the arcs ".", ".", ".", "."
have been removed, and (under Unix) symbolic links have been fully
expanded. Raises SysErr if a directory on the path, or the file or
directory named, does not exist or is not accessible, or if there
is a link loop. Raises Path if p is relative and on a different
volume than the current working directory.

[isLink p] returns true if p names a symbolic link. Raises SysErr
if the file does not exist or there is an access violation. On
operating systems without symbolic links, it returns false, or
raises SysErr if the file does not exist or there is an access
violation.

[readLink p] returns the contents of the symbolic link p. Raises
SysErr if p does not exist or is not a symbolic link, or there is
an access violation. On operating systems without symbolic links,
it raises SysErr.

[modTime p] returns the modification time of file p.

[setTime (p, tmopt)] sets the modification and access time of file
p. If tmopt is SOME t, then the time t is used; otherwise the
current time, that is, Time.now(), is used.

[remove p] deletes file p from the file system.

[rename {old, new}] changes the name of file 'old' to 'new'.

[access] is the type of access permissions:

[A_READ] specifies read access.

[A_WRITE] specifies write access.

[A_EXEC] specifies permission to execute the file (or directory).

[access (p, acs)] tests the access permissions of file p,
expanding symbolic links as necessary. If the list acs of
required access permission is empty, it tests whether p exists. If
acs contains A_READ, A_WRITE, or A_EXEC, respectively, it tests
whether the user process has read, write, or execute permission for
the file.

Under Unix, the access test is done with the 'real' user
id and group id (as opposed to the 'effective' user id and group
id) of the user process. Hence access('file', [A_READ]) may return
false, yet the file may be readable by the process, in case the
effective user id or group id has been changed by setuid.

[fileSize p] return the size, in bytes, of the file p. Raises SysErr
if p does not exist or its directory is not accessible.

[tmpName ()] returns a file name suitable for creating a fresh
temporary file. Note that there is no guarantee that the file name
will be unique, since a file of that name may be created between
the call to tmpName and a subsequent call to openOut which creates
the file. The file name will be absolute, usually of the form
/tmp/xxxxxxx provided by POSIX tmpnam (3).

[file_id] is the type of unique identities of file system objects
(including device ids and volume ids, but possibly insensitive to

```

```

volume changes on removable volumes, such as tapes and diskettes).
The set of file ids is equipped with a total linear order.

[fileId p] returns the file_id of the file system object named by
path p. It holds that fileId p1 = fileId p2 if and only if p1 and
p2 name the same file system object.

[hash fid] returns a hashvalue for fid, suitable for use in a
hashtable of file ids (and hence files).
If fid1 = fid2 then hash fid1 = hash fid2.

[compare (fid1, fid2)] returns LESS, EQUAL, or GREATER, according
as fid1 precedes, equals, or follows fid2 in the total linear order
on file ids. This is suitable for e.g. an ordered binary tree of
file ids (and hence files).

```

Module Gdbm

Gdbm -- GNU gdbm persistent string hashtables -- requires Dynlib

```
type table

datatype openmode =
  READER
  | WRITER
  | WRCREAT
  | NEWDB

type datum = string

exception NotFound
exception AlreadyThere
exception NotWriter
exception Closed
exception GdbmError of string

val withtable : string * openmode -> (table -> 'a) -> 'a
val withtables : (string * openmode) list -> (table list -> 'a) -> 'a
val add : table -> datum * datum -> unit
val insert : table -> datum * datum -> unit
val find : table -> datum -> datum
val peek : table -> datum -> datum option
val haskey : table -> datum -> bool
val remove : table -> datum -> unit
val listkeys : table -> datum list
val listitems : table -> int
val listitems : table -> (datum * datum) list
val app : (datum * datum -> unit) -> table -> unit
val map : (datum * datum -> 'a) -> table -> 'a list
val fold : (datum * datum * 'a -> 'a) -> 'a -> table -> 'a
val fastwrite : bool ref
val reorganize : table -> unit
```

[table] is the type of an opened table. A value of type table can be used only in the argument f to the withtable function. This makes sure that the table is closed after use.

[openmode] is the type of opening modes. Read-only access (READER) is non-exclusive; read/write access (WRITER, WRCREAT, NEWDB) is exclusive.

[withtable (nam, mod) f] first opens the table db in file nam with mode mod, then applies f to db, then closes db. Makes sure to close db even if an exception is raised during the evaluation of f(db). Raises GdbmError with an informative message in case the table cannot be opened. E.g. the table cannot be opened for reading if already opened for writing, and cannot be opened for writing if already opened for reading.

A table is only guaranteed to work properly if created by withtable using open modes WRCREAT or NEWDB. If you create a table by creating and then opening an empty file, then numItems, listKeys, listItems, etc. will raise an exception.

```
[withtables nammod fl], where nammod = [(nam1, mod1), ..., (namn, modn)],
is equivalent to
  withtable (nam1, mod1) (fn db1 =>
    withtable (nam2, mod2) (fn db2 =>
      ... f (db1, db2, ...)))
```

That is, first opens the databases db1, db2, ... in that order in files nam1, nam2, ... with modes mod1, mod2, ..., then applies f to [db1, db2, ...], and finally closes [db1, db2, ...]. Makes sure to close all databases even if an exception is raised during the opening of db1, db2, ... or during the evaluation of f(db1, db2, ...).

[add db (k,v)] adds the pair (k, v) to db. Raises AlreadyThere if there is a pair (k, _) in db already. Raises NotWriter if db is not opened in write mode.

[insert db (k, v)] adds the pair (k, v) to db, replacing any pair (k, _) at k if present. Raises NotWriter if db is not opened in write mode.

[find db k] returns v if the pair (k, v) is in db; otherwise raises NotFound.

[peek db k] returns SOME v if the pair (k, v) is in db; otherwise returns NONE.

[haskey db k] returns true if there is a pair (k, _) in db; otherwise returns false.

[remove db k] deletes the pair (k, _) from the table if present; otherwise raises NotFound. Raises NotWriter if db is not opened in write mode.

[listKeys db] returns a list of all keys in db in an unspecified order.

[numItems db] is the number of (key, value) pairs in db. Equivalent to length(listKeys db).

[listItems db] returns a list of all (key, value) pairs in db in some order. Equivalent to List.map (fn key => (key, find(db,key))) (listKeys db)

[app f db] is equivalent to List.app f (listItems db), provided the function f does not change the set of keys in the table. Otherwise the effect is unpredictable.

[map f db] is equivalent to List.map f (listItems db), provided the function f does not change the set of keys in the table. Otherwise the result and effect are unpredictable.

[fold f a db] is equivalent to List.foldr (fn ((k, v), r) => f(k, v, r)) a (listItems db) provided the function f does not change the set of keys in the table. Otherwise the result and effect are unpredictable.

[fastwrite] can be set to speed up writes to a table. By default, !fastwrite is false and every write to a table will be followed by file system synchronization. This is safe, but slow if you perform thousands of writes. However, if !fastwrite is true when calling withtable, then writes may not be followed by synchronization, which may speed up writes considerably. In any case, the file system is synchronized before withtable returns.

[reorganize db] has no visible effect, but may be called after a lot of deletions to shrink the size of the table file.

Module Gdimage

Gdimage -- creating PNG images -- requires Dynlib

```
type image

type color

datatype style =
  | Colors of color
  | Transparents

datatype mode =
  | Color of color
  | Transparent
  | Brushed of image
  | Styled of style vector
  | StyledBrushed of bool vector * image
  | Tiled of image

datatype font =
  | Tiny
  | Small
  | MediumBold
  | Large
  | Giant

type rgb = int * int * int          RGB color components, 0..255
type xy = int * int                points (x, y) and sizes (w, h)

val image      : xy -> rgb -> image
val fromPng    : string -> image
val toPng      : image -> string -> unit
val stdoutPng  : image -> unit
val size       : image -> xy

val color      : image -> rgb -> color
val rgb        : image -> color -> rgb
val hmlcolors  : image -> { aqua : color, black : color, blue : color,
                           fuchsia : color, gray : color,
                           green : color, lime : color, maroon : color,
                           navy : color, olive : color, purple : color,
                           red : color, silver : color, teal : color,
                           white : color, yellow : color }

val getTransparent : image -> color option
val setTransparent : image -> color -> unit
val noTransparent  : image -> unit

val drawPixel      : image -> mode -> xy -> unit
val drawLine       : image -> mode -> xy * xy -> unit
val drawRect       : image -> mode -> xy * xy -> unit
val fillRect       : image -> mode -> xy * xy -> unit
val drawPolygon    : image -> mode -> xy vector -> unit
val fillPolygon    : image -> mode -> xy vector -> unit
val drawArc        : image -> mode -> { c : xy, wh : xy, from : int, to : int }
                           -> unit
val fill           : image -> mode -> xy -> unit
val fillBorder     : image -> mode -> xy -> color -> unit
val copy           : { src : image, srcxy : xy, srcwh : xy,
                      dst : image, dstxy : xy } -> unit
val copy/resize    : { src : image, srcxy : xy, srcwh : xy,
                      dst : image, dstxy : xy, dstwh : xy } -> unit

val char           : image -> color -> font -> xy -> char -> unit
val charUp         : image -> color -> font -> xy -> char -> unit
val string          : image -> color -> font -> xy -> string -> unit
val stringUp       : image -> color -> font -> xy -> string -> unit
val charsize       : font -> xy
```

This is an interface to version 1.7.3 of Thomas Boutell's gd image package for creating PNG images.

[image] is the type of images being drawn. They can be created from scratch, imported from PNG files, and exported to PNG files.

All functions correctly clip to the actual size of the image.

[color] is the type of colors. Currently there can be at most 256 different colors in an image.

[style] is the type of drawing styles. A style is either a color, or transparent.

[mode] is the type of drawing modes for line drawing and filling. It may be one of

```
Color c          where c is a color
Transparent
Brushed img      for line drawing using the given image as brush
Styled stys       for line drawing, cyclically using the styles
                  in the given vector to create a dashed line
StyledBrushed (vis, img)
                  for line drawing, using the given image as a brush,
                  cyclically switching it on and off according to the
                  given bool vector
Tiled img         for filling, using the given image as a tile
```

[font] is the type of fonts: Tiny, Small, MediumBold, Large, Giant

[rgb] is the type of (r, g, b) triples, where the components indicate color intensity as an integer value in the range 0..255.

[xy] is the type of pairs, used for (x, y) coordinates and to indicate dimensions (width, height). The origin (0, 0) is the upper left-hand corner of the image. The x coordinates increase to the right; the y coordinates increase downwards.

[image (w, h) rgb] creates a new empty image with size (w, h) and the background color rgb. Raises Fail if the image cannot be created.

[fromPng filename] reads an image from the given PNG file. Raises Fail if the file does not exist or does not contain a PNG image.

[size img] returns (w, h) where w is the width and h the height of img.

[toPng img filename] write the image to the given file in PNG format.

[stdoutPng img] writes the image to standard output in PNG format, preceded by the HTTP header "Content-type: image/png\n\n". Useful in CGI scripts.

[color img rgb] returns the color code corresponding to rgb in the color table of img. Reuses the color code if it has already been allocated; otherwise allocates the color if possible; otherwise returns an approximation to the color rgb.

[htmlcolors im] returns a record containing the 16 standard HTML colors: aqua, black, blue, fuchsia, gray, green, lime, maroon, navy, olive, purple, red, silver, teal, white, yellow. This call will allocate all these colors in the color table of the image, even if you do not use all of them.

[rgb img color] returns (r, g, b) where r, g, b are the component intensities of the given color in the color table of img.

[getTransparent img] returns SOME c where c is the 'transparent' color of the image, if any; otherwise returns NONE.

[setTransparent img col] makes the given color transparent in the

image.

[noTransparent img] makes all colors non-transparent in the image. This is useful for images that are to be used as tiles for filling. Such images are not allowed to have a transparent color.

[drawPixel img mode xy] draws the pixel in img at xy using the given mode.

[drawLine img mode {xyl, xy2}] draws a line in img from xyl to xy2 using the given mode.

[drawRect img mode {xyl, xy2}] draws a rectangle in img with opposing corners xyl and xy2 using the given mode.

[fillRect img mode {xyl, xy2}] draws a filled rectangle in img with opposing corners xyl and xy2 using the given mode.

[drawPolygon img mode xys] draws a polygon in img with corners as given by the vector xys of coordinates using the given mode.

[fillPolygon img mode xys] draws a filled polygon in img with corners as given by the vector xys of coordinates using the given mode.

[drawArc img mode { c, wh, from, to }] draw part of an ellipsis arc in img, with center c, width and height wh, using the given 'from' and 'to' angles, given in degrees (0..360).

[fill img mode xy] fills the region in img around xy which has the same color as the point at img, using the given mode.

[fillBorder img mode xy col] fills the region in img around xy which is delimited by the color col, using the given mode.

[copy { src, srcxy, srcwh, dst, dstxy }] copies part of the image src into the image dst, without rescaling. More precisely, copies the subimage of src whose upper left-hand corner is srcxy and whose size is srcwh, into the subimage of dst whose upper left-hand corner is dstxy. The images src and dst may be the same, but if the subimages overlap, then the result is unpredictable.

[copyResize { src, srcxy, srcwh, dst, dstxy, dstwh }] copies part of the image src into the image dst, rescaling to the given size dstwh of the destination subimage. Otherwise works as copy.

[char img col font xy chl] draws the character ch left-right (to be read from south) in img at xy using the given color.

[charUp img col font xy chl] draws the character ch bottom-up (to be read from east) in img at xy using the given color.

[string img col font xy s] draws the string s left-right (to be read from south) in img at xy using the given color.

[stringUp img col font xy s] draws the string s bottom-up (to be read from east) in img at xy using the given color.

[charsize font] returns (w, h) where w is the width and h the height, in pixels, of each character in the given font.

Module General

SML Basis Library and Moscow ML top-level declarations

SML Basis Library types

```
type      exn
datatype unit
datatype order = LESS | EQUAL | GREATER
```

Additional Moscow ML top-level types

```
datatype bool = false | true
datatype char
datatype int
datatype 'a option = NONE | SOME of 'a
type ppstream
datatype real
datatype string
type substring
type syserror
type 'a vector
datatype word
datatype word8
datatype 'a list = nil | op :: of 'a * 'a list
datatype 'a ref = ref of 'a
datatype 'a frag = QUOTE of string | ANTIQUOTE of 'a
```

SML Basis Library exceptions

```
exception Bind
exception Chr
exception Div
exception Domain
exception Fail of string
exception Match
exception Overflow
exception Subscript
exception Size

Additional Moscow ML top-level exceptions

exception Graphic of string
exception Interrupt
exception Invalid_argument of string
exception Io of {function : string, name : string, cause : exn }
exception Out_of_memory
exception SysErr of string * syserror option
```

SML Basis Library values

```
val !      : 'a ref -> 'a
val :=     : 'a ref * 'a -> unit

val o      : ('b->'c) * ('a -> 'b) -> ('a -> 'c)
val ignore : 'a -> unit
val before : 'a * 'b -> 'a

val exnName      : exn -> string
val exnMessage   : exn -> string
```

Additional Moscow ML top-level values

```
val not      : bool -> bool
val ^        : string * string -> string

val =        : "a * "a -> bool
val <>       : "a * "a -> bool

val ceil     : real -> int
val floor    : real -> int
val real     : int -> real

round towards plus infinity
round towards minus infinity
equals Real.FromInt
```

```

val round : real -> int
val trunc : real -> int

val vector : 'a list -> 'a vector

Below, numtxt is int, Word.word, real, char, string:

val < : numtxt * numtxt -> bool
val <= : numtxt * numtxt -> bool
val > : numtxt * numtxt -> bool
val >= : numtxt * numtxt -> bool

val makestring : numtxt -> string

Below, realint is int or real:

val ~ : realint -> realint
val abs : realint -> realint
      raises Overflow
      raises Overflow

Below, num is int, Word.word, Word8.word, or real:

val + : num * num -> num
val - : num * num -> num
val * : num * num -> num
val / : real * real -> real
      raises Div, Overflow

Below, wordint is int, Word.word or Word8.word:

val div : wordint * wordint -> wordint
val mod : wordint * wordint -> wordint
      raises Div

```

[exn] is the type of exceptions.

[unit] is the type containing the empty tuple () which equals the empty record {}.

[order] is used as the return type of comparison functions.

[bool] is the type of booleans: false and true. Equals Bool.bool.

[char] is the type of characters such as #"A". Equals Char.char.

[int] is the type of integers. Equals Int.int.

[option] is the type of optional values. Equals Option.option.

[ppstream] is the type of pretty-printing streams, see structure PP. Pretty-printers may be installed in the top-level by function Meta.installPP; see the Moscow ML Owner's Manual.

[real] is the type of floating-point numbers. Equals Real.real.

[string] is the type of character strings. Equals String.string.

[substring] is the type of substrings. Equals Substring.substring.

[syserror] is the abstract type of system error codes. Equals OS.syserror.

[vector] is the type of immutable vectors. Equals Vector.vector.

[word] is the type of unsigned words. Equals Word.word.

[word8] is the type of unsigned bytes. Equals Word8.word.

['a list] is the type of lists of elements of type 'a. Equals List.list.

['a ref] is the type of mutable references to values of type 'a.

['a frag] is the type of quotation fragments, resulting from the

parsing of quotations ' ... ' and antiquotations. See the Moscow ML Owner's Manual.

[Bind] is the exception raised when the right-hand side value in a valbind does not match the left-hand side pattern.

[Chr] signals an attempt to produce an unrepresentable character.

[Div] signals an attempt to divide by zero.

[Domain] signals an attempt to apply a function outside its domain of definition; such as computing Math.sqrt(-1).

[Fail] signals the failure of some function, usually in the Moscow ML specific library structures.

[Match] signals the failure to match a value against the patterns in a case, handle, or function application.

[Overflow] signals the attempt to compute an unrepresentable number.

[Subscript] signals the attempt to use an illegal index in an array, dynarray, list, string, substring, vector or weak array.

[Size] signals the attempt to create an array, string or vector that is too large for the implementation.

[Graphic] signals the failure of Graphics primitives (DOS only).

[Interrupt] signals user interrupt of the computation.

[Invalid_argument] signals the failure of a function in the runtime system.

[To { function, name, cause }] signals the failure of an input/output operation (function) when operating on a file (name). The third field (cause) may give a reason for the failure.

[Out_of_memory] signals an attempt to create a data structure too large for the implementation, or the failure to extend the heap or stack.

[SysErr (msg, err)] signals a system error, described by msg. A system error code may be given by err. If so, it will usually hold that msg = OS.errorMsg err.

SMU Basis Library values

[! rf] returns the value pointed to by reference rf.

[:=(rf, e)] evaluates rf and e, then makes the reference rf point to the value of e. Since := has infix status, this is usually written rf := e

[o(f, g)] computes the functional composition of f and g, that is, fn x => f(g x). Since o has infix status, this is usually written f o g

[ignore e] evaluates e, discards its value, and returns () : unit.

[before(e1, e2)] evaluates e1, then evaluates e2, then returns the value of e1. Since before has infix status, this is usually written e1 before e2

[exnName exn] returns a name for the exception constructor in exn. Never raises an exception itself. The name returned may be that of any exception constructor aliasing with exn. For instance, let exception E1; exception E2 = E1 in exnName E2 end may evaluate to "E1" or "E2".

[exnMessage exn] formats and returns a message corresponding to

exception `exp`. For the exceptions defined in the SML Basis Library, the message will include the argument carried by the exception.

Additional Moscow ML top-level values

`[not b]` returns the logical negation of `b`.

`[^]` is the string concatenation operator.

`[=]` is the polymorphic equality predicate.

`[<]` is the polymorphic inequality predicate.

`[ceil r]` is the smallest integer $\geq r$ (rounds towards plus infinity). May raise `Overflow`.

`[floor r]` is the largest integer $\leq r$ (rounds towards minus infinity). May raise `Overflow`.

`[real i]` is the floating-point number representing integer `i`. Equivalent to `Real.fromInt`.

`[round r]` is the integer nearest to `r`, using the default rounding mode. May raise `Overflow`.

`[trunc r]` is the numerically largest integer between `r` and zero (rounds towards zero). May raise `Overflow`.

`[vector [x1, ..., xn]]` returns the vector `#[x1, ..., xn]`.

```
[< (x1, x2)]
[<= (x1, x2)]
[> (x1, x2)]
[>= (x1, x2)]
```

These are the standard comparison operators for arguments of type `int`, `Word.word`, `Word8.word`, `real`, `char` or `string`.

`[makestring v]` returns a representation of value `v` as a string, for `v` of type `int`, `Word.word`, `Word8.word`, `real`, `char` or `string`.

`[~ x]` is the numeric negation of `x` (which can be `real` or `int`). May raise `Overflow`.

`[abs x]` is the absolute value of `x` (which can be `real` or `int`). May raise `Overflow`.

```
[+ (e1, e2)]
[- (e1, e2)]
[* (e1, e2)]
```

These are the standard arithmetic operations for arguments of type `int`, `Word.word`, `Word8.word`, and `real`. They are unsigned in the case of `Word.word` and `Word8.word`. May raise `Overflow`.

`[/ (e1, e2)]` is the floating-point result of dividing `e1` by `e2`. May raise `Div` and `Overflow`.

`[div(e1, e2)]` is the integral quotient of dividing `e1` by `e2` for arguments of type `int`, `Word.word`, and `Word8.word`. See `Int.div` and `Word.div` for more details. May raise `Div`, `Overflow`.

`[mod(e1, e2)]` is the remainder when dividing `e1` by `e2`, for arguments of type `int`, `Word.word`, and `Word8.word`. See `Int.mod` and `Word.mod` for more details. May raise `Div`.

Module Help

Help -- on-line help functions

```
val help      : string -> unit
val displayLines : int ref
val helpdirs  : string list ref
val indexfiles : string list ref
val specialfiles : {term : string, file : string, title : string} list ref
val welcome   : string vector ref
val browser   : (string -> unit) ref
val defaultBrowser : string -> unit
```

`[help s]` provides on-line help on the topic indicated by string `s`.

`help "lib";` gives an overview of the Moscow ML library.
`help "id";` provides help on identifier `id` (case-insensitive).

If exactly one identifier in the library matches `id` (case-insensitive), then the browser opens the signature defining that identifier, positioning the first occurrence of `id` at the center of the screen.

If more than one identifier matches `id` (case-insensitive), then a small menu lists the signatures containing the identifier. To invoke the browser, just type in the number of the desired signature.

The browser accepts the following commands, which must be followed by a newline:

```
d      move down by half a screen
u      move up by half a screen
t      move to top of file
b      move to bottom of file
/str   cyclically search for string str in help file (case-insensitive)
n      search for next occurrence of str
q      quit the browser
```

A newline by itself moves down one screen (24 lines).

`[helpdirs]` is a reference to a list of additional directories to be searched for help files. The directories are searched in order, after the `-stdlib` directory.

`[indexfiles]` is a reference to a list of full paths of help term index files. Setting `'indexfiles'` affects subsequent invocations of `'help'`. (Every invocation of `'help'` reads the index files anew).

`[specialfiles]` is a reference to a list of `{term, file, title}` records, each of which maps a search term to the specified file with the specified title (in the browser). The string in the `'term'` field should be all lowercase, since the argument passed to `'help'` will be converted to lowercase.

`[welcome]` is a reference to the text shown in response to the query `help ""`. This is a vector of lines of text.

`[browser]` is a reference to the function that gets invoked on the text of the help file. Initially set to `defaultBrowser`.

`[defaultBrowser]` is the default (built-in) help browser.

`[displayLines]` is a reference to the size of the display (window) assumed by the `defaultBrowser`; initially 24 lines. Set it to the actual size of your window for best results.

Module Int

Int -- *SMW Basis Library*

type int = Int

val precision : int option
val minInt : int option
val maxInt : int option

val ~ : int -> int *Overflow*
val * : int * int -> int *Overflow*
val div : int * int -> int *Div, Overflow*
val mod : int * int -> int *Div*
val quot : int * int -> int *Div, Overflow*
val rem : int * int -> int *Div*
val + : int * int -> int *Overflow*
val - : int * int -> int *Overflow*
val > : int * int -> bool
val < : int * int -> bool
val >= : int * int -> bool
val <= : int * int -> bool
val abs : int -> int
val min : int * int -> int
val max : int * int -> int

val sign : int -> int
val sameSign : int * int -> bool
val compare : int * int -> order

val toInt : int -> int
val fromInt : int -> int
val toLarge : int -> int
val fromLarge : int -> int

val scan : StringCvt.radix -> StringCvt.reader -> (int, 'a) StringCvt.reader
val fmt : StringCvt.radix -> int -> string
val toString : int -> string
val fromString : string -> int option *Overflow*

[precision] is SOME n, where n is the number of significant bits in an integer. In Moscow ML n is 31 in 32-bit architectures and 63 in 64-bit architectures.

[minInt] is SOME n, where n is the most negative integer.

[maxInt] is SOME n, where n is the most positive integer.

[~]
[*]
[+]

[-] are the usual operations on integers. They raise Overflow if the result is not representable as an integer.

[abs] returns the absolute value of its argument. Raises Overflow if applied to the most negative integer.

[div] is integer division, rounding towards minus infinity. Evaluating i div 0 raises Div. Evaluating i div ~1 raises Overflow if i is the most negative integer.

[mod] is the remainder for div. If q = i div d and r = i mod d then it holds that qd + r = i, where either 0 <= r < d or d < r <= 0. Evaluating i mod 0 raises Div, whereas i mod ~1 = 0, for all i.

[quot] is integer division, rounding towards zero. Evaluating quot(i, 0) raises Div. Evaluating quot(i, ~1) raises Overflow if i is the most negative integer.

[rem(i, d)] is the remainder for quot. That is, if q = quot(i, d) and r = rem(i, d) then d * q + r = i, where r is zero or has the same sign as i. If made infix, the recommended fixity for quot and rem is
infix 7 quot rem

[min(x, y)] is the smaller of x and y.

[max(x, y)] is the larger of x and y.

[sign x] is ~1, 0, or 1, according as x is negative, zero, or positive.

[<]
[<=]
[>]
[>=]

are the usual comparisons on integers.

[compare(x, y)] returns LESS, EQUAL, or GREATER, according as x is less than, equal to, or greater than y.

[sameSign(x, y)] is true iff sign x = sign y.

[toInt x] is x (because this is the default int type in Moscow ML).

[fromInt x] is x (because this is the default int type in Moscow ML).

[toLarge x] is x (because this is the largest int type in Moscow ML).

[fromLarge x] is x (because this is the largest int type in Moscow ML).

[fmt radix i] returns a string representing i, in the radix (base) specified by radix.

| radix | description | output format |
|-------|------------------------------|---------------|
| BIN | signed binary (base 2) | ~?[01]+ |
| OCT | signed octal (base 8) | ~?[0-7]+ |
| DEC | signed decimal (base 10) | ~?[0-9]+ |
| HEX | signed hexadecimal (base 16) | ~?[0-9A-F]+ |

[toString i] returns a string representing i in signed decimal format. Equivalent to (fmt DEC i).

[fromString s] returns SOME(i) if a decimal integer numeral can be scanned from a prefix of string s, ignoring any initial whitespace; returns NONE otherwise. A decimal integer numeral must have form, after possible initial whitespace:
[+~?][0-9]+

[scan radix getc charsrc] attempts to scan an integer numeral from the character source charsrc, using the accessor getc, and ignoring any initial whitespace. The radix argument specifies the base of the numeral (BIN, OCT, DEC, HEX). If successful, it returns SOME(i, rest) where i is the value of the number scanned, and rest is the unused part of the character source. A numeral must have form, after possible initial whitespace:

| radix | input format |
|-------|-------------------|
| BIN | [+~?][0-1]+ |
| OCT | [+~?][0-7]+ |
| DEC | [+~?][0-9]+ |
| HEX | [+~?][0-9a-fA-F]+ |

Module Intmap

Intmap -- Applicative maps with integer keys
From *SML/NJ lib 0.2*, copyright 1993 by AT&T Bell Laboratories
Original implementation due to Stephen Adams, Southampton, UK

type 'a intmap

exception NotFound

```
val empty      : unit -> 'a intmap
val insert     : 'a intmap * int * 'a -> 'a intmap
val retrieve   : 'a intmap * int -> 'a
val peek      : 'a intmap * int -> 'a option
val remove    : 'a intmap * int -> 'a intmap * 'a
val numItems  : 'a intmap -> int
val listItems : 'a intmap -> (int * 'a) list
val app       : (int * 'a -> unit) -> 'a intmap -> unit
val revapp    : (int * 'a -> unit) -> 'a intmap -> unit
val foldr     : (int * 'a * 'b -> 'b) -> 'b -> 'a intmap -> 'b
val foldl     : (int * 'a * 'b -> 'b) -> 'b -> 'a intmap -> 'b
val map       : (int * 'a -> 'b) -> 'a intmap -> 'b intmap
val transform : ('a -> 'b) -> 'a intmap -> 'b intmap
```

['a intmap] is the type of applicative maps from int to 'a.

[empty] creates a new empty map.

[insert(m, i, v)] extends (or modifies) map m to map i to v.

[retrieve(m, i)] returns v if m maps i to v; otherwise raises NotFound.

[peek(m, i)] returns SOME v if m maps i to v; otherwise NONE.

[remove(m, i)] removes i from the domain of m and returns the modified map and the element v corresponding to i. Raises NotFound if i is not in the domain of m.

[numItems m] returns the number of entries in m (that is, the size of the domain of m).

[listItems m] returns a list of the entries (i, v) of integers i and the corresponding values v in m, in increasing order of i.

[app f m] applies function f to the entries (i, v) in m, in increasing order of i.

[revapp f m] applies function f to the entries (i, v) in m, in decreasing order of i.

[foldl f e m] applies the folding function f to the entries (i, v) in m, in increasing order of i.

[foldr f e m] applies the folding function f to the entries (i, v) in m, in decreasing order of i.

[map f m] returns a new map whose entries have form (i, f(i.v)), where (i, v) is an entry in m.

[transform f m] returns a new map whose entries have form (i, f(i.v)), where (i, v) is an entry in m.

Module Intset

Intset -- applicative sets of integers
From *SML/NJ lib 0.2*, copyright 1993 by AT&T Bell Laboratories
Original implementation due to Stephen Adams, Southampton, UK

type intset

exception NotFound

```
val empty      : intset
val singleton  : int -> intset
val add        : intset * int -> intset
val addlist    : intset * int list -> intset
val isEmpty    : intset -> bool
val isEqual    : intset * intset -> bool
val isSubset   : intset * intset -> bool
val member     : intset * int -> bool
val delete     : intset * int -> intset
val numItems   : intset -> int
val union      : intset * intset -> intset
val intersection : intset * intset -> intset
val difference : intset * intset -> intset
val listItems  : intset -> int list
val app        : (int -> unit) -> intset -> unit
val revapp     : (int -> unit) -> intset -> unit
val foldr      : (int * 'b -> 'b) -> 'b -> intset -> 'b
val foldl      : (int * 'b -> 'b) -> 'b -> intset -> 'b
val find       : (int -> bool) -> intset -> int option
```

[intset] is the type of sets of integers.

[empty] is the empty set of integers.

[singleton i] is the singleton set containing i.

[add(s, i)] adds item i to set s.

[addList(s, xs)] adds all items from the list xs to the set s.

[isEmpty s] returns true if and only if the set is empty.

[equal(s1, s2)] returns true if and only if the two sets have the same elements.

[isSubset(s1, s2)] returns true if and only if s1 is a subset of s2.

[member(s, i)] returns true if and only if i is in s.

[delete(s, i)] removes item i from s. Raises NotFound if i is not in s.

[numItems s] returns the number of items in set s.

[union(s1, s2)] returns the union of s1 and s2.

[intersection(s1, s2)] returns the intersection of s1 and s2.

[difference(s1, s2)] returns the difference between s1 and s2 (that is, the set of elements in s1 but not in s2).

[listItems s] returns a list of the items in set s, in increasing order.

[app f s] applies function f to the elements of s, in increasing order.

[revapp f s] applies function f to the elements of s, in decreasing order.

[foldl f e s] applies the folding function f to the entries of the set in increasing order.

[foldr f e s] applies the folding function f to the entries of the set in decreasing order.
[find p s] returns SOME i, where i is an item in s which satisfies p, if one exists; otherwise returns NONE.

Module Lexing

*Lexing -- run-time library for lexers generated by mosmllex
Closely based on the library for camlex. Copyright 1993 INRIA, France*

```
local open Obj in
type lexbuf
val createLexerString : string -> lexbuf
val createLexer      : (CharArray.array -> int -> int) -> lexbuf
val getLexeme       : lexbuf -> string
val getLexemeChar   : lexbuf -> int -> char
val getLexemeStart  : lexbuf -> int
val getLexemeEnd    : lexbuf -> int
For internal use in generated lexers:
val dummyAction    : lexbuf -> obj
val backtrack      : lexbuf -> 'a
prim_val getNextChar : lexbuf -> char = 1 "getNext_char"
prim_val getLexBuffer : lexbuf -> string = 1 "field1"
prim_val getLexAbsPos : lexbuf -> int = 1 "field2"
prim_val getLexStartPos : lexbuf -> int = 1 "field3"
prim_val getLexCurrPos : lexbuf -> int = 1 "field4"
prim_val getLexLastPos : lexbuf -> int = 1 "field5"
prim_val getLexLastAction : lexbuf -> obj = 1 "field6"
prim_val setLexAbsPos : lexbuf -> int -> unit = 2 "setfield2"
prim_val setLexStartPos : lexbuf -> int -> unit = 2 "setfield3"
prim_val setLexCurrPos : lexbuf -> int -> unit = 2 "setfield4"
prim_val setLexLastPos : lexbuf -> int -> unit = 2 "setfield5"
prim_val setLexLastAction : lexbuf -> (lexbuf -> obj) -> unit = 2 "setfield6"
end
```

These functions are for use in mosmllex-generated lexers. For further information, see the Moscow ML Owner's Manual. For examples, see mosml/examples/lexyacc and mosml/examples/calc.

[lexbuf] is the type of lexer buffers. A lexer buffer is the argument passed to the scanning functions defined by the mosmllex-generated scanners. The lexer buffer holds the current state of the scanner, plus a function to refill the buffer from the input.

[createLexerString s] returns a lexer buffer which reads from the given string s. Reading starts from the first character in the string. An end-of-input condition is generated when the end of the string is reached.

[createLexer f] returns a lexer buffer that will use the given function f for reading additional input. When the lexer needs more characters, it will call the given function as (f carr n), where carr is a character array, and n is an integer. The function should put at most characters or in carr, starting at character number 0, and return the number of characters actually stored. A return value of 0 means end of input.

A lexer definition (input to mosmllex) consists of fragments of this form

```
parse
  lhs1 { rhs1 }
  |    | lhs2 { rhs2 }
  |    | lhs3 { rhs3 }
  |    | ...
```

where the lhs are regular expressions matching some string of

characters, and the rhs are corresponding semantic actions, written in ML. The following functions can be used in the semantic actions:

[getLexeme lexbuf] returns the string matched by the left-hand side regular expression.

[getLexemeChar lexbuf i] returns character number i in the matched string.

[getLexemeStart lexbuf] returns the start position of the matched string (in the input stream). The first character in the stream has position 0.

[getLexemeEnd lexbuf] returns the end position, plus one, of the matched string (in the input stream). The first character in the stream has position 0.

Module List

List -- SML Basis Library

datatype list = datatype list

exception Empty

```
val null      : 'a list -> bool
val hd       : 'a list -> 'a
val tl       : 'a list -> 'a list
val last     : 'a list -> 'a

val nth      : 'a list * int -> 'a
val take     : 'a list * int -> 'a list
val drop     : 'a list * int -> 'a list

val length   : 'a list -> int

val rev      : 'a list -> 'a list

val @        : 'a list * 'a list -> 'a list
val concat   : 'a list list -> 'a list
val revAppend : 'a list * 'a list -> 'a list

val app      : ('a -> unit) -> 'a list -> unit
val map      : ('a -> 'b) -> 'a list -> 'b list
val mapPartial : ('a -> 'b option) -> 'a list -> 'b list

val find     : ('a -> bool) -> 'a list -> 'a option
val filter   : ('a -> bool) -> 'a list -> 'a list
val partition : ('a -> bool) -> 'a list -> ('a list * 'a list)

val foldr    : ('a * 'b -> 'b) -> 'b -> 'a list -> 'b
val foldl    : ('a * 'b -> 'b) -> 'b -> 'a list -> 'b

val exists   : ('a -> bool) -> 'a list -> bool
val all      : ('a -> bool) -> 'a list -> bool

val collate  : ('a * 'a -> order) -> 'a list * 'a list -> order

val tabulate : int * (int -> 'a) -> 'a list      Size
val getItem  : 'a list -> ('a * 'a list) option
```

['a list] is the type of lists of elements of type 'a.

[null xs] is true iff xs is nil.

[hd xs] returns the first element of xs. Raises Empty if xs is nil.

[tl xs] returns all but the first element of xs. Raises Empty if xs is nil.

[last xs] returns the last element of xs. Raises Empty if xs is nil.

[nth(xs, i)] returns the i'th element of xs, counting from 0. Raises Subscript if i<0 or i>length xs.

[take(xs, i)] returns the first i elements of xs. Raises Subscript if i<0 or i>length xs.

[drop(xs, i)] returns what is left after dropping the first i elements of xs. Raises Subscript if i<0 or i>length xs. It holds that take(xs, i) @ drop(xs, i) = xs when 0 <= i <= length xs.

[length xs] returns the number of elements in xs.

[rev xs] returns the list of xs's elements, reversed.

[xs @ ys] returns the list which is the concatenation of xs and ys.

```
[concat xss] returns the list which is the concatenation of all the
lists in xss.

[revAppend(xs, ys)] is equivalent to rev xs @ ys, but more efficient.

[app f xs] applies f to the elements of xs, from left to right.

[map f xs] applies f to each element x of xs, from left to
right, and returns the list of f's results.

[mapPartial f xs] applies f to each element x of xs, from left
to right, and returns the list of those y's for which f(x)
evaluated to SOME y.

[find p xs] applies p to each element x of xs, from left to right,
until p(x) evaluates to true; returns SOME x if such an x exists,
otherwise NONE.

[filter p xs] applies p to each element x of xs, from left to
right, and returns the sublist of those x for which p(x) evaluated
to true.

[partition p xs] applies p to each element x of xs, from left
to right, and returns a pair (pos, neg) where pos is the sublist
of those x for which p(x) evaluated to true, and neg is the sublist of
those for which p(x) evaluated to false.

[foldr op% e xs] evaluates x1 % (x2 % ( ... % (x(n-1) % (xn % e)) ... ))
where xs = [x1, x2, ..., x(n-1), xn], and % is taken to be infix.

[foldl op% e xs] evaluates xn % (x(n-1) % ( ... % (x2 % (x1 % e))))
where xs = [x1, x2, ..., x(n-1), xn], and % is taken to be infix.

[exists p xs] applies p to each element x of xs, from left to
right until p(x) evaluates to true; returns true if such an x
exists, otherwise false.

[all p xs] applies p to each element x of xs, from left to
right until p(x) evaluates to false; returns false if such an x
exists, otherwise true.

[collate cmp (xs, ys)] returns LESS, EQUAL or GREATER according as
xs precedes, equals or follows ys in the lexicographic ordering on
lists induced by the ordering cmp on elements.

[tabulate(n, f)] returns a list of length n whose elements are
f(0), f(1), ..., f(n-1), created from left to right. Raises Size
if n<0.

[getItem xs] attempts to extract an element from the list xs. It
returns NONE if xs is empty, and returns SOME (x, xr) if xs=x:xr.
This can be used for scanning booleans, integers, reals, and so on
from a list of characters. For instance, to scan a decimal integer
from a list cs of characters, compute
    Int.scan StringCvt.DEC List.getItem cs
```

Module ListPair

ListPair -- SML Basis Library

```
val zip      : 'a list * 'b list -> ('a * 'b) list
val unzip    : ('a * 'b) list -> 'a list * 'b list
val map      : ('a * 'b -> 'c) -> 'a list * 'b list -> 'c list
val app      : ('a * 'b -> unit) -> 'a list * 'b list -> unit
val all      : ('a * 'b -> bool) -> 'a list * 'b list -> bool
val exists   : ('a * 'b -> bool) -> 'a list * 'b list -> bool
val foldr    : ('a * 'b * 'c -> 'c) -> 'c -> 'a list * 'b list -> 'c
val foldl    : ('a * 'b * 'c -> 'c) -> 'c -> 'a list * 'b list -> 'c
val allEq    : ('a * 'b -> bool) -> 'a list * 'b list -> bool

exception UnequalLengths

val zipEq    : ('a list * 'b list) -> ('a * 'b) list
val mapEq    : ('a * 'b -> 'c) -> 'a list * 'b list -> 'c list
val appEq    : ('a * 'b -> 'c) -> 'a list * 'b list -> unit
val foldrEq  : ('a * 'b * 'c -> 'c) -> 'c -> 'a list * 'b list -> 'c
val foldlEq  : ('a * 'b * 'c -> 'c) -> 'c -> 'a list * 'b list -> 'c

These functions process pairs (xs, ys) of lists.
There are three groups of functions:

* zip, map, app, all, exists, foldr and foldl raise no exception
  when the argument lists are found to be of unequal length; the
  excess elements from the longer list are simply disregarded.

* zipEq, mapEq, appEq, foldrEq and foldlEq raise exception
  UnequalLengths when the argument lists are found to be of
  unequal length.

* allEq raises no exception but returns false if the lists are
  found to have unequal lengths (after traversing the lists).

[zip (xs, ys)] returns the list of pairs of corresponding elements
from xs and ys.

[unzip xys] returns a pair (xs, ys), where xs is the list of first
components of xys, and ys is the list of second components from
xys. Hence zip (unzip xys) has the same result and effect as xys.

[map f (xs, ys)] applies function f to the pairs of corresponding
elements of xs and ys from left to right and returns the list of
results. Hence map f (xs, ys) has the same result and effect as
List.map f (zip (xs, ys)).

[app f (xs, ys)] applies function f to the pairs of corresponding
elements of xs and ys from left to right and returns (). Hence
app f (xs, ys) has the same result and effect as
List.app f (zip (xs, ys)).

[all p (xs, ys)] applies predicate p to the pairs of corresponding
elements of xs and ys from left to right until p evaluates to false
or one or both lists is exhausted; returns true if p is true of all
such pairs; otherwise false. Hence all p (xs, ys) has the same
result and effect as List.all p (zip (xs, ys)).

[exists p (xs, ys)] applies predicate p to the pairs of
corresponding elements of xs and ys from left to right until p
evaluates to true or one or both lists is exhausted; returns true
if p is true of any such pair; otherwise false.
Hence exists p (xs, ys) has the same result and effect as
List.exists p (zip (xs, ys)). Also, exists p (xs, ys) is equivalent
to not(all (not o p) (xs, ys)).

[foldr f e (xs, ys)] evaluates f(x1, y1, f(x2, y2, f(..., f(xn, yn, e))))
where xs = [x1, x2, ..., x(n-1), xn, ...],
      ys = [y1, y2, ..., y(n-1), yn, ...],
```

```
and   n = min(length xs, length ys).
Equivalent to List.foldr (fn ((x, y), r) => f(x, Y, r)) e (zip(xs, ys)).

[foldl f e (xs, ys)] evaluates f(xn, yn, f( ..., f(x2, y2, f(x1, y1, e))))
where xs = [x1, x2, ..., x(n-1), xn, ...],
and      ys = [y1, y2, ..., y(n-1), yn, ...],
and   n = min(length xs, length ys).
Equivalent to List.foldl (fn ((x, y), r) => f(x, Y, r)) e (zip(xs, ys)).

[zipEq (xs, ys)] returns the list of pairs of corresponding
elements from xs and ys.  Raises UnequalLengths if xs and ys do not
have the same length.

[mapEq f (xs, ys)] applies function f to pairs of corresponding
elements of xs and ys from left to right, and then returns the list
of results if xs and ys have the same length, otherwise raises
UnequalLengths.  If f has no side effects and terminates, then
it is equivalent to List.map f (zipEq (xs, ys)).

[appEq f (xs, ys)] applies function f to pairs of corresponding
elements of xs and ys from left to right, and then raises
UnequalLengths if xs and ys have the same length.

[foldrEq f e (xs, ys)] raises UnequalLengths if xs and ys do not
have the same length.  Otherwise evaluates
  f(x1, y1, f(x2, y2, f(..., f(xn, yn, e))))
where xs = [x1, x2, ..., x(n-1), xn],
and      ys = [y1, y2, ..., y(n-1), yn],
and   n = length xs = length ys.
Equivalent to List.foldr (fn ((x,y),r) => f(x,Y,r)) e (zipEq(xs, ys)).

[foldlEq f e (xs, ys)] evaluates
  f(xn, yn, f( ..., f(x2, y2, f(x1, y1, e))))
where xs = [x1, x2, ..., x(n-1), xn, ...],
and      ys = [y1, y2, ..., y(n-1), yn, ...],
and   n = min(length xs, length ys).
Then raises UnequalLengths if xs and ys do not have the same
length.  If f has no side effects and terminates normally, then it is
equivalent to List.foldl (fn ((x,y),r) => f(x,Y,r)) e (zipEq(xs, ys)).

[allEq p (xs, ys)] works as all p (xs, ys) but returns false if xs
and ys do not have the same length.  Equivalent to
  all p (xs, ys) and also length xs = length ys.
```

Module Listsort

Listsort

```
val sort   : ('a * 'a -> order) -> 'a list -> 'a list
val sorted : ('a * 'a -> order) -> 'a list -> bool
```

[sort ord xs] sorts the list xs in nondecreasing order, using the given ordering. Uses Richard O'Keefe's smooth applicative merge sort.

[sorted ord xs] checks that the list xs is sorted in nondecreasing order, in the given ordering.

Module Location

```
Location -- error reporting for mosmllex and mosmlyac
Based on src/compiler/location from the Caml Light 0.6 distribution

datatype Location = Source file positions
  Loc of int      Position of the first character
    * int         Position of the character following the last one

val errLocatation : string * BasicIO.instream * Lexing.lexbuf -> Location
    -> unit
val errMsg       : string * BasicIO.instream * Lexing.lexbuf -> Location
    -> string -> 'a
val errPrompt   : string -> unit;
val nilLocation : Location
val getCurrentLocation : unit -> Location
val mkLoc : 'a -> Location * 'a
val xLR : Location * 'a -> Location
val xL : Location * 'a -> int
val xR : Location * 'a -> int
val xxLR : Location * 'a -> Location * 'b -> Location
val xxLR : Location * 'a -> Location * 'b -> Location
val xxRL : Location * 'a -> Location
```

These functions support error reporting in lexers and parsers generated with mosmllex and mosmlyac. The directory mosml/examples/lex yacc/ contains an example of their use.

[errLocatation (file, stream, lexbuf) loc] prints the part of the lexer input which is indicated by location loc.

If file <> "" then it is assumed to be the name of the file from which the lexer reads, the stream is assumed to be an open input stream associated with this file, and lexbuf is the lexer buffer used to read from the stream. Under MS DOS (and presumably Windows, OS/2, and MacOS), the stream must have been opened in binary mode (with NonStdio.open_in_bin), or else the positioning in the file will be wrong (due to the translation of CRLF into newline in text files).

If file = "" then the lexer is assumed to read from some source other than a stream, and the lexbuf (rather than the instream) is used to obtain the location indicated, if possible. In this case the stream is immaterial; it will not be used.

[errMsg (file, stream, lexbuf) loc msg] calls errLocatation to print the indicated part of the lexer input, then prints the error message msg and raises exception Fail.

[errPrompt msg] prints " ! ", the string msg, and a newline on standard output.

[nilLocation] is the undefined location.

[getCurrentLocation ()] can be called within the semantic action part of a grammar rule (only) and returns the location of the string matching the left-hand side of the rule.

[mkLoc a] can be called within the semantic action part of a grammar rule (only), and returns a pair (loc, a) of the current location and the value a. This is typically used to decorate abstract syntax tree nodes with location information, for use in subsequent error reports.

[xLR loc_a] returns the location of the decorated value loc_a.

[xL loc_a] returns the left end position of loc_a.

[xR loc_a] returns the right end position of loc_a.

[xxLR loc_a loc_b] returns the location extending from the left end of loc_a to the right end of loc_b.

[xxRL loc_a loc_b] returns the location extending from the right end of loc_a to the left end of loc_b.

Module Math

Math -- SML Basis Library

```
type real = real

val pi    : real
val e     : real

val sqrt  : real -> real
val sin   : real -> real
val cos   : real -> real
val tan   : real -> real
val atan  : real -> real
val asin  : real -> real
val acos  : real -> real
val atan2 : real * real -> real
val exp   : real -> real
val pow   : real * real -> real
val ln    : real -> real
val log10 : real -> real
val sinh  : real -> real
val cosh  : real -> real
val tanh  : real -> real

[pi] is the circumference of the circle with diameter 1, that is,
3.14159265358979323846.

[e] is the base of the natural logarithm: 2.7182818284590452354.

[sqrt x] is the square root of x.  Raises Domain if x < 0.0.

[sin x] is the sine of x, where x is in radians.

[cos x] is the cosine of x, where x is in radians.

[tan x] is the tangent of x, where x is in radians.  Raises Domain if
x is a multiple of pi/2.

[atan t] is the arc tangent of t, in the open interval ] -pi/2, pi/2 [.

[asin t] is the arc sine of t, in the closed interval [ -pi/2, pi/2 ].
Raises Domain if abs x > 1.

[acos t] is the arc cosine of t, in the closed interval [ 0, pi ].
Raises Domain if abs x > 1.

[atan2(y, x)] is the arc tangent of y/x, in the interval ] -pi, pi [,
except that atan2(y, 0) = sign y * pi/2.  The quadrant of the result
is the same as the quadrant of the point (x, y).
Hence sign(cos(atan2(y, x))) = sign x
and   sign(sin(atan2(y, x))) = sign y.

[exp x] is e to the x'th power.

[pow (x, y)] is x to the y'th power, defined when
y >= 0 and (y integral or x >= 0)
or y < 0 and ((y integral and x <> 0.0) or x > 0).

We define pow(0, 0) = 1.

[ln x] is the natural logarithm of x (that is, with base e).
Raises Domain if x <= 0.0.

[log10 x] is the base-10 logarithm of x.  Raises Domain if x <= 0.0.

[sinh x] returns the hyperbolic sine of x, mathematically defined as
(exp x - exp (-x)) / 2.  Raises Overflow if x is too large.

[cosh x] returns the hyperbolic cosine of x, mathematically defined as
(exp x + exp (-x)) / 2.  Raises Overflow if x is too large.
```

[tanh x] returns the hyperbolic tangent of x, mathematically defined
as (sinh x) / (cosh x). Raises Domain if x is too large.

Module Meta

Meta -- functions available only in interactive Moscow ML sessions

```
val printVal      : 'a -> 'a
val printDepth    : int ref
val printLength   : (ppstream -> 'a -> unit) -> unit
val installPP     : (ppstream -> 'a -> unit) -> unit

val liberal       : unit -> unit
val conservative : unit -> unit
val orthodox      : unit -> unit

val use           : string -> unit
val compile       : string -> unit
val compileTopLevel : string list -> string -> unit
val compileStructure : string list -> string -> unit

val load         : string -> unit
val loadOne      : string -> unit
val loaded       : unit -> string list
val loadPath     : string list ref

val quietdec     : bool ref
val verbose      : bool ref

val quotation    : bool ref
val valuepoly    : bool ref

val quit         : unit -> 'a
```

These values and functions are available in the Moscow ML interactive system only.

[printVal e] prints the value of expression e to standard output exactly as it would be printed at top-level, and returns the value of e. Output is flushed immediately. This function is provided as a simple debugging aid. The effect of printVal is similar to that of 'print' in Edinburgh ML or Umeaa ML. For string arguments, the effect of SML/NJ print can be achieved by the function TextIO.print : string -> unit.

[printDepth] determines the depth (in terms of nested constructors, records, tuples, lists, and vectors) to which values are printed by the top-level value printer and the function printVal. The components of the value whose depth is greater than printDepth are printed as '#'. The initial value of printDepth is 20. This value can be changed at any moment, by evaluating, for example,

```
printDepth := 17;
```

[printLength] determines the way in which list values are printed by the top-level value printer and the function printVal. If the length of a list is greater than printLength, then only the first printLength elements are printed, and the remaining elements are printed as '...'. The initial value of printLength is 200. This value can be changed at any moment, by evaluating, for example,

```
printLength := 500;
```

[quit ()] quits Moscow ML immediately.

[installPP pp] installs the prettyprinter pp : ppstream -> ty -> unit at type ty. The type ty must be a nullary (parameter-less) type constructor representing a datatype, either built-in (such as bool) or user-defined. Whenever a value of type ty is about to be printed by the interactive system, or function printVal is invoked on an argument of type ty, the pretty-printer pp will be invoked to print it. See library unit PP for more information.

[use "f"] causes ML declarations to be read from file f as if they were entered from the console. A file loaded by use may, in turn, evaluate calls to use. For best results, use 'use' only at top

level, or at top level within a use'd file.

[liberal ()] sets liberal mode for the compilation functions: accept (without warnings) all extensions to the SML Modules language. The extensions are: higher-order modules (functors defined within structures and functors); first-order modules (structures can be packed as values, and values can be unpacked as structures); and recursively defined modules (signatures and structures). The liberal, conservative, and orthodox modes affect the functions compile, compileStructure, and compileTopLevel. The liberal mode may be set also by the mosml option -liberal.

[conservative ()] sets conservative mode for the compilation functions: accept all extensions to the SML Modules language, but issue a warning for each use. The conservative mode may be set also by the mosml option -conservative. This is the default.

[orthodox ()] sets orthodox mode for the compilation functions: reject all uses of the extensions to the SML Modules language. That is, accept only SML Modules syntax. The orthodox mode may be set also by the mosml option -orthodox.

[compile "U.sig"] will compile and elaborate the specifications in file U.sig in structure mode, producing a compiled signature U in file U.ui. This function is backwards compatible with Moscow ML 1.44 and earlier. Equivalent to compileStructure [] "U.sig".

[compile "U.sml"] will elaborate and compile the declarations in file U.sml in structure mode, producing a compiled structure U in bytecode file U.uo. If there is an explicit signature file U.sig, then file U.ui must exist, and the unit body must match the signature. If there is no U.sig, then an inferred signature file U.ui will be produced also. No evaluation takes place. This function is backwards compatible with Moscow ML 1.44 and earlier. Equivalent to compileStructure [] "U.sml".

The declared identifiers will be reported if verbose is true (see below); otherwise compilation will be silent. In any case, compilation warnings are reported, and compilation errors about the compilation and raise the exception Fail with a string argument.

[compileStructure opunits "U.sig"] compiles the specifications in file U.sig as if they form a signature declaration signature U = sig ... contents of U.sig ... end The contents of opunits is added to the compilation context in which the specifications in U.sig are compiled. The result is a compiled signature file U.ui. This corresponds to invoking the batch compiler as follows: mosmlc -c U1.ui ... Un.ui -structure U.sig where opunits equals ["U1", ..., "Un"].

[compileStructure opunits "U.sml"] compiles the declarations in file U.sml as if they formed a structure declaration structure U = struct ... contents of U.sml ... end The contents of opunits is added to the compilation context in which the declarations in U.sml are compiled. If U.ui exists already and represents a signature called U, then the compiled declarations are matched against it. The result is a bytecode file U.uo. If no file U.ui existed, then also a file U.ui is created, containing the inferred signature of structure U. This corresponds to invoking the batch compiler as follows: mosmlc -c U1.ui ... Un.ui -structure U.sml where opunits equals ["U1", ..., "Un"].

[compileTopLevel opunits "U.sig"] compiles the specifications in file U.sig, in a context in which all declarations from opunits are visible, creating a compiled signature file U.ui. This corresponds to invoking the batch compiler as follows: mosmlc -c U1.ui ... Un.ui -toplevel U.sig where opunits equals ["U1", ..., "Un"].

[compileTopLevel opunits "U.sml"] compiles the declarations in

file U.sml, in a context in which all declarations from opunits are visible, creating a bytecode file U.uo. If U.ui exists already, then the compiled declarations are matched against it; otherwise the file U.ui is created. This corresponds to invoking the batch compiler as follows

```
mosaic -c U.ui ... Un.ui -toplevel U.sml
where opunits equals ["U", ..., "Un"].
```

[load "U"] will load and evaluate the compiled unit body from file U.uo. The resulting values are not reported, but exceptions are reported, and cause evaluation and loading to stop. If U is already loaded, then load "U" has no effect. If any other unit is mentioned by U but not yet loaded, then it will be loaded automatically before U.

After loading a unit, it can be opened with 'open U'. Opening it at top-level will list the identifiers declared in the unit.

When loading U, it is checked that the signatures of units mentioned by U agree with the signatures used when compiling U, and it is checked that the signature of U has not been modified since U was compiled; these checks are necessary for type safety. The exception Fail is raised if these signature checks fail, or if the file containing U or a unit mentioned by U does not exist.

[loadOne "U"] is similar to 'load "U"', but raises exception Fail if U is already loaded or if some unit mentioned by U is not yet loaded. That is, it does not automatically load any units mentioned by U. It performs the same signature checks as 'load'.

[loaded ()] returns a list of the names of all compiled units that have been loaded so far. The names appear in some random order.

[loadPath] determines the load path: which directories will be searched for interface files (.hi files), bytecode files (.uo files), and source files (.sml files). This variable affects the load, loadOne, and use functions. The current directory is always searched first, followed by the directories in loadPath, in order. By default, only the standard library directory is in the list, but if additional directories are specified using option -I, then these directories are prepended to loadPath.

[quietdec] when true, turns off the interactive system's prompt and responses, except warnings and error messages. Useful for writing scripts in SML. The default value is false; can be set to true with the -quietdec command line option.

[verbose] determines whether the signature inferred by a call to compile will be printed. The printed signature follows the syntax of Moscow ML signatures, so the output of compile "U.sml" can be edited to subsequently create file U.sig. The default value is ref false.

[quotation] determines whether quotations and antiquotations are permitted in declarations entered at top-level and in files compiled with compile. A quotation is a piece of text surrounded by backquote characters 'a b c' and is used to embed object language phrases in ML programs; see the Moscow ML Owner's Manual for a brief explanation of quotations. When quotation is false, the backquote character is an ordinary symbol which can be used in ML symbolic identifiers. When quotation is true, the backquote character is illegal in symbolic identifiers, and a quotation 'a b c' will be recognized by the parser and evaluated to an object of type 'a General.frag list. False by default.

[valuepoly] determines whether value polymorphism is used or not in the type checker. With value polymorphism (the default), there is no distinction between imperative ('a) and applicative ('a) type variables, and type variables are generalized only in bindings to non-expansive expressions. Non-generalized type variables are left free, to be instantiated when the bound identifier is used. An expression is non-expansive if it is a variable, a special

constant, a function, a tuple or record of non-expansive expressions, a parenthesized or typed non-expansive expression, or the application of an exception or value constructor (other than ref) to a non-expansive expression. If valuepoly is false, then the type checker will distinguish imperative and applicative type variables, generalize all applicative type variables, and generalize imperative type variables only in non-expansive expressions. True by default.

Module Mosml

Mosml -- some Moscow ML specific functions

```
val argv      : unit -> string list
val time      : ('a -> 'b) -> ('a -> 'b)
val listDir   : string -> string list
val vecDouble : real -> Word8Vector.vector
val vecDouble : Word8Vector.vector -> real
val floatVec  : real -> Word8Vector.vector
val vecFloat  : Word8Vector.vector -> real
val md5sum    : string -> string
```

```
datatype runresult =
  Success of string
  | Failure of string
```

```
val run : string -> string list -> string -> runresult
```

[argv ()] returns the command line strings of the current process. Hence List.nth(argv (), 0) is the command used to invoke the SML process, List.nth(argv (), 1) is its first argument, and so on. We recommend using the SML Basis Library CommandLine structure instead.

[time f argv] applies f to argv and returns the result; as a side effect, it prints the time (cpu, system, and real time) consumed by the evaluation.

[listDir path] returns the list of all files and subdirectories of the directory indicated by path. Raises OS.SysErr in case of failure.

[doubleVec r] returns an eight-element vector of Word8.word, which contains the real number in the IEEE 754 floating-point 'double format' bit layout stored in big-endian (high byte first) order.

[vecDouble v] accepts an eight-element vector v of Word8.word, and returns the real number obtained by taking v to be an IEEE 754 floating-point 'double format' number stored in big-endian (high byte first) order. Raises Fail if v is not an eight-element vector.

[floatVec r] returns a four-element vector of Word8.word, which contains the real number in the IEEE 754 floating-point 'float format' bit layout stored in big-endian (high byte first) order. Raises Fail if r is not representable as a 32-bit float.

[vecFloat v] accepts a four-element vector v of Word8.word, and returns the real obtained by taking v to be an IEEE 754 floating-point 'float format' number stored in big-endian (high byte first) order. Raises Fail if v is not a four-element vector.

[md5sum s] computes the 128-bit MD5 checksum of string s and returns it as a 22 character base64 string.

[run cmd args inp] executes the program cmd with command-line arguments args and standard input inp. Returns Success s where s is the program s (standard and error) output as a string, if it executed successfully; otherwise returns Failure s where s is its (standard and error) output as a string.

Module Mosmlcgi

Mosmlcgi -- support for writing CGI scripts in Moscow ML

1. Accessing the fields or parameters of a CGI call

```
val cgi_fieldnames      : string list
val cgi_field_strings   : string -> string list;
val cgi_field_string    : string -> string option;
val cgi_field_integer   : string * int -> int;
```

2. Accessing parts in multipart/form-data; form-based file upload

```
val cgi_partnames      : string list
```

```
type part
```

```
val cgi_part           : string -> part option
val cgi_parts          : string -> part list
```

```
val part_fieldnames    : part -> string list
val part_type          : part -> string option
val part_data          : part -> string
val part_field_strings : part -> string -> string list
val part_field_string  : part -> string -> string option
val part_field_integer : part -> string * int -> int
```

3. Administrative information

```
val cgi_server_software : string option
val cgi_server_name     : string option
val cgi_gateway_interface : string option
val cgi_server_protocol : string option
val cgi_server_port     : string option
val cgi_request_method  : string option
val cgi_http_accept     : string option
val cgi_http_user_agent : string option
val cgi_http_referer    : string option
val cgi_path_info       : string option
val cgi_path_translated : string option
val cgi_script_name     : string option
val cgi_query_string    : string option
val cgi_remote_host     : string option
val cgi_remote_addr     : string option
val cgi_remote_user     : string option
val cgi_remote_ident     : string option
val cgi_auth_type       : string option
val cgi_content_type    : string option
val cgi_content_length  : string option
val cgi_annotation_server : string option
```

```
val cgi_http_cookie    : string option
val cgi_http_forwarded : string option
val cgi_http_host      : string option
val cgi_http_proxy_connection : string option
val cgi_script_filename : string option
val cgi_document_root  : string option
val cgi_server_admin   : string option
val cgi_api_version    : string option
val cgi_the_request    : string option
val cgi_request_uri    : string option
val cgi_request_filename : string option
val cgi_is_subreq      : string option
```

The Mosmlcgi library is for writing CGI programs in Moscow ML. A CGI program may be installed on a WWW server and is invoked in response to HTTP requests sent to the server from a web browser, typically from an HTML FORM element.

1. Obtaining field values sent from an ordinary HTML form

[cgi_fieldnames] is a list of the names of fields present in the CGI call message. If field name fnm is in cgi_fieldnames, then cgi_field_string fnm <> NONE.

[cgi_field_strings fnm] is a (possibly empty) list of the strings bound to field fnm.

[cgi_field_string fnm] returns SOME(s) where s is a string bound to field name fnm, if any; otherwise NONE. Equivalent to
 case cgi_field_strings fnm of
 [] => NONE
 | s :: _ => SOME s

[cgi_field_integer (fnm, deflt)] attempts to parse an integer from field fnm. Returns i if cgi_field_string(fnm) = SOME(s) and an integer i can be parsed from a prefix of s; otherwise returns deflt.

2. Obtaining field values sent with ENCTYPE="multipart/form-data"

[cgi_partnames] is a list of the names of the parts of the multipart/form-data message.

The type part is the abstract type of parts of a message. Each part may have several fields. In this implementation, the field of a part cannot be a another part itself.

[cgi_parts pnm] is a (possibly empty) list of the parts called pnm.

[cgi_part pnm] is SOME(prt) where prt is a part called pnm, if any; otherwise NONE. Equivalent to
 case cgi_parts pnm of
 [] => NONE
 | prt :: _ => SOME prt

[part_fieldnames prt] is the list of field names in part pnm.

[part_type prt] is SOME(typ) if the part prt contains a specification 'Context-type: typ'; otherwise NONE.

[part_data prt] is the data contain in part prt; for instance, the contents of a file uploaded via form-based file upload.

[part_field_strings prt fnm] is a (possibly empty) list of the strings bound to field fnm in part prt.

[part_field_string prt fnm] returns SOME(s) where s is a string bound to field name fnm in part prt, if any; otherwise NONE.

Equivalent to
 case part_field_strings prt fnm of
 [] => NONE
 | s :: _ => SOME s

[part_field_integer prt (fnm, deflt)] attempts to parse an integer from field fnm of part prt. Returns i if part_field_string prt fnm = SOME(s) and an integer i can be parsed from a prefix of s; otherwise returns deflt.

3. Administrative and server information

Each of the following variables has the value SOME(s) if the corresponding CGI environment variable is bound to string s; otherwise NONE:

[cgi_server_software] is the value of SERVER_SOFTWARE

[cgi_server_name] is the value of SERVER_NAME

[cgi_gateway_interface] is the value of GATEWAY_INTERFACE

[cgi_server_protocol] is the value of SERVER_PROTOCOL

[cgi_server_port] is the value of SERVER_PORT

[cgi_request_method] is the value of REQUEST_METHOD

[cgi_http_accept] is the value of HTTP_ACCEPT

[cgi_http_user_agent] is the value of HTTP_USER_AGENT

[cgi_http_referer] is the value of HTTP_REFERER

[cgi_path_info] is the value of PATH_INFO

[cgi_path_translated] is the value of PATH_TRANSLATED

[cgi_script_name] is the value of SCRIPT_NAME

[cgi_query_string] is the value of QUERY_STRING

[cgi_remote_host] is the value of REMOTE_HOST

[cgi_remote_addr] is the value of REMOTE_ADDR

[cgi_remote_user] is the value of REMOTE_USER

[cgi_remote_ident] is the value of REMOTE_IDENT

[cgi_auth_type] is the value of AUTH_TYPE

[cgi_content_type] is the value of CONTENT_TYPE

[cgi_content_length] is the value of CONTENT_LENGTH, that is, the length of the data transmitted in the CGI call.

[cgi_annotation_server] is the value of ANNOTATION_SERVER

[cgi_http_cookie] is the value of HTTP_COOKIE

[cgi_http_forwarded] is the value of HTTP_FORWARDED

[cgi_http_host] is the value of HTTP_HOST

[cgi_http_proxy_connection] is the value of HTTP_PROXY_CONNECTION

[cgi_script_filename] is the value of SCRIPT_FILENAME

[cgi_document_root] is the value of DOCUMENT_ROOT

[cgi_server_admin] is the value of SERVER_ADMIN

[cgi_api_version] is the value of API_VERSION

[cgi_the_request] is the value of THE_REQUEST

[cgi_request_uri] is the value of REQUEST_URI

[cgi_request_filename] is the value of REQUEST_FILENAME

[cgi_is_subreq] is the value of IS_SUBREQ

Module Mosmlcookie

Mosmlcookie -- getting and setting cookies in CGI scripts

```
exception CookieError of string

val allCookies      : string list
val getCookieValue  : string -> string option
val getCookie       : string -> string option

type cookiedata =
  { name : string,
    value : string,
    expiry : Date.date option,
    domain : string option,
    path : string option,
    secure : bool }

val setCookie      : cookiedata -> string
val setCookies     : cookiedata list -> string
val deleteCookie   : { name : string, path : string option } -> string
```

These functions may be used in CGI scripts to get and set cookies.
(c) Hans Molin, Computing Science Dept., Uppsala University, 1999.

[getCookieValue ck] returns SOME(v) where v is the value associated with the cookie ck, if any; otherwise returns NONE.

[getCookie ck] returns SOME(nv) where nv is the ck=value string for the cookie ck, if any; otherwise returns NONE.

[allCookies] is a list [nv1, nv2, ..., nvml] of all the ck=value pairs of defined cookies.

[setCookie { name, value, expiry, domain, path, secure }] returns a string which (when transmitted to a browser as part of the HTTP response header) sets a cookie with the given name, value, expiry date, domain, path, and security.

[setCookies ckds] returns a string which (when transmitted to a browser as part of the HTTP response header) sets the specified cookies.

[deleteCookie { name, path }] returns a string which (when transmitted to a browser as part of the HTTP response header) deletes the specified cookie by setting its expiry to some time in the past.

Module Msp

Msp -- utilities for CGI scripts and ML Server Pages

Efficiently concatenable word sequences

```
datatype wseq =
  | Empty
  | NL
  | $ of string
  | $$ of string list
  | && of wseq * wseq;

The empty sequence
Newline
A string
A sequence of strings
Concatenation of sequences

Manipulating wseqs

val prmap      : ('a -> wseq) -> 'a list -> wseq
val prsep      : wseq -> ('a -> wseq) -> 'a list -> wseq
val flatten     : wseq -> string
val printseq    : wseq -> unit
val vec2list    : 'a vector -> 'a list
```

Shorthands for accessing CGI parameters

```
exception ParamMissing of string
exception NotInt of string * string

val %      : string -> string
val %?     : string -> bool
val %%     : string -> int
val %%#    : string * string -> string
val %%##   : string * int -> int
```

HTML generic marks

```
val mark0      : string -> wseq
val mark0a     : string -> string -> wseq
val mark1      : string -> wseq -> wseq
val mark1a     : string -> string -> wseq -> wseq
val comment    : wseq -> wseq
```

HTML documents and headers

```
val html       : wseq -> wseq
val head       : wseq -> wseq
val title      : wseq -> wseq
val body       : wseq -> wseq
val bodya      : string -> wseq -> wseq
val htmldoc    : wseq -> wseq -> wseq
```

HTML headings and vertical format

```
val h1         : wseq -> wseq
val h2         : wseq -> wseq
val h3         : wseq -> wseq
val h4         : wseq -> wseq
val h5         : wseq -> wseq
val h6         : wseq -> wseq
val p          : wseq -> wseq
val pa         : string -> wseq -> wseq
val br         : wseq
val bra        : string -> wseq
val hr         : wseq
val hra        : string -> wseq

val divi       : wseq -> wseq
val divia      : string -> wseq -> wseq
val blockquote : wseq -> wseq
val blockquotea : string -> wseq -> wseq
val center     : wseq -> wseq
```

```
val address      : wseq -> wseq
val pre         : wseq -> wseq

HTML anchors and hyperlinks

val ahref       : string -> wseq
val hrefa      : string -> wseq
val aname      : string -> wseq
```

HTML text formats and style

```
val em         : wseq -> wseq
val strong     : wseq -> wseq
val tt        : wseq -> wseq
val sub       : wseq -> wseq
val sup       : wseq -> wseq
val fonta     : string -> wseq -> wseq
```

HTML lists

```
val ul         : wseq -> wseq
val ula       : string -> wseq
val ol        : wseq -> wseq
val ola       : string -> wseq
val li        : wseq -> wseq
val dli       : wseq -> wseq
val dli       : string -> wseq
val dt        : wseq -> wseq
val dd        : wseq -> wseq
```

HTML tables

```
val table     : wseq -> wseq
val tablea    : string -> wseq
val tr        : wseq -> wseq
val tra       : string -> wseq
val td        : wseq -> wseq
val tda       : string -> wseq
val th        : wseq -> wseq
val tha       : string -> wseq
val caption   : wseq -> wseq
val captiona  : string -> wseq
```

HTML images and image maps

```
val img       : string -> wseq
val imga     : string -> wseq
val map      : string -> wseq
val mapa     : string -> wseq
val area     : { alt : string option, coords : string,
                href : string option, shape : string } -> wseq
```

HTML forms etc

```
val form      : string -> wseq
val forma     : string -> wseq
val input     : string -> wseq
val inputa    : string -> wseq
val text      : string -> wseq
val textarea : string -> wseq
val password  : string -> wseq
val checkbox  : { name : string, value : string } -> wseq
val radio     : { name : string, value : string } -> wseq
val reset     : string -> wseq
val submit    : string -> wseq
val inhidden  : { name : string, value : string } -> wseq
val textarea  : string -> wseq
val select    : string -> wseq
val option    : string -> wseq
```

HTML frames and framesets

```
val frameset   : string -> wseq -> wseq
val frame      : { src : string, name : string } -> wseq
val framea     : { src : string, name : string } -> wseq
```

HTML encoding

```
val urlencode  : string -> string
val htmlencode : string -> string
```

This module provides support functions for writing CGI scripts and ML Server Page scripts.

[wseq] is the type of efficiently concatenable word sequences. Building an HTML page (functionally) as a wseq is more efficient than building it (functionally) as a string, and more convenient and modular than building it (imperatively) by calling print.

[Empty] represents the empty string "".

[NL] represents the string "\n" consisting of a single newline character.

[\$ s] represents the string s.

[\$\$ ss] represents the string String.concat(ss).

[&&(ws1, ws2)] represents the concatenation of the strings represented by ws1 and ws2. The function && should be declared infix &&

[pmap f xs] is f x1 && ... && f xn evaluated from left to right, when xs is [x1, ..., xn].

[prsep sep f xs] is f x1 && sep && ... && sep && f xn, evaluated from left to right, when xs is [x1, ..., xn].

[flatten ws] is the string represented by ws.

[printseq ws] is equivalent to print(flatten ws), but avoids building any new strings.

[vec2list vec] is a list of the elements of vector vec. Use it to convert e.g. the results of a database query into a list, for processing with pmap or prsep.

Shorthands for accessing CGI parameters:

[%? fmm] returns true if there is a string associated with CGI parameter fmm; otherwise returns false.

[% fmm] returns a string associated with CGI parameter fmm if there is any; raises ParamMissing(fmm) if no strings are associated with fmm. Equivalent to

```
case Mosmlogi.cgi_field_string fmm of
| NONE => raise ParamMissing "fmm"
| SOME v => v
```

In general, multiple strings may be associated with a CGI parameter; use Mosmlogi.cgi_field_strings if you need to access all of them.

[%# fmm] returns the integer i if there is a string associated with CGI parameter fmm, and that string is parsable as ML integer i. Raises ParamMissing(fmm) if no string is associated with fmm. Raises NotInt(fmm, s) if there is a string but it is not parsable as an ML int.

[%(fmm, dflt)] returns a string associated with CGI parameter fmm if there is any; otherwise returns the string dflt.

[%%#(fmm, dflt)] returns the integer i if there is a string associated with CGI parameter fmm, and that string is parsable as

an ML int; otherwise returns the string dflt.

HTML generic marks:

- [mark0 t] generates the HTML tag <t> as a wseq.
- [mark0a attr t] generates the attributed HTML tag <t attr> as a wseq.
- [mark1 t ws] generates <t>ws</t> as a wseq.
- [mark1a attr t ws] generates <t attr>ws</t> as a wseq.
- [comment ws] generates <!--ws--> as a wseq.

HTML documents and headers:

- [html ws] generates <HTML>ws</HTML>.
- [head ws] generates <HEAD>ws</HEAD>.
- [title ws] generates <TITLE>ws</TITLE>.
- [body ws] generates <BODY>ws</BODY>.
- [bodya attr ws] generates <BODY attr>ws</BODY>.
- [htmldoc titl ws] generates <HTML><HEAD><TITLE>titl</TITLE></HEAD><BODY>ws</BODY></HTML>.

HTML headings and vertical format:

- [h1 ws] generates <H1>ws</H1>.
- [p ws] generates <P>ws</P>.
- [pa attr ws] generates <P attr>ws</P>.
- [br] generates
.
- [bra attr] generates <BR attr>.
- [hr] generates <HR>.
- [hra attr] generates <HR attr>.
- [divi ws] generates <DIV>ws</DIV>.
- [divia attr ws] generates <DIV attr>ws</DIV>.
- [blockquote ws] generates <BLOCKQUOTE>ws</BLOCKQUOTE>.
- [blockquotea attr ws] generates <BLOCKQUOTE attr>ws</BLOCKQUOTE>.
- [center ws] generates <CENTER>ws</CENTER>.
- [address ws] generates <ADDRESS>ws</ADDRESS>.
- [pre ws] generates <PRE>ws</PRE>.

HTML anchors and hyperlinks:

- [ahref link ws] generates ws.
 - [ahrefa link attr ws] generates ws.
 - [aname nam ws] generates ws.
- generates ws.
- generates ws.
- generates <TT>ws</TT>.
- generates _{ws}.
- generates ^{ws}.
- generates ws.
- HTML lists:
- generates ws.
- generates <UL attr>ws.
- generates ws.
- generates <OL attr>ws.
- generates ws.
- generates <DL>ws</DL>.
- generates <DL attr>ws</DL>.
- generates <DT>ws</DT>.
- generates <DD>ws</DD>.
- HTML tables:
- generates <TABLE>ws</TABLE>.
- generates <TABLE attr>ws</TABLE>.
- generates <TR>ws</TR>.
- generates <TR attr>ws</TR>.
- generates <TD>ws</TD>.
- generates <TD attr>ws</TD>.
- generates <TH>ws</TH>.
- generates <TH attr>ws</TH>.
- generates <CAPTION>ws</CAPTION>.
- generates <CAPTION attr>ws</CAPTION>.
- HTML images and image maps:
- generates .
- generates .
- generates <MAP NAME="name">ws</MAP>.
- generates <MAP NAME="name" attr>ws</MAP>.
- generates
- <AREA SHAPE="shape" COORDS="coords" HREF="link" ALT="desc">
- when href is SOME link (where href is replaced by NOHREF otherwise)

HTML text formats and style:

- [em ws] generates ws.
- [strong ws] generates ws.
- [tt ws] generates <TT>ws</TT>.
- [sub ws] generates _{ws}.
- [sup ws] generates ^{ws}.
- [fonta attr ws] generates ws.

HTML lists:

- [ul ws] generates ws.
- [ula attr ws] generates <UL attr>ws.
- [ol ws] generates ws.
- [ola attr ws] generates <OL attr>ws.
- [li ws] generates ws.
- [dl ws] generates <DL>ws</DL>.
- [dla attr ws] generates <DL attr>ws</DL>.
- [dt ws] generates <DT>ws</DT>.
- [dd ws] generates <DD>ws</DD>.

HTML tables:

- [table ws] generates <TABLE>ws</TABLE>.
- [tablea attr ws] generates <TABLE attr>ws</TABLE>.
- [tr ws] generates <TR>ws</TR>.
- [tra attr ws] generates <TR attr>ws</TR>.
- [td ws] generates <TD>ws</TD>.
- [tda attr ws] generates <TD attr>ws</TD>.
- [th ws] generates <TH>ws</TH>.
- [tha attr ws] generates <TH attr>ws</TH>.
- [caption ws] generates <CAPTION>ws</CAPTION>.
- [captiona attr ws] generates <CAPTION attr>ws</CAPTION>.

HTML images and image maps:

- [img s] generates .
- [imga s attr] generates .
- [map nam ws] generates <MAP NAME="name">ws</MAP>.
- [mapa nam attr ws] generates <MAP NAME="name" attr>ws</MAP>.
- [area { alt, coords, href, shape}] generates <AREA SHAPE="shape" COORDS="coords" HREF="link" ALT="desc">
- when href is SOME link (where href is replaced by NOHREF otherwise)

[htmlencode s] returns the html-encoding of s. That is, < and > are replaced by < and > respectively, and & is replaced by &

| | | (not used by MySQL) |
|-------------------|--|-----------------------|
| datatype dynval = | | MySQL int4 |
| Bool of bool | | MySQL float8 (Float4) |
| Int of int | | MySQL text (varchar) |
| Real of real | | |
| String of string | | |

```
| Date of int * int * int      Mysql date yyyy-mm-dd
| Time of int * int * int      Mysql time hh:mm:ss
| DateTime of Date.date       Mysql datetime
| Old of oid                  (not used by Mysql)
| Bytea of Word8Array.array   Mysql NULL value
| NullVal

val getdymfield : dbresult -> int -> int -> dynval
val getdyncup   : dbresult -> int -> dynval vector
val getdyncups  : dbresult -> dynval vector vector
val dynval2s    : dynval -> string

Bulk copying to or from a table

val copytableto : dbconn * string * (string -> unit) -> unit
val copytablefrom : dbconn * string * ((string -> unit) -> unit) -> unit

Some standard ML and MySQL types:

datatype dyntype =
  BoolTy          ML bool          (not used by Mysql)
| IntTy           ML int           Mysql int4
| RealTy          ML real          Mysql float8, float4
| StringTy        ML string       Mysql text, varchar
| DateTy          ML (yyyy, mth, day) Mysql date
| TimeTy          ML (hh, mm, ss)  Mysql time
| DateTimeTy      ML Date.date     Mysql datetime, abstime
| OldTy           ML oid          (not used by Mysql)
| ByteArrTy      ML Word8Array.array (not used by Mysql)
| UnknownTy      of oid

val fromtag : dyntype -> string
val ftype   : dbresult -> int -> dyntype
val ftypes  : dbresult -> dyntype Vector.vector

val applyto : 'a -> ('a -> 'b) -> 'b

Formatting the result of a database query as an HTML table

val formattable : dbresult -> Msp.wseq
val showquery   : dbconn -> string -> Msp.wseq
```

[dbconn] is the type of connections to a MySQL database.
[dbresult] is the type of result sets from MySQL queries.
[openbase { dbhost, dbport, dboptions, dbtty, dbname, dbuser, dbpwd }] opens a connection to a MySQL database server on the given host (default the local one) on the given port (default ?), to the given database (defaults to the user's login name), for the given user name (defaults to the current user's login name), and the given password (default none). The result is a connection which may be used in subsequent queries. In MySQL, unlike PostgreSQL, the dboptions and dbtty fields are not used.
[closebase dbconn] closes the database connection. No further queries can be executed.
[db dbconn] returns the name of the database.
[host dbconn] returns SOME h, where h is the database server host name, if the connection uses the Internet; returns NONE if the connection is to a socket on the local server.
[options dbconn] returns the options given when opening the database.
[port dbconn] returns the port number of the connection.
[tty dbconn] returns the name of the tty used for logging.

[status dbconn] returns true if the connection is usable, false otherwise.
[reset dbconn] attempts to close and then reopen the connection to the database server.
[errormessage dbconn] returns NONE if no error occurred, and SOME msg if an error occurred, where msg describes the error.
[execute dbconn query] sends an SQL query to the database server for execution, and returns a resultset dbres..
[resultstatus dbres] returns the status of the result set dbres. After a select query that succeeded, it will be `Tuples_ok`.
[ntuples dbres] returns the number of tuples in the result set after a query.
[cmdtuples dbres] returns the number of tuples affected by an insert, update, or delete SQL command.
[nfields dbres] returns the number of fields in each tuple after a query.
[fname dbres fno] returns the name of field number fno (in the result set after a query). The fields are numbered 0, 1,....
[fnames dbres] returns a vector of the field names (in the result set after a query).
[fnumber dbres frame] returns SOME i where i is the number (0, 1, ...) of the field called frame (in the result set after a query), if the result set contains such a field name; returns NONE otherwise.
[ftype dbres fno] returns the dyntype of field number fno (in the result set after a query).
[ftypes dbres] returns a vector of the dyntypes (in the result set after a query).
[fromtag dt] returns the name of the preferred MySQL type used to represent values of the dyntype dt. This may be used when building 'create table' statements.
[getint dbres fno tupno] returns the integer value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL.
[getreal dbres fno tupno] returns the floating-point value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL.
[getstring dbres fno tupno] returns the string value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL.
[getdate dbres fno tupno] returns the date (yyyy, mth, day) value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL. Raises Fail if the field cannot be scanned as a date.
[gettime dbres fno tupno] returns the time-of-day (hh, mm, ss) value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL. Raises Fail if the field cannot be scanned as a time.
[getdatetime dbres fno tupno] returns the Date.date value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL. Raises Fail if the field cannot be scanned as a date.

[getbool dbres fno tupno] returns the boolean value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL.

[isnull dbres fno tupno] returns true if the value of field number fno in tuple tupno of result set dbres is NULL; false otherwise.

[getdynfield dbres fno tupno] returns the value of field number fno in tuple tupno of result set dbres as a dynval (a wrapped value).

A NULL value is returned as NullVal. Note that the partial application (getdynfield dbres fno) precomputes the type of the field fno. Hence it is far more efficient to compute

```
let val getfno = getdynfield dbres fno
in tabulate(ntuples dbres, getfno) end
```

than to compute

```
let fun getfno tupno = getdynfield dbres fno tupno
in tabulate(ntuples dbres, getfno) end
```

because the latter repeatedly computes the type of the field.

[getdynrup dbres tupno] returns the fields of tuple tupno in result set dbres as a vector of dynvals.

[getdyntrups dbres] returns all tuples of result set dbres as a vector of vectors of dynvals.

[dynval2s dv] returns a string representing the dynval dv.

[applyto x f] computes f(x). This is convenient for applying

several functions (given in a list or vector) to the same value:

```
map (applyto 5) (tabulate(3, getdynfield dbres))
```

equals

```
[getdynfield dbres 0 5, getdynfield dbres 1 5, getdynfield dbres 2 5]
```

[copytableto(dbconn, tablename, put)] simulates a PostgreSQL "COPY TABLE TO" statement, applies the function put to every tuple of the table, represented as a line of text (not terminated by newline \n), and cleans up at the end. For instance, to copy the contents of a table t to a text stream s (one tuple on each line), define

```
fun put line =
  (TextIO.output(s, line); TextIO.output(s, "\n"))
```

and execute

```
copytableto(dbconn, "t", put).
```

[copytablefrom(dbconn, tablename, useput)] simulates a PostgreSQL "COPY TABLE FROM" statement, creates a put function for copying lines to the table, passes the put function to useput, and cleans up at the end. The put function may be called multiple times for each line (tuple); the end of each line is indicated by the newline character "\n" as usual. For instance, to copy the contents of a text stream s to a table t, define

```
fun useput put =
  while not (TextIO.endOfStream s) do put(TextIO.inputLine s);
```

and execute

```
copytablefrom(dbconn, "t", useput).
```

Note that TextIO.inputLine preserves the newline at the end of each line.

[formattable dbresult] returns a wseq representing an HTML table.

The HTML table has a column for every field in the dbresult. The first row is a table header giving the names of the fields in the dbresult. The remaining rows correspond to the tuples in the dbresult, in the order they are provided by the database server. Null fields are shown as NULL.

[showquery dbconn query] sends the SQL query to the database server, then uses formattable to format the result of the query.

Module NJ93

NJ93 -- compatibility SML/NJ 0.93 top-level environment

```
val print      : string -> unit
```

NJ93 Integer

```
val max      : int * int -> int
val min      : int * int -> int
```

NJ93 List

exception Hd and Tl and Nth and NthTail

```
val hd       : 'a list -> 'a           Hd
val tl       : 'a list -> 'a list      Tl
val nth      : 'a list * int -> 'a      Nth
val nthtail  : 'a list * int -> 'a list NthTail
val app      : ('a -> 'b) -> 'a list -> unit
val revapp   : ('a -> 'b) -> 'a list -> unit
val fold     : ('a * 'b -> 'b) -> 'a list -> 'b -> 'b
val revfold  : ('a * 'b -> 'b) -> 'a list -> 'b -> 'b
```

NJ93 Real

```
val ceiling  : real -> int
val truncate : real -> int
```

NJ93 Ref

```
val inc      : int ref -> unit
val dec      : int ref -> unit
```

NJ93 String

exception Substring

```
val ordof    : string * int -> int
val ord      : string -> int
val chr      : int -> string
val substring : string * int * int -> string
val explode  : string -> string list
val implode  : string list -> string
```

NJ93 top-level math functions

```
val sqrt      : real -> real
val sin       : real -> real
val cos       : real -> real
val arctan    : real -> real
val exp       : real -> real
val ln        : real -> real
```

NJ93 top-level input/output, standard

type instream and ostream

```
val std_in    : instream
val open_in   : string -> instream
val input     : instream * int -> string
val lookahead : instream -> string
val close_in  : instream -> unit
val end_of_stream : instream -> bool
```

```
val std_out   : ostream
val open_out  : string -> ostream
val output    : ostream * string -> unit
val close_out : ostream -> unit
```

NJ93 top-level input/output, non-standard

```
val open_in_bin      : string -> instream
val open_out_bin     : string -> outstream
val inputc           : instream -> int -> string
val std_err         : outstream
val outputc          : outstream -> string -> unit
val flush_out       : outstream -> unit
val input_line      : instream -> string
val can_input       : instream * int -> bool
val open_append     : string -> outstream
```

Module Nonstdio

```
Nonstdio -- non-standard I/O -- use BinIO and TextIO instead

local open BasicIO in

val open_in_bin      : string -> instream
val buff_input       : instream -> CharArray.array -> int -> int -> int
val input_char       : instream -> char Raises Size
val input_binary_int : instream -> int
val input_value      : instream -> 'a
val seek_in          : instream -> int -> unit
val pos_in           : instream -> int
val in_stream_length : instream -> int
val fast_really_input : instream -> string -> int -> int -> unit

val open_out_bin     : string -> outstream
val open_out_exe     : string -> outstream
val output_char      : outstream -> Char.char -> unit
val output_byte      : outstream -> int -> unit
val buff_output      : outstream -> CharArray.array -> int -> int -> unit
val output_binary_int : outstream -> int -> unit
val output_value     : outstream -> 'a -> unit
val seek_out         : outstream -> int -> unit
val pos_out          : outstream -> int

val file_exists      : string -> bool

end
```

Module OS

```
OS -- SML Basis Library

signature OS = sig
  type syserror = syserror
  exception SysErr of string * syserror option
  val errorMsg      : syserror -> string
  structure FileSys : FileSys
  structure Path    : Path
  structure Process : Process
end
```

[errorMsg err] returns a string explaining the error message system error code err, as found in a SysErr exception. The precise form of the string depends on the operating system.

Module Option

```
Option -- SML Basis Library

exception Option

datatype option = datatype option

val getOpt      : 'a option * 'a -> 'a
val isSome     : 'a option -> bool
val valOf     : 'a option -> 'a
val filter    : ('a -> bool) -> 'a -> 'a option
val map       : ('a -> 'b) -> 'a option -> 'b option
val map2      : ('a -> 'b) * ('a -> 'c) -> 'a option -> 'b option
val map3      : ('a -> 'b) * ('c -> 'd) -> 'a option -> 'b option * 'd option
val mapPartial : ('a -> 'b option) * ('c -> 'd option) -> ('c -> 'b option) * ('d -> 'd option)
```

```
[getOpt (xopt, d)] returns x if xopt is SOME x; returns d otherwise.
[isSome vopt] returns true if xopt is SOME x; returns false otherwise.
[valOf vopt] returns x if xopt is SOME x; raises Option otherwise.
[filter p x] returns SOME x if p x is true; returns NONE otherwise.
[map f xopt] returns SOME (f x) if xopt is SOME x; returns NONE otherwise.
[app f xopt] applies f to x if xopt is SOME x; does nothing otherwise.
[join xopt] returns x if xopt is SOME x; returns NONE otherwise.
[compose (f, g) x] returns SOME (f y) if g x is SOME y; returns NONE otherwise. It holds that compose (f, g) = map f o g.
[mapPartial f xopt] returns f x if xopt is SOME x; returns NONE otherwise. It holds that mapPartial f = join o map f.
[composePartial (f, g) x] returns f y if g x is SOME y; returns NONE otherwise. It holds that composePartial (f, g) = mapPartial f o g.

The operators (map, join, SOME) form a monad.
```

Module PP

PP -- pretty-printing -- from the SML/NJ library

```
type ppconsumer = {
  consumer : string -> unit,
  linewidth : int,
  flush     : unit -> unit };
```

```
datatype break_style =
  CONSISTENT
| INCONSISTENT

val mk_ppstream      : ppconsumer -> ppstream
val dest_ppstream    : ppstream -> ppconsumer
val add_break        : ppstream -> int * int -> unit
val add_newline      : ppstream -> unit
val add_string       : ppstream -> string -> unit
val begin_block      : ppstream -> break_style -> int -> unit
val end_block        : ppstream -> unit
val clear_ppstream   : ppstream -> unit
val flush_ppstream   : ppstream -> unit
val with_pp          : ppconsumer -> (ppstream -> unit) -> unit
val pp_to_string     : int -> (ppstream -> 'a -> unit) -> 'a -> string
```

This structure provides tools for creating customized Openen-style pretty-printers, based on the type `ppstream`. A `ppstream` is an output stream that contains prettyprinting commands. The commands are placed in the stream by various function calls listed below.

There following primitives add commands to the stream: `begin_block`, `end_block`, `add_string`, `add_break`, and `add_newline`. All calls to `add_string`, `add_break`, and `add_newline` must happen between a pair of calls to `begin_block` and `end_block` must be properly nested dynamically. All calls to `begin_block` and `end_block` must be properly nested (dynamically).

`[ppconsumer]` is the type of sinks for pretty-printing. A value of type `ppconsumer` is a record

```
{ consumer : string -> unit,
  linewidth : int,
  flush    : unit -> unit }
```

of a string consumer, a specified linewidth, and a flush function which is called whenever `flush_ppstream` is called.

A prettyprinter can be called outright to print a value. In addition, a prettyprinter for a base type or nullary datatype `ty` can be installed in the top-level system. Then the installed prettyprinter will be invoked automatically whenever a value of type `ty` is to be printed.

`[break_style]` is the type of line break styles for blocks:

`[CONSISTENT]` specifies that if any line break occurs inside the block, then all indicated line breaks occur.

`[INCONSISTENT]` specifies that breaks will be inserted to only to avoid overfull lines.

`[mk_ppstream {consumer, linewidth, flush}]` creates a new `ppstream` which invokes the consumer to output text, putting at most `linewidth` characters on each line.

`[dest_ppstream ppstrm]` extracts the `linewidth`, `flush` function, and consumer from a `ppstream`.

`[add_break ppstrm (size, offset)]` notifies the pretty-printer that a line break is possible at this point.

* When the current block style is `CONSISTENT`:
** if the entire block fits on the remainder of the line, then output size spaces; else
** increase the current indentation by the block offset;

further indent every item of the block by offset, and add one newline at every `add_break` in the block.

* When the current block style is `INCONSISTENT`:
** if the next component of the block fits on the remainder of the line, then output size spaces; else
** issue a newline and indent to the current indentation level plus the block offset plus the offset.

`[add_newline ppstrm]` issues a newline.

`[add_string ppstrm str]` outputs the string `str` to the `ppstream`.

`[begin_block ppstrm style blockoffset]` begins a new block and level of indentation, with the given style and block offset.

`[end_block ppstrm]` closes the current block.

`[clear_ppstream ppstrm]` restarts the stream, without affecting the underlying consumer.

`[flush_ppstream ppstrm]` executes any remaining commands in the `ppstream` (that is, flushes currently accumulated output to the consumer associated with `ppstrm`); executes the flush function associated with the consumer; and calls `clear_ppstream`.

`[with_pp consumer f]` makes a new `ppstream` from the consumer and applies `f` (which can be thought of as a producer) to that `ppstream`, then flushed the `ppstream` and returns the value of `f`.

`[pp_to_string linewidth printit x]` constructs a new `ppstream` `ppstrm` whose consumer accumulates the output in a string `s`. Then evaluates (`printit ppstrm x`) and finally returns the string `s`.

Example 1: A simple prettyprinter for Booleans:

```
load "PP";
fun ppbool pps d =
  let open PP
  in
    begin_block pps INCONSISTENT 6;
    add_string pps (if d then "right" else "wrong");
    end_block pps
  end;
```

Now one may define a `ppstream` to print to, and exercise it:

```
val ppstrm = PP.mk_ppstream {consumer =
  fn s => TextIO.output(TextIO.stdOut, s),
  linewidth = 72,
  flush     =
    fn () => TextIO.flushOut TextIO.stdOut};
```

```
fun ppb b = (ppbool ppstrm b; PP.flush_ppstream ppstrm);

- ppb false;
wrong> val it = () : unit
```

The prettyprinter may also be installed in the toplevel system; then it will be used to print all expressions of type `bool` subsequently computed:

```
- installPP ppbool;
> val it = () : unit
- 1=0;
> val it = wrong : bool
- 1=1;
> val it = right : bool
```

See library `Meta` for a description of `installPP`.

Example 2: Prettyprinting simple expressions (examples/pretty/ppexpr.sml):

```
datatype expr =
  Cst of int
| Neg of expr
| Plus of expr * expr

fun ppexpr pps e0 =
  let open pp
  in fun ppe (Cst i)
      = add_string pps (Int.toString i)
      | ppe (Neg e)
      = (add_string pps "~"; ppe e)
      | ppe (Plus(e1, e2)) = (begin_block pps CONSISTENT 0;
                             ppe (Plus(e1, e2));
                             add_string pps "(";
                             ppe e1;
                             add_string pps " + ";
                             add_break pps (0, 1);
                             ppe e2;
                             add_string pps ")";
                             end_block pps)
  in begin_block pps INCONSISTENT 0;
      ppe e0;
      end_block pps
  end

val _ = installPP ppexpr;

Some example values:

val e1 = Cst 1;
val e2 = Cst 2;
val e3 = Plus(e1, Neg e2);
val e4 = Plus(Neg e3, e3);
val e5 = Plus(Neg e4, e4);
val e6 = Plus(e5, e5);
val e7 = Plus(e6, e6);
val e8 =
  Plus(e3, Plus(e3, Plus(e3, Plus(e3, Plus(e3, e7)))))
```

Parsing -- runtime library for parsers generated by mosmlyac
Based on the runtime library for camlyacc; copyright 1993 INRIA, France

Module Parsing

local open Vector Obj Lexing in

```
val symbolStart : unit -> int
val symbolEnd   : unit -> int
val itemStart   : int -> int
val itemEnd     : int -> int
val clearParser : unit -> unit
```

For internal use in generated parsers:

```
type parseTables =
  actions (unit -> obj) vector *
  transl  int vector *
  lhs     string *
  len     string *
  defred  string *
  dgoto   string *
  sindex  string *
  rindex  string *
  gindex  string *
  tablesize int *
  table   string *
  check   string
```

```
exception Yyexit of obj
exception ParseError of (obj -> bool)
```

```
val yyparse : parseTables -> int -> (lexbuf -> 'a) -> lexbuf -> 'b
val peekVal : int -> 'a
end
```

These functions are for use in mosmlyac-generated parsers. For further information, see the Moscow ML Owner's Manual. For examples, see mosml/examples/lexyacc and mosml/examples/calc.

A grammar definition (input to mosmlyac) consists of fragments of this form

```
nonterm :
  grsyms1 { action1 }
  | grsyms2 { action2 }
  | grsyms3 { action3 }
  ...
```

where the grsyms are sequences of grammar symbols, matching some string of characters, and the actions are corresponding semantic actions, written in ML. The following functions can be used in the semantic actions:

[symbolStart ()] returns the start position of the string that matches the sequence of grammar symbols. The first character in the input stream has position 0. May be called in a semantic action only.

[symbolEnd ()] returns the end position, plus one, of the string that matches the sequence of grammar symbols. The first character in the input stream has position 0. May be called in a semantic action only.

[itemStart i] returns the start position of the string that matches the i'th grammar symbol in the sequence. The first grammar symbol has number 1. The first character in the input stream has position 0. May be called in a semantic action only.

[itemEnd i] returns the end position, plus one, of the string that matches the i'th grammar symbol in the sequence. The first grammar symbols has number 1. The first character in the input stream has position 0. May be called in a semantic action only.

[clearParser ()] clears the parser stack. It may be called after a parsing function has returned, to remove all pointers from the parser stack to structures that were built by semantic actions during parsing. This is not strict necessary, but reduces the memory requirements of the program.

Module Path

OS.Path -- SML Basis Library

exception Path

```
val parentArc      : string
val currentArc     : string
val fromString     : string -> {isAbs : bool, vol : string, arcs : string list}
val toString       : {isAbs : bool, vol : string, arcs : string list} -> string
val getVolume      : string -> string
val validVolume    : {isAbs : bool, vol : string} -> bool
val getParent      : string -> string
val isAbsolute     : string -> bool
val isRelative     : string -> bool
val mkAbsolute     : { path : string, relativeTo : string } -> string
val mkRelative     : { path : string, relativeTo : string } -> string
val concat         : string * string -> string
val mkCanonical    : string -> string
val isCanonical    : string -> bool
val splitDirFile   : string -> {dir : string, file : string}
val joinDirFile    : {dir : string, file : string} -> string
val dir            : string -> string
val file           : string -> string
val splitBaseExt   : string -> {base : string, ext : string option}
val joinBaseExt    : {base : string, ext : string option} -> string
val base           : string -> string
val ext            : string -> string option
```

This module provides OS-independent functions for manipulating strings that represent file names and paths in a directory structure. None of these functions accesses the actual filesystem.

Definitions:

- * An arc denotes a directory or file. Under Unix or DOS, an arc may have form "...", ".", "", or "abc", or similar.
- * An absolute path has a root: Unix examples include "/", "/a/b"; DOS examples include "\", "\a\b", "A:\a\b".
- * A relative path is one without a root: Unix examples include "...", "a/b"; DOS examples include "..", "a\b", "A\b".
- * A path has an associated volume. Under Unix, there is only one volume, whose name is ".". Under DOS, the volume names are "A:", "B:", "C:", and similar.
- * A canonical path contains no occurrences of the empty arc "" or the current arc ".", and contains or the parent arc ".." only at the beginning and only if the path is relative.
- * All functions (except concat) preserve canonical paths. That is, if all arguments are canonical, then so will the result be.
- * All functions are defined so that they work sensibly on canonical paths.
- * There are three groups of functions, corresponding to three ways to look at paths, exemplified by the following paths:

Unix: d/e/f/a.b.c and d/e/f/a.b.c

DOS: A:d\e\f\a.b.c and A:d\e\f\a.b.c

- (1) A path consists of a sequence of arcs, possibly preceded by a volume and a root:

```

-----
vol [--- arcs ---]    vol root [--- arcs ---]
Unix examples:      d e f a.b.c      / d e f a.b.c
DOS examples:      A: d e f a.b      A: \ d e f a.b

```

- (2) A path consists of a directory part and a (last) file name part:

```

-----
directory file      directory file
Unix examples:      d/e/f a.b.c      /d/e/f a.b.c
DOS examples:      A:\e\f a.b      A:\d\e\f a.b

```

- (3) A path consists of a base and an extension:

```

-----
base      extension      base      extension
Unix examples:      d/e/f/a.b      c      /d/e/f/a.b      c
DOS examples:      A:\d\e\f\a      b      A:\d\e\f\a      b

```

GROUP 0: General functions on paths:

[parentArc] is the arc denoting a parent directory: "." under DOS and Unix.

[currentArc] is the arc denoting the current directory: "." under DOS and Unix.

[isRelative p] returns true if p is a relative path.

[isAbsolute p] returns true if p is an absolute path.
Equals not (isRelative p).

[validVolume {isAbs, vol}] returns true if vol is a valid volume name for an absolute path (if isAbs=true) resp. for a relative path (if isAbs=false). Under Unix, the only valid volume name is "" ; under MS DOS and MS Windows the valid volume names are "", "a:", "b:", ..., and "A:", "B:", ...

[getParent p] returns a string denoting the parent directory of p. It holds that getParent p = p if and only if p is a root.

[concat (p1, p2)] returns the path consisting of p1 followed by p2. Does not preserve canonical paths: concat("a/b", "../c") equals "a/b/./c". This is because "a/b/./c" and "a/c" may not be equivalent in the presence of symbolic links. Raises Path if p2 is not a relative path.

[mkAbsolute { path=p1, relativeTo=p2 }] returns the absolute path made by taking path p2, then p1. That is, returns p1 if p1 is absolute; otherwise returns the canonicalized concatenation of p2 and p1. Raises Path if p2 is not absolute (even if p1 is absolute).

[mkRelative { path=p1, relativeTo=p2 }] returns p1 relative to p2. That is, returns p1 if p1 is already relative; otherwise returns the relative path leading from p2 to p1. Raises Path if p2 is not absolute (and even if p1 is relative), or if p1 and p2 are both absolute but have different roots.

[mkCanonical p] returns a canonical path which is equivalent to p. Redundant occurrences of the parent arc, the current arc, and the empty arc are removed. The canonical path will never be the empty string; the empty path is converted to the current directory path ("." under Unix and DOS).

[isCanonical p] is equal to (p = mkCanonical p).

GROUP 1: Manipulating volumes and arcs:

[fromString p] returns {isAbs=false, vol, arcs} if the path p is relative, and {isAbs=true, vol, arcs} if the path p is absolute. In both cases vol is the volume name and arcs is the list of (possibly empty) arcs of the path. Under Unix, the volume name is always the empty string "", under DOS it will have form "A:", "C:", or similar.

[toString path] reconstitutes a path from its root (if any) and arcs. Raises Path if applied to a relative path whose first arc is empty. It holds that toString(fromString p) = p, except that in MS DOS slashes "/" in p will be replaced by backslashes "\". It holds that fromString (toString p) = p when no exception is raised. It holds that isRelative(toString {isAbs=false, vol, arcs}) = true when no exception is raised.

[getVolume p] returns the volume name of the path p, if given. Under Unix and MacOS, this is always the empty string "", and under MS DOS and MS Windows, it may have form "A:", "B:", ...

GROUP 2: Manipulating directory paths and file names:

[splitDirFile p] returns {dir, file} where file is the last arc in p, and dir is the path preceding that arc. A typical use is to split a path into the directory part (dir) and the filename (file).

[joinDirFile (dir, file)] returns the path p obtained by extending the path dir with the arc file.

[dir p] equals #dir (splitDirFile p).

[file p] equals #file (splitDirFile p).

GROUP 3: Manipulating file names and extensions:

[splitBaseExt s] returns {base, ext} where ext = NONE if s has no extension, and ext = SOME e if s has extension e; base is the part of s preceding the extension. A path s is considered having no extension if its last arc contains no extension separator (typically ".") or contains an extension separator only as its leftmost character, or contains an extension separator as its rightmost character. Hence none of "a.b/cd", "a/.login", "a.", "...", ".", and "." has an extension.

[joinBaseExt {base, ext}] returns an arc composed of the base name and the extension (if different from NONE). It is a left inverse of splitBaseExt, so joinBaseExt (splitBaseExt s) = s, but the opposite does not hold (since the extension may be empty, or may contain extension separators).

[ext s] equals #ext (splitBaseExt s).

[base s] equals #base (splitBaseExt s).

Module Polygbm

Polygbm -- GNU gdbm persistent polymorphic hashtablees -- requires Dynlib

type ('key, 'data) table

exception NotFound
exception AlreadyThere
exception NotWriter
exception Closed
exception GdbmError of string

```
val withtable      : string * Gdbm.openmode -> (('key, 'data) table -> 'a) -> 'a  
val add            : ('key, 'data) table -> 'key * 'data -> unit  
val insert         : ('key, 'data) table -> 'key * 'data -> unit  
val find           : ('key, 'data) table -> 'key -> 'data  
val peek           : ('key, 'data) table -> 'key -> 'data option  
val haskey         : ('key, 'data) table -> 'key -> bool  
val remove         : ('key, 'data) table -> 'key -> unit  
val listkeys       : ('key, 'data) table -> 'key list  
val numitems       : ('key, 'data) table -> int  
val listitems      : ('key, 'data) table -> ('key * 'data) list  
val app            : ('key * 'data -> unit) -> ('key, 'data) table -> unit  
val map            : ('key * 'data -> 'a) -> ('key, 'data) table -> 'a list  
val fold           : ('key * 'data * 'a -> 'a) -> 'a -> ('key, 'data) table -> 'a  
val fastwrite      : bool ref  
val reorganize     : ('key, 'data) table -> unit
```

[('key, 'data) table] is the type of an opened table with keys of type 'key and associated values of type 'data. The actual values of type 'key and 'data cannot contain function closures or abstract values. Values involving references (even circular values) can be stored, but the identity of references is preserved only with every single key or value stored, not across several different values.

The Polygbm table files of are not portable across platforms, because word size and endianness affects the lay-out of values.

A value of type table can be used only in the argument f to the withtable function. This makes sure that the table is closed after use.

[withtable (nam, mod) f] first opens the table db in file nam with mode mod, then applies f to db, then closes db. Makes sure to close db even if an exception is raised during the evaluation of f(db). Raises GdbmError with an informative message in case the table cannot be opened. E.g. the table cannot be opened for reading if already opened for writing, and cannot be opened for writing if already opened for reading.

[add db (k,v)] adds the pair (k, v) to db. Raises AlreadyThere if there is a pair (k, _) in db already. Raises NotWriter if db is not opened in write mode.

[insert db (k, v)] adds the pair (k, v) to db, replacing any pair (k, _) at k if present. Raises NotWriter if db is not opened in write mode.

[find(db, k)] returns v if the pair (k, v) is in db; otherwise raises NotFound.

[peek db k] returns SOME v if the pair (k, v) is in db; otherwise returns NONE.

[haskey(db, k)] returns true if there is a pair (k, _) in db; otherwise returns false.

[remove db k] deletes the pair (k, _) from the table if present; otherwise raises NotFound. Raises NotWriter if db is not opened in write mode.

[listKeys db] returns a list of all keys in db in an unspecified order.

[numItems db] is the number of (key, value) pairs in db. Equivalent to length(listKeys db).

[listItems db] returns a list of all (key, value) pairs in db in some order. Equivalent to

List.map (fn key => (key, find(db,key))) (listKeys db)

[app f db] is equivalent to list.app f (listItems db), provided the function f does not change the set of keys in the table. Otherwise the effect is unpredictable.

[map f db] is equivalent to list.map f (listItems db), provided the function f does not change the set of keys in the table. Otherwise the result and effect are unpredictable.

[fold f a db] is equivalent to List.foldr (fn ((k, v), r) => f(k, v, r)) a (listItems db) provided the function f does not change the set of keys in the table. Otherwise the result and effect are unpredictable.

[fastwrite] can be set to speed up writes to a table. By default, if fastwrite is false and every write to a table will be followed by file system synchronization. This is safe, but slow if you perform thousands of writes. However, if !fastwrite is true when calling withtable, then writes may not be followed by synchronization, which may speed up writes considerably. In any case, the file system is synchronized before withtable returns.

[reorganize db] has no visible effect, but may be called after a lot of deletions to shrink the size of the table file.

Module Polyhash

Polyhash -- polymorphic hashtables as in the SML/NJ Library

```

type ('key, 'data) hash_table

val mkTable      : ('key -> int) * ('key * 'key -> bool) -> int * exn
                  -> ('key, 'data) hash_table
val numItems     : ('key, 'data) hash_table -> int
val insert       : ('key, 'data) hash_table -> 'key * 'data -> unit
val peekInsert   : ('key, 'data) hash_table -> 'key * 'data
                  -> 'data option
val find         : ('key, 'data) hash_table -> 'key -> 'data
val peek         : ('key, 'data) hash_table -> 'key -> 'data option
val remove       : ('key, 'data) hash_table -> 'key -> 'data
val listItems    : ('key, 'data) hash_table -> ('key * 'data) list
val apply        : ('key * 'data -> unit) -> ('key, 'data) hash_table -> unit
val map          : ('key * 'data -> 'res) -> ('key, 'data) hash_table
                  -> ('key, 'res) hash_table
val filter       : ('key * 'data -> bool) -> ('key, 'data) hash_table -> unit
val transform    : ('data -> 'res) -> ('key, 'data) hash_table
                  -> ('key, 'res) hash_table
val copy         : ('key, 'data) hash_table -> ('key, 'data) hash_table
val bucketSizes : ('key, 'data) hash_table -> int list

Polymorphic hash primitives from Caml Light

val hash        : 'key -> int
val hash_param  : int -> int -> 'key -> int
val mkPolyTable : int * exn -> ('key, 'data) hash_table

```

`[('key, 'data) hash_table]` is the type of hashtables with keys of type 'key and data values of type 'data.

`[mkTable (hashVal, sameKey) (sz, exc)]` returns a new hashtable, using hash function hashVal and equality predicate sameKey. The sz is a size hint, and exc is the exception raised by function find. It must be the case that sameKey(k1, k2) implies hashVal(k1) = hashVal(k2) for all k1,k2.

`[numItems htbl]` is the number of items in the hash table.

`[insert htbl (k, d)]` inserts data d for key k. If k already had an item associated with it, then the old item is overwritten.

`[find htbl k]` returns d, where d is the data item associated with key k, or raises the exception (given at creation of htbl) if there is no such d.

`[peek htbl k]` returns SOME d, where d is the data item associated with key k, or NONE if there is no such d.

`[peekInsert htbl (k, d)]` inserts data d for key k, if k is not already in the table, returning NONE. If k is already in the table, and the associated data value is d', then returns SOME d' and leaves the table unmodified.

`[remove htbl k]` returns d, where d is the data item associated with key k, removing d from the table; or raises the exception if there is no such d.

`[listItems htbl]` returns a list of the (key, data) pairs in the hashtable.

`[apply f htbl]` applies function f to all (key, data) pairs in the hashtable, in some order.

`[map f htbl]` returns a new hashtable, whose data items have been obtained by applying f to the (key, data) pairs in htbl. The new tables have the same keys, hash function, equality predicate, and exception, as htbl.

`[filter p htbl]` deletes from htbl all data items which do not satisfy predicate p.

`[transform f htbl]` as map, but only the (old) data values are used when computing the new data values.

`[copy htbl]` returns a complete copy of htbl.

`[bucketSizes htbl]` returns a list of the sizes of the buckets. This is to allow users to gauge the quality of their hashing function.

`[hash k]` returns the hash value of k, as a positive integer. If k1=k2 then hash(k1) = hash(k2), so this function can be used when creating hashtables. The application hash(k) always terminates, even on cyclic structures. (From the Caml Light implementation).

`[hash_param n m k]` computes a hash value for k with the same properties as for hash. The parameters n and m give more precise control over hashing. Hashing performs a depth-first, right-to-left traversal of the structure k, stopping after n meaningful nodes were encountered, or m nodes, meaningful or not, were encountered. Meaningful nodes are: integers, floating-point numbers, strings, characters, booleans, references, and constant constructors.

`[mkPolyTable (sz, exc)]` creates a new hashtable using the polymorphic hash function (hash) and ML equality (op =); the integer sz is a size hint and the exception exc is to be raised by find.


```
[tty dbconn] returns the name of the tty used for logging.

[status dbconn] returns true if the connection is usable, false otherwise.

[reset dbconn] attempts to close and then reopen the connection to the database server.

[errormessage dbconn] returns NONE if no error occurred, and SOME msg if an error occurred, where msg describes the error.

[execute dbconn query] sends an SQL query to the database server for execution, and returns a resultset dbres.

[resultstatus dbres] returns the status of the result set dbres. After a select query that succeeded, it will be Tuples_ok.

[n tuples dbres] returns the number of tuples in the result set after a query.

[cmdtuples dbres] returns the number of tuples affected by an insert, update, or delete SQL command.

[n fields dbres] returns the number of fields in each tuple after a query.

[name dbres fno] returns the name of field number fno (in the result set after a query). The fields are numbered 0, 1,...

[names dbres] returns a vector of the field names (in the result set after a query).

[number dbres fname] returns SOME i where i is the number (0, 1,...) of the field called fname (in the result set after a query). If the result set contains such a field name; returns NONE otherwise.

[f type dbres fno] returns the dyntype of field number fno (in the result set after a query).

[f types dbres] returns a vector of the dyntypes (in the result set after a query).

[frontag dt] returns the name of the preferred PostgreSQL type used to represent values of the dyntype dt. This may be used when building 'create table' statements.

[getint dbres fno tupno] returns the integer value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL.

[getreal dbres fno tupno] returns the floating-point value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL.

[getstring dbres fno tupno] returns the string value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL.

[getdate dbres fno tupno] returns the date (yyyy, mth, day) value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL. Raises Fail if the field cannot be scanned as a date.

[gettime dbres fno tupno] returns the time-of-day (hh, mm, ss) value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL. Raises Fail if the field cannot be scanned as a time.

[getdatetime dbres fno tupno] returns the Date.date value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL. Raises Fail if the field cannot be scanned as a
```

```
date.

[getbool dbres fno tupno] returns the boolean value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL.

[isnull dbres fno tupno] returns true if the value of field number fno in tuple tupno of result set dbres is NULL; false otherwise.

[getdynfield dbres fno tupno] returns the value of field number fno in tuple tupno of result set dbres as a dynval (a wrapped value). A NULL value is returned as Nullval. Note that the partial application (getdynfield dbres fno) precomputes the type of the field fno. Hence it is far more efficient to compute
    let val getfno = getdynfield dbres fno
in tabulate(ntuples dbres, getfno) end
than to compute
    let fun getfno tupno = getdynfield dbres fno tupno
in tabulate(ntuples dbres, getfno) end
because the latter repeatedly computes the type of the field.

[getdyntup dbres tupno] returns the fields of tuple tupno in result set dbres as a vector of dynvals.

[getdyntups dbres] returns all tuples of result set dbres as a vector of vectors of dynvals.

[dynvals2s div] returns a string representing the dynval div.

[applyto x f] computes f(x). This is convenient for applying several functions (given in a list or vector) to the same value:
    map (applyto 5) (tabulate(3, getdynfield dbres))
equals
    [getdynfield dbres 0 5, getdynfield dbres 1 5, getdynfield dbres 2 5]

[copytableto(dbconn, tablename, put)] executes a "COPY TABLE TO" statement, applies the function put to every tuple of the table, represented as a line of text (not terminated by newline \n), and cleans up at the end. For instance, to copy the contents of a table t to a text stream s (one tuple on each line), define
    fun put line =
      (TextIO.output(s, line); TextIO.output(s, "\n"))
and execute
    copytableto(dbconn, "t", put).

[copytablefrom(dbconn, tablename, useput)] executes a "COPY TABLE FROM" statement, creates a put function for copying lines to the table, passes the put function to useput, and cleans up at the end. The put function may be called multiple times for each line (tuple); the end of each line is indicated with the newline character "\n" as usual. For instance, to copy the contents of a text stream s to a table t, define
    fun useput put =
      while not (TextIO.endOfStream s) do put(TextIO.inputLine s);
and execute
    copytablefrom(dbconn, "t", useput).
Note that TextIO.inputLine preserves the newline at the end of each line.

[formattable dbresult] returns a wseq representing an HTML table. The HTML table has a column for every field in the dbresult. The first row is a table header giving the names of the fields in the dbresult. The remaining rows correspond to the tuples in the dbresult, in the order they are provided by the database server. Null fields are shown as NULL.

[showquery dbconn query] sends the SQL query to the database server, then uses formattable to format the result of the query.
```

Module Process

```
OS.Process -- SML Basis Library

type status
val success      : status
val failure      : status
val isSuccess    : status -> bool
val system       : string -> status
val atExit       : (unit -> unit) -> unit
val exit         : status -> 'a
val terminate    : status -> 'a
val sleep        : Time.time -> unit
val getEnv       : string -> string option
```

Portable functions for manipulating processes.

[success] is the unique status value that signifies successful termination of a process. Note: MS DOS (sometimes) believes that all processes are successful.

[failure] is a status value that signifies an error during execution of a process. Note that in contrast to the success value, there may be several distinct failure values. Use function isSuccess to reliably test for success.

[isSuccess sv] returns true if the status value sv represents a successful execution, false otherwise. It holds that isSuccess success = true and isSuccess failure = false.

[system cmd] asks the operating system to execute command cmd, and returns a status value.

[atExit act] registers the action act to be executed when the current SML program calls Process.exit. Actions will be executed in reverse order of registration.

[exit i] executes all registered actions, then terminates the SML process with completion code i.

[terminate i] terminates the SML process with completion code i (but without executing the registered actions).

[sleep t] suspends this process for approximately the time indicated by t. The actual time slept depends on the capabilities of the underlying system and the system load. Does not sleep at all if t <= Time.zeroTime.

[getEnv evar] returns SOME s if the environment variable evar is defined and is associated with the string s; otherwise NONE.

Module Random

```
Random -- random number generator

type generator
val newGenSeed   : real -> generator
val newGen       : unit -> generator
val random       : generator -> real
val randomList   : int * generator -> real list
val range        : int * int -> generator -> int
val rangeList    : int * int -> int * generator -> int list
```

[generator] is the type of random number generators, here the linear congruential generators from Paulson 1991, 1996.

[newGenSeed seed] returns a random number generator with the given seed.

[newGen ()] returns a random number generator, taking the seed from the system clock.

[random gen] returns a random number in the interval [0..1).

[randomList (n, gen)] returns a list of n random numbers in the interval [0,1).

[range (min, max) gen] returns an integral random number in the range [min, max). Raises Fail if min > max.

[rangeList (min, max) (n, gen)] returns a list of n integral random numbers in the range [min, max). Raises Fail if min > max.

Module Real

Real -- SML Basis Library

type real = real

exception Div
and Overflow

val ~
val +
val -
val *
val /
val abs
val min
val max
val sign
val compare

val sameSign
val toDefault
val fromDefault
val fromInt

val floor
val ceil
val trunc
val round

val >
val >=
val <
val <=
val ==
val !=
val ?=

val toString
val fromString
val scan
val fmt

[~]
[*]
[/]
[+]
[-]
[>
[>=]
[<
[<=]

[abs x] is x if x >= 0, and ~x if x < 0, that is, the absolute value of x.

[min(x, y)] is the smaller of x and y.

[max(x, y)] is the larger of x and y.

[sign x] is ~1, 0, or 1, according as x is negative, zero, or positive.

[compare(x, y)] returns LESS, EQUAL, or GREATER, according as x is less than, equal to, or greater than y.

[sameSign(x, y)] is true iff sign x = sign y.

[toDefault x] is x.

[fromDefault x] is x.

[fromInt i] is the floating-point number representing integer i.

[floor r] is the largest integer <= r (rounds towards minus infinity). May raise Overflow.

[ceil r] is the smallest integer >= r (rounds towards plus infinity). May raise Overflow.

[trunc r] is the numerically largest integer between r and zero (rounds towards zero). May raise Overflow.

[round r] is the integer nearest to r, using the default rounding mode. May raise Overflow.

[==(x, y)] is equivalent to x=y in Moscow ML (because of the absence of NaNs and Infs).

[!=(x, y)] is equivalent to x<y in Moscow ML (because of the absence of NaNs and Infs).

[?=(x, y)] is false in Moscow ML (because of the absence of NaNs and Infs).

[fmt spec r] returns a string representing r, in the format specified by spec (see below). The requested number of digits must be >= 0 in the SCI and FIX formats and > 0 in the GEN format; otherwise Size is raised, even in a partial application fmt(spec).

| spec | description | C printf |
|--------------|------------------------------------|----------|
| SCI NONE | scientific, 6 digits after point | %e |
| SCI (SOME n) | scientific, n digits after point | %ne |
| FIX NONE | fixed-point, 6 digits after point | %f |
| FIX (SOME n) | fixed-point, n digits after point | %nf |
| GEN NONE | auto choice, 12 significant digits | %12g |
| GEN (SOME n) | auto choice, n significant digits | %ng |

[toString r] returns a string representing r, with automatic choice of format according to the magnitude of r. Equivalent to (fmt (GEN NONE) r).

[fromString s] returns SOME(r) if a floating-point numeral can be scanned from a prefix of string s, ignoring any initial whitespace; returns NONE otherwise. The valid forms of floating-point numerals are described by:

[+-~]?([0-9]+(\.[0-9]+)?|(\.[0-9]+))([eE][+-~]?[0-9]+)?

[scan getc charsrc] attempts to scan a floating-point number from the character source charsrc, using the accessor getc, and ignoring any initial whitespace. If successful, it returns SOME(r, rest) where r is the number scanned, and rest is the unused part of the character source. The valid forms of floating-point numerals are described by:

[+-~]?([0-9]+(\.[0-9]+)?|(\.[0-9]+))([eE][+-~]?[0-9]+)?

Module Regex

Regex -- regular expressions a la POSIX 1003.2 -- requires Dynlib

exception Regex of string

type regex

A compiled regular expression

datatype cflag =

- Extended
 - Icase
 - Newline
- Compile POSIX extended REs
Compile case-insensitive match
Treat \n in target string as new line

datatype eflag =

- Notbol
 - Noteol
- Do not match ^ at beginning of string
Do not match \$ at end of string

val regcomp : string -> cflag list -> regex

val regexec : regex -> eflag list -> string -> substring vector option

val regexecBool : regex -> eflag list -> string -> bool

val regnexec : regex -> eflag list -> substring

-> substring vector option

val regnexecBool : regex -> eflag list -> substring -> bool

val regmatch : { pat : string, tgt : string } -> cflag list

-> eflag list -> bool

datatype replacer =

- Str of string
 - Sus of int
 - Tr of (string -> string) * int
 - Trs of substring vector -> string
- A literal string
The i'th parenthesized group
Transformation of i'th group
Transformation of all groups

val replacel : regex -> replacer list -> string -> string

val replace : regex -> replacer list -> string -> string

val substitute1 : regex -> (string -> string) -> string -> string

val substitute : regex -> (string -> string) -> string -> string

val tokens : regex -> string -> substring list

val fields : regex -> string -> substring list

val map : regex -> (substring vector -> 'a) -> string -> 'a list

val app : regex -> (substring vector -> unit) -> string -> unit

val fold : regex -> (substring 'a -> 'a) * (substring vector * 'a -> 'a)
-> 'a -> string -> 'a

This structure provides pattern matching with POSIX 1003.2 regular expressions.

The form and meaning of Extended and Basic regular expressions are described below. Here R and S denote regular expressions; m and n denote natural numbers; L denotes a character list; and d denotes a decimal digit:

| Extended | Basic | Meaning |
|----------|-------|-----------------------------|
| c | c | Match the character c |
| . | . | Match any character |
| R* | R* | Match R zero or more times |
| R+ | R+ | Match R one or more times |
| R S | R S | Match R or S |
| R? | R? | Match R or the empty string |
| R{m} | R{m} | Match R exactly m times |
| R{m,} | R{m,} | Match R at least m times |

| | | |
|--------|--------|--|
| R{m,n} | R{m,n} | Match R at least m and at most n times |
| [L] | [L] | Match any character in L |
| [^L] | [^L] | Match any character not in L |
| ^ | ^ | Match at string's beginning |
| \$ | \$ | Match at string's end |
| \(R\) | \(R\) | Match R as a group; save the match |
| \d | \d | Match the same as previous group d |
| \\ | \\ | Match \ --- similarly for *,{,^,\$ |
| + | + | Match + --- similarly for ,{}() |

Some example character lists L:

| | |
|------------------|---|
| [aeiou] | Match vowel: a or e or i or o or u |
| [0-9] | Match digit: 0 or 1 or 2 or ... or 9 |
| [^0-9] | Match non-digit |
| [~*/*^] | Match - or + or * or / or ^ |
| [^a-z] | Match lowercase letter or hyphen (-) |
| [0-9a-fA-F] | Match hexadecimal digit |
| [[[:alnum:]]] | Match letter or digit |
| [[[:alpha:]]] | Match letter |
| [[[:cntrl:]]] | Match ASCII control character |
| [[[:digit:]]] | Match decimal digit; same as [0-9] |
| [[[:graph:]]] | Same as [:print:] but not [:space:] |
| [[[:lower:]]] | Match lowercase letter |
| [[[:print:]]] | Match printable character |
| [[[:punct:]]] | Match punctuation character |
| [[[:space:]]] | Match SML #", #"\r", #"\n", #"\t", #"\v", #"\f" |
| [[[:upper:]]] | Match uppercase letter |
| [[[:xdigit:]]] | Match hexadecimal digit; same as [0-9a-fA-F] |
| [[[:lower:]]æøä] | Match lowercase Danish letters (ISO Latin 1) |

Remember that backslash (\) must be escaped as "\\" in SML strings.

[regcomp pat cflags] returns a compiled representation of the regular expression pat. Raises Regex in case of failure.

[cflag] is the type of compilation flags with the following meanings:

[Extended] : compile as POSIX extended regular expression.

[Icase] : compile case-insensitive match.

[Newline] : make the newline character \n significant, so ^ matches just after newline (\n), and \$ matches just before \n.

Example: Match SML integer constant:

regcomp "~?[0-9]+\$" [Extended]

Example: Match SML alphanumeric identifier:

regcomp "~^[a-zA-Z0-9][a-zA-Z0-9_]*\$" [Extended]

Example: Match SML floating-point constant:

regcomp "~[+-]?[0-9]+((\.[0-9]+)?[eE][+-]?[0-9]+)?\$" [Extended]

Example: Match any HTML start tag; make the tag's name into a group:

regcomp "<([[:alnum:]]+)[^>]*>" [Extended]

[regexec regex eflags s] returns SOME(vec) if some substring of s matches regex, NONE otherwise. In case of success, vec is the match vector, a vector of substrings such that vec[0] is the (longest leftmost) substring of s matching regex, and vec[1], vec[2], ... are substrings matching the parenthesized groups in pat (numbered 1, 2, ... from left to right in the order of their opening parentheses). For a group that does not take part in the match, such as (ab) in "(ab)(cd)" when matched against the string "xcdy", the corresponding substring is the empty substring at the beginning of the underlying string. For a group that takes part in the match repeatedly, such as the group (b+) in "(a(b+))*" when matched against "babbbbbb", the corresponding substring is the last (rightmost) one matched.

[eflag] is the type of end flags with the following meaning:

[Notbol] : do not match ^ at beginning of string.

[Noteol] : do not match \$ at end of string.

[regexecBool regex eflags s] returns true if some substring of *s* matches *regex*, false otherwise. Equivalent to, but faster than, *Option.isSome(regexec regexec eflags s)*.

[regnexec regex eflags sus] returns *SOME(vec)* if some substring of *sus* matches *regex*, *NONE* otherwise. The substrings returned in the vector *vec* will have the same base string as *sus*. Useful e.g. for splitting a string into fragments separated by substrings matching some regular expression.

[regnexecBool regex eflags sus] returns true if some substring of *sus* matches *regex*, false otherwise. Equivalent to, but faster than, *Option.isSome(regnexec regexec eflags sus)*.

[regmatch { pat, tgt } cflags eflags] is equivalent to *regexec (regcomp pat cflags) eflags tgt* but more efficient when the compiled *regex* is used only once.

[regmatchBool { pat, tgt } cflags eflags] is equivalent to *regexecBool (regcomp pat cflags) eflags tgt* but more efficient when the compiled *regex* is used only once.

[replace regex repl s] finds the (disjoint) substrings of *s* matching *regex* from left to right, and returns the string obtained from *s* by applying the replacer list *repl* to every such substring (see below). Raises *Regex* if it fails to make progress in decomposing *s*, that is, if *regex* matches an empty string at the head of *s* or immediately after a previous *regex* match. Example use: delete all HTML tags from *s*:

```
replace (regcomp "<[^>]*>") [] s
```

[replacel regex repl s] finds the leftmost substring *bl* of *s* matching *regex*, and returns the string resulting from *s* by applying the replacer list *repl* to the match vector *vecl* (see below).

Let *x0* be a substring matching the entire *regex* and *xi* be the substring matching the *i*'th parenthesized group in *regex*; thus *xi* = *vec[i]* where *vec* is the match vector (see *regexec* above). Then a single replacer evaluates to a string as follows:

```
[Str s]      gives the string s
[Sub i]      gives the string xi
[Tr (f, i)]  gives the string f(xi)
[Trs f]      gives the string f(vec)
```

A replacer list *repl* evaluates to the concatenation of the results of the replacers. The replacers are applied from left to right.

[substitute regex f s] finds the (disjoint) substrings *bl*, ..., *bn* of *s* matching *regex* from left to right, and returns the string obtained from *s* by replacing every *bi* by *f(bi)*. Function *f* is applied to the matching substrings from left to right. Raises *Regex* if it fails to make progress in decomposing *s*. Equivalent to *replace regex [Tr (f, 0)] s*

[substitutel regex f s] finds the leftmost substring *b* of *s* matching *regex*, and returns the string obtained from *s* by replacing that substring by *f(b)*. Equivalent to *replacel regex [Tr (f, 0)] s*

[map regex f s] finds the (disjoint) substrings of *s* matching *regex* from left to right, applies *f* to the match vectors *vecl*, ..., *vecn*, and returns the list *[f(vecl), ..., f(vecn)]*. Raises *Regex* if it fails to make progress in decomposing *s*.

[app regex f s] finds the (disjoint) substrings of *s* matching *regex* from left to right, and applies *f* to the match vectors *vecl*, ..., *vecn*. Raises *Regex* if the *regex* fails to make progress in decomposing *s*.

[fields regex s] returns the list of fields in *s*, from left to right. A field is a (possibly empty) maximal substring of *s* not containing any delimiter. A delimiter is a maximal substring that matches *regex*. The eflags *Notbol* and *Noteol* are set. Raises *Regex* if it fails to make progress in decomposing *s*. Example use:

```
fields (regcomp " *,*" []) "56; 23 ; 22;; 89; 99"
```

[tokens regex s] returns the list of tokens in *s*, from left to right. A token is a non-empty maximal substring of *s* not containing any delimiter. A delimiter is a maximal substring that matches *regex*. The eflags *Notbol* and *Noteol* are set. Raises *Regex* if it fails to make progress in decomposing *s*. Equivalent to *List.filter (not o Substring.isEmpty) (fields regex s)*

Two tokens may be separated by more than one delimiter, whereas two fields are separated by exactly one delimiter. If the only delimiter is the character *#*|"", then

```
"abc||def" contains three fields: "abc" and "" and "def"
"abc||def" contains two tokens:  "abc" and "def"
```

[fold regex (fa, fb) e s] finds the (disjoint) substrings *bl*, ..., *bn* of *s* matching *regex* from left to right, and splits *s* into the substrings

```
a0, bl, a1, b2, a2, ..., bn, an
```

where *n* >= 0 and where *a0* is the (possibly empty) substring of *s* preceding the first match, and *ai* is the (possibly empty) substring between the matches *bi* and *b(i+1)*. Then it computes and returns *fa(an, fb(vecn), ..., fa(a1, fb(vecl, fa(a0, e))) ...)* where *vecl* is the match vector corresponding to *bl*. Raises *Regex* if it fails to make progress in decomposing *s*.

If we define the auxiliary functions

```
fun fapp f (x, r) = f x :: r
fun get i vec = Substring.string(Vector.sub(vec, i))
then
  map regex f s = List.rev (fold regex (#2, fapp f) [] s)
  app regex f s = fold regex (ignore, f o #1) () s
  fields regex s = List.rev (fold regex (op ::, #2) [] s)
  substitute regex f s =
    Substring.concat(List.rev
      (fold regex (op ::, fapp (Substring.all o f o get 0)) [] s))
```

Module SML90

SML90 -- part of the initial basis of the 1990 Definition

Math

```
val sqrt      : real -> real
val sin       : real -> real
val cos       : real -> real
val arctan    : real -> real
val exp       : real -> real
val ln        : real -> real

Strings

val chr       : int -> string
val ord       : string -> int

val explode   : string -> string list
val implode   : string list -> string

exception Abs
and Diff
and Exp
and Floor
and Neg
and Prod
and Sum
and Mod
and Quot

Input/output

type instream and outstream

val std_in    : instream
val open_in   : string -> instream
val input     : instream * int -> string
val lookahead : instream -> string
val close_in  : instream -> unit
val end_of_stream : instream -> bool

val std_out   : outstream
val open_out  : string -> outstream
val output    : outstream * string -> unit
val close_out : outstream -> unit
```

Module Signal

Signal -- SML Basis Library

eqtype signal

```
val abrt : signal
val alrm : signal
val bus  : signal
val fpe  : signal
val hup  : signal
val ill  : signal
val int  : signal
val kill : signal
val pipe : signal
val quit : signal
val segv : signal
val term : signal
val usr1 : signal
val usr2 : signal
val chld : signal
val cont : signal
val stop : signal
val tstp : signal
val ttin : signal
val ttou : signal

val toWord : signal -> Word.word
val fromWord : Word.word -> signal
```

```
[signal] is the type of Unix/Posix-style signals, which can be sent
to another process.

[toWord sig] returns the signal number as an unsigned word.

[fromWord w] returns the signal whose number is w.

[abrt] is SIGABRT, the abort signal from abort(3).

[alrm] is SIGALRM, a timer signal from alarm(1).

[bus] is SIGBUS, a bus error.

[fpe] is SIGFPE, a floating point exception.

[hup] is SIGHUP, a hangup.

[ill] is SIGILL, an illegal instruction.

[int] is SIGINT, an interrupt.

[kill] is SIGKILL, the kill signal.

[pipe] is SIGPIPE, a broken pipe.

[quit] is SIGQUIT, a quit from keyboard.

[segv] is SIGSEGV, a segmentation violation.

[term] is SIGTERM, the termination signal.

[usr1] is SIGUSR1, the first user signal.

[usr2] is SIGUSR2, the second user signal.

[chld] is SIGCHLD, child process stopped or terminated.

[cont] is SIGCONT, continue if stopped.

[stop] is SIGSTOP, signal to stop process.
```

[tstp] is SIGTSTP, a stop signal typed at the tty.
[ttin] is SIGTTIN, tty input for background process.
[ttou] is SIGTTOU, tty output for background process.

Module Socket

Socket -- SML Basis Library -- requires Dynlib

```
type ('addressfam, 'socketype) sock
type 'addressfam sock_addr

Socket types
type dgram          A datagram socket
type 'a stream      A stream socket
type passive        A passive stream
type active          An active, connected, stream

Socket protocol families
type pf_file        The Unix file protocol family
type pf_inet        The Internet protocol family

Address constructors
val fileAddr : string -> pf_file sock_addr
val inetAddr : string -> int -> pf_inet sock_addr

Socket constructors
val fileStream : unit -> (pf_file, 'a stream) sock
val fileDgram : unit -> (pf_file, dgram) sock
val inetStream : unit -> (pf_inet, 'a stream) sock
val inetDgram : unit -> (pf_inet, dgram) sock

val accept : ('a, passive stream) sock
-> ('a, active stream) sock * 'a sock_addr
val bind : ('a, 'b) sock * 'a sock_addr -> unit
val connect : ('a, 'b) sock * 'a sock_addr -> unit
val listen : ('a, passive stream) sock * int -> unit
val close : ('a, 'b) sock -> unit

Socket management
datatype shutdown_mode =
| NO_RECVS          No further receives
| NO_SENDS          No further sends
| NO_RECVS_OR_SENDS No receives nor sends

val shutdown : ('a, 'b stream) sock * shutdown_mode -> unit

type sock_desc

val sockDesc : ('a, 'b) sock -> sock_desc
val sameDesc : sock_desc * sock_desc -> bool
val compare : sock_desc * sock_desc -> order
val select :
{ rds : sock_desc list, wrs : sock_desc list, exs : sock_desc list,
  timeout : Time.time option }
-> { rds : sock_desc list, wrs : sock_desc list, exs : sock_desc list }

val getinetaddr : pf_inet sock_addr -> string

Sock I/O option types
type out_flags = { don't_route : bool, oob : bool }
type in_flags = { peek : bool, oob : bool }

type 'a buf = { buf : 'a, ofs : int, size : int option }

Socket output operations
val sendVec : ('a, active stream) sock * Word8Vector.vector buf -> int
val sendArr : ('a, active stream) sock * Word8Array.array buf -> int
val sendVec' : ('a, active stream) sock * Word8Vector.vector buf
* out_flags -> int
val sendArr' : ('a, active stream) sock * Word8Array.array buf
* out_flags -> int
val sendVecTo : ('a, dgram) sock * 'a sock_addr * Word8Vector.vector buf
-> int
val sendArrTo : ('a, dgram) sock * 'a sock_addr * Word8Array.array buf
```

```

-> int
val sendVecTo' : ('a, dgram) sock * 'a sock_addr * Word8Vector.vector buf
* out_flags -> int
val sendArrTo' : ('a, dgram) sock * 'a sock_addr * Word8Array.array buf
* out_flags -> int

Socket input operations
val recvVec : ('a, active stream) sock * int -> Word8Vector.vector
val recvArr : ('a, active stream) sock * Word8Array.array buf -> int
val recvVec' : ('a, active stream) sock * int * in_flags
-> Word8Vector.vector
val recvArr' : ('a, active stream) sock * Word8Array.array buf * in_flags
-> int
val recvVecFrom : ('a, dgram) sock * int
-> Word8Vector.vector * 'a sock_addr
val recvArrFrom : ('a, dgram) sock * Word8Array.array buf
-> int * 'a sock_addr
val recvVecFrom' : ('a, dgram) sock * int * in_flags
-> Word8Vector.vector * 'a sock_addr
val recvArrFrom' : ('a, dgram) sock * Word8Array.array buf * in_flags
-> int * 'a sock_addr

```

Structure Socket defines functions for creating and using sockets, a means for communication between SWM processes on the same machine or via a network.

[('addressfam, 'socktype) sock] is the type of sockets with address family 'addressfam and having type 'socktype.

[('addressfam sock_addr)] is the type of sockets addresses.

The possible address (protocol) families are

```

type pf_file   The Unix address family (file)
type pf_inet   The Internet address family

```

The possible socket types are

```

type dgram     datagram sockets
type 'a stream stream sockets
type passive   passive stream sockets
type active    active, or connected, stream sockets

```

[fileAddr fname] returns a socket address for the Unix protocol family, created from the given file name fname.

[inetAddr inetaddr portno] returns a socket address for the Internet protocol family, created from the given Internet number (e.g. "130.225.40.253") and port number (e.g. 8080).

[fileStream ()] returns a new stream socket for the Unix protocol family.

[fileDgram ()] returns a new datagram socket for the Unix protocol family.

[inetStream ()] returns a new stream socket for the Internet protocol family.

[inetDgram ()] returns a new datagram socket for the Internet protocol family.

[accept sock] extracts the first connection on the queue of pending connections to sock. Returns (sock', addr) where sock' is a copy of the socket sock, bound to that connection, and addr is the address of the communications counterpart (the other end of the connection). Blocks if no connections are pending. The stream socket sock must have been assigned a name (with bind) and must be listening for connections (following a call to listen).

[bind sock addr] binds the socket sock to the address addr, that is, assigns the name addr to the socket. Binding a name in the

Unix protocol family creates a socket in the file system that must be deleted when it is no longer needed

[connect (sock, addr)] attempts to connect socket sock to the communications peer at address addr. If sock is a datagram socket, then addr is the address to which datagrams is to be sent, and the only address from which datagrams will be accepted. If sock is a stream socket, then addr specifies another socket to which to connect.

[listen (sock, queuelen)] enables the passive stream socket sock to accept incoming connections. The parameter queuelen specifies the maximal number of pending connections. Further connections from clients may be refused when this limit is reached.

[close sock] closes the socket.

[shutdown sock shutdown_mode] shuts down socket sock for further communication, as specified by the shutdown_mode parameter:

[NO_RECVS] no further receives are allowed;

[NO_SENDS] no further sends are allowed;

[NO_RECVS_OR_SENDS] no further receives or sends are allowed.

[getinetaddr addr] returns the Internet number (e.g. "130.225.40.253") of the Internet socket address addr.

[('a buf)] is the type of records { buf, ofs, size } which represent subvectors or subarrays:
if size = SOME s it represents buf[ofs..ofs+s-1];
if size = NONE it represents buf[ofs..len-1] where len is buf's length.
When the subbuffer is used in a call, exception Subscript will be raised if ofs < 0 or size < 0 or ofs+size > len.

[sendVec (sock, vecbuf)] transmits the bytes from buffer vecbuf on the active stream socket sock. Returns the number of bytes sent. Blocks until sufficient space is available at the socket.

[sendArr (sock, arrbuf)] is analogous til sendVec.

[sendVec' (sock, vecbuf, out_flags)] transmits the bytes from buffer vecbuf on the active stream socket sock, observing the out_flags. Returns the number of bytes sent. Blocks until sufficient space is available at the socket.

[out_flags] is the type of records { don't_route, oob } in which the field don't_route specifies whether routing should be bypassed, and the field oob specifies whether data should be sent out-of-band.

[sendArr' (sock, arrbuf, out_flags)] is analogous til sendVec'.

[sendVecTo (sock, addr, vecbuf)] transmits the bytes from buffer vecbuf on the datagram socket sock to the target address addr. Returns the number of bytes sent. Blocks until sufficient space is available at the socket.

[sendArrTo (sock, addr, arrbuf)] is analogous til sendVecTo.

[sendVecTo' (sock, addr, vecbuf, out_flags)] transmits the bytes from buffer vecbuf on the datagram socket sock to the target address addr, observing the out_flags. Returns the number of bytes sent. Blocks until sufficient space is available at the socket. See above for a description of vecbuf and out_flags.

[sendArrTo' (sock, addr, arrbuf, out_flags)] is analogous til sendVecTo'.

[recvVec (sock, n)] receives up to n bytes from the active stream socket sock. Returns a byte vector containing the bytes actually received. Blocks until some data become available at the socket, then returns any available data, up to n bytes. Excess data are

not lost; they are available for subsequent receive calls.

`[recvArr (sock, arrbuf)]` receives bytes from the active stream socket sock into the subarray arrbuf, up to the available space. If `#size(arrbuf) = SOME(s)` the available space is `s` bytes; if `#size(arrbuf) = NONE` the available space is `len - #ofs(arrbuf)` bytes. Returns the number of bytes actually received. Blocks until some data become available at the socket. Excess data are not lost; they are available for subsequent receive calls.

`[recvVec' (sock, n, in_flags)]` receives up to `n` bytes from the active stream socket sock, observing the `in_flags`. Returns a byte vector containing the bytes actually received. Blocks until some data become available at the socket, then returns any available data, up to `n` bytes. Data in excess of `n` bytes are not lost; they are available for subsequent receive calls.

`[in_flags]` is the type of records `{ peek, oob }` in which the field `peek` specifies that the data read should not be removed from the receive queue, and the field `oob` specifies that data may be received out-of-band.

`[recvArr' (sock, arrbuf, in_flags)]` receives bytes from the active stream socket sock into the subarray arrbuf, observing the `in_flags`, up to the available space. Returns the number of bytes actually received. Blocks until some data become available at the socket. Excess data are not lost; they are available for subsequent receive calls.

`[recvVecFrom (sock, n)]` receives up to `n` bytes from the datagram socket sock. Returns a byte vector containing the bytes actually received. Blocks until some data become available at the socket, then returns any available data, up to `n` bytes.

`[recvArrFrom (sock, arrbuf)]` receives bytes from the datagram socket sock into the subarray arrbuf. Returns the number of bytes actually received. Blocks until some data become available at the socket.

`[recvVecFrom' (sock, n, in_flags)]` receives up to `n` bytes from the datagram socket sock, observing the `in_flags` (see above). Returns `(vec, addr)` where `vec` is a byte vector containing the bytes actually received, and `addr` is the source address of the message. Blocks until some data become available at the socket, then returns any available data, up to `n` bytes.

`[recvArrFrom' (sock, arrbuf, in_flags)]` receives bytes from the datagram socket sock into the array buffer arrbuf, observing the `in_flags` (see above). Returns `(n, addr)` where `n` is the number of bytes actually received, and `addr` is the source address of the message. Blocks until some data become available at the socket.

`[sockDesc sock]` returns a descriptor for the socket sock, to be used in a call to `select`.

`[compare (sd1, sd2)]` compares `sd1` and `sd2` according to an unspecified total ordering, and returns `LESS` if `sd1` precedes `sd2`, returns `GREATER` if `sd1` precedes `sd2`, and returns `EQUAL` otherwise.

`[sameDesc (sd1, sd2)]` returns true if `sd1` and `sd2` describe the same socket. Equivalent to `compare(sd1, sd2) = EQUAL`.

`[select { rds, wrs, eks, timeout }]` blocks the calling process until some input/output operations become possible on some sockets. The call will check the sockets described in `rds` for reading, those in `wrs` for writing, and those in `eks` for exceptional conditions. Returns `{ rds, wrs, eks }` where `rds` now is a list of descriptors of sockets ready for reading, `wrs` are ready for writing, and `eks` have exceptional conditions. The order of the socket descriptors in the results is the same as their order in the corresponding arguments. If timeout is `NONE` then the call blocks until some input/output operations become possible; if timeout is `SOME(t)` then the call

blocks for at most time `t`.

A server socket is considered ready for reading if there is a pending connection which can be accepted with `'accept'`. A client socket is ready for writing when its connection is fully established.

Module Spraymap

Spraymap -- applicative maps implemented by splay-trees
From SWML/NJ lib 0.2, copyright 1993 by AT&T Bell Laboratories

```
type ('key, 'a) dict
exception NotFound

val mkDict      : ('key * 'key -> order) -> ('_key, 'a) dict
val insert      : ('key, 'a) dict * 'key * 'a -> ('_key, 'a) dict
val find        : ('key, 'a) dict * 'key -> 'a
val peek        : ('key, 'a) dict * 'key -> 'a option
val remove      : ('_key, '_a) dict * 'key -> ('_key, '_a) dict * 'a
val numItems    : ('key, 'a) dict -> int
val listItems   : ('key, 'a) dict -> ('key * 'a) list
val app         : ('key * 'a -> unit) -> ('key, 'a) dict -> unit
val revapp      : ('key * 'a -> 'b) -> ('key, 'a) dict -> unit
val foldr       : ('key * 'a * 'b -> 'b) -> 'b -> ('key, 'a) dict -> 'b
val foldl       : ('key * 'a * 'b -> 'b) -> 'b -> ('key, 'a) dict -> 'b
val map         : ('_key * 'a -> '_b) -> ('_key, 'a) dict -> ('_key, '_b) dict
val transform   : ('a -> '_b) -> ('_key, 'a) dict -> ('_key, '_b) dict
```

`[('key, 'a) dict]` is the type of applicative maps from domain type 'key to range type 'a, or equivalently, applicative dictionaries with keys of type 'key and values of type 'a. They are implemented as ordered splay-trees (Sleator and Tarjan).

`[mkDict ord]` returns a new, empty map whose keys have ordering `ord`.

`[insert(m, i, v)]` extends (or modifies) map `m` to map `i` to `v`.

`[find (m, k)]` returns `v` if `m` maps `k` to `v`; otherwise raises `NotFound`.

`[peek(m, k)]` returns `SOME v` if `m` maps `k` to `v`; otherwise returns `NONE`.

`[remove(m, k)]` removes `k` from the domain of `m` and returns the modified map and the element `v` corresponding to `k`. Raises `NotFound` if `k` is not in the domain of `m`.

`[numItems m]` returns the number of entries in `m` (that is, the size of the domain of `m`).

`[listItems m]` returns a list of the entries `(k, v)` of keys `k` and the corresponding values `v` in `m`, in increasing order of `k`.

`[app f m]` applies function `f` to the entries `(k, v)` in `m`, in increasing order of `k` (according to the ordering `ord` used to create the map or dictionary).

`[revapp f m]` applies function `f` to the entries `(k, v)` in `m`, in decreasing order of `k`.

`[foldl f e m]` applies the folding function `f` to the entries `(k, v)` in `m`, in increasing order of `k`.

`[foldr f e m]` applies the folding function `f` to the entries `(k, v)` in `m`, in decreasing order of `k`.

`[map f m]` returns a new map whose entries have form `(k, f(k.v))`, where `(k, v)` is an entry in `m`.

`[transform f m]` returns a new map whose entries have form `(k, f v)`, where `(k, v)` is an entry in `m`.

Module Splayset

Splayset -- applicative sets implemented by splay-trees
From SWML/NJ lib 0.2, copyright 1993 by AT&T Bell Laboratories

```
type 'item set
exception NotFound

val empty       : ('item * 'item -> order) -> 'item set
val singleton   : ('item * 'item -> order) -> 'item -> 'item set
val add         : 'item set * 'item -> 'item set
val addlist     : 'item set * 'item list -> 'item set
val retrieve     : 'item set * 'item -> 'item
val peek        : 'item set * 'item -> 'item option
val isEmpty     : 'item set -> bool
val isEqual     : 'item set * 'item set -> bool
val isSubset    : 'item set * 'item set -> bool
val member      : 'item set * 'item -> bool
val delete      : 'item set * 'item -> 'item set
val numItems    : 'item set -> int
val union       : 'item set * 'item set -> 'item set
val intersection : 'item set * 'item set -> 'item set
val difference   : 'item set * 'item set -> 'item set
val listItems    : 'item set -> 'item list
val app         : ('item -> unit) -> 'item set -> unit
val revapp      : ('item -> unit) -> 'item set -> unit
val foldr       : ('item * 'b -> 'b) -> 'b -> 'item set -> 'b
val foldl       : ('item * 'b -> 'b) -> 'b -> 'item set -> 'b
val find        : ('item -> bool) -> 'item set -> 'item option
```

`['item set]` is the type of sets of ordered elements of type 'item. The ordering relation on the elements is used in the representation of the set. The result of combining two sets with different underlying ordering relations is undefined. The implementation uses splay-trees (Sleator and Tarjan).

`[empty ord]` creates a new empty set with the given ordering relation.

`[singleton ord i]` creates the singleton set containing `i`, with the given ordering relation.

`[add(s, i)]` adds item `i` to set `s`.

`[addlist(s, xs)]` adds all items from the list `xs` to the set `s`.

`[retrieve(s, i)]` returns `i` if it is in `s`; raises `NotFound` otherwise.

`[peek(s, i)]` returns `SOME i` if `i` is in `s`; returns `NONE` otherwise.

`[isEmpty s]` returns true if and only if the set is empty.

`[equal(s1, s2)]` returns true if and only if the two sets have the same elements.

`[isSubset(s1, s2)]` returns true if and only if `s1` is a subset of `s2`.

`[member(s, i)]` returns true if and only if `i` is in `s`.

`[delete(s, i)]` removes item `i` from `s`. Raises `NotFound` if `i` is not in `s`.

`[numItems s]` returns the number of items in set `s`.

`[union(s1, s2)]` returns the union of `s1` and `s2`.

`[intersection(s1, s2)]` returns the intersection of `s1` and `s2`.

`[difference(s1, s2)]` returns the difference between `s1` and `s2` (that is, the set of elements in `s1` but not in `s2`).

```

[listItems s] returns a list of the items in set s, in increasing
order.

[app f s] applies function f to the elements of s, in increasing
order.

[revapp f s] applies function f to the elements of s, in decreasing
order.

[foldl f e s] applies the folding function f to the entries of the
set in increasing order.

[foldr f e s] applies the folding function f to the entries of the
set in decreasing order.

[find p s] returns SOME i, where i is an item in s which satisfies
p, if one exists; otherwise returns NONE.

```

Module String

```

String -- SML Basis Library

local
  in
    type char = Char.char
    type string = string
    val maxSize : int
    val size : string * int -> int
    val sub : string * int * int -> char
    val substring : string * int * int -> string
    val extract : string * int * int option -> string
    val ^ : string * string -> string
    val concat : string list -> string
    val concatWith : string -> string list -> string
    val str : char -> string
    val implode : char list -> string
    val explode : string -> char list

    val map : (char -> char) -> string -> string
    val translate : (char -> string) -> string -> string
    val tokens : (char -> bool) -> string -> string list
    val fields : (char -> bool) -> string -> string list

    val compare : string * string -> order
    val collate : (char * char -> order) -> string * string -> order

    val isPrefix : string -> string -> bool
    val isSuffix : string -> string -> bool
    val isSubstring : string -> string -> bool

    val fromString : string -> string option
    val toString : string -> string
    val fromCString : string -> string option
    val toCString : string -> string
    val < : string * string -> bool
    val <= : string * string -> bool
    val > : string * string -> bool
    val >= : string * string -> bool
  end

[string] is the type of immutable strings of characters, with
constant-time indexing.

[maxSize] is the maximal number of characters in a string.

[size s] is the number of characters in string s.

[sub(s, i)] is the i'th character of s, counting from zero.
Raises Subscript if i<0 or i>size s.

[substring(s, i, n)] is the string s[i..i+n-1]. Raises Subscript
if i<0 or n<0 or i+n>size s. Equivalent to extract(s, i, SOME n).

[extract (s, i, NONE)] is the string s[i..size s-1].
Raises Subscript if i<0 or i>size s.

[extract (s, i, SOME n)] is the string s[i..i+n-1].
Raises Subscript if i<0 or n<0 or i+n>size s.

[s1 ^ s2] is the concatenation of strings s1 and s2.

[concat ss] is the concatenation of all the strings in ss.
Raises Size if the sum of their sizes is greater than maxSize.

[concatWith sep ss] is the concatenation of all the strings in ss,
using sep as a separator. Thus
  concatWith sep ss      is the empty string ""
  concatWith sep {s}     is s

```

`concatWith sep [s1, ..., sn]` is `concat[s1, sep, ..., sep, sn]`.
 Raises `Size` if the resulting string would have more than `maxSize` characters.

`[str c]` is the string of size one which contains the character `c`.

`[implode cs]` is the string containing the characters in the list `cs`.
 Equivalent to `concat (List.map str cs)`.

`[explode s]` is the list of characters in the string `s`.

`[map f s]` applies `f` to every character of `s`, from left to right, and returns the string consisting of the resulting characters.
 Equivalent to `CharVector.map f s`
 and to `implode (List.map f (explode s))`.

`[translate f s]` applies `f` to every character of `s`, from left to right, and returns the concatenation of the resulting strings.
 Raises `Size` if the sum of their sizes is greater than `maxSize`.
 Equivalent to `concat (List.map f (explode s))`.

`[tokens p s]` returns the list of tokens in `s`, from left to right, where a token is a non-empty maximal substring of `s` not containing any delimiter, and a delimiter is a character satisfying `p`.

`[fields p s]` returns the list of fields in `s`, from left to right, where a field is a (possibly empty) maximal substring of `s` not containing any delimiter, and a delimiter is a character satisfying `p`.

Two tokens may be separated by more than one delimiter, whereas two fields are separated by exactly one delimiter. If the only delimiter is the character `#` `"|"`, then

```
"abc||def" contains two tokens:  "abc" and "def"
"abc||def" contains three fields: "abc" and "" and "def"
```

`[isPrefix s1 s2]` is true if `s1` is a prefix of `s2`.
 That is, if there exists a string `u` such that `s1 ^ u = s2`.

`[isSuffix s1 s2]` is true if `s1` is a suffix of `s2`.
 That is, if there exists a string `t` such that `t ^ s1 = s2`.

`[isSubstring s1 s2]` is true if `s1` is a substring of `s2`.
 That is, if there exist strings `t` and `u` such that `t ^ s1 ^ u = s2`.

`[fromString s]` scans the string `s` as an ML source program string, converting escape sequences into the appropriate characters. Does not skip leading whitespace.

`[toString s]` returns a string corresponding to `s`, with non-printable characters replaced by ML escape sequences.
 Equivalent to `String.translate Char.toString`.

`[fromCString s]` scans the string `s` as a C source program string, converting escape sequences into the appropriate characters. Does not skip leading whitespace.

`[toCString s]` returns a string corresponding to `s`, with non-printable characters replaced by C escape sequences.
 Equivalent to `String.translate Char.toCString`.

`[compare (s1, s2)]` does lexicographic comparison, using the standard ordering `Char.compare` on the characters. Returns `LESS`, `EQUAL`, or `GREATER`, according as `s1` is less than, equal to, or greater than `s2`.

`[collate cmp (s1, s2)]` performs lexicographic comparison, using the given ordering `cmp` on characters.

```
[<]
[<=]
[>]
```

`[>=]` compare strings lexicographically, using the representation ordering on characters.

Module StringCvt

StringCvt -- SML Basis Library

| datatype | radix = BIN | OCT | DEC | HEX |
|----------|-------------|-----|-----|-----|
|----------|-------------|-----|-----|-----|

```

datatype realfmt =
  | SCI of int option    scientific, arg = # dec. digits, dflt=6
  | FIX of int option    fixed-point, arg = # dec. digits, dflt=6
  | GEN of int option    auto choice of the above,
                        arg = # significant digits, dflt=12

```

```

type cs                character source state

type ('a, 'b) reader = 'b -> ('a * 'b) option

val scanString : (char, cs) reader -> ('a, cs) reader -> string -> 'a option

val splitl           : (char -> bool) -> (char, 'a) reader -> 'a -> string * 'a
val take1            : (char -> bool) -> (char, 'a) reader -> 'a -> string
val drop1            : (char -> bool) -> (char, 'a) reader -> 'a -> 'a
val skipws           : (char, 'a) reader -> 'a -> 'a

val padLeft         : char -> int -> string -> string
val padRight        : char -> int -> string -> string

```

This structure presents tools for scanning strings and values from functional character streams, and for simple formatting.

[[('elm', src) reader] is the type of source readers for reading a sequence of 'elm' values from a source of type 'src'. For instance, a character source reader

```
getc : (char, cs) reader
```

is used for obtaining characters from a functional character source src of type cs, one at a time. It should hold that

```

getch src = SOME(c, src')
    if the next character in src
    is c, and src' is the rest of src;
    = NONE
    if src contains no characters

```

A character source scanner takes a character source reader gets as argument and uses it to scan a data value from the character source.

`[scanString scan s]` turns the string `s` into a character source and applies the scanner `'scan'` to that source.

[splitl p getc src] returns (pref, suff) where pref is the longest prefix (left substring) of src all of whose characters satisfy p, and suff is the remainder of src. That is, the first character retrievable from suff, if any, is the leftmost character not satisfying p. Does not skip leading whitespace.

[take! p getc src] returns the longest prefix (left substring) of all of whose characters satisfy predicate *p*. That is, if the left-most character does not satisfy *p*, the result is the empty string. Does not skip leading whitespace. It holds that

```
take! p getc src = #1 (split! p getc src)
```

```
[drop] p getc src] drops the longest prefix (left substring) of
src all of whose characters satisfy predicate p. If all characters
do, it returns the empty source. It holds that
drop1 p getc src = #2 (split) p getc src)
```

`[skipWS getc src]` drops any leading whitespace from `src`.
Equivalent to `drop1 Char.isSpace`.

[padLeft c n s] returns the string s if size s >= n, otherwise pads s with (n - size s) copies of the character c on the left. In other words, right-justifies s in a field n characters wide.

[padRight c n s] returns the string s if size s >= n, otherwise pads s with (n - size s) copies of the character c on the right. In other words, left-justifies s in a field n characters wide.

Module Substring

Substring -- *SWL Basis Library*

type substring

```

val substring
: string * int * int -> substring
val extract
: string * int * int option -> substring
val full
: string -> substring
val all
: string -> substring
val string
: substring -> string
val base
: substring -> (string * int * int)

val isEmpty
: substring -> bool
val getc
: substring -> (char * substring) option
val first
: substring -> char option
val triml
: int -> substring -> substring
val trimr
: int -> substring -> substring
val sub
: substring * int -> char
val size
: substring -> int
val slice
: substring * int * int option -> substring
val concat
: substring list -> string
val concatWith
: string -> substring list -> string
val explode
: substring -> char list
val compare
: substring * substring -> order
val collate
: (char * char -> order) -> substring * substring -> order

val dropL
: (char -> bool) -> substring -> substring
val dropR
: (char -> bool) -> substring -> substring
val takel
: (char -> bool) -> substring -> substring
val taker
: (char -> bool) -> substring -> substring
val splitL
: (char -> bool) -> substring -> substring * substring
val splitR
: (char -> bool) -> substring -> substring * substring
val splitAt
: substring * int -> substring * substring

val position
: string -> substring -> substring * substring
val isPrefix
: string -> substring -> bool
val isSuffix
: string -> substring -> bool
val isSubString
: string -> substring -> bool

exception Span
val span
: substring * substring -> substring

val translate
: (char -> string) -> substring -> string

val tokens
: (char -> bool) -> substring -> substring list
val fields
: (char -> bool) -> substring -> substring list

val foldl
: (char * 'a -> 'a) -> 'a -> substring -> 'a
val foldr
: (char * 'a -> 'a) -> 'a -> substring -> 'a
val app
: (char -> unit) -> substring -> unit

[substring] is the type of substrings of a basestring, an efficient
representation of a piece of a string.
A substring (s,i,n) is valid if 0 <= i <= i+n <= size s,
or equivalently, 0 <= i and 0 <= n and i+n <= size s.
A valid substring (s, i, n) represents the string s[i...i+n-1].
Invariant in the implementation: Any value of type substring is valid.

A substring is the same as a CharVectorSlice.slice, so substrings
may be processed using the functions declared in CharVectorSlice.

[substring(s, i, n)] creates the substring (s, i, n), consisting of
the substring of s with length n starting at i. Raises Subscript
if i<0 or n<0 or i+n > size s. Equivalent to extract(s, i, SOME n).

[extract(s, i, NONE)] creates the substring (s, i, size s-i)
consisting of the tail of s starting at i.
Raises Subscript if i<0 or i > size s.

[extract(s, i, SOME n)] creates the substring (s, i, n),

```

consisting of the substring of s with length n starting at i.
Raises Subscript if i<0 or n<0 or i+n > size s.

[full s] is the substring (s, 0, size s).

[all s] is the same as full(s). Its use is deprecated.

[string sus] is the string s[i..i+n-1] represented by sus = (s, i, n).

[base sus] is the concrete triple (s, i, n), where sus = (s, i, n).

[isEmpty (s, i, n)] true if the substring is empty (that is, n = 0).

[getc sus] returns SOME(c, rst) where c is the first character and rst the remainder of sus, if sus is non-empty; otherwise returns NONE. Note that
#1 0 valOf o scanFn Substring.getc
is equivalent to, but more efficient than,
valOf o StringCvt.scanString scanFn o Substring.string

[first sus] returns SOME c where c is the first character in sus, if sus is non-empty; otherwise returns NONE.

[trimL k sus] returns sus less its leftmost k characters; or the empty string at the end of sus if it has less than k characters. Raises Subscript if k < 0, even in the partial application trimL(k).

[sub (sus, k)] returns the k'th character of the substring; that is, s[i+k] where sus = (s, i, n). Raises Subscript if k<0 or k>=n.

[size (s, i, n)] returns the size of the substring, that is, n.

[slice (sus, i', NONE)] returns the substring (s, i+i', n-i'), where sus = (s, i, n). Raises Subscript if i' < 0 or i' > n.

[slice (sus, i', SOME n')] returns the substring (s, i+i', n'), where sus = (s, i, n). Raises Subscript if i' < 0 or n' < 0 or i'+n' > n.

[concat sus] returns a string consisting of the concatenation of the substrings. Equivalent to String.concat (List.map string sus). Raises Size if the resulting string would be longer than String.maxSize.

[concatWith sep sus] returns a string consisting of the concatenation of the substrings in sus, using sep as a separator. Equivalent to String.concatWith sep (List.map string sus). Raises Size if the resulting string would be longer than String.maxSize.

[explode sus] returns the list of characters of sus, that is,
[s(i), s(i+1), ..., s(i+n-1)]
where sus = (s, i, n). Equivalent to String.explode(string ss).

[compare (sus1, sus2)] performs lexicographic comparison, using the standard ordering Char.compare on the characters. Returns LESS, EQUAL, or GREATER, according as sus1 is less than, equal to, or greater than sus2. Equivalent to, but more efficient than,
String.compare(string sus1, string sus2).

[collate cmp (sus1, sus2)] performs lexicographic comparison, using the given ordering cmp on characters. Equivalent to, but more efficient than, String.collate cmp (string sus1, string sus2).

[dropL p sus] drops the longest prefix (left substring) of sus all of whose characters satisfy predicate p. If all characters do, it returns the empty substring (s, i+n, 0) where sus = (s, i, n).

[dropR p sus] drops the longest suffix (right substring) of sus all of whose characters satisfy predicate p. If all characters do, it returns the empty substring (s, i, 0) where sus = (s, i, n).

[take1 p sus] returns the longest prefix (left substring) of sus all of whose characters satisfy predicate p. That is, if the left-most character does not satisfy p, returns the empty (s, i, 0) where sus = (s, i, n).

[take2 p sus] returns the longest suffix (right substring) of sus all of whose characters satisfy predicate p. That is, if the right-most character satisfies p, returns the empty (s, i+n, 0) where sus = (s, i, n).

Let p be a predicate and xxxxyyyfzzzz a string where all characters in xxxx and zzzz satisfy p, and f a is character not satisfying p. Then

```

sus = xxxxyyyfzzzz      sus = xxxzzzzz
-----
dropl p sus = fyyyfzzzz
dropr p sus = xxxxyyyf
take1 p sus = xxxx      xxxzzzzz
take2 p sus = zzzz      xxxzzzzz

```

It also holds that

```

concat(take1 p sus, dropl p sus) = string sus
concat(dropr p sus, take2 p sus) = string sus

```

[split1 p sus] splits sus into a pair (sus1, sus2) of substrings where sus1 is the longest prefix (left substring) all of whose characters satisfy p, and sus2 is the rest. That is, sus2 begins with the leftmost character not satisfying p. Disregarding sideeffects, we have:

```
split1 p sus = (take1 p sus, dropl p sus).
```

[split2 p sus] splits sus into a pair (sus1, sus2) of substrings where sus2 is the longest suffix (right substring) all of whose characters satisfy p, and sus1 is the rest. That is, sus1 ends with the rightmost character not satisfying p. Disregarding sideeffects, we have:

```
split2 p sus = (dropr p sus, take2 p sus)
```

[splitAt (sus, k)] returns the pair (sus1, sus2) of substrings, where sus1 contains the first k characters of sus, and sus2 contains the rest. Raises Subscript if k < 0 or k > size sus.

[isPrefix s1 s2] is true if s1 is a prefix of s2. That is, if there exists a string u such that s1 ^ u = string s2.

[isSuffix s1 s2] is true if s1 is a suffix of s2. That is, if there exists a string t such that t ^ s1 = string s2.

[isSubstring s1 s2] is true if s1 is a substring of s2. That is, if there exist strings t and u such that t ^ s1 ^ u = string s2.

[position s (s', i, n)] splits the substring into a pair (pref, suff) of substrings, where suff is the longest suffix of (s', i, n) which has s as a prefix. More precisely, let m = size s. If there is a least index k in i..i+n-m for which s = s'[k..k+m-1], then the result is pref = (s', i, k-i) and suff = (s', k, n-(k-i)); otherwise the result is pref = (s', i, n) and suff = (s', i+n, 0).

[span (sus1, sus2)] returns a substring spanning from the start of sus1 to the end of sus2, provided this is well-defined: sus1 and sus2 must have the same underlying string, and the start of sus1 must not be to the right of the end of sus2; otherwise raises Span.

More precisely, if base(sus1) = (s, i, n) and base(sus2) = (s', i', n') and s = s' and i <= i'+n', then base(join(sus1, sus2)) = (s, i, i'+n'-i). This may be used to compute 'span', 'union', and 'intersection'.

[translate f sus] applies f to every character of sus, from left to right, and returns the concatenation of the results. Raises Size if the sum of their sizes is greater than String.maxSize.

Equivalent to String.concat(List.map f (explode sus)).

[tokens p sus] returns the list of tokens in sus, from left to right, where a token is a non-empty maximal substring of sus not containing any delimiter, and a delimiter is a character satisfying p.

[fields p sus] returns the list of fields in sus, from left to right, where a field is a (possibly empty) maximal substring of sus not containing any delimiter, and a delimiter is a character satisfying p.

Two tokens may be separated by more than one delimiter, whereas two fields are separated by exactly one delimiter. If the only delimiter is the character #|"", then

```

"abc||def" contains two tokens: "abc" and "def"
"abc||def" contains three fields: "abc" and "" and "def"

```

[foldl f e sus] folds f over sus from left to right. That is, evaluates f(s[i+n-1], f(... f(s[i+1], f(s[i] % e)) ...)) tail-recursively, where sus = (s, i, n).

Equivalent to List.foldl f e (explode sus).

[foldr f e sus] folds f over sus from right to left. That is, evaluates f(s[i], f(s[i+1], f(... f(s[i+n-1] % e) ...))) tail-recursively, where sus = (s, i, n).

Equivalent to List.foldr f e (explode sus).

[app f sus] applies f to all characters of sus, from left to right.

Equivalent to List.app f (explode sus).

Module Susp

Susp -- support for lazy evaluation

```
type 'a susp
val delay : (unit -> 'a) -> 'a susp
val force : 'a susp -> 'a
```

[*'a susp*] is the type of lazily evaluated expressions with result type *'a*.
[*delay (fn () => e)*] creates a suspension for the expression *e*. The first time the suspension is forced, the expression *e* will be evaluated, and the result stored in the suspension. All subsequent forcing of the suspension will just return this result, so *e* is evaluated at most once. If the suspension is never forced, then *e* is never evaluated.
[*force su*] forces the suspension *su* and returns the result of the expression *e* stored in the suspension.

Module TextIO

TextIO -- SML Basis Library

```
type elem = Char.char
type vector = string

Text input
type instream
  val openIn      : string -> instream
  val closeIn    : instream -> unit
  val input      : instream -> vector
  val inputAll   : instream -> vector
  val inputNoBlock : instream -> vector option
  val input1     : instream -> elem option
  val inputN     : instream * int -> vector
  val inputLine  : instream -> string
  val endOfStream : instream -> bool
  val lookahead  : instream -> elem option

type cs character source state
val scanStream : ((char, cs) StringCvt.reader -> ('a, cs) StringCvt.reader)
               -> instream -> 'a option

val stdIn      : instream

Text output
type ostream
  val openOut      : string -> ostream
  val openAppend   : string -> ostream
  val closeOut     : ostream -> unit
  val output       : ostream * vector -> unit
  val output1      : ostream * elem -> unit
  val outputSubstr : ostream * substring -> unit
  val flushOut     : ostream -> unit

  val stdout      : ostream
  val stderr      : ostream

  val print       : string -> unit
```

This structure provides input/output functions on text streams. The functions are state-based: reading from or writing to a stream changes the state of the stream. The streams are buffered: output to a stream may not immediately affect the underlying file or device.

Note that under DOS, Windows, OS/2, and MacOS, text streams will be 'translated' by converting (e.g.) the double newline CRLF to a single newline character \n.

- [*instream*] is the type of state-based characters input streams.
- [*ostream*] is the type of state-based character output streams.
- [*elem*] is the type char of characters.
- [*vector*] is the type of character vectors, that is, strings.

TEXT INPUT:

[*openIn s*] creates a new instream associated with the file named *s*. Raises *Io.Io* if file *s* does not exist or is not accessible.

[*closeIn istr*] closes stream *istr*. Has no effect if *istr* is closed

already. Further operations on istr will behave as if istr is at end of stream (that is, will return "" or NONE or true).

[input istr] reads some elements from istr, returning a vector v of those elements. The vector will be empty (size v = 0) if and only if istr is at end of stream or is closed. May block (not return until data are available in the external world).

[inputAll istr] reads and returns the string v of all characters remaining in istr up to end of stream.

[inputNoBlock istr] returns SOME(v) if some elements v can be read without blocking; returns SOME("") if it can be determined without blocking that istr is at end of stream; returns NONE otherwise. If istr does not support non-blocking input, raises Io.NonblockingNotSupported.

[input1 istr] returns SOME(e) if at least one element e of istr is available; returns NONE if istr is at end of stream or is closed; blocks if necessary until one of these conditions holds.

[inputN(istr, n)] returns the next n characters from istr as a string, if that many are available; returns all remaining characters if end of stream is reached before n characters are available; blocks if necessary until one of these conditions holds. (This is the behaviour of the 'input' function prescribed in the 1990 Definition of Standard ML).

[inputLine istr] returns one line of text, including the terminating newline character. If end of stream is reached before a newline character, then the remaining part of the stream is returned, with a newline character added. If istr is at end of stream or is closed, then the empty string "" is returned.

[endOfStream istr] returns false if any elements are available in istr; returns true if istr is at end of stream or closed; blocks if necessary until one of these conditions holds.

[lookahead istr] returns SOME(e) where e is the next element in the stream; returns NONE if istr is at end of stream or is closed; blocks if necessary until one of these conditions holds. Does not advance the stream.

[stdIn] is the buffered state-based standard input stream.

[scanStream scan istr] turns the instream istr into a character source and applies the scanner 'scan' to that source. See StringCvt for more on character sources and scanners. The Moscow ML implementation currently can backtrack only 512 characters, and raises Fail if the scanner backtracks further than that.

TEXT OUTPUT:

[openOut s] creates a new outstream associated with the file named s. If file s does not exist, and the directory exists and is writable, then a new file is created. If file s exists, it is truncated (any existing contents are lost).

[openAppend s] creates a new outstream associated with the file named s. If file s does not exist, and the directory exists and is writable, then a new file is created. If file s exists, any existing contents are retained, and output goes at the end of the file.

[closeOut ostr] closes stream ostr; further operations on ostr (except for additional close operations) will raise exception Io.Io.

[output(ostr, v)] writes the string v on outstream ostr.

[output1(ostr, e)] writes the character e on outstream ostr.

[flushOut ostr] flushes the outstream ostr, so that all data written to ostr becomes available to the underlying file or device.

[stdOut] is the buffered state-based standard output stream.

[stdErr] is the unbuffered state-based standard error stream. That is, it is always kept flushed, so flushOut(stdErr) is redundant.

[print s] outputs s to stdOut and flushes immediately.

The functions below are not yet implemented:

[setPosIn(istr, i)] sets istr to the (untranslated) position i. Raises Io.Io if not supported on istr.

[getPosIn istr] returns the (untranslated) current position of istr. Raises Io.Io if not supported on istr.

[endPosIn istr] returns the (untranslated) last position of istr. Because of translation, one cannot expect to read endPosIn istr - getPosIn istr from the current position.

[getPosOut ostr] returns the current position in stream ostr. Raises Io.Io if not supported on ostr.

[endPosOut ostr] returns the ending position in stream ostr. Raises Io.Io if not supported on ostr.

[setPosOut(ostr, i)] sets the current position in stream to ostr to i. Raises Io.Io if not supported on ostr.

[mkInstream sistr] creates a state-based instream from the functional instream sistr.

[getInstream istr] returns the functional instream underlying the state-based instream istr.

[setInstream(istr, sistr)] redirects istr, so that subsequent input is taken from the functional instream sistr.

[mkOutstream sostr] creates a state-based outstream from the outstream sostr.

[getOutstream ostr] returns the outstream underlying the state-based outstream ostr.

[setOutstream(ostr, sostr)] redirects the outstream ostr so that subsequent output goes to sostr.

Module Time

Time -- SML Basis Library

datatype time

exception Time

val zeroTime : time
val now : unit -> time

val toSeconds : time -> int
val toMilliseconds : time -> int
val toMicroseconds : time -> int
val fromSeconds : int -> time
val fromMilliseconds : int -> time
val fromMicroseconds : int -> time

val fromReal : real -> time
val toReal : time -> real

val toString : time -> string rounded to millisecond precision
val fmt : int -> time -> string
val fromString : string -> time option
val scan : (char, 'a) StringCvt.reader -> (time, 'a) StringCvt.reader

val + : time * time -> time
val - : time * time -> time
val < : time * time -> bool
val <= : time * time -> bool
val > : time * time -> bool
val >= : time * time -> bool

val compare : time * time -> order

[fmt n t] returns as a string the number of seconds represented by t, rounded to n decimal digits. If n <= 0, then no decimal digits are reported.

[toString t] returns as a string the number of seconds represented by t, rounded to 3 decimal digits. Equivalent to (fmt 3 t).

[fromString s] returns SOME t where t is the time value represented by the string s of form [\\n\\t]*[+-]?((0-9)+\\.([0-9]+)?|\\([0-9]+)); or returns NONE if s cannot be parsed as a time value.

[scangetc src], wheregetc is a character accessor, returns SOME (t, rest) where t is a time and rest is rest of the input, or NONE if s cannot be parsed as a time value.

[+] adds two time values. For reals r1, r2 >= 0.0, it holds that fromReal r1 + fromReal r2 = fromReal(Real.(r1,r2)). Raises Overflow if the result is not representable as a time value.

[-] subtracts a time value from another. That is, t1 - t2 is the duration from t2 to t1 (which may be negative). It holds that t - zeroTime = t.

[<]
[<=]
[>]

[>=] compares time values. For instance, for reals r1, r2 >= 0.0 it holds that fromReal r1 < fromReal r2 iff Real.<(r1, r2)

[compare(t1, t2)] returns LESS, EQUAL, or GREATER, according as t1 precedes, equals, or follows t2 in time.

[time] is a type for representing durations as well as absolute points in time (which can be thought of as durations since some fixed time zero). Times can be negative, zero, or positive.

[zeroTime] represents the 0-second duration, and the origin of time, so zeroTime + t = t + zeroTime = t for all t.

[now ()] returns the point in time at which the application occurs.

[fromSeconds s] returns the time value corresponding to s seconds.

[fromMilliseconds ms] returns the time value corresponding to ms milliseconds.

[fromMicroseconds us] returns the time value corresponding to us microseconds.

[toSeconds t] returns the number of seconds represented by t, truncated (towards zero). Raises Overflow if that number is not representable as an int.

[toMilliseconds t] returns the number of milliseconds represented by t, truncated (towards zero). Raises Overflow if that number is not representable as an int.

[toMicroseconds t] returns the number of microseconds represented by t, truncated (towards zero). Raises Overflow if t that number is not representable as an int.

[fromReal r] converts a real to a time value representing that many seconds. It holds that fromReal 0.0 = zeroTime.

[toReal t] converts a time to the number of seconds it represents; hence fromReal and toReal are inverses of each other.

Module Timer

Timer -- SML Basis Library

```
type cpu_timer
type real_timer

val startCPUTimer : unit -> cpu_timer
val totalCPUTimer : unit -> cpu_timer
val checkCPUTime : cpu_timer -> {usr : Time.time, sys : Time.time}
val checkGCTime : cpu_timer -> Time.time

val startRealTimer : unit -> real_timer
val totalRealTimer : unit -> real_timer
val checkRealTime : real_timer -> Time.time
```

[cpu_timer] is the type of timers for measuring CPU time consumption (user time, garbage collection time, and system time).

[real_timer] is the type of timers for measuring the passing of real time (wall-clock time).

[startCPUTimer ()] returns a cpu_timer started at the moment of the call.

[totalCPUTimer ()] returns a cpu_timer started at the moment the library was loaded.

[checkCPUTime tmr] returns {usr, sys} where usr is the amount of user CPU time consumed since tmr was started and sys is the amount of system CPU time consumed since tmr was started. Note that garbage collection time is included in the usr time. Under MS DOS and MS Windows, usr time is measured as real time.

[checkGCTime tmr] returns the amount of user CPU time spent on garbage collection since tmr was started. Under MS DOS and MS Windows, gc time is measured in real time.

[startRealTimer ()] returns a real_timer started at the moment of the call.

[totalRealTimer ()] returns a real_timer started at the moment the library was loaded.

[checkRealTime tmr] returns the amount of real time that has passed since tmr was started.

Module Unix

Unix -- SML Basis Library

```
type proc
type signal = Signal.signal

val executeInEnv : string * string list * string list -> proc
val execute : string * string list -> proc
val streamsOf : proc -> TextIO.instream * TextIO.outstream
val kill : proc * signal -> unit
val reap : proc -> Process.status
```

This structure allows Moscow ML programs to start other processes and to communicate with them.

Child processes are not automatically terminated when the parent (ML) process terminates. To forcibly terminate a child process pr, use Unix.kill(pr, Signal.term). Then, to remove the terminated process from the operating system tables, call Unix.reap(pr).

The protocol for communication between the ML program and its child process must be designed with some care, typically using non-blocking input for reading from the child process.

[proc] is the type of processes started by the ML program.

[signal] is the type of Unix-style signals, which can be sent to another process. Signal values must be obtained from the Signal structure.

[execute (cmd, args)] asks the operating system to execute the command cmd with the argument list args, as a separate process. Two pipes connected to the standard input and standard output of the new process are created; these may be obtained using streamsOf. A proc value representing the new process is returned. The new process executes using the same environment as the calling process. Raises Fail in case of failure, e.g. if the process or the pipes cannot be created.

Typically, the cmd argument will be the full pathname of an executable. On Unix systems, simple command searching as done by the shell, allowing cmd to be a relative pathname, can be achieved by using

```
execute("/bin/sh", "-c" :: concat (cmd :: " " :: args))
```

[executeInEnv (cmd, args, env)] asks the operating system to execute the command cmd with the argument list args in the environment env, as a separate process. Returns a proc value representing the new process. Typically, a string in the env list has the form "NAME=VALUE". See also Process.getEnv.

[streamsOf pr] returns a pair (ins, outs) of input and output streams associated with process pr. The standard output of pr is the source for the input stream ins, and the standard input of pr is the sink for the output stream outs.

[reap pr] closes the input and output streams associated with pr, and then suspends the current (ML) process until the process corresponding to pr terminates. Returns the exit status given by pr when it terminated. Raises Fail in case of failure, e.g. if pr has already been reaped.

Under Unix, information about a terminated process remains in the system tables until the process is reaped. Thus, an ML program using execute or executeInEnv must make sure to reap any process it has created, or else the system tables will fill up.

[kill (pr, s)] sends the signal s to the process pr. Raises Fail in case of failure, e.g. if pr has already been killed.

Module Vector

Vector -- SML Basis Library

```

type 'a vector = 'a vector
val maxLen : int

val fromList : 'a list -> 'a vector
val tabulate : int * (int -> 'a) -> 'a vector

val length : 'a vector -> int
val sub : 'a vector * int -> 'a
val update : 'a vector * int * 'a -> 'a vector
val concat : 'a vector list -> 'a vector

val find : ('a -> bool) -> 'a vector -> 'a option
val exists : ('a -> bool) -> 'a vector -> bool
val all : ('a -> bool) -> 'a vector -> bool

val app : ('a -> unit) -> 'a vector -> unit
val map : ('a -> 'b) -> 'a vector -> 'b vector
val foldl : ('a * 'b -> 'b) -> 'b -> 'a vector -> 'b
val foldr : ('a * 'b -> 'b) -> 'b -> 'a vector -> 'b

val findi : (int * 'a -> bool) -> 'a vector -> (int * 'a) option
val appi : (int * 'a -> unit) -> 'a vector -> unit
val mapi : (int * 'a -> 'b) -> 'a vector -> 'b vector
val foldli : (int * 'a * 'b -> 'b) -> 'b -> 'a vector -> 'b
val foldri : (int * 'a * 'b -> 'b) -> 'b -> 'a vector -> 'b

val collate : ('a * 'a -> order) -> 'a vector * 'a vector -> order

```

[`'ty vector`] is the type of one-dimensional, immutable, zero-based constant-time-access vectors with elements of type `'ty`. Type `'ty` vector admits equality if `'ty` does. Vectors `v1` and `v2` are equal if they have the same length and their elements are equal.

[`maxLen`] is the maximal number of elements in a vector.

[`fromList xs`] returns a vector whose elements are those of `xs`. Raises `Size` if `length xs > maxLen`.

[`tabulate(n, f)`] returns a vector of length `n` whose elements are `f 0, f 1, ..., f (n-1)`, created from left to right. Raises `Size` if `n<0` or `n>maxLen`.

[`length v`] returns the number of elements in `v`.

[`sub(v, i)`] returns the `i`'th element of `v`, counting from 0. Raises `Subscript` if `i<0` or `i=length v`.

[`update(v, i, x)`] creates a copy of `v`, sets position `i` to `x`, and returns the new vector. In contrast to `Array.update`, this is not a constant-time operation, because it must copy the entire vector. Raises `Subscript` if `i<0` or `i=length v`.

[`concat vs`] returns a vector which is the concatenation from left to right of the vectors in `vs`. Raises `Size` if the sum of the sizes of the vectors in `vs` is larger than `maxLen`.

[`find p v`] applies `p` to each element `x` of `v`, from left to right, until `p(x)` evaluates to `true`; returns `SOME x` if such an `x` exists, otherwise `NONE`.

[`exists p v`] applies `p` to each element `x` of `v`, from left to right, until `p(x)` evaluates to `true`; returns `true` if such an `x` exists, otherwise `false`.

[`all p v`] applies `p` to each element `x` of `v`, from left to right, until `p(x)` evaluates to `false`; returns `false` if such an `x` exists, otherwise `true`.

[`foldl f e v`] folds function `f` over `v` from left to right. That is, computes `f(v[len-1], f(v[len-2], ..., f(v[1], f(v[0], e)) ...))`, where `len` is the length of `v`.

[`foldr f e v`] folds function `f` over `v` from right to left. That is, computes `f(v[0], f(v[1], ..., f(v[len-2], f(v[len-1], e)) ...))`, where `len` is the length of `v`.

[`app f v`] applies `f` to `v[j]` for `j=0,1,...,length v-1`.

[`map f v`] applies `f` to `v[j]` for `j=0,1,...,length v-1` and returns a new vector containing the results.

The following iterators generalize the above ones by passing also the vector element index `j` to the function being iterated.

[`findi p a`] applies `f` to successive pairs `(j, a[j])` for `j=0,1,...,n-1`, until `p(j, a[j])` evaluates to `true`; returns `SOME (j, a[j])` if such a pair exists, otherwise `NONE`.

[`foldli f e v`] folds function `f` over the vector from left to right. That is, computes `f(n-1, vin-1], f(..., f(1, v[1], f(0, v[0], e)) ...)` where `n = length v`.

[`foldri f e v`] folds function `f` over the vector from right to left. That is, computes `f(0, v[0], f(1, v[1], ..., f(n-1, v[n-1], e) ...)` where `n = length v`.

[`appi f v`] applies `f` to successive pairs `(j, v[j])` for `j=0,1,...,n-1` where `n = length v`.

[`mapi f v`] applies `f` to successive pairs `(j, v[j])` for `j=0,1,...,n-1` where `n = length v` and returns a new vector containing the results.

[`collate cmp (xs, ys)`] returns `LESS`, `EQUAL` or `GREATER` according as `xs` precedes, equals or follows `ys` in the lexicographic ordering on vectors induced by the ordering `cmp` on elements.

Module VectorSlice

VectorSlice -- SML Basis Library

type 'a slice

```

val length : 'a slice -> int
val sub : 'a slice * int -> 'a
val slice : 'a Vector.vector * int * int option -> 'a slice
val full : 'a Vector.vector -> 'a slice
val subslice : 'a slice * int * int option -> 'a slice
val base : 'a slice -> 'a Vector.vector * int * int
val vector : 'a slice -> 'a Vector.vector
val concat : 'a slice list -> 'a Vector.vector
val isEmpty : 'a slice -> bool
val isEmpty : 'a slice -> bool
val getItem : 'a slice -> ('a * 'a slice) option

val find : ('a -> bool) -> 'a slice -> 'a option
val exists : ('a -> bool) -> 'a slice -> bool
val all : ('a -> bool) -> 'a slice -> bool

val app : ('a -> unit) -> 'a slice -> unit
val map : ('a -> 'b) -> 'a slice -> 'b Vector.vector
val foldl : ('a * 'b -> 'b) -> 'b -> 'a slice -> 'b
val foldr : ('a * 'b -> 'b) -> 'b -> 'a slice -> 'b

val findi : (int * 'a -> bool) -> 'a slice -> (int * 'a) option
val appi : (int * 'a -> unit) -> 'a slice -> unit
val mapi : (int * 'a -> 'b) -> 'a slice -> 'b Vector.vector
val foldli : (int * 'a * 'b -> 'b) -> 'b -> 'a slice -> 'b
val foldri : (int * 'a * 'b -> 'b) -> 'b -> 'a slice -> 'b

val collate : ('a * 'a -> order) -> 'a slice * 'a slice -> order

```

[*'ty slice*] is the type of vector slices, that is, sub-vectors. The slice (*a*,*i*,*n*) is valid if $0 \leq i \leq i+n \leq \text{size } s$, or equivalently, $0 \leq i$ and $0 \leq n$ and $i+n \leq \text{size } s$. A valid slice *sli* = (*a*,*i*,*n*) represents the sub-vector *a*[*i*..*i+n-1*], so the elements of *sli* are *a*[*i*], *a*[*i*+1], ..., *a*[*i+n-1*], and *n* is the length of the slice. Only valid slices can be constructed by the functions below.

[*length sli*] returns the number *n* of elements in *sli* = (*s*,*i*,*n*).

[*sub (sli, k)*] returns the *k*'th element of the slice, that is, *a*[*i*+*k*] where *sli* = (*a*,*i*,*n*). Raises Subscript if *k*<0 or *k*>*n*.

[*slice (a, i NONE)*] creates the slice (*a*, *i*, *length a-i*), consisting of the tail of *a* starting at *i*.

Raises Subscript if *i*<0 or *i* > *Vector.length a*.

Equivalent to *slice (a, i, SOME(Vector.length a - i))*.

[*slice (a, i, SOME n)*] creates the slice (*a*, *i*, *n*), consisting of the sub-vector of *a* with length *n* starting at *i*. Raises Subscript if *i*<0 or *n*<0 or *i+n* > *Vector.length a*.

| slice | meaning |
|---|--|
| (<i>a</i> , 0, NONE) | the whole vector |
| (<i>a</i> , 0, SOME <i>n</i>) | a left sub-vector (prefix) <i>a</i> [0.. <i>n-1</i>] |
| (<i>a</i> , <i>i</i> , NONE) | a right sub-vector (suffix) <i>a</i> [<i>i</i> .. <i>length a</i>] |
| (<i>a</i> , <i>i</i> , SOME <i>n</i>) | a general slice <i>a</i> [<i>i</i> .. <i>i+n-1</i>] |

[*full a*] creates the slice (*a*, 0, *Vector.length a*).

Equivalent to *slice(a,0,NONE)*

[*subslice (sli, i', NONE)*] returns the slice (*a*, *i*+*i'*, *n-i'*) when *sli* = (*a*,*i*,*n*). Raises Subscript if *i'* < 0 or *i'* > *n*.

[*subslice (sli, i', SOME n')*] returns the slice (*a*, *i*+*i'*, *n'*) when *sli* = (*a*,*i*,*n*). Raises Subscript if *i'* < 0 or *n'* < 0 or *i'*+*n'* > *n*.

[*base sli*] is the concrete triple (*a*, *i*, *n*) when *sli* = (*a*, *i*, *n*).

[*vector sli*] creates and returns a vector consisting of the elements of the slice, that is, *a*[*i*..*i+n-1*] when *sli* = (*a*,*i*,*n*).

[*concat sli*] creates a vector containing the concatenation of the slices in *sli*s.

[*isEmpty sli*] returns true if the slice *sli* = (*a*,*i*,*n*) is empty, that is, if *n*=0.

[*getItem sli*] returns *SOME(x, rst)* where *x* is the first element and *rst* the remainder of *sli*, if *sli* is non-empty; otherwise returns NONE.

[*find p sli*] applies *p* to each element *x* of *sli*, from left to right, until *p(x)* evaluates to true; returns *SOME x* if such an *x* exists, otherwise NONE.

[*exists p sli*] applies *p* to each element *x* of *sli*, from left to right, until *p(x)* evaluates to true; returns true if such an *x* exists, otherwise false.

[*all p sli*] applies *p* to each element *x* of *sli*, from left to right, until *p(x)* evaluates to false; returns false if such an *x* exists, otherwise true.

[*app f sli*] applies *f* to all elements of *sli* = (*a*,*i*,*n*), from left to right. That is, applies *f* to *a*[*j*+*i*] for *j*=0,1,...,*n*.

[*map f sli*] applies *f* to all elements of *sli* = (*a*,*i*,*n*), from left to right, and returns a vector of the results.

[*foldl f e sli*] folds function *f* over *sli* = (*a*,*i*,*n*) from left to right. That is, computes *f*(*a*[*i+n-1*], *f*(*a*[*i+n-2*], ..., *f*(*a*[*i*+1], *f*(*a*[*i*], *e*))...).

[*foldr f e sli*] folds function *f* over *sli* = (*a*,*i*,*n*) from right to left. That is, computes *f*(*a*[*i*], *f*(*a*[*i*+1], ..., *f*(*a*[*i+n-2*], *f*(*a*[*i+n-1*], *e*))...).

The following iterators generalize the above ones by also passing the index into the vector *a* underlying the slice to the function being iterated.

[*findi p sli*] applies *p* to the elements of *sli* = (*a*,*i*,*n*) and the underlying vector indices, and returns the least (*j*, *a*[*j*]) for which *p*(*j*, *a*[*j*]) evaluates to true, if any; otherwise returns NONE. That is, evaluates *p*(*j*, *a*[*j*]) for *j*=*i*,..*i+n-1* until it evaluates to true for some *j*, then returns *SOME(j, a[j])*; otherwise returns NONE.

[*appi f sli*] applies *f* to the slice *sli* = (*a*,*i*,*n*) and the underlying vector indices. That is, applies *f* to successive pairs (*j*, *a*[*j*]) for *j*=*i*,*i*+1,...,*i+n-1*.

[*mapi f sli*] applies *f* to the slice *sli* = (*a*,*i*,*n*) and the underlying vector indices, and returns a vector of the results. That is, applies *f* to successive pairs (*j*, *a*[*j*]) for *j*=*i*,*i*+1,...,*i+n-1*, and returns #[*f*(*i*,*a*[*i*]), ..., *f*(*i+n-1*, *a*[*i+n-1*])].

[*foldli f e sli*] folds function *f* over the slice *sli* = (*a*,*i*,*n*) and the underlying vector indices from left to right. That is, computes *f*(*i+n-1*, *a*[*i+n-1*], *f*(..., *f*(*i*+1, *a*[*i*+1], *f*(*i*, *a*[*i*], *e*)) ...).

[*foldri f e sli*] folds function *f* over the slice *sli* = (*a*,*i*,*n*) and the underlying vector indices from right to left. That is, computes *f*(*i*, *a*[*i*], *f*(*i*+1, *a*[*i*+1], ..., *f*(*i+n-1*, *a*[*i+n-1*], *e*)) ...).

[*collate cmp (sli1, sli2)*] returns LESS, EQUAL or GREATER according as *sli1* precedes, equals or follows *sli2* in the lexicographic ordering on slices induced by the ordering *cmp* on elements.

Module Weak

Weak --- weak pointers and arrays of weak pointers

Single weak pointers

```
type 'a weak
val weak      : 'a -> 'a weak
val set       : 'a weak * 'a -> unit
val get       : 'a weak -> 'a
val isweak    : 'a weak -> bool
```

Arrays of weak pointers

```
prim_EQtype , a array
```

```
val maxLen : int
```

```

val array      : int -> 'a array      Raises Size
val sub        : 'a array * int -> 'a   Raises Fail and Subscript
val update     : 'a array * int * 'a -> unit  Raises Subscript
val isequal    : 'a array * int -> bool   Raises Subscript
val length     : 'a array -> int

```

```

: ('a -> unit) -> 'a array -> unit
val app
: ('a * 'b -> 'b) -> 'b -> 'a array -> 'b
val foldl
: ('a * 'b -> 'b) -> 'b -> 'a array -> 'b
val foldr
: ('a -> 'a) -> 'a array -> unit
val modify

```

```

val appi      : (int * 'a -> unit) -> 'a array * int * int option -> unit
val foldl1   : (int * 'a * 'b -> 'b) -> 'a array * int * int option -> 'b
val foldl    : (int * 'a * 'b -> 'b) -> 'a array * int * int option -> 'b

```

[`'a weak`] is the type of weak pointers to objects of type `'a`. A weak pointer is a pointer that cannot itself keep an object alive. Hence the object pointed to by a weak pointer may be deallocated by the garbage collector if the object is reachable only by weak pointers. In this case, subsequent accesses via the `'get` function will raise `Fail "Dangling weak pointer"`. (We raise an exception instead of returning an option value, because access via a weak pointer to a deallocated object is likely to be a programming error).

Integers, characters, words and booleans will not be deallocated by the garbage collector, and will remain reachable forever by a weak pointer. Reals, strings, tuples and other non-nullary constructors may be deallocated by the garbage collector. Constants, even composite ones, will not be deallocated either.

`[weak v]` creates and returns a weak pointer to value `v`.

[get w] returns the value pointed to by weak pointer w, if the value is still alive. Otherwise raises Fail "Dangling weak pointer".

`[set(w, v)]` makes the weak pointer `w` point to the value `v`.

`lisweak_wl` returns true if the value pointed to by `w` is dead; returns false otherwise. If an object is reported to be dead, it remains dead. However, an object is reported to be live just if it has not yet been deallocated by the garbage collector. The allocation of any new value may activate the garbage collector and cause the object to die. Thus

```

will not raise exception Fail, whereas the following might:
    if not (isweak w) then ([1,2] @ [3,4]; get w) else "bl
because evaluation of the list append may cause w to die.

```

The value of isweak is the same as that of

WEAK

(get w; false) handle Fail _ => true
but evaluating the latter expression may have the side effect of
keeping w alive for slightly longer, because a pointer to w
returned by get w.

...

`['a array']` is the type of arrays of weak pointers to objects of type 'a'.

A value of type `'a Weak.weak` (above) is equivalent to, but more efficient than, a one-element `'a Weak.array`. On the other hand, an `'a Weak.array` is more efficient than an `('a Weak.weak) Array.array`.

[array n] creates an array of n weak pointers. Initially, any access to the array will raise Fail.

[sub(a, i)] returns the object pointed to by cell i (counting from 0) of the array a, if it is live. Raises fail "dangling weak pointer" if cell i has never been updated or if the object pointed to has been deallocated by the garbage collector. Raises Subscript if l < 0 or l > length a. To make 'sub' infix, use the declaration

```
infix 9 sub
```

[update(a, i, v)] updates cell i of array a to point (weakly) to the value v. Raises Subscript if i<0 or i>=length a

`[isdead(a, i)]` returns true if the object in cell `i` of array `a` is dead, and false otherwise. Analogous to `isweak`; see above.

`[length a]` returns the number of elements in `a`.

`[maxLen]` is the maximal number of elements in an array.

The iterators described below operate on the live elements only. Note that an element `a[k]` may die in the course of folding `f` over earlier elements (e.g. `a[1] ... a[k-1]`). Thus the functions should be used with great care.

[foldl f e a] folds function f over the live elements of a, from left to right.

[foldr f e a] folds function f over the live elements of a, from right to left.

[app f a] applies f to the live elements of a from left to right.

```
[modify f a] applies f to a[j] and updates a[j] with the result
f(a[j]), for each live element a[j], from left to right.
```

The following iterators generalize the above ones in two ways:

- the index `j` is also being passed to the function being iterated;
- the iterators work on a slice (subarray) of an array

The slice `(a, i, SOME n)` denotes the subarray `a[i..i+n-1]`. That is, `a[i]` is the first element of the slice, and `n` is the length of the slice. Valid only if `0 <= i <= i+n <= length a`.

The slice `(a, i, NONE)` denotes the subarray `a[i..length a-1]`. That is, the slice denotes the suffix of the array starting at `i`. Valid only if `0 <= i <= length a`. Equivalent to `(a, i, SOME(length a - i))`.

| slice | meaning |
|-----------------------------|---------------------------|
| <code>(a, 0, None)</code> | the whole array |
| <code>(a, 0, SOME n)</code> | a left subarray (prefix) |
| <code>(a, i, None)</code> | a right subarray (suffix) |
| <code>(a, i, SOME n)</code> | a general slice |

[foldl f e (a, i, SOME n)] folds function f over the live elements of the subarray a[i..n-1] from left to right. Raises Subscript

```

if i<0 or n<0 or i+n > length a.

[foldl f e (a, i, NONE)] folds function f over the live elements
of the subarray a[i..len-1] from left to right, where len = length
a. Raises Subscript if i<0 or i > length a.

[foldr f e (a, i, SOME n)] folds function f over the live elements
of the subarray a[i..i+n-1] from right to left. Raises Subscript
if i<0 or n<0 or i+n > length a.

[foldri f e (a, i, NONE)] folds function f over the live elements
of the subarray a[i..len-1] from right to left, where len = length
a. Raises Subscript if i<0 or i > length a.

[appi f (a, i, SOME n)] applies f to successive pairs (j, a[j]) for
j=i,i+1,...,i+n-1, provided a[j] is live. Raises Subscript if i<0
or n<0 or i+n > length a.

[appi f (a, i, NONE)] applies f to successive pairs (j, a[j]) for
j=i,i+1,...,len-1, where len = length a, provided a[j] is live.
Raises Subscript if i<0 or i > length a.

[modifi f (a, i, SOME n)] applies f to (j, a[j]) and updates a[j]
with the result f(j, a[j]) for j=i,i+1,...,i+n-1, provided a[j] is
live. Raises Subscript if i<0 or n<0 or i+n > length a.

[modifi f (a, i, NONE)] applies f to (j, a[j]) and updates a[j]
with the result f(j, a[j]) for j=i,i+1,...,len-1, provided a[j] is
live. Raises Subscript if i<0 or i > length a.

```

Module Word

Word -- *SML Basis Library*

```

type word = word

val wordSize      : int
val orb           : word * word -> word
val andb          : word * word -> word
val xorb          : word * word -> word
val notb          : word -> word
val ~             : word -> word

val <<            : word * word -> word
val >>            : word * word -> word
val ~->>          : word * word -> word

val +             : word * word -> word
val -             : word * word -> word
val *             : word * word -> word
val div           : word * word -> word
val mod           : word * word -> word

val >             : word * word -> bool
val <             : word * word -> bool
val =             : word * word -> bool
val <=            : word * word -> bool
val compare       : word * word -> order

val min           : word * word -> word
val max           : word * word -> word

val toString      : word -> string
val fromString    : string -> word option
val scan          : StringCvt.radix
                  -> (char, 'a) StringCvt.reader -> (word, 'a) StringCvt.reader
val fmt           : StringCvt.radix -> word -> string

val toInt         : word -> int
val toIntX        : word -> int
val fromInt       : int -> word
                                with sign extension

val toLargeWord   : word -> word
val toLargeWordX  : word -> word
val fromLargeWord : word -> word
                                with sign extension

val toLargeInt    : word -> int
val toLargeIntX   : word -> int
val fromLargeInt  : int -> word
                                with sign extension

[word] is the type of n-bit words, or n-bit unsigned integers.

[wordSize] is the value of n above. In Moscow ML, n=31 on 32-bit
machines and n=63 on 64-bit machines.

[orb(w1, w2)] returns the bitwise 'or' of w1 and w2.

[andb(w1, w2)] returns the bitwise 'and' of w1 and w2.

[xorb(w1, w2)] returns the bitwise 'exclusive or' of w1 and w2.

[notb w] returns the bitwise negation (one's complement) of w.

[~ w] returns the arithmetic negation (two's complement) of w.

[<<(w, k)] returns the word resulting from shifting w left by k
bits. The bits shifted in are zero, so this is a logical shift.
Consequently, the result is 0-bits when k >= wordSize.

[>>(w, k)] returns the word resulting from shifting w right by k

```

bits. The bits shifted in are zero, so this is a logical shift. Consequently, the result is 0-bits when `k >= wordSize`.

`[~>(w, k)]` returns the word resulting from shifting `w` right by `k` bits. The bits shifted in are replications of the left-most bit: the 'sign bit', so this is an arithmetical shift. Consequently, and for `k >= wordSize` and `wordInt w >= 0` the result is all 0-bits, and for `k >= wordSize` and `wordInt w < 0` the result is all 1-bits.

To make `<<`, `>>`, and `~>` infix, use the declaration

```
infix 5 << >> ~>
```

`[+]`
`[-]`
`[*]`
`[div]`
`[mod]` represent unsigned integer addition, subtraction, multiplication, division, and remainder, modulus 2 raised to the `n`'th power, where `n=wordSize`. The operations `(i div j)` and `(i mod j)` raise `Div` when `j=0`. Otherwise no exceptions are raised.

`[<]`
`[<=]`
`[>]`
`[>=]` compare words as unsigned integers.

`[compare(w1, w2)]` returns `LESS`, `EQUAL`, or `GREATER`, according as `w1` is less than, equal to, or greater than `w2` (as unsigned integers).

`[min(w1, w2)]` returns the smaller of `w1` and `w2` (as unsigned integers).

`[max(w1, w2)]` returns the larger of `w1` and `w2` (as unsigned integers).

`[fmt radix w]` returns a string representing `w`, in the radix (base) specified by `radix`.

| radix | description | output format |
|-------|--------------------------------|---------------|
| ----- | | |
| BIN | unsigned binary (base 2) | [01]+ |
| OCT | unsigned octal (base 8) | [0-7]+ |
| DEC | unsigned decimal (base 10) | [0-9]+ |
| HEX | unsigned hexadecimal (base 16) | [0-9A-F]+ |

`[toString w]` returns a string representing `w` in unsigned hexadecimal format. Equivalent to `(fmt HEX w)`.

`[fromString s]` returns `SOME(w)` if a hexadecimal unsigned numeral can be scanned from a prefix of string `s`, ignoring any initial whitespace; returns `NONE` otherwise. Raises `Overflow` if the scanned number cannot be represented as a word. An unsigned hexadecimal numeral must have form, after possible initial whitespace:

```
[0-9a-fA-F]+
```

`[scan radix getc charsrc]` attempts to scan an unsigned numeral from the character source `charsrc`, using the accessor `getc`, and ignoring any initial whitespace. The `radix` argument specifies the base of the numeral (BIN, OCT, DEC, HEX). If successful, it returns `SOME(w, rest)` where `w` is the value of the numeral scanned, and `rest` is the unused part of the character source. Raises `Overflow` if the scanned number cannot be represented as a word. A numeral must have form, after possible initial whitespace:

```
radix  input format
-----
BIN    (0w)?[0-1]+
OCT    (0w)?[0-7]+
DEC    (0w)?[0-9]+
HEX    (0wx|0wX|0x|0X)?[0-9a-fA-F]+
```

`[toInt w]` returns the (signed) integer represented by bit-pattern `w`.
`[toIntX w]` returns the (signed) integer represented by bit-pattern `w`.
`[fromInt i]` returns the word representing integer `i`.

`[toLargeInt w]` returns the (signed) integer represented by bit-pattern `w`.
`[toLargeIntX w]` returns the (signed) integer represented by bit-pattern `w`.
`[fromLargeInt i]` returns the word representing integer `i`.

`[toLargeWord w]` returns `w`.
`[toLargeWordX w]` returns `w`.
`[fromLargeWord w]` returns `w`.

Module Word8

Word8 -- SML Basis Library

```
type word = word8

val wordSize : int

val orb : word * word -> word
val andb : word * word -> word
val xorb : word * word -> word
val notb : word -> word
val ~ : word -> word

val << : word * Word.word -> word
val >> : word * Word.word -> word
val ~>> : word * Word.word -> word

val + : word * word -> word
val - : word * word -> word
val * : word * word -> word
val div : word * word -> word
val mod : word * word -> word

val > : word * word -> bool
val < : word * word -> bool
val <= : word * word -> bool
val >= : word * word -> bool
val compare : word * word -> order

val min : word * word -> word
val max : word * word -> word

val toString : word -> string
val fromString : string -> word option
val scan : StringCvt.radix : StringCvt.radix -> (char, 'a) StringCvt.reader -> (word, 'a) StringCvt.reader -> StringCvt.radix -> word -> string
val fmt : StringCvt.radix -> word -> string

val toInt : word -> int
val toIntX : word -> int
val fromInt : int -> word

val toLargeInt : word -> int
val toLargeIntX : word -> int
val fromLargeInt : int -> word

val toLargeWord : word -> Word.word
val toLargeWordX : word -> Word.word
val fromLargeWord : Word.word -> word

[word] is the type of 8-bit words, or 8-bit unsigned integers in the range 0..255.
[wordSize] equals 8.
[orb(w1, w2)] returns the bitwise 'or' of w1 and w2.
[andb(w1, w2)] returns the bitwise 'and' of w1 and w2.
[xorb(w1, w2)] returns the bitwise 'exclusive or' of w1 and w2.
[notb w] returns the bitwise negation (one's complement) of w.
[~ w] returns the arithmetic negation (two's complement) of w.
[<<(w, k)] returns the word resulting from shifting w left by k bits. The bits shifted in are zero, so this is a logical shift. Consequently, the result is 0-bits when k >= wordSize.
[>>(w, k)] returns the word resulting from shifting w right by k
```

```
bits. The bits shifted in are zero, so this is a logical shift. Consequently, the result is 0-bits when k >= wordSize.

[~>>(w, k)] returns the word resulting from shifting w right by k bits. The bits shifted in are replications of the left-most bit: the 'sign bit', so this is an arithmetical shift. Consequently, for k >= wordSize and wordPoint w >= 0 the result is all 0-bits, and for k >= wordSize and wordPoint w < 0 the result is all 1-bits.

To make <<, >>, and ~>> infix, use the declaration:
infix 5 << >> ~>>

[+]
[-]
[*]
[div]
[mod] represent unsigned integer addition, subtraction, multiplication, division, and remainder, modulus 256. The operations (i div j) and (i mod j) raise Div when j = 0. Otherwise no exceptions are raised.

[<]
[<=]
[>]
[>=] compare words as unsigned integers.

[compare(w1, w2)] returns LESS, EQUAL, or GREATER, according as w1 is less than, equal to, or greater than w2 (as unsigned integers).

[min(w1, w2)] returns the smaller of w1 and w2 (as unsigned integers).

[max(w1, w2)] returns the larger of w1 and w2 (as unsigned integers).

[fmt radix w] returns a string representing w, in the radix (base) specified by radix.

radix  description                               output format
-----
BIN    unsigned binary (base 2) [01]+
OCT    unsigned octal (base 8)  [0-7]+
DEC    unsigned decimal (base 10) [0-9]+
HEX    unsigned hexadecimal (base 16) [0-9A-F]+

[toString w] returns a string representing w in unsigned hexadecimal format. Equivalent to (fmt HEX w).

[fromString s] returns SOME(w) if a hexadecimal unsigned numeral can be scanned from a prefix of string s, ignoring any initial whitespace; returns NONE otherwise. Raises Overflow if the scanned number cannot be represented as a word. An unsigned hexadecimal numeral must have form, after possible initial whitespace:
[0-9a-fA-F]+

[scan radix {getc} charsrc] attempts to scan an unsigned numeral from the character source charsrc, using the accessor getc, and ignoring any initial whitespace. The radix argument specifies the base of the numeral (BIN, OCT, DEC, HEX). If successful, it returns SOME(w, rest) where w is the value of the numeral scanned, and rest is the unused part of the character source. Raises Overflow if the scanned number cannot be represented as a word. A numeral must have form, after possible initial whitespace:

radix  input format
-----
BIN    (0w)?[0-1]+
OCT    (0w)?[0-7]+
DEC    (0w)?[0-9]+
HEX    (0wx|[0wx][0x]?[0-9a-fA-F]+

[toInt w] returns the integer in the range 0..255 represented by w.

[toIntX w] returns the signed integer (in the range ~128..127)
```

represented by bit-pattern *w*.

[fromInt *i*] returns the word holding the 8 least significant bits of *i*.

[toLargeInt *w*] returns the integer in the range 0..255 represented by *w*.

[toLargeIntX *w*] returns the signed integer (in the range ~128..127) represented by bit-pattern *w*.

[fromLargeInt *i*] returns the word holding the 8 least significant bits of *i*.

[toLargeWord *w*] returns the Word.word value corresponding to *w*.

[toLargeWordX *w*] returns the Word.word value corresponding to *w*, with sign extension. That is, the 8 least significant bits of the result are those of *w*, and the remaining bits are all equal to the most significant bit of *w*: its 'sign bit'.

[fromLargeWord *w*] returns *w* modulo 256.

Module Word8Array

Word8Array -- *SML Basis Library*

```
eqtype array
type elem = Word8.word
type vector = Word8Vector.vector

val maxLen      : int
val array       : int * elem -> array
val tabulate    : int * (int -> elem) -> array
val fromList    : elem list -> array
val length      : array -> int
val sub         : array * int -> elem
val update      : array * int * elem -> unit
val vector      : array -> vector
val copy        : {src: array, dst: array, di: int} -> unit
val copyVec     : {src: vector, dst: array, di: int} -> unit
val find        : (elem -> bool) -> array -> elem option
val exists      : (elem -> bool) -> array -> bool
val all         : (elem -> bool) -> array -> bool
val app         : (elem -> unit) -> array -> unit
val foldl       : (elem * 'b -> 'b) -> 'b -> array -> 'b
val foldr       : (elem * 'b -> 'b) -> 'b -> array -> 'b
val modify      : (elem -> elem) -> array -> unit
val findi       : (int * elem -> bool) -> array -> (int * elem) option
val appi        : (int * elem -> unit) -> array -> unit
val foldli      : (int * elem * 'b -> 'b) -> 'b -> array -> 'b
val foldri      : (int * elem * 'b -> 'b) -> 'b -> array -> 'b
val modifyi     : (int * elem -> elem) -> array -> unit
val collate     : (elem * elem -> order) -> array * array -> order
```

[array] is the type of one-dimensional, mutable, zero-based constant-time-access arrays with elements of type Word8.word, that is, 8-bit words. Arrays *a1* and *a2* are equal if both were created by the same call to a primitive (array0, array, tabulate, fromList).

All operations are as for Array.array.

Module Word8ArraySlice

Word8ArraySlice -- *SML Basis Library*

```
type elem = Word8.word
type array = Word8Array.array
type vector = Word8Vector.vector
type vector_slice = Word8VectorSlice.slice

type slice
  : slice -> int
  : slice * int -> elem
  : slice * int * elem -> unit
  : array * int * int option -> slice
  : array -> slice
  : array * slice
  : slice * int * int option -> slice
  : slice * array * int * int
  : slice -> vector
  : {src: slice, dst: array, di: int} -> unit
  : {src: vector_slice, dst: array, di: int} -> unit
  : slice -> bool
  : slice * slice -> (elem * slice) option
  : (elem -> bool) -> slice -> elem option
  : (elem -> bool) -> slice -> bool
  : (elem -> bool) -> slice -> bool
  : (elem -> unit) -> slice -> unit
  : (elem * 'b -> 'b) -> 'b -> slice -> 'b
  : (elem * 'b -> 'b) -> 'b -> slice -> 'b
  : (elem -> elem) -> slice -> unit
  : (int * elem -> bool) -> slice -> (int * elem) option
  : (int * elem -> unit) -> slice -> unit
  : (int * elem * 'b -> 'b) -> 'b -> slice -> 'b
  : (int * elem * 'b -> 'b) -> 'b -> slice -> 'b
  : (int * elem -> elem) -> slice -> unit
  : (elem * elem -> order) -> slice * slice -> order
```

[slice] is the type of Word8Array slices, that is, sub-arrays of Word8Array.array values.
The slice (a,i,n) is valid if 0 <= i <= i+n <= size s,
or equivalently, 0 <= i and 0 <= n and i+n <= size s.
A valid slice sli = (a,i,n) represents the sub-array a[i..i+n-1],
so the elements of sli are a[i], a[i+1], ..., a[i+n-1], and n is
the length of the slice. Only valid slices can be constructed by
the functions below.

All operations are as for ArraySlice.slice.

Module Word8Vector

Word8Vector -- *SML Basis Library*

```
eqtype vector
type elem = Word8.word

val maxLen      : int
val fromList    : elem list -> vector
val tabulate    : int * (int -> elem) -> vector

val length      : vector -> int
val sub         : vector * int -> elem
val update      : vector * int * elem -> vector
val concat      : vector list -> vector

val find        : (elem -> bool) -> vector -> elem option
val exists      : (elem -> bool) -> vector -> bool
val all         : (elem -> bool) -> vector -> bool

val app         : (elem -> unit) -> vector -> unit
val map         : (elem -> elem) -> vector -> vector
val foldl       : (elem * 'b -> 'b) -> 'b -> vector -> 'b
val foldr       : (elem * 'b -> 'b) -> 'b -> vector -> 'b

val findi       : (int * elem -> bool) -> vector -> (int * elem) option
val appi        : (int * elem -> unit) -> vector -> unit
val mapi        : (int * elem -> elem) -> vector -> vector
val foldli       : (int * elem * 'b -> 'b) -> 'b -> vector -> 'b
val foldri       : (int * elem * 'b -> 'b) -> 'b -> vector -> 'b

val collate     : (elem * elem -> order) -> vector * vector -> order
```

[vector] is the type of one-dimensional, immutable, zero-based constant-time-access vectors with elements of type Word8.word, that is, 8-bit words. Type vector admits equality, and vectors v1 and v2 are equal if they have the same length and their elements are equal.

All operations are as for Vector.vector.

value (Word8), 152, 153
A_EXEC
 constructor (FileSys), 38
A_READ
 constructor (FileSys), 38
A_WRITE
 constructor (FileSys), 38
abrt
 value (Signal), 115
Abs
 exception (SML90), 114
abs
 value (General), 46, 48
 value (Int), 50
 value (Real), 108
accept
 value (Socket), 117, 118
access
 type (FileSys), 37, 38
 value (FileSys), 37, 38
acos
 value (Math), 64
active
 type (Socket), 117, 118
add
 value (Binaryset), 16
 value (Gdbm), 40, 41
 value (Intset), 53
 value (Polygdbm), 98
 value (Splayset), 123
 add_break
 value (PP), 90
 add_newline
 value (PP), 90, 91
 add_string
 value (PP), 90, 91
 add_list
 value (Binaryset), 16
 value (Intset), 53
 value (Splayset), 123
 address
 value (Msp), 76, 78
 ahref
 value (Msp), 76, 78
 ahrefa
 value (Msp), 76, 78
all
 value (Array), 3, 4
 value (ArraySlice), 8, 9
 value (CharArray), 26
 value (CharArraySlice), 27
 value (CharVector), 28
 value (CharVectorSlice), 29
 value (List), 57, 58
 value (ListPair), 59
 value (Substring), 130, 131
 value (Vector), 142

app4
 value (Callback), 20, 21
 value (Dynlib), 35, 36
app5
 value (Callback), 20, 22
 value (Dynlib), 35, 36
appEq
 value (ListPair), 59, 60
appi
 value (Array), 3, 4
 value (Array2), 5, 7
 value (ArraySlice), 8, 9
 value (CharArray), 26
 value (CharArraySlice), 27
 value (CharVector), 28
 value (CharVectorSlice), 29
 value (Vector), 142, 143
 value (VectorSlice), 144, 145
 value (Weak), 146, 148
 value (Word8Array), 155
 value (Word8ArraySlice), 156
 value (Word8Vector), 157
 value (Word8VectorSlice), 158
AppleScript
 AppleScriptErr
 exception (AppleScript), 2
 apply
 value (Polynash), 100
 applyto
 value (Mysql), 82, 84
 value (Postgres), 103, 105
 arctan
 value (NJ93), 85
 value (SML90), 114
 area
 value (Msp), 76, 79
 arguments
 value (CommandLine), 30
 argv
 value (Mosml), 70
 Array (structure), 3–4
 array
 type (Array), 3
 type (Array2), 5
 type (CharArray), 26
 type (CharArraySlice), 27
 type (Dynarray), 34
 type (Weak), 146, 147
 type (Word8Array), 155
 type (Word8ArraySlice), 156
 value (Array), 3
 value (Array2), 5
 value (CharArray), 26
 value (Dynarray), 34
 value (Weak), 146, 147
 value (Word8Array), 155
 Array2 (structure), 5–7
 value (VectorSlice), 144, 145
 value (Word8Array), 155
 value (Word8Vector), 157
 value (Word8VectorSlice), 158
 allCookies
 value (Mosmlcookie), 74
 alleq
 value (ListPair), 59, 60
 AlreadyThere
 exception (Gdbm), 40
 exception (Polygdbm), 98
 alarm
 value (Signal), 115
 aname
 value (Msp), 76, 78
 andb
 value (Word), 149
 value (Word8), 152
 app
 value (Array), 3, 4
 value (Array2), 5, 6
 value (ArraySlice), 8, 9
 value (Binarymap), 15
 value (Binaryset), 16, 17
 value (CharArray), 26
 value (CharArraySlice), 27
 value (CharVector), 28
 value (CharVectorSlice), 29
 value (Gdbm), 40, 41
 value (Intmap), 52
 value (Intset), 53
 value (List), 57, 58
 value (ListPair), 59
 value (NJ93), 85
 value (Option), 89
 value (Polygdbm), 98, 99
 value (Regex), 110, 112
 value (Splaymap), 122
 value (Splayset), 123, 124
 value (Substring), 130, 133
 value (Vector), 142, 143
 value (VectorSlice), 144, 145
 value (Weak), 146, 147
 value (Word8Array), 155
 value (Word8ArraySlice), 156
 value (Word8Vector), 157
 value (Word8VectorSlice), 158
 app1
 value (Callback), 20, 21
 value (Dynlib), 35, 36
 app2
 value (Callback), 20, 21
 value (Dynlib), 35, 36
 app3
 value (Callback), 20, 21
 value (Dynlib), 35, 36
 ArraySlice (structure), 8–10
 Arraysort (structure), 11
 as_compile
 value (AppleScript), 2
 as_dispose
 value (AppleScript), 2
 as_run_script
 value (AppleScript), 2
 as_run_text
 value (AppleScript), 2
 asin
 value (Math), 64
 atan
 value (Math), 64
 atan2
 value (Math), 64
 atExit
 value (Process), 106
 backtrack
 value (Lexing), 55
 base
 value (ArraySlice), 8, 9
 value (CharArraySlice), 27
 value (CharVectorSlice), 29
 value (Path), 95, 97
 value (Substring), 130, 131
 value (VectorSlice), 144, 145
 value (Word8ArraySlice), 156
 value (Word8VectorSlice), 158
 before
 value (General), 45, 47
 begin_block
 value (PP), 90, 91
 Binarymap (structure), 15
 Binaryset (structure), 16–17
 Bind
 exception (General), 45, 47
 bind
 value (Socket), 117, 118
 BinIO (structure), 12–14
 blockquote
 value (Msp), 75, 78
 blockquotea
 value (Msp), 75, 78
 body
 value (Msp), 75, 78
 bodya
 value (Msp), 75, 78
 Bool (structure), 18
 bool
 type (Bool), 18
 type (General), 45, 46
 bound
 value (Dynarray), 34
 br
 value (Msp), 75, 78
 bra

value (Msp), 75, 78
break_style
type (PP), 90
browser
value (Help), 49
bucketSizes
value (Polyhash), 100, 101
buf
type (Socket), 117, 119
buff_input
value (NonstdIo), 87
buff_output
value (NonstdIo), 87
bus
value (Signal), 115
Byte (structure), 19
bytesToString
value (Byte), 19
byteToChar
value (Byte), 19
Callback (structure), 20-22
can_input
value (NJ93), 86
caption
value (Msp), 76, 79
captiona
value (Msp), 76, 79
ceil
value (General), 45, 48
value (Real), 108, 109
ceiling
value (NJ93), 85
center
value (Msp), 75, 78
cfIag
type (Regex), 110, 111
cgi_annotation_server
value (Mosmlcgi), 71, 73
cgi_api_version
value (Mosmlcgi), 71, 73
cgi_auth_type
value (Mosmlcgi), 71
cgi_content_length
value (Mosmlcgi), 71, 73
cgi_content_type
value (Mosmlcgi), 71
cgi_document_root
value (Mosmlcgi), 71, 73
cgi_field_integer
value (Mosmlcgi), 71, 72
cgi_field_string
value (Mosmlcgi), 71, 72
cgi_field_strings
value (Mosmlcgi), 71, 72
cgi_fieldnames
value (Mosmlcgi), 71, 72
cgi_gateway_interface
value (Mosmlcgi), 71, 72
value (Mosmlcgi), 71, 73
cgi_http_accept
value (Mosmlcgi), 71, 73
cgi_http_cookie
value (Mosmlcgi), 71, 73
cgi_http_forwarded
value (Mosmlcgi), 71, 73
cgi_http_host
value (Mosmlcgi), 71, 73
cgi_http_proxy_connection
value (Mosmlcgi), 71, 73
cgi_http_referer
value (Mosmlcgi), 71, 73
cgi_http_user_agent
value (Mosmlcgi), 71, 73
cgi_is_subreq
value (Mosmlcgi), 71, 73
cgi_part
value (Mosmlcgi), 71, 72
cgi_partnames
value (Mosmlcgi), 71, 72
cgi_parts
value (Mosmlcgi), 71, 72
cgi_path_info
value (Mosmlcgi), 71, 73
cgi_path_translated
value (Mosmlcgi), 71, 73
cgi_query_string
value (Mosmlcgi), 71, 73
cgi_remote_addr
value (Mosmlcgi), 71, 73
cgi_remote_host
value (Mosmlcgi), 71, 73
cgi_remote_ident
value (Mosmlcgi), 71, 73
cgi_remote_user
value (Mosmlcgi), 71, 73
cgi_request_filename
value (Mosmlcgi), 71, 73
cgi_request_method
value (Mosmlcgi), 71, 73
cgi_request_uri
value (Mosmlcgi), 71, 73
cgi_script_filename
value (Mosmlcgi), 71, 73
cgi_script_name
value (Mosmlcgi), 71, 73
cgi_server_admin
value (Mosmlcgi), 71, 73
cgi_server_name
value (Mosmlcgi), 71, 72
cgi_server_port
value (Mosmlcgi), 71, 73
cgi_server_protocol
value (Mosmlcgi), 71, 73
cgi_server_software
value (Mosmlcgi), 71, 72

cgi_the_request
value (Mosmlcgi), 71, 73
Char (structure), 23-25
char
type (Char), 23
type (General), 45, 46
value (Gdimage), 42, 44
CharArray (structure), 26
CharArraySlice (structure), 27
charsize
value (Gdimage), 42, 44
charToByte
value (Byte), 19
charUp
value (Gdimage), 42, 44
CharVector (structure), 28
CharVectorSlice (structure), 29
chDir
value (FileSys), 37
checkCPUTime
value (Timer), 140
checkGCTime
value (Timer), 140
checkRealTime
value (Timer), 140
child
value (Signal), 115
Chr
exception (General), 45
chr
value (Char), 23
value (NJ93), 85
value (SML90), 114
clear_ppstream
value (PP), 90, 91
clearParser
value (Parsing), 93, 94
close
value (Socket), 117, 119
close_in
value (NJ93), 85
value (SML90), 114
close_out
value (NJ93), 85
value (SML90), 114
closebase
value (Mysql), 81, 82
value (Postgres), 102, 103
Closed
exception (Dynlib), 35
exception (Gdbm), 40
exception (Mysql), 81
exception (Polygdbm), 98
exception (Postgres), 102
closeDir
value (FileSys), 37
closeIn
value (Meta), 66, 67
compileStructure
value (Meta), 66, 67
compileTopLevel
value (Meta), 66, 67
compose
value (Option), 89
composePartial
value (Option), 89
value (BinIO), 12
value (TextIO), 135
closeOut
value (BinIO), 12, 13
value (TextIO), 135, 136
cmdtuples
value (MysqI), 81, 83
value (Postgres), 102, 104
collate
value (Array), 3, 4
value (ArraySlice), 8, 10
value (CharArray), 26
value (CharArraySlice), 27
value (CharVector), 28
value (CharVectorSlice), 29
value (List), 57, 58
value (String), 125, 126
value (Substring), 130, 131
value (Vector), 142, 143
value (VectorSlice), 144, 145
value (Word8Array), 155
value (Word8ArraySlice), 156
value (Word8Vector), 157
value (Word8VectorSlice), 158
ColMajor
constructor (Array2), 5
color
constructor (Gdimage), 43
type (Gdimage), 42, 43
value (Gdimage), 42, 43
column
value (Array2), 5, 6
comment
value (Msp), 75, 78
compare
value (Char), 23, 25
value (Date), 31, 32
value (FileSys), 37, 39
value (Int), 50, 51
value (Real), 108
value (Socket), 117, 120
value (String), 125, 126
value (Substring), 130, 131
value (Time), 138, 139
value (Word), 149, 150
value (Word8), 152, 153
compile
value (Meta), 66, 67
compileStructure
value (Meta), 66, 67
compileTopLevel
value (Meta), 66, 67
compose
value (Option), 89
composePartial
value (Option), 89

concat
 value (CharVector), 28
 value (CharVectorSlice), 29
 value (List), 57, 58
 value (Path), 95, 96
 value (String), 125
 value (Substring), 130, 131
 value (Vector), 142
 value (VectorSlice), 144, 145
 value (Word8Vector), 157
 value (Word8VectorSlice), 158
concatWith
 value (String), 125
 value (Substring), 130, 131
connect
 value (Socket), 117, 119
conservative
 value (Meta), 66, 67
CONSISTENT
 constructor (PP), 90
cont
 value (Signal), 115
contains
 value (Char), 23, 24
cookieData
 type (Mosmlcookie), 74
CookieError
 exception (Mosmlcookie), 74
copy
 value (Array), 3
 value (Array2), 5, 7
 value (ArraySlice), 8, 9
 value (CharArray), 26
 value (CharArraySlice), 27
 value (Gdimage), 42, 44
 value (Polyhash), 100, 101
 value (Word8Array), 155
 value (Word8ArraySlice), 156
copyResize
 value (Gdimage), 42, 44
copyTableFrom
 value (Mysql), 82, 84
 value (Postgres), 103, 105
copyTableTo
 value (Mysql), 82, 84
 value (Postgres), 103, 105
copyVec
 value (Array), 3, 4
 value (ArraySlice), 8, 9
 value (CharArray), 26
 value (CharArraySlice), 27
 value (Word8Array), 155
 value (Word8ArraySlice), 156
cos
 value (Math), 64
 value (N93), 85
 value (SML90), 114

cosh
 value (Math), 64
cptr
 type (Callback), 20, 21
cpu_timer
 type (Timer), 140
createLexer
 value (Lexing), 55
createLexerString
 value (Lexing), 55
cs
 type (StringCvt), 128
 type (TextIO), 135
currentArc
 value (Path), 95, 96
Date
 exception (Date), 31
Date (structure), 31–33
date
 type (Date), 31
 value (Date), 31
datum
 type (Gdbm), 40
day
 value (Date), 31, 32
db
 value (Mysql), 81, 82
 value (Postgres), 102, 103
dbConn
 type (Mysql), 81, 82
 type (Postgres), 102, 103
dbResult
 type (Mysql), 81, 82
 type (Postgres), 102, 103
dbResultStatus
 type (Mysql), 81
 type (Postgres), 102
dd
 value (Msp), 76, 79
dec
 value (N93), 85
default
 value (Dynarray), 34
defaultBrowser
 value (Help), 49
delay
 value (Susp), 134
delete
 value (Binaryset), 16
 value (Intset), 53
 value (Splayset), 123
deleteCookie
 value (Mosmlcookie), 74
dest_ppstream
 value (PP), 90
dgram
 type (Socket), 117, 118

dict
 type (Binarymap), 15
 type (Splaymap), 122
difference
 value (Binaryset), 16
 value (Intset), 53
 value (Splayset), 123
dimensions
 value (Array2), 5, 6
dir
 value (Path), 95, 97
dirstream
 type (FileSys), 37
displayLines
 value (Help), 49
Div
 exception (General), 45
 exception (Real), 108
 value (General), 47
div
 value (General), 46, 48
 value (Int), 50
 value (Word), 149, 150
 value (Word8), 152, 153
divi
 value (Msp), 75, 78
divia
 value (Msp), 75, 78
dl
 value (Msp), 76, 79
dla
 value (Msp), 76, 79
dlClose
 value (Dynlib), 35, 36
dlHandle
 type (Dynlib), 35
dlopen
 value (Dynlib), 35, 36
dlSym
 value (Dynlib), 35, 36
Domain
 exception (General), 45
doubleVec
 value (Mosml), 70
drawArc
 value (Gdimage), 42, 44
drawLine
 value (Gdimage), 42, 44
drawPixel
 value (Gdimage), 42, 44
 value (Splayset), 123
drawPolygon
 value (Gdimage), 42, 44
drawRect
 value (Gdimage), 42, 44
drop
 value (List), 57
drop1
 value (Binaryset), 16
 value (Intset), 53
 value (Splayset), 123
errLocation

value (Location), 62
errMsg
value (Location), 62
errorMessage
value (Mysql), 81, 83
value (Postgres), 102, 104
errorMsg
value (OS), 88
errPrompt
value (Location), 62
execute
value (Mysql), 81, 83
value (Postgres), 102, 104
value (Unix), 141
executeInEnv
value (Unix), 141
exists
value (Array), 3, 4
value (ArraySlice), 8, 9
value (CharArray), 26
value (CharArraySlice), 27
value (CharVector), 28
value (CharVectorSlice), 29
value (List), 57, 58
value (ListPair), 59
value (Vector), 142
value (VectorSlice), 144, 145
value (Word8Array), 155
value (Word8ArraySlice), 156
value (Word8Vector), 157
value (Word8VectorSlice), 158
exit
value (Process), 106
enn
type (General), 45, 46
ennMessage
value (General), 45, 47
ennName
value (General), 45, 47
exp
value (Math), 64
value (NJ93), 85
value (SML90), 114
explode
value (NJ93), 85
value (SML90), 114
value (String), 125, 126
value (Substring), 130, 131
ext
value (Path), 95, 97
Extended
constructor (Regex), 111
extract
value (String), 125
value (Substring), 130
Fail
exception (General), 45

value (VectorSlice), 144, 145
value (Word8Array), 155
value (Word8ArraySlice), 156
value (Word8Vector), 157
value (Word8VectorSlice), 158
findi
value (Array), 3, 4
value (ArraySlice), 8, 9
value (CharArray), 26
value (CharArraySlice), 27
value (CharVector), 28
value (CharVectorSlice), 29
value (Vector), 142, 143
value (VectorSlice), 144, 145
value (Word8Array), 155
value (Word8ArraySlice), 156
value (Word8Vector), 157
value (Word8VectorSlice), 158
first
value (Substring), 130, 131
flag
type (DynLib), 35, 36
flatten
value (Msp), 75, 77
FloatVec
value (Mosml), 70
floor
value (General), 45, 48
value (Real), 108, 109
flush_out
value (NJ93), 86
flush_ppstream
value (PP), 90, 91
flushOut
value (BinIO), 12, 13
value (TextIO), 135, 137
fmt
value (Date), 31, 32
value (Int), 50, 51
value (Real), 108, 109
value (Time), 138, 139
value (Word), 149, 150
value (Word8), 152, 153
fname
value (Mysql), 81, 83
value (Postgres), 102, 104
fnames
value (Mysql), 81, 83
value (Postgres), 102, 104
fnnumber
value (Mysql), 81, 83
value (Postgres), 102, 104
fold
value (Array2), 5, 6
value (Gdbm), 40, 41
value (NJ93), 85
value (Polygdbm), 98, 99

value (Regex), 110, 113
foldi
value (Array2), 5, 7
foldl
value (Array), 3, 4
value (ArraySlice), 8, 9
value (Binarymap), 15
value (Binaryset), 16, 17
value (CharArray), 26
value (CharArraySlice), 27
value (CharVector), 28
value (CharVectorSlice), 29
value (Intmap), 52
value (Intset), 53
value (List), 57, 58
value (ListPair), 59, 60
value (Splaymap), 122
value (Splayset), 123, 124
value (Substring), 130, 133
value (Vector), 142, 143
value (VectorSlice), 144, 145
value (Weak), 146, 147
value (Word8Array), 155
value (Word8ArraySlice), 156
value (Word8Vector), 157
value (Word8VectorSlice), 158
foldLEq
value (ListPair), 59, 60
foldli
value (Array), 3, 4
value (ArraySlice), 8, 9
value (CharArray), 26
value (CharArraySlice), 27
value (CharVector), 28
value (CharVectorSlice), 29
value (Vector), 142, 143
value (VectorSlice), 144, 145
value (Weak), 146-148
value (Word8Array), 155
value (Word8ArraySlice), 156
value (Word8Vector), 157
value (Word8VectorSlice), 158
foldr
value (Array), 3, 4
value (ArraySlice), 8, 9
value (Binarymap), 15
value (Binaryset), 16, 17
value (CharArray), 26
value (CharVector), 28
value (CharVectorSlice), 29
value (Intmap), 52
value (Intset), 53, 54
value (List), 57, 58
value (ListPair), 59
value (Splaymap), 122
value (Splayset), 123, 124

value (Substring), 130, 133
value (Vector), 142, 143
value (VectorSlice), 144, 145
value (Weak), 146, 147
value (Word8Array), 155
value (Word8ArraySlice), 156
value (Word8Vector), 157
value (Word8VectorSlice), 158
foldrEq
value (ListPair), 59, 60
foldr
value (Array), 3, 4
value (ArraySlice), 8, 10
value (CharArray), 26
value (CharArraySlice), 27
value (CharVector), 28
value (CharVectorSlice), 29
value (Vector), 142, 143
value (VectorSlice), 144, 145
value (Weak), 146, 148
value (Word8Array), 155
value (Word8ArraySlice), 156
value (Word8Vector), 157
value (Word8VectorSlice), 158
font
type (GdiImage), 42, 43
fonta
value (Map), 76, 79
force
value (Susp), 134
form
value (Map), 76, 80
forma
value (Map), 76, 80
formattable
value (MMap), 82, 84
value (Postgres), 103, 105
fpe
value (Signal), 115
frag
type (General), 45, 46
frame
value (Map), 77, 80
framea
value (Map), 77, 80
frameset
value (Map), 77, 80
fromCString
value (Char), 23, 25
value (String), 125, 126
fromDefault
value (Real), 108
fromInt
value (Int), 50
value (Real), 108
value (Word), 149, 150
value (Word8), 152, 154
fromLarge
value (Int), 50
fromLargeInt
value (Word), 149, 151
value (Word8), 152, 154
fromLargeWord
value (Word), 149, 151
value (Word8), 152, 154
fromList
value (Array), 3
value (Array2), 5
value (CharArray), 26
value (CharVector), 28
value (Dynarray), 34
value (Vector), 142
value (Vector), 155
value (Word8Array), 157
fromMicroseconds
value (Time), 138
fromMilliseconds
value (Time), 138
fromPng
value (GdiImage), 42, 43
fromReal
value (Time), 138
fromSeconds
value (Time), 138
fromString
value (Bool), 18
value (Char), 23, 24
value (Date), 31, 32
value (Int), 50, 51
value (Path), 95, 97
value (Real), 108, 109
value (String), 125, 126
value (Time), 138, 139
value (Word), 149, 150
value (Word8), 152, 153
frontag
value (Mysql), 82
value (Postgres), 103
fromTimeLocal
value (Date), 31, 33
fromTimeUrv
value (Date), 31, 33
fromWord
value (Signal), 115
ftype
value (Mysql), 82
value (Postgres), 103
ftypes
value (Mysql), 82
value (Postgres), 103
full
value (ArraySlice), 8
value (CharArraySlice), 27
value (CharVectorSlice), 29

value (Substring), 130, 131
value (VectorSlice), 144
value (Word8ArraySlice), 156
value (Word8VectorSlice), 158
fullPath
value (FileSys), 37, 38
Gdbm (structure), 40–41
GdbmError
exception (Gdbm), 40
exception (Polygdbm), 98
GdiImage (structure), 42–44
General (structure), 45–48
generator
type (Random), 107
get
value (Weak), 146
getbool
value (Mysql), 81, 84
value (Postgres), 102, 105
getc
value (Substring), 130, 131
getCookie
value (Mysqlcookie), 74
getCookieValue
value (Mysqlcookie), 74
getcptr
value (Callback), 20, 21
getCurrentLocation
value (Location), 62
getdate
value (Mysql), 81, 83
value (Postgres), 102, 104
getdatetime
value (Mysql), 81, 83
value (Postgres), 102, 104
getDir
value (FileSys), 37
getdynfield
value (Mysql), 82, 84
value (Postgres), 103, 105
getdynintup
value (Mysql), 82, 84
value (Postgres), 103, 105
getdynintups
value (Mysql), 82, 84
value (Postgres), 103, 105
getEnv
value (Process), 106
getinetaddr
value (Socket), 117, 119
getint
value (Mysql), 81, 83
value (Postgres), 102, 104
getItem
value (ArraySlice), 8, 9
value (CharArraySlice), 27
value (CharVectorSlice), 29
value (List), 57, 58
value (VectorSlice), 144, 145
value (Word8ArraySlice), 156
value (Word8VectorSlice), 158
getLexeme
value (Lexing), 55, 56
getLexemeChar
value (Lexing), 55, 56
getLexemeEnd
value (Lexing), 55, 56
getLexemeStart
value (Lexing), 55, 56
getOpt
value (Option), 89
getParent
value (Path), 95, 96
getreal
value (Mysql), 81, 83
value (Postgres), 102, 104
getstring
value (Mysql), 81, 83
value (Postgres), 102, 104
getTime
value (Mysql), 81, 83
value (Postgres), 102, 104
getTransparent
value (GdiImage), 42, 43
getVolume
value (Path), 95, 97
Graphic
exception (General), 45
h1
value (MMap), 75, 78
h2
value (MMap), 75
h3
value (MMap), 75
h4
value (MMap), 75
h5
value (MMap), 75
h6
value (MMap), 75
hash
value (FileSys), 37, 39
value (Polyhash), 100, 101
hash_param
value (Polyhash), 100, 101
hash_table
type (Polyhash), 100
haskey
value (Gdbm), 40, 41
value (Polygdbm), 98
Hd
exception (N993), 85
hd
value (List), 57

value (NJ93), 85
head
value (Msp), 75, 78
Help (structure), 49
help
value (Help), 49
helpdirs
value (Help), 49
host
value (Mysql), 81, 82
value (Postgres), 102, 103
hour
value (Date), 31, 32
hr
value (Msp), 75, 78
hra
value (Msp), 75, 78
html
value (Msp), 75, 78
htmlcolors
value (Gdimage), 42, 43
htmldoc
value (Msp), 75, 78
htmlencode
value (Msp), 77, 80
hup
value (Signal), 115
Icase
constructor (Regex), 111
ignore
value (General), 45, 47
ill
value (Signal), 115
image
type (Gdimage), 42, 43
value (Gdimage), 42, 43
img
value (Msp), 76, 79
imga
value (Msp), 76, 79
implode
value (NJ93), 85
value (SML90), 114
value (String), 125, 126
in_flags
type (Socket), 117, 120
in_stream_length
value (Nonstdio), 87
inc
value (NJ93), 85
inbox
value (Msp), 76, 80
INCONSISTENT
constructor (PP), 90
indexfiles
value (Help), 49
inetAddr

value (Socket), 117, 118
inetDgram
value (Socket), 117, 118
inetStream
value (Socket), 117, 118
inhidden
value (Msp), 76, 80
inpassword
value (Msp), 76, 80
input
value (BinIO), 12
value (Msp), 76, 80
value (NJ93), 85
value (SML90), 114
value (TextIO), 135, 136
input1
value (BinIO), 12
value (TextIO), 135, 136
input_binary_int
value (Nonstdio), 87
input_char
value (Nonstdio), 87
input_line
value (NJ93), 86
input_value
value (Nonstdio), 87
inputa
value (Msp), 76, 80
inputAll
value (BinIO), 12
value (TextIO), 135, 136
inputc
value (NJ93), 86
inputLine
value (TextIO), 135, 136
inputN
value (BinIO), 12, 13
value (TextIO), 135, 136
inputNoBlock
value (BinIO), 12
value (TextIO), 135, 136
inradio
value (Msp), 76, 80
inreset
value (Msp), 76, 80
insert
value (Binarraymap), 15
value (Gdbm), 40, 41
value (Intmap), 52
value (Polygdbm), 98
value (Polyhash), 100
value (Splaymap), 122
installPP
value (Meta), 66
instream
type (BinIO), 12
type (NJ93), 85

type (SML90), 114
type (TextIO), 135
insubmit
value (Msp), 76, 80
Int (structure), 50–51
int
type (General), 45, 46
type (Int), 50
value (Signal), 115
Interrupt
exception (General), 45
intersection
value (Binaryset), 16
value (Intset), 53
value (Splayset), 123
intext
value (Msp), 76, 80
Intmap (structure), 52
intmap
type (Intmap), 52
Intset (structure), 53–54
intset
type (Intset), 53
Invalid_argument
exception (General), 45
Io
exception (General), 45
isAbsolute
value (Path), 95, 96
isAlpha
value (Char), 23, 24
isAlphaNum
value (Char), 23, 24
isAscii
value (Char), 23, 24
isCanonical
value (Path), 95, 96
isCtrl
value (Char), 23, 24
isdead
value (Weak), 146, 147
isDigit
value (Char), 23
isDir
value (FileSys), 37, 38
isDst
value (Date), 31, 32
isEmpty
value (ArraySlice), 8, 9
value (Binaryset), 16
value (CharArraySlice), 27
value (CharVectorSlice), 29
value (Intset), 53
value (Splayset), 123
value (Substring), 130, 131
value (VectorSlice), 144, 145
value (Word8ArraySlice), 156
value (Word8VectorSlice), 158
isGraph
value (Char), 23, 24
isHexDigit
value (Char), 23, 24
isLink
value (FileSys), 37, 38
isLower
value (Char), 23
ismull
value (Mysql), 81, 84
value (Postgres), 102, 105
isPrefix
value (String), 125, 126
value (Substring), 130, 132
isPrint
value (Char), 23, 24
isPunct
value (Char), 23, 24
isRegistered
value (Callback), 20, 21
isRelative
value (Path), 95, 96
isSome
value (Option), 89
isSpace
value (Char), 23, 24
isSubset
value (Binaryset), 16
value (Intset), 53
value (Splayset), 123
isSubstring
value (String), 125, 126
value (Substring), 130, 132
isSuccess
value (Process), 106
isSuffix
value (String), 125, 126
value (Substring), 130, 132
isUpper
value (Char), 23
isweak
value (Weak), 146
itemEnd
value (Parsing), 93, 94
itemStart
value (Parsing), 93
join
value (Option), 89
joinBaseExt
value (Path), 95, 97
joinDirFile
value (Path), 95, 97
kill
value (Signal), 115
value (Unix), 141

last
 value (List), 57
length
 value (Array), 3
 value (ArraySlice), 8
 value (CharArray), 26
 value (CharArraySlice), 27
 value (CharVector), 28
 value (CharVectorSlice), 29
 value (List), 57
 value (Vector), 142
 value (VectorSlice), 144
 value (Weak), 146, 147
 value (WordArray), 155
 value (WordArraySlice), 156
 value (Word8Vector), 157
 value (Word8VectorSlice), 158
lexbuf
 type (Lexing), 55
Lexing (structure), 55–56
li
 value (Msp), 76, 79
liberal
 value (Meta), 66, 67
List (structure), 57–58
list
 type (General), 45, 46
 type (List), 57
listDir
 value (Mosml), 70
listen
 value (Socket), 117, 119
listItems
 value (Binarymap), 15
 value (Binaryset), 16, 17
 value (Gdbm), 40, 41
 value (Intmap), 52
 value (Intset), 53
 value (Polygdbm), 98, 99
 value (Polyhash), 100
 value (Splaymap), 122
 value (String), 125, 126
 value (Vector), 142, 143
 value (VectorSlice), 144, 145
 value (Word8Vector), 157
 value (Word8VectorSlice), 158
mapa
 value (Msp), 76, 79
mapEq
 value (ListPair), 59, 60
mapI
 value (CharVector), 28
 value (CharVectorSlice), 29
 value (Vector), 142, 143
 value (VectorSlice), 144, 145
 value (Word8Vector), 157
 value (Word8VectorSlice), 158
mapPartial
 value (List), 57, 58
 value (Option), 89
mark0
 value (Msp), 75, 78
mark0a
 value (Msp), 75, 78
mark1
 value (Msp), 75, 78
mark1a
 value (Msp), 75, 78

Match
 exception (General), 45
Math (structure), 64–65
max
 value (Int), 50, 51
 value (NJ93), 85
 value (Real), 108
 value (Word), 149, 150
 value (Word8), 152, 153
maxChar
 value (Char), 23
maxInt
 value (Int), 50
maxLen
 value (Array), 3
 value (CharArray), 26
 value (CharVector), 28
 value (Vector), 142
 value (Weak), 146, 147
 value (Word8Array), 155
 value (Word8Vector), 157
maxOrd
 value (Char), 23
maxSize
 value (String), 125
md5sum
 value (Mosml), 70
member
 value (Binaryset), 16
 value (Intset), 53
 value (Splayset), 123
Meta (structure), 66–69
min
 value (Int), 50, 51
 value (NJ93), 85
 value (Real), 108
 value (Word), 149, 150
 value (Word8), 152, 153
minChar
 value (Char), 23
minInt
 value (Int), 50
minute
 value (Date), 31, 32
mk_ppstream
 value (PP), 90
mkAbsolute
 value (Path), 95, 96
mkCanonical
 value (Path), 95, 96
mkDict
 value (Binarymap), 15
 value (Splaymap), 122
mkDir
 value (FileSys), 37
mkLoc
 value (Location), 62
mkPolyTable
 value (Polyhash), 100, 101
mkRelative
 value (Path), 95, 96
mkTable
 value (Polyhash), 100
mod
 value (General), 46, 48
 value (Int), 50
 value (Word), 149, 150
 value (Word8), 152, 153
mode
 type (Gdimage), 42, 43
modify
 value (Array), 3, 4
 value (Array2), 5, 6
 value (ArraySlice), 8, 9
 value (CharArray), 26
 value (CharArraySlice), 27
 value (Weak), 146, 147
 value (Word8Array), 155
 value (Word8ArraySlice), 156
modifyI
 value (Array), 3, 4
 value (Array2), 5, 7
 value (ArraySlice), 8, 10
 value (CharArray), 26
 value (CharArraySlice), 27
 value (Weak), 146, 148
 value (Word8Array), 155
 value (Word8ArraySlice), 156
modTime
 value (FileSys), 37, 38
month
 type (Date), 31
 value (Date), 31, 32
Mosml (structure), 70
Mosmlcgi (structure), 71–73
Mosmlcookie (structure), 74
Msp (structure), 75–80
Mysql (structure), 81–84
name
 value (CommandLine), 30
nCols
 value (Array2), 5, 6
newgen
 value (Random), 107
newgensseed
 value (Random), 107
NewLine
 constructor (Regex), 111
nfields
 value (Mysql), 81, 83
 value (Postgres), 102, 104
nilLocation
 value (Location), 62
NJ93 (structure), 85–86

NI1 constructor (Msp), 77
NO_RECVS constructor (Socket), 119
NO_RECVS_OR_SENDS constructor (Socket), 119
NO_SENDS constructor (Socket), 119
NonstdIo (structure), 87
not value (Bool), 18
notb value (General), 45, 48
notb value (Word), 149
notb value (Word8), 152
NotBool constructor (Regex), 111
notContains value (Char), 23, 24
Noteol constructor (Regex), 112
NotFound exception (Binarymap), 15
exception (Binaryset), 16
exception (Gdbm), 40
exception (Intset), 52
exception (Polygdbm), 98
exception (Splaymap), 122
exception (Splayset), 123
NotInt exception (Msp), 75
notTransparent value (Gdimage), 42, 44
NotWriter exception (Gdbm), 40
exception (Polygdbm), 98
now value (Time), 138
nRows value (Array2), 5, 6
nth value (List), 57
value (NJ93), 85
nthtail value (NJ93), 85
ntuples value (Msp), 81, 83
value (Postgres), 102, 104
Null exception (Msp), 81
exception (Postgres), 102
null value (List), 57
numItems value (Binarymap), 15
value (Binaryset), 16

value (Msp), 76, 80
options value (Msp), 81, 82
value (Postgres), 102, 103
orb value (Word), 149
value (Word8), 152
ord value (Char), 23
value (NJ93), 85
value (SML90), 114
order type (General), 45, 46
ordof value (NJ93), 85
orthodox value (Meta), 66, 67
OS (structure), 88
OSaerr type (AppleScript), 2
OSAID type (AppleScript), 2
out_flags type (Socket), 117, 119
Out_of_memory exception (General), 45
output value (BinIO), 12, 13
value (NJ93), 85
value (SML90), 114
value (TextIO), 135, 136
output1 value (BinIO), 12, 13
value (TextIO), 135, 136
output_binary_int value (NonstdIo), 87
output_byte value (NonstdIo), 87
value (NonstdIo), 87
output_char value (NonstdIo), 87
output_value value (NonstdIo), 87
outputc value (NJ93), 86
outputSubstr value (TextIO), 135
outstream type (BinIO), 12
type (TextIO), 135
Overflow exception (General), 45
P value (Msp), 75, 78
pa value (Msp), 75, 78
packString value (Byte), 19
padLeft value (StringCvt), 128
padRight value (StringCvt), 128, 129
ParamMissing exception (Msp), 75
parentArc value (Path), 95, 96
ParseError exception (Parsing), 93
parseTables type (Parsing), 93
Parsing (structure), 93–94
part type (MosmLcgi), 71
part_data value (MosmLcgi), 71, 72
part_field_integer value (MosmLcgi), 71, 72
part_field_string value (MosmLcgi), 71, 72
part_field_strings value (MosmLcgi), 71, 72
part_fieldnames value (MosmLcgi), 71, 72
part_type value (MosmLcgi), 71
partition value (List), 57, 58
passive type (Socket), 117, 118
Path exception (Path), 95
Path (structure), 95–97
peek value (Binarymap), 15
value (Binaryset), 16
value (Gdbm), 40, 41
value (Intmap), 52
value (Polygdbm), 98
value (Polyhash), 100
value (Splaymap), 122
value (Splayset), 123
peekInsert value (Polyhash), 100
peekVal value (Parsing), 93
pf_file type (Socket), 117, 118
pf_inet type (Socket), 117, 118
pi value (Math), 64
pipe value (Signal), 115
Polygdbm (structure), 98–99
Polyhash (structure), 100–101

port
 value (MySQL), 81, 82
 value (Postgres), 102, 103
pos_in
 value (NonstdIo), 87
pos_out
 value (NonstdIo), 87
position
 value (SubString), 130, 132
Postgres (structure), 102–105
pow
 value (Math), 64
pp (structure), 90–92
pp_to_string
 value (PP), 90, 91
ppconsumer
 type (PP), 90
ppstream
 type (General), 45, 46
pre
 value (Msp), 76, 78
precision
 value (Int), 50
pred
 value (Char), 23
print
 value (NJ93), 85
 value (TextIO), 135, 137
printDepth
 value (Meta), 66
printLength
 value (Meta), 66
printseq
 value (Msp), 75, 77
printVal
 value (Meta), 66
prmap
 value (Msp), 75, 77
proc
 type (Unix), 141
Process (structure), 106
praepr
 value (Msp), 75, 77
quietdec
 value (Meta), 66, 68
quit
 value (Meta), 66
 value (Signal), 115
quot
 value (Int), 50
quotation
 value (Meta), 66, 68
radius
 type (StringCvt), 128
Random (structure), 107
random
 value (Random), 107
 value (Random), 107
 range
 value (Random), 107
rangelist
 value (Random), 107
reader
 type (StringCvt), 128
readLink
 value (FileSys), 37, 38
Real (structure), 108–109
real
 type (General), 45, 46
 type (Math), 64
 type (Real), 108
 value (General), 45, 48
real_timer
 type (Timer), 140
realfmt
 type (StringCvt), 128
realPath
 value (FileSys), 37, 38
reap
 value (Unix), 141
recvArr
 value (Socket), 118, 120
 value (Meta), 66
recvArr'
 value (Socket), 118, 120
recvArrFrom
 value (Socket), 118, 120
 value (Socket), 118, 120
recvArrFrom'
 value (Socket), 118, 120
recvVec
 value (Socket), 118, 119
 value (Socket), 118, 120
recvVec'
 value (Socket), 118, 120
recvVecFrom
 value (Socket), 118, 120
recvVecFrom'
 value (Socket), 118, 120
ref
 constructor (General), 46
 type (General), 45, 46
regcomp
 value (Meta), 66
 value (Signal), 115
Regex
 exception (Regex), 110
Regex (structure), 110–113
regex
 type (Regex), 110
regexec
 value (Regex), 110, 111
regexecBool
 value (Regex), 110, 112

region
 type (Array2), 5, 6
register
 value (Callback), 20, 21
regmatch
 value (Regex), 110, 112
regmatchBool
 value (Regex), 110, 112
regnexec
 value (Regex), 110, 112
 value (Regex), 110, 112
regnexecBool
 value (Regex), 110, 112
rem
 value (Int), 50, 51
remove
 value (Binarymap), 15
 value (FileSys), 37, 38
 value (Gdbm), 40, 41
 value (Intmap), 52
 value (Polygdbm), 98
 value (Polynash), 100
 value (Splaymap), 122
rename
 value (FileSys), 37, 38
reorganize
 value (Gdbm), 40, 41
 value (Polygdbm), 98, 99
replace
 value (Regex), 110, 112
replaceAll
 value (Regex), 110, 112
replacer
 type (Regex), 110
reset
 value (MySQL), 81, 83
 value (Postgres), 102, 104
resultstatus
 value (MySQL), 81, 83
 value (Postgres), 102, 104
retrieve
 value (Binaryset), 16
 value (Intmap), 52
 value (Splayset), 123
rev
 value (List), 57
revapp
 value (Binarymap), 15
 value (Binaryset), 16, 17
 value (Intmap), 52
 value (Intset), 53
 value (NJ93), 85
 value (Splaymap), 122
 value (Splayset), 123, 124
revAppend
 value (List), 57, 58
revfold
 value (NJ93), 85
rewindDir
 value (FileSys), 37
rgb
 type (Gdimage), 42, 43
 value (Gdimage), 42, 43
rmdir
 value (FileSys), 37
round
 value (General), 46, 48
 value (Real), 108, 109
row
 value (Array2), 5, 6
RowMajor
 constructor (Array2), 5
 RTLD_LAZY
 constructor (Dynlib), 36
 RTLD_NOW
 constructor (Dynlib), 36
run
 value (Mosml), 70
runresult
 type (Mosml), 70
sameDesc
 value (Socket), 117, 120
sameSign
 value (Int), 50, 51
 value (Real), 108
scan
 value (Bool), 18
 value (Date), 31, 33
 value (Int), 50, 51
 value (Real), 108, 109
 value (Time), 138, 139
 value (Word), 149, 150
 value (Word8), 152, 153
scanStream
 value (TextIO), 135, 136
scanString
 value (StringCvt), 128
second
 value (Date), 31, 32
seek_in
 value (NonstdIo), 87
seek_out
 value (NonstdIo), 87
segv
 value (Signal), 115
select
 value (Msp), 76, 80
 value (Socket), 117, 120
sendArr
 value (Socket), 117, 119
sendArr'
 value (Socket), 117, 119
sendArrTo
 value (Socket), 117, 119
sendArrTo'

value (Socket), 118, 119
sendVec
value (Socket), 117, 119
sendVec'
value (Socket), 117, 119
sendVecTo
value (Socket), 117, 119
sendVecTo'
value (Socket), 118, 119
set
type (Binaryset), 16
type (Splayset), 123
value (Weak), 146
setCookie
value (MosmCookie), 74
setCookies
value (MosmCookie), 74
setTime
value (FileSys), 37, 38
setTransparent
value (Gdimage), 42, 43
showquery
value (MySQL), 82, 84
value (Postgres), 103, 105
shutdown
value (Socket), 117, 119
shutdown_mode
type (Socket), 117
sign
value (Int), 50, 51
value (Real), 108
Signal (structure), 115–116
signal
type (Signal), 115
type (Unix), 141
sin
value (Math), 64
value (NJ93), 85
value (SML90), 114
singleton
value (Binaryset), 16
value (Intset), 53
value (Splayset), 123
sinh
value (Math), 64
Size
exception (General), 45
size
value (Gdimage), 42, 43
value (String), 125
value (Substring), 130, 131
skipWS
value (StringCvt), 128
sleep
value (Process), 106
slice
type (ArraySlice), 8
type (CharArraySlice), 27
type (CharVectorSlice), 29
type (VectorSlice), 144
type (Word8ArraySlice), 156
type (Word8VectorSlice), 158
value (ArraySlice), 8
value (CharArraySlice), 27
value (CharVectorSlice), 29
value (Substring), 130, 131
value (VectorSlice), 144
value (Word8ArraySlice), 156
value (Word8VectorSlice), 158
SML90 (structure), 114
sock
type (Socket), 117, 118
sock_addr
type (Socket), 117, 118
sock_desc
type (Socket), 117
sockDesc
value (Socket), 117, 120
Socket (structure), 117–121
sort
value (Arraysort), 11
value (Listsort), 61
sorted
value (Arraysort), 11
value (Listsort), 61
Span
exception (Substring), 130
span
value (Substring), 130, 132
specialfiles
value (Help), 49
Splaymap (structure), 122
Splayset (structure), 123–124
splitAt
value (Substring), 130, 132
splitBaseExt
value (Path), 95, 97
splitDirFile
value (Path), 95, 97
splitl
value (StringCvt), 128
value (Substring), 130, 132
splitr
value (Substring), 130, 132
sqrt
value (Math), 64
value (NJ93), 85
value (SML90), 114
startCPUTimer
value (Timer), 140
startRealTimer
value (Timer), 140
status
type (Process), 106

value (MySQL), 81, 83
value (Postgres), 102, 104
std_err
value (NJ93), 86
std_in
value (NJ93), 85
value (SML90), 114
std_out
value (NJ93), 85
value (SML90), 114
stdErr
value (TextIO), 135, 137
stdIn
value (TextIO), 135, 136
stdOut
value (TextIO), 135, 137
stdoutPrg
value (Gdimage), 42, 43
stop
value (Signal), 115
Str
constructor (Regex), 112
str
value (String), 125, 126
stream
type (Socket), 117, 118
streamsOf
value (Unix), 141
String (structure), 125–127
string
type (General), 45, 46
type (String), 125
value (Gdimage), 42, 44
value (Substring), 130, 131
StringCvt (structure), 128–129
stringToBytes
value (Byte), 19
stringUp
value (Gdimage), 42, 44
strong
value (Msp), 76, 79
style
type (Gdimage), 42, 43
sub
value (Array), 3
value (Array2), 5, 6
value (ArraySlice), 8
value (CharArray), 26
value (CharArraySlice), 27
value (CharVector), 28
value (CharVectorSlice), 29
value (Dynamray), 34
value (Msp), 76, 79
value (String), 125
value (Substring), 130, 131
value (Vector), 142
value (VectorSlice), 144
value (Weak), 146, 147
value (Word8Array), 155
value (Word8ArraySlice), 156
value (Word8Vector), 157
value (Word8VectorSlice), 158
subArray
value (Dynamray), 34
Subscript
exception (General), 45
subslice
value (ArraySlice), 8, 9
value (CharArraySlice), 27
value (CharVectorSlice), 29
value (VectorSlice), 144
value (Word8ArraySlice), 156
value (Word8VectorSlice), 158
substitute
value (Regex), 110, 112
substitutel
value (Regex), 110, 112
Substring
exception (NJ93), 85
Substring (structure), 130–133
substring
type (General), 45, 46
type (Substring), 130
value (NJ93), 85
value (String), 125
value (Substring), 130
succ
value (Char), 23
success
value (Process), 106
sup
value (Msp), 76, 79
Sus
constructor (Regex), 112
Susp (structure), 134
susp
type (Susp), 134
symbolEnd
value (Parsing), 93
symbolStart
value (Parsing), 93
symHandle
type (Dymlib), 35
SysErr
exception (General), 45
exception (OS), 88
syserror
type (General), 45, 46
type (OS), 88
system
value (Process), 106
table
type (Gdbm), 40
type (Polysdbm), 98

value (Msp), 76, 79
tablea
value (Msp), 76, 79
tabulate
value (Array), 3
value (Array2), 5, 6
value (CharArray), 26
value (CharVector), 28
value (Dynarray), 34
value (List), 57, 58
value (Vector), 142
value (Word8Array), 155
value (Word8Vector), 157
take
value (List), 57
take1
value (StringCvt), 128
value (Substring), 130, 132
taker
value (Substring), 130, 132
tan
value (Math), 64
tanh
value (Math), 64, 65
td
value (Msp), 76, 79
tda
value (Msp), 76, 79
term
value (Signal), 115
terminate
value (Process), 106
textarea
value (Msp), 76, 80
textareaa
value (Msp), 76, 80
TextIO (structure), 135–137
th
value (Msp), 76, 79
tha
value (Msp), 76, 79
Time
exception (Time), 138
Time (structure), 138–139
time
type (Time), 138
value (Mosml), 70
Timer (structure), 140
title
value (Msp), 75, 78
tl
value (List), 57
value (NJ93), 85
tmpName
value (FileSys), 37, 38
tocString
value (Char), 23, 25
value (String), 125, 126
toDefault
value (Real), 108
toInt
value (Int), 50
value (Word), 149, 150
value (Word8), 152, 153
toIntX
value (Word), 149, 150
value (Word8), 152, 153
tokens
value (Regex), 110, 113
value (String), 125, 126
value (Substring), 130, 133
tolarge
value (Int), 50
tolargeInt
value (Word), 149, 151
value (Word8), 152, 154
tolargeIntX
value (Word), 149, 151
value (Word8), 152, 154
tolargeWord
value (Word), 149, 151
value (Word8), 152, 154
tolargeWordX
value (Word), 149, 151
value (Word8), 152, 154
toLower
value (Char), 23, 24
toMicroseconds
value (Time), 138
toMilliSeconds
value (Time), 138
toPng
value (Gdimage), 42, 43
toReal
value (Time), 138
toSeconds
value (Time), 138
toString
value (Bool), 18
value (Char), 23, 24
value (Date), 31, 32
value (Int), 50, 51
value (Path), 95, 97
value (Real), 108, 109
value (String), 125, 126
value (Time), 138, 139
value (Word), 149, 150
value (Word8), 152, 153
totalCPUTimer
value (Timer), 140
totalRealTimer
value (Timer), 140
toTime
value (Date), 31, 33

toUpperCase
value (Char), 23, 24
toWord
value (Signal), 115
Tr
constructor (Regex), 112
tr
value (Msp), 76, 79
value (Msp), 76, 79
transform
value (Binarystack), 15
value (Intmap), 52
value (Polyhash), 100, 101
value (Splaymap), 122
translate
value (String), 125, 126
value (Substring), 130, 132
traversal
type (Array2), 5
triml
value (Substring), 130, 131
trimr
value (Substring), 130, 131
Trs
constructor (Regex), 112
trunc
value (General), 46, 48
value (Real), 108, 109
truncate
value (NJ93), 85
tstp
value (Signal), 115
tt
value (Msp), 76, 79
ttin
value (Signal), 115, 116
ttou
value (Signal), 115, 116
tty
value (Mysql), 81, 82
value (Postgres), 102, 104
ul
value (Msp), 76, 79
ula
value (Msp), 76, 79
UnequalLengths
exception (ListPair), 59
union
value (Binarystack), 16
value (Intset), 53
value (Splayset), 123
unit
type (General), 45, 46
Unix (structure), 141
unpackString
value (Byte), 19
unpackStringVec
value (Byte), 19
unregister
value (Callback), 20, 21
unzip
value (ListPair), 59
update
value (Array), 3
value (Array2), 5, 6
value (ArraySlice), 8
value (CharArray), 26
value (CharArraySlice), 27
value (CharVector), 28
value (Dynarray), 34
value (Vector), 142
value (Weak), 146, 147
value (Word8Array), 155
value (Word8ArraySlice), 156
value (Word8Vector), 157
urlencode
value (Msp), 77, 80
use
value (Meta), 66
usr1
value (Signal), 115
usr2
value (Signal), 115
validVolume
value (Path), 95, 96
valof
value (Option), 89
valuepoly
value (Meta), 66, 68
var
value (Callback), 20, 21
value (Dynlib), 35, 36
vec2list
value (Msp), 75, 77
vecDouble
value (Mosml), 70
vecFloat
value (Mosml), 70
Vector (structure), 142–143
vector
type (BinIO), 12
type (CharArray), 26
type (CharArraySlice), 27
type (CharVector), 28
type (CharVectorSlice), 29
type (General), 45, 46
type (TextIO), 135
type (Vector), 142
type (Word8Array), 155
type (Word8ArraySlice), 156
type (Word8Vector), 157
type (Word8VectorSlice), 158
value (Array), 3

- value (ArraySlice), 8, 9
- value (CharArray), 26
- value (CharArraySlice), 27
- value (CharVectorSlice), 29
- value (General), 46, 48
- value (VectorSlice), 144, 145
- value (Word8Array), 155
- value (Word8ArraySlice), 156
- value (Word8VectorSlice), 158
- vector_slice
 - type (CharArraySlice), 27
 - type (Word8ArraySlice), 156
- VectorSlice (structure), 144–145
- verbose
 - value (Meta), 66, 68
- Weak (structure), 146–148
- weak
 - type (Weak), 146
 - value (Weak), 146
- weekDay
 - value (Date), 31, 32
- weekDay
 - type (Date), 31
- welcome
 - value (Help), 49
- with_pp
 - value (PP), 90, 91
- withtable
 - value (Gdbm), 40
 - value (Polygdbm), 98
- withtables
 - value (Gdbm), 40
- Word (structure), 149–151
- word
 - type (General), 45, 46
 - type (Word), 149
 - type (Word8), 152
- Word8 (structure), 152–154
- word8
 - type (General), 45, 46
 - Word8Array (structure), 155
 - Word8ArraySlice (structure), 156
 - Word8Vector (structure), 157
 - Word8VectorSlice (structure), 158
- wordSize
 - value (Word), 149
 - value (Word8), 152
- wseq
 - type (Msp), 75, 77
- xL
 - value (Location), 62
- xLR
 - value (Location), 62
- xorb
 - value (Word), 149
 - value (Word8), 152
- xxR
 - value (Location), 62
- xxLR
 - value (Location), 62
- xxRL
 - value (Location), 62, 63
- xy
 - type (Gdimage), 42, 43
- year
 - value (Date), 31, 32
- yearDay
 - value (Date), 31, 32
- yyexit
 - exception (Parsing), 93
- Yyparse
 - value (Parsing), 93
- zeroTime
 - value (Time), 138
- zip
 - value (ListPair), 59
- zipEq
 - value (ListPair), 59, 60