VŠB – Technická univerzita Ostrava Fakulta elektrotechniky a informatiky Katedra informatiky

# SPS - Semestrální projekt SPS - Semestral project

# Abstrakt

SPS

Klíčová slova: SPS

# Abstract

SPS

 $\mathbf{Keywords} \colon \mathrm{SPS}$ 

# Obsah

1	Plán číslování VLAN a implementace VLAN	4
2	L2 v access a distribuční vrstvě	5
	2.1 VLANs	5
	2.2 Trunks	7
	2.3 LACP	9
3	Spanning Tree	11
4	Adresování	22
	4.1 IPv4	22
	4.2 IPv6	25
	4.3 Rekonvergence	28
5	FHRP	29
	5.1 Implementace	29
	5.2 Tracking	29
6	BGP	38
7	Management	39
	7.1 IPv4 VRRP	39
8	IGP	40
9	Link state	59
10	) Konektivita IPv4	60
	10.1 Ping	60
	10.2 Traceroute	60
11	Konektivita IPv6	61
	11.1 Ping	61
	11.9 Traceroute	61

# 1 Plán číslování VLAN a implementace VLAN

Název	Číslo	Popis
Klient 101	101	
Klient 102	102	
Klient 103	103	
Klient 301	301	
Klient 302	301	
Klient 303	303	
g	9	datový provoz
M	91	management VRF
MA	18	management VRF
unused	998	nevyužité porty
native	999	nativní

# 2 L2 v access a distribuční vrstvě

### 2.1 VLANs

do sh vlan

	Name				Sta	tus	Ports			
	defaul	lt			act	ive				
.8	MA				act	ive	Gi1/0			
01	klient	:101			act:	ive	Gi0/3			
.02	klient	102			act	ive				
.03	klient	:103			act	ive				
01	server	r301			act	ive	Gi0/0			
02	server	r302			act:	ive				
03	server	2303			act:	ive				
98	unused	i			act	ive				
99	native	е			act	ive				
.002	fddi-d	default			act	/unsup				
.003	token-	-ring-defau	lt			/unsup				
		et-default				/unsup				
1005	trnet-	-default			act	/unsup				
LAN	Туре	SAID	MTU	Parent	RingNo	Bridge	No Stp	BrdgMode	Trans1	Tran
	enet	100001	1500						0	0
.8	enet	100018	1500						0	0
	enet	100101	1500						0	0
101	enet enet		1500 1500						0	0
L01 L02										
L01 L02 L03	enet enet	100102	1500						0	0
01 02 03 01	enet enet enet	100102 100103	1500 1500						0	0
101 102 103 801 802	enet enet enet enet	100102 100103 100301	1500 1500 1500						0 0 0	0
101 102 103 801 802 803	enet enet enet enet enet	100102 100103 100301 100302	1500 1500 1500 1500						0 0 0 0	0 0 0
.01 .02 .03 .01 .02 .03	enet enet enet enet enet	100102 100103 100301 100302 100303	1500 1500 1500 1500 1500						0 0 0 0	0 0 0 0
.01 .02 .03 .01 .02 .03 .03 .098	enet enet enet enet enet	100102 100103 100301 100302 100303 100998 100999	1500 1500 1500 1500 1500 1500 1500						0 0 0 0	0 0 0 0 0 0
101 102 103 801 802 803 898 899	enet enet enet enet enet enet enet fddi	100102 100103 100301 100302 100303 100998	1500 1500 1500 1500 1500 1500						0 0 0 0 0 0 0	0 0 0 0 0 0 0 0
101 102 103 301 302 303 398 399 1002	enet enet enet enet enet enet enet fddi tr	100102 100103 100301 100302 100303 100998 100999 101002	1500 1500 1500 1500 1500 1500 1500						0 0 0 0 0 0	0 0 0 0 0 0 0

Obrázek 1: ALSW1 VLANs

DLSW1(config) #do sh vlan										
VLAN	Name				Stat	tus	Ports			
1	defaul	lt			act	ive	Gi0/3			
18	MA				act		310,0			
101	klient	:101			act					
102	klient				act					
103	klient				act					
301	serve				act					
302	serve	302			act	ive				
303	serve	303			act	ive				
998	unused	1			act:	ive				
999	native	9			act:	ive				
1002	fddi-	default			act	/unsup				
1003	token-	-ring-defau	lt			/unsup				
		et-default			act	/unsup				
1005	trnet-	default			act	/unsup				
						-				
VLAN	Туре	SAID	MTU	Parent	RingNo	Bridge	No Stp	BrdgMode	Trans1	Trans2
1	enet	100001	1500		_	_			0	0
18	enet	100018	1500	_	_	_	_	_	0	0
101	enet	100010	1500		_	_	_	_	0	0
102	enet	100101	1500	_		_	_		0	0
103	enet	100102	1500	_	_	_	_	_	0	0
301	enet	100301	1500	_	_	_	_	_	0	0
302	enet	100301	1500	_	_	_	_	_	0	0
303	enet	100302	1500			_			0	0
998		100303	1500	_	_	_	_	_	0	0
999		100999	1500						0	0
1002		101002	1500						0	0
1002		101002	1500	_	_	_	_	_	0	0
		101003	1500				ieee		0	0
		101004	1500				ibm		0	0
1005	crnet	101005	1300				LDIII			0
Remot	e SPAN	N VLANs								
Prima	ary Sec	condary Typ	e 		Ports					

Obrázek 2: DLSW1 VLANs

/LAN	Name				Sta	tus F	orts			
	defau	lt			act	ive G	;i0/3			
L8	MA				act:	ive				
01	klient	:101			act:	ive				
.02	klient	:102			act:	ive				
.03	klient	t103			act:	ive				
301	serve	r301			act:	ive				
302	serve	r302			act:	ive				
303	serve	r303			act:	ive				
98	unuse	1			act:	ive				
99	native	=			act	ive				
1002	fddi-	default			act	/unsup				
1003	token	-ring-defau	lt		act	/unsup				
L004	fddine	et-default			act	/unsup				
1005	trnet-	-default			act	/unsup				
LAN	Type	SAID	MTU	Parent	RingNo	BridgeN	lo Stp	${\tt BrdgMode}$	Trans1	Trans2
L		100001	1500						0	0
18		100018	1500						0	0
		100101	1500						0	0
		100102	1500						0	0
		100103	1500						0	0
		100301	1500						0	0
302	enet	100302	1500						0	0
303	enet	100303	1500						0	0
	enet	100998	1500						0	0
999	enet	100999	1500						0	0
002	fddi	101002	1500						0	0
	tr	101003	1500						0	0
1003	fdnet	101004	1500				ieee		0	0
		101005	1500				ibm		0	0
1004	trnet	Remote SPAN VLANS								
004		N VLANs								
L004 L005		N VLANs				<u>-</u> -				
.004		N VLANS								

Obrázek 3: DLSW2 VLANs

### 2.2 Trunks

do sh int trunk

```
ALSW1(config)#do sh int trunk
                                     Encapsulation Status
802.1q trunkir
Port
Gi0/1
                                                                          Native vlan
               Mode
                                                        trunking
                                                                           999
Gi0/2
                                                        trunking
               on
                                     802.1q
                                                                           999
Gi1/1
Gi1/2
                                     802.1q
802.1q
                                                        trunking
                                                                           999
               on
                                                        trunking
                                                                           999
               on
Gi1/3
                                     802.1q
                                                        trunking
                                                                           999
               on
Port
Gi0/1
Gi0/2
               Vlans allowed on trunk
               18,101-103,301-303,999
               18,101-103,301-303,999
998
Gi1/1
Gi1/2
Gi1/3
               998
               998
Port
GiO/1
GiO/2
               Vlans allowed and active in management domain
               18,101-103,301-303,999
               18,101-103,301-303,999
Gi1/1
Gi1/2
Gi1/3
               998
               998
               998
Port
Gi0/1
               Vlans in spanning tree forwarding state and not pruned
               18,301-303,999
18,101-103,999
GiO/1
GiO/2
Gi1/1
Gi1/2
               998
               998
Gi1/3
               998
```

Obrázek 4: ALSW1 Trunks

DLSW1(co	nfig)#do sh int	trunk		
			S: .	
Port	Mode	Encapsulation	Status	Native vlan
Gi0/0	on	802.1q	trunking	
Gi0/1	on	802.1q	trunking	
Gi1/0	on	802.1q	trunking	
Po1	on	802.1q	trunking	999
Port	Vlans allow	wed on trunk		
Gi0/0	998			
Gi0/1	18,101-103,	301-303,999		
Gi1/0	18,101-103,	301-303,999		
Po1	18,101-103,	301-303,999		
Port	Vlans allow	wed and active in man	agement doma	in
Gi0/0	998			
Gi0/1	18,101-103,	301-303,999		
Gi1/0	18,101-103,	301-303,999		
Po1	18,101-103	301-303,999		
Port	Vlans in sp	oanning tree forwardi	ng state and	not pruned
Gi0/0	998	,	,	_
Gi0/1	18,101-103	.301-303,999		
Gi1/0		301-303,999		
Po1		.301-303,999		
101	10,101 103,	.001 000,		

Obrázek 5: DLSW1 Trunks

```
DLSW2(config)#do sh int trunk
                                Encapsulation Status
            Mode
                                                               Native vlan
Port
Gi0/0
Gi0/1
                               802.1q
                                                trunking
                                                                999
             On
                                802.1q
                                                trunking
                                                                999
             on
Gi1/0
                                802.1q
                                                trunking
                                                                999
             on
Po1
                               802.1q
                                                trunking
                                                                999
            on
Port
             Vlans allowed on trunk
Gi0/0
             998
Gi0/1
             18,101-103,301-303,999
Gi1/0
             18,101-103,301-303,999
Po1
             18,101-103,301-303,999
Port
             Vlans allowed and active in management domain
Gi0/0
             998
Gi0/1
             18,101-103,301-303,999
             18,101-103,301-303,999
18,101-103,301-303,999
Gi1/0
Po1
Port
Gi0/0
             Vlans in spanning tree forwarding state and not pruned
Gi0/1
             18,101-103,301-303,999
Gi1/0
             18,101-103,301-303,999
Po1
             101-103,301-303
```

Obrázek 6: DLSW2 Trunks

### 2.3 LACP

do sh etherchannel summary

```
SW1(config)#do sh etherchannel
Flags: D - down P - bundled in port-channel
I - stand-alone s - suspended
           H - Hot-standby (LACP only)
          R - Layer3 S - Layer2
U - in use N - not in use, no aggregation
f - failed to allocate aggregator
          M - not in use, minimum links not met
m - not in use, port not aggregated due to minimum links not met
u - unsuitable for bundling
w - waiting to be aggregated
           d - default port
           A - formed by Auto LAG
Number of channel-groups in use: 1
Number of aggregators:
        Port-channel Protocol
                                                Ports
Froup
         Pol(SU)
                                 LACP
                                               Gi0/2(P)
                                                                 Gi0/3(s)
```

Obrázek 7: DLSW1 LACP

Obrázek 8: DLSW2 LACP

# 3 Spanning Tree

do sh spanning-tree

```
ALSW1(config) #do sh spanning-tree
/LAN0018
  Spanning tree enabled protocol rstp
Root ID Priority 32786
                               32786
5254.0005.5cd0
                Address
                This bridge is the root
Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
                Priority 32786 (priority 32768 sys-id-ext 18)
Address 5254.0005.5cd0
Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
Aging Time 300 sec
  Bridge ID Priority
                                                  Prio.Nbr Type
                         Role Sts Cost
Interface
Gi0/1
                         Desg FWD 4
                                                  128.2
                                                              P2p
Gi0/2
Gi1/0
                                                  128.3
128.5
                         Desg FWD 4
                                                              P2p
                         Desg FWD 4
/LAN0101
  Spanning tree enabled protocol rstp
  Root ID
                Priority
                Address
                                5254.0016.6c37
                Cost
                                3 (GigabitEthernet0/2)
2 sec Max Age 20 sec Forward Delay 15 sec
                Port
                Hello Time
                                32869 (priority 32768 sys-id-ext 101) 5254.0005.5cd0
  Bridge ID Priority
                Address
Hello Time
Aging Time
                               2 sec Max Age 20 sec Forward Delay 15 sec 300 sec
                         Role Sts Cost
Interface
                                                  Prio.Nbr Type
Gi0/1
                         Altn BLK 20
                                                  128.2
                                                              P2p
Gi0/2
                         Root FWD 5
                                                  128.3
                                                              P2p
Gi0/3
                         Desg FWD 4
                                                  128.4
                                                              P2p Edge
```

Obrázek 9: ALSW1 SPT 1/5

```
Spanning tree enabled protocol rstp
Root ID Priority 28774
                                   5254.0016.6c37
                 Address
                  Cost
                                  3 (GigabitEthernet0/2)
2 sec Max Age 20 sec Forward Delay 15 sec
                  Hello Time
                 Priority 32870 (priority 32768 sys-id-ext 102)
Address 5254.0005.5cd0
Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
Aging Time 300 sec
  Bridge ID Priority
Interface
                           Role Sts Cost
                                                       Prio.Nbr Type
Gi0/1
                           Altn BLK 20
                                                       128.2
                                                                    P2p
Gi0/2
                            Root FWD 5
                                                       128.3
                                                                    P2p
VLAN0103
 Root ID Priority 28775
Address 5254.0016.6c37
                                 9
3 (GigabitEthernet0/2)
2 sec Max Age 20 sec Forward Delay 15 sec
                  Cost
                  Port
                  Hello Time
                 Priority 32871 (priority 32768 sys-id-ext 103)
Address 5254.0005.5cd0
Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
Aging Time 300 sec
  Bridge ID Priority
                                                       Prio.Nbr Type
Interface
                           Role Sts Cost
Gi0/1
                            Altn BLK 20
                                                       128.2
                                                                    P2p
Gi0/2
                            Root FWD 5
                                                       128.3
                                                                    P2p
```

Obrázek 10: ALSW1 SPT 2/5

```
VLAN0301
  Root ID Priority 24877
Address 5254.0016.6c37
                  Cost
                  Port
                                   2 (GigabitEthernet0/1)
                  Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
                  Priority 33069 (priority 32768 sys-id-ext 301)
Address 5254.0005.5cd0
Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
Aging Time 300 sec
  Bridge ID Priority
                                                        Prio.Nbr Type
Interface
                            Role Sts Cost
Gi0/0
Gi0/1
                            Desg FWD 4
Root FWD 5
                                                        128.1
                                                                     P2p Edge
P2p
P2p
                                                        128.2
                            Altn BLK 20
                                                        128.3
Gi0/2
VLAN0302
  Spanning tree enabled protocol rstp
Root ID Priority 24878
Address 5254.0016.6c37
                  Cost
                                   2 (GigabitEthernet0/1)
2 sec Max Age 20 sec Forward Delay 15 sec
                  Hello Time
                  Priority 33070 (priority 32768 sys-id-ext 302)
Address 5254.0005.5cd0
Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
Aging Time 300 sec
  Bridge ID Priority
Interface
                            Role Sts Cost
                                                        Prio.Nbr Type
Gi0/1
                            Root FWD 5
                                                        128.2
                                                                     P2p
Gi0/2
                            Altn BLK 20
                                                        128.3
                                                                     P2p
```

Obrázek 11: ALSW1 SPT 3/5

```
VLAN0303
  Spanning tree enabled protocol rstp
Root ID Priority 24879
                               24879
5254.0016.6c37
                Address
                                5
2 (GigabitEthernet0/1)
                Cost
                Port
                Hello Time
                                2 sec Max Age 20 sec Forward Delay 15 sec
                               33071 (priority 32768 sys-id-ext 303) 5254.0005.5cd0
  Bridge ID Priority
                Address
Hello Time
                                2 sec Max Age 20 sec Forward Delay 15 sec
                Aging Time
                               300 sec
Interface
                         Role Sts Cost
                                                  Prio.Nbr Type
Gi0/1
                                                              P2p
                         Root FWD 5
                                                  128.2
Gi0/2
                         Altn BLK 20
                                                  128.3
                                                              P2p
NECONATA
  Spanning tree enabled protocol rstp
Root ID Priority 33766
Address 5254.0005.5cd0
                Address 5254.0005.5cdu
This bridge is the root
Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
                               33766 (priority 32768 sys-id-ext 998) 5254.0005.5cd0
  Bridge ID Priority
                Address 5254.0005.5cd0

Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec Aging Time 300 sec
                                                  Prio.Nbr Type
Interface
                         Role Sts Cost
                                                              P2p
P2p
Gi1/1
                                                  128.6
                         Desg FWD 4
                                                  128.7
128.8
Gi1/2
                         Desg FWD 4
Gi1/3
                         Desg FWD 4
                                                              P2p
```

Obrázek 12: ALSW1 SPT 4/5

```
VLAN0999
 Spanning tree enabled protocol rstp
             Priority
 Root ID
                          33767
             Address 5254.0005.50
This bridge is the root
                          5254.0005.5cd0
              Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
                          33767 (priority 32768 sys-id-ext 999) 5254.0005.5cd0
 Bridge ID Priority
             Address
              Hello Time
                           2 sec Max Age 20 sec Forward Delay 15 sec
              Aging Time
                          300 sec
                     Role Sts Cost
Interface
                                          Prio.Nbr Type
Gi0/1
                     Desg FWD 4
                                          128.2
                                                    P2p
Gi0/2
                     Desg FWD 4
                                          128.3
                                                    P2p
```

Obrázek 13: ALSW1 SPT 5/5

```
DLSW1(config)#do sh spanning-tree
VLAN0018
  Spanning tree enabled protocol rstp
Root ID Priority 32786
                                       5254.0005.5cd0
                    Address
                                       4
5 (GigabitEthernet1/0)
                    Cost
                    Port
                    Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
                   Priority 32786 (priority 32768 sys-id-ext 18)
Address 5254.0016.6c37
Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
Aging Time 300 sec
  Bridge ID Priority
Interface
                              Role Sts Cost
                                                             Prio.Nbr Type
                                                             128.2
128.5
128.65
Gi0/1
                              Desg FWD 4
                                                                           P2p
                              Root FWD 4
Desg FWD 4
Gi1/0
                                                                           P2p
                                                                           P2p
Po1
VLAN0101
  RANDIOI

Spanning tree enabled protocol rstp

Root ID Priority 28773

Address 5254.0016.6c37

This bridge is the root

Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
                   Priority 28773 (priority 28672 sys-id-ext 101)
Address 5254.0016.6c37
Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
Aging Time 300 sec
  Bridge ID Priority
Interface
                               Role Sts Cost
                                                             Prio.Nbr Type
Gi0/1
Gi1/0
                              Desg FWD 4
Desg FWD 20
Desg FWD 4
                                                             128.2
128.5
                                                                           P2p
                                                                           P2p
                                                                           P2p
                                                             128.65
Po1
```

Obrázek 14: DLSW1 SPT 1/5

```
VLAN0102
   Spanning tree enabled protocol rstp
Root ID Priority 28774
Address 5254.0016.6c37
                     Address 5254.0016.6c37
This bridge is the root
Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
                                       28774 (priority 28672 sys-id-ext 102) 5254.0016.6c37
  Bridge ID Priority
                     Address 5254.0016.6c37
Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec Aging Time 300 sec
Interface
                                Role Sts Cost
                                                               Prio.Nbr Type
                                Desg FWD 4
Desg FWD 20
Desg FWD 4
                                                               128.2
Gi0/1
                                                                              P2p
                                                               128.5
128.65
                                                                              P2p
P2p
Gi1/0
Po1
VLAN0103
  Spanning tree enabled protocol rstp
Root ID Priority 28775
Address 5254.0016.6c37
                     Address 5254.0016.6c37
This bridge is the root
Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
                     Priority 28775 (priority 28672 sys-id-ext 103)
Address 5254.0016.6c37
Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
Aging Time 300 sec
  Bridge ID Priority
Interface
                                Role Sts Cost
                                                               Prio.Nbr Type
                                Desg FWD 4
                                                               128.2
128.5
128.65
                                                                              P2p
P2p
Gi0/1
                                Desg FWD 20
Desg FWD 4
Gi1/0
Po1
                                                                               P2p
```

Obrázek 15: DLSW1 SPT 2/5

```
LAN0301
  Spanning tree enabled protocol rstp
               Priority
  Root ID
                             24877
               Address
                              5254.0016.6c37
               This bridge is the root
               Hello Time
                              2 sec Max Age 20 sec Forward Delay 15 sec
                             24877 (priority 24576 sys-id-ext 301) 5254.0016.6c37
  Bridge ID Priority
               Address Hello Time
                              2 sec Max Age 20 sec Forward Delay 15 sec
               Aging Time 300 sec
Interface
                       Role Sts Cost
                                              Prio.Nbr Type
Gi0/1
                       Desg FWD 4
Desg FWD 5
Desg FWD 4
                                              128.2
                                                         P2p
                                              128.5
Gi1/0
                                                         P2p
Po1
                                              128.65
                                                         P2p
VLAN0302
 Spanning tree enabled protocol rstp
Root ID Priority 24878
               Address
                              5254.0016.6c37
               This bridge is the root
Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
                             24878 (priority 24576 sys-id-ext 302) 5254.0016.6c37
  Bridge ID Priority
               Address 5254.0016.6c37
Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec Aging Time 300 sec
Interface
                       Role Sts Cost
                                              Prio.Nbr Type
Gi0/1
                       Desg FWD 4
                                              128.2
                                                         P2p
Gi1/0
                        Desg FWD 5
                                               128.5
                                                         P2p
Po1
                        Desg FWD 4
                                               128.65
                                                         P2p
```

#### Obrázek 16: DLSW1 SPT 3/5

```
VLAN0303
  Spanning tree enabled protocol rstp
Root ID Priority 24879
               Address 5254.0016.6c37
This bridge is the root
Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
                             24879 (priority 24576 sys-id-ext 303) 5254.0016.6c37
  Bridge ID Priority
               Address
Hello Time
                              2 sec Max Age 20 sec Forward Delay 15 sec
               Aging Time 300 sec
Interface
                       Role Sts Cost
                                              Prio.Nbr Type
Gi0/1
                       Desg FWD 4
                                              128.2
                                                         P2p
                       Desg FWD 5
Desg FWD 4
                                              128.5
Gi1/0
                                              128.65
201
VLAN0998
  Spanning tree enabled protocol rstp
                           33766
               Priority
  Root ID
                             5254.0016.6c37
               Address
               This bridge is the root
Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
                             33766 (priority 32768 sys-id-ext 998) 5254.0016.6c37
  Bridge ID Priority
               Address
Hello Time
                              2 sec Max Age 20 sec Forward Delay 15 sec
               Aging Time 300 sec
Interface
                       Role Sts Cost
                                              Prio.Nbr Type
Gi0/0
                                              128.1
                       Desg FWD 4
                                                         P2p
```

#### Obrázek 17: DLSW1 SPT 4/5

```
VLAN0999
 Spanning tree enabled protocol rstp
  Root ID
              Priority
              Address
                           5254.0005.5cd0
              Cost
                           5 (GigabitEthernet1/0)
              Port.
                           2 sec Max Age 20 sec Forward Delay 15 sec
              Hello Time
                           33767 (priority 32768 sys-id-ext 999) 5254.0016.6c37
 Bridge ID Priority
             Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
Aging Time 300 sec
Interface
                     Role Sts Cost
                                           Prio.Nbr Type
Gi0/1
                     Desg FWD 4
                                           128.2
                                                     P2p
                     Root FWD 4
Desg FWD 4
Gi1/0
                                           128.5
                                                     P2p
                                           128.65
Po1
                                                     P2p
```

Obrázek 18: DLSW1 SPT 5/5

```
DLSW2(config)#do sh spanning-tree
VLAN0018
  Spanning tree enabled protocol rstp
                             32786
5254.0005.5cd0
  Root ID
               Priority
               Address
               Cost
                             5 (GigabitEthernet1/0)
               Port
               Hello Time
                             2 sec Max Age 20 sec Forward Delay 15 sec
                             32786 (priority 32768 sys-id-ext 18) 5254.001d.c647
  Bridge ID Priority
               Address 5254.001
Hello Time 2 sec
Aging Time 300 sec
                             2 sec Max Age 20 sec Forward Delay 15 sec
                       Role Sts Cost
Interface
                                              Prio.Nbr Type
Gi0/1
                       Desg FWD 4
                                              128.2
                                                         P2p
                       Root FWD 4
Altn BLK 4
                                              128.5
128.65
Gi1/0
                                                         P2p
Po1
                                                         P2p
VLAN0101
  Spanning tree enabled protocol rstp
               Priority
  Root ID
                             28773
                             5254.0016.6c37
               Address
               Cost
               Fort 65 (Port-channel1)
Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
                             28773 (priority 28672 sys-id-ext 101) 5254.001d.c647
  Bridge ID Priority
               Address
               Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec Aging Time 300 sec
Interface
                       Role Sts Cost
                                              Prio.Nbr Type
Gi0/1
                                              128.2
                       Desg FWD 4
                                                         P2p
                       Desg FWD 5
Root FWD 4
                                              128.5
128.65
Gi1/0
Po1
                                                         P2p
P2p
```

Obrázek 19: DLSW2 SPT 1/5

```
Spanning tree enabled protocol rstp
Root ID Priority 28774
                 Address
                                  5254.0016.6c37
                                 4
65 (Port-channel1)
2 sec Max Age 20 sec Forward Delay 15 sec
                 Cost
                 Port
                 Hello Time
                                 28774 (priority 28672 sys-id-ext 102) 5254.001d.c647
  Bridge ID Priority
                 Address
                 Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
Aging Time 300 sec
Interface
                           Role Sts Cost
                                                     Prio.Nbr Type
Gi0/1
                           Desg FWD 4
Desg FWD 5
Root FWD 4
                                                     128.2
128.5
128.65
                                                                  P2p
                                                                 P2p
P2p
Gi1/0
Po1
VLAN0103
 Spanning tree enabled protocol rstp
Root ID Priority 28775
Address 5254.0016.6c37
                 Cost
                                  .
65 (Port-channel1)
2 sec Max Age 20 sec Forward Delay 15 sec
                 Hello Time
                                 28775 (priority 28672 sys-id-ext 103) 5254.001d.c647
  Bridge ID Priority
                 Address 5254.001d.c647

Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec Aging Time 300 sec
                                                     Prio.Nbr Type
Interface
                           Role Sts Cost
                                                     128.2
128.5
Gi0/1
                           Desg FWD 4
                                                                  P2p
                           Desg FWD 5
Root FWD 4
                                                                  P2p
P2p
Gi1/0
Po1
                                                     128.65
```

Obrázek 20: DLSW2 SPT 2/5

```
T.AN0301
  Spanning tree enabled protocol rstp
  Root ID
               Priority
                             24877
               Address
                              5254.0016.6c37
                             4
65 (Port-channel1)
2 sec Max Age 20 sec Forward Delay 15 sec
               Cost
               Port.
               Hello Time
  Bridge ID Priority
                              24877 (priority 24576 sys-id-ext 301)
               Address 5254.001d.c647
Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec Aging Time 300 sec
Interface
                       Role Sts Cost
                                               Prio.Nbr Type
                       Desg FWD 4
Desg FWD 20
Root FWD 4
Gi0/1
                                               128.2
                                                          P2p
                                               128.5
128.65
Gi1/0
                                                          P2p
Po1
VLAN0302
  Spanning tree enabled protocol rstp
  Root ID
               Priority
                             24878
                              5254.0016.6c37
               Address
               Cost
                              65 (Port-channel1)
               Port
               Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
 Bridge ID Priority
                             24878 (priority 24576 sys-id-ext 302) 5254.001d.c647
               Address 5254.001d.c647
Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec Aging Time 300 sec
Interface
                       Role Sts Cost
                                               Prio.Nbr Type
                                               128.2
128.5
128.65
Gi0/1
                       Desg FWD 4
                                                          P2p
Gi1/0
                        Desg FWD 20
                                                          P2p
Po1
                       Root FWD 4
                                                         P2p
```

#### Obrázek 21: DLSW2 SPT 3/5

```
VLAN0303
 Spanning tree enabled protocol rstp
                             24879
5254.0016.6c37
               Priority
  Root ID
               Address
                              65 (Port-channel1)
2 sec Max Age 20 sec Forward Delay 15 sec
               Cost
               Hello Time
                             24879 (priority 24576 sys-id-ext 303) 5254.001d.c647
 Bridge ID Priority
               Address 5254.001d.c647

Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec Aging Time 300 sec
                                               Prio.Nbr Type
                       Role Sts Cost
Interface
Gi0/1
                                               128.2
                       Desg FWD 4
                                                          P2p
                       Desg FWD 20
Root FWD 4
Gi1/0
                                               128.5
                                                          P2p
                                                          P2p
                                               128.65
Po1
/LAN0998
 Spanning tree enabled protocol rstp
 Root ID
               Priority
                             33766
               Address 5254.001d.c647
This bridge is the root
Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
                             33766 (priority 32768 sys-id-ext 998) 5254.001d.c647
 Bridge ID Priority
               Address
Hello Time
                             2 sec Max Age 20 sec Forward Delay 15 sec
               Aging Time 300 sec
Interface
                       Role Sts Cost
                                               Prio.Nbr Type
                       Desg FWD 4
Gi0/0
                                               128.1
                                                          P2p
```

Obrázek 22: DLSW2 SPT 4/5

```
LAN0999
   Spanning tree enabled protocol rstp
Root ID Priority 33767
                                         33767
5254.0005.5cd0
                      Address
                                         5 (GigabitEthernet1/0)
2 sec Max Age 20 sec Forward Delay 15 sec
                      Cost
Port
                      Hello Time
                     Priority 33767 (priority 32768 sys-id-ext 999)
Address 5254.001d.c647
Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
Aging Time 300 sec
   Bridge ID Priority
Interface
                                 Role Sts Cost
                                                                  Prio.Nbr Type
Gi0/1
Gi1/0
Po1
                                                                 128.2
128.5
128.65
                                 Desg FWD 4
Root FWD 4
Altn BLK 4
                                                                                P2p
P2p
P2p
```

Obrázek 23: DLSW2 SPT 5/5

# 4 Adresování

# 4.1 IPv4

# Klient/server


Name	Network address	Description	
VLAN 101	44.9.0.0/25	Client VLAN 1	
$VLAN\ 102$	44.9.0.128/26	Client VLAN 2	
$VLAN\ 103$	44.9.0.192/28	Client VLAN 3	
Client 1	44.9.1.0/25	First client subnet	
Client 200	44.9.100.128/25	Last client subnet	
Server 1	44.9.222.0/25	First server subnet	
Server 50	44.9.246.128/25	Last server subnet	
<b>VLAN 301</b>	44.9.247.0/25	Server VLAN 1	
VLAN~302	44.9.247.128/26	Server VLAN 2	
VLAN~303	44.9.247.192/28	Server VLAN 3	

# Global


Name	Network address	First address	Second address	Description
R1-WAN1	44.9.248.0/31	44.9.248.0	44.9.248.1	IC Link
DLSW1	44.9.254.0/32	44.9.254.0	-	Loopback01

Management

Name	Network address	First address	Second address	Description
R1-WAN1	44.9.253.248/31	44.9.253.248	44.9.253.249	IC Link
R1-WAN2	44.9.253.250/31	44.9.253.250	44.9.253.251	IC Link
R2-WAN1	44.9.253.252/31	44.9.253.252	44.9.253.253	IC Link
R2-WAN2	44.9.253.254/31	44.9.253.254	44.9.253.255	IC Link
VRRP	44.9.252.0/24	44.9.252.1	-	R1 & R2 virtual
R1	44.9.252.0/24	44.9.252.2	-	Adress on interface
R2	44.9.252.0/24	44.9.252.3	-	Adress on interface
DLSW1	44.9.252.0/24	44.9.252.4	-	VLAN 18
DLSW2	44.9.252.0/24	44.9.252.5	-	VLAN 18
ALSW1	44.9.252.0/24	44.9.252.6	-	VLAN 18
$\mathrm{TEST}\;\mathrm{PC}$	44.9.252.0/24	44.9.252.20	-	VLAN 18
R1	44.9.253.244/32	44.9.253.244	-	Loopback1
R2	44.9.253.245/32	44.9.253.245	-	Loopback1
WAN1	44.9.253.246/32	44.9.253.246	-	Loopback1
WAN2	44.9.253.247/32	44.9.253.247	_	Loopback1



Obrázek 24: IPv4 addressing



Obrázek 25: IPv4 management addressing


# 4.2 IPv6

Klient/server

Name	Network address	Description	
VLAN 101	44.9.0.0/25	Client VLAN 1	
$VLAN\ 102$	44.9.0.128/26	Client VLAN 2	
$VLAN\ 103$	44.9.0.192/28	Client VLAN 3	
Client 1	44.9.1.0/25	First client subnet	
Client 200	44.9.100.128/25	Last client subnet	
•••			
Server 1	44.9.222.0/25	First server subnet	
•••			
Server 50	44.9.246.128/25	Last server subnet	
VLAN~301	44.9.247.0/25	Server VLAN 1	
VLAN~302	44.9.247.128/26	Server VLAN 2	
VLAN~303	44.9.247.192/28	Server VLAN 3	

# Management

Name	Network address	First address	Second address	Description
R1-WAN1	44.9.253.248/31	44.9.253.248	44.9.253.249	IC Link
R1-WAN2	44.9.253.250/31	44.9.253.250	44.9.253.251	IC Link
R2-WAN1	44.9.253.252/31	44.9.253.252	44.9.253.253	IC Link
R2-WAN2	44.9.253.254/31	44.9.253.254	44.9.253.255	IC Link
VRRP	44.9.252.0/24	44.9.252.1	-	R1 & R2 virtual
R1	44.9.252.0/24	44.9.252.2	_	Adress on interface
R2	44.9.252.0/24	44.9.252.3	_	Adress on interface
DLSW1	44.9.252.0/24	44.9.252.4	_	VLAN 18
DLSW2	44.9.252.0/24	44.9.252.5	-	VLAN 18
ALSW1	44.9.252.0/24	44.9.252.6	-	VLAN 18
$\mathrm{TEST}\;\mathrm{PC}$	44.9.252.0/24	44.9.252.20	-	VLAN 18
R1	44.9.253.244/32	44.9.253.244	-	Loopback1
R2	44.9.253.245/32	44.9.253.245	_	Loopback1
WAN1	44.9.253.246/32	44.9.253.246	-	Loopback1
WAN2	44.9.253.247/32	44.9.253.247	_	Loopback1



Obrázek 26: IPv6 addressing

### 4.3 Rekonvergence

V IGP je primárně preferována cesta přes WAN1, při výpadku cesty trvá cca 35 s než dojde k převzetí jinou cestou

```
localhost:~$ ping 1.0.0.1 -w 50
PING 1.0.0.1 (1.0.0.1): 56 data bytes
64 bytes from 1.0.0.1: seq=0 ttl=42 time=9.225 ms
64 bytes from 1.0.0.1: seq=1 ttl=42 time=8.573 ms
64 bytes from 1.0.0.1: seq=2 ttl=42 time=9.392 ms
64 bytes from 1.0.0.1: seq=3 ttl=42 time=11.693 ms
64 bytes from 1.0.0.1: seq=4 ttl=42 time=8.659 ms
64 bytes from 1.0.0.1: seq=41 ttl=42 time=12.754 ms
64 bytes from 1.0.0.1: seq=42 ttl=42 time=8.459 ms
64 bytes from 1.0.0.1: seq=43 ttl=42 time=15.174 ms
64 bytes from 1.0.0.1: seq=44 ttl=42 time=10.563 ms
64 bytes from 1.0.0.1: seq=45 ttl=42 time=9.732 ms
64 bytes from 1.0.0.1: seq=46 ttl=42 time=9.518 ms
64 bytes from 1.0.0.1: seq=47 ttl=42 time=14.431 ms
64 bytes from 1.0.0.1: seq=48 ttl=42 time=11.416 ms
64 bytes from 1.0.0.1: seq=49 ttl=42 time=9.151 ms
```

Obrázek 27: IPv4 rekonvergence

### 5 FHRP

### 5.1 Implementace

do sh standby br

```
R1(config-subif)#do sh standby br
                             P indicates configured to preempt.
                       Pri P State Active Standby
120 P Standby FE80::5054:FF:FE17:C2F3
                                                                                         Virtual IP
Interface
                Grp
Gi0/1.101
                                                                                         FE80::5:73FF:FEA0:B
                                                                  local
Gi0/1.101
Gi0/1.102
                       120 P Standby 44.9.0.3 local
120 P Standby FE80::5054:FF:FE17:C2F3
                                                                                         44.9.0.1
                                                                  local
                                                                                         FE80::5:73FF:FEA0:C
Gi0/1.102
Gi0/1.103
                       120 P Standby 44.9.0.131 local
120 P Standby FE80::5054:FF:FE17:C2F3
                102
                                                                                         44.9.0.129
                                                                                         FE80::5:73FF:FEA0:D
44.9.0.193
44.9.247.1
Gi0/1.103
Gi0/1.301
                       120 P Standby 44.9.0.195
150 P Active local
150 P Active local
                103
                                                                  local
                                                                  44.9.247.3
Gi0/1.301
                                                                  FE80::5054:FF:FE17:C2F3
                                                                                         FE80::5:73FF:FEA0:15
44.9.247.129
Gi0/1.302
                2
22
                                                                  44.9.247.131 44.9.24
FE80::5054:FF:FE17:C2F3
                        150 P Active
                                           local
Gi0/1.302
                       150 P Active
                                           local
                                                                                         FE80::5:73FF:FEA0:16
Gi0/1.303
                                                                  44.9.247.195 44.9.24
FE80::5054:FF:FE17:C2F3
                3
23
                       150 P Active
150 P Active
                                           local
                                                                                         44.9.247.193
Gi0/1.303
                                           local
                                                                                         FE80::5:73FF:FEA0:17
```

Obrázek 28: R1 FHRP implementace

```
R2(config-subif) #do sh standby br
P indicates configured to preempt.
                                                                        Standby Virtual FE80::5054:FF:FE06:69A1
                          Pri P State
120 P Active
                                                                                                 Virtual IP
Interface
                                               Active
                  Grp
Gi0/1.101
                                                                        FE80::5:73FF:FEA0:B
44.9.0.2 44.9.0.1
FE80::5054:FF:FE06:69A1
Gi0/1.101
Gi0/1.102
                          150 P Active
                                               local
                          150 P Active
                                                                        FE80::5:73FF:FEA0:C
44.9.0.130 44.9.0.129
FE80::5054:FF:FE06:69A1
Gi0/1.102
Gi0/1.103
                          150 P Active
                  102
                                               local
                          150 P Active
                                               local
                                                                                                FE80::5:73FF:FEA0:D
44.9.0.193
44.9.247.1
Gi0/1.103
Gi0/1.301
Gi0/1.301
                          150 P Active local 44.9.0.
120 P Standby 44.9.247.2 local
120 P Standby FE80::5054:FF:FE06:69A1
                  103
                                                                        44.9.0.194
                                                                        local
                                                                                                 FE80::5:73FF:FEA0:15
                          120 P Standby 44.9.247.130 local
120 P Standby FE80::5054:FF:FE06:69A1
Gi0/1.302
                  2
22
                                                                                                 44.9.247.129
Gi0/1.302
                                                                                                FE80::5:73FF:FEA0:16
44.9.247.193
                                                                        local
                          120 P Standby 44.9.247.194 local
120 P Standby FE80::5054:FF:FE06:69A1
Gi0/1.303
 i0/1.303
                                                                                                 FE80::5:73FF:FEA0:17
```

Obrázek 29: R2 FHRP implementace

#### 5.2 Tracking

do sh standby

```
R1(config-if)#do sh standby
GigabitEthernet0/1.101 - Group 11 (version 2)
  State is Standby
  5 state changes, last state change 00:05:20
Link-Local Virtual IPv6 address is FE80::5:73FF:FEA0:B (impl auto EUI64)
     Virtual IPv6 address 2001:9999:1::/64
  Active virtual MAC address is 0005.73a0.000b

Local virtual MAC address is 0005.73a0.000b (v2 IPv6 default)
Hello time 3 sec, hold time 10 sec
     Next hello sent in 2.288 secs
  Preemption enabled
  Active router is FE80::5054:FF:FE17:C2F3, priority 120 (expires in 9.184 sec) MAC address is 5254.0017.c2f3
  Standby router is local
  Priority 120 (configured 120)
Group name is "hsrp-Gi0/1.101-11" (default)
 igabitEthernet0/1.101 - Group 101 (version 2)
  State is Standby
     6 state changes, last state change 00:05:19
  Virtual IP address is 44.9.0.1
Active virtual MAC address is 0000.0c9f.f065
Local virtual MAC address is 0000.0c9f.f065 (v2 default)
Hello time 3 sec, hold time 10 sec
Next hello sent in 0.192 secs
   Preemption enabled
  Active router is 44.9.0.3, priority 150 (expires in 8.848 sec) MAC address is 5254.0017.c2f3
  Standby router is local
Priority 120 (configured 120)
Group name is "hsrp-Gi0/1.101-101" (default)
```

### Obrázek 30: R1 FHRP detail 1/6

```
GigabitEthernet0/1.102 - Group 12 (version 2)
State is Standby
6 state changes, last state change 00:05:20
Link-Local Virtual IPv6 address is FE80::5:73FF:FEA0:C (impl auto EUI64)
Virtual IPv6 address 2001:9999:1:1::/64
Active virtual MAC address is 0005.73a0.000c
Local virtual MAC address is 0005.73a0.000c (v2 IPv6 default)
Hello time 3 sec, hold time 10 sec
Next hello sent in 0.448 secs
Preemption enabled
Active router is FE80::5054:FF:FE17:C2F3, priority 150 (expires in 10.000 sec)
MAC address is 5254.0017.c2f3
Standby router is local
Priority 120 (configured 120)
Group name is "hsrp-Gio/1.102-12" (default)
GigabitEthernet0/1.102 - Group 102 (version 2)
State is Standby
6 state changes, last state change 00:05:20
Virtual IP address is 44.9.0.129
Active virtual MAC address is 0000.0c9f.f066
Local virtual MAC address is 0000.0c9f.f066 (v2 default)
Hello time 3 sec, hold time 10 sec
Next hello sent in 0.160 secs
Preemption enabled
Active router is 44.9.0.131, priority 150 (expires in 7.776 sec)
MAC address is 5254.0017.c2f3
Standby router is local
Priority 120 (configured 120)
Group name is "hsrp-Gio/1.102-102" (default)
```

Obrázek 31: R1 FHRP detail 2/6

```
GigabitEthernet0/1.103 - Group 13 (version 2)
   State is Standby
   3 state changes, last state change 00:05:18
Link-Local Virtual IPv6 address is FE80::5:73FF:FEA0:D (impl auto EUI64)
      Virtual IPv6 address 2001:9999:1:2::/64
  Virtual TPV6 address 2001:99991:2::/04
Active virtual MAC address is 0005.73a0.000d
Local virtual MAC address is 0005.73a0.000d (v2 IPv6 default)
Hello time 3 sec, hold time 10 sec
Next hello sent in 1.392 secs
   Preemption enabled
  Active router is FE80::5054:FF:FE17:C2F3, priority 150 (expires in 8.448 sec) MAC address is 5254.0017.c2f3
 Priority 120 (configured 120)
Group name is "hsrp-Gi0/1.103-13" (default)
igabitEthernet0/1.103 - Group 103 (version 2)
   State is Standby
      3 state changes, last state change 00:05:21
  Virtual IP address is 44.9.0.193
Active virtual MAC address is 0000.0c9f.f067
  Local virtual MAC address is 0000.0c9f.f067 (v2 default) Hello time 3 sec, hold time 10 sec
     Next hello sent in 0.864 secs
   Preemption enabled
  Active router is 44.9.0.195, priority 150 (expires in 9.760 sec)
MAC address is 5254.0017.c2f3
   Standby router is local
  Priority 120 (configured 120)
Group name is "hsrp-Gi0/1.103-103" (default)
```

#### Obrázek 32: R1 FHRP detail 3/6

```
GigabitEthernet0/1.301 - Group 1 (version 2)

State is Active

4 state changes, last state change 00:05:41

Virtual IP address is 44.9.247.1

Active virtual MAC address is 0000.0c9f.f001

Local virtual MAC address is 0000.0c9f.f001 (v2 default)

Hello time 3 sec, hold time 10 sec

Next hello sent in 0.864 secs

Preemption enabled

Active router is local

Standby router is 44.9.247.3, priority 120 (expires in 10.848 sec)

Priority 150 (configured 150)

Track object 301 state Up decrement 30

Group name is "hsrp-Gi0/1.301-1" (default)

GigabitEthernet0/1.301 - Group 21 (version 2)

State is Active

4 state changes, last state change 00:05:41

Link-Local Virtual IPv6 address is FE80::5:73FF:FEA0:15 (impl auto EUI64)

Virtual IPv6 address 2001:9999:2::/64

Active virtual MAC address is 0005.73a0.0015

Local virtual MAC address is 0005.73a0.0015 (v2 IPv6 default)

Hello time 3 sec, hold time 10 sec

Next hello sent in 2.672 secs

Preemption enabled

Active router is local

Standby router is FE80::5054:FF:FE17:C2F3, priority 120 (expires in 10.880 sec)

Priority 150 (configured 150)

Track object 31 state Up decrement 30

Group name is "hsrp-Gi0/1.301-21" (default)
```

Obrázek 33: R1 FHRP detail 4/6

```
GigabitEthernet0/1.302 - Group 2 (version 2)
State is Active

4 state changes, last state change 00:05:42
Virtual IP address is 44.9.247.129
Active virtual MAC address is 0000.0c9f.f002
Local virtual MAC address is 0000.0c9f.f002
Local virtual MAC address is 0000.0c9f.f002 (v2 default)
Hello time 3 sec, hold time 10 sec
Next hello sent in 1.040 secs
Preemption enabled
Active router is local
Standby router is 44.9.247.131, priority 120 (expires in 11.360 sec)
Priority 150 (configured 150)
Track object 302 state Up decrement 30
Group name is "hsrp-Gi0/1.302-2" (default)
GigabitEthernet0/1.302 - Group 22 (version 2)
State is Active
4 state changes, last state change 00:05:41
Link-Local Virtual IPv6 address is FE80::5:73FF:FEA0:16 (impl auto EUI64)
Virtual IPv6 address 2001:9999:2:1::/64
Active virtual MAC address is 0005.73a0.0016
Local virtual MAC address is 0005.73a0.0016 (v2 IPv6 default)
Hello time 3 sec, hold time 10 sec
Next hello sent in 0.128 secs
Preemption enabled
Active router is local
Standby router is FE80::5054:FF:FE17:C2F3, priority 120 (expires in 8.000 sec)
Priority 150 (configured 150)
Track object 32 state Up decrement 30
Group name is "hsrp-Gi0/1.302-22" (default)
```

Obrázek 34: R1 FHRP detail 5/6

```
GigabitEthernet0/1.303 - Group 3 (version 2)

State is Active

4 state changes, last state change 00:05:42

Virtual IP address is 44.9.247.193

Active virtual MAC address is 0000.0c9f.f003

Local virtual MAC address is 0000.0c9f.f003 (v2 default)

Hello time 3 sec, hold time 10 sec

Next hello sent in 1.136 secs

Freemption enabled

Active router is local

Standby router is 44.9.247.195, priority 120 (expires in 9.680 sec)

Priority 150 (configured 150)

Track object 303 state Up decrement 30

Group name is "hsrp-Gi0/1.303-3" (default)

GigabitEthernet0/1.303 - Group 23 (version 2)

State is Active

4 state changes, last state change 00:05:41

Link-Local Virtual IPv6 address is FE80::5:73FF:FEA0:17 (impl auto EUI64)

Virtual IPv6 address 2001:9999:2:2:/64

Active virtual MAC address is 0005.73a0.0017

Local virtual MAC address is 0005.73a0.0017

Local virtual MAC address is 0005.73a0.0017

Local virtual MAC address is 005.73a0.0017 (v2 IPv6 default)

Hello time 3 sec, hold time 10 sec

Next hello sent in 0.464 secs

Preemption enabled

Active router is local

Standby router is FE80::5054:FF:FE17:C2F3, priority 120 (expires in 10.288 sec)

Priority 150 (configured 150)

Track object 33 state Up decrement 30

Group name is "hsrp-Gi0/1.303-23" (default)
```

Obrázek 35: R1 FHRP detail 6/6

```
GigabitEthernetO/1.101 - Group 11 (version 2)

State is Active

2 state changes, last state change 01:54:45

Link-Local Virtual IPv6 address is FE80::5:73FF:FEA0:B (impl auto EUI64)

Virtual IPv6 address 2001:9999:1::/64

Active virtual MAC address is 0005.73a0.000b

Local virtual MAC address is 0005.73a0.000b (v2 IPv6 default)

Hello time 3 sec, hold time 10 sec

Next hello sent in 0.112 secs

Preemption enabled

Active router is local

Standby router is FE80::5054:FF:FE06:69A1, priority 120 (expires in 8.688 sec)

Priority 120 (configured 120)

Track object 11 state Up decrement 30

Group name is "hsrp-Gi0/1.101-11" (default)

GigabitEthernetO/1.101 - Group 101 (version 2)

State is Active

1 state change, last state change 01:55:07

Virtual IP address is 44.9.0.1

Active virtual MAC address is 0000.0c9f.f065

Local virtual MAC address is 0000.0c9f.f065

Local virtual MAC address is 0000.0c9f.f065

Next hello sent in 2.288 secs

Preemption enabled

Active router is local

Standby router is 44.9.0.2, priority 120 (expires in 8.816 sec)

Priority 150 (configured 150)

Track object 101 state Up decrement 30

Group name is "hsrp-Gi0/1.101-101" (default)
```

Obrázek 36: R2 FHRP detail 1/6

```
GigabitEthernet0/1.102 - Group 12 (version 2)
State is Active

1 state change, last state change 01:55:07
Link-Local Virtual IPV6 address is FE80::5:73FF:FEA0:C (impl auto EUI64)
Virtual IPV6 address 2001:9999:1:1::/64
Active virtual MAC address is 0005.73a0.000c
Local virtual MAC address is 0005.73a0.000c (v2 IPV6 default)
Hello time 3 sec, hold time 10 sec
Next hello sent in 0.576 secs
Preemption enabled
Active router is local
Standby router is FE80::5054:FF:FE06:69A1, priority 120 (expires in 9.600 sec)
Priority 150 (configured 150)
Track object 12 state Up decrement 30
Group name is "hsrp-Gi0/1.102-12" (default)
GigabitEthernet0/1.102 - Group 102 (version 2)
State is Active
1 state change, last state change 01:55:06
Virtual IP address is 44.9.0.129
Active virtual MAC address is 0000.0c9f.f066
Local virtual MAC address is 0000.0c9f.f066 (v2 default)
Hello time 3 sec, hold time 10 sec
Next hello sent in 2.192 secs
Preemption enabled
Active router is local
Standby router is 44.9.0.130, priority 120 (expires in 8.176 sec)
Priority 150 (configured 150)
Track object 102 state Up decrement 30
Group name is "hsrp-Gi0/1.102-102" (default)
```

Obrázek 37: R2 FHRP detail 2/6

```
igabitEthernet0/1.103 - Group 13 (version 2)
 State is Active
 2 state changes, last state change 01:52:38
Link-Local Virtual IPv6 address is FE80::5:73FF:FEA0:D (impl auto EUI64)
 Virtual IPv6 address is FE80::5:73FF:FEA0:D (impl au Virtual IPv6 address 2001:9999:1:2::/64
Active virtual MAC address is 0005.73a0.000d
Local virtual MAC address is 0005.73a0.000d (v2 IPv6 default)
Hello time 3 sec, hold time 10 sec
    Next hello sent in 0.528 secs
 Preemption enabled
 Active router is local
 Standby router is FE80::5054:FF:FE06:69A1, priority 120 (expires in 10.608 sec)
 Priority 150 (configured 150)
Track object 13 state Up decrement 30
Group name is "hsrp-Gi0/1.103-13" (default)
igabitEthernet0/1.103 - Group 103 (version 2)
 State is Active
     2 state changes, last state change 01:52:48
 Virtual IP address is 44.9.0.193
Active virtual MAC address is 0000.0c9f.f067
Local virtual MAC address is 0000.0c9f.f067 (v2 default)
Hello time 3 sec, hold time 10 sec
    Next hello sent in 0.688 secs
 Preemption enabled
 Active router is local
Standby router is 44.9.0.194, priority 120 (expires in 9.840 sec)
 Priority 150 (configured 150)
 Track object 103 state Up decrement 30 Group name is "hsrp-Gi0/1.103-103" (default)
```

Obrázek 38: R2 FHRP detail 3/6

```
GigabitEthernet0/1.301 - Group 1 (version 2)
   State is Standby
  4 state changes, last state change 00:17:50 Virtual IP address is 44.9.247.1
  Active virtual MAC address is 0000.0c9f.f001
Local virtual MAC address is 0000.0c9f.f001 (v2 default)
Hello time 3 sec, hold time 10 sec
Next hello sent in 1.824 secs
   Preemption enabled
  Active router is 44.9.247.2, priority 150 (expires in 10.032 sec) MAC address is 5254.0006.69a1
   Standby router is local
  Priority 120 (configured 120)
Group name is "hsrp-Gi0/1.301-1" (default)
igabitEthernet0/1.301 - Group 21 (version 2)
   State is Standby
  4 state changes, last state change 00:17:50
Link-Local Virtual IPv6 address is FE80::5:73FF:FEA0:15 (impl auto EUI64)
  Virtual IPv6 address 2001:9999:2::/64
Active virtual MAC address is 0005.73a0.0015
Local virtual MAC address is 0005.73a0.0015 (v2 IPv6 default)
  Hello time 3 sec, hold time 10 sec
Next hello sent in 2.544 secs
   Preemption enabled
   Active router is FE80::5054:FF:FE06:69A1, priority 150 (expires in 7.680 sec)
      MAC address is 5254.0006.69a1
  Standby router is local
Priority 120 (configured 120)
Group name is "hsrp-Gi0/1.301-21" (default)
```

Obrázek 39: R2 FHRP detail 4/6

```
GigabitEthernet0/1.302 - Group 2 (version 2)
State is Standby
4 state changes, last state change 00:17:50
Virtual IP address is 44.9.247.129
Active virtual MAC address is 0000.0c9f.f002
Local virtual MAC address is 0000.0c9f.f002 (v2 default)
Hello time 3 sec, hold time 10 sec
Next hello sent in 1.136 secs
Preemption enabled
Active router is 44.9.247.130, priority 150 (expires in 10.944 sec)
MAC address is 5254.0006.69a1
Standby router is local
Priority 120 (configured 120)
Group name is "hsrp-Gi0/1.302-2" (default)

GigabitEthernet0/1.302 - Group 22 (version 2)
State is Standby
4 state changes, last state change 00:17:50
Link-Local Virtual IPv6 address is FE80::5:73FF:FEA0:16 (impl auto EUI64)
Virtual IPv6 address is 0005.73a0.0016
Local virtual MAC address is 0005.73a0.0016
Local virtual MAC address is 0005.73a0.0016
Local virtual Sec, hold time 10 sec
Next hello sent in 0.272 secs
Preemption enabled
Active router is FE80::5054:FF:FE06:69A1, priority 150 (expires in 8.288 sec)
MAC address is 5254.0006.69a1
Standby router is local
Priority 120 (configured 120)
Group name is "hsrp-Gi0/1.302-22" (default)
```

Obrázek 40: R2 FHRP detail 5/6

```
gabitEthernet0/1.303 - Group 3 (version 2)
State is Standby
   4 state changes, last state change 00:17:50
Virtual IF address is 44.9.247.193
Active virtual MAC address is 0000.0c9f.f003
Local virtual MAC address is 0000.0c9f.f003 (v2 default)
Hello time 3 sec, hold time 10 sec
Next hello sent in 0.304 secs
Preemption enabled
Active router is 44.9.247.194, priority 150 (expires in 8.192 sec)
MAC address is 5254.0006.69a1
Standby router is local
Priority 120 (configured 120)
Group name is "hsrp-Gi0/1.303-3" (default)
igabitEthernet0/1.303 - Group 23 (version 2)
State is Standby
4 state changes, last state change 00:17:48
Link-Local Virtual IPv6 address is FE80::5:73FF:FEA0:17 (impl auto EUI64)
Virtual IPv6 address 2001:9999:2:2::/64
Active virtual MAC address is 0005.73a0.0017
Local virtual MAC address is 0005.73a0.0017 (v2 IPv6 default)
Hello time 3 sec, hold time 10 sec
Next hello sent in 1.552 secs
Preemption enabled
Active router is FE80::5054:FF:FE06:69A1, priority 150 (expires in 8.000 sec) MAC address is 5254.0006.69a1
Standby router is local
Priority 120 (configured 120)
Group name is "hsrp-Gi0/1.303-23" (default)
```

Obrázek 41: R2 FHRP detail 6/6

do sh track

```
R1(config-if)#do sh track
Track 31
  IPv6 route 2001:9999:2::/64 reachability
  Reachability is Up (connected)
  1 change, last change 01:50:00
First-hop interface is GigabitEthernet0/1.301
  Tracked by:
    HSRP GigabitEthernet0/1.301 21
Track 32
 IPv6 route 2001:9999:2:1::/64 reachability
 Reachability is Up (connected)
1 change, last change 01:50:00
First-hop interface is GigabitEthernet0/1.302
  Tracked by:
    HSRP GigabitEthernet0/1.302 22
Track 33
 IPv6 route 2001:9999:2:2::/64 reachability
  Reachability is Up (connected)

1 change, last change 01:50:00

First-hop interface is GigabitEthernet0/1.303
  Tracked by:
    HSRP GigabitEthernet0/1.303 23
Track 301
 IP route 44.9.247.0 255.255.255.128 reachability Reachability is Up (connected) 2 changes, last change 02:19:48
  First-hop interface is GigabitEthernet0/1.301
  Tracked by:
    HSRP GigabitEthernet0/1.301 1
Track 302
 IP route 44.9.247.128 255.255.255.192 reachability
  Reachability is Up (connected)
    2 changes, last change 02:19:48
  First-hop interface is GigabitEthernet0/1.302
  Tracked by:
    HSRP GigabitEthernet0/1.302 2
Track 303
 IP route 44.9.247.192 255.255.255.240 reachability
  Reachability is Up (connected)
    2 changes, last change 02:19:48
  First-hop interface is GigabitEthernet0/1.303
  Tracked by:
    HSRP GigabitEthernet0/1.303 3
```

Obrázek 42: R1 Tracking

```
R2(config-if)#do sh track
Track 11
 IPv6 route 2001:9999:1::/64 reachability
 Reachability is Up (connected)
   1 change, last change 01:59:35
 First-hop interface is GigabitEthernet0/1.101
 Tracked by:
    HSRP GigabitEthernet0/1.101 11
Track 12
  IPv6 route 2001:9999:1:1::/64 reachability
 Reachability is Up (connected)
 1 change, last change 01:59:35
First-hop interface is GigabitEthernet0/1.102
 Tracked by:
   HSRP GigabitEthernet0/1.102 12
Track 13
 IPv6 route 2001:9999:1:2::/64 reachability
 Reachability is Up (connected)
   1 change, last change 01:59:35
 First-hop interface is GigabitEthernet0/1.103
 Tracked by:
    HSRP GigabitEthernet0/1.103 13
Track 101
 IP route 44.9.0.0 255.255.255.128 reachability
 Reachability is Up (connected)
    2 changes, last change 02:28:14
  First-hop interface is GigabitEthernet0/1.101
 Tracked by:
    HSRP GigabitEthernet0/1.101 101
Track 102
 IP route 44.9.0.128 255.255.255.192 reachability
 Reachability is Up (connected)
    2 changes, last change 02:28:14
  First-hop interface is GigabitEthernet0/1.102
 Tracked by:
    HSRP GigabitEthernet0/1.102 102
 IP route 44.9.0.192 255.255.255.240 reachability
 Reachability is Up (connected)
    2 changes, last change 02:28:14
 First-hop interface is GigabitEthernet0/1.103
 Tracked by:
    HSRP GigabitEthernet0/1.103 103
```

Obrázek 43: R2 Tracking

# 6 BGP

do sh ip bgp do sh bgp ipv6 prefixy

- 7 Management
- 7.1 IPv4 VRRP

## 8 IGP

do sh ip int br

```
ISP2(config) #do sh ip int br

Interface IP-Address OK? Method Status Protocol
GigabitEthernet0/0 unassigned YES unset administratively down down
GigabitEthernet0/1 44.9.248.15 YES manual up up
GigabitEthernet0/2 44.9.248.13 YES manual up up
GigabitEthernet0/3 unassigned YES unset administratively down down
Loopback0 44.9.254.8 YES manual up up
Loopback100 2.0.0.1 YES manual up up
```

Obrázek 44: ISP1 IPv4 interface brief

ISP1 (config) #do sh ip i	nt br		
Interface	IP-Address	OK? Method Status	Protocol
GigabitEthernet0/0	unassigned	YES unset administratively down	down
GigabitEthernet0/1	44.9.248.14	YES manual up	up
GigabitEthernet0/2	44.9.248.11	YES manual up	up
GigabitEthernet0/3	unassigned	YES unset administratively down	down
Loopback0	44.9.254.7	YES manual up	up
Loopback100	1.0.0.1	YES manual up	up

Obrázek 45: ISP2 IPv4 interface brief

WAN1(config-if)#do sh i	o int br		
Interface	IP-Address	OK? Method Status	Protocol
GigabitEthernet0/0	unassigned	YES unset administratively down	down
GigabitEthernet0/1	44.9.248.8	YES manual up	up
GigabitEthernet0/2	44.9.248.10	YES manual up	up
GigabitEthernet0/3	unassigned	YES unset up	up
GigabitEthernet0/3.9	44.9.248.1	YES manual up	up
GigabitEthernet0/3.91	44.9.253.249	YES manual up	up
GigabitEthernet0/4	unassigned	YES unset up	up
GigabitEthernet0/4.9	44.9.248.5	YES manual up	up
GigabitEthernet0/4.91	44.9.253.253	YES manual up	up
Loopback0	44.9.254.5	YES manual up	up
Loopback1	44.9.253.246	YES manual up	up

Obrázek 46: WAN1 IPv4 interface brief

WAN2(config-router)#do s Interface	IP-Address	OK? Method Status	Protocol
GigabitEthernet0/0	unassigned	YES unset administratively of	lown down
GigabitEthernet0/1	44.9.248.9	YES manual up	up
GigabitEthernet0/2	44.9.248.12	YES manual up	up
GigabitEthernet0/3	unassigned	YES unset up	up
GigabitEthernet0/3.9	44.9.248.7	YES manual up	up
GigabitEthernet0/3.91	44.9.253.255	YES manual up	up
GigabitEthernet0/4	unassigned	YES unset up	up
GigabitEthernet0/4.9	44.9.248.3	YES manual up	up
GigabitEthernet0/4.91	44.9.253.251	YES manual up	up
Loopback0	44.9.254.6	YES manual up	up
Loopback1	44.9.253.247	YES manual up	up

Obrázek 47: WAN2 IPv4 interface brief

```
IP-Address
                                                           OK? Method Status
                                                                                                         Protocol
GigabitEthernet0/0
GigabitEthernet0/0.9
                                    unassigned
unassigned
unassigned
                                                           YES unset up
YES manual deleted
                                                                                                        YES unset up
YES manual up
 igabitEthernet0/1
                                     44.9.252.2
44.9.0.2
igabitEthernet0/1.18
                                                           YES manual up
SigabitEthernet0/1.101
SigabitEthernet0/1.102
                                                           YES manual up
 igabitEthernet0/
                                                           YES manual
GigabitEthernet0/1.301
GigabitEthernet0/1.302
                                                           YES manual
                                                           YES manual
 igabitEthernet0/1.303
GigabitEthernet0/2
GigabitEthernet0/2.9
                                     unassigned
44.9.248.2
                                                           YES unset
                                                           YES manual
 igabitEthernet0/2.91
                                                           YES manual
GigabitEthernet0/3
GigabitEthernet0/3.9
GigabitEthernet0/3.9
                                     unassigned
                                                           YES unset
                                         9.248.0
                                                           YES manual
                                     44.9.253.248
 oopback1
                                                           YES
                                                                 manual
```

Obrázek 48: R1 IPv4 interface brief

R2(config)#do sh ip int b	r		
Interface	IP-Address	OK? Method Status	Protocol
GigabitEthernet0/0	unassigned	YES unset up	up
GigabitEthernet0/0.9	unassigned	YES manual deleted	down
GigabitEthernet0/1	unassigned	YES unset up	up
GigabitEthernet0/1.18	44.9.252.3	YES manual up	up
GigabitEthernet0/1.101	44.9.0.3	YES manual up	up
GigabitEthernet0/1.102	44.9.0.131	YES manual up	up
GigabitEthernet0/1.103	44.9.0.195	YES manual up	up
GigabitEthernet0/1.301	44.9.247.3	YES manual up	up
GigabitEthernet0/1.302	44.9.247.131	YES manual up	up
GigabitEthernet0/1.303	44.9.247.195	YES manual up	up
GigabitEthernet0/2	unassigned	YES unset up	up
GigabitEthernet0/2.9	44.9.248.4	YES manual up	up
GigabitEthernet0/2.91	44.9.253.252	YES manual up	up
GigabitEthernet0/3	unassigned	YES unset up	up
GigabitEthernet0/3.9	44.9.248.6	YES manual up	up
GigabitEthernet0/3.91	44.9.253.254	YES manual up	up
Loopback0	44.9.254.4	YES manual up	up
Loopback1	44.9.253.245	YES manual up	up

Obrázek 49: R2 IPv4 interface brief

DLSW1(config)#do sh i	p int br		
Interface	IP-Address	OK? Method Status	Protocol
GigabitEthernet0/0	unassigned	YES unset up	up
GigabitEthernet0/1	unassigned	YES unset up	up
GigabitEthernet0/2	unassigned	YES unset up	up
GigabitEthernet0/3	unassigned	YES unset up	down
GigabitEthernet1/0	unassigned	YES unset up	up
Loopback0	44.9.254.0	YES manual up	up
Port-channel1	unassigned	YES unset up	up
Vlan18	44.9.252.4	YES manual up	up

Obrázek 50: DLSW1 IPv4 interface brief

p int br			
IP-Address	OK? Method St	tatus Proto	col
unassigned	YES unset up	up	
unassigned	YES unset up	up	
unassigned	YES unset up	up	
unassigned	YES unset up	o down	
unassigned	YES unset up	up	
44.9.254.1	YES manual up	up	
unassigned	YES unset up	up	
44.9.252.5	YES manual up	up	
	IP-Address unassigned unassigned unassigned unassigned unassigned 44.9.254.1 unassigned	IP-Address OK? Method St unassigned YES unset up unassigned YES unset up unassigned YES unset up unassigned YES unset up unassigned YES unset up 44.9.254.1 YES manual up unassigned YES unset up	IP-Address OK? Method Status Proto unassigned YES unset up up unassigned YES unset up up unassigned YES unset up up unassigned YES unset up down unassigned YES unset up up up

Obrázek 51: DLSW2 IPv4 interface brief

```
Protocol
Interface
                           IP-Address
                                              OK? Method Status
GigabitEthernet0/0
                           unassigned
                                              YES unset
                                                                                       up
up
up
                                                            up
GigabitEthernet0/1
                           unassigned
                                              YES unset
GigabitEthernet0/2
                           unassigned
                                               YES unset
                                                            up
GigabitEthernet0/3
                           unassigned
                                               YES unset
                                                            up
GigabitEthernet1/0
GigabitEthernet1/1
                           unassigned
                                              YES unset
                           unassigned
unassigned
                                              YES unset
GigabitEthernet1/2
                                              YES unset
GigabitEthernet1/3
                           unassigned
                                              YES unset
                           44.9.254.2
44.9.252.6
44.9.0.126
44.9.0.190
44.9.0.206
                                               YES manual
                                                                                       up
                                                            up
Vlan18
                                               YES manual
Vlan101
                                              YES manual up
                                              YES manual up
Vlan102
71an103
                                               YES manual
 lan301
                                               YES manual
                                                            up
 lan302
                                               YES manual
                                                            up
71an303
                                               YES manual
```

Obrázek 52: ALSW1 IPv4 interface brief

### do sh ipv6 int br

```
ISP1(config)#do sh ipv6 int br
GigabitEthernet0/0
                        [administratively down/down]
    unassigned
GigabitEthernet0/1
                        [up/up]
    FE80::5054:FF:FE15:C3EB
    2001:9999::E
GigabitEthernet0/2
                        [up/up]
    FE80::5054:FF:FE14:A49F
    2001:9999::A
GigabitEthernet0/3
                        [administratively down/down]
    unassigned
Loopback0
                        [up/up]
    FE80::5054:FF:FE09:3F75
    2001:9999::407
Loopback100
                        [up/up]
    FE80::5054:FF:FE09:3F75
    2001:9999:1000::1
```

Obrázek 53: ISP1 IPv6 interface brief

```
ISP2(config)#do sh ipv6 int br
                        [administratively down/down]
GigabitEthernet0/0
    unassigned
GigabitEthernet0/1
                        [up/up]
    FE80::5054:FF:FE03:212C
    2001:9999::F
GigabitEthernet0/2
                        [up/up]
    FE80::5054:FF:FE06:8F9B
    2001:9999::C
GigabitEthernet0/3
                        [administratively down/down]
    unassigned
Loopback0
                        [up/up]
    FE80::5054:FF:FE10:E291
    2001:9999::408
Loopback100
                        [up/up]
    FE80::5054:FF:FE10:E291
    2001:9999:2000::1
```

Obrázek 54: ISP2 IPv6 interface brief

```
WAN1(config)#do sh ipv6 int br
                       [administratively down/down]
GigabitEthernet0/0
   unassigned
GigabitEthernet0/1
                       [up/up]
   FE80::5054:FF:FE1B:E376
   2001:9999::8
GigabitEthernet0/2
                        [up/up]
    FE80::5054:FF:FE1B:4A54
    2001:9999::B
GigabitEthernet0/3
                        [up/up]
   unassigned
GigabitEthernet0/3.9
                        [up/up]
   FE80::5054:FF:FE0A:6D0E
   2001:9999::
GigabitEthernet0/3.91
                       [up/up]
   unassigned
GigabitEthernet0/4
                        [up/up]
   unassigned
GigabitEthernet0/4.9
                        [up/up]
   FE80::5054:FF:FE13:CC01
   2001:9999::4
GigabitEthernet0/4.91
                       [up/up]
   unassigned
Loopback0
                        [up/up]
   FE80::5054:FF:FE0D:670B
   2001:9999::405
Loopback1
                        [up/up]
   unassigned
```

Obrázek 55: WAN1 IPv6 interface brief

```
WAN2(config) #do sh ipv6 int br
GigabitEthernet0/0
                        [administratively down/down]
    unassigned
GigabitEthernet0/1
                        [up/up]
    FE80::5054:FF:FE1C:3953
    2001:9999::9
GigabitEthernet0/2
                        [up/up]
    FE80::5054:FF:FE02:DE55
    2001:9999::D
GigabitEthernet0/3
                        [up/up]
    unassigned
GigabitEthernet0/3.9
                        [up/up]
    FE80::5054:FF:FE11:C5A
    2001:9999::6
GigabitEthernet0/3.91
                        [up/up]
    unassigned
GigabitEthernet0/4
                        [up/up]
    unassigned
GigabitEthernet0/4.9
                        [up/up]
    FE80::5054:FF:FE0D:9884
    2001:9999::2
GigabitEthernet0/4.91
                        [up/up]
    unassigned
Loopback0
                        [up/up]
    FE80::5054:FF:FE1D:FB56
    2001:9999::408
Loopback1
                        [up/up]
    unassigned
```

Obrázek 56: WAN2 IPv6 interface brief

```
R1(config)#do sh ipv6 int br
GigabitEthernet0/0
                       [up/up]
   unassigned
GigabitEthernet0/0.9
                       [deleted/down]
   unassigned
                  [up/up]
GigabitEthernet0/1
   unassigned
GigabitEthernet0/1.18 [up/up]
   unassigned
GigabitEthernet0/1.101 [up/up]
   FE80::5054:FF:FE06:69A1
   2001:9999:1::
   2001:9999:1::1
GigabitEthernet0/1.102 [up/up]
    FE80::5054:FF:FE06:69A1
    2001:9999:1:1::
    2001:9999:1:1::1
GigabitEthernet0/1.103 [up/up]
   FE80::5054:FF:FE06:69A1
   2001:9999:1:2::
    2001:9999:1:2::1
GigabitEthernet0/1.301 [up/up]
   FE80::5054:FF:FE06:69A1
   2001:9999:2::
   2001:9999:2::1
GigabitEthernet0/1.302 [up/up]
   FE80::5054:FF:FE06:69A1
   2001:9999:2:1::
    2001:9999:2:1::1
GigabitEthernet0/1.303 [up/up]
   FE80::5054:FF:FE06:69A1
    2001:9999:2:2::
   2001:9999:2:2::1
GigabitEthernet0/2
                    [up/up]
   unassigned
GigabitEthernet0/2.9 [up/up]
   FE80::5054:FF:FE02:5CF
    2001:9999::3
GigabitEthernet0/2.91 [up/up]
   unassigned
GigabitEthernet0/3 [up/up]
   unassigned
GigabitEthernet0/3.9 [up/up]
```

FE80::5054:FF:FE1F:1E47

Obrázek 57: R1 IPv6 interface brief 1/2

```
2001:9999::
2001:9999::1

GigabitEthernet0/3.91 [up/up]
unassigned

Loopback0 [up/up]
FE80::5054:FF:FE08:4BB5
2001:9999::403

Loopback1 [up/up]
unassigned
```

Obrázek 58: R1 IPv6 interface brief 2/2

```
R2(config)#do sh ipv6 int br
GigabitEthernet0/0
                    [up/up]
    unassigned
GigabitEthernet0/0.9
                       [deleted/down]
    unassigned
GigabitEthernet0/1 [up/up]
    unassigned
GigabitEthernet0/1.18 [up/up]
    unassigned
GigabitEthernet0/1.101 [up/up]
    FE80::5054:FF:FE17:C2F3
    2001:9999:1::
    2001:9999:1::2
GigabitEthernet0/1.102 [up/up]
    FE80::5054:FF:FE17:C2F3
    2001:9999:1:1::
    2001:9999:1:1::2
GigabitEthernet0/1.103 [up/up]
    FE80::5054:FF:FE17:C2F3
    2001:9999:1:2::
    2001:9999:1:2::2
GigabitEthernet0/1.301 [up/up]
    FE80::5054:FF:FE17:C2F3
    2001:9999:2::
    2001:9999:2::2
GigabitEthernet0/1.302 [up/up]
    FE80::5054:FF:FE17:C2F3
    2001:9999:2:1::
    2001:9999:2:1::2
GigabitEthernet0/1.303 [up/up]
    FE80::5054:FF:FE17:C2F3
    2001:9999:2:2::
    2001:9999:2:2::2
                       [up/up]
GigabitEthernet0/2
    unassigned
GigabitEthernet0/2.9 [up/up]
    FE80::5054:FF:FE1B:7390
    2001:9999::5
GigabitEthernet0/2.91 [up/up]
    unassigned
GigabitEthernet0/3
                       [up/up]
    unassigned
GigabitEthernet0/3.9 [up/up]
```

Obrázek 59: R2 IPv6 interface brief 1/2

FE80::5054:FF:FE02:4B2E
2001:9999::7

GigabitEthernet0/3.91 [up/up]
unassigned

Loopback0 [up/up]
FE80::5054:FF:FE11:7D40
2001:9999::404

Loopback1 [up/up]
unassigned

Obrázek 60: R2 IPv6 interface brief 1/2

DLSW1(config)#do sh ipv6 int br GigabitEthernet0/0 [up/up] unassigned GigabitEthernet0/1 [up/up] unassigned GigabitEthernet0/1.101 [deleted/down] unassigned GigabitEthernet0/2 [up/up] unassigned [up/down] GigabitEthernet0/3 unassigned GigabitEthernet1/0 [up/up] unassigned [up/up] Loopback0 FE80::5054:FF:FE00:6E45 2001:9999::400 Port-channel1 [up/up] unassigned Vlan18 [up/up] unassigned

Obrázek 61: DLSW1 IPv6 interface brief

GigabitEthernet0/0	[up/up]
unassigned	
GigabitEthernet0/1	[up/up]
unassigned	
GigabitEthernet0/2	[up/up]
unassigned	
GigabitEthernet0/3	[up/down]
unassigned	
GigabitEthernet1/0	[up/up]
unassigned	
Loopback0	[up/up]
FE80::5054:FF:FE01:	: 6758
2001:9999::401	
Port-channel1	[up/up]
unassigned	
Vlan18	[up/up]
unassigned	

Obrázek 62: DLSW2 IPv6 interface brief

ALSW1(config)#do sh ipv	76 int br
GigabitEthernet0/0	[up/up]
unassigned	
GigabitEthernet0/1	[up/up]
unassigned	
GigabitEthernet0/2	[up/up]
unassigned	
GigabitEthernet0/3	[up/up]
unassigned	
${ t GigabitEthernet1/0}$	[up/up]
unassigned	
GigabitEthernet1/1	[up/up]
unassigned	
GigabitEthernet1/2	[up/up]
unassigned	
GigabitEthernet1/3	[up/up]
unassigned	
Loopback0	[up/up]
FE80::5054:FF:FE0A:	:F92C
2001:9999::402	
Vlan18	[up/up]
unassigned	
Vlan101	[up/up]
FE80::5054:FF:FE0A:	: 8065
2001:9999:1::3	
Vlan102	[up/up]
unassigned	
Vlan103	[up/up]
unassigned	
Vlan301	[up/up]
unassigned	
Vlan302	[up/up]
unassigned	
Vlan303	[up/up]
unassigned	

#### Obrázek 63: ALSW1 IPv6 interface brief

#### do sh ip route

```
1.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
1.0.0.0/8 is directly connected, Loopback100
1.0.0.1/32 is directly connected, Loopback100
2.0.0.0/16 is subnetted, 1 subnets
2.0.0.0 [200/0] via 44.9.254.8, 02:15:52
44.0.0.0/8 is variably subnetted, 12 subnets, 5 masks
44.9.0.0/25 [20/1] via 44.9.248.10, 01:32:08
44.9.0.128/26 [20/1] via 44.9.248.10, 01:32:08
44.9.0.128/26 [20/1] via 44.9.248.10, 01:32:08
44.9.247.0/25 [20/1] via 44.9.248.10, 01:32:08
44.9.247.128/26 [20/1] via 44.9.248.10, 01:32:08
44.9.247.128/26 [20/1] via 44.9.248.10, 01:32:08
44.9.247.128/26 [20/1] via 44.9.248.10, 01:32:08
44.9.247.192/28 [20/1] via 44.9.248.10, 01:32:08
44.9.248.11/32 is directly connected, GigabitEthernet0/2
44.9.248.14/31 is directly connected, GigabitEthernet0/1
44.9.248.14/32 is directly connected, GigabitEthernet0/1
44.9.254.7/32 is directly connected, Loopback0
44.9.254.8/32 [1/0] via 44.9.248.15
```

#### Obrázek 64: ISP1 IPv4 routes

```
B 1.0.0.0/8 [200/0] via 44.9.254.7, 02:16:01
2.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
2.0.0.0/16 is directly connected, Loopback100
2.0.0.1/32 is directly connected, Loopback100
44.0.0.0/8 is variably subnetted, 9 subnets, 5 masks
44.9.247.0/25 [20/1] via 44.9.248.12, 02:03:24
B 44.9.247.128/26 [20/1] via 44.9.248.12, 02:03:24
C 44.9.248.12/31 is directly connected, GigabitEthernet0/2
44.9.248.13/32 is directly connected, GigabitEthernet0/2
44.9.248.14/31 is directly connected, GigabitEthernet0/1
44.9.248.15/32 is directly connected, GigabitEthernet0/1
44.9.248.15/32 is directly connected, GigabitEthernet0/1
44.9.254.7/32 [1/0] via 44.9.248.14
C 44.9.254.8/32 is directly connected, Loopback0
```

#### Obrázek 65: ISP2 IPv4 routes

```
E 1.0.0.0/8 [20/0] via 44.9.248.11, 02:04:29
2.0.0.0/16 is subnetted, 1 subnets
2.0.0.0 [20/0] via 44.9.248.11, 02:04:29
44.0.0.0/8 is variably subnetted, 20 subnets, 5 masks
0 E2 44.9.0.0/25 [110/1] via 44.9.248.4, 00:33:14, GigabitEthernet0/4.9
[110/1] via 44.9.248.0, 01:33:24, GigabitEthernet0/4.9
[110/1] via 44.9.248.0, 01:33:24, GigabitEthernet0/4.9
[110/1] via 44.9.248.0, 01:33:24, GigabitEthernet0/3.9
0 E2 44.9.0.192/28 [110/1] via 44.9.248.4, 00:33:14, GigabitEthernet0/4.9
[110/1] via 44.9.248.0, 01:33:24, GigabitEthernet0/4.9
[110/1] via 44.9.248.0, 01:33:24, GigabitEthernet0/4.9
[110/1] via 44.9.248.0, 01:33:24, GigabitEthernet0/3.9
0 E2 44.9.247.10/25 [110/1] via 44.9.248.0, 01:33:24, GigabitEthernet0/3.9
0 E2 44.9.247.128/26
[110/1] via 44.9.248.0, 01:33:24, GigabitEthernet0/3.9
0 E2 44.9.247.192/28
[110/1] via 44.9.248.0, 01:33:24, GigabitEthernet0/3.9
0 E2 44.9.247.192/28
[110/1] via 44.9.248.0, 01:33:24, GigabitEthernet0/3.9
0 E2 44.9.248.0/31 is directly connected, GigabitEthernet0/3.9
0 E4 4.9.248.1/32 is directly connected, GigabitEthernet0/3.9
0 E4 4.9.248.1/32 is directly connected, GigabitEthernet0/3.9
0 E4 9.248.8/31 is directly connected, GigabitEthernet0/4.9
0 44.9.248.8/31 is directly connected, GigabitEthernet0/1
0 44.9.248.8/32 is directly connected, GigabitEthernet0/1
0 44.9.248.10/31 is directly connected, GigabitEthernet0/1
0 44.9.248.10/31 is directly connected, GigabitEthernet0/1
0 44.9.248.10/32 is directly connected, GigabitEthernet0/2
0 44.9.254.3/32 [110/10] via 44.9.248.9, 01:33:24, GigabitEthernet0/4.9
0 44.9.254.3/32 is directly connected, GigabitEthernet0/1
```

#### Obrázek 66: WAN1 IPv4 routes

Obrázek 67: WAN2 IPv4 routes

```
0.*E2 0.0.0.0/0 [110/1] via 44.9.248.1, 01:10:48, GigabitEthernet0/3.9
44.0.0.0/8 is variably subnetted, 23 subnets, 5 masks

44.9.0.0/25 is directly connected, GigabitEthernet0/1.101
44.9.0.2/32 is directly connected, GigabitEthernet0/1.101
44.9.0.128/26 is directly connected, GigabitEthernet0/1.102
44.9.0.130/32 is directly connected, GigabitEthernet0/1.102
44.9.0.192/28 is directly connected, GigabitEthernet0/1.103
44.9.0.194/32 is directly connected, GigabitEthernet0/1.103
44.9.0.194/32 is directly connected, GigabitEthernet0/1.301
44.9.247.0/25 is directly connected, GigabitEthernet0/1.301
44.9.247.128/26 is directly connected, GigabitEthernet0/1.302
44.9.247.130/32 is directly connected, GigabitEthernet0/1.302
44.9.247.194/32 is directly connected, GigabitEthernet0/1.303
44.9.247.194/32 is directly connected, GigabitEthernet0/1.303
44.9.247.194/32 is directly connected, GigabitEthernet0/3.9
44.9.248.0/31 is directly connected, GigabitEthernet0/3.9
44.9.248.0/32 is directly connected, GigabitEthernet0/2.9
44.9.248.2/31 is directly connected, GigabitEthernet0/2.9
44.9.248.2/31 is directly connected, GigabitEthernet0/2.9
44.9.248.2/31 is directly connected, GigabitEthernet0/2.9
44.9.248.8/31 [110/20] via 44.9.248.1, 00:10:31, GigabitEthernet0/3.9
44.9.248.8/31 [110/61] via 44.9.248.1, 01:10:48, GigabitEthernet0/3.9
44.9.248.8/31 [110/20] via 44.9.248.1, 01:10:48, GigabitEthernet0/3.9
44.9.254.4/32 [110/20] via 44.9.248.1, 01:10:48, GigabitEthernet0/3.9
44.9.254.4/32 [110/20] via 44.9.248.1, 01:10:48, GigabitEthernet0/3.9
44.9.254.4/32 [110/20] via 44.9.248.1, 01:10:48, GigabitEthernet0/3.9
44.9.254.6/32 [110/10] via 44.9.248.1, 01:10:48, GigabitEthernet0/3.9
```

Obrázek 68: R1 IPv4 routes

Obrázek 69: R2 IPv4 routes

#### do sh ipv6 route

```
2001:9999::A/127 [0/0]
 via GigabitEthernet0/2, directly connected
2001:9999::A/128 [0/0]
 via GigabitEthernet0/2, receive
2001:9999::E/127 [0/0]
 via GigabitEthernet0/1, directly connected
2001:9999::E/128 [0/0]
 via GigabitEthernet0/1, receive
2001:9999::407/128 [0/0]
 via Loopback0, receive
2001:9999::408/128 [1/0]
 via 2001:9999::F
2001:9999:1000::/48 [0/0]
via Loopback100, directly connected 2001:9999:1000::1/128 [0/0]
via Loopback100, receive
FF00::/8 [0/0]
via NullO, receive
```

Obrázek 70: ISP1 IPv6 routes

```
2001:9999::c/127 [0/0]
    via GigabitEthernet0/2, directly connected
   2001:9999::c/128 [0/0]
    via GigabitEthernet0/2, receive
    2001:9999::E/127 [0/0]
    via GigabitEthernet0/1, directly connected
    2001:9999::F/128 [0/0]
    via GigabitEthernet0/1, receive
    2001:9999::407/128 [1/0]
    via 2001:9999::E
   2001:9999::408/128 [0/0]
T.C.
    via Loopback0, receive
    2001:9999:1000::/48 [200/0]
    via 2001:9999::407
    2001:9999:2000::/56 [0/0]
    via Loopback100, directly connected
   2001:9999:2000::1/128 [0/0]
    via Loopback100, receive
   FF00::/8 [0/0]
    via NullO, receive
```

Obrázek 71: ISP2 IPv6 routes

```
2001:9999::/127 [0/0]
 via GigabitEthernet0/3.9, directly connected
2001:9999::2/127 [110/51]
via FE80::5054:FF:FE1C:3953, GigabitEthernet0/1
2001:9999::4/127 [0/0]
 via GigabitEthernet0/4.9, directly connected
2001:9999::4/128 [0/0]
 via GigabitEthernet0/4.9, receive
2001:9999::6/127 [110/51]
via FE80::5054:FF:FE1C:3953, GigabitEthernet0/1
2001:9999::8/127 [0/0]
 via GigabitEthernet0/1, directly connected
2001:9999::8/128 [0/0]
 via GigabitEthernet0/1, receive
2001:9999::A/127 [0/0]
via GigabitEthernet0/2, directly connected
2001:9999::B/128 [0/0]
 via GigabitEthernet0/2,
2001:9999::403/128 [110/10]
 via FE80::5054:FF:FE1F:1E47, GigabitEthernet0/3.9
2001:9999::404/128 [110/10]
via FE80::5054:FF:FE1B:7390, GigabitEthernet0/4.9
2001:9999::405/128 [0/0]
via Loopback0, receive
2001:9999::408/128 [110/1]
 via FE80::5054:FF:FE1C:3953, GigabitEthernet0/1
2001:9999:1000::/48 [20/0]
via FE80::5054:FF:FE14:A49F, GigabitEthernet0/2
FF00::/8 [0/0]
 via NullO, receive
```

Obrázek 72: WAN1 IPv6 routes

```
2001:9999::/127 [110/11]
 via FE80::5054:FF:FE1B:E376, GigabitEthernet0/1
2001:9999::2/127 [0/0]
 via GigabitEthernet0/4.9, directly connected
2001:9999::2/128 [0/0]
 via GigabitEthernet0/4.9, receive
2001:9999::4/127 [110/11]
via FE80::5054:FF:FE1B:E376, GigabitEthernet0/1
2001:9999::6/127 [0/0]
 via GigabitEthernet0/3.9, directly connected
2001:9999::6/128 [0/0]
 via GigabitEthernet0/3.9, receive
2001:9999::8/127 [0/0]
 via GigabitEthernet0/1, directly connected
2001:9999::9/128 [0/0]
 via GigabitEthernet0/1, receive
2001:9999::c/127 [0/0]
 via GigabitEthernet0/2, directly connected
2001:9999::D/128 [0/0]
 via GigabitEthernet0/2, receive
2001:9999::403/128 [110/11]
via FE80::5054:FF:FE1B:E376, GigabitEthernet0/1
2001:9999::404/128 [110/11]
 via FE80::5054:FF:FE1B:E376, GigabitEthernet0/1
2001:9999::405/128 [110/1]
via FE80::5054:FF:FE1B:E376, GigabitEthernet0/1
2001:9999::408/128 [0/0]
 via Loopback0, receive
2001:9999:1000::/48 [20/0]
 via FE80::5054:FF:FE06:8F9B, GigabitEthernet0/2
FF00::/8 [0/0]
 via Null0, receive
```

Obrázek 73: WAN2 IPv6 routes

```
::/0 [110/1], tag 2
 via FE80::5054:FF:FE0A:6D0E, GigabitEthernet0/3.9
2001:9999::/127 [0/0]
via GigabitEthernet0/3.9, directly connected
2001:9999::/128 [0/0]
 via GigabitEthernet0/3.9, receive
2001:9999::1/128 [0/0]
 via GigabitEthernet0/3.9, receive
2001:9999::2/127 [0/0]
via GigabitEthernet0/2.9, directly connected
2001:9999::3/128 [0/0]
 via GigabitEthernet0/2.9, receive
2001:9999::4/127 [110/20]
 via FE80::5054:FF:FE0A:6D0E, GigabitEthernet0/3.9
2001:9999::6/127 [110/61]
 via FE80::5054:FF:FE0A:6D0E, GigabitEthernet0/3.9
2001:9999::8/127 [110/11]
 via FE80::5054:FF:FE0A:6D0E, GigabitEthernet0/3.9
2001:9999::403/128 [0/0]
via Loopback0, receive
2001:9999::404/128 [110/20]
 via FE80::5054:FF:FE0A:6D0E, GigabitEthernet0/3.9
2001:9999::405/128 [110/10]
via FE80::5054:FF:FE0A:6D0E, GigabitEthernet0/3.9
2001:9999::408/128 [110/11]
 via FE80::5054:FF:FE0A:6D0E, GigabitEthernet0/3.9
2001:9999:1::/64 [0/0]
via GigabitEthernet0/1.101, directly connected
```

Obrázek 74: R1 IPv6 routes 1/2

```
2001:9999:1::1/128 [0/0]
via GigabitEthernet0/1.101, receive
2001:9999:1:1::/64 [0/0]
via GigabitEthernet0/1.102, directly connected
2001:9999:1:1::1/128 [0/0]
 via GigabitEthernet0/1.102, receive
2001:9999:1:2::/64 [0/0]
 via GigabitEthernet0/1.103, directly connected
2001:9999:1:2::1/128 [0/0]
via GigabitEthernet0/1.103, receive
2001:9999:2::/64 [0/0]
via GigabitEthernet0/1.301, directly connected
2001:9999:2::/128 [0/0]
via GigabitEthernet0/1.301, receive
2001:9999:2::1/128 [0/0]
via GigabitEthernet0/1.301, receive
2001:9999:2:1::/64 [0/0]
via GigabitEthernet0/1.302, directly connected
2001:9999:2:1::/128 [0/0]
via GigabitEthernet0/1.302, receive
2001:9999:2:1::1/128 [0/0]
via GigabitEthernet0/1.302, receive
2001:9999:2:2::/64 [0/0]
via GigabitEthernet0/1.303, directly connected
2001:9999:2:2::/128 [0/0]
via GigabitEthernet0/1.303, receive
2001:9999:2:2::1/128 [0/0]
via GigabitEthernet0/1.303, receive
FF00::/8 [0/0]
via NullO, receive
```

Obrázek 75: R1 IPv6 routes 2/2

```
::/0 [110/1], tag 2
 via FE80::5054:FF:FE13:CC01, GigabitEthernet0/2.9
2001:9999::/127 [110/20]
via FE80::5054:FF:FE13:CC01, GigabitEthernet0/2.9
2001:9999::2/127 [110/61]
via FE80::5054:FF:FE13:CC01, GigabitEthernet0/2.9
2001:9999::4/127 [0/0]
 via GigabitEthernet0/2.9, directly connected
2001:9999::5/128 [0/0]
via GigabitEthernet0/2.9, receive
2001:9999::6/127 [0/0]
via GigabitEthernet0/3.9, directly connected
2001:9999::7/128 [0/0]
via GigabitEthernet0/3.9, receive
2001:9999::8/127 [110/11]
via FE80::5054:FF:FE13:CC01, GigabitEthernet0/2.9
2001:9999::403/128 [110/20]
via FE80::5054:FF:FE13:CC01, GigabitEthernet0/2.9
2001:9999::404/128 [0/0]
via Loopback0, receive
2001:9999::405/128 [110/10]
 via FE80::5054:FF:FE13:CC01, GigabitEthernet0/2.9
2001:9999::408/128 [110/11]
via FE80::5054:FF:FE13:CC01, GigabitEthernet0/2.9
```

Obrázek 76: R2 IPv6 routes 1/2

```
2001:9999:1::/64 [0/0]
via GigabitEthernet0/1.101, directly connected
2001:9999:1::/128 [0/0]
via GigabitEthernet0/1.101, receive
2001:9999:1::2/128 [0/0]
via GigabitEthernet0/1.101, receive
2001:9999:1:1::/64 [0/0]
via GigabitEthernet0/1.102, directly connected
2001:9999:1:1::/128 [0/0]
 via GigabitEthernet0/1.102, receive
2001:9999:1:1::2/128 [0/0]
 via GigabitEthernet0/1.102, receive
2001:9999:1:2::/64 [0/0]
 via GigabitEthernet0/1.103, directly connected
2001:9999:1:2::/128 [0/0]
via GigabitEthernet0/1.103, receive
2001:9999:1:2::2/128 [0/0]
via GigabitEthernet0/1.103, receive
2001:9999:2::/64 [0/0]
via GigabitEthernet0/1.301, directly connected
2001:9999:2::2/128 [0/0]
via GigabitEthernet0/1.301, receive
2001:9999:2:1::/64 [0/0]
via GigabitEthernet0/1.302, directly connected
2001:9999:2:1::2/128 [0/0]
via GigabitEthernet0/1.302, receive
2001:9999:2:2::/64 [0/0]
via GigabitEthernet0/1.303, directly connected
2001:9999:2:2::2/128 [0/0]
 via GigabitEthernet0/1.303, receive
FF00::/8 [0/0]
via Nullo, receive
```

Obrázek 77: R2 IPv6 routes 2/2

### do sh ospfv3 int br

R1(config)#	do sh	ospfv3	int br				
Interface	PID	Area		AF	Cost	State	Nbrs F/C
Lo0	1	0		ipv4	1	LOOP	0/0
Gi0/3.9	1	0		ipv4	10	DR	1/1
Gi0/2.9	1	0		ipv4	50	DR	1/1
Lo0	2	0		ipv6	1	LOOP	0/0
Gi0/3.9	2	0		ipv6	10	DR	1/1
Gi0/2.9	2	0		ipv6	50	DR	1/1
Gi0/0.9	4	0		ipv4	1	DR	0/0
Gi0/1.103	4	1		ipv4	1	DR	0/0
Gi0/1.102	4	1		ipv4	1	DR	0/0
Gi0/1.101	4	1		ipv4	1	DR	0/0
Gi0/1.303	4	2		ipv4	1	DR	0/0
Gi0/1.302	4	2		ipv4	1	DR	0/0
Gi0/1.301	4	2		ipv4	1	DR	0/0
Gi0/0.9	6	0		ipv6	1	DR	0/0
Gi0/1.103	6	1		ipv6	1	DR	0/0
Gi0/1.102	6	1		ipv6	1	DR	0/0
Gi0/1.101	6	1		ipv6	1	DR	0/0
Gi0/1.303	6	2		ipv6	1	DR	0/0
Gi0/1.302	6	2		ipv6	1	DR	0/0
Gi0/1.301	6	2		ipv6	1	DR	0/0

Obrázek 78: R1 OSPFv3 Brief

R2(config-if	) #do :	sh ospfv3 int br				
Interface	PID	Area	AF	Cost	State	Nbrs F/C
Lo0	1	0	ipv4	1	LOOP	0/0
Gi0/3.9	1	0	ipv4	50	BDR	1/1
Gi0/2.9	1	0	ipv4	10	DR	0/0
Lo0	2	0	ipv6	1	LOOP	0/0
Gi0/3.9	2	0	ipv6	50	BDR	1/1
Gi0/2.9	2	0	ipv6	10	DR	0/0
Gi0/0.9	4	0	ipv4	1	DR	0/0
Gi0/1.103	4	1	ipv4	1	DR	0/0
Gi0/1.102	4	1	ipv4	1	DR	0/0
Gi0/1.101	4	1	ipv4	1	DR	0/0
Gi0/1.303	4	2	ipv4	1	DR	0/0
Gi0/1.302	4	2	ipv4	1	DR	0/0
Gi0/1.301	4	2	ipv4	1	DR	0/0
Gi0/0.9	6	0	ipv6	1	DR	0/0
Gi0/1.103	6	1	ipv6	1	DR	0/0
Gi0/1.102	6	1	ipv6	1	DR	0/0
Gi0/1.101	6	1	ipv6	1	DR	0/0
Gi0/1.303	6	2	ipv6	1	DR	0/0
Gi0/1.302	6	2	ipv6	1	DR	0/0
Gi0/1.301	6	2	ipv6	1	DR	0/0

Obrázek 79: R2 OSPFv3 Brief

WAN1 (config	-if)#d	o sh ospfy	v3 int br			
Interface	PID	Area	AF	Cost	State	Nbrs F/C
Lo0	1	0	ipv4	1	LOOP	0/0
Gi0/4.9	1	0	ipv4	10	DOWN	0/0
Gi0/3.9	1	0	ipv4	10	BDR	1/1
Gi0/1	1	0	ipv4	1	BDR	1/1
Lo0	2	0	ipv6	1	LOOP	0/0
Gi0/4.9	2	0	ipv6	10	DOWN	0/0
Gi0/3.9	2	0	ipv6	10	BDR	1/1
Gi0/1	2	0	ipv6	1	BDR	1/1

Obrázek 80: WAN1 OSPFv3 Brief

WAN2 (config	-route:	r)#do sh	ospfv3 int br			
Interface	PID	Area	AF	Cost	State	Nbrs F/C
Lo0	1	0	ipv4	1	LOOP	0/0
Gi0/4.9	1	0	ipv4	50	BDR	1/1
Gi0/3.9	1	0	ipv4	50	DR	1/1
Gi0/1	1	0	ipv4	1	DR	1/1
Lo0	2	0	ipv6	1	LOOP	0/0
Gi0/4.9	2	0	ipv6	50	BDR	1/1
Gi0/3.9	2	0	ipv6	50	DR	1/1
Gi0/1	2	0	ipv6	1	DR	1/1

Obrázek 81: WAN2 OSPFv3 Brief

## 9 Link state

žádné bodíky nebudou :(

- 10 Konektivita IPv4
- 10.1 Ping
- 10.2 Traceroute

# 11 Konektivita IPv6

- 11.1 Ping
- 11.2 Traceroute