DeepSignal - Complete Project Guide

This guide describes the application as it exists in this repository: its architecture, pages, data flow, models, evaluation and backtesting, persistence, scheduled work, setup, APIs, and limitations. It is intended to be the main technical and user-facing reference for the project.

> Purpose: DeepSignal is an educational stock-analysis and machine-learning research prototype. It does not place trades, provide financial advice, or guarantee a prediction or return. Market data from Yahoo Finance can be delayed, incomplete, or unavailable.

Contents

1. At a glance
2. System architecture
3. User interface and workflows
4. Market data, news, and features
5. Prediction models and the hybrid signal
6. Saved model artifacts and versioning
7. Evaluation and backtesting
8. Caching and scheduled market-data updates
9. Persistence and database design
10. API reference
11. Project layout
12. Run the project
13. Configuration
14. Validation and troubleshooting
15. Security, privacy, and boundaries
16. Current limitations and future work
17. Glossary

1. At a glance

DeepSignal is a local full-stack web app. The browser provides the dashboard and analysis pages. A Python API fetches market data, engineers features, runs model components, combines their evidence, and returns a JSON result. The app can optionally use a hosted Supabase database for online history; without it, the backend writes supported records to local JSON files.

Main capabilities

- Select a ticker from saved signal history or type a new symbol. The shared ticker control appears on Dashboard, Analysis, Backtest, and Models. It displays a company name from a small built-in list or looks one up through Yahoo Finance.
- Display daily OHLCV market history, a candlestick chart, technical indicators, recent headlines, sentiment, feature importance, and signal evidence.
- Estimate next-session up/down direction with an explicit weighted hybrid of LSTM, Random Forest, FinBERT sentiment, and technical rules.
- Show Buy, Sell, or Hold signals, including the stronger Buy/Sell variants in the backend response.
- Compare models on a chronological holdout and run a separate reproducible chronological evaluation.
- Run a rule-based, next-open backtest with transaction fees, slippage, portfolio tracking, and baselines.
- Save versioned fitted model artifacts and enough metadata to identify the data, preprocessing, configuration, software versions, and target used.
- Periodically refresh and persist daily bars and technical features in a lightweight background thread.
- Store cache, job, model, prediction, and experiment status for inspection through API routes.

Main technologies

Area	Technology
Browser UI	React, React Router, Vite, Recharts, Lucide icons, CSS
HTTP API	FastAPI, Uvicorn, Pydantic
Data handling	Python, pandas, NumPy, yfinance, requests
Models	TensorFlow/Keras LSTM, scikit-learn Random Forest, Hugging Face FinBERT
Optional comparison/explanation	XGBoost, SHAP
Hosted persistence	Supabase Postgres through its HTTPS REST API


The project does not require installing a local database server. Supabase is optional. The backend's local JSON fallback works without it.

2. System architecture

The React application and FastAPI service run as separate processes. In local development, Vite serves the web app on port 5173 and forwards /api requests to FastAPI on port 8000. The browser never imports or runs the Python model code directly.

The colored boxes marked MODEL are the model/evidence components. XGBoost is drawn outside the ensemble because it is an optional comparison model, not a voting component.

System architecture - model components highlighted




Blue = trained model component Green = explicit hybrid Purple = optional comparison

Main request flow: prediction

1. A user selects or types a ticker and chooses a forecast display horizon on Analysis.
2. React sends GET /api/predict/{symbol}?timeframe=... to FastAPI.
3. FastAPI normalizes the symbol and gets adjusted daily OHLCV history from Yahoo Finance through yfinance.
4. The service hashes the exact downloaded window and calculates indicators. It builds a next-session-up training target from adjacent closes.
5. It retrieves recent headlines from NewsAPI when configured and then Yahoo Finance sources as needed. FinBERT scores up to eight headlines; unavailable news/model output falls back to neutral sentiment.
6. LSTM and Random Forest independently produce probabilities for the same directional target. XGBoost may provide a separate holdout comparison. Technical rules produce a fourth evidence value.
7. backend/hybrid.py combines the four compatible inputs using the fixed versioned weights. Thresholds turn the combined score into a signal.
8. The backend creates an accompanying rule-based backtest report, attaches data and model metadata, and persists the prediction when configured.
9. React renders the result and adds the prediction to the browser's signal history.

Prediction request: backend processing and output



Separate stores: fitted model files stay local - cache is temporary - browser signals stay in localStorage - backtest uses its own technical strategy.

The pipeline view expands the deployment architecture into the request-time sequence. The trained estimators produce direction evidence, while FinBERT and technical rules contribute independent inputs before the hybrid. Persistence and browser state are separate outputs.

Two distinct meanings of “saved”

- Saved signals in the UI: Stored in the current browser's localStorage. This is what the ticker dropdown and Signals page use. It does not require Supabase and is not synchronized between browsers.
- Backend prediction/history records: Saved through Supabase when configured, otherwise to backend JSON. These can be read from /api/history/predictions; the UI signal list does not currently import that backend history automatically.

3. User interface and workflows

The app uses React Router. All pages share a selected ticker state. The selected ticker is retained in browser local storage, so changing pages does not reset it.

Shared ticker picker and company name

Dashboard, Analysis, Backtest, and Models share the same ticker control. It contains a text input with a datalist of Apple and tickers found in locally saved signals. The user can choose a suggestion or type another ticker. Typing is normalized to uppercase.

The company name appears beside the input, outside the ticker box. A short built-in map covers common symbols; other valid-looking symbols are looked up by GET /api/company/{symbol} after a short pause in typing. The backend caches successful names for one day and lookup misses for 30 minutes. If Yahoo cannot supply a name, the UI says the company name is unavailable. The lookup is a convenience and does not validate that a ticker has usable historical prices.

Header and appearance

- The theme button switches between light and dark themes. The selected theme is saved in browser local storage.
- The small Live badge means the interface can refresh status/data periodically. It does not mean exchange-level real-time prices. Its tooltip explains that status refresh is periodic and prices use the latest available daily data.
- Layout, charts, cards, ticker fields, tables, and navigation are styled for desktop and smaller screens. The navigation collapses on mobile. The charts are lazy-loaded to reduce the initial UI bundle.

Dashboard

Shows browser-saved signal counts, buy/sell counts, average saved confidence, and the data source. The market card lets the user pick a ticker, then loads approximately three months of daily history and displays a candlestick chart, latest available price, period change, indicators, and a directional price-momentum gauge.

Below the gauge, the Latest Saved Signal panel shows the most recently saved Buy/Hold/Sell-style result for that selected ticker, confidence when available, and its saved time. It does not infer a Buy or Sell from the gauge. If the browser has no saved signal for that ticker, it links to Analysis to generate one. This means a prediction saved on another browser or only in backend history will not appear in this panel.

Dashboard market history refreshes when the selected ticker changes and then periodically while the page is open. A separate status poll reads /api/jobs/market-data. Those refreshes do not make the underlying daily price feed real-time.

Analysis

Select a ticker, choose 1D, 1W, 1M, or 3M, and run Analyze. The result includes:

- signal, trend, latest close and market date;
- estimated direction score, confidence-style display, and a heuristic predicted-change figure;
- an evidence panel showing component probability, weight, and contribution;
- the feature importance and available SHAP explanation;
- technical indicators and recent news/sentiment;
- an accompanying historical chart and risk/interpretation notes.

The underlying classifier target is always next-session direction. The selected horizon changes only the separate predicted-change heuristic; it does not train a 1-week or 1-month price model. Running a new analysis saves/replaces the same ticker+horizon item in browser history, retaining up to 100 signals.

Backtest

Runs a separate technical momentum/RSI strategy over historical bars, then displays the strategy curve beside buy-and-hold and no-trade. Metrics include return, CAGR, Sharpe, drawdown, exposure, turnover, and executed trades. It is not a simulation of the live hybrid prediction signal.

Models

Shows the model families and invokes a prediction to display model comparison data, chronological holdout dates, feature importance, and SHAP values if available. Random Forest and optional XGBoost holdout results are shown when returned. LSTM validation metadata is recorded in its saved artifact; the Models page's primary comparison report should not be mistaken for the dedicated /api/evaluate experiment.

Tuning

Loads and saves backend settings for LSTM lookback, LSTM units, epochs, Random Forest tree count, transaction-cost percentage, and slippage percentage. The backend validates ranges and writes settings to backend/tuning_config.json. The prediction and backtest services read this shared process configuration.

Signals

Lists prediction results saved by the current browser. The user can clear this browser's signal history. Clearing it does not delete backend/Supabase prediction records.

Research and Settings

Research summarizes the workflow and methodology. Settings describes the local /api path and deployment CORS configuration; it does not expose or edit secrets.

4. Market data, news, and features

Price history

download_history requests Yahoo Finance auto-adjusted daily OHLCV bars: open, high, low, close, volume. It normalizes dates, sorts/cleans data, and rejects empty or malformed results. Prediction normally uses a multi-year data window; dashboard history requests three months, while history/evaluation endpoints allow specified periods. Yahoo Finance is an external provider, not a guaranteed feed. U.S. symbols are usually plain tickers (for example AAPL); Yahoo uses suffix conventions for some markets (for example RELIANCE.NS). A symbol must be recognized by Yahoo and have usable data.

The prediction response distinguishes market_timestamp/as_of (date of last market bar) from retrieved_at/prediction_timestamp (when the backend fetched or produced the result). A recent retrieval time does not mean the underlying bar is from the current minute.

Company-name lookup

GET /api/company/{symbol} calls yfinance ticker metadata and returns symbol, company_name, and found. It accepts a restricted ticker-character set and caches the result. Built-in frontend names can be displayed without calling the lookup endpoint. Company metadata is not a substitute for successful price-history validation.

News collection and FinBERT input

If NEWS_API_KEY exists, the backend first tries the NewsAPI Everything endpoint. If fewer than eight headlines were collected or that provider fails, it can add Yahoo Finance search results and then yfinance ticker news. It filters empty/duplicate titles and returns at most eight headlines for sentiment scoring. Provider/network failures are tolerated; prediction continues with an empty or partial news list.

The default sentiment model is ProsusAI/finbert from Hugging Face Transformers; FINBERT_MODEL can override it. The first use may download model weights into the local Transformers cache and consume disk, memory, and network bandwidth. FinBERT analyzes headline text and returns positive probability minus negative probability, producing a signed score approximately in [-1, +1]. No articles or model failure yields neutral sentiment (0). FinBERT is pretrained; it is not trained from this project's stock history.

Technical features

Indicators are computed in pandas; TA-Lib is not required.

Feature	Meaning
SMA 20 / SMA 50	Rolling averages of adjusted daily closing prices.
RSI 14	Rolling gain/loss momentum indicator. Extreme values are clues, not guaranteed reversals.
MACD / signal	EMA(12) minus EMA(26), with an EMA(9) signal line.
Bollinger bands	SMA(20) plus/minus two rolling standard deviations.
return_1d, return_5d	Change in close over one or five trading observations.
sma20_gap, sma50_gap	Close relative to the corresponding average.

Feature	Meaning
bb_position	Close position relative to lower/upper Bollinger bands.
volume_change	Change in volume from the preceding observation.
sentiment	Current request's aggregate headline sentiment.

Rolling indicators need a warm-up period. Rows with missing or infinite required feature values are excluded from model fitting.

Backend data preparation, in execution order

The prediction path is orchestrated in backend/main.py by build_prediction. It normalizes the ticker, obtains daily bars, records retrieval time and the last bar date, hashes the raw input window, and computes or reuses technical features. It then gathers current headlines, scores them, creates next-session labels for historical rows, and invokes the LSTM and Random Forest paths. The latest feature row is inference input: its next-session target is unknown and is not used as a training label.

download_history asks yfinance for auto-adjusted daily bars and normalizes the date column to UTC before removing the timezone for internal calculations. The returned frame contains date, open, high, low, close, and volume. The input fingerprint is SHA-256 over those ordered bar values and is attached to the prediction so the exact source window can be identified later. indicators derives rolling and exponential calculations from close and volume. Early rows naturally lack some rolling values; the model paths remove rows missing required inputs. Infinite percentage changes are converted to missing values rather than passed to estimators.

The label is aligned to the row that makes the decision: target[t] = 1 if close[t+1] > close[t]; otherwise it is 0 (down or unchanged). Thus the feature vector at row t contains information available through that close, while its label refers to the next trading observation. This is why the most recent row can be scored for inference but cannot contribute a known label. The live backend uses the current headline aggregate as a request-level sentiment value; it does not reconstruct historical news for every training row.

There are two model input matrices because the model families consume different representations:

- LSTM sequence input: ordered close, sma20, sma50, rsi, macd, bb_upper, bb_lower; each sample is a sliding window of the most recent lookback rows. MinMaxScaler transforms those columns. The latest sequence produces one sigmoid value in [0, 1].
- Random Forest tabular input: return_1d, return_5d, sma20_gap, sma50_gap, rsi, macd, macd_signal, bb_position, and volume_change. It consumes one row at a time and does not scale the values. Although sentiment exists in the general feature frame, it is deliberately excluded from the forest input; sentiment has its own FinBERT component in the hybrid.

After these model outputs are ready, the backend computes explicit technical evidence from the latest row, maps it to a 0-1 value, and sends the four compatible values into backend/hybrid.py. The API response preserves the raw market dates, component values, weights, weighted contributions, signal rule, feature importance, optional SHAP values, model comparison, and model-version ID. React formats these fields; it does not train or alter the models.

5. Prediction models and the hybrid signal

Target definition

The classifier target is 1 when the next trading session's adjusted close is above the current session's adjusted close, otherwise 0. The decision convention is after the current session close; the outcome is measured at the next session close. It is a direction target, not a future dollar-price prediction.

Model roles

Component	Role in the live hybrid	Inputs / output
LSTM	40% of the hybrid	Sequence of recent price/indicator rows; probability of next-session up direction.
Random Forest	40% of the hybrid	Tabular returns, gaps, RSI, MACD, Bollinger position, volume change; probability of up direction.

Component	Role in the live hybrid	Inputs / output
FinBERT	10% of the hybrid after mapping	Recent headline text; positive-minus-negative sentiment, mapped to a 0-1 proxy.
Technical rules	10% of the hybrid	Moving-average alignment, 5-day return threshold, and RSI/MACD conditions; mapped to a 0-1 score.
XGBoost	Not in the hybrid	Optional separate model comparison and probability; its result does not vote in the final signal.

LSTM

TensorFlow/Keras builds a binary sequence classifier. The live model uses the ordered columns close, sma20, sma50, rsi, macd, bb_upper, and bb_lower; a MinMaxScaler transforms them. Defaults are 30 observations of lookback, 48 LSTM units, 0.2 dropout, a 16-unit dense layer, sigmoid output, Adam, binary cross-entropy, batch size 32, and up to 6 epochs with early stopping. The random seed is 42.

The scaler is saved with the fitted LSTM artifact. In the live training path it is fit on the available feature window before the sequence validation split; therefore the reported validation behavior is not a fully untouched chronological test. If TensorFlow is missing/incompatible or there are too few sequences, LSTM probability falls back to 0.5 and metadata records why.

Each sample is one lookback x 7 array and its label is the following close-direction value. The backend requires at least 80 sequences. It uses the earlier portion for fitting and a trailing validation slice for early stopping; the split point is max(floor(85% of samples), sample_count - 40), so validation is at least roughly 15% until the 40-row cap applies. It restores the best validation weights. A saved matching LSTM and scaler bypass refitting and transform only the latest sequence for inference. A neutral 0.5 fallback is an explicit availability path, not a learned result.

Random Forest

The forest is a scikit-learn RandomForestClassifier with a default of 250 trees, maximum depth 7, minimum leaf size 4, balanced class weights, and seed 42. It uses return_1d, return_5d, moving-average gaps, RSI, MACD and signal, Bollinger position, and volume change. No scaling is applied. With enough labeled data, a trailing chronological holdout is scored first; then a separate forest is refit on all available labeled rows for the current inference. With fewer than 100 usable rows, the component returns 0.5 and reports insufficient samples.

The live holdout is the latest 20% where possible, with at least 20 test rows and at least 80 earlier fitting rows. The holdout accuracy is descriptive metadata; the inference model is a newly fitted forest using all rows whose next-session label is known. The latest unlabeled row is held aside for the actual score. Feature importance is the forest's impurity-based feature importance, which describes split usage in this fitted forest and is not a causal explanation.

Optional XGBoost and SHAP

When XGBoost imports and fits successfully, the backend scores it on the Random Forest comparison window, then refits it for an up probability. The comparison uses 180 estimators, depth 4, learning rate 0.05, row/column subsampling of 0.85, log-loss, and seed 42. XGBoost is guarded as optional; failures do not stop the main prediction. It is not included in hybrid weights. SHAP is also attempted for the latest Random Forest input; when unavailable or failing, its explanation is omitted/empty. Random Forest feature importance is separately returned.

FinBERT is different from the locally fitted estimators: it is a pretrained text classifier loaded lazily through Transformers. The backend asks it for positive, negative, and neutral label scores for each of up to eight titles; for each title it computes positive minus negative, then averages the title scores. Its neutral label is not added to the formula. No headlines or an import/inference error produces score 0 and allows price-based components to proceed. Headlines and sentiment accompany the API response; they are not persisted as a separate training corpus.

Explicit hybrid rule

backend/hybrid.py owns the target definition, hybrid version (weighted-probability-v1), and fixed weights:

```
hybrid up score =
0.40 x LSTM probability-up
+ 0.40 x Random Forest probability-up
+ 0.10 x ((FinBERT score + 1) / 2)
+ 0.10 x technical probability-up
```

The sentiment mapping is a simple, documented proxy, not a calibrated probability. Technical rules add/subtract fixed points, clip the result to [-1, +1], then map it to [0, 1]. The score and its component inputs, weights, and contributions are returned for inspection.

In the technical component, bullish alignment (close > SMA20 > SMA50) adds 0.45; bearish alignment subtracts 0.45. A five-day return above +2% adds 0.25 and below -2% subtracts 0.25. RSI below 35 with MACD above its signal adds 0.30; RSI above 65 with MACD below its signal subtracts 0.30. The sum is clipped to [-1, 1], then converted to a probability-like value using (score + 1) / 2. These are hand-authored rules and fixed point sizes, not fitted coefficients.

Combined score	Signal
0.64 or higher	Strong Buy
0.54 to below 0.64	Buy
Above 0.46 to below 0.54	Hold
Above 0.36 through 0.46	Sell
0.36 or lower	Strong Sell

The dashboard's saved-signal card presents the simpler BUY/HOLD/SELL wording and does not derive a signal from the price-momentum gauge. Backend prediction details may include Strong Buy or Strong Sell.

Confidence and predicted change

The displayed confidence-like number is derived from distance of the combined score from 0.5. It is not a calibrated probability, confidence interval, or percentage chance of profit. The predicted_change figure is a separate heuristic based on the combined score, recent 5-day return, and square-root horizon scaling. It is not an output of a regression model and is not a price target. Selecting 1W/1M/3M does not change the model's next-session classification target.

What the prediction output contains

The GET /api/predict/{symbol} response is a structured record rather than a single label. Its main fields have distinct purposes:

Output	How the backend creates it	How the UI uses it
stock_symbol, company_name	Normalized ticker; company_name in this prediction payload is initially the ticker placeholder. The frontend resolves a display name separately through /api/company/{symbol}.	Labels the selected security, using the separate lookup when available.
market_data, as_of, latest_close	Source, interval, last market timestamp, retrieval time, date range, row count, and SHA-256 of the exact bar window.	Shows what data the result is based on and its freshness.
lstm_probability_up, classifier_probability_up	Latest sequence score and latest-row forest score.	Supports component comparison and evidence.
sentiment_score, news	FinBERT signed title scores and up to eight scored titles.	Displays current headline evidence and sentiment.
signal_explanation	Hybrid score, target, version, weights, each component's value and contribution, and technical factors.	Powers the evidence panel and makes the rule auditable.
signal_type, predicted_trend, confidence	Thresholded hybrid score and distance-from-neutral display.	Headline signal and confidence-style presentation.
predicted_change	Separate horizon-scaled heuristic, not a price-regression model.	Displays an estimated directional change figure with interpretation limits.
technical_indicators, feature_importance, model_comparison	Latest indicators, forest importances, holdout comparison and optional SHAP.	Feeds indicator cards and Models/Analysis explanation panels.

Output	How the backend creates it	How the UI uses it
model_version	Deterministic identity for ticker, exact data window, code/configuration, features, and installed package set.	Identifies which saved fitted artifact matched this prediction.
backtest, risk_factors, analysis_summary	Separate technical strategy report and explanatory text.	Adds historical context and limitations; backtest is not the hybrid's simulated return.

Once model construction and inference complete, the API tries to save the result. A storage write failure is returned as a persistence.status=failed field while the computed prediction is still returned. This lets the UI show a result while making its save status explicit.

6. Saved model artifacts and versioning

backend/model_registry.py writes fitted model artifacts under backend/model_artifacts/ by default (or DEEPSIGNAL_ARTIFACT_DIR if configured). It stores a deterministic version identity based on ticker, exact market-data SHA-256 fingerprint and date window, target, ordered feature lists, preprocessing/feature/model-code versions, hybrid version, tuning configuration, sentiment model name, random seeds, and installed package versions.

Each artifact directory contains JSON metadata plus whichever fitted files were actually captured: a Random Forest estimator, optional XGBoost estimator, LSTM Keras model, and LSTM scaler. The metadata records data window/hash, target, feature order and input shape, hyperparameters, package versions, validation status/metrics, model statuses, and inference explanation metadata. The directory is written through a temporary path and atomically renamed to avoid a partially written version. Loading verifies the metadata identity, expected files, model/scaler dimensions, and Random Forest feature order before putting the bundle into the process cache. The version is an identity hash, not a claim that model quality improved.

The full identity includes the complete price-window hash and configuration. Since the hash changes when the downloaded window changes, matching is exact and a new version is usually created after new market bars arrive. FinBERT's pretrained weights are managed by the Hugging Face cache rather than this registry. The registry is for reproducibility and reuse on the same machine; metadata in Supabase does not upload the binary files.

When the same complete identity is requested again, the backend can load the saved model, scaler, and metadata instead of fitting again. If the market data window or identity changes, a different version is created. Saved LSTM, Random Forest, and available XGBoost estimators, the LSTM scaler, and optional Keras model are written as an artifact bundle with JSON metadata; the loader checks identifiers, expected files, input shape, and feature order. A bounded in-process loaded-model cache holds recent versions. Older artifacts are retained for rollback; they are local files, not automatically uploaded to Supabase.

Useful routes:

- GET /api/models - list model-version metadata.
- GET /api/models/{version} - inspect one version.
- POST /api/models/{version}/load - validate and load it into the current backend process.

Loading an artifact does not force its use for a different ticker/data/configuration identity. The pretrained FinBERT weights remain in the Hugging Face cache and are identified by model name; they are not copied into every trained-model artifact. The backtest is rule-based and carries strategy/engine versions instead of a fitted model version.

7. Evaluation and backtesting

Dedicated direction evaluation

GET /api/evaluate/{symbol} downloads up to three years of daily history and builds a chronological train/validation/test report for next-session direction. It needs at least 120 usable samples and both classes in fitting data; otherwise it returns an explicit insufficient-data status.

- First 60%: initial training window; the LSTM scaler is fit only on these rows.
- Rows through the first 80% are available to fit/evaluate models before the final holdout. The Random Forest is fit on those first 80%; the LSTM uses an earlier fit portion and an internal validation portion for early stopping.
- Final 20%: shared holdout test window for all compared methods.
- Compares previous-session-direction baseline, Random Forest, LSTM, and weighted hybrid.

- Reports accuracy, precision/recall/F1 for up class, confusion matrix, and simplified trading metrics.
- Reports buy-and-hold and flat-cash baselines and hybrid deltas versus component models.
- Records the data hash, dates, parameters, model/package versions, and assumptions.

Evaluation fits the LSTM scaler using only the earlier 60% training rows. Historical point-in-time news is not available, so evaluation explicitly uses neutral sentiment on all historical hybrid test rows. This means it does not validate the live news/FinBERT contribution. The models share final test dates, but this is one final holdout, not repeated rolling retraining of every component.

Rule-based historical backtest

The Backtest page and GET /api/backtest/{symbol} use a separate long-only technical strategy. Signals are created after each daily close using:

- BUY when 5-day return is above 0.6% and RSI is below 72;
- SELL when 5-day return is below -0.6% and RSI is above 28;
- otherwise HOLD.

Signals execute at the next available daily open, which prevents using a future price for the order. Position size targets the configured fraction of equity (default 100%); fractional shares are allowed. Buys/sells include adverse slippage and a percentage transaction cost. The engine tracks cash, holdings, equity, trades, drawdown, exposure, turnover, return, CAGR, and annualized Sharpe. It liquidates any remaining position at the final close with costs.

The report compares the strategy with buy-and-hold (including modeled costs) and no-trade cash. It contains the price-data hash, signal hash, date window, strategy and engine versions, parameters, and execution assumptions. It sets model_version to null because it is not a trained-model strategy. The live prediction endpoint also includes a rule-based backtest payload for presentation, but that payload is not a simulation of the prediction ensemble.

Metrics: what they do and do not say

- Accuracy: fraction of direction labels classified correctly; can hide class imbalance.
- Precision / recall / F1: focus on the positive/up class and its false alarms/misses.
- Confusion matrix: counts actual versus predicted up/down labels.
- Cumulative return / CAGR: historical simulated account growth over a selected window.
- Maximum drawdown: largest peak-to-trough loss in the reported equity curve.
- Sharpe: annualized average return relative to variability under the report's assumptions.
- Turnover / trade count / exposure: describe trading activity and time invested.

Metrics depend on provider data, window, thresholds, costs, and implementation assumptions. Past simulation is not a promise of future results.

8. Caching and scheduled market-data updates

In-process cache

backend/cache.py provides a bounded, thread-safe TTL cache. It is local to one backend process and clears on restart. It tracks hits, misses, expirations, evictions, and provider call timing.

- Yahoo daily OHLCV requests: 15-minute default TTL (MARKET_DATA_CACHE_TTL_SECONDS); 0 disables this cache. Scheduled refresh explicitly bypasses it.
- Technical feature results: keyed by input-data fingerprint and feature-code version; cached for 24 hours.
- Company-name lookups: successful result cached for one day; unsuccessful lookup cached for 30 minutes.
- Prediction response: not cached because market data/news can change.

GET /api/cache/status reports cache and TTL details. This cache reduces repeated work but is not shared between backend workers and does not survive restart.

Scheduler

backend/scheduler.py starts a daemon thread during backend startup unless MARKET_DATA_REFRESH_ENABLED=false. It immediately attempts a refresh, then waits the configured interval (six hours by default; minimum five minutes). MARKET_DATA_SYMBOLS is a comma-separated ticker list, default AAPL.

For each ticker it fetches about one year of daily bars, bypasses the request cache, validates missing/duplicate/out-of-order data, computes technical features, and stores bars and features. A ticker is retried up to three times with short exponential delays. The job records start/end times, success/partial/failure state, rows, tickers, and per-symbol failures. Its latest status is available at GET /api/jobs/market-data.

The scheduler handles market-data refresh and feature calculation. It does not perform scheduled model fitting/inference. Yahoo determines when daily data becomes available; scheduled polling cannot make that source real-time. A single in-process thread is suitable for this prototype, not a distributed job system.

9. Persistence and database design

Storage choices

The backend talks to Supabase Postgres through HTTPS REST calls using requests; no local DB server or Postgres Python driver is required. Set both SUPABASE_URL and SUPABASE_SECRET_KEY in backend/.env to use it. If both are absent, the backend uses local JSON fallbacks. If only one or invalid settings are supplied, storage reports an incomplete/invalid state rather than silently pretending it connected.

The backend persists:

- Predictions: prediction response, ticker, horizon, timestamp, signal, model version, input window, data fingerprint, and explanation.
- Signals: signal type, timestamp, strategy/hybrid version, reason, and metadata tied to the prediction.
- Market-data runs: metadata/fingerprint and reference to the data used by a prediction.
- Experiments: evaluation/backtest report, run ID, metric summaries, parameters, versions, date window, and assumptions.
- Scheduled market bars: daily OHLCV bars and computed feature JSON for configured tickers, after migration 002 is installed.
- Background job runs: scheduler status and details, after migration 002 is installed.

Each record exists to answer a different operational or research question:

Stored record	Reason to retain it	Important boundary
Market-data run metadata	Identify the provider, date range, input row count, retrieval time, quality status, and hash that underpinned a prediction.	The live prediction path stores metadata; it does not upload every historical OHLCV row into this table.
Prediction	Reopen prior backend outputs and compare ticker, signal, horizon, model version, input window, score, and response.	Backend history is separate from the browser's local signal cards.
Signal	Maintain a queryable, prediction-linked signal record with its hybrid version and reason.	It is descriptive output storage; there is no order execution or risk-control engine.
Experiment	Preserve a backtest/evaluation run with parameters, metrics, dates, data hash, and assumptions for later inspection or comparison.	It stores the report and provenance, not a guarantee of future behavior.
Scheduled bars and features	Retain refreshable OHLCV and derived feature snapshots for configured symbols, keyed by symbol/interval/date.	Only the background refresh writes these rows; migration 002 is required.
Job run	Explain whether a scheduled refresh succeeded, partially failed, or failed, how many rows it processed, and per-ticker errors.	Job state is a persisted summary; the scheduler itself still runs in one backend process.
Model artifact files	Reuse a fitted estimator and scaler when the complete model identity matches; record enough metadata to inspect the build.	Files remain local unless manually backed up; Supabase stores identifiers/records, not these binaries.
Tuning configuration	Keep user-selected model and simulation parameters across backend restarts.	Stored in local backend/tuning_config.json, not in the Supabase schema.
Backend cache	Avoid repeating provider and feature work during a process lifetime.	Temporary and cleared when the backend restarts.
Browser localStorage	Keep selected ticker, theme, and up to 100 UI signal snapshots on that browser.	Device/browser-specific; not synchronized with backend prediction history.

In Supabase, market_data_runs is the provenance record referenced by predictions; predictions holds the result; signals has a one-to-one foreign-key link to that result; and experiments holds evaluation/backtest report payloads. Migration 002 adds market_data_bars (unique by symbol, interval, timestamp) and background_job_runs. These are not interchangeable stores: model files are local, the TTL cache is ephemeral, and UI history lives in the browser.

Tables for predictions/signals/market-data runs/experiments are in backend/sql/001_persistent_storage.sql. Scheduler tables are in backend/sql/002_market_data_scheduler.sql. Both migrations are run in the Supabase Dashboard SQL Editor. They enable row-level security, revoke public/anonymous/authenticated access, and grant the backend service role the intended table access. The secret key belongs only in the backend environment; do not put it in frontend code or commit it.

Without Supabase, local fallbacks include prediction_runs.json, evaluation_runs.json, backtest_runs.json, market_data_bars.json, and job_runs.json under backend/. They are local and ignored by Git. Tuning config and model artifacts are also local. The frontend's browser signal history is separate from all these backend stores.

Supabase setup

1. Create a Supabase project and copy its Project URL and Secret key.
2. Run backend/sql/001_persistent_storage.sql once in that project's SQL Editor.
3. If scheduled bar/job persistence is wanted, also run backend/sql/002_market_data_scheduler.sql.
4. Put SUPABASE_URL and SUPABASE_SECRET_KEY in backend/.env, preserving other settings. Never paste the secret into frontend settings or a public place.
5. Restart the backend and open http://localhost:8000/api/storage/status. Confirm status is connected.
6. Run predictions/evaluations/backtests; inspect history via the API. Restarting the backend should not remove Supabase records.
7. Existing local experiment reports can be imported once through POST /api/storage/import-local-experiments; run IDs make retries idempotent.

The prediction/history API can save metadata and model outputs without uploading every historical price row. The scheduler separately stores daily bars when migration 002 is applied. Browser-only saved signals are not automatically migrated to Supabase.

10. API reference

Interactive API docs are available at http://localhost:8000/docs while the backend is running. API responses are JSON. Vite proxies browser /api calls to the backend during development.

Method	Route	Purpose
GET	/api/health	Basic backend health and UTC time.
GET	/api/company/{symbol}	Resolve a ticker to a company name through Yahoo metadata.
GET	/api/predict/{symbol}?timeframe=1D	Run live model inference, return signal/evidence, include a rule-based backtest, and persist prediction. Horizons accepted: 1D, 1W, 1M, 3M.
GET	/api/history/{symbol}?period=3mo	Return daily OHLCV history. Periods accepted: 3mo, 6mo, 1y, 2y, 3y.
GET	/api/backtest/{symbol}	Run and persist the rule-based next-open backtest.
GET	/api/evaluate/{symbol}	Run and persist the chronological direction model evaluation.
GET	/api/generalization	Run the fixed multi-sector example backtest basket.
GET	/api/config	Read tuning configuration.
POST	/api/config	Validate and save tuning configuration JSON.
GET	/api/models	List saved model versions; accepts optional limit.
GET	/api/models/{version}	Return saved version metadata.

Method	Route	Purpose
POST	/api/models/{version}/load	Validate/load a saved artifact into the backend process. Requires POST, not browser address-bar GET.
GET	/api/history/predictions?symbol=AAPL	Read backend-saved predictions; symbol filter is optional.
GET	/api/history/experiments?kind=backtest	Read evaluation/backtest runs; kind is optional.
GET	/api/storage/status	Check configured storage connectivity or local fallback mode.
POST	/api/storage/import-local-experiments	Import local evaluation/backtest JSON into configured Supabase.
GET	/api/jobs/market-data	Scheduler enablement, configured symbols, last run and latest successful refresh.
GET	/api/cache/status	In-process cache counts and TTL configuration.

11. Project layout

```
DeepSignal/

|-- backend/

| |-- main.py FastAPI routes, prediction orchestration, features and model calls

| |-- hybrid.py Direction target, hybrid version, weights and probability fusion

| |-- model_registry.py Artifact identity, persistence, validation and loading

| |-- evaluation.py Chronological model evaluation report

| |-- backtesting.py Timestamp-aware portfolio simulation engine

| |-- scheduler.py Background daily market-data refresh

| |-- cache.py Bounded in-process TTL cache

| |-- database.py Supabase REST and local JSON persistence

| |-- requirements.txt Backend runtime dependencies

| |-- requirements-dev.txt Runtime plus test client dependency

| |-- .env.example Safe settings template

| |-- sql/

| | |-- 001_persistent_storage.sql

| | `-- 002_market_data_scheduler.sql

| `-- tests/ Focused unittest suite

|-- frontend/

| |-- package.json

| |-- package-lock.json
```

```
| |-- vite.config.js

| |-- index.html

| `-- src/

| |-- main.jsx Pages, shared ticker state, API calls, UI logic

| |-- Charts.jsx Reusable Recharts components

| `-- styles.css Themes, layouts, responsive UI and component styles

|-- docs/

| `-- DeepSignal_Project_Guide.md This complete project reference

`-- tools/

`-- build_project_guide_pdf.py Rebuilds the guide PDF with Python only
```

Generated directories such as backend/.venv, frontend/node_modules, frontend/dist, backend/model_artifacts, local environment files, and local run histories are not source files and are ignored by Git.

File-by-file responsibilities

The tree above is the quick map. This inventory describes the maintained source and configuration files individually; generated environments, downloaded model weights, caches, and local run-history JSON are runtime data and are intentionally not listed as source.

Repository-level files

File	Responsibility
README.md	Short project overview, local setup, first prediction, evaluation, backtesting, and Supabase/scheduler guidance. The detailed behavior reference is this guide.
.gitignore	Excludes virtual environments, installed frontend packages, build output, secrets, local configuration, reports, and fitted artifacts from version control.
.gitattributes	Repository text-file and line-ending conventions.
.vscode/settings.json	Workspace editor preferences for contributors using Visual Studio Code.
run_backend.bat	Windows helper that checks Python, creates the backend virtual environment if needed, copies the safe environment template when absent, installs runtime requirements, and launches Uvicorn on port 8000.
run_frontend.bat	Windows helper that checks npm, installs locked frontend dependencies when needed, and starts the Vite development server.

Backend Python modules

File	Responsibility
backend/main.py	FastAPI application and route definitions; ticker normalization; Yahoo price and company lookups; indicator construction; news collection and FinBERT scoring; LSTM/forest inference and optional comparison; prediction orchestration; tuning configuration; scheduler lifecycle hooks. This is the service composition layer.
backend/hybrid.py	Defines the next-session-up target contract, hybrid version and component weights; validates probabilities; maps sentiment and produces the auditable weighted result and signal category.
backend/model_registry.py	Creates stable model identities and version IDs; writes and validates local artifact bundles; restores compatible estimators/scalers; maintains a bounded loaded-model cache.
backend/evaluation.py	Builds chronological train, validation, and final test windows; compares direction models and baselines on common dates; produces metrics, hashes, assumptions, and a persisted experiment report.

File	Responsibility
backend/backtesting.py	Implements the separate timestamp-aware technical strategy; executes orders at the next open; accounts for costs/slippage, cash, shares, equity, baselines, trades, and performance metrics.
backend/database.py	Storage adapter for optional Supabase Postgres over HTTPS and local JSON fallback; persists predictions, signals, experiments, market bars, and scheduler status.
backend/cache.py	Bounded, thread-safe in-process TTL cache and cache/provider timing counters. It does not share state between backend processes.
backend/scheduler.py	Starts/stops the background refresh thread; fetches configured symbols, validates and feature-engineers bars, retries failures, persists data, and reports job status.

Backend configuration and database schema

File	Responsibility
backend/requirements.txt	Runtime Python packages needed by the API and its supported model/data paths.
backend/requirements-dev.txt	Development/test dependency additions on top of runtime requirements.
backend/.env.example	Safe template for optional provider keys, Supabase settings, cache/scheduler controls, artifact path, and CORS origins. It contains no live secret.
backend/sql/001_persistent_storage.sql	Creates the core Supabase tables and access policies for prediction and experiment persistence.
backend/sql/002_market_data_scheduler.sql	Adds scheduled market-bar and refresh-job persistence used by the background scheduler.

Backend test files

File	Responsibility
backend/tests/test_validation.py	Checks health/prediction response shapes, signal boundaries, tuning validation/persistence, provider absence, and graceful optional-model failure behavior.
backend/tests/test_routes.py	Guards route declaration ordering so fixed history routes are not captured by the dynamic ticker route.
backend/tests/test_hybrid.py	Verifies weighted component arithmetic, audit fields, invalid-input rejection, and shared evaluation comparisons.
backend/tests/test_model_registry.py	Verifies artifact identity changes and reloading compatible artifacts in a clean process.
backend/tests/test_backtesting.py	Verifies next-open order timing, portfolio accounting, and cost/slippage reporting.
backend/tests/test_database.py	Checks local JSON persistence/readback and Supabase request/upsert behavior, including symbol filtering and backend-only secret headers.
backend/tests/test_cache.py	Checks TTL expiration, copy protection, and avoiding repeated provider calls for cached price history.
backend/tests/test_scheduler.py	Checks configured ticker selection and refresh validation/persistence summaries.

The focused tests also exercise evaluation through its shared hybrid comparison logic; there is no separate test_evaluation.py file. The full suite is invoked from the repository root with python -m unittest discover -s backend/tests -v.

Frontend files

File	Responsibility
frontend/package.json	Declares React/Vite dependencies and frontend scripts.
frontend/package-lock.json	Locks the resolved npm dependency tree for reproducible installation.
frontend/vite.config.js	Configures the Vite development server and proxies /api requests to the backend.
frontend/index.html	Browser document shell and React mount point.
frontend/src/main.jsx	Application entry point: routing, shared ticker/theme state, API helpers, page components, prediction display, local signal history, dashboard and user interactions.

File	Responsibility
frontend/src/Charts.jsx	Lazy-loadable reusable Recharts panels used for historical and comparative visualizations.
frontend/src/styles.css	Theme tokens, page layout, cards, navigation, chart presentation, responsive behavior, and interaction styling.

Documentation and PDF tooling

File	Responsibility
docs/DeepSignal_Project_Guide.md	Canonical long-form reference for implemented behavior, architecture, APIs, setup, persistence, evaluation, dashboard, and limitations.
tools/build_project_guide_pdf.py	Dependency-free Markdown-to-PDF renderer used to create the styled, searchable guide at docs/DeepSignal_Project_Guide.pdf, including tables and a vector architecture diagram.
tools/generate_project_guide_pdf.py	Compatibility entry point that delegates to the canonical builder, so either PDF command produces the same document.

> Inventory note: This guide intentionally does not enumerate ignored machine-local files such as backend/.env, tuning overrides, downloaded model weights, virtual environments, node_modules, or generated run-history JSON. They can contain secrets, large data, or machine-specific state and are not part of the shared source tree.

12. Run the project

Windows: simplest start from scratch

Install Python and Node.js (which includes npm) first. In two PowerShell terminals opened at the project root, run:

```
cd C:\Users\Athira\Downloads\DeepSignal
.\run_backend.bat
```

In the second terminal:

```
cd C:\Users\Athira\Downloads\DeepSignal
.\run_frontend.bat
```

Keep both terminals open. Open the local URL printed by Vite, usually http://localhost:5173. Stop each server with Ctrl+C.

Regenerate this guide as a PDF

With Python installed, run from the project root:

```
python tools/build_project_guide_pdf.py
```

The script uses only Python's standard library. It writes docs/DeepSignal_Project_Guide.pdf and renders the architecture diagram with the model components highlighted.

run_backend.bat creates backend/.venv if needed, creates backend/.env from the example only if no .env exists, installs/updates backend/requirements.txt, and starts Uvicorn on 127.0.0.1:8000 with auto-reload. It never replaces an existing .env.

run_frontend.bat checks npm, installs packages on first setup (npm ci when a lockfile is present; otherwise npm install), and runs Vite. If dependencies change after node_modules already exists, run npm ci manually inside frontend to synchronize with the lockfile.

Manual Windows setup

From the project root:

```
cd backend
python -m venv .venv
.\.venv\Scripts\Activate.ps1
python -m pip install -r requirements.txt
Copy-Item .env.example .env # only if .env does not already exist
python -m uvicorn main:app --reload --host 127.0.0.1 --port 8000
```

In a second terminal:

```
cd frontend
npm ci
npm run dev
```

macOS / Linux manual setup

```
cd backend
python3 -m venv .venv
source .venv/bin/activate
python -m pip install -r requirements.txt
cp .env.example .env # only if .env does not already exist
python -m uvicorn main:app --reload --host 127.0.0.1 --port 8000
```

In a second terminal:

```
cd frontend
npm ci
npm run dev
```

TensorFlow support depends on operating system and Python version. The app has a neutral LSTM fallback if TensorFlow cannot load, but the Random Forest/FinBERT dependency paths still need their packages and provider access. First FinBERT use may download model weights.

13. Configuration

Create backend/.env from .env.example and keep it private. Current settings:

Setting	Default / purpose
SUPABASE_URL	Hosted project URL; blank means local JSON fallback.
SUPABASE_SECRET_KEY	Backend-only secret key; blank means local fallback.
MARKET_DATA_REFRESH_ENABLED	true; set false to disable the scheduler.
MARKET_DATA_REFRESH_MINUTES	360; job cadence, clamped to a minimum of five minutes.
MARKET_DATA_SYMBOLS	AAPL; comma-separated symbols for scheduled refresh.
MARKET_DATA_CACHE_TTL_SECONDS	900; daily history cache TTL; 0 disables it.
NEWS_API_KEY	Optional NewsAPI key; Yahoo news remains a fallback.
FINBERT_MODEL	Optional Transformers model name; default ProsusAI/finbert.
DEEPSIGNAL_ARTIFACT_DIR	Optional model artifact folder override.
CORS_ORIGINS	Allowed origins for non-Vite deployment; default localhost Vite URL.

Model and backtest values are managed through the Tuning page/API and saved in backend/tuning_config.json. Current defaults and accepted ranges:

Setting	Default	Accepted range
LSTM lookback	30	10-120
LSTM units	48	8-256
LSTM epochs	6	1-100

Setting	Default	Accepted range
Random Forest trees	250	50-1,000
Transaction cost	0.06%	0-2%
Slippage	0.04%	0-2%

When live model training or preprocessing code changes, increment PREDICTION_MODEL_CODE_VERSION in backend/main.py; that makes the new identity avoid reusing artifacts created by older code. Keep the feature and hybrid versions accurate when their corresponding behavior changes.

14. Validation and troubleshooting

Run the backend tests

From the project root in PowerShell:

```
.\.venv\Scripts\python -m pip install -r backend/requirements-dev.txt
python -m unittest discover -s backend/tests -v
```

The focused suite covers cache behavior, data/storage handling, model artifacts, hybrid math, backtesting, scheduler behavior, API routes, and input validation. Tests use mocks where needed so normal test runs do not need live market/news calls. Run the suite after code changes when you want verification.

Useful checks

- Backend health: http://localhost:8000/api/health
- Interactive API docs: http://localhost:8000/docs
- Storage mode/connection: http://localhost:8000/api/storage/status
- Scheduler status: http://localhost:8000/api/jobs/market-data
- Cache status: http://localhost:8000/api/cache/status
- Saved model versions: http://localhost:8000/api/models
- Saved AAPL predictions: http://localhost:8000/api/history/predictions?symbol=AAPL
- Saved experiment reports: http://localhost:8000/api/history/experiments

Common problems

Symptom	Likely cause / next check
Frontend loads but API calls fail	Ensure the backend window is running on port 8000; restart the backend if its console shows an import or dependency error.
No market data found	Check ticker spelling/market suffix, Yahoo availability, network access, and provider throttling.
Supabase says incomplete or invalid_url	Check both settings in backend/.env, then restart. Ensure SQL migrations ran in the same Supabase project.
PGRST205 table/schema cache error	Apply the referenced SQL migration to the correct project, then reload the Supabase schema cache/restart the backend.
Job status is running but last run failed	running means the scheduler thread is active; inspect last_run.status, failures, storage error, and backend logs.
Empty backend prediction/experiment history	Create a prediction/evaluation/backtest through the API after connecting storage. Browser-only signals do not populate these API endpoints.
Model artifact load returns method not allowed	The route requires POST. A browser address bar sends GET; use PowerShell Invoke-RestMethod -Method Post or the API docs. Substitute a real version ID, not the literal placeholder.
LSTM probability is neutral	TensorFlow could not import or there were too few sequences. Check artifact model status and Python/TensorFlow compatibility.
Company name does not appear	Wait briefly after entering the symbol; verify backend connectivity and Yahoo metadata for that symbol. The ticker may still be usable even if no display name is found.

Symptom	Likely cause / next check
First analysis is slow	Initial fitting and/or model loading, FinBERT download/load, and provider calls can take time. Later requests can reuse matching model artifacts and in-process caches.

15. Security, privacy, and boundaries

- Keep backend/.env and Supabase secrets out of Git, screenshots, browser developer settings, and frontend bundles. .gitignore excludes the local backend .env.
- The backend uses the Supabase secret only in server-side REST headers. SQL enables RLS and restricts table permissions to the service role.
- This project has no user login, tenant boundary, brokerage connection, order execution, or public production hardening. Do not expose the backend or service secret as a public multi-user service without adding authentication, authorization, rate limiting, secret management, and operational controls.
- Browser localStorage holds theme, selected ticker, and locally saved signal copies. It is browser/device-specific and can be cleared by the user.
- Provider requests send ticker queries to Yahoo Finance and, when configured, NewsAPI. Avoid treating personal information as input.
- Supabase is optional; without it, local JSON reports, model artifacts, cache, and browser history have different backup and persistence scopes.

16. Current limitations and future work

These are material distinctions to state in demonstrations and reports:

1. Daily, provider-dependent prices: This is not an exchange-grade real-time feed. Yahoo may delay or revise data. The “Live” badge refers to periodic interface/status refresh, not live tick data.
2. Forecast horizon: LSTM/RF/hybrid direction target is one session. Longer horizon choices scale a heuristic change estimate; they do not create independently trained 1-week or 1-month models.
3. Not a trading recommendation: Signal thresholds, technical points, sentiment mapping, and confidence display are heuristic and not calibrated to realized profit probability.
4. Historical news alignment: Live headline sentiment is not reconstructed point-in-time for historical dates. The dedicated historical hybrid evaluation uses neutral news sentiment.
5. Single-window evaluation: The report has chronological train/validation/test windows and baselines but is not a comprehensive repeated walk-forward retraining study across many market regimes and tickers.
6. Live LSTM validation: The live scaler is fit on the feature window before its internal validation split. Dedicated evaluation fits the scaler on training rows only; prefer that report when discussing out-of-sample model assessment.
7. Backtest separation: The backtest tests the deterministic technical strategy, not the exact live model hybrid. Costs, fractional shares, fills, and long-only position sizing are simplified assumptions.
8. Persistence boundaries: Artifact binaries remain local. Database rows record model-version identifiers but do not automatically move artifact files to Supabase. Browser signals are not automatically imported to backend history.
9. Prototype operations: Scheduler/cache are in-process and local to one backend instance. There is no distributed worker, job queue, authentication, or deployment-grade monitoring.
10. Optional dependencies/providers: XGBoost/SHAP failures are tolerated, FinBERT can be unavailable, and news or company metadata can be missing without stopping all core features.

Reasonable next steps for a more rigorous research system include repeated rolling/expanding-window tests across multiple tickers, point-in-time news archives, calibrated probability evaluation, ablation studies for hybrid components, stronger price-adjusted execution assumptions, and deployment security. Add these only with a clearly defined research objective; more complexity alone does not establish model quality.

17. Glossary

Term	Simple meaning
OHLCV	Open, High, Low, Close, and Volume market bar fields.
Ticker / symbol	Short identifier for a listed security, such as AAPL.

Term	Simple meaning
Feature	A numeric input calculated from market data for a model.
Target / label	The outcome the model is trained to estimate; here, next-session up or down.
LSTM	A neural network architecture designed to process ordered sequences.
Random Forest	An ensemble of decision trees for classification.
FinBERT	A finance-oriented pretrained language model used here to score headlines.
Hybrid	A versioned rule that combines compatible component outputs.
Holdout	Later historical rows kept out of a model's fitting for evaluation.
Data fingerprint	A hash used to identify the exact input price window.
Artifact	Saved fitted model/preprocessor files plus the metadata needed to identify them.
Backtest	Historical simulation with defined signal timing, execution, and costs.
Slippage	Difference between a reference price and a less favorable assumed fill.
TTL cache	Temporary stored response that expires after a configured time.
Walk-forward	Testing in time order so decisions do not use future rows.