

The 300 SERIES Power Transfer Switch combines ASCO's industry-leading load transfer technology with new multi-voltage capability that speed projects by making these configured-to-order units easy to distribute procure, distribute, and install. Listed to UL 1008, these models help avoid delays that increase the time and cost required to build and commission backup power systems.

Product Features

- Field-selectable to 208, 220, 230, 240, 380, 400, 415, 440, 460, or 480 volts
- Sizes available from 30 to 600 amps, 480 VAC, 50 or 60 Hz, single or 3-phase
- Listed to UL 1008
- Silver-plated copper ground and neutral bus with solderless screw-type terminals
- Refer to ASCO Power Technologies [Publication 1128](#) for up-to-date ratings information
- Available with solid or switched neutral

Order Information

To order an ASCO 300 SERIES Multi-Voltage Transfer Switch, complete the following catalog number:

J	+	03AUS	+	B	+	3	+	0600	+	N	+	GX	+	C
Frame		Product Type		Neutral Code		Phase Poles		Amperes Continuous Rating		Voltage Code		Controller Code		Enclosure
D = 30 - 230 Amp		03AUS = Automatic		A = Solid Neutral		2		0030 ¹		Y = 208 - 480		G = No Optional Accessories		O = Open Type (zero)
J = 150 - 600 Amp		03NUS = Non-Automatic		B = Switched Neutral		3		0070 ¹				GX = Optional Accessories		C = Type 1 Enclosure
		3ADUS = Automatic Delayed Transition						0104 ¹						F = Type 3R' Enclosure
		3NDUS = Non-Automatic, Delayed Transition						0150 ^{1,3}						G = Type 4' Enclosure
								0200 ^{1,2,3}						L = Type 12 Enclosure
								0230 ^{1,2,3}						M = Type 3R' Secure Double-Door Enclosure
								0260 ^{1,3}						N = Type 4' Secure Double-Door Enclosure
								0400 ^{1,3}						Q = Type 12 Secure Double-Door Enclosure
								0600 ¹						S = Type 3RXa Secure Double-Door Enclosure (316 Stainless Steel)
														U = Type 4X' Enclosure (316 Stainless Steel)
														V = Type 4X' Secure Double-Door Enclosure (316 Stainless Steel)

- Notes:**
1. Switch sizes 30-600 amperes supplied in non-secure enclosures as standard.
 2. 200 and 230 amperes rated switches for use with copper cable only.
 3. Switch sizes 800-3000 amperes, and 150-400 amperes 3ADTS/3NDTS provided in secure type outdoor enclosures when required.
 4. Use Type 3R secure for 1200, 2000, 2600, and 3000.
 5. Available on switches rated 1200, 2000, 2600, and 3000 amperes.
 6. When temperatures below 32°F can be experienced, special precautions should be taken, such as the inclusion of strip heaters, to prevent condensation and freezing of this condensation. This is particularly important when environmental enclosures (Type 3R, 4) are ordered for outdoor applications.
 7. Type 3R enclosures are not suitable for installations subject to wind blown rain or snow. Use Type 4 enclosures where available or install supplemental shelter protection around the 3R enclosure.
 8. Multi-voltage available only on switches rated 30-600 amperes.

Specifications

ASCO 300 SERIES Multi-voltage Power Transfer Switch Dimensions and Shipping Weights

UL Type 1 Enclosure

Switch Rating Amps	Phase Poles	Neutral Code¹	Dimensions, in.²			Approx. Shipping Weight, lb.
			Width	Height	Depth	
30³, 70³, 104³, 150³, 200³	2	A	18	31	13	69
	2	B	18	31	13	72
	3	A	18	31	13	72
	3	B	18	31	13	75
230	2	A	18	48	13	117
	2	B	18	48	13	125
	3	A	18	48	13	125
	3	B	18	48	13	133
260, 400	2	A	24	56	14	250
	2	B	24	56	14	260
	3	A	24	56	14	260
	3	B	24	56	14	270
150, 200, 230 SERIES 3ADTS/3NTS only	2	A	24	56	14	250
	2	B	24	56	14	260
	3	A	24	56	14	260
	3	B	24	56	14	270
600	2	A	24	63	17	300
	2	B	24	63	17	320
	3	A	24	63	17	320
	3	B	24	63	17	320

- Notes:** 1. Neutral Codes: A=Solid, B=Switched
2. Dimensional data is approximate and subject to change. Certified dimensions available upon request.
3. Dimensions for 30-200 ampere models when furnished with accessory 135L power meter are 18"W x 41"H x 13"D.

* Unit is designed for top cable entry of emergency and load, and bottom entry of normal.
A cable pull box is also available for all top or bottom cable access when required (optional accessory kit #K609027).
Not required for type 3R, 4X, and 12 enclosures where available.

A space heater accessory 44G is required with all service entrance (Type 3R) switches to help reduce condensation and protect the circuit breaker.
Accessory 44G is recommended when environmental enclosures (Type 4 or Type 12) will be installed outdoors.

UL Type 3R Enclosure

Switch Rating Amps	Phase Poles	Neutral Code¹	Dimensions, in.²			Approx. Shipping Weight, lb.
			Width	Height	Depth	
30³, 70³, 104³, 150³, 200³	2	A	18	35	14	86
	2	B	18	35	14	88
	3	A	18	35	14	88
	3	B	18	35	14	90
230	2	A	18	35	14	86
	2	B	18	35	14	88
	3	A	18	35	14	88
	3	B	18	35	14	90
260, 400	2	A	24	64	18	206
	2	B	24	64	18	206
	3	A	24	64	18	212
	3	B	24	64	18	218
150, 200, 230 SERIES 3ADTS/3NTS only	2	A	24	64	18	222
	2	B	24	64	18	222
	3	A	24	64	18	228
	3	B	24	64	18	224
600 (Non-Secure Enclosure)	2	A	24	64	18	247
	2	B	24	64	18	247
	3	A	24	64	18	234
	3	B	24	64	18	241

300 SERIES Multi-voltage Power External Power Connections Sizes UL-Listed Solderless Screw-Type Terminals

Switch Rating	Ranges of AL-CU Wire Sizes
70, 100, 150, 200², 225²	One #14 to 4/0 AWG
150³, 200³, 225³, 250, 400	One #4 AWG to 600 MCM Two 1/0 to 250 MCM
600	Two 1/0 to 600 MCM

- Notes:** 1. All 300 SERIES switches default to a solid neutral assembly unless a switched neutral is specified. If no neutral is required, order as solid neutral and left unwired.
2. 200 and 225 ampere rated switches for use with copper cable only.
Refer to paragraph 310.15 of the NEC for all additional information.
3. J 150-225 ampere for SERIES 3ADUS/3NDUS only.
4. Use wire rated 75 degrees minimum for all power connections.
5. Refer to the outline drawing for maximum power cable connections for circuit breaker.

Extended Warranties for 300 SERIES Multi-voltage Power Transfer Switches (3AUS/3NUS/3ADUS/3NDUS)

Description
1 Year Extension (Total of 3 Years)
2 Year Extension (Total of 4 Years)
3 Year Extension (Total of 5 Years)

- Notes:** 1. Standard warranty is (24) months, 2 years from date of shipment, extended warranty is in addition to the two years, for a total of 3, 4 or 5 years, except where the warranty period for the circuit breaker shall be limited to 24 months from date of shipment from ASCO.
2. Refer to Publication 3223 for warranty terms and conditions.