

DB4B loudspeaker range up to 25 watts

Hazardous & ordinary locations



Overview

The DB4B is a high power explosion proof loudspeaker, introduced as a replacement for the current DB4 with improved intelligibility and acoustic performance. Certified for use in a wide range of temperatures from -67°F to +185°F the Ex enclosure is manufactured from GRP with a rugged thermoplastic flare providing a corrosion free and aesthetically pleasing product.

Features

- UL certified for USA and Canada
Class I, Div 2, Groups A-D
Class I, Zone 1
Class II, Div 2, Groups F & G
Zone 21
Class III, Div. 1
- Certified temperature -55°C to +85°C (-67°F to + 185°F)*
- NEMA 4X & 6/IP66 & IP67
- SIL 2 certified
- 114dB at 25W, 10 feet*
- 8W, 15W & 25W versions
- Power tapings, via integral transformer
- Frequency response 350Hz - 8kHz
- Ex enclosure - Glass reinforced polyester
- Flare - High impact thermoplastic polyester
- Stainless steel mounting bracket and cover screws
- Mounting bracket has ratchet facility as standard
- Optional swivel bracket available
- Optional resettable fuse†

* Depending on version

† Contact MEDC for details

The frequency response of the unit ensures that critical voice messages and general alarm tones are highly intelligible. The specific SPL figure for sensitivity, 1W @ 10 feet is 100dB whilst at 10 feet the 25W unit produces 114dB, the 15W unit 112dB and the 8W unit 110dB.

Options include DC blocking capacitors for monitored systems, resettable fuses for compliance with marine regulations and a swivel bracket that gives the installer greater flexibility when positioning the unit. The short flare option is a worthy addition to the range offering a high SPL and wide dispersion angle in a compact unit.



