

JB10 & JB11 junction boxes range

Hazardous locations, ordinary locations



Overview

These GRP terminal boxes have been designed for use in hazardous locations and hostile environments.

The robust design, coupled with corrosion-free glass reinforced polyester and high ingress protection, ensure a long life, low maintenance product.

European and other world wide approvals are available, refer to main section of catalogue.

Features

- UL certified for USA and Canada:
 - Class I, Div 2, Groups A, B, C, D
 - Class I, Zone 1, AEx e IIC, Ex e IIC
- ATEX approved
- IECEx approved
- NEMA 4x & 6, IP66 & IP67
- Certified temperature:
 - 4°F to +131°F
 - 20°C to +55°C
- Glass reinforced polyester
- Lightweight
- Robust
- Corrosion free
- Retained stainless steel cover screws
- Optional gland continuity plate
- Mixed rail mounted terminals



UL	Cert No. E237592 Class I, Div. 2, Groups A, B, C & D Class I, Zone 1, AEx e IIC, Ex e IIC
----	---

Material	Glass reinforced polyester, stainless steel cover screws
Finish	Self coloured black
Certified temp	Standard -4°F to +131°F (-20°C to + 55°C)
Weight	JB10, 2.4 lbs (1.1 Kg.) average JB11, 4.0 lbs (1.8 Kg.) average
Gland continuity	Via an internal BZP (bright zinc plated) steel plate
Ingress protection	NEMA 4x & 6, IP66 & IP67

*275V if fitted with QB2 or QB4 cross connection links

All junction boxes will be supplied with an internal earth terminal appropriate to the terminals fitted. If more than one internal earth terminal is required the maximum number of feed-through terminals must be reduced.

Gland entries	Maximum no. of gland entries sides 1 & 3	Maximum no. of gland entries sides 2 & 4		Maximum no. gland entries (base)
	With or without earth continuity	With earth continuity	Without earth continuity	With or without earth continuity
1/2" NPT	2	1	2	2
3/4" NPT	1	1	1	N/A

Gland entries	Maximum no. of gland entries per side with or without earth continuity	Maximum no. of gland entries (base) with or without earth continuity
1/2" NPT	2	4
3/4" NPT	2	N/A

The following code is designed to help in selection of the correct unit. Build up the reference number by inserting the code for each component into the appropriate box

Terminal box	Certification	Terminals	Earth continuity	Gland continuity	Side cable entries	Tag/label	Option	Finish
JB10 JB11	UL	Type None ES0001(6mm² cable max) ES0003(16mm² cable max) Code N R* S*	Type None ES0001(6mm² cable max) ES0003(16mm² cable max) Code N R* S*	Continuity None Yes Code N E*	Size None 1/2"NPT 3/4"NPT Code N M*† O*†	Label None Yes Code N T*	Option None Extra internal earth Base entry Code N W* Y*	Finish Natural black Code N
		Certification MK6/6 BK6 UK2.5N UK5N UK10N UK16N BK4 Code J* K* L* M* N* O* R*	Certification MK6/6 BK6 UK2.5N UK5N UK10N UK16N BK4 Code J* K* L* M* N* O* R*	Continuity None Yes Code N E*	Size None 1/2"NPT 3/4"NPT Code N M*† O*†	Label None Yes Code N T*	Option None Extra internal earth Base entry Code N W* Y*	Finish Natural black Code N

* Suffix with side, e.g: R1 ES0001 x side 1

* Suffix with number of terminals, e.g: L6 = 6 x UK 2.5N
Terminal types can be mixed, eg L4M2

* Gland continuity 'E' must be selected when Ext earth 'R' or 'S' is required

* Prefix with cable entry position (see diagram above) e.g 2M
† UL version supplied with adaptor

* Please discuss your requirements with MEDC application engineers prior to ordering

*Please specify

Technical drawing of the 150.68mm x 150.68mm enclosure, showing front, side, and top views with dimensions and labels.

Front View Dimensions:

- Overall width: 150.68mm
- Overall height: 150.68mm
- Top edge dimensions (from left): 53/64" (21mm), 5-9/32" (134mm), 53/64" (21mm)
- Bottom edge dimensions (from left): 53/64" (21mm), 5-9/32" (134mm), 53/64" (21mm)
- Left edge dimensions (from top): 53/64" (21mm), 12mm, 11mm, 10mm
- Right edge dimensions (from top): 5-9/32" (134mm), 150.68mm
- Internal dimensions (from left): 53/64" (21mm), 12mm, 11mm, 10mm
- Internal dimensions (from right): 5-9/32" (134mm), 150.68mm
- Internal dimensions (from bottom): 53/64" (21mm), 12mm, 11mm, 10mm

Side View Dimensions:

- Overall height: 150.68mm
- Top edge dimensions (from left): 3-49/64" (95.5mm), 1-49/64" (145mm), 3/8" (9.5mm)

Top View Dimensions:

- Overall width: 150.68mm
- Overall height: 150.68mm
- Top edge dimensions (from left): 1-31/32" (50mm), 1/2" (12.5mm)
- Bottom edge dimensions (from left): 1-31/32" (50mm), 1/2" (12.5mm)
- Left edge dimensions (from top): 1-31/32" (50mm), 1/2" (12.5mm)
- Right edge dimensions (from top): 1-31/32" (50mm), 1/2" (12.5mm)

Labels and Features:

- CERTIFICATION LABEL:** Located in the center of the front panel.
- OPTIONAL TAG LABEL:** Located below the certification label.
- FIXING HOLE Ø9/32" (Ø7mm) 4 POS:** Four holes for mounting the enclosure.
- GLAND G:** Located on the right side of the enclosure.
- M5 CAPTIVE SCREW (4 POS):** Four screws for mounting the enclosure.