

খুব ভালো প্রশ্ন 👍

DRF **class-based ViewSet** ব্যবহার করলে `queryset` **attribute** আর `get_queryset()` **method**—এই দুইটার ব্যবহার বুঝলে অনেক clean ও optimized API লেখা যায়।

নিচে পরিষ্কারভাবে ব্যাখ্যা করছি 📌

---

## ♦ `queryset (attribute)` — কখন ব্যবহার করবে

ব্যবহার করবে যখন:

- `queryset` **static** (সব request-এ একই)
- request / user / params এর উপর depend করে না
- শুধু basic CRUD দরকার

**Example:**

```
class ProductViewSet(ModelViewSet):  
    queryset = Product.objects.filter(is_active=True)  
    serializer_class = ProductSerializer
```

✅ ভালো যখন:

- list / retrieve same data
- simple API
- দ্রুত লেখা

❌ ব্যবহার কোনো না যখন:

- user-specific data
  - query param অনুযায়ী filter
  - permission অনুযায়ী data বদলায়
- 

## ♦ `get_queryset()` (method) — কখন ব্যবহার করবে

ব্যবহার করবে যখন:

- `queryset` **dynamic**
- `request.user` দরকার
- URL param / query param লাগবে

- role / permission অনুযায়ী data দেখাতে হবে

## Example:

```
class OrderViewSet(ModelViewSet):
    serializer_class = OrderSerializer

    def get_queryset(self):
        user = self.request.user
        if user.is_staff:
            return Order.objects.all()
        return Order.objects.filter(user=user)
```

### ✓ Best practice:

- production API তে বেশি ব্যবহার হয়
- security & flexibility বেশি

## 🔄 দুটো একসাথে ব্যবহার করা যাবে?

হ্যাঁ, এবং এটাই সবচেয়ে clean approach 👉

```
class OrderViewSet(ModelViewSet):
    serializer_class = OrderSerializer
    queryset = Order.objects.select_related('user')

    def get_queryset(self):
        qs = super().get_queryset()
        if not self.request.user.is_staff:
            qs = qs.filter(user=self.request.user)
        return qs
```

👉 এতে:

- base optimization attribute এ
- dynamic filter method এ

## 🔥 Real-world guideline

Situation	Use
Simple CRUD	queryset

Situation	Use
Auth-based filtering	<code>get_queryset()</code>
Query param filter	<code>get_queryset()</code>
Performance optimization	<code>queryset</code>
Role-based access	<code>get_queryset()</code>

---

## ! Common mistake

```
queryset = Model.objects.filter(user=self.request.user)
```

✗ এটা কাজ করবে না — class load হওয়ার সময় request থাকে না

---

## 🎯 Bottom line

- Static → `queryset`
- Dynamic → `get_queryset()`
- Optimization আগে, condition পরে

চাও তো তুমি তোমার ViewSet code দিলে আমি বলে দেব  
কোথায় attribute ভালো, কোথায় method লাগবে 🤖

---

সংক্ষেপে উত্তর 👉 হ্যাঁ,

condition অনুযায়ী query বদলাতে হলে `get_queryset()` method ব্যবহার করাই সঠিক ✅

এখন পরিষ্কার করে বুঝাই 📌

---

## ? কেন `queryset` attribute দিয়ে condition দেওয়া যায় না?

কারণ `queryset` class load হওয়ার সময় evaluate হয়, তখন:

- `request`
  - `request.user`
  - query params
- 👉 কিছুই থাকে না

তাই condition কাজ করবে না ✗

---

## ✓ সঠিক উপায়: `get_queryset()`

### Example 1: user অনুযায়ী data

```
class OrderViewSet(ModelViewSet):
    serializer_class = OrderSerializer

    def get_queryset(self):
        user = self.request.user
        if user.is_staff:
            return Order.objects.all()
        return Order.objects.filter(user=user)
```

---

### Example 2: query params অনুযায়ী condition

```
def get_queryset(self):
    qs = Order.objects.all()
    status = self.request.query_params.get('status')

    if status:
        qs = qs.filter(status=status)

    return qs
```

---

### Example 3: queryset + get\_queryset (BEST PRACTICE)

```
class OrderViewSet(ModelViewSet):
    serializer_class = OrderSerializer
    queryset = Order.objects.select_related('user')

    def get_queryset(self):
        qs = super().get_queryset()

        if not self.request.user.is_staff:
            qs = qs.filter(user=self.request.user)

        return qs
```

👉 এতে:

- base optimization ( `select_related` ) attribute এ

- condition logic method এ

## ❌ ভুল উদাহরণ

```
queryset = Order.objects.filter(user=self.request.user)
```

❌ কাজ করবে না

## 📌 Summary

- ✓ condition থাকলে → `get_queryset()`
- ✓ static হলে → `queryset`
- ✓ দুটো একসাথে ব্যবহার করা যায় (recommended)

চাও তো তুমি তোমার actual condition / code পাঠাও,  
আমি সেটাকে clean & optimized করে সাজিয়ে দেব 👍

এটা DRF/Django ORM-এর সবচেয়ে গুরুত্বপূর্ণ performance প্রশ্নগুলোর একটা 👍  
আমি simple rule → example → mistake → real-life guideline এইভাবে বুঝাচ্ছি।

## 🔑 মূল পার্থক্য (১ লাইনে)

- `select_related` → ForeignKey / OneToOne → SQL JOIN
- `prefetch_related` → ManyToMany / reverse FK → আলাদা query + Python join

## 1 `select_related` কখন ব্যবহার করবে

✓ ব্যবহার করবে যখন:

- relationship ForeignKey বা OneToOne
- child object থেকে parent এর field দরকার
- একসাথে JOIN করলেও data বেশি বড় না

**Example (Bus Ticket):**

```
Booking.objects.select_related(
    'user',      # FK
    'trip',      # FK
    'seat'       # FK
)
```

👉 এখানে:

- Booking → User
  - Booking → Trip
  - Booking → Seat
- সবই **ForeignKey**

● ১টা query তেই সব data

---

## ❌ ভুল ব্যবহার

```
Booking.objects.select_related('payments')
```

❌ payments যদি ManyToMany / reverse FK হয় → কাজ করবে না

---

## 2 prefetch\_related কখন ব্যবহার করবে

✓ ব্যবহার করবে যখন:

- ManyToMany
- reverse ForeignKey (parent → children)
- child object এর list দরকার

### Example (Trip → Seats):

```
Trip.objects.prefetch_related('seat_set')
```

👉 Queries:

- 1 query → Trip
  - 1 query → Seat
- Python এ matching হয়
-

## Another example:

```
Bus.objects.prefetch_related('trips')
```

✓ One Bus → Many Trips

---

### 3 একসাথে ব্যবহার (Most Common & Best)

```
Trip.objects.select_related(  
    'bus', 'route'  
) .prefetch_related(  
    'seat_set'  
)
```

✓ Parent data JOIN

✓ Child list prefetch

---

### 4 কখন কোনটা? (Cheat Table)

Situation	Use
FK / OneToOne	<code>select_related</code>
ManyToMany	<code>prefetch_related</code>
Reverse FK	<code>prefetch_related</code>
Single object detail API	<code>select_related</code>
List + child list	<code>prefetch_related</code>
Large child list	<code>prefetch_related</code>

---

### 5 DRF ViewSet-এ Best Practice

```
class BookingViewSet(ModelViewSet):  
    serializer_class = BookingSerializer  
    queryset = Booking.objects.select_related(  
        'trip', 'seat'  
    ).prefetch_related(  
        'payments'  
    )
```

- 👉 Base optimization attribute এ
- 👉 Condition → `get_queryset()`

---

## 6 Common Performance Mistake 🚨

```
for booking in bookings:
    print(booking.trip.bus.name)
```

- ❌ যদি `select_related('trip__bus')` না থাকে
- 👉 N+1 query

---

## 7 Debug করার উপায়

```
django-debug-toolbar
```

বা

```
print(len(connection.queries))
```

---

## 🎯 Golden Rules (মুখস্থ করে ফেলো)

- ✓ FK → `select_related`
- ✓ List of children → `prefetch_related`
- ✓ Doubt হলে → relation type দেখো
- ✓ Loop এর ভিতরে query দেখলে 🚨

---

চাও তো তুমি তোমার **model relationship** পাঠাও,  
আমি exact বলে দেব—কোথায় কোনটা বসবে 🔥

---

```
from django.db import models
```

```
# =====
```



```

# Patient

# =====

class Patient(models.Model):

    CHOOSE_GENDER = [

        ('male', 'Male'),

        ('female', 'Female')

    ]

    CHOOSES_BLOOD_GROUP = [

        ('A+', 'A+'), ('B+', 'B+'), ('O+', 'O+'), ('AB+', "AB+"),

        ('A-', 'A-'), ('B-', 'B-'), ('O-', 'O-'), ('AB-', "AB-")

    ]

    first_name = models.CharField(max_length=50)

    last_name = models.CharField(max_length=50)

    email = models.EmailField(unique=True)

    phone = models.CharField(max_length=20)

    gender = models.CharField(max_length=6, choices=CHOOSE_GENDER)

    dob = models.DateField()

    blood_group = models.CharField(max_length=5, choices=CHOOSES_BLOOD_GROUP)

    address = models.TextField()

    emergency_contact = models.CharField(max_length=20)

    created_at = models.DateTimeField(auto_now_add=True)

class Meta:

```

```
ordering = ['first_name', 'last_name']
```

```
def __str__(self):
```

```
    return f"{self.first_name} {self.last_name}"
```

```
# =====
```

```
# Department
```

```
# =====
```

```
class Department(models.Model):
```

```
    name = models.CharField(max_length=200)
```

```
    description = models.TextField()
```

```
class Meta:
```

```
    ordering = ['name']
```

```
def __str__(self):
```

```
    return self.name
```

```
# =====
```

```
# Doctor
```

```
# =====
```

```
class Doctor(models.Model):
```

```
    name = models.CharField(max_length=100)
```

```
    department = models.ForeignKey(Department, on_delete=models.CASCADE,
```



```

date = models.DateField()

time = models.TimeField()

status = models.CharField(max_length=10, choices=STATUS_CHOICES,
default='pending')

notes = models.TextField(blank=True, null=True)


class Meta:

ordering = ['-date', '-time']


def __str__(self):

return f"Appointment: {self.patient.first_name} with {self.doctor.name}"


# =====

# Schedule

# =====

class Schedule(models.Model):

WEEKDAYS = [

('mon', 'MONDAY'),

('tue', 'TUESDAY'),

('wed', 'WEDNESDAY'),

('thu', 'THURSDAY'),

('fri', 'FRIDAY'),

('sat', 'SATURDAY'),

('sun', 'SUNDAY'),

]

```

```
doctor = models.ForeignKey(Doctor, on_delete=models.CASCADE,  
related_name='schedules')
```

```
weekday = models.CharField(max_length=3, choices=WEEKDAYS)
```

```
start_time = models.TimeField()
```

```
end_time = models.TimeField()
```

```
def __str__(self):
```

```
    return f"{self.doctor.name} - {self.weekday}"
```

```
# =====
```

```
# Ward
```

```
# =====
```

```
class Ward(models.Model):
```

```
    WARD_CHOOSE = [
```

```
        ('general', 'GENERAL'),
```

```
        ('icu', 'ICU'),
```

```
        ('cabin', 'CABIN')
```

```
    ]
```

```
    name = models.CharField(max_length=100)
```

```
    type = models.CharField(max_length=10, choices=WARD_CHOOSE)
```

```
    def __str__(self):
```

```
        return self.name
```

# \_\_\_\_\_

# Room

```
# =====
```

```
class Room(models.Model):
```

```
ward = models.ForeignKey(Ward, on_delete=models.CASCADE,  
related_name='rooms')
```

```
room_no = models.CharField(max_length=10)
```

```
bed_count = models.PositiveIntegerField()
```

```
is_available = models.BooleanField(default=True)
```

```
def __str__(self):
```

```
return f"Room {self.room_no} ({self.ward.name})"
```

# \_\_\_\_\_

## # Admission

# =====

```
class Admission(models.Model):
```

```
STATUS_CHOOSE = [
```

```
('admitted', 'ADMITTED'),
```

```
('discharged', 'DISCHARGED'),
```

1

```
patient = models.ForeignKey(Patient, on_delete=models.CASCADE,  
related_name='admissions')
```

```

room = models.ForeignKey(Room, on_delete=models.CASCADE,
related_name='admissions')

admitted_at = models.DateTimeField(auto_now_add=True)

discharged_at = models.DateTimeField(null=True, blank=True)

status = models.CharField(max_length=10, choices=STATUS_CHOICES,
default='admitted')


def __str__(self):

    return f"Admission: {self.patient.first_name}"


# =====

# Treatment

# =====

class Treatment(models.Model):

    admission = models.ForeignKey(Admission, on_delete=models.CASCADE,
related_name='treatments')

    doctor = models.ForeignKey(Doctor, on_delete=models.CASCADE,
related_name='treatments')

    description = models.TextField()

    treatment_date = models.DateField()


def __str__(self):

    return f"Treatment for {self.admission.patient.first_name}"


# =====

# Medication

```

```
# =====
```

```
class Medication(models.Model):
```

```
    treatment = models.ForeignKey(Treatment, on_delete=models.CASCADE,  
    related_name='medications')
```

```
    medicine_name = models.CharField(max_length=100)
```

```
    dosage = models.CharField(max_length=100)
```

```
    frequency = models.CharField(max_length=100)
```

```
    def __str__(self):
```

```
        return self.medicine_name
```

```
# =====
```

```
# Nurse
```

```
# =====
```

```
class Nurse(models.Model):
```

```
    name = models.CharField(max_length=100)
```

```
    phone = models.CharField(max_length=20)
```

```
    department = models.ForeignKey(Department, on_delete=models.CASCADE,  
    related_name='nurses')
```

```
    assign_room = models.ForeignKey(Room, on_delete=models.SET_NULL,  
    null=True, blank=True, related_name='nurses')
```

```
    def __str__(self):
```

```
        return self.name
```



```
# =====

# Lab Test

# =====

class LabTest(models.Model):

    test_name = models.CharField(max_length=200)

    description = models.TextField()

    price = models.PositiveIntegerField()


    def __str__(self):

        return self.test_name


# =====

# Lab Report

# =====

class LabReport(models.Model):

    patient = models.ForeignKey(Patient, on_delete=models.CASCADE,
                                related_name='lab_reports')

    doctor = models.ForeignKey(Doctor, on_delete=models.CASCADE,
                                related_name='lab_reports')

    test = models.ForeignKey(LabTest, on_delete=models.CASCADE,
                              related_name='lab_reports')

    report_file = models.FileField(upload_to='reports/')

    created_at = models.DateTimeField(auto_now_add=True)


    def __str__(self):

        return f"Lab Report for {self.patient.first_name}"
```

```

# =====

# Prescription

# =====

class Prescription(models.Model):

    appointment = models.ForeignKey(Appointment, on_delete=models.CASCADE,
    related_name='prescriptions')

    doctor = models.ForeignKey(Doctor, on_delete=models.CASCADE,
    related_name='prescriptions')

    patient = models.ForeignKey(Patient, on_delete=models.CASCADE,
    related_name='prescriptions')

    notes = models.TextField()

    created_at = models.DateTimeField(auto_now_add=True)

    def __str__(self):

    return f"Prescription for {self.patient.first_name}"


# =====

# Invoice

# =====

class Invoice(models.Model):

    STATUS_CHOOSE = [

    ('paid', 'PAID'),

    ('unpaid', 'UNPAID'),

    ]

```

```

patient = models.ForeignKey(Patient, on_delete=models.CASCADE,
                             related_name='invoices')

admission = models.ForeignKey(Admission, on_delete=models.SET_NULL,
                               null=True, blank=True, related_name='invoices')

total_amount = models.FloatField()

status = models.CharField(max_length=10, choices=STATUS_CHOICES,
                           default='unpaid')

created_at = models.DateTimeField(auto_now_add=True)


def __str__(self):

    return f"Invoice - {self.patient.first_name}"


# =====

# Payment

# =====

class Payment(models.Model):

    METHOD_CHOICES = [

        ('cash', 'CASH'),

        ('card', 'CARD'),

        ('online', 'ONLINE'),

    ]

    invoice = models.ForeignKey(Invoice, on_delete=models.CASCADE,
                                related_name='payments')

    amount = models.FloatField()

    method = models.CharField(max_length=10, choices=METHOD_CHOICES)

```

```
paid_at = models.DateTimeField(auto_now_add=True)
```

```
def __str__(self):
```

```
    return f"Payment for {self.invoice.id}"
```

চমৎকার 👍

তুমি যেহেতু সব **models** দিয়ে দিয়েছ, এখন আমি একদম এই **Hospital Management System** অনুযায়ী বলছি—

👉 কোন **model relation** এ **select\_related**

👉 কোন **relation** এ **prefetch\_related**

👉 Real DRF queryset example

---

## 🔑 Golden Rule (আবার মনে করাই)

- **ForeignKey / OneToOne** → **select\_related**
- **reverse ForeignKey / Many list** → **prefetch\_related**

---

## 🔗 তোমার Model Relationship Analysis

### 1 Appointment

```
Appointment
├── patient (FK)
├── doctor (FK)
```

### ✅ Use **select\_related**

```
Appointment.objects.select_related(
    'patient',
    'doctor',
    'doctor__department'
)
```

📌 কেন?

- Appointment → Patient (FK)
- Appointment → Doctor (FK)

- Doctor → Department (FK)

🟢 ১টা JOIN query তেই সব data

---

## 2 Doctor

Doctor

- └ department (FK)
- └ schedules (reverse FK)
- └ appointments (reverse FK)
- └ treatments (reverse FK)

### ✓ Correct way

```
Doctor.objects.select_related(  
    'department'  
)  
.prefetch_related(  
    'schedules',  
    'appointments'  
)
```

📌 কারণ:

- department → FK → `select_related`
  - schedules / appointments → list → `prefetch_related`
- 

## 3 Patient

Patient

- └ appointments
- └ admissions
- └ lab\_reports
- └ prescriptions
- └ invoices

### ✓ Use `prefetch_related`

```
Patient.objects.prefetch_related(  
    'appointments',  
    'admissions',  
    'lab_reports',
```

```
'prescriptions',  
'invoices'  
)
```

📌 Patient থেকে সবই **reverse FK (one-to-many)**

---

## 4 Admission

Admission

- └─ patient (FK)
- └─ room (FK)
- └─ treatments (reverse FK)
- └─ invoices (reverse FK)

### ✓ Best

```
Admission.objects.select_related(  
    'patient',  
    'room',  
    'room__ward'  
) .prefetch_related(  
    'treatments'  
)
```

## 5 Treatment

Treatment

- └─ admission (FK)
- └─ doctor (FK)
- └─ medications (reverse FK)

### ✓ Correct

```
Treatment.objects.select_related(  
    'admission',  
    'doctor'  
) .prefetch_related(  
    'medications'  
)
```

## 6 Room & Ward

Room

- |— ward (FK)
- |— admissions
- |— nurses

```
Room.objects.select_related(  
    'ward'  
) prefetch_related(  
    'admissions',  
    'nurses'  
)
```

---

## 7 LabReport

LabReport

- |— patient (FK)
- |— doctor (FK)
- |— test (FK)

### ✓ Only `select_related`

```
LabReport.objects.select_related(  
    'patient',  
    'doctor',  
    'test'  
)
```

---

## 8 Invoice

Invoice

- |— patient (FK)
- |— admission (FK)
- |— payments (reverse FK)

### ✓ Correct

```
Invoice.objects.select_related(  
    'patient',
```

```
        'admission'
    ).prefetch_related(
        'payments'
    )
```

---

## 9 Prescription

```
Prescription
├─ appointment (FK)
├─ doctor (FK)
└─ patient (FK)
```

```
Prescription.objects.select_related(
    'appointment',
    'doctor',
    'patient'
)
```

---

## DRF ViewSet Real Example

### AppointmentViewSet

```
class AppointmentViewSet(ModelViewSet):
    serializer_class = AppointmentSerializer
    queryset = Appointment.objects.select_related(
        'patient',
        'doctor',
        'doctor__department'
    )
```

---

### Patient Detail API (Heavy but optimized)

```
class PatientViewSet(ModelViewSet):
    serializer_class = PatientDetailSerializer

    def get_queryset(self):
        return Patient.objects.prefetch_related(
            'appointments__doctor',
            'appointments__doctor__department',
```



```
'admissions__room__ward',  
'lab_reports__test',  
'prescriptions'  
)
```

## ⚠ Common Mistake (তোমার project এ হতে পারে)

```
for appointment in appointments:  
    print(appointment.doctor.department.name)
```

❌ যদি `select_related('doctor__department')` না থাকে

👉 N+1 query problem

## 🎯 Final Cheat Sheet (এই project অনুযায়ী)

Model	Use
Appointment	<code>select_related(patient, doctor)</code>
Doctor	<code>select_related(department) + prefetch(schedules)</code>
Patient	<code>prefetch(all reverse)</code>
Admission	<code>select_related(patient, room)</code>
Treatment	<code>select_related(admission, doctor)</code>
Room	<code>select_related(ward)</code>
Invoice	<code>select_related(patient) + prefetch(payments)</code>
LabReport	<code>select_related(all)</code>

যদি চাও 👉

আমি একটা **complete Patient Dashboard API** বানিয়ে দিতে পারি

যেখানে ১-২ query তেই সব data আসবে 🔥