

Carefully read the question and answer accordingly.

State TRUE or FALSE.

```
line 1: public class Test {  
line 2:     public static void main(String[] args) {  
line 3:     Queue queue = new LinkedList();  
line 4:         queue.add("Hello");  
line 5:         queue.add("World");  
line 6:         List list = new ArrayList(queue);  
line 7:     System.out.println(list); }  
line 8: }
```

Above code will give run time error at line number 3. **FALSE**

Identify the different actions which are generally used while integrating JavaBeans with JSP?

**<jsp:useBean><jsp:setProperty> and <jsp:getProperty>**

**<jsp:useBean> and <jsp:include>**

**<jsp:setProperty> <jsp:getProperty> and <jsp:forward>**

**<jsp:useBean> and <jsp:plugin>**

Mohanta, Priyanka (Cognizant) ?10:06 AM?:

1st option

Dey, Shatabdi (Cognizant) ?10:12 AM?:

Carefully read the question and answer accordingly

Which of the following is true with respect to code given below?

```
import java.sql.*;  
public class OracleDemo  
{  
    public static void main(String [] args) throws SQLException, ClassNotFoundException  
    {
```

```

Class.forName("oracle.jdbc.driver.OracleDriver");

Connection con=DriverManager.getConnection("jdbc
:oracle:thin:@PC188681:1521:training","scott","tig
er");
Statement stmt=con.createStatement();
ResultSet rs=stmt.executeQuery("SELECT * FROM Per
son");
while(rs.next())
{
    System.out.println(rs.getString("column1"));
}
}
}

```

The code will not compile as no try catch block specified

The code will display all values in column named column1

Class.forName must be mentioned after Connection statement

"SELE

T \* FROM Person" query must be passed as parameter to con.createStatement()

Mohanta, Priyanka (Cognizant) ?10:17 AM?:

1

Dey, Shatabdi (Cognizant) ?10:19 AM?:

Which statements are true about IN parameter?

IN Parameter is the default parameter.

IN Parameter value should be passed to the procedure for processing.

The same parameter will serve as input and output.

The IN parameter is a variable whose value will change in the invoked procedure.

Mohanta, Priyanka (Cognizant) ?10:24 AM?:

1,2,4

Dey, Shatabdi (Cognizant) ?10:25 AM?:

Which of the following statements are true?

- 1.A collection is an ordered group of elements, all of the same type
- 2.Each element in collection has a unique subscript that determines its position in the collection.
- 3.A collection is a ordered group of elements of different types
- 4.Records are composite types that have internal components that can be manipulated individually
- 5.Nested Table is also known as associative arrays

1&2

1&2&3

1&3&4

1&2&4

1&3&5

Mohanta, Priyanka (Cognizant) ?10:27 AM?:

1,2,4

waala option

While architecting a system, if "minimum down time" is the primary expected behavior of the system, the system architecture should be based on -----  
-----

Firewall

Cluster

Application Servers

Proxy Server

Sam is writing a web application program. He has implemented ServletContextListener interface in his web application program. Which method of ServletContextListener interface he should use to perform startup activities for web application?

init()

initiateContext()

contextInitialized()

start()

Mohanta, Priyanka (Cognizant) ?10:45 AM?:

3

context initialized

Carefully read the question and answer accordingly.

State whether TRUE or FALSE.

The below code will compile & provide desired output:

```
package p1;
interface Bounceable {
    void bounce();
    void setBounceFactor(int bf);
    private class BusinessLogic
    {
        int var1;
        float var2;
        double result(int var1,float var2){
            return var1*var2;
        }
    }
}
```

```

    }
  }
}
class Test {
    public static void main(String[] args) {
        System.out.println(new Bounceable.BusinessLogic()
            .result(12,12345.22F));
    }
}

```

TRUE

FALSE

Ans- false

Data can be passed to the function \_\_\_\_\_

by value

by reference

Both by value & reference

none of these

Mohanta, Priyanka (Cognizant) ?10:58 AM?:

both by value & reference

Dey, Shatabdi (Cognizant) ?10:58 AM?:

Garbage collector thread is a daemon thread.  
State True or False.

TRUE

FALSE

Mohanta, Priyanka (Cognizant) ?10:58 AM?:

true

Dey, Shatabdi (Cognizant) ?10:59 AM?:

Which tag creates containers to other HTML tags/elements?

I: DIV  
II: SPAN

I

II

Both I & II

None of the listed options  
Mohanta, Priyanka (Cognizant) ?11:00 AM?:

both I & II

i»¿[â€Ž9/â€Ž19/â€Ž2015 9:41 AM] Kumar, Pushpraj (Cognizant):  
is it valid to place some code in between try and catch blocks.

TRUE

FALSE  
[â€Ž9/â€Ž19/â€Ž2015 9:41 AM] Kumar, Pritam (Cognizant):  
false

[â€Ž9/â€Ž19/â€Ž2015 9:41 AM] Kumar, Pushpraj (Cognizant):  
BufferedWriter constructor CAN ACCEPT FileWriter Object as a parameter.  
State True or False.

TRUE

FALSE  
[â€Ž9/â€Ž19/â€Ž2015 9:41 AM] Kumar, Pritam (Cognizant):  
true

[â€Ž9/â€Ž19/â€Ž2015 9:45 AM] Kumar, Pushpraj (Cognizant):

Which method executes an SQL statement that may return multiple results?

`executeUpdate()`

`executeQuery()`

`execute()`

`noexecute()`

[â€Ž9/â€Ž19/â€Ž2015 9:48 AM] Kumar, Pritam (Cognizant):

`executeQuery()`

[â€Ž9/â€Ž19/â€Ž2015 9:48 AM] Kumar, Pushpraj (Cognizant):

Which of the below is invalid state of thread?

Runnable

Running

Dead

Blocked

Stop

[â€Ž9/â€Ž19/â€Ž2015 9:49 AM] Kumar, Pritam (Cognizant):

running

[â€™9/â€™19/â€™2015 9:51 AM] Kumar, Pushpraj (Cognizant):

Which of the following is not an attribute of meta tag?

content

name

value

http-equiv

[â€™9/â€™19/â€™2015 9:51 AM] Kumar, Pritam (Cognizant):

value

[â€™9/â€™19/â€™2015 9:54 AM] Kumar, Pushpraj (Cognizant):

Which tag is used to include multiple HTML pages in single page?

frame

frameset

frames

None of the listed options

[â€™9/â€™19/â€™2015 10:06 AM] Kumar, Pushpraj (Cognizant):

Which of the following is valid `_jspService()` method signature?

`private void _jspService(HttpServletRequest request, HttpServletResponse response) throws ServletException`



ption, java.io.IOException

```
public void _jspService(HttpServletRequest request
, HttpServletResponse response)throws ServletException,
java.io.IOException
```

```
public void _jspService(HttpServletRequest request
, HttpServletResponse response)throws ServletException
```

```
public void _jspService(HttpServletRequest request
, HttpServletResponse response)throws java.io.IOException
```

Lisa is a systems programmer at ABC Consultants. She has written an application to accept student marks in the variable marks. If the student has scored marks greater than 60. She needs to forward the control of the program to another file called as "Ex.jsp" else the control should be forwarded to a file called as "Av.jsp".

Which of the following code snippets should she use for checking this condition and forward control?

```
<% if(Integer.parseInt(request.getParameter("marks"))>=60) { %> <jsp:forward page="Ex.jsp" /> <% } else { %> <jsp:forward page="Av.jsp" /> <% } %>
```

```
<% if (request.retrieveParameter("marks"))>=60) { %> <jsp:moveforward page="Ex.jsp"> </jsp:forward> <% } else { %> <jsp:moveforward page="Av.jsp"> </jsp:forward> <% } %>
```

```
<% if (request.getParameter("marks"))>=6
```

[â€™9/â€™19/â€™2015 10:10 AM] Kumar, Pritam (Cognizant):

[â€™9/â€™19/â€™2015 10:08 AM] Ranjan, Kumar Alok (Cognizant):

```
ans:--- public void _jspService(HttpServletRequest request, HttpServletResponse response)throws ServletException, java.io.IOException
```

```
public void wala
```

Consider you are developing web application. Which of the following option is a valid in JSP for importing the package?

```
<%@ page import="java.util.*" %>
```

```
<%@ page session="true*" %>
```

```
<%@ include import="java.util.*" %>
```

```
<%@ include autoFlush="java.util.*" %>
```

```
<%@ page import="java.util.*" %>
```

[â€Ž9/â€Ž19/â€Ž2015 10:18 AM] Kumar, Pushpraj (Cognizant):

General Syntax for coding exception

DECLARE

Declaration Section

BEGIN

Exception Section

When ex\_name 1 THEN

Error handling Statements

When Others THEN

Error handling Statements

When ex\_name 1 THEN

Error handling Statements

END;

TRUE

**FALSE**

[â€Ž9/â€Ž19/â€Ž2015 10:20 AM] Kumar, Pritam (Cognizant):

true

[â€™9/â€™19/â€™2015 10:21 AM] Kumar, Pushpraj (Cognizant):

The functions used in SQL statements should not use OUT or IN OUT mode parameters

TRUE

FALSE

[â€™9/â€™19/â€™2015 10:22 AM] Kumar, Pritam (Cognizant):

true

[â€™9/â€™19/â€™2015 10:23 AM] Kumar, Pushpraj (Cognizant):

Statement A:Listener process scans for connection requests to an Oracle Instance

Statement B:Listener process links up a dispatcher process to user process.

which of the following is true?

Both Statements A and B are true

Statement A is true and Statement B is false

Statement A is false and Statement B is true

Both Statements A and B are false

[â€™9/â€™19/â€™2015 10:25 AM] Kumar, Pritam (Cognizant):

Both Statements A and B are true

[â€Ž9/â€Ž19/â€Ž2015 10:25 AM] Kumar, Pushpraj (Cognizant):

What will be the output of the below query?

```
select to_CHAR(sysdate+(10/1400),'HH:MI:SS') from dual;
```

adds 10 seconds to the current Timestamp

adds 10 minutes to the current Timestamp

adds 10 days to the current Timestamp

query contains error

date functions cannot be converted into char

[â€Ž9/â€Ž19/â€Ž2015 10:26 AM] Kumar, Pritam (Cognizant):

adds 10 minutes to the current Timestamp

Ronald has observed that his Web application has some HTML tags or features that all the Web browsers do not support. If the client's browser does not support the application may or may not run or may generate undesired output in the Web browser of the client. Therefore Ronald wants to identify the type of browser and other specific information about the client that sends the request to the Web application before invoking the servlet. Which of the following options will help Ronald provide this functionality?

By programming filters

By creating security constraints

By modifying the web deployment descriptor

By implementing the Listeners

[â€™9/â€™19/â€™2015 10:30 AM] Kumar, Pritam (Cognizant):

By programming filters

[â€™9/â€™19/â€™2015 10:33 AM] Kumar, Pushpraj (Cognizant):

If 1000 users are accessing SampleServlet how many actual object of servlets exist in web container?

1000

1

10

0

[â€™9/â€™19/â€™2015 10:33 AM] Kumar, Pritam (Cognizant):

1

Sam is writing a web application program. He has implemented ServletContextListener interface in his web application program. Which method of ServletContextListener interface he should use to perform startup activities for web application?

init()

initiateContext()

contextInitialized()

start()

contextInitialized()

[â€Ž9/â€Ž19/â€Ž2015 10:35 AM] Kumar, Pushpraj (Cognizant):

Consider the following code snippet:

```
ServletContext sc = this.getServletContext();
RequestDispatcher dis = sc.getRequestDispatcher("/menu.jsp");
if (dis != null){
    dis.include(request, response);
}
PrintWriter out = response.getWriter();
out.print("Output after menu.jsp");
```

Which one of the following will be the correct outcome when the above lines are executed?

Compilation and output of the contents of menu.jsp only

Compilation and output of the contents of menu.jsp followed by "Output after menu.jsp"

Compilation error

Compilation, but runtime error, the buffer has been flushed

[â€Ž9/â€Ž19/â€Ž2015 10:41 AM] Kumar, Pritam (Cognizant):

Compilation, but runtime error, the buffer has been flushed

Mark is developing a web based application. The home page is a servlet that accepts the user name and password. Mark does not want the user to enter t

he username every time he logs into the website. He wants to find a way to store the value on the user's machine. Which method should he use so that the value gets stored on the user's machine?

`getCookie()`

`addCookie()`

`addSession()`

`getSession()`

[â€™9/â€™19/â€™2015 10:44 AM] Kumar, Pritam (Cognizant):  
`addCookie`

[â€™9/â€™19/â€™2015 10:45 AM] Kumar, Pushpraj (Cognizant):  
Which complex type signifies that only one of the child elements can appear?

```
<xs:complexType name="CountrInfo"><xs:all> <xs:element name="countryName" type="xs:String"/> <xs:element name="states" type="xs:integer"/></xs:all></xs:complexType>
```

```
<xs:complexType name="CountrInfo"><xs:choice> <xs:element name="countryName" type="xs:String"/> <xs:element name="states" type="xs:integer"/></xs:choice></xs:complexType>
```

```
<xs:complexType name="CountrInfo"><xs:Sequence> <xs:element name="countryName" type="xs:String"/> <xs:element name="states" type="xs:integer"/></xs:Sequence></xs:complexType>
```

None of the listed options

[â€™9/â€™19/â€™2015 10:47 AM] Kumar, Pritam (Cognizant):

```
<xs:complexType name="CountrInfo"><xs:choice> <xs:element name="countryName" type="xs:String"/> <xs:element name="states" type="xs:integer"/></xs:choice></xs:complexType>
```

Consider the following code snippet:

```
String thought = "Green";
StringBuffer bufferedThought = new StringBuffer(
thought);
String secondThought = bufferedThought.toString(
);
System.out.println(thought == secondThought);
```

Which of the following option gives the output of the above code snippet?

TRUE

FALSE

[â€™9/â€™19/â€™2015 10:49 AM] Kumar, Pritam (Cognizant):

true h

[â€™9/â€™19/â€™2015 10:49 AM] Kumar, Pushpraj (Cognizant):

Any text that should not be parsed by the xml parser needs to declare as:

I: PCDATA

II: CDATA



I

II

Both I & II

None of the listed options

[â€™9/â€™19/â€™2015 10:54 AM] Kumar, Pritam (Cognizant):

II cdata is the answer

A good designed application should have " tight coupling and low cohesion"

TRUE

FALSE

[â€™9/â€™19/â€™2015 10:51 AM] Kumar, Pushpraj (Cognizant):

Examine the PL/SQL Block

declare

result Number;

num1 Number:=&number1;

num2 Number:=&number2;

begin

select num1/num2 into result from dual;

dbms\_output.put\_line('Result is '||result);

exception

when ZEROS\_DIVIDE then

dbms\_output.put\_line('Exception Occurred Divide by Zero');

end;

/

What will be the output of the above code when user passes the value for NUM1 as 0 and NUM2 as 10

Exception Occurred Divide by Zero

Result is 10

Result is 0

Compilation fails

ans:-- Result is 0

Compiles successfully and terminates the program due to an Exception

[â€™9/â€™19/â€™2015 10:58 AM] Kumar, Pushpraj (Cognizant):

Which code assign null to all the fields in the record

emp\_info?

```
DECLARE TYPE EmpRec IS RECORD ( emp_id emp.empno%TYPE, job_title VARCHAR2(9), salary NUMBER(7,2)); emp_info EmpRec; BEGIN emp_info.emp_id := 7788; emp_info.job_title := 'ANALYST'; emp_info.salary := 3500; END;
```

```
DECLARE TYPE EmpRec IS RECORD ( emp_id emp.empno%TYPE, job_title VARCHAR2(9), salary NUMBER(7,2)); emp_info EmpRec; BEGIN emp_info.emp_id := 7788; emp_info.job_title := 'ANALYST'; emp_info.salary := 3500; emp_info := emp_null; END;
```

```
DECLARE TYPE EmpRec IS RECORD ( emp_id emp.empno%TYPE, job_title VARCHAR2(9), salary NUMBER(7,2)); emp_info EmpRec; emp_null EmpRec; BEGIN emp_info.emp_id := 7788; emp_info.job_title := 'ANALYST'; emp_info.salary := 3500; emp_info := emp_null; END;
```

None of the above

[â€Ž9/â€Ž19/â€Ž2015 11:01 AM] Kumar, Pushpraj (Cognizant):  
Garbage collector thread is a daemon thread.  
State True or False.

TRUE

FALSE

[â€Ž9/â€Ž19/â€Ž2015 11:02 AM] Kumar, Pritam (Cognizant):

true

[â€Ž9/â€Ž19/â€Ž2015 11:03 AM] Kumar, Pritam (Cognizant):

DECLARE

```

â€Ž â€Ž â€Ž TYPE EmpRec IS RECORD (â€Ž
â€Ž â€Ž â€Ž â€Ž â€Ž emp_id      emp.empno%TYPE,
â€Ž â€Ž â€Ž â€Ž â€Ž job_title  VARCHAR2(9),
â€Ž â€Ž â€Ž â€Ž â€Ž salary      NUMBER(7,2));
â€Ž â€Ž â€Ž emp_info EmpRec;
â€Ž â€Ž â€Ž emp_null EmpRec;
```

BEGIN

```

â€Ž â€Ž â€Ž emp_info.emp_id := 7788;
â€Ž â€Ž â€Ž emp_info.job_title := 'ANALYST';
â€Ž â€Ž â€Ž emp_info.salary := 3500;
â€Ž â€Ž â€Ž emp_info := emp_null; -- nulls all fields in
emp_info
â€Ž â€Ž â€Ž ...
```

END;

b hain answer pr mila le

[â€Ž9/â€Ž19/â€Ž2015 11:05 AM] Kumar, Pushpraj (Cognizant):

kiska b?

[â€Ž9/â€Ž19/â€Ž2015 11:05 AM] Kumar, Pritam (Cognizant):

emp nul wala ka

c bhai krle

abhi dekhe

[â€Ž9/â€Ž19/â€Ž2015 11:07 AM] Kumar, Pritam (Cognizant):

emp wala ka c h option thik h

Which code assign null to all the fields in the record

emp\_info?

answer c h

[â€™9/â€™19/â€™2015 11:09 AM] Kumar, Pushpraj (Cognizant):

ohhk bhai

Carefully read the question and answer accordingly.

Examine the code snippet

declare

TYPE ABC is VARRAY(10) of NUMBER;

v2 ABC:=ABC(10,8,9,6,5,4,3,32);

begin

Dbms\_output.put\_line(v2(1));

end;

what will be the output of the above code ?

Compilation fails

Compiles and prints 8

Compiles and prints 10

Compiles and prints 1

Compiles and runs without any output

DECLARE

A BOOLEAN := NULL;

B BOOLEAN;

BEGIN

B := A IS NULL;

IF B IS NULL THEN

DBMS\_OUTPUT.PUT\_LINE('HI');

END IF;

END[â€™9/â€™19/â€™2015 11:16 AM] Kumar, Pushpraj (Cognizant):

Carefully read the question and answer accordingly.

Statement A:Listener process scans for connection requests to an Oracle Instance

Statement B:Listener process links up a dispatcher process to user process.

which of the following is true?

Both Statements A and B are true

Statement A is true and Statement B is false

Statement A is false and Statement B is true

Both Statements A and B are false

[â€™9/â€™19/â€™2015 11:16 AM] Kumar, Pritam (Cognizant):

Both Statements A and B are true

[â€™9/â€™19/â€™2015 11:17 AM] Kumar, Pushpraj (Cognizant):

aur upar wala dekh bhai

[â€™9/â€™19/â€™2015 11:18 AM] Kumar, Pritam (Cognizant):

upar wala dono ka nhi mil rha

dekh rha hu

[â€™9/â€™19/â€™2015 11:20 AM] Kumar, Pushpraj (Cognizant):

Carefully read the question and answer accordingly.

Which trigger is used to display the salary change information whenever a DELETE , INSERT or UPDATE statement affects the tbl\_employees table(Salary Column)- The trigger should be FOR EACH ROW trigger. SAMPLE OUTPUT : Fahan,Karn: Old salary = 3500, New salary = 4500, Difference: 1000

```
CREATE OR REPLACE TRIGGER salary_changes BEFORE DE
LETE OR INSERT OR UPDATE ON TBL_EMPLOYEES FOR EACH
ROW DECLARE sal_diff NUMBER; BEGIN sal_diff := :N
EW.salary - :OLD.salary; DBMS_OUTPUT.PUT(:OLD.firs
tname||','||:OLD.lastname|| ': '); DBMS_OUTPUT.PUT
('Old salary = ' || :OLD.salary || ', '); DBMS_OUT
PUT.PUT('New salary = ' || :NEW.salary || ', '); D
BMS_OUTPUT.PUT_LINE('Difference: ' || sal_diff); E
ND;
```

CREATE OR REPLACE TRIGGER salary\_changes BEFORE  
[â€™9/â€™19/â€™2015 11:23 AM] Kumar, Pritam (Cognizant):

```

CREATE OR REPLACE TRIGGER salary_changes BEFORE DE
LETE OR INSERT OR UPDATE ON TBL_EMPLOYEES FOR EACH
ROW DECLARE sal_diff NUMBER; BEGIN sal_diff := :N
EW.salary - :OLD.salary;
[â€™9/â€™19/â€™2015 11:24 AM] Kumar, Pritam (Cogniz
ant):
DECLARE
A BOOLEAN := NULL;
B BOOLEAN;
BEGIN
B := A IS NULL;
IF B IS NULL THEN
DBMS_OUTPUT.PUT_LINE('HI');
END IF;
END
ans is false
[â€™9/â€™19/â€™2015 11:26 AM] Kumar, Pushpraj (Cogn
izant):
trigger ka fir se bhejo
nhi aaya pura
[â€™9/â€™19/â€™2015 11:26 AM] Kumar, Pritam (Cogniz
ant):
CREATE OR REPLACE TRIGGER salary_changes BEFORE DE
LETE OR INSERT OR UPDATE ON TBL_EMPLOYEES FOR EACH
ROW DECLARE sal_diff NUMBER; BEGIN sal_diff := :N
EW.salary - :OLD.salary;
1st option
[â€™9/â€™19/â€™2015 11:28 AM] Kumar, Pushpraj (Cogn
izant):
thnx bhai
[â€™9/â€™19/â€™2015 11:29 AM] Kumar, Pritam (Cogniz
ant):
ho gya naa
1.A field with default access specifier can be acce
ssed out side the package.
State True or False.
a:f

```

2.Constructor of an class is executed each time whe  
n an object of that class is created

TRUE

3.Carefully read the question and answer accordingly.

Which of the following are not List implementations?

1.Vector

2.Hashtable

3.LinkedList

4.Properties

2,4

4.Carefully read the question and answer accordingly.

executeUpdate() & execute() are valid methods that can be used for executing DDL statements. State True or False

f

5.What will happen if two thread of same priority are called to be processed simultaneously?

a:It is dependent on the operating system.

6.Which of the following statements are true?

Statement1: When a thread is sleeping as a result of sleep(), it releases its locks.

Statement2: The Object.wait() method can be invoked only from a synchronized context.

a:2

6.What are the benefits of Logging?

1.Debug applications issues easily

2.Detect compiler errors easily

3.Trouble Shoot performance problems

a:1,3

7.What is the use of GOOGLEBOT command?

a:shd b archived

8.Consider Vijay is developing web page using HTML .Which method he can use for sending large amount of data on submitting the form?

I: POST

9Automatic page Refresh can be done by using refresh Meta Tag.

State True or False.

TRUE

10.Which of the following are used for executing client side script?

1.JavaScript

2.JSP

3.Servlets

4.VBScript

1,4

11.Consider you are developing java application in a team consists of 20 developers and you have been asked to develop class by Name ProgrammerAnalyst and to ensure that other developers in team use ProgrammerAnalyst class only by creating object and team member should not be given provision to inherit and modify any functionality written in ProgrammerAnalyst class using inheritance. How do you achieve this requirement in development scenario?

Declare the ProgrammerAnalyst class has final

12.The method Class.forName() is a part of JDBC API . State True or False.

TRUE

13.Which packages contain the JDBC classes?

java.sql and javax.sql

14.Which of these interface is not a member of java



.io package?

ObjectFilter

14.

all d options r correct??

Padhi, Bibhuti Bhusan (Cognizant) ?9:50 AM?:

yup

send the subclass question ones more

SAHU, SARTHAK (Cognizant) ?9:51 AM?:

Carefully read the question and answer accordingly.

Choose the correct option.

Statement I: A subclass inherits all of the "public" and "protected" members of its parent, no matter what package the subclass is in.

Statement II: If the subclass of any class is in the same package then it inherits the default access members of the parent.

Statement I & II are TRUE

Statement I is TRUE & II is FALSE

Statement I is FALSE & II is TRUE

Statement I & II are FALSE

Carefully read the question and answer accordingly.

Which object allows you to execute parametrized queries?

ResultSet

Parametrized

PreparedStatement

Condition

the ans for subclass

and the next questions

Carefully read the question and answer accordingly.

The method `Class.forName()` is a part of JDBC API. State True or False.

TRUE

FALSE

Padhi, Bibhuti Bhusan (Cognizant) ?9:56 AM?:

TRUE

SAHU, SARTHAK (Cognizant) ?9:57 AM?:

Carefully read the question and answer accordingly.

Garbage collector thread is a daemon thread.  
State True or False.

TRUE

FALSE

??

Carefully read the question and answer accordingly.

Consider you are developing a JDBC application, where you have to retrieve quarterly report from database by executing database store procedure created by database developer. Which statement API you will use to execute store procedure and retrieve ResultSet information?

Statement

PreparedStatement

## CallableStatement

None of the listed options

??

Padhi, Bibhuti Bhusan (Cognizant) ?10:04 AM?:

CallableStatement

SAHU, SARTHAK (Cognizant) ?10:06 AM?:

Carefully read the question and answer accordingly.

If we want to apply a style for a text or a part of a text which tag will be used?

I: **SPAN**

II: DIV

**I**

II

Both I & II

None of the listed options

??

??

Padhi, Bibhuti Bhusan (Cognizant) ?10:11 AM?:

BOTH I & II

both

SAHU, SARTHAK (Cognizant) ?10:14 AM?:

Carefully read the question and answer accordingly.

How to divide the page into two equal halves when we are using frameset ?

1.By using cols=50%,50%

2.By using rows=50%,50%

3.By using colspan  
4.by using rowspan

1&2

3&4

2&3

1&4

??

Carefully read the question and answer accordingly.

What are the types of refactoring?

- 1.Physical Structure
- 2.Logical Structure
- 3.Method Level
- 4.Class Level Structure

1&2

3&4

2&3

1&4

Padhi, Bibhuti Bhusan (Cognizant) ?10:19 AM?:

1&2

SAHU, SARTHAK (Cognizant) ?10:19 AM?:

Carefully read the question and answer accordingly.

What are the major areas PMD tool scans java code?

Coding standards

Violation of best practice

Possible performance bottlenecks

All of the listed options

Padhi, Bibhuti Bhusan (Cognizant) ?10:20 AM?:

3&4

All of the listed options

SAHU, SARTHAK (Cognizant) ?10:21 AM?:

Carefully read the question and answer accordingly.

An art of identifying, organizing, controlling and verifying the modification to the software work products built by the developer.

SDLC

SVN

SCM

HCM

Padhi, Bibhuti Bhusan (Cognizant) ?10:22 AM?:

Garbage collector thread is a daemon thread.  
State True or False.

TRUE

FALSE

??

ans:true

SAHU, SARTHAK (Cognizant) ?10:22 AM?:

kk

Carefully read the question and answer accordingly.

An art of identifying, organizing, controlling and verifying the modification to the software work products built by the developer.

roducts built by the developer.

SDLC

SVN

SCM

HCM

Padhi, Bibhuti Bhusan (Cognizant) ?10:22 AM?:

scm

SAHU, SARTHAK (Cognizant) ?10:23 AM?:

Carefully read the question and answer accordingly.

In JavaScript, for accessing first paragraph tag in the document which of the statement is used?

`document.getElementsByTagName("p")[0]`

`document.getElementsByTagName("p")`

`document.getElementsByTagName("p[0]")`

None of the listed options

Carefully read the question and answer accordingly.

Identify the entry in web.xml that will instruct the container to compile the JSP when the container starts rather than waiting for the first time.

`<load-on-startup>`

`<load-on-start>`

`<loadonstartup>`

`<load-on-Init>`

Padhi, Bibhuti Bhusan (Cognizant) ?10:25 AM?:

```
document.getElementsByTagName("p")[0]
```

```
<load-on-startup>
```

```
SAHU, SARTHAK (Cognizant) ?10:30 AM?:
```

Carefully read the question and answer accordingly.

How do you declare a tag library within a JSP page to use custom tags?

By using scriptlet.

By using taglib directive.

By using unique variable.

By using path to the tag handler.

??

Carefully read the question and answer accordingly.

Consider you are developing web application which following code snippet listed depicts that the JSP page is an errorpage?

```
<%@ page isErrorPage="true" %>
```

```
<%@ page ErrorPage="true" %>
```

```
<%@ page isErrorPage="false" %>
```

```
<%@ page ErrorPage="false" %>
```

Carefully read the question and answer accordingly.

Expression Language treats null values as "zero" in arithmetic operations. State True or False.

TRUE

FALSE

??

Carefully read the question and answer accordingly.

Scripting can be blocked in a jsp by:

Putting <scripting-invalid> element in web.xml

Declaring <scripting-invalid> tag at the top of JSP page

Putting scripting-invalid=true attribute in form tag

Scripting can't be blocked

Carefully read the question and answer accordingly.

Expression Language treats null values as "zero" in arithmetic operations. State True or False.

TRUE

FALSE

??

Padhi, Bibhuti Bhusan (Cognizant) ?10:42 AM?:

By using taglib directive.

```
<%@ page isErrorPage="true" %>
SAHU, SARTHAK (Cognizant) ?10:44 AM?:
```

Carefully read the question and answer accordingly.

You cannot assign nulls to a variable defined as NOT NULL. If you try, PL/SQL raises the predefined exception \_\_\_\_\_

STORAGE\_ERROR



VALUE\_ERROR

SELF\_IS\_NULL

PROGRAM\_ERROR

Padhi, Bibhuti Bhusan (Cognizant) ?10:45 AM?:

Declaring <scripting-invalid> tag at the top of JSP page

TRUE (Expression Language treats null values as "zero" In arithmetic operations.State True or False.)

SAHU, SARTHAK (Cognizant) ?10:46 AM?:

ans the recent ques

Carefully read the question and answer accordingly.

You cannot assign nulls to a variable defined as NOT NULL. If you try, PL/SQL raises the predefined exception \_\_\_\_\_

STORAGE\_ERROR

VALUE\_ERROR

SELF\_IS\_NULL

PROGRAM\_ERROR

Padhi, Bibhuti Bhusan (Cognizant) ?10:48 AM?:

VALUE\_ERROR

SAHU, SARTHAK (Cognizant) ?10:48 AM?:

Carefully read the question and answer accordingly.

The functions can return PL/SQL specific data types such as BOOLEAN, RECORD, or TABLE

TRUE

FALSE

Padhi, Bibhuti Bhusan (Cognizant) ?10:48 AM?:

\*CHANGE IN ANSWER Putting scripting-invalid=true at  
tribute in form tag

SAHU, SARTHAK (Cognizant) ?10:49 AM?:

kk

Padhi, Bibhuti Bhusan (Cognizant) ?10:49 AM?:

TRUE

TRUE FOR PL/SQL

SAHU, SARTHAK (Cognizant) ?10:49 AM?:

Carefully read the question and answer accordingly.

Which of the following is the benefits using triggers in database management system?

Faster application development. Because the database stores triggers, you do not have to code the trigger actions into each database application.

Global enforcement of business rules. Define a trigger once and then reuse it for any application that uses the database.

Easier maintenance. If a business policy changes, you need to change only the corresponding trigger program instead of each application program.

Improve performance in client/server environment. All rules run in the server before the result returns.

All of the listed options

Padhi, Bibhuti Bhusan (Cognizant) ?10:49 AM?:

PL/SQL

SAHU, SARTHAK (Cognizant) ?10:52 AM?:

Carefully read the question and answer accordingly.

Which of the following Listener can get context in it parameter and run some code before rest of the application can service a client?

ServletContextAttributeListener

ServletContextListener

HttpSessionListener

None of the listed options

Carefully read the question and answer accordingly.

Consider you are trying to persist or store object of Customer class using ObjectOutputStream class in java. When you are trying to persist customer object data java code is throwing runtime exception without persisting object information. Please suggest what is the key important factor you have consider in code in order to persist customer object data.

Check whether you have implemented Customer class with Serializable interface

Check whether you have implemented Customer class with Externalizable interface

Check whether you have marked Customer class methods with synchronized keyword

None of the listed options

Carefully read the question and answer accordingly.

You are developing a web application and based on the client requests, your application has to share huge data files with respective clients. To save the network bandwidth, the files have to be compressed.

used before sending the response. The logic for compressing the data files should not be redundant though compression has to be applied for all the responses. Which design pattern should be used in this scenario to avoid the duplication of the compression code?

## Intercepting Filter

DAO

Model - View - Controller

Transfer Object

??

Padhi, Bibhuti Bhusan (Cognizant) ?11:00 AM?:

ServletContextAttributeListener

SAHU, SARTHAK (Cognizant) ?11:02 AM?:

plz focus on recent two questions

Padhi, Bibhuti Bhusan (Cognizant) ?11:02 AM?:

wait....

SAHU, SARTHAK (Cognizant) ?11:03 AM?:

kk

Padhi, Bibhuti Bhusan (Cognizant) ?11:04 AM?:

Check whether you have marked Customer class methods with synchronized keyword

DAO

SAHU, SARTHAK (Cognizant) ?11:06 AM?:

are u sure DAO??

YA transfer object

Carefully read the question and answer accordingly.

Examine the table structure of Employee

Ename	Ecode	Dept
-------	-------	------

John	1	Sal
Smith	3	Mar
Max	2	Sal
Joe	4	Mar
Laura	5	Dep

What will be the output of below query ?

```
select decode(Ecode,5,'Department',4,'Marketing',3  
, 'Marketing', 'Sales') as result from Employee;
```

Query contains error

Sales Marketing Sales Marketing Department

Department Marketing Marketing Sales Sales

Cannot predict the output of the query

Padhi, Bibhuti Bhusan (Cognizant) ?11:08 AM?:

query contain error

yah dao

SAHU, SARTHAK (Cognizant) ?11:08 AM?:

kk

Carefully read the question and answer accordingly.

What are the types of refactoring?

1.Physical Structure

2.Logical Structure

3.Method Level

4.Class Level Structure

Padhi, Bibhuti Bhusan (Cognizant) ?11:10 AM?:

`option

phy method class

SAHU, SARTHAK (Cognizant) ?11:11 AM?:

Carefully read the question and answer accordingly.

What are the types of refactoring?

1.Physical Structure

- 2.Logical Structure
- 3.Method Level
- 4.Class Level Structure

1&2

3&4

2&3

1&4

??

Padhi, Bibhuti Bhusan (Cognizant) ?11:14 AM?:

3&4

SAHU, SARTHAK (Cognizant) ?11:14 AM?:

Carefully read the question and answer accordingly.

Select the best definition for Why Collection needed in Oracle?

A group of related data items stored in fields , each fields has its own name and datatype.

You can think of a record as a variable that can hold a table row or some columns from a table row.

An software application links up with a Active data objects, there is a not much performance value to be paid. Not only that, programs that continually switch off between code and SQL can become quite complex.

Every time a software application connect up with a database, there is a performance value to be paid. Not only that, programs that continually switch off between code and SQL can become quite complex.

Padhi, Bibhuti Bhusan (Cognizant) ?11:15 AM?:

nope cant find this

-----

deepjyoti.dev@cognizant.com ?9:40 AM?:

Carefully read the question and answer accordingly.

LinkedList represents a collection that does not allow duplicate elements.

TRUE

FALSE

Padhi, Bibhuti Bhusan (Cognizant) ?9:40 AM?:

FALSE

Dev, Deepjyoti (Cognizant) ?9:42 AM?:

Carefully read the question and answer accordingly.

State whether TRUE or FALSE.

Object class provides a method named getClass() which returns runtime class of an object.

TRUE

FALSE

Padhi, Bibhuti Bhusan (Cognizant) ?9:43 AM?:

TRUE

Dev, Deepjyoti (Cognizant) ?9:44 AM?:

Carefully read the question and answer accordingly.

You are using JDBC-ODBC bridge driver to establish a connection with a database. You have created a DSN Mydsn. Which statement will you use to connect to the database?

```
Connection cn=DriverManager.getConnection("jdbc:odbc");
```

```
Connection cn=DriverManager.getConnection("jdbc:odbc:Mydsn", "username", "password");
```

```
Connection cn=DriverManager.getConnection("jdbc:odbc ", "username", "password");
```

```
Connection cn=DriverManager.getConnection("jdbc:odbc:dsn", "username", "password");
```

Padhi, Bibhuti Bhusan (Cognizant) ?9:45 AM?:

```
Connection cn=DriverManager.getConnection("jdbc:odbc:Mydsn", "username", "password");
```

Dev, Deepjyoti (Cognizant) ?9:55 AM?:

Q13

Carefully read the question and answer accordingly.

Interfaces are mainly used to expose behavior or functionality not the implementation code.

State true or false

TRUE

FALSE

Padhi, Bibhuti Bhusan (Cognizant) ?9:57 AM?:

TRUE

Dev, Deepjyoti (Cognizant) ?9:58 AM?:

Carefully read the question and answer accordingly.

Automatic page Refresh can be done by using refresh Meta Tag.

State True or False.

TRUE

FALSE

Padhi, Bibhuti Bhusan (Cognizant) ?10:03 AM?:

TRUE

Dev, Deepjyoti (Cognizant) ?10:15 AM?:



Carefully read the question and answer accordingly.

An art of identifying, organizing, controlling and verifying the modification to the software work products built by the developer.

SDLC

SVN

SCM

HCM

Padhi, Bibhuti Bhusan (Cognizant) ?10:18 AM?:

SCM

Dev, Deepjyoti (Cognizant) ?10:25 AM?:

Carefully read the question and answer accordingly.

Consider the following statements:

Statement A: A tag library descriptors an XML document that contains information about a library as a whole and about each tag contained in the library.

Statement B: TLDs are used by a Web container to validate the tags used by JSP page development tools.

Which of the following is true about these statements?

Statement A is true and statement B is true.

Statement A is true and statement B is false.

Statement A is false and statement B is true.

Statement A is false and statement B is false.

31

Padhi, Bibhuti Bhusan (Cognizant) ?10:28 AM?:

both

Dev, Deepjyoti (Cognizant) ?10:30 AM?:

bioth true ya false..???

Padhi, Bibhuti Bhusan (Cognizant) ?10:34 AM?:

oh sorry...true

Dev, Deepjyoti (Cognizant) ?10:37 AM?:

Q37

Carefully read the question and answer accordingly.

What exception is raised when the user enters the ID as -6 in the below code?

```
DECLARE
```

```
    c_id customers.id%type := &cc_id;
```

```
    c_name  customers.name%type;
```

```
    c_addr customers.address%type;
```

```
    -- user defined exception
```

```
    ex_invalid_id  EXCEPTION;
```

```
BEGIN
```

```
    IF c_id <= 0 THEN
```

```
        RAISE ex_invalid_id;
```

```
    ELSE
```

```
        SELECT  name, address INTO  c_name, c_addr
```

```
        FROM customers
```

```
        WHERE id = c_id;
```

```
    END IF;
```

```
EXCEPTION
```

```
    WHEN ex_invalid_id THEN
```

```
        dbms_output.put_line('ID must be greater than  
zero!');
```

```
    WHEN no_data_found THEN
```

```
        dbms_output.put_line('No such customer!');
```

```
END; /
```

NO DATA FOUND exception will be raised

`ex_invalid_id` exception will be raised

The program will be terminated abruptly.

TOO MANY ROWS exce

Q51

Carefully read the question and answer accordingly.

The method `getWriter()` of `HttpServletResponse` returns an object of type \_\_\_\_\_.

`HttpServletRequest`

`PrintWriter`

`ServletContext`

`ServletConfig`

Padhi, Bibhuti Bhusan (Cognizant) ?10:50 AM?:

`PrintWriter`

Dev, Deepjyoti (Cognizant) ?10:52 AM?:

Q47

Carefully read the question and answer accordingly.

Which of the following interface represents the `Servlet Config` for the current `Servlet`?

`javax.servlet.ServletConfig`

`javax.Servlet.Config`

`javax.Config`

`Servlet.Config`

Padhi, Bibhuti Bhusan (Cognizant) ?10:53 AM?:

`javax.servlet.config`

ricky ami dipa

:P

ami bibhuti er account e online

ok

Dev, Deepjyoti (Cognizant) ?10:53 AM?:

Q49

Carefully read the question and answer accordingly.

A filter configuration object used by a servlet container to pass information to a filter during initialization.

State True or False.

TRUE

FALSE

Padhi, Bibhuti Bhusan (Cognizant) ?10:56 AM?:

true

Dev, Deepjyoti (Cognizant) ?10:56 AM?:

Carefully read the question and answer accordingly.

Which of the following codes will allow the user to load the servlet using form. The form should first display submit button and when the user clicks on submit button it should load the servlet called myservlet?

```
<HTML> <BODY> <FORM ACTION=http://localhost:8080/servlet/myservlet METHOD=GET> </FORM> </BODY> </HTML>
```

```
<HTML> <BODY> <FORM ACTION=http://localhost:8080/servlet/myservlet METHOD=GET> <INPUT TYPE=SUBMIT VALUE=SUBMIT> </FORM> </BODY> </HTML>
```

```
<HTML> <BODY> <INPUT TYPE=SUBMIT VALUE=SUBMIT> </FORM> </BODY> </HTML>
```

```
<HTML> <BODY> <FORM ACTION=http://localhost:8080/servlet METHOD=GET> <INPUT TYPE=SUBMIT VALUE=SUBMIT> </FORM> </BODY> </HTML>
```

-----  
-

hi

bhai online rehna pls

:)

Padhi, Bibhuti Bhusan (Cognizant) ?9:27 AM?:

yup I am :)

Mitra, Arunava (Cognizant) ?9:40 AM?:

If any class has at least one abstract method you must declare it as abstract class

t or F

?

Padhi, Bibhuti Bhusan (Cognizant) ?9:41 AM?:

TRUE

Mitra, Arunava (Cognizant) ?9:46 AM?:

Which of the following is an empty tag in HTML?

<a>

<br>

<input>

<h1>

??

Padhi, Bibhuti Bhusan (Cognizant) ?9:46 AM?:

<br>

Mitra, Arunava (Cognizant) ?9:47 AM?:

What is the use of GOOGLEBOT command?

To tell google that the page should not be archived

To tell google that the page should be archived

To tell google that the page should not be saved

None of the listed options

??

Padhi, Bibhuti Bhusan (Cognizant) ?9:52 AM?:

To tell google that the page should be archived

Mitra, Arunava (Cognizant) ?9:56 AM?:

Carefully read the question and answer accordingly.

Which tool verifies for best practice adherence?

- 1.PMD
- 2.Check Style
- 3.CPD
- 4.ANT

?

1&2

1&2&3

1&3&4

1&2&4

1&3

Padhi, Bibhuti Bhusan (Cognizant) ?9:57 AM?:

1&2

Mitra, Arunava (Cognizant) ?9:57 AM?:

Which of the following is valid `_jspService()` method signature?

```
private void _jspService(HttpServletRequest request, HttpServletResponse response) throws ServletException, java.io.IOException
```

```
public void _jspService(HttpServletRequest request, HttpServletResponse response) throws ServletException, java.io.IOException
```

```
public void _jspService(HttpServletRequest request, HttpServletResponse response) throws ServletException
```

```
public void _jspService(HttpServletRequest request, HttpServletResponse response) throws java.io.IOException
```

Padhi, Bibhuti Bhusan (Cognizant) ?10:00 AM?:

```
public void _jspService(HttpServletRequest request, HttpServletResponse response) throws java.io.IOException
```

```
public void _jspService(HttpServletRequest request, HttpServletResponse response) throws ServletException, java.io.IOException
```

\*change of ans

```
public void _jspService(HttpServletRequest request, HttpServletResponse response) throws ServletException, java.io.IOException
```

Mitra, Arunava (Cognizant) ?10:10 AM?:

ok

Identify the correct syntax to create a sequence which generates values as 2,4,6,8,10?

Create sequence MySeq Start with 2 Increment by 1

Create sequence MySeq ( Start with 2 Increment by 1 )

Create sequence MySeq ( Start with 2 Increment by 2 )

Create sequence MySeq Start with 2 Increment by 2

Create sequence MySeq as Start with 2 Increment by 2

Carefully read the question and answer accordingly.

What will be the output of the query?

Select trim(0 from '00003443500') from dual?

Query contains error

34435

3443500

3443500

344350

Carefully read the question and answer accordingly.

Which of the following codes will allow the user to load the servlet using form. The form should first display submit button and when the user clicks on submit button it should load the servlet called myservlet?

<HTML> <BODY> <FORM ACTION=http://localhost:8080/s



```
ervlet/myervlet METHOD=GET> </FORM> </BODY> </HTML>
```

```
<HTML> <BODY> <FORM ACTION=http://localhost:8080/s  
ervlet/myervlet METHOD=GET> <INPUT TYPE=SUBMIT VA  
LUE=SUBMIT> </FORM> </BODY> </HTML>
```

```
<HTML> <BODY> <INPUT TYPE=SUBMIT VALUE=SUBMIT> </FO  
RM> </BODY> </HTML>
```

```
<HTML> <BODY> <FORM ACTION=http://localhost:8080/s  
ervlet METHOD=GET> <INPUT TYPE=SUBMIT VALUE=SUBMIT  
> </FORM> </BODY> </HTML>
```

??

Padhi, Bibhuti Bhusan (Cognizant) ?10:29 AM?:

```
<HTML> <BODY> <FORM ACTION=http://localhost:8080/s  
ervlet/myervlet METHOD=GET> <INPUT TYPE=SUBMIT VA  
LUE=SUBMIT> </FORM> </BODY> </HTML>
```

34435

-----