



Digital Image Processing Chapter 9

Morphological Image Processing

By: Dr. Hafeez

Contents

Once segmentation is complete, morphological operations can be used to remove imperfections in the segmented image and provide information on the form and structure of objects in the image

In this lecture we will consider

- What is morphology?
- Simple morphological operations
- Compound operations
- Morphological algorithms

1, 0, Black, White?

Throughout all of the following slides whether 0 and 1 refer to white or black is a little interchangeable

All of the discussion that follows assumes segmentation has already taken place and that images are made up of 0s for background pixels and 1s for object pixels

After this it doesn't matter if 0 is black, white, yellow, green......

What Is Morphology?

Morphological image processing (or *morphology*) describes a range of image processing techniques that deal with the **shape (or morphology) of objects in an image**

Morphological operations are typically applied to remove imperfections introduced during segmentation, and so typically operate on bi-level images

Quick Example








Image after segmentation and morphological processing



Structuring Elements, Hits & Fits





Fit: All *on pixels* in the structuring element cover *on pixels* in the image

Hit: Any on pixel in the structuring element covers an on pixel in the image

All morphological processing operations are based on these simple ideas

Structuring Elements

Structuring elements can be any size and make any shape

However, for simplicity we will use rectangular structuring elements with their origin at the middle pixel

1	1	1
1	1	1
1	1	1

0	1	0
1	1	1
0	1	0

0	0	1	0	0
0	1	7	7	0
1	1	1	1	1
0	1	1	1	0
0	0	1	0	0

Fitting & Hitting

0	0	0	0	0	0	0	0	0	0	0	0
0	0	0	1	1	0	0	0	0	0	0	0
0	0	1	88	1	1	1	0	0	0	0	0
0	1	1	1	1	1	1	1	0	0	0	0
0	1	1	1	1	1	1	1	0	0	0	0
0	0	1	1	1	1	1	1	0	0	0	0
0	0	1	7	1	1	1	1	1	0	0	0
0	0	1	7	1	1	1	A	1	1	1	0
0	0	0	0	0	1	1	1	1	1	1	0
0	0	0	0	0	0	0	0	0	0	0	0

1	1	1
1	1	1
1	1	1

Structuring Element 1

0	1	0
1	1	1
0	1	0

Structuring Element 2

Fundamental Operations

- Fundamentally morphological image processing is very like spatial filtering
- The structuring element is moved across every pixel in the original image to give a pixel in a new processed image
- The value of this new pixel depends on the operation performed
- There are two basic morphological operations: **erosion** and **dilation**


Erosion of image f by structuring element s is given by $f \ominus s$

The structuring element s is positioned with its origin at (x, y) and the new pixel value is determined using the rule:

$$g(x, y) = \begin{cases} 1 & \text{if } s \text{ fits } f \\ 0 & \text{otherwise} \end{cases}$$


11 of 40

Erosion Example



Structuring Element

Erosion Example



Structuring Element

Erosion Example 1






Erosion by 3*3 square structuring element



Erosion by 5*5 square structuring element

Watch out: In these examples a 1 refers to a black pixel!


Erosion Example 2






What Is Erosion For?

Erosion can split apart joined objects



Erosion can strip away extrusions




Watch out: Erosion shrinks objects


Dilation of image f by structuring element s is given by $f \oplus s$


The structuring element s is positioned with its origin at (x, y) and the new pixel value is determined using the rule:


$$g(x, y) = \begin{cases} 1 & \text{if } s \text{ hits } f \\ 0 & \text{otherwise} \end{cases}$$



Structuring Element







Structuring Element





Dilation by 3*3 square structuring element



Dilation by 5*5 square structuring element

Watch out: In these examples a 1 refers to a black pixel!

Original image

Historically, certain computer programs were written using only two digits rather than four to define the applicable year. Accordingly, the company's software may recognize a date using "00" as 1900 rather than the year 2000.

After dilation

Historically, certain computer programs were written using only two digits rather than four to define the applicable year. Accordingly, the company's software may recognize a date using "00" as 1900 rather than the year 2000.


0	1	0
1	1	1
0	1	0

Structuring element



What Is Dilation For?

Dilation can repair breaks



Dilation can repair intrusions



Watch out: Dilation enlarges objects

Compound Operations

More interesting morphological operations can be performed by performing combinations of erosions and dilations


The most widely used of these *compound* operations are:

- Opening
- Closing

Opening

The opening of image f by structuring element s, denoted $f \circ s$ is simply an erosion followed by a dilation

$$f \circ s = (f \ominus s) \oplus s$$



Note a disc shaped structuring element is used



Opening Example







Image After **Opening**





Opening Example






Closing

The closing of image f by structuring element s, denoted $f \cdot s$ is simply a dilation followed by an erosion

$$f \cdot s = (f \oplus s) \ominus s$$



Note a disc shaped structuring element is used



Closing Example

Original **I**mage






Image After Closing






Closing Example








Structuring Element

Morphological Processing Example





Morphological Algorithms

Using the simple technique we have looked at so far we can begin to consider some more interesting morphological algorithms

We will look at:

- Boundary extraction
- Region filling

There are lots of others as well though:


- Extraction of connected components
- Thinning/thickening
- Skeletonisation


Boundary Extraction


Extracting the boundary (or outline) of an object is often extremely useful


The boundary can be given simply as

$$\beta(A) = A - (A \ominus B)$$










Boundary Extraction Example


A simple image and the result of performing boundary extraction using a square 3*3 structuring element





Region Filling

Given a pixel inside a boundary, *region filling* attempts to fill that boundary with object pixels (1s)



Given a point inside here, can we fill the whole circle?



Region Filling (cont...)

The key equation for region filling is

$$X_{k} = (X_{k-1} \oplus B) \cap A^{c}$$
 $k = 1, 2, 3....$


Where X₀ is simply the starting point inside the boundary, B is a simple structuring element and A^c is the complement of A


This equation is applied repeatedly until X_k is equal to X_{k-1}

Finally the result is unioned with the original boundary




Region Filling Step By Step





Region Filling Example





Summary

The purpose of morphological processing is primarily to remove imperfections added during segmentation

The basic operations are erosion and dilation

Using the basic operations we can perform opening and closing

More advanced morphological operation can then be implemented using combinations of all of these

The End