

NAME : ATIF MALIK

ROLL NO : 2K23/CSM/23

Topic: PEAS Framework and Task Environment Analysis

Option A: An Automated Warehouse Sorting Robot

Task 1: PEAS Specification

The PEAS framework defines the operational parameters of an intelligent agent. The specification for a warehouse sorting robot is as follows:

- **Performance Measure:** To quantify the success of the agent's behavior, the following four metrics are monitored:
 - **Throughput Efficiency:** The average number of packages successfully retrieved, transported, and sorted into the correct outbound chute per hour.
 - **Sorting Accuracy Rate:** The percentage of total items successfully delivered to their target destination without being dropped or placed in an incorrect bin.
 - **Collision-Free Navigation Time:** The mean time (or distance traveled) between emergency stops, navigational deadlocks, or physical collisions with obstacles.
 - **Energy Utilization:** The ratio of operational battery life consumed per package processed, optimizing for the least amount of energy expended per successful sort.
- **Environment:** The warehouse environment dictates where the agent acts and the external factors it faces. The robot operates on a flat, structured concrete indoor warehouse floor. Key external factors include dynamic obstacles like other autonomous mobile robots (AMRs) and human warehouse staff, static infrastructure like storage racks and conveyor belts, and ambient variables such as varying overhead lighting and dust.
- **Actuators:** These are the physical tools the agent uses to interact with and change its world.
 - Brushless DC motors connected to differential drive wheels for navigating the warehouse floor and executing precise turns.
 - A multi-jointed robotic manipulator arm equipped with a pneumatic vacuum suction gripper for lifting packages of varying geometries.

- A motorized tilt-tray mounted on the robot chassis to slide packages into designated sorting bins.
- High-visibility directional LEDs and an audio speaker system to signal the robot's intended path and operational status to nearby human workers.
- **Sensors:** These inputs allow the agent to perceive its current state and environmental conditions.
 - A 360-degree 2D/3D LiDAR scanner mounted on the chassis for real-time obstacle detection and spatial mapping.
 - A high-resolution RGB-D (depth) camera array used to identify package barcodes, estimate object poses, and distinguish items from background clutter.
 - A downward-facing optical sensor designed to continuously read floor-embedded QR code matrices for absolute grid localization.
 - Incremental wheel encoders and inertial measurement units (IMUs) to calculate real-time odometry and dead-reckoning data.

Task 2: Environment Classification

This section classifies the robot's task environment across six dimensions, with exactly one-sentence justifications for each.

- **Fully Observable vs. Partially Observable:** The environment is **Partially Observable**. The robot's onboard optical and LiDAR sensors suffer from line-of-sight occlusion caused by tall storage racks and blind corners, meaning distant parts of the warehouse state remain hidden until approached.
- **Single-agent vs. Multi-agent:** The system operates in a **Multi-agent** environment. The robot must continuously coordinate its path planning and collision-avoidance strategies with dozens of other autonomous sorting robots and human staff sharing the same physical workspace.
- **Deterministic vs. Stochastic:** The environment is **Stochastic**. Physical uncertainties, such as wheel slippage on the concrete floor, unpredictable packaging materials causing suction failures, and the spontaneous movements of human workers, make state transitions probabilistic rather than guaranteed.
- **Episodicity vs. Sequential:** The task structure is **Sequential**. A pathing or battery-management decision made by the agent in the current time step directly dictates its future spatial coordinates and available operational energy in all subsequent steps.
- **Static vs. Dynamic:** The environment is highly **Dynamic**. The state of the warehouse constantly changes while the agent computes its next action, as other robots continue to move, inventory levels fluctuate, and human workers cross intersections.
- **Discrete vs. Continuous:** The operational space is **Continuous**. The robot must navigate through infinite continuous physical coordinates, managing analog variables such as motor acceleration profiles and steering angles over fluid time intervals.

Task 3: Critical Analysis

1. Greatest Technical Challenge Of the six environmental dimensions analyzed, the multi-agent aspect presents the most severe technical hurdle for AI engineers. Managing a dense fleet of autonomous robots requires solving highly complex multi-agent pathfinding (MAPF) problems under strict real-time constraints. If each agent plans its trajectory using isolated, single-agent logic, the warehouse will quickly succumb to localized traffic jams, intersection deadlocks, and severe throughput bottlenecks. The engineering difficulty lies in designing hybrid control architectures where decentralized local obstacle avoidance runs seamlessly alongside a centralized, global fleet-coordination algorithm, ensuring the entire swarm operates optimally without any single point of computational failure.

2. Utility Function and Trade-offs To handle the trade-off between operational speed and navigational safety, we can define a Utility Function $U(s, r)$ based on the agent's normalized velocity $s \in [0, 1]$ and its real-time collision risk factor $r \in [0, 1]$.

$$U(s, r) = (w_1 \cdot s) - (w_2 \cdot r)$$

Assuming initial weights are balanced at $w_1 = 0.6$ and $w_2 = 0.4$. If the weight of the safety parameter (w_2) is doubled to 0.8 , the agent's behavioral policy will drastically shift toward extreme caution. Rather than taking aggressive, high-speed trajectories through congested intersections to maximize sorting throughput, the robot will deliberately throttle its velocity, expand its safety-braking radius, and actively reroute through longer, lower-density aisles to ensure the collision risk remains as close to zero as possible.

Structured Representation

```
{
  "system_name": "Automated Warehouse Sorting Robot",
  "peas": {
    "performance_measures": [
      "throughput_efficiency_per_hour",
      "sorting_accuracy_rate",
      "collision_free_navigation_time",
      "energy_utilization_per_package"
    ],
    "environment": "Flat indoor warehouse floor containing dynamic obstacles (human workers, other robots), static infrastructure (racks, chutes), and ambient lighting/dust variables.",
    "actuators": [
      "brushless_dc_drive_motors",
      "pneumatic_vacuum_gripper",
      "motorized_tilt_tray",
      "directional_led_and_audio_alerts"
    ],
    "sensors": [
      "lidar_360_scanner",
      "rgb_d_depth_camera",
      "downward_facing_qr_sensor",
```

```

    "wheel_encoders_and_imu"
  ]
},
"environment_classification": {
  "observability": {
    "choice": "Partially Observable",
    "justification": "Onboard sensors suffer from line-of-sight occlusion caused by tall storage racks, keeping distant parts of the warehouse hidden."
  },
  "agents": {
    "choice": "Multi-agent",
    "justification": "The robot must continuously coordinate its path planning with dozens of other autonomous units and human staff sharing the workspace."
  },
  "determinism": {
    "choice": "Stochastic",
    "justification": "Physical uncertainties like wheel slippage and the spontaneous movements of human workers make state transitions probabilistic."
  },
  "episodicity": {
    "choice": "Sequential",
    "justification": "A pathing decision made in the current time step directly dictates future spatial coordinates and available operational energy."
  },
  "dynamism": {
    "choice": "Dynamic",
    "justification": "The state of the warehouse constantly changes while the agent computes its next action as other entities continue to move."
  },
  "continuity": {
    "choice": "Continuous",
    "justification": "The robot navigates through infinite physical coordinates while managing analog variables such as motor acceleration."
  }
},
"utility_function": "U(s, r) = (w1 * s) - (w2 * r)"
}

```