

Exercise 9: Facial Keypoints Detection

Keypoint Model

```
class KeypointModel(pl.LightningModule):
    """Facial keypoint detection model"""
    def __init__(self, hparams):
        super(KeypointModel, self).__init__()
        self.hparams = hparams
        #####
        # TODO #
        #####
        def conv_sandwich(inp, out, kernel_size, stride, pad):
            return nn.Sequential(
                nn.Conv2d(inp, out, kernel_size, stride, pad),
                nn.MaxPool2d(2, 2),
                nn.ReLU()
            )

        layers = []
        layers.append(conv_sandwich(1, 32, kernel_size=3, stride=1, pad=1))
        layers.append(conv_sandwich(32, 64, kernel_size=3, stride=1, pad=1))
        layers.append(conv_sandwich(64, 128, kernel_size=3, stride=1, pad=1))
        layers.append(conv_sandwich(128, 256, kernel_size=3, stride=1, pad=1))
        self.convs = nn.Sequential(*layers)

        self.fc1 = nn.Sequential(nn.Linear(256 * 6 * 6, 256), nn.ReLU())
        self.fc2 = nn.Sequential(nn.Linear(256, 30), nn.Tanh())

        #####
        #                               END OF YOUR CODE                               #
        #####
```

Tips:

- You can use `nn.Sequential` for stacking layers together in order to avoid writing this common block again.

- `nn.Sequential` doesn't take list as argument, so we need to decompose it by using the `*` operator.

Feature
extraction

Classification

Keypoint Model

```
def conv_sandwich(inp, out, kernel_size, stride, pad):  
    return nn.Sequential(  
        nn.Conv2d(inp, out, kernel_size, stride, pad),  
        nn.MaxPool2d(2, 2),  
        nn.ReLU()  
    )  
  
layers = []  
layers.append(conv_sandwich(1, 32, kernel_size=3, stride=1, pad=1))  
layers.append(conv_sandwich(32, 64, kernel_size=3, stride=1, pad=1))  
layers.append(conv_sandwich(64, 128, kernel_size=3, stride=1, pad=1))  
layers.append(conv_sandwich(128, 256, kernel_size=3, stride=1, pad=1))  
self.convs = nn.Sequential(*layers)
```

Feature
extraction

CONV2D

```
CLASS torch.nn.Conv2d(in_channels: int, out_channels: int, kernel_size: Union[T, Tuple[T,  
T]], stride: Union[T, Tuple[T, T]] = 1, padding: Union[T, Tuple[T, T]] = 0,  
dilation: Union[T, Tuple[T, T]] = 1, groups: int = 1, bias: bool = True,  
padding_mode: str = 'zeros')
```

[SOURCE]

For the first sandwich layer:

```
conv_sandwich(1, 32, kernel_size=3, stride=1, pad=1)
```

```
nn.Conv2d(inp, out, kernel_size, stride, pad),
```

after the conv2d:

the output size = $(width + 2 \cdot padding - kernel_size) / stride + 1$
 $= (96 + 2 \cdot 3) / 1 + 1 = 96$

```
nn.MaxPool2d(2, 2),
```

after maxpooling: $96 / 2 = 48$

output dimension: (32,48,48)

After 4 sandwich layers, the output dimension is (256,6,6)

Keypoint Model – forward

```
class KeypointModel(pl.LightningModule):
    """Facial keypoint detection model"""
    def forward(self, x):
        #####
        # TODO: Define the forward pass behavior of your model                #
        # for an input image x, forward(x) should return the                  #
        # corresponding predicted keypoints                                    #
        #####
        x = x.view(x.size(0), -1)
        x = self.fc1(x)
        x = self.fc2(x)
        #####
        #                               END OF YOUR CODE                       #
        #####
        return x
```

Remark:

Keep in mind that we need to reshape the output after applying the convolutional layers.

Training Loop

```
#####
# TODO - Train Your Model                                     #
#####

import torch.optim as optim
from torch import nn

batch_size = 20
n_epochs = 15

criterion = nn.MSELoss()
train_loader = DataLoader(
    train_dataset,
    batch_size=batch_size,
    shuffle=True,
    num_workers=0
)

optimizer = optim.SGD(
    model.parameters(),
    lr=0.01,
    momentum=0.9,
    weight_decay=1e-6,
    nesterov=True
)
```

```
model.train() # prepare net for training
running_loss = 0.0
for epoch in range(n_epochs):
    for i, data in enumerate(train_loader):
        image, keypoints = data['image'], data['keypoints']
        predicted_keypoints = model(image).view(-1,15,2)
        loss = criterion(
            torch.squeeze(keypoints),
            torch.squeeze(predicted_keypoints)
        )
        optimizer.zero_grad()
        loss.backward()
        optimizer.step()
        running_loss += loss.item()
    if i % 10 == 9: # print every 10 batches
        avg_loss = running_loss / (len(train_loader) * epoch + i)
        print(
            'Epoch: {}, Batch: {}, Avg. Loss: {}'.format(
                epoch + 1, i + 1, avg_loss
            )
        )
print('Finished Training')

#####
#                               END OF YOUR CODE                #
#####
```

- Load training data in batches and shuffle the data with PyTorch's DataLoader class.
- Train the model and track the loss

Hyperparameters tuning:

We have trained the model with different combination of hyperparameters, and the best Score we have achieved is 283. You can train with other hyperparameters and get better results!

```
layers.append(conv_sandwich(1, 32, kernel_size=3, stride=1, pad=1))
layers.append(conv_sandwich(32, 256, kernel_size=3, stride=1, pad=1))
layers.append(conv_sandwich(256, 128, kernel_size=3, stride=1, pad=1))
layers.append(conv_sandwich(128, 256, kernel_size=3, stride=1, pad=1))
self.convs = nn.Sequential(*layers)
self.fc1 = nn.Sequential(nn.Linear(256 * 6 * 6, 256), nn.ReLU())
self.fc2 = nn.Sequential(nn.Linear(256, 30), nn.Tanh())
```

weight decay	momentum	Learning rate	Score
1e-7	1.0	0.01	167.84
1e-7	0.9	0.01	163.06
1e-6	1.0	0.01	127.22
1e-6	0.9	0.01	156.90
1e-7	1.0	0.1	0.94
1e-7	0.9	0.1	251.66
1e-6	1.0	0.1	0.99
1e-6	0.9	0.1	121.56

I2DL: Prof. Niessner

```
layers.append(conv_sandwich(1, 32, kernel_size=3, stride=1, pad=1))
layers.append(conv_sandwich(32, 64, kernel_size=3, stride=1, pad=1))
layers.append(conv_sandwich(64, 128, kernel_size=3, stride=1, pad=1))
layers.append(conv_sandwich(128, 256, kernel_size=3, stride=1, pad=1))
self.convs = nn.Sequential(*layers)
self.fc1 = nn.Sequential(nn.Linear(256 * 6 * 6, 256), nn.ReLU())
self.fc2 = nn.Sequential(nn.Linear(256, 30), nn.Tanh())
```

weight decay	momentum	Learning rate	Score
1e-7	1.0	0.01	130.93
1e-7	0.9	0.01	160.91
1e-6	1.0	0.01	101.45
1e-6	0.9	0.01	160.06
1e-7	1.0	0.1	0.96
1e-7	0.9	0.1	259.32
1e-6	1.0	0.1	0.70
1e-6	0.9	0.1	283.31

Optional Exercise 9:

Spatial Batch Normalization

The forward pass

```
def spatial_batchnorm_forward(x, gamma, beta, bn_param):
    """
    ...
    """
    out, cache = None, None

    #####
    # TODO: Implement the forward pass for spatial batch normalization. #
    # #
    # HINT: You can implement spatial batch normalization using the #
    # vanilla version of batch normalization defined above. Your #
    # implementation should be very short; ours is less than five lines. #
    #####

    # Computation in one sweep by rearranging the dims to fit into
    # the batchnorm_forward framework
    x_swapped = np.transpose(x, (0, 2, 3, 1))
    x_swapped_reshaped = np.reshape(x_swapped, (-1, x_swapped.shape[-1]))

    out_temp, cache = batchnorm_forward(
        | x_swapped_reshaped, gamma, beta, bn_param)
    out = np.transpose(np.reshape(out_temp, x_swapped.shape), (0, 3, 1, 2))

    #####
    #                               END OF YOUR CODE                               #
    #####
    return out, cache
```

- Unlike the normal batchnorm which computes mean and variance of each feature, spatial batchnorm computes them of each channel.

- We only need to rearrange the dimensions of data and then use the normal batchnorm forward function here.

The backward pass

```
def spatial_batchnorm_backward(dout, cache):
    """
    """
    dx, dgamma, dbeta = None, None, None

    #####
    # TODO: Implement the backward pass for spatial batch normalization. #
    # #
    # HINT: You can implement spatial batch normalization using the #
    # vanilla version of batch normalization defined above. Your #
    # implementation should be very short; ours is less than five lines. #
    #####

    dout_swapped = np.transpose(dout, (0, 2, 3, 1))
    dout_swapped_reshaped = np.reshape(
        |    dout_swapped, (-1, dout_swapped.shape[-1]))

    dx_sr, dgamma, dbeta = batchnorm_backward(dout_swapped_reshaped, cache)

    dx = np.transpose(np.reshape(dx_sr, dout_swapped.shape), (0, 3, 1, 2))

    #####
    #                               END OF YOUR CODE                               #
    #####
    return dx, dgamma, dbeta
```

- Similar as the forward pass, in the backward pass we can compute the gradients by using the backprop from normal batchnorm with the rearranged dimensions.

Questions? Piazza 😊