

Possible Research Topics USRA 2025

Atishaya Maharjan

University of Manitoba
Geometric, Approximation, and Distributed Algorithms (GADA) lab

May 12, 2025

Possible Research Topics

- 1 Geometric Spanning Trees and Hypergraphs that Minimizes the Wiener Index
- 2 Inside-Out Dissection

Wiener Index in Graphs

- Let $G = (V, E)$ be a weighted undirected graph and let $\delta_G(u, v)$ denote the **shortest (minimum-weight) path** between vertices u and v in G .

Wiener Index in Graphs


- Let $G = (V, E)$ be a weighted undirected graph and let $\delta_G(u, v)$ denote the **shortest (minimum-weight) path** between vertices u and v in G .
- The Wiener index is defined as:

$$W(G) = \sum_{u,v \in V} \delta_G(u, v)$$

Wiener Index in Graphs

- Let $G = (V, E)$ be a weighted undirected graph and let $\delta_G(u, v)$ denote the **shortest (minimum-weight) path** between vertices u and v in G .
- The Wiener index is defined as:

$$W(G) = \sum_{u, v \in V} \delta_G(u, v)$$



Wiener Index in Network Design

- Given an undirected graph $G = (V, E)$ and a non-negative weight function $w : E \rightarrow \mathbb{R}^+$, the goal is to find a spanning tree T of G that minimizes the Wiener index.

Wiener Index in Network Design

- Given an undirected graph $G = (V, E)$ and a non-negative weight function $w : E \rightarrow \mathbb{R}^+$, the goal is to find a spanning tree T of G that minimizes the Wiener index.
- The **routing cost** $c(T)$ of a spanning tree T of G is:

$$c(T) = \sum_{u,v \in V} \delta_T(u, v)$$

Wiener Index in Network Design

- Given an undirected graph $G = (V, E)$ and a non-negative weight function $w : E \rightarrow \mathbb{R}^+$, the goal is to find a spanning tree T of G that minimizes the Wiener index.
- The **routing cost** $c(T)$ of a spanning tree T of G is:

$$c(T) = \sum_{u,v \in V} \delta_T(u, v)$$

The Minimum Routing Cost Spanning Tree (MRCST) problem

- Input: A graph $G = (V, E)$ with a non-negative weight function $w : E \rightarrow \mathbb{R}^+$.
- Output: A spanning tree T of G that minimizes the routing cost $c(T)$.

Wiener Index in Network Design

- Given an undirected graph $G = (V, E)$ and a non-negative weight function $w : E \rightarrow \mathbb{R}^+$, the goal is to find a spanning tree T of G that minimizes the Wiener index.
- The **routing cost** $c(T)$ of a spanning tree T of G is:

$$c(T) = \sum_{u,v \in V} \delta_T(u, v)$$

The Minimum Routing Cost Spanning Tree (MRCST) problem

- Input: A graph $G = (V, E)$ with a non-negative weight function $w : E \rightarrow \mathbb{R}^+$.
- Output: A spanning tree T of G that minimizes the routing cost $c(T)$.
- The MRCST problem is NP-Complete. There exists a PTAS for MRCST.

Problem Statement: Geometric Spanning Trees

Reference: WADS 2023 [Abu-Affash et al., 2023]

- ① Input: A set P of n points in the plane.

Problem Statement: Geometric Spanning Trees

Reference: WADS 2023 [Abu-Affash et al., 2023]

- ➊ Input: A set P of n points in the plane.
- ➋ Goal: Construct a **spanning tree** on P that minimizes the **Wiener index**.

Problem Statement: Geometric Spanning Trees

Reference: WADS 2023 [Abu-Affash et al., 2023]

- ➊ Input: A set P of n points in the plane.
- ➋ Goal: Construct a **spanning tree** on P that minimizes the **Wiener index**.
- ➌ The weight function is defined as the Euclidean distance between points.

Results Summary: Geometric Spanning Trees

- Spanning tree of P that minimizes the Wiener index is planar.

Results Summary: Geometric Spanning Trees

- Spanning tree of P that minimizes the Wiener index is planar.
- When P is in convex position, this can be solved in polynomial time.

Results Summary: Geometric Spanning Trees

- Spanning tree of P that minimizes the Wiener index is planar.
- When P is in convex position, this can be solved in polynomial time.
- The hamiltonian path of P that minimizes the Wiener index is not necessarily planar.

Results Summary: Geometric Spanning Trees

- Spanning tree of P that minimizes the Wiener index is planar.
- When P is in convex position, this can be solved in polynomial time.
- The hamiltonian path of P that minimizes the Wiener index is not necessarily planar.
- Computing such a hamiltonian path is NP-Hard.

Hypergraphs and their Wiener Index

Hypergraphs and their Wiener Index

Hypergraph

A **hypergraph** $H = (V, E)$ is a pair where V is a set of vertices and E is a set of hyperedges, each of which is a subset of V .

Hypergraphs and their Wiener Index

Hypergraph

A **hypergraph** $H = (V, E)$ is a pair where V is a set of vertices and E is a set of hyperedges, each of which is a subset of V .

Distance in Hypergraphs

The **distance** between two vertices u and v in a hypergraph H is defined as the minimum number of hyperedges in a chain connecting u and v .

- A **chain** is a sequence of hyperedges where each consecutive pair shares at least one vertex.
- The distance is denoted as $\delta_H(u, v)$.

Hypergraphs and their Wiener Index

Hypergraph

A **hypergraph** $H = (V, E)$ is a pair where V is a set of vertices and E is a set of hyperedges, each of which is a subset of V .

Distance in Hypergraphs

The **distance** between two vertices u and v in a hypergraph H is defined as the minimum number of hyperedges in a chain connecting u and v .

- A **chain** is a sequence of hyperedges where each consecutive pair shares at least one vertex.
- The distance is denoted as $\delta_H(u, v)$.

k-uniform hypergraph

A hypergraph is **k-uniform** if every hyperedge has cardinality k .

Wiener Index in Hypergraphs

Wiener Index in Hypergraphs

Wiener Index in Hypergraphs

The **Wiener index** of a hypergraph H is defined as:

$$W(H) = \sum_{u,v \in V} \delta_H(u,v)$$

Some facts about HyperGraphs

Some facts about HyperGraphs

- Finding a spanning tree of general hypergraphs is NP-Complete, while spanning tree of 3-uniform hypergraphs has a polynomial time algorithm using matroid matching.
[Goodall and de Mier, 2011]

Some facts about HyperGraphs

- Finding a spanning tree of general hypergraphs is NP-Complete, while spanning tree of 3-uniform hypergraphs has a polynomial time algorithm using matroid matching.
[Goodall and de Mier, 2011]
- Finding a spanning tree of a k -uniform 2-regular hypergraph is NP-Complete for any $k \geq 4$. [Demaine and Rudoy, 2018]

Proposed Open Work: Wiener Index in Hypergraphs

Proposed Open Work: Wiener Index in Hypergraphs

- Focus: Define and study the **Wiener index** in various classes of hypergraphs.

Proposed Open Work: Wiener Index in Hypergraphs

- Focus: Define and study the **Wiener index** in various classes of hypergraphs.
- Distance: Find a suitable weighted/unweighted distance metric for hypergraphs.

Proposed Open Work: Wiener Index in Hypergraphs

- Focus: Define and study the **Wiener index** in various classes of hypergraphs.
- Distance: Find a suitable weighted/unweighted distance metric for hypergraphs.
- Goal: Characterize structures that minimize/maximize the Wiener index.

Proposed Open Work: Wiener Index in Hypergraphs

- Focus: Define and study the **Wiener index** in various classes of hypergraphs.
- Distance: Find a suitable weighted/unweighted distance metric for hypergraphs.
- Goal: Characterize structures that minimize/maximize the Wiener index.

Side note: We could also explore **spatially embedded hypergraphs**, drawing inspiration from [Abu-Affash et al., 2023], and their Wiener index.

Problem Statement: Inside-Out Dissection

Reference: Open problem was mentioned in CCCG 2024.

[Akpanya et al., 2024] answered the open problem and raised some new questions.

Problem Statement: Inside-Out Dissection

Reference: Open problem was mentioned in CCCG 2024.

[Akpanya et al., 2024] answered the open problem and raised some new questions.

Inside-out dissection

Let P be a polygon (polyhedron). An **inside-out dissection** of P is a decomposition of P into finitely many polygons (polyhedra) P_1, \dots, P_k such that:

- P_1, \dots, P_k can be rearranged by only applying rotations and translations to form a polygon (polyhedron) P' that is congruent to P .
- The boundary of P' is composed of internal cuts of P .

Visualizing the Problem

Chalk and Talk

Recent Work Summary

Recent Work Summary

- General n -gon: inside-out dissection possible with at most $2n + 1$ pieces.

Recent Work Summary

- General n -gon: inside-out dissection possible with at most $2n + 1$ pieces.
- Regular polygons (e.g., equilateral triangle, square, regular pentagon): at most 6 pieces suffice.

Recent Work Summary

- General n -gon: inside-out dissection possible with at most $2n + 1$ pieces.
- Regular polygons (e.g., equilateral triangle, square, regular pentagon): at most 6 pieces suffice.
- Extension to 3D:
 - If a polyhedron can be tiled with regular tetrahedra and octahedra, it can be inside-out dissected.

Recent Work Summary

- General n -gon: inside-out dissection possible with at most $2n + 1$ pieces.
- Regular polygons (e.g., equilateral triangle, square, regular pentagon): at most 6 pieces suffice.
- Extension to 3D:
 - If a polyhedron can be tiled with regular tetrahedra and octahedra, it can be inside-out dissected.
- Tools used include symmetry arguments and constructive dissections.

Open Work Presented in the Main Reference

Open Work Presented in the Main Reference





- Can a triangle be inside-out dissected with 3 pieces?

Open Work Presented in the Main Reference

- Can a triangle be inside-out dissected with 3 pieces?
- Can general n -gons be inside-out dissected with lesser than $2n + 1$ pieces? Maybe convex polygons can be done with constant pieces like regular polygons?

Open Work Presented in the Main Reference

- Can a triangle be inside-out dissected with 3 pieces?
- Can general n -gons be inside-out dissected with lesser than $2n + 1$ pieces? Maybe convex polygons can be done with constant pieces like regular polygons?
- They have a method of general polyhedra, but the number of pieces required is quite large. Therefore, an efficient method for inside-out dissections of polyhedra is still open.

-  Abu-Affash, A. K., Carmi, P., Luwisch, O., and Mitchell, J. S. B. (2023).
Geometric spanning trees minimizing the wiener index.
-  Akpanya, R., Rivkin, A., and Stock, F. (2024).
On inside-out dissections of polygons and polyhedra.
-  Demaine, E. D. and Rudoy, M. (2018).
Tree-residue vertex-breaking: a new tool for proving hardness.
-  Goodall, A. and de Mier, A. (2011).
Spanning trees of 3-uniform hypergraphs.
Advances in Applied Mathematics, 47(4):840–868.

The end.
maharjaa@umanitoba.ca