AgriHGT: A Heterogeneous Graph Transformer for Cross-Crop and Cross-Disease Plant Leaf Diagnosis

I. Introduction

Plant diseases remain one of the most persistent threats to global food security, causing substantial reductions in crop yield, produce quality, and farm income in every growing season. Smallholder farmers, who produce a large share of food in regions such as South Asia, often lack timely access to trained plant pathologists, which makes automated disease diagnosis from leaf images an attractive substitute for manual field inspection. Over the past decade, the combination of large public leaf-image repositories such as PlantVillage with the rapid progress of deep learning has produced disease-classification systems that approach near-perfect accuracy under controlled conditions.

Early systems relied on convolutional neural networks (CNNs) trained directly on leaf images, in some cases paired with classical image-processing pipelines for pre-processing or severity estimation [Srivastava et al.(2021)Srivastava, Mishra, Awasthi, Sahu, and Pal]. Deeper CNN architectures such as AlexNet, GoogLeNet, and VGG variants subsequently pushed PlantVillage classification accuracy above 99%, once sufficient labelled data and model capacity were available [Ferentinos(2018)]. More recently, Vision Transformers (ViTs) have been adopted to exploit global self-attention rather than the local receptive fields used by convolution, yielding further accuracy gains and improved robustness to symptom variability [Murugavalli and Gopi(2025)], [Boukabouya et al.(2022)Boukabouya, Moussaoui, and Berrimi]. Swin-style hierarchical transformers have likewise been adapted for harder, field-collected datasets such as PlantDoc [Liu and Zhang(2025)], and graph neural networks (GNNs) have begun to appear as a way of modelling structural relationships within a single leaf image [Ananthajothi and Lokesh(2026)], [Elumalai et al.(2026)Elumalai, Annamalai, and M]. Most recently, heterogeneous ensembles that combine segmentation networks with hybrid convolution-transformer classifiers and metaheuristic fusion weighting have pushed PlantVillage accuracy to 99.31% [Kalpana et al.(2025)Kalpana, Gera, Alabdulkreem, Quasim, Baili, Cho, and Nam].

Despite this progress, a closer reading of the literature reveals a consistent architectural gap. Almost without exception, existing systems – whether CNN-, ViT-, Swin-, or GNN-based – treat every leaf image as an isolated classification instance. A model that has learned to recognise one disease on one crop gains no structured benefit from also having seen a visually or pathologically related disease on a different host plant, even though such relationships are common in practice. The GNN-based studies that do exist construct graphs only at the image level, connecting diseased and healthy regions within a single leaf, or restrict themselves to one or two plant species [Ananthajothi and Lokesh(2026)], [Elumalai et al.(2026)Elumalai, Annamalai, and M]; and the most accurate heterogeneous ensemble achieves its gains through multi-stage segmentation and metaheuristic optimisation rather than through any explicit reasoning about how crops and diseases relate to one another [Kalpana et al.(2025)Kalpana, Gera, Alabdulkreem, Quasim, Baili, Cho, and Nam]. In short, the field has optimised heavily for within-image accuracy while leaving cross-crop and cross-disease relational knowledge almost entirely unexploited.

This paper addresses that gap by proposing AgriHGT, a Heterogeneous Graph Transformer that explicitly represents crops, diseases, and image-derived visual features as distinct node types connected through a single heterogeneous graph. Our architecture builds on the Heterogeneous Graph Transformer (HGT) framework of Hu et al. [Hu et al.(2020)Hu, Dong, Wang, and Sun], originally proposed for Web-scale heterogeneous information networks such as academic citation graphs, which introduced node- and edge-type dependent attention parameters so that heterogeneous mutual attention, message passing, and aggregation could each be computed with respect to the meta relation of a given edge rather than a single shared weight matrix. We adapt this node- and edge-type dependent attention mechanism to the agricultural domain, where crop, disease, and image-feature nodes play the role that paper, author, venue, and field nodes play in the original academic graph setting. By learning attention-weighted message passing across crop–disease–image relations, AgriHGT is designed to transfer knowledge between related diseases across entirely different plant species – for example Tomato, Papaya, Zucchini, and Bottle Gourd – without requiring the multi-stage segmentation, dual classification branches, or optimisation overhead used in prior heterogeneous ensembles [Kalpana et al.(2025)Kalpana, Gera, Alabdulkreem, Quasim, Baili, Cho, and Nam]. The remainder of this paper is organised as follows. Section II reviews related work in CNN-, transformer-, and graph-based plant disease detection in greater detail and positions AgriHGT relative to each line of work; the sections that follow describe the proposed methodology, experimental setup, and results.

II. Related Work

A. CNN-Based Plant Disease Detection

Convolutional neural networks were the first deep architectures to deliver strong results on image-based plant disease classification and remain a common baseline today. Srivastava et al. [Srivastava et al.(2021)Srivastava, Mishra,

Awasthi, Sahu, and Pal] combined a CNN classifier with a classical image-processing pipeline on the PlantVillage dataset, reporting 94.87% accuracy, with deployment on IoT devices and drones as the motivating use case. Ferentinos [Ferentinos(2018)] trained several CNN architectures, including AlexNet, GoogLeNet, and VGG variants, on a substantially larger collection of PlantVillage images spanning dozens of plant-disease combinations, achieving 99.53% accuracy on previously unseen test images. Both studies, however, frame disease recognition purely as single-image classification: each leaf is scored independently of every other crop or disease class, so a model that has learned the visual signature of one disease gains no structured benefit from having also seen a related disease on a different host plant, and neither approach generalises naturally beyond the specific crops present in its training data.

B. Vision Transformer and Swin Transformer-Based Approaches

To capture longer-range visual dependencies than the local receptive fields of CNNs allow, several recent works have turned to Vision Transformers (ViTs). Murugavalli and Gopi [Murugavalli and Gopi(2025)] proposed PLA-ViT, a Precision Leaf Analysis Vision Transformer that combines patch-based self-attention with data augmentation and adaptive learning-rate scheduling, reporting 94.2% accuracy together with favourable inference time and parameter efficiency on PlantVillage. Boukabouya et al. [Boukabouya et al.(2022)Boukabouya, Moussaoui, and Berrimi] compared several ViT configurations on a PlantVillage-derived tomato-disease subset and reported top accuracies as high as 99.7%, confirming that self-attention-based architectures can match or exceed CNN performance on controlled datasets. Working on the more challenging, field-collected PlantDoc dataset, Liu and Zhang [Liu and Zhang(2025)] introduced an Efficient Swin Transformer with a Selective Token Generator and a Feature Fusion Aggregator, reducing parameter count by roughly 20.89% relative to standard Swin-T while achieving 80.14% precision and 76.27% recall under realistic, cluttered backgrounds. Parez et al. [Parez et al.(2023)Parez, Dilshad, Alghamdi, Alanazi, and Lee] proposed GreenViT, a fine-tuned Vision Transformer that segments leaf images into sequential patches rather than relying on convolutional pooling, and reported 100%, 98%, and 99% accuracy on the PlantVillage, Data Repository of Leaf Images, and a merged Plant Composite dataset, respectively, outperforming several pretrained CNN baselines. Shandilya et al. [Shandilya et al.(2025)Shandilya, Gupta, Mohamed, Bharany, Rehman, and Hussen] combined a CNN branch for fine-grained local features with a ViT branch for long-range contextual dependencies in a hybrid CNN-ViT architecture for maize leaf disease classification, reporting 99.15% accuracy on a combined Kaggle-Mendeley dataset and 95.93% on an independent corn disease-and-severity dataset. Singha Roy and Kukreja [Roy and Kukreja(2025)] trained a ViT with a shared backbone to jointly classify rice leaf disease type and severity level on a custom 3,345-image dataset, achieving a 54.17% weighted-F1 for disease classification and a substantially higher 77.94% weighted-F1 for severity estimation. While these transformer-based methods improve global feature extraction within a single image, none of them model relationships across different crops, diseases, or symptom types; PLA-ViT and the ViT comparison study, in particular, remain confined to the PlantVillage benchmark and a single crop (tomato), respectively, and even the more recent GreenViT, maize CNN-ViT, and rice ViT studies treat every leaf image as an isolated prediction target, with no relational or graph-based reasoning component and no mechanism for transferring symptom knowledge between crops.

C. Graph Neural Network-Based Approaches

A smaller body of work has begun to apply graph neural networks (GNNs) to plant disease imagery, but so far only at the level of structure within a single leaf or a single crop. Ananthajothi and Lokesh [Ananthajothi and Lokesh(2026)] construct image-level graphs that connect diseased and healthy leaf regions, with nodes representing leaf parts and edges representing their structural associations, to detect apple scab, cercospora leaf spot, late blight, and powdery mildew on a custom plant image dataset. Elumalai et al. [Elumalai et al.(2026)Elumalai, Annamalai, and M] proposed an Attention-Enhanced GNN (AE-GNN) that similarly models leaf images as graphs of discriminative regions, applying an attention-weighting step to refocus on disease-relevant nodes before classifying fifteen fungal diseases (plus healthy classes) on a curated half-spinach and curry-leaf dataset, and reporting that AE-GNN outperforms both CNN and other graph-based baselines. Bera et al. [Bera et al.(2024)Bera, Bhattacharjee, and Krejcar] proposed PND-Net, which adds a graph convolutional network on top of a backbone CNN, using region-based and spatial-pyramid pooling to build node features for plant nutrition-deficiency and disease classification, reporting accuracies between 84.30% (PlantDoc) and 96.18% (potato disease) across four datasets. Bajpai et al. [Bajpai et al.(2024)Bajpai, Pal, Sahu, and Srivastava] fused a GNN branch with a ResNet18 branch for potato leaf disease detection, while Maheswara Rao et al. [Rao et al.(2024)Rao, Sreekala, Rao, Shirisha, Srinivas, and Sreedevi] integrated a CNN with a GCN across 31 disease classes spanning eight crops, in both cases combining visual and graph-structured features within a single crop family rather than across distinct host plants. Surekha and Subha Mastan Rao [Surekha and Rao(2026)] proposed AdjLeafGNN, which pairs an enhanced CNN (LDDNet) with a GNN to additionally predict the probability of disease spreading between physically adjacent leaves, reporting 98.88% classification accuracy and a 98.71% F1-score on a PlantVillage subset. All of these graph-based approaches demonstrate that relational reasoning can usefully model structure that CNNs and ViTs do not explicitly capture, but their graphs remain homogeneous, image-internal, or restricted to a single crop or a narrow set of one or two species: they provide no mechanism for transferring knowledge between unrelated crops or disease categories.

D. Knowledge-Graph and Hybrid Symbolic-Connectionist Approaches

A parallel line of work has explored knowledge graphs as a way of organising agricultural disease information, though typically from text or alongside, rather than in place of, image-based classification. Li et al. [Li et al.(2025)Li, Yang, Liang, Chen, and Dong] proposed MARBC, a RoBERTa-BiLSTM-CRF model with multi-head attention, to extract entities and relations from a multi-source Chinese rice-disease-and-pest text corpus and construct a heterogeneous knowledge graph, reporting 94.44% F1 on entity-relation extraction. Zhao et al. [Zhao et al.(2024)Zhao, Chen, Ji, Wang, Yan, Zhang, Liu, Ye, and Lv] combined large language models, an agricultural knowledge graph, and a graph attention network for disease detection in a single crop (*Elaeagnus angustifolia*), reporting 93% accuracy and showing that graph-attention-based fusion outperformed several alternative loss formulations. Lin et al. [Lin et al.(2023)Lin, Xiu, Kong, Yang, and Zhao] took a different, purely visual route with GPA-Net, a graph pyramid attention CNN that learns multiscale spatial and graphic relations for fine-grained pest and disease identification, reporting up to 99.0%, 97.0%, and 56.9% accuracy on the cassava-leaf, AI Challenger, and IP102 pest benchmarks, respectively. These studies confirm that graph-structured representations of agricultural knowledge are useful for both textual and visual reasoning, but each remains confined to a single crop or to text-derived entities rather than to image-derived crop, disease, and symptom nodes spanning multiple unrelated host plants.

E. Heterogeneous Ensemble and Hybrid Transformer Approaches

The strongest reported accuracy among the reviewed studies comes from a two-stage heterogeneous ensemble. Kalpana et al. [Kalpana et al.(2025)Kalpana, Gera, Alabdulkreem, Quasim, Baili, Cho, and Nam] first use U-Net and Swin Transformer V2 to segment diseased leaf regions, then classify the segmented regions using CoAtNet and an enhanced CoAtNet variant, before fusing the predictions of all branches with weights tuned by a Levy Flight Honey Badger Algorithm (LFHBA). On PlantVillage, this pipeline reaches 99.31% accuracy with 99.32% precision and 99.31% F1-score. The result illustrates how far single-image classification accuracy can be pushed with sufficient architectural and optimisation complexity, but it also illustrates the cost of that approach: the pipeline requires a dedicated segmentation stage, two parallel classification branches, and a metaheuristic fusion step, none of which provide any explicit, queryable representation of how the diseases of one crop relate to those of another.

F. Summary and Research Gap

Two patterns emerge consistently across model families, namely CNN, ViT, Swin, GNN, knowledge-graph, and heterogeneous ensemble alike. First, every reviewed method treats disease classification as an independent, per-image (or, for the knowledge-graph studies, per-crop) decision; none constructs an explicit representation of how diseases relate to one another across crops. Second, where relational structure is modelled at all, as in the GNN- and knowledge-graph-based studies [Ananthajothi and Lokesh(2026)], [Elumalai et al.(2026)Elumalai, Annamalai, and M], [Bera et al.(2024)Bera, Bhattacharjee, and Krejcar], [Bajpai et al.(2024)Bajpai, Pal, Sahu, and Srivastava], [Rao et al.(2024)Rao, Sreekala, Rao, Shirisha, Srinivas, and Sreedevi], [Surekha and Rao(2026)], [Li et al.(2025)Li, Yang, Liang, Chen, and Dong], [Zhao et al.(2024)Zhao, Chen, Ji, Wang, Yan, Zhang, Liu, Ye, and Lv], [Lin et al.(2023)Lin, Xiu, Kong, Yang, and Zhao], it is confined to the interior of a single image, a single crop, or a narrow set of one or two species, rather than spanning the heterogeneous space of crops, diseases, and symptoms that a real agricultural deployment must handle. Pushing single-image accuracy still higher, as the heterogeneous ensemble of Kalpana et al. [Kalpana et al.(2025)Kalpana, Gera, Alabdulkreem, Quasim, Baili, Cho, and Nam] does, or pushing global visual attention further, as GreenViT, the maize CNN-ViT model, and the rice severity-estimation ViT do [Parez et al.(2023)Parez, Dilshad, Alghamdi, Alanazi, and Lee], [Shandilya et al.(2025)Shandilya, Gupta, Mohamed, Bharany, Rehman, and Hussen], [Roy and Kukreja(2025)], comes at the price of substantial architectural and optimisation overhead, without addressing this relational gap at all. AgriHGT is designed to close this gap directly: rather than adding another image-classification branch, it represents crops, diseases, and image-derived features as distinct heterogeneous graph node types and uses a Heterogeneous Graph Transformer to learn attention-weighted relations between them, enabling knowledge transfer across related diseases on entirely different host plants (for example Tomato, Papaya, Zucchini, and Bottle Gourd) within a single, end-to-end model.

REFERENCES

[Ananthajothi and Lokesh(2026)] K. Ananthajothi and K. Lokesh. Graph neural networks for smarter plant disease diagnosis and classification. In *2026 International Conference on Intelligent and Innovative Technologies in Computing, Electrical and Electronics (IITCEE)*, Bangalore, India, 2026. doi:10.1109/IITCEE67948.2026.11394113.

[Bajpai et al.(2024)Bajpai, Pal, Sahu, and Srivastava] Abhishek Bajpai, Yash Pal, Sristi Sahu, and Vidushi Srivastava. Enhanced potato leaf disease detection through multi-modal fusion of graph neural networks and resnet18. In *2024 IEEE 16th International Conference on Computational Intelligence and Communication Networks (CICN)*, pages 1498–1504, 2024. doi:10.1109/CICN63059.2024.10847571.

[Bera et al.(2024)Bera, Bhattacharjee, and Krejcar] Asish Bera, Debotosh Bhattacharjee, and Ondrej Krejcar. Pnd-net: Plant nutrition deficiency and disease classification using graph convolutional network. *Scientific Reports*, 14:15537, 2024. doi:10.1038/s41598-024-66543-7.

[Boukabouya et al.(2022)Boukabouya, Moussaoui, and Berrimi] R. A. Boukabouya, A. Moussaoui, and M. Berrimi. Vision transformer based models for plant disease detection and diagnosis. In *Proceedings of the 5th International Symposium on Informatics and Its Applications (ISIA)*, pages 1–6, 2022. doi:10.1109/ISIA.2022.9923797.

[Elumalai et al.(2026)Elumalai, Annamalai, and M] Meganathan Elumalai, Mohan Annamalai, and Devika M. Attention-enhanced gnn model for fungal disease classification in spinach leaves using monospectral imaging. *Scientific Reports*, 2026. doi:10.1038/s41598-026-54574-1. Published online ahead of issue/volume assignment.

[Ferentinos(2018)] Konstantinos P. Ferentinos. Deep learning models for plant disease detection and diagnosis. *Computers and Electronics in Agriculture*, 145:311–318, 2018. doi:10.1016/j.compag.2018.01.009.

[Hu et al.(2020)Hu, Dong, Wang, and Sun] Ziniu Hu, Yuxiao Dong, Kuansan Wang, and Yizhou Sun. Heterogeneous graph transformer. In *Proceedings of The Web Conference 2020 (WWW '20)*, pages 2704–2710, Taipei, Taiwan, 2020. ACM. doi:10.1145/3366423.3380027.

[Kalpana et al.(2025)Kalpana, Gera, Alabdulkreem, Quasim, Baili, Cho, and Nam] P. Kalpana, P. Gera, E. Alabdulkreem, M. T. Quasim, J. Baili, Y. Cho, and Y. Nam. An ensemble heterogeneous transformer model for an effective diagnosis of multiple plant diseases. *Frontiers in Plant Science*, 16:1693095, 2025. doi:10.3389/fpls.2025.1693095.

[Li et al.(2025)Li, Yang, Liang, Chen, and Dong] Chunchun Li, Siyi Yang, Dong Liang, Peng Chen, and Wei Dong. Construction of a multi-source, heterogeneous rice disease and pest knowledge graph based on the marbc model. *Agronomy*, 15(3):566, 2025. doi:10.3390/agronomy15030566.

[Lin et al.(2023)Lin, Xiu, Kong, Yang, and Zhao] Sen Lin, Yucheng Xiu, Jianlei Kong, Chengcai Yang, and Chunjiang Zhao. An effective pyramid neural network based on graph-related attentions structure for fine-grained disease and pest identification in intelligent agriculture. *Agriculture*, 13(3):567, 2023. doi:10.3390/agriculture13030567.

[Liu and Zhang(2025)] W. Liu and A. Zhang. Plant disease detection algorithm based on efficient swin transformer. *Computers, Materials & Continua*, 82(2):3045–3068, 2025. doi:10.32604/cmc.2024.058640.

[Murugavalli and Gopi(2025)] S. Murugavalli and R. Gopi. Plant leaf disease detection using vision transformers for precision agriculture. *Scientific Reports*, 15:22361, 2025. doi:10.1038/s41598-025-05102-0.

[Parez et al.(2023)Parez, Dilshad, Alghamdi, Alanazi, and Lee] S. Parez, N. Dilshad, N. S. Alghamdi, T. M. Alanazi, and J. W. Lee. Visual intelligence in precision agriculture: Exploring plant disease detection via efficient vision transformers. *Sensors*, 23(15):6949, 2023. doi:10.3390/s23156949.

[Rao et al.(2024)Rao, Sreekala, Rao, Shirisha, Srinivas, and Sreedevi] Saka Uma Maheswara Rao, Keshetti Sreekala, Pulluri Srinivas Rao, Nalla Shirisha, Gunnam Srinivas, and Erry Sreedevi. Plant disease classification using novel integration of deep learning cnn and graph convolutional networks. *Indonesian Journal of Electrical Engineering and Computer Science*, 36(3):1721–1730, 2024. doi:10.11591/ijeecs.v36.i3.pp1721-1730.

[Roy and Kukreja(2025)] Pritha Singha Roy and Vinay Kukreja. Vision transformers for rice leaf disease detection and severity estimation: A precision agriculture approach. *Journal of the Saudi Society of Agricultural Sciences*, 24:3, 2025. doi:10.1007/s44447-025-00007-w.

[Shandilya et al.(2025)Shandilya, Gupta, Mohamed, Bharany, Rehman, and Hussen] Gunjan Shandilya, Sheifali Gupta, Heba G. Mohamed, Salil Bharany, Ateeq Ur Rehman, and Seada Hussen. Enhanced maize leaf disease detection and classification using an integrated cnn-vit model. *Food Science & Nutrition*, 13(7):e70513, 2025. doi:10.1002/fsn3.70513.

[Srivastava et al.(2021)Srivastava, Mishra, Awasthi, Sahu, and Pal] P. Srivastava, K. Mishra, V. Awasthi, V. K. Sahu, and P. K. Pal. Plant disease detection using convolutional neural network. In *Proceedings of the 2021 IEEE Bombay Section Signature Conference (IBSSC)*, pages 1–6, Mumbai, India, 2021. doi:10.1109/IBSSC53889.2021.9673493.

[Surekha and Rao(2026)] B. Surekha and T. Subha Mastan Rao. Adjleafgnn: A hybrid deep learning and graph neural network framework for probabilistic modeling of adjacent leaf disease spread in precision agriculture. *Scientific Reports*, 2026. doi:10.1038/s41598-026-45061-8. Published online ahead of issue/volume assignment.

[Zhao et al.(2024)Zhao, Chen, Ji, Wang, Yan, Zhang, Liu, Ye, and Lv] Xinyan Zhao, Baiyan Chen, Mengxue Ji, Xinyue Wang, Yuhan Yan, Jinming Zhang, Shiyingjie Liu, Muyang Ye, and Chunli Lv. Implementation of large language models and agricultural knowledge graphs for efficient plant disease detection. *Agriculture*, 14(8):1359, 2024. doi:10.3390/agriculture14081359.