
DUAL-IN-LINE SO

SERIES 299 • RIGHT ANGLE MOUNT • CLOSED FRAME



- Ideal for mounting components, such as LED displays, where the face must be parallel to the PCB surface
- Sockets have solder tail termination and are available with either .300" (standard) or .100" row spacing
- Series 299 uses MM #1103/0903, #1103/1610 or #1103/0904 pins. See pages 166 & 167 for details
- Hi-Rel, 4-finger BeCu #30 contact is rated at 3 amps. See page 253 for details
- Insulators are high temperature thermoplastic, suitable for all soldering operations
- For Electrical, Mechanical and Environmental Data, see page 264 for details



Total number of pins	B 000 000 1			Quantity per tube	ORDERING INFORMATION					
Tota	Α	В	C	Qq	E=.100		E = .300			
6 8 10 12 14 16 18 20 24 8 10 12 14 16 18 20 22 24 26 28 30 32 36 40	0.3 0.4 0.5 0.6 0.7 0.8 0.9 1.0 1.2 0.4 0.5 0.6 0.7 0.8 0.9 1.0 1.1 1.2 1.3 1.4 1.5 1.6 1.8 2.0	0.3 0.3 0.3 0.3 0.3 0.3 0.3 0.6 0.6 0.6 0.6 0.6 0.6 0.6 0.6	0.4 0.4 0.4 0.4 0.4 0.4 0.4 0.7 0.7 0.7 0.7 0.7 0.7 0.7 0.7	33 29 25 22 20 16 50 40 34 28 25 22 20 18 16 15 14 13 12 11	299-XX-306-11-001000 299-XX-308-11-001000 299-XX-310-11-001000 299-XX-312-11-001000 299-XX-314-11-001000 299-XX-316-11-001000 299-XX-320-11-001000 299-XX-324-11-001000	* 299 * 299 * 299 * 299 * 299 * 299 299 299 299 299 299 299 299 299 299	9-XX-306-10-00 9-XX-310-10-00 9-XX-312-10-00 9-XX-314-10-00 9-XX-316-10-00 9-XX-318-10-00 9-XX-320-10-00 9-XX-324-10-00 9-XX-608-10-00 9-XX-610-10-00 9-XX-614-10-00 9-XX-614-10-00 9-XX-620-10-00 9-XX-620-10-00 9-XX-620-10-00 9-XX-620-10-00 9-XX-620-10-00 9-XX-630-10-00 9-XX-630-10-00 9-XX-630-10-00 9-XX-630-10-00 9-XX-630-10-00 9-XX-630-10-00 9-XX-640-10-00	01000 01000 01000 01000 01000 01000 01000 01000 01000 01000 01000 02000 02000 02000 02000 02000 02000 02000 02000 02000 02000	RoHS-2011/65/N	EU
						* Not available in tubes				Code
SPECIFY PLATING CODE XX =				XX =		93			43 🔷	
Sleeve (Pin)					200) μ" Sn/Pb			200 μ″ Sn	
Contact (Clip)					3	30 μ" Au			30 μ" Au	

