

RaceDay API Endpoint Plan

Part B — Endpoint Specification with Example Data

1. Users Entity

Method	Route	Description	Role Required	Request Body / Example Data	Expected Response
POST	/api/auth/register	Creates a new RaceDay user account.	None (Public)	{ "email": "john@gmail.com", "password": "Password123!", "role": "Participant" }	201 Created – { "userId": 1, "email": "john@gmail.com", "role": "Participant" } 400 – invalid data. 409 – email already exists.
POST	/api/auth/login	Authenticates a user and returns an access token.	None (Public)	{ "email": "john@gmail.com", "password": "Password123!" }	200 OK – { "token": "...", "userId": 1, "role": "Participant" } 401 – invalid credentials.
GET	/api/users	Returns all registered users.	Admin	None	200 OK – list of users. 403 – insufficient permissions.
GET	/api/users/{id}	Returns a specific user's account details.	Admin	None	200 OK – { "userId": 1, "email": "john@gmail.com", "role": "Participant" } 404 – user not found.
PUT	/api/users/{id}	Updates a user's email or role.	Admin	{ "email": "john.new@gmail.com", "role": "Participant" }	200 OK – updated user. 404 – user not found.
DELETE	/api/users/{id}	Deletes a user account.	Admin	None	204 No Content – user deleted. 404 – user not found.

2. Profiles Entity

Method	Route	Description	Role Required	Request Body / Example Data	Expected Response
GET	/api/profiles/me	Returns the profile of the logged-in user.	Any (Logged in)	None	200 OK – { "profileId": 1, "userId": 1, "firstName": "John", "lastName": "Mokoena", "phone": "0821234567", "location": "Johannesburg" }
PUT	/api/profiles/me	Creates or updates the logged-in user's profile.	Any (Logged in)	{ "firstName": "John", "lastName": "Mokoena", "phone": "0821234567", "location": "Johannesburg" }	200 OK – updated profile. 400 – invalid information.
GET	/api/profiles/{id}	Returns a specific user's profile.	Admin	None	200 OK – profile details.

Method	Route	Description	Role Required	Request Body / Example Data	Expected Response
					404 – profile not found.

3. Categories Entity

Method	Route	Description	Role Required	Request Body / Example Data	Expected Response
GET	/api/categories	Returns all available RaceDay event categories.	None (Public)	None	200 OK – [{ "categoryId": 1, "name": "Running", "description": "Road running events" }]
GET	/api/categories/{id}	Returns details of a specific category.	None (Public)	None	200 OK – { "categoryId": 1, "name": "Running", "description": "Road running events" } 404 – category not found.
POST	/api/categories	Creates a new event category.	Organiser	{ "name": "Cycling", "description": "Road cycling events" }	201 Created – category created. 409 – category already exists.
PUT	/api/categories/{id}	Updates an existing category.	Organiser	{ "name": "Walking", "description": "Community walking events" }	200 OK – updated category. 404 – category not found.
DELETE	/api/categories/{id}	Deletes an event category.	Organiser	None	204 No Content – category deleted. 404 – category not found.

4. Events Entity

Method	Route	Description	Role Required	Request Body / Example Data	Expected Response
GET	/api/events	Returns upcoming running, walking and cycling events.	None (Public)	None	200 OK – list of upcoming events.
GET	/api/events/{id}	Returns details of a specific event.	None (Public)	None	200 OK – event details. 404 – event not found.
POST	/api/events	Creates a new RaceDay event.	Organiser	{ "organizerId": 2, "categoryId": 1, "name": "Cape Town 10K", "description": "Annual road running event", "eventType": "Road Run", "eventDate": "2026-10-18T07:00:00", "location": "Cape Town", "entryFee": 250.00, "status": "Open" }	201 Created – event created with eventId. 400 – invalid data.

Method	Route	Description	Role Required	Request Body / Example Data	Expected Response
PUT	/api/events/{id}	Updates an existing event.	Organiser	{ "categoryId": 1, "name": "Cape Town 10K", "description": "Updated road running event", "eventType": "Road Run", "eventDate": "2026-10-18T07:00:00", "location": "Cape Town", "entryFee": 275.00, "status": "Open" }	200 OK – updated event. 404 – event not found.
DELETE	/api/events/{id}	Deletes or cancels an event.	Organiser	None	204 No Content – event deleted/cancelled. 404 – event not found.

5. EventEnrolments Entity

Method	Route	Description	Role Required	Request Body / Example Data	Expected Response
GET	/api/events/{eventId}/enrolments	Returns all participants enrolled in an event.	Organiser	None	200 OK – list of participants enrolled in the event.
POST	/api/events/{eventId}/enrolments	Registers the logged-in participant for an event.	Participant	{}	201 Created – { "enrolmentId": 1, "eventId": 1, "participantId": 1, "status": "Registered", "bibNumber": null } 409 – participant already enrolled.
GET	/api/enrolments/me	Returns all events entered by the logged-in participant.	Participant	None	200 OK – list of the participant's enrolments.
GET	/api/enrolments/{id}	Returns details of a specific enrolment.	Participant / Organiser	None	200 OK – enrolment details. 404 – enrolment not found.
PUT	/api/enrolments/{id}	Updates enrolment status or bib number.	Organiser	{ "status": "Confirmed", "bibNumber": "A1025" }	200 OK – updated enrolment. 404 – enrolment not found.
DELETE	/api/enrolments/{id}	Withdraws a participant from an event.	Participant	None	204 No Content – enrolment removed. 404 – enrolment not found.

6. Results Entity

Method	Route	Description	Role Required	Request Body / Example Data	Expected Response
GET	/api/events/{eventId}/results	Returns all results for an event.	None (Public)	None	200 OK – list of participant results.

Method	Route	Description	Role Required	Request Body / Example Data	Expected Response
GET	/api/results/me	Returns the logged-in participant's performance history.	Participant	None	200 OK – [{ "resultId": 1, "eventId": 1, "finishTime": "00:52:31", "position": 25, "pace": "05:15/km" }]
GET	/api/results/{id}	Returns a specific race result.	None (Public)	None	200 OK – result details. 404 – result not found.
POST	/api/events/{eventId}/results	Records a participant's result after completing an event.	Organiser	{ "enrolmentId": 1, "finishTime": "00:52:31", "position": 25, "pace": "05:15/km" }	201 Created – result recorded. 404 – enrolment not found. 409 – result already exists.
PUT	/api/results/{id}	Corrects or updates a participant's result.	Organiser	{ "finishTime": "00:51:45", "position": 23, "pace": "05:10/km" }	200 OK – updated result. 404 – result not found.
DELETE	/api/results/{id}	Removes an incorrect race result.	Organiser	None	204 No Content – result deleted. 404 – result not found.