MXL TIMING BELT PULLEYS • 2.03 mm PITCH



FOR 6 mm BELTS

MOLDED WITH METAL HUB SINGLE OR DOUBLE FLANGE

MATERIAL:

Pulley - Polycarbonate, Fiberglass Reinforced **Insert** - Aluminum, Knurled Clear Anodized

SPECIFICATION:

Pulleys with 18 to 40 grooves do not have webs.



PHONE: 516.328.3300 • FAX: 516.326.8827 • WWW.SDP-SI.COM



2

3

4

5

6

Q

9

10

12

13

14

+ 17.5 **→** 4.5 4.5 2 WEB 2 WEB -SUB DRILL -SUB DRILL Ød Ø13 Ød Ø13 Ø8 Ø8 ØD₁ ØD ØD₁ ØD **A V** M3 SET SCREW M3 SET SCREW 6.3 ← ←1.6 (TYP) **-**1.6 Fig. 1 Fig. 2

METRIC COMPONENT

Catalog Number		No.		D	D_1	d Bore
Fig. 1 Single Flange	Fig. 2 Double Flange	of Grooves	P.D.	Dia.	Dia.	Dia. +0.025 0
A 6T16M018SF6005	A 6T16M018DF6005	18	11.6	11.1	16	5
A 6T16M018SF6006	A 6T16M018DF6006	18	11.6	11.1	16	6
A 6T16M020SF6005	A 6T16M020DF6005	20	12.9	12.4	17	5
A 6T16M020SF6006	A 6T16M020DF6006	20	12.9	12.4	17	6
A 6T16M021SF6005	A 6T16M021DF6005	21	13.6	13.1	18	5
A 6T16M021SF6006	A 6T16M021DF6006	21	13.6	13.1	18	6
A 6T16M022SF6005	A 6T16M022DF6005	22	14.2	13.7	19	5
A 6T16M022SF6006	A 6T16M022DF6006	22	14.2	13.7	19	6
A 6T16M024SF6005	A 6T16M024DF6005	24	15.5	15	20	5
A 6T16M024SF6006	A 6T16M024DF6006	24	15.5	15	20	6
A 6T16M026SF6005	A 6T16M026DF6005	26	16.8	16.3	21	5
A 6T16M026SF6006	A 6T16M026DF6006	26	16.8	16.3	21	6
A 6T16M028SF6005	A 6T16M028DF6005	28	18.1	17.6	22	5
A 6T16M028SF6006	A 6T16M028DF6006	28	18.1	17.6	22	6
A 6T16M030SF6005	A 6T16M030DF6005	30	19.4	18.9	24	5
A 6T16M030SF6006	A 6T16M030DF6006	30	19.4	18.9	24	6
A 6T16M032SF6005	A 6T16M032DF6005	32	20.7	20.2	25	5
A 6T16M032SF6006	A 6T16M032DF6006	32	20.7	20.2	25	6
A 6T16M036SF6005	A 6T16M036DF6005	36	23.3	22.8	28	5
A 6T16M036SF6006	A 6T16M036DF6006	36	23.3	22.8	28	6
A 6T16M040SF6005	A 6T16M040DF6005	40	25.9	25.4	30	5
A 6T16M040SF6006	A 6T16M040DF6006	40	25.9	25.4	30	6
A 6T16M042SF6005	A 6T16M042DF6005	42	27.2	26.7	31	5
A 6T16M042SF6006	A 6T16M042DF6006	42	27.2	26.7	31	6
A 6T16M044SF6005	A 6T16M044DF6005	44	28.5	28	33	5
A 6T16M044SF6006	A 6T16M044DF6006	44	28.5	28	33	6