



LAYER-STACK

01-16

01-20

Sym	Nº	Mils	MM	Qty	Plated
+	1	15	0.38	45	YES
×	2	32	0.81	2	YES
□	3	35	0.90	2	NOT
◇	4	40	1.02	45	YES

Notes:

This PCB to be manufactured to meet all acceptance levels of a CLASS 2 PCB per ANSI/IPC-A-600G.

Material: Isola PCL370HR FR-4 or equivalent.

Multilayer

2 Layers

Controlled Impedance

Cu weight external layers : 1oz

Cu weight internal layers :

Finished overall thickness : 0.062

Finish:

Immersion Gold

X Immersion Tin

Soldermask over bare copper (SMOBC) with
Hot-Air-Leveled-Solder

If edge connector fingers are present, plate
with Nicel/Gold >= 20 microinches Gold

Soldermask: Dynachem EPIC 200 LPI or equivalent.

Soldermask Color: Green

Silkscreen Color: White

Artwork Set No. 05-10134 Rev 1.5

All holes to be located by the NC Drill File.

Indicate Country where PCB was fabricated on the
side indicated.

Any deviation from the above specs must be approved
by Schmalz Haus LLC.

Copyright 2012 Brian Schmalz Copyright and related rights are licensed under the Solderpad Hardware License, Version 0.51 (the "License?");
you may not use this file except in compliance with the License. You may obtain a copy of the License at <http://solderpad.org/licenses/SHL-0.51>. Unless required by applicable law or agreed to in writing,
software, hardware and materials distributed under this License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and limitations under the License.