1. Identification

Product identifier 46910-MX

Product Identity Slide Mold Cleaner 4
Other means of identification Slide Mold Cleaner 4, 46910

Relevant identified uses of the substance or mixture and uses advised against

Industrial Mold Cleaner

Details of the supplier of the safety data sheet

Company Name
Slide Products Inc.
430 Wheeling Road
Wheeling, IL 60090

Emergency
24 hour Emergency Telephone No.
Emergency Telephone INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

Customer Service:
Phone: 1-847-541-7220
Fax: 1-847-541-7986

2. Hazard(s) identification

Classification of the substance or mixture

Flam. Gas 1;H220	Extremely flammable gas.
Press. Gas;H280	Contains gas under pressure; may explode if heated.
Skin Irrit. 2;H315	Causes skin irritation.
Eye Irrit. 2;H319	Causes serious eye irritation.
STOT SE 3;H336	May cause drowsiness or dizziness.
Aquatic Acute 1;H400	Very toxic to aquatic life.
Aquatic Chronic 1;H410	Very toxic to aquatic life with long lasting effects.

Label elements






Danger

H220 Extremely flammable gas.
H280 Contains gas under pressure; may explode if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness and dizziness.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
[Prevention]:
P210 Keep away from heat, sparks, open flames, and other ignition sources - No smoking.
P233 Keep container tightly closed.
P261 Avoid breathing dust, fume, gas, mist, vapours, spray.
P264 Wash thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves, eye protection, and face protection.
[Response]:
P302+352 IF ON SKIN: Wash with plenty of soap and water.
P304+340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTER, doctor or physician if you feel unwell.
P332+313 If skin irritation occurs: Get medical attention.
P337+313 If eye irritation persists: Get medical advice or attention.
P362+364 Take off contaminated clothing and wash it before reuse.
P377 Leaking gas fire - do not extinguish unless leak can be stopped safely.
P381 Eliminate all ignition sources if safe to do so.
P391 Collect spillage.
[Storage]:
P403+233 Store in a well ventilated place. Keep container tightly closed.
P403+235 Store in a well ventilated place. Keep cool.
P405 Store locked up.
P410+403 Protect from sunlight. Store in a well ventilated place.
[Disposal]:
P501 Dispose of contents or container in accordance with local and national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the NOM-018-STPS-2015 Regulation.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Isopropyl Alcohol **CAS Number: 0000067-63-0**	**25 - 50**	**Flam. Liq. 2;H225** **Eye Irrit. 2;H319** **STOT SE 3;H336**	**----**
Heptane **CAS Number: 0000142-82-5**	**25 - 50**	**Flam. Liq. 2;H225** **Asp. Tox. 1;H304** **Skin Irrit. 2;H315** **STOT SE 3;H336** **Aquatic Acute 1;H400** **Aquatic Chronic 1;H410**	**----**
Petroleum gases, liquefied **CAS Number: 0068476-86-8**	**10 - 25**	**Press. Gas;H280** **Flam. Gas 1;H220**	**----**

The actual concentration or concentration range is withheld as a trade secret.
*PBT/vPvB - PBT-substance or vPvB-substance.
The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Eyes Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

Ingestion If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Overview Treat symptomatically. Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Inhalation May cause drowsiness or dizziness.

Eyes Causes serious eye irritation.

Skin Causes skin irritation.

Section 5. Fire-fighting measures

Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO_2, powder, water spray.
Unsuitable extinguishing media: Do not use; water jet.

Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.
Keep away from heat, sparks, open flames, and other ignition sources - No smoking.
Keep container tightly closed.
Avoid breathing dust, fume, gas, mist, vapours, spray.

Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

ERG Guide No. ----

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).
Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Environmental precautions

Do not allow spills to enter drains or waterways.

Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapours. Take the personal protective measures listed in section 8.
Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

Section 7. Handling and storage

Precautions for safe handling
Handle containers carefully to prevent damage and spillage.
See section 2 for further details. - [Prevention]:

Conditions for safe storage, including any incompatibilities
Incompatible materials: Strong oxidizing agents and acids.
See section 2 for further details. - [Storage]:

Specific end use(s)
No available information

Section 8. Exposure controls / personal protection

Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0000067-63-0	Isopropyl Alcohol	ACGIH	TWA: 200 ppm STEL: 400 ppm
DNEL Local Exposure	No Established Limit		
DNEL Systematic Exposure	No Established Limit		
National	200 ppm TWA VLE-PPT 400 ppm STEL [PPT-CT]		
0000142-82-5	Heptane	ACGIH	TWA: 400 ppm STEL: 500 ppm
DNEL Local Exposure	No Established Limit		
DNEL Systematic Exposure	No Established Limit		
National	400 ppm TWA VLE-PPT; 1600 mg/m^{3}TWA VLE-PPT 500 ppm STEL [PPT-CT]		
0068476-86-8	Petroleum gases, liquefied	ACGIH	No Established Limit
DNEL Local Exposure	No Established Limit		
DNEL Systematic Exposure	No Established Limit		
National	No Established Limit		

Exposure controls

Respiratory If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

Eyes Protective safety glasses recommended

Skin Avoid skin contact. Protective gloves recommended.

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapour below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.

Section 9. Physical and chemical properties

Appearance	Clear Pressurized aerosol dispensed as a mist.
Odour	Characteristic
Odour threshold	No available information
pH	No available information
Melting point / freezing point	No available information
Initial boiling point and boiling range	70.6°C / 159°F
Flash Point	Not available
Evapouration rate (Ether = 1)	Faster than ether
Flammability (solid, gas)	Gas
Upper/lower flammability or explosive limits	**Lower Explosive Limit:** 1.2 **Upper Explosive Limit:** 7.5
Vapour pressure (Pa)	137 mmHg @ 20 C
Vapour Density	Heavier than air
Relative Density	0.6587
Solubility in Water	No available information
Partition coefficient n-octanol/water (Log Kow)	No available information
Auto-ignition temperature	No available information
Decomposition temperature	No available information
Viscosity (cSt)	No available information
VOC Content	100%
Oxidising properties	No available information
Explosive properties	No available information
Water Solubility	Insoluble in water

Other information
No other relevant information.

Section 10. Stability and reactivity

Reactivity
Hazardous Polymerization will not occur.
Chemical stability
Stable under normal circumstances.
Possibility of hazardous reactions
No available information
Conditions to avoid
Excessive heat and open flame.
Incompatible materials
Strong oxidizing agents and acids.
Hazardous decomposition products
High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation vapour LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Isopropyl Alcohol - (67-63-0)					

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation vapour LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
	5,840.00, Rat - Category: NA	16,400.00, Rabbit - Category: NA	72.60, Rat - Category: NA	No data available.	No data available.
Heptane - (142-82-5)	17,000.00, Rat - Category: NA	3,000.00, Rabbit - Category: 5	103.00, Rat - Category: NA	No data available.	No data available.
Petroleum gases, liquefied - (68476-86-8)	No data available.	No data available.	No data available.	No data available.	No data available.

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000067-63-0	Isopropyl Alcohol	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
ACGIH	A4		
0000142-82-5	Heptane	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
ACGIH	No Established Limit		
0068476-86-8	Petroleum gases, liquefied	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
ACGIH	No Established Limit		

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Serious eye damage/irritation	2	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

Symptoms and effects, both acute and delayed::
Treat symptomatically.

Inhalation May cause drowsiness or dizziness.
Eyes Causes serious eye irritation.
Skin Causes skin irritation.

Section 12. Ecological information

Toxicity
Very toxic to aquatic life.
Very toxic to aquatic life with long lasting effects.
No additional information provided for this product. See Section 3 for chemical specific data.
Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
Isopropyl Alcohol - (67-63-0)	10,000.00, Pimephales promelas	No data available.	No data available.
Heptane - (142-82-5)	375.00, Oreochromis mossambicus	3.90, Daphnia magna	4.34, Pseudokirchneriella subcapitata
Petroleum gases, liquefied - (68476-86-8)	No data available.	No data available.	No data available.

Persistence and degradability
There is no data available on the preparation itself.
Bioaccumulative potential
No available information
Mobility in soil
No available information
Results of PBT and vPvB assessment
This product contains no PBT/vPvB chemicals.
Other adverse effects
No available information

Section 13. Disposal considerations

Waste treatment methods
Observe all federal, provincial and local regulations when disposing of this substance.

Section 14. Transport information

When shipped in containers of 0.3 gallons (1 L) or less this material may be reclassified in accordance with DOT regulations 49 CFR 173.150 / IATA DGR packing instruction Y341/ IMDG Code 3.4 as: Limited Quantity.

Classification Method: Classified as per Part 2, Sections 2.1 - 2.8 of the Transportation of Dangerous Goods Regulations.

	SCT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
UN number	UN1950	UN1950	UN1950
UN proper shipping name	UN1950,Aerosols	Aerosols, Flammable, (each not exceeding 1 L capacity) (Heptane)	Aerosols, Flammable, (each not exceeding 1 L capacity) (Heptane)
Transport hazard class(es)	**DOT Hazard Class:**2.1 **Sub Class:**Not Applicable	**IMDG:**2.1 **Sub Class:**Not Applicable	**Air Class:**2.1 **Sub Class:**Not Applicable
Packing group	Not Applicable	Not Applicable	Not Applicable
Environmental hazards	Marine Pollutant: Yes; (Heptane)		
Special precautions for user	No available information		

Section 15. Regulatory information

This product has been classified in accordance with the hazard criteria of NOM-018-STPS-2015 and the SDS contains the information required by those regulations.

NFPA	Health Hazards	Flammability	Instability	Special Hazards
	Not determined	Not determined	Not determined	Not determined

Mexico - National Inventory of Chemical Substances (INSQ):

Heptane
Isopropyl Alcohol
Petroleum gases, liquefied

Section 16. Other information

SDS Revision Date 11/06/2023

HMIS	Health Hazards	Flammability	Physical Hazards	Personal Protection
	1	4	0	**B**

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

End of Document