# Shop Pro Brake Parts Cleaner Non-VOC

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 10/28/2022 Revision date: 10/28/2022 Supersedes: 12/20/2021 Version: 1.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixture

Product name : Shop Pro Brake Parts Cleaner Non-VOC

Product code : SP-BPC-10

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Brake Parts Cleaner

### 1.3. Details of the supplier of the safety data sheet

Autozone
PO Box 2198
Memphis, TN 38101
T 901-495-7522

### 1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

**GHS US classification**

| | |
|---|---|
| Flammable aerosol Category 1 | H222 Extremely flammable aerosol |
| Gases under pressure Compressed gas | H280 Contains gas under pressure; may explode if heated |
| Skin corrosion/irritation Category 2 | H315 Causes skin irritation |
| Reproductive toxicity Category 2 | H361 Suspected of damaging fertility or the unborn child |
| Specific target organ toxicity — Single exposure, Category 3, Narcosis | H336 May cause drowsiness or dizziness |
| Specific target organ toxicity (repeated exposure) Category 2 | H373 May cause damage to organs through prolonged or repeated exposure |

Full text of H- and EUH-statements: see section 16

### 2.2. Label elements

**GHS US labeling**

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US) :
H222 - Extremely flammable aerosol
H280 - Contains gas under pressure; may explode if heated
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness
H361 - Suspected of damaging fertility or the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS US) :
P201 - Obtain special instructions
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Pressurized container: Do not pierce or burn, even after use.
P260 - Do not breathe dust,fumes,gas,mist,vapor spray
P261 - Avoid breathing dust,fume,gas,mist,vapor spray
P264 - Wash affected areas thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves,protective clothing,eye protection,face protection
P302+P352 - If on skin: Wash with plenty of soap and water
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P312 - Call a POISON CONTROL CENTER, doctor, if you feel unwell.
P314 - Get medical advice/attention if you feel unwell.
P321 - Specific treatment: See section 4.1 on SDS
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P410+P403 - Protect from sunlight. Store in a well-ventilated place.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

### 2.3. Other hazards

Other hazards which do not result in classification : Contains gas under pressure; may explode if heated. None under normal conditions.

### 2.4. Unknown acute toxicity (GHS US)

No data available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

| Name | Product identifier | % | GHS US classification |
|---|---|---|---|
| Heptane, Branched Cyclic | (CAS-No.) 426260-76-6 | 40-60 | Flam. Liq. 1, H224<br>Skin Irrit. 2, H315<br>STOT SE 3, H336<br>Asp. Tox. 1, H304<br>Aquatic Chronic 3, H412 |
| Toluene | (CAS-No.) 108-88-3 | 30 – 50 | Flam. Liq. 2, H225<br>Skin Irrit. 2, H315<br>STOT SE 3, H336<br>STOT RE 2, H373<br>Asp. Tox. 1, H304 |
| n-Heptane | (CAS-No.) 142-82-5 | 10-35 | Flam. Liq. 2, H225<br>Skin Irrit. 2, H315<br>STOT SE 3, H336<br>Asp. Tox. 1, H304<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410 |
| Carbon Dioxide, Liquefied, Under Pressure | (CAS-No.) 124-38-9 | 1 – 5 | Press. Gas (Comp.), H280 |

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Cough. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Direct contact with the eyes is likely to be irritating. Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Suspected of damaging fertility or the unborn child. Causes damage to organs.

Symptoms/effects after inhalation : Shortness of breath. May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

### 5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. DO NOT fight fire when fire reaches explosives. Evacuate area.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Other information : Aerosol level 3.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : No open flames. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges.

#### 6.1.1. For non-emergency personnel

Protective equipment : Gloves. Safety glasses.

Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust,fume,gas,mist,vapor spray.

Emergency procedures : Ventilate area.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment : Dam up the liquid spill. Contain released product, collect/pump into suitable containers. Plug the leak, cut off the supply.

Methods for cleaning up : Store away from other materials.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or burn, even after use.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not spray on an open flame or other ignition source. Obtain special instructions . Do not handle until all safety precautions have been read and understood. Avoid breathing dust,fume,gas,mist,vapor spray. Use only outdoors or in a well-ventilated area.

Hygiene measures : Wash affected areas thoroughly after handling.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Keep container tightly closed.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

Storage area : Store in a well-ventilated place.

### 7.3. Specific end use(s)

Follow Label Directions.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

| **Shop Pro Brake Parts Cleaner Non-VOC** | |
|---|---|
| No additional information available | |

| **n-Heptane (142-82-5)** | |
|---|---|
| **USA - ACGIH - Occupational Exposure Limits** | |
| ACGIH OEL TWA [ppm] | 400 ppm |
| ACGIH OEL STEL [ppm] | 500 ppm |

| **Heptane, Branched Cyclic (426260-76-6)** | |
|---|---|
| **USA - ACGIH - Occupational Exposure Limits** | |
| ACGIH OEL TWA [ppm] | 400 ppm |
| ACGIH OEL STEL [ppm] | 500 ppm |

| | |
|---|---|
| **USA - OSHA - Occupational Exposure Limits** | |
| OSHA PEL (TWA) [2] | 500 ppm |
| **Carbon Dioxide, Liquefied, Under Pressure (124-38-9)** | |
| **USA - ACGIH - Occupational Exposure Limits** | |
| ACGIH OEL TWA | 9000 mg/m³ |
| ACGIH OEL TWA [ppm] | 5000 ppm |
| ACGIH OEL STEL | 54000 |
| ACGIH OEL STEL [ppm] | 30000 ppm |
| **USA - OSHA - Occupational Exposure Limits** | |
| OSHA PEL (TWA) [1] | 9000 mg/m³ |
| OSHA PEL (TWA) [2] | 5000 ppm |
| **USA - NIOSH - Occupational Exposure Limits** | |
| NIOSH REL (TWA) | 9000 mg/m³ |
| NIOSH REL TWA [ppm] | 5000 ppm |
| NIOSH REL (Ceiling) | 54000 mg/m³ |
| NIOSH REL C [ppm] | 30000 ppm |
| **Toluene (108-88-3)** | |
| **USA - ACGIH - Occupational Exposure Limits** | |
| ACGIH OEL TWA [ppm] | 20 ppm |

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Local exhaust venilation, vent hoods . Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

**Personal protective equipment:**

Avoid all unnecessary exposure.

**Materials for protective clothing:**

Excellent resistance:

**Hand protection:**

Wear protective gloves

**Eye protection:**

Chemical goggles or safety glasses

**Skin and body protection:**

Wear suitable protective clothing

**Respiratory protection:**

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

**Personal protective equipment symbol(s):**



**Other information:**

Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Aerosol

Appearance : Aerosols.

Color : Colorless.

Odor : characteristic.

Odor threshold : No data available

pH : No data available

Relative evaporation rate (butyl acetate=1) : No data available

| | | |
|---|---|---|
| Melting point | : | No data available |
| Freezing point | : | No data available |
| Boiling point | : | 88 °C (Lowest Component) |
| Flash point | : | -9 °C (Lowest Component) |
| Auto-ignition temperature | : | No data available |
| Decomposition temperature | : | No data available |
| Flammability | : | No data available |
| Vapor pressure | : | No data available |
| Relative vapor density at 20 °C | : | No data available |
| Relative density | : | 0.75 |
| Solubility | : | Poorly soluble in water. |
| Partition coefficient n-octanol/water (Log Pow) | : | No data available |
| Partition coefficient n-octanol/water (Log Kow) | : | No data available |
| Viscosity, kinematic | : | No data available |
| Viscosity, dynamic | : | No data available |
| Explosive properties | : | No data available |
| Oxidizing properties | : | No data available |
| Explosion limits | : | No data available |

### 9.2. Other information

VOC content : 95.5 %

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

| | | |
|---|---|---|
| Acute toxicity (oral) | : | Not classified |
| Acute toxicity (dermal) | : | Not classified |
| Acute toxicity (inhalation) | : | Not classified |

| **n-Heptane (142-82-5)** | |
|---|---|
| LD50 oral rat | > 5000 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Read-across, Oral, 14 day(s)) |
| LD50 dermal rabbit | > 2000 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Read-across, Dermal, 14 day(s)) |
| LC50 Inhalation - Rat | > 29.29 mg/l/4h (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours)) |

| **Heptane, Branched Cyclic (426260-76-6)** | |
|---|---|
| LD50 oral rat | > 5000 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Read-across, Oral, 14 day(s)) |
| LD50 dermal rabbit | > 2000 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Read-across, Dermal, 14 day(s)) |
| LC50 Inhalation - Rat | > 29.29 mg/l/4h (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours)) |

| Toluene (108-88-3) | |
|---|---|
| LD50 oral rat | 5580 mg/kg body weight (Equivalent or similar to EU Method B.1, Rat, Male, Experimental value, Oral, 7 day(s)) |
| LD50 dermal rabbit | > 5000 mg/kg body weight (24 h, Rabbit, Male, Experimental value, Dermal) |
| LC50 Inhalation - Rat | 28.1 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours)) |
| ATE US (oral) | 5580 mg/kg body weight |

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

STOT-single exposure : May cause drowsiness or dizziness.

| n-Heptane (142-82-5) | |
|---|---|
| STOT-single exposure | May cause drowsiness or dizziness. |

| Heptane, Branched Cyclic (426260-76-6) | |
|---|---|
| STOT-single exposure | May cause drowsiness or dizziness. |

| Toluene (108-88-3) | |
|---|---|
| STOT-single exposure | May cause drowsiness or dizziness. |

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

| Toluene (108-88-3) | |
|---|---|
| STOT-repeated exposure | May cause damage to organs through prolonged or repeated exposure. |

Aspiration hazard : Not classified

Viscosity, kinematic : No data available

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

Symptoms/effects : Suspected of damaging fertility or the unborn child. Causes damage to organs.

Symptoms/effects after inhalation : Shortness of breath. May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes eye irritation.

## SECTION 12: Ecological information

### 12.1. Toxicity

| Carbon Dioxide, Liquefied, Under Pressure (124-38-9) | |
|---|---|
| LC50 - Fish [1] | 35 mg/l (96 h, Salmo gairdneri, Literature study, Lethal) |

| Toluene (108-88-3) | |
|---|---|
| LC50 - Fish [1] | 5.5 mg/l (96 h, Oncorhynchus kisutch, Flow-through system, Fresh water, Experimental value, Lethal) |

### 12.2. Persistence and degradability

| Shop Pro Brake Parts Cleaner Non-VOC | |
|---|---|
| Persistence and degradability | Not established. |

| n-Heptane (142-82-5) | |
|---|---|
| Persistence and degradability | Readily biodegradable in water. Forming sediments in water. Biodegradable in the soil. Low potential for adsorption in soil. Photolysis in the air. Not established. |
| Biochemical oxygen demand (BOD) | 1.92 g $O_2$/g substance |
| Chemical oxygen demand (COD) | 0.06 g $O_2$/g substance |
| ThOD | 3.52 g $O_2$/g substance |

| Heptane, Branched Cyclic (426260-76-6) | |
|---|---|
| Persistence and degradability | May cause long-term adverse effects in the environment. |

| Carbon Dioxide, Liquefied, Under Pressure (124-38-9) | |
|---|---|
| Persistence and degradability | Biodegradability: not applicable. Not established. |
| Chemical oxygen demand (COD) | Not applicable (inorganic) |
| ThOD | Not applicable (inorganic) |

| Toluene (108-88-3) | |
|---|---|
| Persistence and degradability | Readily biodegradable in water. |
| Biochemical oxygen demand (BOD) | 2.15 g $O_2$/g substance |
| Chemical oxygen demand (COD) | 2.52 g $O_2$/g substance |
| ThOD | 3.13 g $O_2$/g substance |
| BOD (% of ThOD) | 0.69 |

### 12.3. Bioaccumulative potential

| Shop Pro Brake Parts Cleaner Non-VOC | |
|---|---|
| Bioaccumulative potential | Not established. |

| n-Heptane (142-82-5) | |
|---|---|
| BCF - Other aquatic organisms [1] | 552 (BCFBAF v3.00, Calculated value) |
| Partition coefficient n-octanol/water (Log Pow) | 4.5 (Literature) |
| Bioaccumulative potential | Potential for bioaccumulation (4 ≥ Log Kow ≤ 5). Not established. |

| Heptane, Branched Cyclic (426260-76-6) | |
|---|---|
| Bioaccumulative potential | Not established. |

| Carbon Dioxide, Liquefied, Under Pressure (124-38-9) | |
|---|---|
| Partition coefficient n-octanol/water (Log Pow) | 0.83 (Experimental value) |
| Bioaccumulative potential | Low potential for bioaccumulation (Log Kow < 4). Not established. |

| Toluene (108-88-3) | |
|---|---|
| BCF - Fish [1] | 90 (72 h, Leuciscus idus, Static system, Fresh water, Experimental value) |
| Partition coefficient n-octanol/water (Log Pow) | 2.73 (Experimental value, 20 °C) |
| Bioaccumulative potential | Low potential for bioaccumulation (BCF < 500). |

### 12.4. Mobility in soil

| n-Heptane (142-82-5) | |
|---|---|
| Surface tension | 19.66 mN/m (25 °C) |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 2.38 (log Koc, SRC PCKOCWIN v2.0, Calculated value) |
| Ecology - soil | Low potential for adsorption in soil. |

| Carbon Dioxide, Liquefied, Under Pressure (124-38-9) | |
|---|---|
| Ecology - soil | Not applicable (gas). |

| Toluene (108-88-3) | |
|---|---|
| Surface tension | 27.73 mN/m (25 °C, 0.05 %) |
| Ecology - soil | Low potential for adsorption in soil. |

### 12.5. Other adverse effects

Effect on global warming : No known effects from this product.

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

Additional information : Flammable vapors may accumulate in the container.

Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information

**Department of Transportation (DOT)**

In accordance with DOT

US DOT (ground) (DOT) : UN1950 Aerosols (Flammable, (each not exceeding 1 L capacity)), 2.1

UN-No.(DOT) : UN1950

Proper Shipping Name (DOT) : Aerosols
Flammable, (each not exceeding 1 L capacity)

Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

DOT Packaging Non Bulk (49 CFR 173.xxx) : None

DOT Packaging Bulk (49 CFR 173.xxx) : None

| | | |
|---|---|---|
| DOT Special Provisions (49 CFR 172.102) | : | N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols. |
| DOT Packaging Exceptions (49 CFR 173.xxx) | : | 306 |
| DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) | : | 75 kg |
| DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) | : | 150 kg |
| DOT Vessel Stowage Location | : | A - The material may be stowed ‘‘on deck’’ or ‘‘under deck’’ on a cargo vessel and on a passenger vessel. |
| DOT Vessel Stowage Other | : | 48 - Stow ‘‘away from’’ sources of heat,87 - Stow ‘‘separated from’’ Class 1 (explosives) except Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials |
| Other information | : | No supplementary information available. |

### Transport by sea

| | | |
|---|---|---|
| UN-No. (IMDG) | : | 1950 |
| Class (IMDG) | : | 2.1 - Flammable gases |

### Air transport

| | | |
|---|---|---|
| UN-No. (IATA) | : | 1950 |
| Proper Shipping Name (IATA) | : | Aerosols |
| Class (IATA) | : | 2.1 - Gases : Flammable |

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

| **Shop Pro Brake Parts Cleaner Non-VOC** | |
|---|---|
| SARA Section 311/312 Hazard Classes | Fire hazard<br>Delayed (chronic) health hazard<br>Immediate (acute) health hazard<br>Sudden release of pressure hazard |

| **n-Heptane (142-82-5)** |
|---|
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |

| **Heptane, Branched Cyclic (426260-76-6)** | |
|---|---|
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| SARA Section 311/312 Hazard Classes | Fire hazard<br>Immediate (acute) health hazard<br>Delayed (chronic) health hazard |

| **Carbon Dioxide, Liquefied, Under Pressure (124-38-9)** | |
|---|---|
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| SARA Section 311/312 Hazard Classes | Sudden release of pressure hazard<br>Immediate (acute) health hazard |

### 15.2. International regulations

#### CANADA

| **Shop Pro Brake Parts Cleaner Non-VOC** | |
|---|---|
| WHMIS Classification | Class B Division 5 - Flammable Aerosol |

| **n-Heptane (142-82-5)** |
|---|
| Listed on the Canadian DSL (Domestic Substances List) |

| **Heptane, Branched Cyclic (426260-76-6)** | |
|---|---|
| Listed on the Canadian DSL (Domestic Substances List) | |
| WHMIS Classification | Class B Division 2 - Flammable Liquid<br>Class D Division 2 Subdivision B - Toxic material causing other toxic effects |

| **Carbon Dioxide, Liquefied, Under Pressure (124-38-9)** |
|---|
| Listed on the Canadian DSL (Domestic Substances List) |

#### EU-Regulations

| **Heptane, Branched Cyclic (426260-76-6)** |
|---|

| **Carbon Dioxide, Liquefied, Under Pressure (124-38-9)** |
|---|

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

#### 15.2.2. National regulations

**Heptane, Branched Cyclic (426260-76-6)**

**Carbon Dioxide, Liquefied, Under Pressure (124-38-9)**

### 15.3. US State regulations

| **Shop Pro Brake Parts Cleaner Non-VOC()** | |
|---|---|
| U.S. - California - Proposition 65 - Carcinogens List | No |
| U.S. - California - Proposition 65 - Developmental Toxicity | No |
| U.S. - California - Proposition 65 - Reproductive Toxicity - Female | No |
| U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No |
| State or local regulations | U.S. - California - Proposition 65 |

| **n-Heptane (142-82-5)** | | | | |
|---|---|---|---|---|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) |
| No | No | No | No | |

| **Heptane, Branched Cyclic (426260-76-6)** | | | | |
|---|---|---|---|---|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) |
| No | No | No | No | |

| **Carbon Dioxide, Liquefied, Under Pressure (124-38-9)** | | | | |
|---|---|---|---|---|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) |
| No | No | No | No | |

| **Toluene (108-88-3)** | | | | |
|---|---|---|---|---|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) |
| No | No | No | No | |

**n-Heptane (142-82-5)**

**State or local regulations**

U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. – New York City – Right to Know Hazardous Substances List
U.S. - Pennsylvania - RTK (Right to Know) List

**Carbon Dioxide, Liquefied, Under Pressure (124-38-9)**

**State or local regulations**

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. – New York City – Right to Know Hazardous Substances List
U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: Other information

Indication of changes : Revision - See : *.

Other information : None.


Full text of H-phrases:

| | |
|---|---|
| H222 | Extremely flammable aerosol |
| H224 | Extremely flammable liquid and vapor |
| H225 | Highly flammable liquid and vapor |
| H280 | Contains gas under pressure; may explode if heated |
| H304 | May be fatal if swallowed and enters airways |
| H315 | Causes skin irritation |
| H336 | May cause drowsiness or dizziness |
| H361 | Suspected of damaging fertility or the unborn child |
| H373 | May cause damage to organs through prolonged or repeated exposure |
| H400 | Very toxic to aquatic life |
| H410 | Very toxic to aquatic life with long lasting effects |
| H412 | Harmful to aquatic life with long lasting effects |

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 4 - Materials that rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and burn readily.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.




**Hazard Rating**

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 4 Severe Hazard

Physical : 1 Slight Hazard

Personal protection : B

*The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product*

*Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.*