SAFETY DATA SHEET

Product Number: 639 **Revision Date** 29-May-2015 **Revision Number** 1

The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name **2 Minute Remover**

Other means of identification

UN-No. UN1593

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Paint or Varnish Remover (Paint or Paint-Related)

This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) of processed (as defined in TSCA section 3(13)) for consumer paint and coating removal.

Details of the supplier of the safety data sheet

Supplier Name Sunnyside Corporation

Supplier Address 225 Carpenter Avenue
Wheeling
IL
60090
US

Supplier Phone Number Phone:8475415700
Fax:8475419043

Supplier Email sscontact@sunnysidecorp.com

Emergency telephone number

Company Emergency Phone Number Chem Trec: 800-424-9300

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Acute toxicity - Oral	Category 4
Serious eye damage/eye irritation	Category 2A

Carcinogenicity	Category 1B
Specific target organ toxicity (single exposure)	Category 1

GHS Label elements, including precautionary statements

Emergency Overview

Signal word **Danger**

Hazard Statements
Harmful if swallowed
Causes serious eye irritation
May cause cancer
Causes damage to organs



Appearance Clear **Physical state** Liquid **Odor** Pungent

Precautionary Statements - Prevention
Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Do not breathe dust/fume/gas/mist/vapors/spray
Wear eye/face protection

Precautionary Statements - Response
IF exposed: Call a POISON CENTER or doctor/physician
Specific treatment (see supplemental first aid instructions on this label)

Eyes
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention

Ingestion
IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
Rinse mouth

Precautionary Statements - Storage
Store locked up

Precautionary Statements - Disposal
Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity
0% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Causes mild skin irritation
INHALATION MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS

Interactions with Other Chemicals
Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

.

Chemical Name	CAS No	Weight-%	Trade Secret
Dichloromethane	75-09-2	60 - 100	
Methyl alcohol	67-56-1	1 - 5	
Xylene, mixed isomers	1330-20-7	1 - 5	
Poly(oxy-1,2-ethanediyl), .alpha.-[(1,1,3,3-tetramethylbutyl)phenyl]-.omega.-hydroxy-	9036-19-5	1 - 5	
Dipropylene glycol monomethyl ether	34590-94-8	1 - 5	
Ethylbenzene	100-41-4	0.1 - 1	
Ammonia	7664-41-7	0.1 - 1	

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice Show this safety data sheet to the doctor in attendance.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. If symptoms persist, call a physician.

Skin contact Wash off immediately with soap and plenty of water for at least 15 minutes. If symptoms persist, call a physician.

Inhalation Remove to fresh air.

Ingestion Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects Burning sensation.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media
CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical
No information available.

Uniform Fire Code Irritant: Liquid
Combustible Liquid: III-B

Hazardous Combustion Products
Carbon oxides.

Explosion Data
Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge No.

Protective equipment and precautions for firefighters
As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas.

Other Information Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers. Soak up with inert absorbent material.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Store locked up.

Incompatible Products None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Dichloromethane 75-09-2	TWA: 50 ppm	TWA: 25 ppm Action Level: 12.5 ppm See 29 CFR 1910.1052 (vacated) TWA: 500 ppm (vacated) STEL: 2000 ppm 5 min in any 3 h (vacated) Ceiling: 1000 ppm STEL: 125 ppm see 29 CFR 1910.1052	IDLH: 2300 ppm
Methyl alcohol 67-56-1	STEL = 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m^3 (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m^3 (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m^3 (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m^3 STEL: 325 mg/m^3 STEL: 250 ppm
Xylene, mixed isomers 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m^3 (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m^3 (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m^3	
Dipropylene glycol monomethyl ether 34590-94-8	STEL: 150 ppm TWA: 100 ppm S*	TWA: 100 ppm TWA: 600 mg/m^3 (vacated) TWA: 100 ppm (vacated) TWA: 600 mg/m^3 (vacated) STEL: 150 ppm (vacated) STEL: 900 mg/m^3 (vacated) S* S*	IDLH: 600 ppm TWA: 100 ppm TWA: 600 mg/m^3 STEL: 150 ppm STEL: 900 mg/m^3
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m^3 (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m^3 (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m^3	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m^3 STEL: 125 ppm STEL: 545 mg/m^3
Ammonia 7664-41-7	STEL: 35 ppm TWA: 25 ppm	TWA: 50 ppm TWA: 35 mg/m^3	IDLH: 300 ppm TWA: 18 mg/m^3

		(vacated) STEL: 35 ppm (vacated) STEL: 27 mg/m^3	TWA: 25 ppm STEL: 27 mg/m^3 STEL: 35 ppm

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection If splashes are likely to occur:. Wear safety glasses with side shields (or goggles). None required for consumer use.

Skin and body protection Wear protective gloves and protective clothing.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state	Liquid		
Appearance	Clear	**Odor**	Pungent
Color	No information available	**Odor Threshold**	No information available

Property	**Values**	**Remarks Method**
pH	UNKNOWN	None known
Melting / freezing point	No data available	None known
Boiling point / boiling range	40 °C / 104 °F	None known
Flash Point	200 C / 392 F	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Specific Gravity	1.0389	None known
Water Solubility	Partially soluble	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

Explosive properties No data available
Oxidizing properties No data available

Other Information

Softening Point No data available
VOC Content (%) No data available
Particle Size No data available
Particle Size Distribution

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability
Stable under recommended storage conditions.
Possibility of Hazardous Reactions
None under normal processing.
Hazardous Polymerization
Hazardous polymerization does not occur.

Conditions to avoid
None known based on information supplied.
Incompatible materials
None known based on information supplied.
Hazardous Decomposition Products
Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information .

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.

Skin contact Specific test data for the substance or mixture is not available. May cause irritation. Prolonged contact may cause redness and irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Harmful if swallowed. (based on components).

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Dichloromethane 75-09-2	= 1600 mg/kg (Rat)	-	= 53 mg/L (Rat) 6 h = 76000 mg/m³ (Rat) 4 h
Methyl alcohol 67-56-1	= 5628 mg/kg (Rat)	-	= 83.2 mg/L (Rat) 4 h
Xylene, mixed isomers 1330-20-7	= 4300 mg/kg (Rat)	> 1700 mg/kg (Rabbit)	= 47635 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h
Dipropylene glycol monomethyl	= 5230 mg/kg (Rat)	= 9500 mg/kg (Rabbit)	-

ether 34590-94-8			
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15354 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h
Ammonia 7664-41-7	= 350 mg/kg (Rat)	-	= 2000 ppm (Rat) 4 h

Information on toxicological effects

Symptoms May cause redness and tearing of the eyes.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Dichloromethane 75-09-2	A3	Group 2A	Reasonably Anticipated	X
Xylene, mixed isomers 1330-20-7		Group 3		
Ethylbenzene 100-41-4	A3	Group 2B		X

ACGIH (American Conference of Governmental Industrial Hygienists)
A3 - Animal Carcinogen
IARC (International Agency for Research on Cancer)
Group 2A - Probably Carcinogenic to Humans
Group 2B - Possibly Carcinogenic to Humans
Group 3 - Not Classifiable as to Carcinogenicity in Humans
NTP (National Toxicology Program)
Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
X - Present

Reproductive toxicity No information available.

STOT - single exposure Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from acute exposure. (STOT SE). If this product is a mixture, the classification is not based on toxicology studies for this product, but is based solely on toxicology studies for ingredients found within this product. Detailed substance and/or ingredient information may be provided in other sections of this SDS. Target organs effects listed in this document may result from a single overexposure to this product. Causes damage to organs if swallowed.

STOT - repeated exposure No information available.

Chronic Toxicity No known effect based on information supplied. Contains a known or suspected carcinogen. Effects from this product caused by acute exposure may cause permanent damage to target organs and/or may cause chronic conditions. May cause adverse liver effects.

Target Organ Effects Eyes. Respiratory system. Skin. Gastrointestinal tract (GI). Central Nervous System (CNS). Central Vascular System (CVS). Liver. Lungs. Endocrine system. Kidney. Systemic Toxicity. Thyroid. Testes.

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)
958.00 mg/kg
ATEmix (dermal)
6,323.00 mg/kg (ATE)
ATEmix (inhalation-gas)
2,000,000.00
ATEmix (inhalation-dust/mist)
9.00 mg/l
ATEmix (inhalation-vapor)
62.00 ATEmix

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Dichloromethane 75-09-2	96h EC50: > 500 mg/L (Pseudokirchneriella subcapitata) 72h EC50: > 500 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 140.8 - 277.8 mg/L (Pimephales promelas) 96h LC50: 262 - 855 mg/L (Pimephales promelas) 96h LC50: = 193 mg/L (Lepomis macrochirus)	EC50 = 1 mg/L 24 h EC50 = 2.88 mg/L 15 min	48h EC50: 1532 - 1847 mg/L 48h EC50: = 190 mg/L
Methyl alcohol 67-56-1		96h LC50: = 28200 mg/L (Pimephales promelas) 96h LC50: > 100 mg/L (Pimephales promelas) 96h LC50: 19500 - 20700 mg/L (Oncorhynchus mykiss) 96h LC50: 18 - 20 mL/L (Oncorhynchus mykiss) 96h LC50: 13500 - 17600 mg/L (Lepomis macrochirus)	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	
Xylene, mixed isomers 1330-20-7		96h LC50: = 13.4 mg/L (Pimephales promelas) 96h LC50: 2.661 - 4.093 mg/L (Oncorhynchus mykiss) 96h LC50: 13.5 - 17.3 mg/L (Oncorhynchus mykiss) 96h LC50: 13.1 - 16.5 mg/L (Lepomis macrochirus) 96h LC50: = 19 mg/L (Lepomis macrochirus) 96h LC50: 7.711 - 9.591 mg/L (Lepomis macrochirus) 96h LC50: 23.53 - 29.97 mg/L (Pimephales promelas) 96h LC50: = 780 mg/L (Cyprinus carpio) 96h LC50: > 780 mg/L (Cyprinus carpio) 96h LC50: 30.26 - 40.75 mg/L (Poecilia reticulata)		48h EC50: = 3.82 mg/L 48h LC50: = 0.6 mg/L
Dipropylene glycol monomethyl ether 34590-94-8		96h LC50: > 10000 mg/L (Pimephales promelas)		48h LC50: = 1919 mg/L
Ethylbenzene 100-41-4	72h EC50: = 4.6 mg/L (Pseudokirchneriella subcapitata) 96h EC50: > 438 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 2.6 - 11.3 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 1.7 - 7.6 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 11.0 - 18.0 mg/L (Oncorhynchus mykiss) 96h LC50: = 4.2 mg/L (Oncorhynchus mykiss) 96h LC50: 7.55 - 11 mg/L (Pimephales promelas) 96h LC50: = 32 mg/L (Lepomis macrochirus) 96h LC50: 9.1 - 15.6 mg/L (Pimephales promelas) 96h LC50: = 9.6 mg/L (Poecilia reticulata)	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	48h EC50: 1.8 - 2.4 mg/L
Ammonia 7664-41-7		96h LC50: = 0.44 mg/L (Cyprinus carpio) 96h LC50: = 1.19 mg/L (Poecilia reticulata) 96h LC50: > 1.5 mg/L (Poecilia reticulata) 96h LC50: = 5.9 mg/L (Pimephales promelas) 96h LC50: 0.73 - 2.35 mg/L (Pimephales promelas) 96h		48h LC50: = 25.4 mg/L

		LC50: = 1.17 mg/L (Lepomis macrochirus) 96h LC50: 0.26 - 4.6 mg/L (Lepomis macrochirus)		

Persistence and Degradability
No information available.

Bioaccumulation

Chemical Name	Log Pow
Dichloromethane 75-09-2	1.25
Methyl alcohol 67-56-1	-0.77
Xylene, mixed isomers 1330-20-7	3.15
Dipropylene glycol monomethyl ether 34590-94-8	-0.064
Ethylbenzene 100-41-4	3.118
Ammonia 7664-41-7	-1.14

Other adverse effects
No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

US EPA Waste Number U239 U154 U080

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Dichloromethane 75-09-2	waste number U080	Included in waste streams: F001, F002, F024, F025, F039, K009, K010, K156, K157, K158		U080
Methyl alcohol 67-56-1		Included in waste stream: F039		U154
Xylene, mixed isomers 1330-20-7		Included in waste stream: F039		U239
Ethylbenzene 100-41-4		Included in waste stream: F039		

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Dichloromethane 75-09-2	Category I - Volatiles		Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Dichloromethane 75-09-2	Toxic
Methyl alcohol 67-56-1	Toxic Ignitable
Xylene, mixed isomers 1330-20-7	Toxic Ignitable
Ethylbenzene 100-41-4	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN-No.	UN1593
Proper Shipping Name	DICHLOROMETHANE
Hazard Class	6.1
Packing Group	III
Description	UN1593, DICHLOROMETHANE, 6.1, III
Emergency Response Guide Number	160

TDG

UN-No.	UN1593
Proper Shipping Name	DICHLOROMETHANE
Hazard Class	6.1
Packing Group	III
Description	UN1593, DICHLOROMETHANE, 6.1, III

MEX

UN-No.	UN1593
Proper Shipping Name	DICHLOROMETHANE
Hazard Class	6.1
Packing Group	III
Description	UN1593, DICHLOROMETHANE, 6.1, III

ICAO

UN-No.	UN1593
Proper Shipping Name	DICHLOROMETHANE
Hazard Class	6.1
Packing Group	III
Description	UN1593, DICHLOROMETHANE, 6.1, III

IATA

UN-No.	UN1593
Proper Shipping Name	DICHLOROMETHANE
Hazard Class	6.1
Packing Group	III
Description	UN1593, DICHLOROMETHANE, 6.1, III

IMDG/IMO

UN-No.	UN1593
Proper Shipping Name	DICHLOROMETHANE
Hazard Class	6.1
Packing Group	III
EmS-No.	F-A, S-A
Description	UN1593, DICHLOROMETHANE, 6.1, III

RID

UN-No.	UN1593
Proper Shipping Name	DICHLOROMETHANE
Hazard Class	6.1
Packing Group	III
Classification code	T1
Description	UN1593, DICHLOROMETHANE, 6.1, III

ADR

UN-No.	UN1593
Proper Shipping Name	DICHLOROMETHANE
Hazard Class	6.1
Packing Group	III
Classification code	T1

Tunnel restriction code	(E)
Description	UN1593, DICHLOROMETHANE, 6.1, III

ADN

UN-No.	UN1593
Proper Shipping Name	DICHLOROMETHANE
Hazard Class	6.1
Packing Group	III
Classification code	T1
Special Provisions	516, 802
Description	UN1593, DICHLOROMETHANE, 6.1, III
Hazard Labels	6.1
Limited Quantity	5 L
Ventilation	VE02

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL	All components are listed either on the DSL or NDSL.
IECSC	-

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) of processed (as defined in TSCA section 3(13)) for consumer paint and coating removal.

US Federal Regulations

SARA 313
Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Dichloromethane - 75-09-2	75-09-2	60 - 100	0.1
Methyl alcohol - 67-56-1	67-56-1	1 - 5	1.0
Xylene, mixed isomers - 1330-20-7	1330-20-7	1 - 5	1.0
Ethylbenzene - 100-41-4	100-41-4	0.1 - 1	0.1
Ammonia - 7664-41-7	7664-41-7	0.1 - 1	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)
This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Dichloromethane 75-09-2		X	X	
Xylene, mixed isomers 1330-20-7	100 lb			X
Ethylbenzene 100-41-4	1000 lb	X	X	X
Ammonia 7664-41-7	100 lb			X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Dichloromethane 75-09-2	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Methyl alcohol 67-56-1	5000 lb		RQ= 2270 kg final RQ RQ= 5000 lb final RQ
Xylene, mixed isomers 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Ethylbenzene 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Ammonia 7664-41-7	100 lb	100 lb	RQ 100 lb final RQ RQ 45.4 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Dichloromethane - 75-09-2	Carcinogen
Methyl alcohol - 67-56-1	Developmental
Ethylbenzene - 100-41-4	Carcinogen

U.S. State Right-to-Know Regulations

.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Dichloromethane 75-09-2	X	X	X	X	X
Methyl alcohol 67-56-1	X	X	X	X	X
Xylene, mixed isomers 1330-20-7	X	X	X	X	X
Dipropylene glycol monomethyl ether 34590-94-8	X	X	X	X	X
Ethylbenzene 100-41-4	X	X	X	X	X
Ammonia 7664-41-7	X	X	X	X	

International Regulations

Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Dichloromethane 75-09-2 (60 - 100)	A3	Mexico: TWA 100 ppm Mexico: TWA 330 mg/m^3 Mexico: STEL 500 ppm Mexico: STEL 1740 mg/m^3
Methyl alcohol 67-56-1 (1 - 5)		Mexico: TWA= 200 ppm Mexico: TWA= 260 mg/m^3 Mexico: STEL= 250 ppm Mexico: STEL= 310 mg/m^3
Xylene, mixed isomers 1330-20-7 (1 - 5)		Mexico: TWA 100 ppm Mexico: TWA 435 mg/m^3 Mexico: STEL 150 ppm Mexico: STEL 655 mg/m^3
Dipropylene glycol monomethyl ether 34590-94-8 (1 - 5)		Mexico: TWA 100 ppm Mexico: TWA 60 mg/m^3 Mexico: STEL 150 ppm Mexico: STEL 900 mg/m^3

Ethylbenzene 100-41-4 (0.1 - 1)		Mexico: TWA 100 ppm Mexico: TWA 435 mg/m³ Mexico: STEL 125 ppm Mexico: STEL 545 mg/m³
Ammonia 7664-41-7 (0.1 - 1)		Mexico: TWA 25 ppm Mexico: TWA 18 mg/m³ Mexico: STEL 35 ppm Mexico: STEL 27 mg/m³

Mexico - Occupational Exposure Limits - Carcinogens
A3 - Confirmed Animal Carcinogen

Canada
WHMIS Hazard Class
Not determined

16. OTHER INFORMATION

NFPA	**Health Hazards** 3	**Flammability** 1	**Instability** 0	**Physical and Chemical Hazards** -
HMIS	**Health Hazards** * 3	**Flammability** 1	**Physical Hazard** 0	**Personal Protection** X

Chronic Hazard Star Legend * = Chronic Health Hazard

Prepared By
Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Revision Date 29-May-2015
Revision Note No information available

Disclaimer
The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet