# Safety Data Sheet

**Revision Number:** 012.0

**Issue date:** 06/04/2025

## 1. IDENTIFICATION

**Product name:** LOCTITE® 515™ FLANGE SEALANT GASKET ELIMINATOR®

**IDH number:** 256973

**Product type/ Recommended use:** Anaerobic Adhesive

**Item number:** 33422

**Restriction of Use:** None identified

**Region:** United States

**Company address:**
Henkel Corporation
One Henkel Way
Rocky Hill, Connecticut 06067

**Contact information:**
Telephone: +1 (860) 571-5100
MEDICAL EMERGENCY Phone: Poison Control Center
1-877-671-4608 (toll free) or 1-303-592-1711
TRANSPORT EMERGENCY Phone: CHEMTREC
1-800-424-9300 (toll free) or 1-703-527-3887
MEDICAL EMERGENCY Phone: Poison Control Center
1-877-671-4608 (toll free) or 1-303-592-1711
TRANSPORT EMERGENCY Phone: CHEMTREC
1-800-424-9300 (toll free) or 1-703-527-3887
Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

| EMERGENCY OVERVIEW | |
|---|---|
| DANGER: | H315 - CAUSES SKIN IRRITATION.<br>H317 - MAY CAUSE AN ALLERGIC SKIN REACTION.<br>H318 - CAUSES SERIOUS EYE DAMAGE.<br>H351 - SUSPECTED OF CAUSING CANCER.<br>H373 - MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE. |

| HAZARD CLASS | HAZARD CATEGORY |
|---|---|
| SKIN IRRITATION | 2 |
| SERIOUS EYE DAMAGE | 1 |
| SKIN SENSITIZATION | 1 |
| CARCINOGENICITY | 2 |
| SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE | 2 |

**PICTOGRAM(S)**



**Precautionary Statements**

**Prevention:**
P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P260 - Do not breathe vapors, mist, or spray.
P264 - Wash affected area thoroughly after handling.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P280 - Wear protective gloves, clothing, eye and face protection.

**Response:**
P302+P352 - IF ON SKIN: Wash with plenty of water.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - IF exposed or concerned: Get medical attention.
P333+P313 - If skin irritation or rash occurs: Get medical attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.

**Storage:**
P405 - Store locked up.

**Disposal:**
P501 - Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

**Other hazards** Not available.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

**See Section 11 for additional toxicological information.**

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s) | CAS Number | Weight %* |
|---|---|---|
| Silica, amorphous, fumed, cryst.-free | 112945-52-5 | 5 - 10 |
| Acrylic acid | 79-10-7 | 1 - 5 |
| Cumene hydroperoxide | 80-15-9 | 1 - 5 |
| 2-Hydroxyethyl methacrylate | 868-77-9 | 0.1 - 1 |
| 1-Acetyl-2-phenylhydrazine | 114-83-0 | 0.1 - 1 |

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

## 4. FIRST AID MEASURES

### First Aid Measures by likely routes of exposure

**Inhalation:** Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

**Skin contact:** Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Wash clothing before reuse. Get medical attention.

**Eye contact:** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

**Ingestion:** DO NOT induce vomiting unless directed to do so by medical personnel. Get medical attention.

**Most important symptoms and effects (acute and delayed):** The most important known symptoms and effects, both acute and delayed, are described in Section 11: Toxicological Information.

**Indication of any immediate medical attention / special treatment needed:** Not available.

## 5. FIRE FIGHTING MEASURES

**Extinguishing media:** Water spray (fog), foam, dry chemical or carbon dioxide.

**Improper extinguishing agents:** Not available.

**Special firefighting procedures:** Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray.

**Unusual fire or explosion hazards:** Uncontrolled polymerization may occur at high temperatures resulting in explosions or rupture of storage containers.

**Hazardous combustion products:** Oxides of sulfur. Oxides of carbon. Oxides of nitrogen. Irritating organic vapours.

## 6. ACCIDENTAL RELEASE MEASURES

**Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.**

**Environmental precautions:** Do not allow product to enter sewer or waterways.

**Clean-up methods:** Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean-up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

## 7. HANDLING AND STORAGE

**Handling:** Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. Refer to Section 8.

**Storage:** For safe storage, store between 0 °C (32°F) and 32 °C (89.6 °F)
Keep in a cool, well ventilated area away from heat, sparks and open flame.
Keep container tightly closed until ready for use.

**For information on product shelf life, please review labels on container or check the Technical Data Sheet.**

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.**

| Hazardous Component(s) | ACGIH TLV | OSHA PEL | AIHA WEEL | OTHER |
|---|---|---|---|---|
| Silica, amorphous, fumed, cryst.-free | 3 mg/m3 TWA Respirable particles.<br>10 mg/m3 TWA Inhalable particles. | 20 MPPCF TWA<br>0.8 mg/m3 TWA<br>50 MPPCF TWA Total dust.<br>5 mg/m3 TWA Respirable fraction.<br>15 mg/m3 TWA Total dust.<br>15 MPPCF TWA Respirable fraction. | None | None |
| Acrylic acid | 2 ppm TWA (SKIN) | None | None | 1 ppm TWA<br>3 ppm STEL (SKIN) |
| Cumene hydroperoxide | None | None | 1 ppm (6 mg/m3) TWA (SKIN) | None |
| methacrylic acid | 20 ppm TWA | None | None | None |

**Engineering controls:** Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

**Respiratory protection:** Use NIOSH approved respirator if there is potential to exceed exposure limit(s). Use an organic vapor respirator for concentrations exceeding the Occupational Exposure Limit.

**Eye/face protection:** Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

**Skin protection:** Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact. Neoprene gloves.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical state:** Gel, Liquid
**Color:** Purple
**Odor:** Sharp
**Odor threshold:** Not available.
**pH:** Not applicable, Product is non-polar/aprotic.
**Vapor pressure:** < 10 mm hg (20 °C (68°F)) < 300 mbar (50 °C (122°F)) no method / method unknown < 0.13 mbar (20 °C (68°F))
**Boiling point/range:** > 150 °C (> 302°F)
**Melting point/ range:** Not applicable, Product is a liquid
**Density/Relative density:** 1.1
**Relative vapor density:** > 1 20 °C
**Flash point:** > 100 °C (> 212°F)

| | |
|---|---|
| **Flammable/Explosive limits - lower:** | Not available. |
| **Flammable/Explosive limits - upper:** | Not available. |
| **Autoignition temperature:** | Not available. |
| **Flammability:** | The product is not flammable. |
| **Evaporation rate:** | Not available. |
| **Solubility:** | Slight Water |
| **Partition coefficient n-octanol/water (logarithmic value):** | Not available. |
| **VOC content:** | 1.41 %; 15.4 g/l |
| **Dynamic viscosity:** | Not available. |
| **Kinematic viscosity:** | > 20.5 mm2/s |
| **Particle characteristics:** | Not applicable, Product is a liquid |
| **Decomposition temperature:** | Not available. |

## 10. STABILITY AND REACTIVITY

| | |
|---|---|
| **Stability:** | Stable under normal conditions of storage and use. |
| **Hazardous reactions:** | None under normal processing. Polymerization may occur at elevated temperature or in the presence of incompatible materials. |
| **Hazardous decomposition products:** | Oxides of sulfur. Oxides of carbon. Oxides of nitrogen. Irritating organic vapours. |
| **Incompatible materials:** | Strong oxidizing agents. |
| **Reactivity:** | Not available. |
| **Conditions to avoid:** | Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from incompatible materials. |

## 11. TOXICOLOGICAL INFORMATION

**Likely routes of exposure:** Skin, Inhalation, Eyes, Ingestion

**Potential Health Effects/Symptoms**

**Inhalation:** Inhalation of vapors or mists of the product may be irritating to the respiratory system. May cause nose, throat and lung irritation.
**Skin contact:** May cause allergic skin reaction. This product may be severely irritating to the skin.
**Eye contact:** Causes serious eye damage.
**Ingestion:** May cause gastrointestinal tract irritation if swallowed.

| Hazardous Component(s) | LD50s and LC50s |
|---|---|
| Silica, amorphous, fumed, cryst.-free | None |
| Acrylic acid | Oral LD50 (Rat) = 33.5 mg/kg<br>Oral LD50 (Mouse) = 2,400 mg/kg<br>Oral LD50 (Rat) = 2.5 g/kg<br>Oral LD50 (Rat) = 193 mg/kg<br>Oral LD50 (Rat) = 1,250 mg/kg<br>Inhalation LC50 (Rat, 4 h) = 3.6 mg/l<br>Inhalation LC50 (Rat, 4 h) = > 3.9 - < 4.8 mg/l<br>Inhalation LC50 (Rat, 4 h) = > 5.1 mg/l |
| Cumene hydroperoxide | None |
| 2-Hydroxyethyl methacrylate | Oral LD50 (Rat) = 11.2 g/kg<br>Oral LD50 (Rat) = 5,050 mg/kg |
| 1-Acetyl-2-phenylhydrazine | Oral LD50 (Mouse) = 270 mg/kg |

| Hazardous Component(s) | Immediate Health Effects | Delayed Health Effects | Chronic Health Effects |
|---|---|---|---|
| Silica, amorphous, fumed, cryst.-free | | | |
| Acrylic acid | Corrosive<br>Irritant | Allergen | Kidney<br>Liver |
| Cumene hydroperoxide | Corrosive<br>Irritant | Allergen | Central nervous system<br>Mutagen |
| 2-Hydroxyethyl methacrylate | Irritant | Allergen | |
| 1-Acetyl-2-phenylhydrazine | | Allergen | Blood<br>Kidney<br>Mutagen<br>Some evidence of carcinogenicity |

| Hazardous Component(s) | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|---|---|---|---|
| Silica, amorphous, fumed, cryst.-free | No | No | No |
| Acrylic acid | No | No | No |
| Cumene hydroperoxide | No | No | No |
| 2-Hydroxyethyl methacrylate | No | No | No |
| 1-Acetyl-2-phenylhydrazine | No | No | No |

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

**Information provided is for unused product only.**

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

**U.S. Department of Transportation Ground (49 CFR)**
**Proper shipping name:** RQ, Environmentally hazardous substance, liquid, n.o.s.
**Hazard class or division:** 9
**Identification number:** UN 3082
**Packing group:** III
**DOT Hazardous Substance(s):** alpha,alpha-Dimethylbenzylhydroperoxide

**International Air Transportation (ICAO/IATA)**

| | |
|---|---|
| **Proper shipping name:** | RQ, Environmentally hazardous substance, liquid, n.o.s. |
| **Hazard class or division:** | 9 |
| **Identification number:** | UN 3082 |
| **Packing group:** | III |

**Water Transportation (IMO/IMDG)**

| | |
|---|---|
| **Proper shipping name:** | RQ, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. |
| **Hazard class or division:** | 9 |
| **Identification number:** | UN 3082 |
| **Packing group:** | III |

## 15. REGULATORY INFORMATION

**United States Regulatory Information**

| | |
|---|---|
| **TSCA 8 (b) Inventory Status:** | All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory. |
| **TSCA 12 (b) Export Notification:** | None above reporting de minimisNone above reporting de minimis |
| **CERCLA/SARA Section 302 EHS:** | None above reporting de minimis. |
| **CERCLA/SARA Section 311/312:** | Please refer to the GHS classification in Section 2 |
| **CERCLA/SARA Section 313:** | This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Acrylic acid (CAS# 79-10-7). Cumene hydroperoxide (CAS# 80-15-9). Saccharin (CAS# 81-07-2). |
| **CERCLA Reportable quantity:** | Cumene hydroperoxide (CAS# 80-15-9) 10 lbs. (4.54 kg) |
| **California Proposition 65:** | This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. |

**Canada Regulatory Information**

| | |
|---|---|
| **CEPA DSL/NDSL Status:** | Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details. |

## 16. OTHER INFORMATION

**This safety data sheet contains changes from the previous version in sections:** 3,8,9,11

**Prepared by:** Product Safety and Regulatory Affairs

**Issue date:** 06/04/2025

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.