Power Clean Aerosol

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard
Revision date: 7/19/2024 Supersedes: 6/6/2024 Version: 2.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Power Clean Aerosol
Product code : PC-100-12C

1.2. Recommended use and restrictions on use

Recommended use : Mold cleaner
Restrictions on use : None known

1.3. Supplier

Nanoplas Inc.
2950 Prairie Street South West
Suite 900
Grandville, MI, 49418
T (616)-452-3707
info@nanomoldcoating.com

1.4. Emergency telephone number

Emergency number : For Chemical Emergency Call INFOTRAC 24hr/day 7days/week
(collect calls accepted)
Within USA, Mexico and Canada: 800-535-5053 ID# 102222
Outside USA, Mexico and Canada: 1-352-323-3500 ID# 102222

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable aerosol Category 1	H222	Extremely flammable aerosol
	H229	Pressurized container: may burst if heated
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Eye irritation Category 2	H319	Causes serious eye irritation
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Germ cell mutagenicity Category 2	H341	Suspected of causing genetic defects
Carcinogenicity Category 1A	H350	May cause cancer
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger
Hazard statements (GHS US) : H222 - Extremely flammable aerosol
H229 - Pressurized container: may burst if heated
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction

		H319 - Causes serious eye irritation H336 - May cause drowsiness or dizziness H341 - Suspected of causing genetic defects H350 - May cause cancer
Precautionary statements (GHS US)	:	P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Pressurized container: Do not pierce or burn, even after use. P261 - Avoid breathing spray, vapors, gas. P264 - Wash hands thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing must not be allowed out of the workplace. P280 - Wear protective gloves, protective clothing, eye protection. P302+P352 - If on skin: Wash with plenty of water. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. P312 - Call a poison center or doctor if you feel unwell. P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice/attention. P308+P313 - If exposed or concerned: Get medical advice/attention. P403 - Store in a well-ventilated place. P405 - Store locked up. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P501 - Dispose of contents/container to a hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : None known.

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
trichloroethylene, trichloroethene	CAS-No.: 79-01-6	80-90
Propan-2-ol, isopropyl alcohol, isopropanol	CAS-No.: 67-63-0	1-10
Carbon dioxide (CO2)	CAS-No.: 124-38-9	1-5
1,2-epoxybutane	CAS-No.: 106-88-7	0.1-<1.0

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret
Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Move the affected person to fresh air. If experiencing respiratory symptoms: Call a poison center or a doctor.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Immediately rinse with plenty of water (for at least 15 minutes). Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness. May cause cancer. Suspected of causing genetic defects.

Inhalation : High concentration of vapors may induce: headache, nausea, dizziness. May cause minor irritation to the respiratory tract and to other mucous membranes. Intentional abuse may be harmful or fatal.

Skin : Causes skin irritation. May cause an allergic skin reaction.

Eyes : Causes serious eye irritation.

Ingestion : May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic symptoms : May cause cancer. Suspected of causing genetic defects.

4.3. Immediate medical attention and special treatment, if necessary

Not required. Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use dry chemical, CO2, water spray or alcohol-resistant foam.

Unsuitable extinguishing media : None.

5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol. Keep away from open flames, hot surfaces and sources of ignition. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors. Exposure to fire may cause containers to rupture/explode.

Explosion hazard : Contains gas under pressure; may explode if heated. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

Hazardous decomposition products in case of fire : Toxic fumes may be released. May produce hydrogen chlorides, hydro chloric acid, chlorine gas, phosgene, and carbon oxides.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. On heating, there is a risk of bursting due to internal pressure build-up. Cool down the containers exposed to heat with a water spray.

Protection during firefighting : Use shielding to protect from bursting cans. Do not attempt to take action without suitable protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate all ignition sources. Ventilate area. Wear suitable protective clothing. Avoid contact with eyes, skin and clothing.

6.1.1. For non-emergency personnel

Emergency procedures : No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Avoid breathing gas, spray, vapors.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Leaking cans should be placed in a plastic bag or open pail until the pressure has dissipated. Absorb and/or contain spill with inert material, then place in suitable container. Notify authorities if product enters sewers or public waters.

Other information : Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : U.F.C. (NFPA 30B) Level I Aerosol.

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact with eyes, skin and clothing. Avoid breathing vapors, spray, gas. Ensure adequate ventilation. Use only outdoors or in a well-ventilated area. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Unplug electrical tools, motors, and appliances before spraying or bringing the can near any source of electricity. Electricity can burn a hole in the can and cause contents to burst into flames. To avoid serious burn injury, do not let the can touch battery terminals, electrical connections on motors or appliances, or any other source of electricity. Pressurized container: Do not pierce or burn, even after use. Wash hands with water and soap.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a cool, well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up.

Incompatible materials : Strong oxidizers. Direct sunlight. Sources of ignition.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

trichloroethylene, trichloroethene (79-01-6)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Trichloroethylene
ACGIH OEL TWA	10 ppm
ACGIH OEL STEL	25 ppm
Remark (ACGIH)	TLV® Basis: CNS impair; cognitive decrements; renal toxicity. Notations: A2 (Suspected Human Carcinogen); BEI
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Trichloroethylene
OSHA PEL (TWA)	100 ppm
OSHA PEL (Ceiling)	200 ppm
Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift	300 ppm 5 mins. in any 2 hrs.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-2

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
USA - ACGIH - Occupational Exposure Limits	
Local name	2-Propanol
ACGIH OEL TWA	200 ppm
ACGIH OEL STEL	400 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2024
USA - ACGIH - Biological Exposure Indices	
Local name	2-Propanol
BEI (BLV)	40 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift at end of workweek - Notations: B, Ns
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Isopropyl alcohol
OSHA PEL (TWA)	980 mg/m³
	400 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

Carbon dioxide (CO_2) (124-38-9)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Carbon dioxide

Carbon dioxide (CO2) (124-38-9)	
ACGIH OEL TWA	5000 ppm
ACGIH OEL STEL	30000 ppm
Remark (ACGIH)	TLV® Basis: Asphyxia
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Carbon dioxide
OSHA PEL (TWA)	9000 mg/m³
	5000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide adequate general and local exhaust ventilation. No particular/specific measures required.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear impervious gloves.

Eye protection:

Chemical goggles

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection. In operations where exposure limits are exceeded or exposure levels are excessive, an approved respirator should be used. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Clear, colorless liquid.
Color : Colorless Clear
Odor : Solvent
Odor threshold : No data available
pH : No data available
Melting point : Not applicable
Freezing point : No data available
Boiling point : No data available
Flash point : 12 °C Based on data available for ingredients
Relative evaporation rate (butyl acetate=1) : No data available
Flammability (solid, gas) : Extremely flammable aerosol.
Vapor pressure : No data available

Relative vapor density at 20°C	:	No data available
Relative density	:	1.362
Solubility	:	Negligible.
Partition coefficient n-octanol/water (Log Pow)	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity, kinematic	:	No data available
Viscosity, dynamic	:	No data available
Explosion limits	:	No data available
Explosive properties	:	Pressurized container: may burst if heated.
Oxidizing properties	:	No data available
Particle Characteristics		Not applicable

9.2. Other information

VOC content	:	95.43 %

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions. May decompose under ultra violet light.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Keep away from open flames, hot surfaces and sources of ignition. May decompose under ultra violet light. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture or incinerate containers.

10.5. Incompatible materials

Keep away from oxidizers, strong acids and strong bases.

10.6. Hazardous decomposition products

May produce hydrogen chlorides, hydro chloric acid, chlorine gas, phosgene, and carbon oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	:	Not classified
Acute toxicity (dermal)	:	Not classified
Acute toxicity (inhalation)	:	Not classified

trichloroethylene, trichloroethene (79-01-6)	
LD50 oral rat	5620 mg/kg
LD50 dermal rabbit	> 20000 mg/kg
LC50 Inhalation - Rat	67.17 mg/l/4h
LC50 Inhalation - Rat [ppm]	12500 ppm Animal: rat, Animal sex: male

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
LD50 oral rat	5840 mg/kg
LD50 dermal rabbit	16.4 ml/kg
LC50 Inhalation - Rat [ppm]	1666.66 ppm/1h

1,2-epoxybutane (106-88-7)	
LD50 oral rat	900 mg/kg
LD50 dermal rabbit	1.77 ml/kg
LC50 Inhalation - Rat	> 6.3 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Suspected of causing genetic defects.

Carcinogenicity : May cause cancer.

trichloroethylene, trichloroethene (79-01-6)	
NOAEL (chronic,oral,animal/male,2 years)	1000 mg/kg body weight Animal: mouse, Animal sex: male, Remarks on results: not determinable
NOAEL (chronic,oral,animal/female,2 years)	1000 mg/kg body weight Animal: mouse, Animal sex: female, Remarks on results: not determinable
IARC group	1 - Carcinogenic to humans
National Toxicity Program (NTP) Status	Known Human Carcinogens

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
IARC group	3 - Not classifiable

1,2-epoxybutane (106-88-7)	
IARC group	2B - Possibly carcinogenic to humans

Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness.

trichloroethylene, trichloroethene (79-01-6)	
STOT-single exposure	May cause drowsiness or dizziness.

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
STOT-single exposure	May cause drowsiness or dizziness.

1,2-epoxybutane (106-88-7)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : Not classified

trichloroethylene, trichloroethene (79-01-6)	
NOAEL (oral,rat,90 days)	50 mg/kg body weight Animal: rat, Animal sex: male

Aspiration hazard : Not classified

Viscosity, kinematic : No data available

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
Viscosity, kinematic	2.58 mm²/s

Symptoms/effects : Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness. May cause cancer. Suspected of causing genetic defects.

Inhalation	:	High concentration of vapors may induce: headache, nausea, dizziness. May cause minor irritation to the respiratory tract and to other mucous membranes. Intentional abuse may be harmful or fatal.
Skin	:	Causes skin irritation. May cause an allergic skin reaction.
Eyes	:	Causes serious eye irritation.
Ingestion	:	May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	:	May cause cancer. Suspected of causing genetic defects.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

trichloroethylene, trichloroethene (79-01-6)	
LC50 - Fish [1]	16 mg/l
EC50 - Crustacea [1]	14 mg/l
LC50 - Fish [2]	28.3 mg/l
EC50 - Crustacea [2]	20.8 mg/l
EC50 72h - Algae [1]	36.5 mg/l
NOEC chronic fish	5.76 mg/l Test organisms (species): Jordanella floridae Duration: '10 d'

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
LC50 - Fish [1]	10000 mg/l Pimephales promelas (Fathead minnow)
EC50 - Crustacea [1]	> 10000 mg/l
LC50 - Fish [2]	9640 mg/l Pimephales promelas (Fathead minnow)
NOEC chronic crustacea	3.37 mg/l

12.2. Persistence and degradability

Power Clean Aerosol	
Persistence and degradability	No additional information available.

trichloroethylene, trichloroethene (79-01-6)	
Persistence and degradability	Not readily biodegradable.

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
Persistence and degradability	Readily biodegradable.

Carbon dioxide (CO2) (124-38-9)	
Persistence and degradability	Biodegradation is not applicable to inorganic compounds..

1,2-epoxybutane (106-88-7)	
Persistence and degradability	Readily biodegradable, failing 10-d window..

12.3. Bioaccumulative potential

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
BCF - Fish [1]	3
Partition coefficient n-octanol/water (Log Kow)	0.05

12.4. Mobility in soil

Propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.5

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with DOT / IMDG / IATA

DOT	IMDG	IATA
14.1. UN number		
1950	1950	1950
14.2. Proper Shipping Name		
Aerosols	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)		
2.1	2.1	2.1
		
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available		

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN1950
DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx) : 306
DOT Packaging Non Bulk (49 CFR 173.xxx) : None
DOT Packaging Bulk (49 CFR 173.xxx) : None
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg

DOT Vessel Stowage Location	:	A - The material may be stowed ‘‘on deck’’ or ‘‘under deck’’ on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	:	25 - Protected from sources of heat,87 - Stow ‘‘separated from’’ Class 1 (explosives) except Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

IMDG

Special provision (IMDG)	:	63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	:	P207, LP200
Packing provisions (IMDG)	:	PP87, L2
EmS-No. (Fire)	:	F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	:	S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	:	None
Stowage and handling (IMDG)	:	SW1, SW22
Segregation (IMDG)	:	SG69

IATA

PCA Excepted quantities (IATA)	:	E0
PCA Limited quantities (IATA)	:	Y203
PCA limited quantity max net quantity (IATA)	:	30kgG
PCA packing instructions (IATA)	:	203
PCA max net quantity (IATA)	:	75kg
CAO packing instructions (IATA)	:	203
CAO max net quantity (IATA)	:	150kg
Special provision (IATA)	:	A145, A167, A802
ERG code (IATA)	:	10L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Power Clean Aerosol	
SARA Section 311/312 Hazard Classes	Refer to Section 2 for OSHA Hazard Classification.

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.		
Contains chemical(s) subject to TSCA 12b export notification if product is shipped outside the U.S		
trichloroethylene, trichloroethene	CAS-No. 79-01-6	80-90%

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.		
trichloroethylene, trichloroethene	CAS-No. 79-01-6	80-90%

trichloroethylene, trichloroethene (79-01-6)	
Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	100 lb

1,2-epoxybutane (106-88-7)
Listed on EPA Hazardous Air Pollutant (HAPS)

1,2-epoxybutane (106-88-7)	
CERCLA RQ	100 lb

15.2. International regulations

No additional information available

15.3. US State regulations

WARNING: This product can expose you to Trichloroethylene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.


Component	State or local regulations
trichloroethylene, trichloroethene(79-01-6)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - New Jersey - Right to Know Hazardous Substance List
Propan-2-ol, isopropyl alcohol, isopropanol(67-63-0)	U.S. - New Jersey - Right to Know Hazardous Substance List
Carbon dioxide (CO2)(124-38-9)	U.S. - New Jersey - Right to Know Hazardous Substance List
1,2-epoxybutane(106-88-7)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

According to 29CFR 1910.1200 OSHA Hazard Communication Standard
Revision date : 7/19/2024

Full text of H-phrases	
H222	Extremely flammable aerosol
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H341	Suspected of causing genetic defects
H350	May cause cancer

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA fire hazard : 4 - Materials that rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and burn readily.
NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating
Health : 2 Moderate Hazard - Temporary or minor injury may occur
: * - Chronic (long-term) health effects may result from repeated overexposure
Flammability : 2 Moderate Hazard

Physical	:	0 Minimal Hazard

Indication of changes:
revised edition. All chapters have been modified since the previous version.

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.