ENTERPRISE ARCHITECTURAL SPECIFICATION & USER MANUAL

Criation UI

A Unified React 18+ Design System, Fluent English Chaining DSL, and Enterprise Component Framework

SYSTEM RELEASE

v0.2.1 (Production Ready)

AUTHOR & PROPRIETOR

Divyanshu Kumar (@Atomic-Quark)

CONTACT & INQUIRIES

143479650+Atomic-Quark@users.noreply.github.com

REPOSITORY

https://github.com/Atomic-Quark/Criation-UI

MIT OPEN SOURCE LICENSE • DIVYANSHU KUMAR

Criation UI is released under the permissive MIT License. Full commercial and private developer rights granted.

📄 Criation UI: Comprehensive Architectural Specification & Official User Manual

A Unified React Design System, Fluent English Chaining DSL, and Enterprise Component Framework

---

Document Metadata	Specification Details
System Title	Criation UI Design System & Component Library
Current Release	**v0.3.0** (Production Enterprise Release)
Author & Lead Architect	**Divyanshu Kumar** (@Atomic-Quark)
Author Contact	`143479650+Atomic-Quark@users.noreply.github.com`
Copyright Notice	Copyright © 2026 Divyanshu Kumar. All Rights Reserved.
Legal Framework	MIT Open Source License (Permissive Commercial & Private Use)
Target Runtimes	React 18+, Next.js 15/16 (App Router & Pages Router), Vite, Remix
Language & Engine	TypeScript 5.7+ (100% Strongly Typed), Precompiled CSS Custom Properties

---

📑 Table of Contents

1. Abstract & Executive Overview
2. Architectural Foundation & Core Philosophy
3. The Four Expressive Modalities
    - 3.1 Modality 1: Conventional JSX Component API (Recommended Default)
    - 3.2 Modality 2: Decoupled Fluent Builder (`ui.*` Namespace)
    - 3.3 Modality 3: Strongly-Typed Options Objects (Deprecating Ambiguous Positional Slots)
    - 3.4 Modality 4: Explicit Natural-Language DSL (`describe` / `parseDSL`)
4. What Is There: Complete Component & Hook Inventory
    - 4.1 Core & Typography Primitives
    - 4.2 Form & Interactive Input Primitives
    - 4.3 Layout, Containers & Grid Primitives
    - 4.4 Feedback, Indicators & Overlays
    - 4.5 Navigation & App Scaffolds
    - 4.6 Complete React Hooks Suite
    - 4.7 Utility Helpers & Parsers
5. What Changed & What Was Fixed: v0.1.0 vs v0.2.0/v0.2.1

    - 5.1 Component Bug Fixes & Hardening
    - 5.2 Accessibility (WAI-ARIA) & Focus Management
    - 5.3 Core Builders & Key Handling
    - 5.4 Asynchronous Remote Search & Stale Request Cancellation
    - 5.5 Declarative Tables & Controlled Accordions
    - 5.6 The Typed `useForm` Engine
    - 5.7 Next.js App Router Client Boundary
    - 5.8 The Open-Source MIT License Transition
6. How It Works Under the Hood
    - 6.1 Fluent Parsing & AST Token Extraction Engine
    - 6.2 Positional Slot Inference Algorithm
    - 6.3 WAI-ARIA Focus Trap & Focus Restoration Mechanism
    - 6.4 Reactive Cross-Tab Storage Bus
7. Official Developer User Manual: Step-by-Step Practical Recipes
    - 7.1 Installation & Setup
    - 7.2 Recipe: Rapid 3-Line Website Construction
    - 7.3 Recipe: Production Authentication Form with `useForm`
    - 7.4 Recipe: Declarative Table with Custom Column Formatters
    - 7.5 Recipe: Asynchronous Autocomplete with Stale Request Protection
    - 7.6 Recipe: Accessible Overlays (Modal, Drawer, AlertDialog)
    - 7.7 Recipe: Cross-Tab Synchronized Local State
    - 7.8 Recipe: Next.js 14/15 App Router Clean Integration
8. Comparative Analysis: The Difference
    - 8.1 Criation UI vs. Tailwind CSS
    - 8.2 Criation UI vs. Material UI & Chakra UI
    - 8.3 Criation UI vs. Shadcn/ui
9. Open-Source Licensing & Commercial Developer Rights (MIT License)
10. Troubleshooting, Edge Cases & FAQ

---

1. Abstract & Executive Overview

Modern web frontend development has reached an unsustainable level of boilerplate. Developers spend a disproportionate amount of time authoring repetitive JSX tags, managing unstandardized property names, binding accessible keyboard handlers, handling responsive styles through ad-hoc classes, and debugging race conditions in form state and asynchronous select widgets.

Criation UI is an enterprise-grade React design system, UI engine, and component library authored and owned solely by **Divyanshu Kumar** (`Atomic-Quark`). It eliminates frontend friction through a dual-engine architecture:

1. **The Native JSX Engine**: A battle-tested suite of 50+ fully accessible (WAI-ARIA compliant) React primitives and 14 reactive hooks.
2. **The Fluent English Chaining DSL**: A domain-specific language that allows developers to write user interfaces as naturally as writing an English sentence—either via chained method calls (`Button("Submit").green().large().link("/dashboard")`) or natural English phrases (`Button("Submit order, green, large, to /dashboard")`) or ultra-concise 1-line shorthands.

This whitepaper and user manual serves as the definitive reference manual for understanding, implementing, and deploying Criation UI v0.2.1.

---

2. Architectural Foundation & Core Philosophy

2.1 The Problem Space

- **Tag Fatigue**: Writing `<button className="..." onClick={...}><span>Submit</span></button>` dozens of times slows prototyping to a crawl.
- **Inconsistent Prop Surfaces**: One component accepts `size="lg"`, another accepts `fontSize="18px"`, while another accepts `dimension="large"`.
- **Accessibility Blindspots**: Standard overlays frequently fail to trap keyboard focus, allow focus to escape into hidden background DOM nodes, or fail to restore focus to trigger elements upon dismissal.
- **Async State Regressions**: Search inputs that do not cancel or ignore stale out-of-order network responses cause incorrect results to overwrite fresh searches.

2.2 The Criation UI Core Axioms

Criation UI is designed according to five architectural pillars:

1. **Human Readability as First Principle**: Writing code should feel like writing natural English. If a human can describe the button ("A large red button that links to checkout"), they can write it in code identically: `Button("Checkout").red().large().link("/checkout")`.
2. **Zero Mandatory Configuration**: Every property, slot, and argument across all 50+ components is 100% optional. Default fallbacks ensure elements look visually striking without specifying any props.
3. **Ironclad Accessibility (a11y)**: Focus trapping, focus restoration, roving tabindex keyboard navigation, and explicit WAI-ARIA relationship attributes (`aria-controls`, `aria-describedby`, `aria-labelledby`, `role`) are built directly into components.
4. **Clean Separation of Concerns**: Visual styling (`class`, `size`, `color`, `position`) is decoupled from routing destinations (`to`, `href`, `direction`) and authentication policies (`requiredRole`, `fallback`).
5. **Lightweight & Self-Contained**: Powered exclusively by React 18+ and Lucide React. Zero heavy runtime dependencies, zero complex build configs, and zero third-party utility bloat.

---

3. The Four Expressive Modalities

Criation UI provides four distinct expression modalities tailored to team preferences, architectural requirements, and productivity needs:

3.1 Modality 1: Conventional JSX Component API (Recommended Default)

The primary and official API for production applications. Standard, idiomatic React 18+ JSX components with full TypeScript prop validation, complete tree-shaking support, and accessible WAI-ARIA semantics:

```
import React from "react";
import {
  Button,
  TextInput,
  Card,
  Stack,
  Badge,
  ThemeProvider
} from "@criation/ui";

export function UserSettings() {
  return (
    <ThemeProvider defaultTheme="dark">
      <Card variant="glass" padding="xl">
        <Stack direction="column" gap="md">
          <Badge variant="success">Online</Badge>
          <h2>Standard JSX Mode</h2>
          <TextInput placeholder="Enter your username" label="Username" />
          <Button variant="primary" size="lg" onClick={() => console.log("Activated")}>
            Save Changes
          </Button>
        </Stack>
      </Card>
    </ThemeProvider>
  );
}
```

3.2 Modality 2: Decoupled Fluent Builder (`ui.*` Namespace)

An optional, highly expressive builder pattern that decouples method chaining from React component prototypes. It produces immutable React elements via an explicit `.build()` method:

```
import { ui } from "@criation/ui";

const SaveButton = ui.button("Save Changes")
  .primary()
  .large()
  .onClick(() => console.log("Saved"))
  .build();

const HeroHeading = ui.heading("Criation UI Design System")
  .level(1)
  .gradient()
  .center()
  .build();

const FeatureCard = ui.card("Enterprise modular design system")
  .glass()
  .padding("xl")
  .build();
```

3.3 Modality 3: Strongly-Typed Options Objects (Deprecating Ambiguous Positional Slots)

To eliminate parameter-order confusion and enable robust IDE autocomplete, high-level composite builders accept structured options objects rather than positional arguments:

```
import { ui } from "@criation/ui";

// Strongly-typed options object:
const Navigation = ui.navbar({
  brand: "Criation Store",
  links: ["Products", "Pricing", "Documentation", "Contact"]
});

const AppFooter = ui.footer({
  brand: "Criation UI",
  links: ["Privacy Policy", "Terms of Service", "Security"]
});
```

> [!NOTE] **Legacy Positional Parameter Deprecation:** Early alpha versions supported 8-slot positional signatures (e.g. `Button(label, size, id, auth, path, color, pos, ptr)`). While backward-compatible fallbacks remain available in `src/core/shorthand.tsx`, positional signatures are considered legacy. All new development should use standard JSX props or typed options objects.

3.4 Modality 4: Explicit Natural-Language DSL (`describe` / `parseDSL`)

Bounded, opt-in natural-language string parsing designed specifically for rapid wireframing and prototyping. String parsing is strictly isolated behind explicit calls to `describe()` or `parseDSL()`, preventing unintended string coercion in core components:

```
import { describe, parseDSL } from "@criation/ui";

// Bounded natural-language token parsing:
const PrimaryAction = describe("button Get Started primary large");
const HeroTitle = describe("heading Build Faster with Criation UI level 1 gradient center");

// Fault-tolerant parsing with syntax warning fallback:
const CustomElement = parseDSL("button Submit Order blue large");
```

> [!IMPORTANT] **Security & Authentication Boundary Notice:** Frontend authentication helpers and natural-language tokens (e.g., text containing "admin", "auth", or "protected") do NOT secure backend APIs. Authentication and authorization must be enforced by the actual application and identity provider on the server side. Presentation helpers manage UI visibility, disabled states, and navigation transitions only. Never infer security policies or access control rules from UI strings or button labels.

---

4. What Is There: Complete Component & Hook Inventory

4.1 Core & Typography Primitives

- **`Button`**: Full-featured button primitive with variants (`primary`, `secondary`, `outline`, `ghost`, `danger`, `success`, `link`), sizes (`xs`, `sm`, `md`, `lg`, `xl`), full loading state management with accessible spinner, and custom cursor pointer control.

- `IconButton`: Specialized square or circular button designed for standalone icon triggers with accessible labels.
- `ButtonGroup`: Harmonious container for grouping buttons with optional connected borders (`attached`).
- `Heading`: Typography heading (`h1` through `h6`) with linear gradients and responsive font-scaling.
- `Text`: Paragraph, span, or label with weights (`normal`, `medium`, `semibold`, `bold`), colors, and text-truncation.
- `Label`: Form field label with automated asterisk rendering for required inputs.
- `Link`: Internal and external link primitive with automatic `noopener noreferrer` and external icon badges.
- `Code`: Inline code highlights and preformatted code blocks with built-in one-click clipboard copying.

4.2 Form & Interactive Input Primitives

- `Input` / `TextInput`: Foundational input supporting prefix/suffix icons, clear buttons, size tokens, and accessible error message strings.
- `PasswordInput`: Secure password field with built-in toggle to reveal/hide characters.
- `EmailInput`: Auto-configured email field with mail icon and built-in format validation attributes.
- `NumberInput`: Numeric input with min, max, step, and keyboard increment controls.
- `TextArea`: Multi-line text field featuring dynamic `autoResize` based on content `scrollHeight`.
- `SearchInput`: Specialized search field with search icon, clear button, and platform shortcut badges (⌘K / `Ctrl+K`).
- `OTPInput`: Multi-digit verification code input supporting masked PIN display, auto-focus advancement, paste distribution, and dynamic length resizing.
- `Rating`: Interactive or read-only 5-star rating widget with hover states and keyboard arrow adjustments.
- `Combobox`: Single-select searchable autocomplete dropdown with local filtering and remote asynchronous querying.
- `MultiSelect`: Multi-tag select input with removable badge chips and remote search capability.
- `ColorPicker`: Color selection widget featuring visual swatch preview and hex code readout.
- `Select`: Native select element styled with custom chevrons, React-compliant default values, and error messaging.
- `Checkbox`: Custom styled checkbox with title, subtitle description, and indeterminate state support.
- `Radio`: Custom radio options for single-selection choice lists.
- `Switch`: Smooth iOS-style sliding toggle switch for boolean settings.
- `Slider`: Track and thumb range slider with real-time value readout.
- `DatePicker`: Date selector with calendar icon and formatting constraints.
- `FileUpload`: Drag-and-drop file upload zone with file size formatting, dragover animations, and progress readouts.
- `Form`, `FormField`, `FormLabel`, `FormError`, `FormProvider`: Compound declarative form components.

4.3 Layout, Containers & Grid Primitives

- `Box`: Polymorphic container (`as="div" | "section" | "article" | ...`) with direct styling attributes (`padding`, `margin`, `position`, `cursor`, `background`, `color`).
- `Container`: Max-width content boundary with responsive breakpoint centering (`sm`, `md`, `lg`, `xl`, `2xl`, `full`).
- `Stack`: Flexbox layout engine supporting row/column direction, alignment, justification, and uniform gap spacing.
- `Grid`: CSS Grid container supporting column counts, auto-fit responsive column sizing (`minChildWidth`), and grid gap tokens.

- `Flex`: Shorthand flex wrapper with wrapping and alignment presets.
- `AspectRatio`: Responsive aspect ratio box (`16:9`, `4:3`, `1:1`, etc.) preventing layout shifts during asset loads.
- `ScrollArea`: Custom styled scroll container with customized cross-browser scrollbars and height clamping.
- `Collapsible`: Expandable disclosure section with smooth height transition.
- `Card`: Elevated, outlined, or glassmorphic content containers with customizable padding and hover effects.
- `Divider`: Horizontal or vertical separating rule with optional embedded text.
- `Spacer`: Explicit pixel or rem layout spacer.

4.4 Feedback, Indicators & Overlays

- `Alert`: Notification banner with semantic themes (`info`, `success`, `warning`, `danger`) and dismiss actions.
- `Toast`: Contextual, floating notification toasts managed via `useToast()`.
- `Modal`: Accessible dialog overlay featuring backdrop blur, focus trapping, focus restoration, `Escape` dismissal, and root portal rendering.
- `Drawer`: Sliding side sheet panel emerging from `left` or `right` viewport edges with focus trap.
- `AlertDialog`: Confirmation modal with dedicated destructive action buttons and accessible alertdialog role.
- `Popover`: Floating contextual popover with keyboard trigger activation and outside click closing.
- `Tooltip`: Hover helper tooltip powered by leak-free timer refs and automated positioning.
- `ContextMenu`: Right-click desktop menu overlay.
- `Spinner`: Smooth animated circular loading spinner.
- `Skeleton`: Shimmering geometric placeholder simulating content while loading.
- `Progress`: Linear progress bar with percentage readout and color variants.
- `EmptyState`: Zero-data illustration container with action button slots.
- `ErrorState`: Standardized failure view with retry actions.
- `ErrorBoundary`: React class component catching rendering crashes with fallback presentation.

4.5 Navigation & App Scaffolds

- `Navbar`: Responsive header bar with brand logo, nav links, and mobile hamburger drawer.
- `Sidebar`: Vertical collapsible navigation menu with active route tracking.
- `Tabs`: Full WAI-ARIA tabbed switcher supporting roving arrow key navigation and matching tabpanels.
- `Breadcrumbs`: Hierarchical path trail with separator icons.
- `Pagination`: Multi-page selector with previous/next triggers and page number buttons.
- `DropdownMenu`: Pop-out dropdown action list with divider rules.
- `Stepper`: Multi-step wizard indicator tracking progress through numbered phases.
- `Timeline`: Vertical chronological event stream with connecting lines and date tags.
- `Result`: Full-page success, error, or warning status screen with illustrations and action buttons.
- `NotFoundPage`: Production-ready 404 error page with search bar and home navigation.
- `LandingLayout`, `DashboardLayout`, `AuthLayout`, `SettingsLayout`: Full-page responsive layout shells.

4.6 Complete React Hooks Suite

Criation UI includes 14 custom hooks covering state, DOM, lifecycle, and browser capabilities:

1. `useForm<T>`: Full-featured form management hook providing `values`, `errors`, `touched`, `isValid`, `isDirty`, `isSubmitting`, `register`, `handleChange`, `handleBlur`, `handleSubmit`, and `reset`.
2. `useLocalStorage<T>`: Reactive local storage state with automatic cross-tab synchronization and incognito mode safety.
3. `useClipboard`: Clipboard copy utility with ref-tracked timeout resolution preventing state collisions.
4. `useTheme`: Light/Dark mode state with system preference auto-detection.
5. `useDisclosure`: Common boolean disclosure controller (`isOpen`, `onOpen`, `onClose`, `onToggle`).
6. `useDebounce<T>`: Value debouncing hook for throttling search and window inputs.
7. `useClickOutside`: Detects and triggers callbacks for mouse clicks outside a specified element ref.
8. `useMediaQuery`: Reactive CSS media query evaluator matching viewport size changes.
9. `useWindowSize`: Real-time window viewport width and height dimensions.
10. `useOnlineStatus`: Real-time network connectivity monitor (`navigator.onLine`).
11. `useIntersectionObserver`: Viewport visibility tracker for infinite scrolling and lazy loading.
12. `usePrevious<T>`: Tracks the previous state or prop value across renders.
13. `useEventListener`: Managed DOM event listener with automated cleanup on unmount.
14. `useKeyPress`: Keyboard key press detector for global shortcuts (`Escape`, `Enter`, etc.).

4.7 Utility Helpers & Parsers

- `formatFileSize(bytes)`: Converts raw bytes to human-readable format (`KB`, `MB`, `GB`, `TB`).
- `formatDate(date, format)`: Flexible date formatter with relative time support.
- `formatNumber(num, options)`: Currency, percentage, and localized number formatter.
- `validateEmail`, `validateRequired`, `validateUrl`: Reusable validation predicate functions.
- `classNames(...args)`: High-speed conditional class builder (equivalent to `clsx`).
- `throttle(fn, limitMs)`: Execution frequency limiter for scroll and resize handlers.

---

5. What Changed & What Was Fixed: v0.1.0 vs v0.2.0/v0.2.1

A major overhaul was conducted between v0.1.0 and v0.2.1 to transform Criation UI from an experimental component draft into a robust, enterprise-ready, accessible, and legally protected design system.

5.1 Component Bug Fixes & Hardening

Component / Hook	Issue in v0.1.0	Resolution in v0.2.0 / v0.2.1
`Input`	When `error="Required field"` was supplied as a string, no visible DOM text element was rendered; only a red border appeared.	Added `<span className="cr-input__error-message" role="alert">` displaying the exact error text, tied to the input via `aria-describedby`.
`TextArea`	Multi-line textareas did not expand dynamically, causing awkward inner scrollbars. Strings passed to `error` did not display text.	Integrated automated `autoResize` based on `scrollHeight` recalculation on mount and input; added accessible error message text rendering.
`Select`	The placeholder option rendered `<option selected ...>`, which caused React console warnings (`Use defaultValue or value instead`). Error string was not rendered.	Replaced with React-compliant `defaultValue=""` ; added accessible error message text rendering.
`Tooltip`	Timeout identifiers were saved in component state (`useState`), causing race conditions and React state updates on unmounted components during fast pointer movement.	Migrated to `useRef<number
`useClipboard`	Calling `copy(text)` rapidly in succession left stale timers active, causing the `hasCopied` status to prematurely reset to `false` .	Added timer ref tracking (`timeoutRef.current`) that cancels prior timeouts upon each new copy invocation.
`OTPInput`	When the `length` property changed dynamically (e.g., from 4 to 6 digits), internal state remained fixed at the initial length.	Added `useEffect` listening to `length` that dynamically synchronizes the internal `digits` array state.
`useLocalStorage`	Did not synchronize across browser tabs; crashed with a `SecurityError` when accessed inside private/incognito browsing windows.	Added window `storage` and custom `local-storage-sync` event buses; wrapped all storage access in defensive `try/catch` fallbacks.

5.2 Accessibility (WAI-ARIA) & Focus Management

Overlays in v0.1.0 were basic DOM elements placed in the tree without focus constraints. In v0.2.0 and v0.2.1:

- `Modal` & `Drawer` & `AlertDialog` :
  - Implemented the `useFocusTrap` hook, which intercepts `Tab` and `Shift+Tab` key events, ensuring keyboard navigation cycles exclusively within the interactive elements of the active dialog.
  - Added **automatic focus restoration**: when the dialog opens, it saves `document.activeElement` ; when the dialog closes, it seamlessly restores focus to the triggering button or link.
  - Implemented **Root-Level Portal Rendering**: overlays render at `document.body` via `ReactDOM.createPortal(..., document.body)` with SSR safety checks (`typeof document !== "undefined"`), preventing CSS z-index and clipping bugs.
- `Popover` :
  - Added full keyboard activation: pressing `Enter` or `Space` on the trigger opens the popover; pressing `Escape` dismisses it and returns focus to the trigger. Added `role="button"` and `tabIndex={0}` .

- `Tabs`:
  - Implemented the official WAI-ARIA Tabs pattern with roving focus: pressing `ArrowLeft` or `ArrowRight` moves focus between tabs; pressing `Home` or `End` jumps to the first or last tab.
  - Explicitly linked tabs to panels via `aria-controls={panelId}` and `aria-labelledby={tabId}`.

5.3 Core Builders & Key Handling

- `renderWebsite` & `shorthand`:
  - In v0.1.0, rendering arrays of components via `Website(...)` triggered React console warnings (`Each child in a list should have a unique "key" prop`) because elements were cloned repeatedly with ad-hoc keys.
  - In v0.2.0, React keys are systematically assigned at the map boundary (`item.id || "section-${index}"`) without introducing redundant cloning or key instability.
  - Added `WebsiteLayoutOptions`: `createWebsiteLayout` now accepts `maxWidth`, `padding`, `header`, and `footer` customization parameters.

5.4 Asynchronous Remote Search & Stale Request Cancellation

- `Combobox` & `MultiSelect`:
  - Added native support for asynchronous querying via `onSearch?: (query: string) => Promise<ComboboxOption[]>`.
  - Added visual loading spinners and dedicated error message displays.
  - **Stale Request Cancellation**: Implemented `latestRequestIdRef` tracking. If query `A` takes 500ms to resolve, but query `B` was initiated 200ms later and resolves in 100ms, the response from query `A` is automatically discarded, preventing out-of-order network responses from corrupting search results.

5.5 Declarative Tables & Controlled Accordions

- `Table`:
  - In v0.1.0, tables only supported static JSX children (`<thead><tr><th>...`).
  - In v0.2.0, tables accept declarative data configurations: `columns: TableColumn<T>[]` and `data: T[]`. Supports custom column cell formatters (`render: (value, row) => ...`), text alignments (`left`, `center`, `right`), and an `emptyText` fallback for empty data sets, while retaining 100% backward compatibility for raw JSX children.

- `Accordion`:
  - Added controlled behavior via `expandedIds?: string[]` and `onChange?: (ids: string[]) => void`.
  - Maintained uncontrolled behavior via `defaultExpandedIds`.
  - Connected buttons and collapsible regions via accessible `aria-controls` and `aria-labelledby` IDs.

5.6 The Typed `useForm` Engine

A brand-new, enterprise-grade form management hook was authored from scratch in src/forms/useForm.ts:

- **Full Type Safety**: Generically typed with form values `T`.
- **Form State**: Tracks `values`, `errors`, `touched`, `isValid`, `isDirty`, and `isSubmitting`.
- **Validation**: Supports synchronous or asynchronous validation rules returning field-specific error messages.
- **Automation**: `register(name)` helper automatically attaches `name`, `value`, `onChange`, `onBlur`, and `error` attributes to any input.

5.7 Next.js App Router Client Boundary

- **Vite & Rollup Configuration**:
  - In vite.config.lib.ts, added `banner: '"use client";\n'` to the compiled library output.
  - Ensures that when consumers import components from `@criation/ui` inside Next.js 14 or Next.js 15 App Router applications (`app/page.tsx`), the bundler treats them as client components without throwing server component serialization errors.
  - Standardized CSS distribution so both `import "@criation/ui/styles.css"` and `import "@criation/ui/ui.css"` resolve cleanly.

5.8 The Open-Source MIT License Transition

- Replaced the early restrictive proprietary draft with the standard permissive **MIT License** (Copyright © 2026 Divyanshu Kumar).
- Sole author and lead architect established as **Divyanshu Kumar** (`@Atomic-Quark`).
- Third-party developers, corporations, and open-source contributors are granted full permission to use, copy, modify, merge, publish, distribute, sublicense, and sell copies in commercial and non-commercial applications.

---

6. How It Works Under the Hood

6.1 Fluent Parsing & AST Token Extraction Engine

When you invoke a component using the optional natural-language DSL:

```
describe("button Proceed to Checkout green large to /checkout")
```

The internal parser executes the following pipeline:

1. **String Tokenization**: The argument is split into descriptor tokens: `["Proceed to Checkout", "green", "large", "to /checkout"]`.
2. **First Slot Extraction**: The first token (`Proceed to Checkout`) is identified as the visible label.
3. **Pattern Matching & AST Normalization**: Each subsequent token is scanned against known design-system grammar dictionaries:
   - Color Dictionary: `"green"` $\rightarrow$ `color: "green"`, `variant: "success"`.
   - Size Dictionary: `"large"` $\rightarrow$ `size: "lg"`.
   - Routing Dictionary: `"to /checkout"` $\rightarrow$ `to: "/checkout"`.

4. **React Element Synthesis**: The normalized properties are fed directly into the native React primitive, returning `React.createElement(ButtonComponent, resolvedProps)`.
5. **Security Separation**: Notice that authentication and authorization checks are NEVER inferred from string tokens or labels. UI elements rely strictly on explicit boolean flags (`disabled`, `hidden`) while real access control is enforced by the application server.

6.2 Positional Slot Inference Algorithm

When you call `Button("Go to cart", "300px", "btn_cart", "admin", "/cart", "red")`:

- The engine uses an inference algorithm that checks parameter types:
  - If argument 2 contains `"px"`, `"rem"`, or space-separated units, it assigns it to `width` / `boxSize`.
  - If argument 4 matches `"admin"`, `"user"`, or `"auth"`, it sets authentication guards.
  - If argument 5 starts with `"/"` or `"http"`, it sets navigation routing. This allows developers to omit slot indices without breaking property assignments.

6.3 WAI-ARIA Focus Trap & Focus Restoration Mechanism

When a `Modal`, `Drawer`, or `AlertDialog` mounts:

```
graph TD
    A[User clicks Trigger Button] --> B[Save activeElement into triggerRef]
    B --> C[Render Dialog via Portal to document.body]
    C --> D[useFocusTrap scans all interactive elements in Dialog]
    D --> E[Move active focus to first interactive element]
    E --> F{User presses Tab / Shift+Tab}
    F -->|At last element| G[Cycle focus back to first element]
    F -->|At first element + Shift| H[Cycle focus back to last element]
    F -->|User presses Escape or Close| I[Unmount Portal]
    I --> J[Restore active focus to triggerRef]
```

1. **Trigger Element Capture**: `const triggerRef = useRef<HTMLElement | null>(document.activeElement as HTMLElement)`.
2. **Interactive Node Querying**: The trap scans all focusable selectors: `button, [href], input, select, textarea, [tabindex]:not([tabindex="-1"])`.
3. **Key Event Interception**: A `keydown` listener intercepts `Tab` events:
   - If the user is on the last focusable element and presses `Tab`, the event is prevented and focus moves to the first focusable element.
   - If the user is on the first focusable element and presses `Shift+Tab`, the event is prevented and focus moves to the last focusable element.
4. **Focus Restoration**: During the unmount phase of `useEffect`, `triggerRef.current?.focus()` is called to return focus to the user's previous context.

6.4 Reactive Cross-Tab Storage Bus

The `useLocalStorage` hook establishes real-time synchronization across browser tabs without inefficient polling:

1. When `setValue(newValue)` is called in Tab A:
    - `window.localStorage.setItem(key, serialized)` writes to disk.
    - A custom `window.dispatchEvent(new CustomEvent("local-storage-sync", { detail: { key, value } }))` updates other components in Tab A immediately.
2. In Tab B, the native `window.addEventListener("storage", (event) => ...)` fires automatically.
3. The hook checks if `event.key === targetKey`, parses the payload safely in a `try/catch` block, and updates the local React state.

---

7. Official Developer User Manual: Step-by-Step Practical Recipes

7.1 Installation & Setup

In your React or Next.js project:

```
npm install @criation/ui
```

Import the stylesheet once at the root of your application (`src/main.tsx` or `app/layout.tsx`):

```
import "@criation/ui/styles.css";
```

7.2 Recipe: Rapid 3-Line Website Construction

You can build a full marketing page with dark mode, responsive container, gradient headings, badges, and buttons in 3 lines:

```
import { Website, Heading, Text, Button, Badge } from "@criation/ui";

export default function HomePage() {
  return Website("My SaaS Application", [
    Badge("NEW GENERATION 2.0").green().small(),
    Heading("Build Websites 10x Faster").gradient().center().level(1),
    Text("The ultimate fluent React component foundation").muted().center(),
    Button("Start Your Free Trial").green().large().link("/signup"),
  ]);
}
```

7.3 Recipe: Production Authentication Form with `useForm`

Build a secure login form with type safety, field errors, touched states, and asynchronous submission:

```tsx
import React from "react";
import { useForm, Card, Stack, Input, Button, Alert } from "@criation/ui";

interface LoginFormValues {
  email: string;
  password: string;
}

export function LoginForm() {
  const {
    values,
    errors,
    touched,
    isSubmitting,
    register,
    handleSubmit,
    reset
  } = useForm<LoginFormValues>({
    initialValues: {
      email: "",
      password: "",
    },
    validate: (vals) => {
      const errs: Partial<Record<keyof LoginFormValues, string>> = {};
      if (!vals.email) {
        errs.email = "Email address is required";
      } else if (!vals.email.includes("@")) {
        errs.email = "Please enter a valid email address";
      }
      if (!vals.password) {
        errs.password = "Password is required";
      } else if (vals.password.length < 8) {
        errs.password = "Password must be at least 8 characters long";
      }
      return errs;
    },
    onSubmit: async (vals) => {
      // Simulate API call
      await new Promise((res) => setTimeout(res, 1500));
      alert(`Logged in successfully as ${vals.email}`);
      reset();
    },
  });

  return (
    <Card variant="glass" padding="xl" style={{ maxWidth: "420px", margin: "2rem auto" }}>
      <form onSubmit={handleSubmit}>
        <Stack direction="column" gap="md">
          <h2>Sign In to Your Account</h2>

          {errors.email && touched.email && (
            <Alert variant="danger" title="Validation Error">
              {errors.email}
            </Alert>
          )}

          <Input
            {...register("email")}
            type="email"
            label="Email Address"
            placeholder="you@company.com"
          />
```

```
          <Input
            {...register("password")}
            type="password"
            label="Password"
            placeholder="••••••••"
          />

          <Button
            type="submit"
            variant="primary"
            loading={isSubmitting}
            style={{ width: "100%", marginTop: "1rem" }}
          >
            {isSubmitting ? "Authenticating..." : "Sign In"}
          </Button>
        </Stack>
      </form>
    </Card>
  );
}
```

7.4 Recipe: Declarative Table with Custom Column Formatters

Render tabular data cleanly using the declarative `columns` and `data` API:

```tsx
import React from "react";
import { Table, TableColumn, Badge } from "@criation/ui";

interface Order {
  id: string;
  customer: string;
  amount: number;
  status: "paid" | "pending" | "refunded";
  date: string;
}

const orders: Order[] = [
  { id: "ORD-001", customer: "Alice Smith", amount: 149.99, status: "paid", date: "2026-10-21" },
  { id: "ORD-002", customer: "Bob Jones", amount: 89.50, status: "pending", date: "2026-10-20" },
  { id: "ORD-003", customer: "Charlie Brown", amount: 24.00, status: "refunded", date: "2026-10-19" },
];

const columns: TableColumn<Order>[] = [
  {
    key: "id",
    header: "Order ID",
    render: (val) => <strong>{String(val)}</strong>,
  },
  {
    key: "customer",
    header: "Customer",
  },
  {
    key: "amount",
    header: "Amount",
    align: "right",
    render: (val) => `$${Number(val).toFixed(2)}`,
  },
  {
    key: "status",
    header: "Status",
    align: "center",
    render: (val) => {
      const variant = val === "paid" ? "success" : val === "pending" ? "warning" : "danger";
      return <Badge variant={variant}>{String(val).toUpperCase()}</Badge>;
    },
  },
  {
    key: "date",
    header: "Date",
  },
];

export function OrdersTable() {
  return (
    <Table
      columns={columns}
      data={orders}
      striped
      hoverable
      emptyText="No customer orders found."
    />
  );
}
```

7.5 Recipe: Asynchronous Autocomplete with Stale Request Protection

Search remote data sources cleanly without worrying about slow responses overwriting fast responses:

```
import React, { useState } from "react";
import { Combobox, ComboboxOption } from "@criation/ui";

export function UserSearchCombobox() {
  const [selectedUser, setSelectedUser] = useState("");

  const handleRemoteSearch = async (query: string): Promise<ComboboxOption[]> => {
    const response = await fetch(`https://api.example.com/users?q=${encodeURIComponent(query)}`);
    const users = await response.json();
    return users.map((u: { id: string; name: string }) => ({
      value: u.id,
      label: u.name,
    }));
  };

  return (
    <Combobox
      placeholder="Type to search users remotely..."
      value={selectedUser}
      onChange={setSelectedUser}
      onSearch={handleRemoteSearch}
      label="Assignee"
    />
  );
}
```

7.6 Recipe: Accessible Overlays (Modal, Drawer, AlertDialog)

Trigger overlays with guaranteed focus trapping, focus restoration, and backdrop dismissal:

```tsx
import React from "react";
import { Modal, AlertDialog, Drawer, Button, useDisclosure } from "@criation/ui";

export function OverlaysDemo() {
  const modal = useDisclosure();
  const alert = useDisclosure();
  const drawer = useDisclosure();

  return (
    <div>
      <Button variant="primary" onClick={modal.onOpen}>
        Open Settings Modal
      </Button>
      <Button variant="danger" onClick={alert.onOpen}>
        Delete Project
      </Button>
      <Button variant="secondary" onClick={drawer.onOpen}>
        Open Navigation Drawer
      </Button>

      {/* 1. Modal with Focus Trap & Restoration */}
      <Modal
        isOpen={modal.isOpen}
        onClose={modal.onClose}
        title="Account Preferences"
      >
        <p>Modal content is fully isolated in a root portal.</p>
        <Button onClick={modal.onClose}>Save & Close</Button>
      </Modal>

      {/* 2. Destructive Alert Dialog */}
      <AlertDialog
        isOpen={alert.isOpen}
        onClose={alert.onClose}
        onConfirm={() => {
          alert.onClose();
          console.log("Project destroyed");
        }}
        title="Permanently Delete Project?"
        message="This action is irreversible. All assets and databases will be deleted."
        confirmText="Yes, Delete Permanently"
      />

      {/* 3. Slide-in Side Drawer */}
      <Drawer
        isOpen={drawer.isOpen}
        onClose={drawer.onClose}
        title="Navigation Menu"
        placement="right"
      >
        <p>Drawer slides smoothly from the right with focus trapped inside.</p>
      </Drawer>
    </div>
  );
}
```

7.7 Recipe: Cross-Tab Synchronized Local State

Keep user preferences or carts in sync across multiple browser tabs automatically:

```
import React from "react";
import { useLocalStorage, Button, Badge } from "@criation/ui";

export function ShoppingCartBadge() {
  // Synchronized across all tabs in real-time
  const [cartCount, setCartCount] = useLocalStorage<number>("cart_item_count", 0);

  return (
    <div>
      <Badge variant="success">Items in Cart: {cartCount}</Badge>
      <Button onClick={() => setCartCount((prev) => prev + 1)}>
        Add Item (Syncs Across Tabs)
      </Button>
      <Button variant="outline" onClick={() => setCartCount(0)}>
        Clear Cart
      </Button>
    </div>
  );
}
```

7.8 Recipe: Next.js 14/15 App Router Clean Integration

In a Next.js App Router project:

`app/layout.tsx`:

```
import "@criation/ui/styles.css";

export default function RootLayout({ children }: { children: React.ReactNode }) {
  return (
    <html lang="en">
      <body>{children}</body>
    </html>
  );
}
```

`app/page.tsx`:

```
import { Heading, Text, Button, Card, Stack } from "@criation/ui";

export default function Page() {
  return (
    <main style={{ padding: "3rem" }}>
      <Card variant="glass" padding="xl">
        <Stack direction="column" gap="md">
          {Heading("Next.js 14/15 App Router Ready").gradient().level(1)}
          {Text("Criation UI seamlessly resolves client-boundary directives.").muted()}
          {Button("Explore Dashboard").green().link("/dashboard")}
        </Stack>
      </Card>
    </main>
  );
}
```

---

8. Comparative Analysis: The Difference

8.1 Criation UI vs. Tailwind CSS

- **Tailwind CSS**: Requires authoring long strings of utility classes (`className="flex flex-col items-center justify-between p-4 bg-slate-900 border border-slate-800 rounded-xl hover:bg-slate-800 transition-all duration-200"`). It creates noisy JSX and lacks native accessible component logic (no built-in modals, focus traps, or autocomplete).
- **Criation UI**: Provides rich, pre-built design system tokens with glassmorphism, micro-animations, and full accessible component primitives. You can write `Card("...").glass()` instead of 20 utility classes.

8.2 Criation UI vs. Material UI & Chakra UI

- **MUI & Chakra UI**: Heavy bundle sizes (often adding 300KB+ to JavaScript bundles), complex CSS-in-JS runtimes (Emotion/styled-components) that degrade Next.js App Router performance, and rigid opinionated aesthetics.
- **Criation UI**: Zero CSS-in-JS runtime overhead. Uses clean Vanilla CSS custom properties with instant compilation. Zero runtime styling penalty, and 100% Next.js 14/15 compatibility out of the box.

8.3 Criation UI vs. Shadcn/ui

- **Shadcn/ui**: Requires copying dozens of raw files into your repository (`components/ui/...`), requiring you to manage, patch, and maintain Radix primitives, Tailwind configs, and utility files yourself.
- **Criation UI**: Ships as an integrated, production-built, tree-shakeable NPM package (`@criation/ui`) with automated TypeScript `.d.ts` declarations, zero copy-paste maintenance, and the revolutionary Fluent English Chaining DSL.

Comparative Benchmark Matrix:

Feature / Metric	Criation UI (v0.2.1)	Tailwind CSS	Material UI (MUI)	Shadcn/ui
Fluent English Chaining	✅ Native First-Class	❌ None	❌ None	❌ None
1-Line Component Shorthands	✅ Native First-Class	❌ None	❌ None	❌ None
3-Line Website Scaffold (`Website`)	✅ Built-in	❌ None	❌ None	❌ None
Next.js 14/15 Client Boundary	✅ Pre-configured	⚠️ Manual config	⚠️ Complex SSR setup	⚠️ Manual `"use client"`
Runtime CSS Overhead	**0 KB (Vanilla CSS)**	0 KB	⚠️ Heavy (Emotion)	0 KB (Tailwind)
Keyboard Focus Trapping	✅ Built-in (`Modal` / `Drawer`)	❌ None	✅ Built-in	✅ Radix-dependent
Stale Request Cancellation	✅ Built-in (`Combobox`)	❌ None	❌ Manual	❌ Manual
Cross-Tab Sync State	✅ Built-in (`useLocalStorage`)	❌ None	❌ None	❌ None
Form Management Engine	✅ Built-in (`useForm`)	❌ None	❌ None	❌ None
Component Maintenance Burden	**Zero (Package-managed)**	Manual	Package-managed	⚠️ High (Local copies)

---

9. Open-Source Licensing & Commercial Developer Rights (MIT License)

Criation UI is released under the permissive **MIT License**:

```
MIT License

Copyright (c) 2026 Divyanshu Kumar

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
```

1. **Permissive Commercial Rights**: Developers and enterprises may freely install, build, customize, and deploy Criation UI inside commercial SaaS products, private codebases, and open-source packages.
2. **Author Attribution**: Divyanshu Kumar (`Atomic-Quark`) is recognized as the sole author and lead architect of Criation UI.
3. **Repository & Community**:
    - **Lead Architect**: Divyanshu Kumar
    - **GitHub**: https://github.com/Atomic-Quark/Criation-UI
    - **Inquiries**: `143479650+Atomic-Quark@users.noreply.github.com`

---

10. Troubleshooting, Edge Cases & FAQ

Q1: Does Criation UI require Tailwind CSS or a CSS processor?

No. Criation UI is 100% self-contained. It relies on vanilla CSS variables. You simply import `@criation/ui/styles.css` once at your application root.

Q2: Why did I receive a warning when rendering a list of items?

In v0.1.0, rendering lists without explicit keys could trigger React key warnings. In v0.2.0+, all list mapping operations inside `Website(...)` automatically assign unique, stable keys. When rendering your own custom arrays in JSX, provide `key={item.id}` as standard React practice.

Q3: How do I handle SSR in frameworks like Next.js?

All components in `@criation/ui` are compiled with the `"use client";` boundary banner in v0.2.0+. You can import them directly into any App Router client component or page. All browser APIs (`window` , `localStorage` , `document`) are defended with SSR checks (`typeof window !== "undefined"`).

Q4: How does `Combobox` handle rapid typing with slow network connections?

`Combobox` and `MultiSelect` utilize internal request ID counters. If an older, slower search query completes after a newer search query has already returned, the older response is discarded automatically, preventing race condition UI bugs.

Criation UI Architectural Specification & User Manual — Authored and Maintained by Divyanshu Kumar (Atomic-Quark).
