Wire Pay Payment Provider Connection Specification

Item	Value
Version	1.1.0
Target system	Wire Pay (payment management dashboard) — commit `cf1c153` (`main`)
Date / revised	2026-09-06 (1.0.0) / 2026-09-07 (1.1.0; see the revision history at the end and `docs/spec/CHANGELOG.md`)
Language	English (Japanese edition: `docs/spec/ja/B-provider-connection-spec.md`)
Terminology	Follows `docs/spec/en/glossary.md`

Intended readers

This document is for the parties Wire Pay entrusts payment processing to:

- card issuers, acquirers and card platforms such as Stripe
- QR / wallet operators such as PayPay
- konbini (convenience-store) payment collection agencies
- banks and collection institutions providing virtual accounts or Pay-easy
- upstream PSPs / wallets that Wire Pay uses as a client
- developers who implement and operate provider connections on the Wire Pay side

The specification for parties that use Wire Pay's API (merchants, downstream PSPs / wallets) is the companion document Specification A (Merchant & Connecting-Client Integration Specification) `docs/spec/en/A-merchant-integration-spec.md`. Where merchant-side behaviour matters here, the relevant chapter of Specification A is referenced rather than repeated.

How this document is written

- The body contains only facts verifiable from the implementation. At the target commit Wire Pay runs in demo mode and never calls an external payment network, so no real traffic with a provider exists. This document therefore describes the current connection settings, receiving interfaces and state transitions exactly as implemented, and states the interface requirements Wire Pay will impose on providers for a live connection as explicitly separated "requirements" (sections headed "Requirements for a live connection").
- Unimplemented or mocked functions are listed at the end of each chapter under "Not implemented / planned" and in chapter 11, never in the body.
- Statements involving inference carry "※要確認" (to be confirmed) and are listed with reasons in `docs/spec/ASSUMPTIONS.md`.
- Unless stated otherwise, dates use Japan Standard Time (Asia/Tokyo); API timestamps are ISO 8601 / UTC; amounts are whole yen (JPY).


Contents

1. Overview
2. Connection model per payment method
3. Receiving deposit and result notifications
4. Identifier mapping
5. Reconciliation and short / excess handling
6. Authorization, capture, void, refund, chargeback
7. Settlement and the flow of funds
8. Incident operations
9. Security requirements
10. Adding a new provider
11. Not implemented / planned

- Appendix A Data model (ER diagram)
- Appendix B Configuration items
- Appendix C Vendor notification mapping (reference, not implemented)
- Appendix D Requirements for a live connection (list)
- Revision history

1. Overview

1.1 Division of responsibilities



Responsibility	Wire Pay	Provider
Accepting transactions, issuing identifiers	Issues the transaction ID, transfer ID (7 / 8 digits) and receipt number (13 digits) and presents them to merchants and customers	When issuing its own identifiers (virtual account numbers, collection numbers) keeps them mapped to Wire Pay's (chapter 4)
Executing authorization, capture, void, refund	Manages the state machine and ledger (`Payment` / `Refund` / `PaymentEvent`). No external call at the target commit (demo)	The real operation against the card network / wallet balance (live-connection requirement)
Notifying results and deposits	Receives them through the receiving interfaces (chapter 3), applies transitions, sends merchant webhooks and e-mails	Signs notifications; Wire Pay processes idempotently so retries are tolerated
Reconciliation, short / excess	Cumulative-amount decision (chapter 5); operator screens for unmatched and short / excess deposits	Notifies amount, time, payer name and bank reference
Settlement	Per-merchant batches and net payout (chapter 7), qualified invoice PDF	Funds transfer to Wire Pay. No funds-movement connection at the target commit
Chargebacks	Registration, dispute, outcome, confirmation and settlement deduction	Notification of disputes (currently entered manually by PSP operators)
Incidents	Payment-method suspension (global / per merchant), notification centre, webhook resend	Incident communication (no system integration today)

1.2 Connection model at the target commit

Element	Implementation
Provider definitions	`PROVIDERS` in `lib/providers/registry.ts` (15 definitions in 5 categories). Credential fields, secrecy and test-mode support are defined in code
Provider connection (instance)	`PaymentProvider` table: `providerKey` , `category` , `displayName` , `status` (`active` / `disabled`), `testMode` , `credentials` (JSON; secret fields as AES-256-GCM ciphertext)
Connection test	`runConnectionTest` : presence of required fields and URL format only. No external API call
Provider selection at creation	Public API: the oldest row with `status = active` , `category = method` and the key's environment (`testMode = !livemode`). PSP dashboard: chosen explicitly. Payment links: one active provider per category in the link's environment. Subscriptions: the active credit provider of the environment (else any active provider)
Transaction environment	`Payment.livemode = !provider.testMode` , snapshotted at creation
Provider-side identifier	`Payment.externalId` (in the demo generated by Wire Pay as `<first 6 chars of providerKey>_<time base36>_<random>` ; unique per `(providerId, externalId)`)

Element	Implementation
Receiving interfaces	(a) `POST /api/webhooks/{providerId}` (signed result notifications), (b) `POST /api/demo/deposit-notify` (bank deposits), (c) `POST /api/demo/cvs-notify` (konbini payments). (b) and (c) share `processDepositNotification` in `lib/deposits/notify.ts` (idempotency, environment matching, the deposit notification log; 1.1.0). Chapter 3
Sending interfaces	Wire Pay → merchant webhooks (Specification A, chapter 6). No Wire Pay → provider API calls
Ledger protection	A provider with transactions cannot be deleted (409 `provider_has_payments`); it is disabled instead

1.3 Environments (test / live)

- A provider connection has `testMode` (true = test). Definitions with `supportsTestMode: false` (the custom webhook integration) hide the toggle in the form (※要確認: `supportsTestMode` only controls the UI toggle; the API accepts any `testMode`).
- Test and live are separate **`PaymentProvider`** rows of the same definition with different `testMode`.
- Transactions, refunds, settlements and webhook deliveries are all separated by `livemode` (Specification A, 1.3).

1.4 Not implemented / planned (chapter 1)

- No API calls from Wire Pay to providers (authorize, capture, void, refund, balance).
- No provider adapter layer (vendor notification formats → Wire Pay's internal events). The receiving interfaces use Wire Pay's own format (chapter 3; a mapping proposal is in Appendix C).

---

2. Connection model per payment method

2.1 Provider definitions (**`PROVIDERS`**) and the connection form

On the PSP dashboard ("Payment providers → + Add payment provider", `/providers/new` → `/providers/new/[provider]`) the operator picks a category and a provider and fills in the fields below. Fields with `secret: true` are AES-256-GCM encrypted on save and displayed masked (`••••••••` + last 4 characters, chapter 9). `required` fields are mandatory; `type: url` fields must match `http(s)://`.

Credit card (**`credit`**)

`providerKey`	Name	Fields (**`key`**: type / required / secret)
`stripe`	Stripe	`publishable_key`: text / required; `secret_key`: password / required / secret; `webhook_secret`: password / secret (verifies incoming webhooks); `statement_descriptor`: text (≤22 chars)
`square`	Square	`application_id`: text / required; `access_token`: password / required / secret; `location_id`: text / required

providerKey	Name	Fields (key : type / required / secret)
gmo_pg	GMO Payment Gateway	site_id : text / required; site_password : password / required / secret; shop_id : text / required; shop_password : password / required / secret; api_endpoint : url

QR code (qr)

providerKey	Name	Fields
paypay	PayPay	merchant_id : text / required; api_key : text / required (public identifier, stored in plaintext); api_secret : password / required / secret; store_id : text
au_pay	au PAY	merchant_id : text / required; store_id : text / required; api_key : text / required (plaintext); api_secret : password / required / secret; callback_url : url
rakuten_pay	Rakuten Pay (Online)	service_id : text / required; auth_key : password / required / secret; shop_url : url
docomo_pay	d Payment	merchant_id : text / required; api_key : password / required / secret; callback_url : url

Konbini (convenience)

providerKey	Name	Fields
bitcash	BitCash	merchant_code : text / required; auth_key : password / required / secret; notify_url : url
smartpit	Smart Pit	client_id : text / required; client_secret : password / required / secret; expiry_days : text (※要確認: display only; the payment deadline comes from the merchant's cvsDueDays)
web_conveni	Multi-Konbini Payment	contract_code : text / required; api_token : password / required / secret; stores : select (all / lawson / familymart / seven ; ※要確認: display only; the payment page always offers CVS_BRANDS)

Bank transfer (bank)

providerKey	Name	Fields
pay_easy	Pay-easy	collection_agency : text / required (collection agency number); customer_number_prefix : text; confirmation_number : password / secret
virtual_account	Virtual Account (GMO/SBI etc.)	bank_partner : select / required (gmo_aozora / sbi / mizuho / rakuten); api_user : text / required; api_password : password / required / secret; branch_code : text; webhook_url : url (deposit notification webhook URL; ※要確認: display only — Wire Pay's receiving URL is fixed at /api/demo/deposit-notify)

Other (other)


providerKey	Name	Fields
custom_webhook	Custom Webhook	service_name : text / required; endpoint : url / required; auth_header : password / secret; webhook_secret : password / secret (verifies incoming webhooks); notes : textarea. supportsTestMode: false

The only field actually read at the target commit is webhook_secret (stripe , custom_webhook). All other fields are stored, displayed and checked by the connection test but never used for processing (chapter 11).

2.2 What Wire Pay exchanges with providers per method


The sequence diagrams distinguish implemented paths (solid) from requirements for a live connection (dashed, marked "Requirement").

Credit / QR


Merchant / payment page
Wire Pay
Card / QR provider
create transaction (method credit|qr, autoCapture)
today: authorization and capture settle in the DB immediately (captured or authorized) — no call to P
[Requirement] authorize / capture / void / refund API calls
[Requirement] result (approval code, provider transaction ID)
result notification POST /api/webhooks/{providerId} (signed, implemented)
payment.captured → capture / payment.failed → fail / payment.cancelled → cancel / payment.refunded → refund
Merchant / payment page
Wire Pay
Card / QR provider

- The implemented receiver is `POST /api/webhooks/{providerId}` (3.1): it finds the transaction by `externalId` and applies the transition per `EVENT_TO_ACTION`.
- What Wire Pay sends (requirement): amount (yen), Wire Pay transaction ID (reference), the merchant's order number, card data (Wire Pay never holds the PAN, so a live connection must rely on the provider's tokenisation / hosted fields, chapter 9).
- What Wire Pay receives: the provider transaction ID (stored in `externalId`), the result type, optionally an amount.

Konbini


Merchant / payment page
Wire Pay
Konbini collection agency
Customer
create transaction (method convenience, cvsBrand)
Wire Pay issues the 13-digit receipt number and the deadline (pending)
[Requirement] register receipt number, amount, deadline, store (or obtain K's number)
e-mail "konbini payment instructions"
pays at the counter
payment notification POST /api/demo/cvs-notify {receiptNo, amount?} (implemented)
deposit → captured, cvsPaidAt — payment.completed to the merchant
past the deadline → hourly cron expires it (no cancellation sent to K)
Merchant / payment page
Wire Pay
Konbini collection agency
Customer

Bank transfer (virtual account / Pay-easy)



2.3 Provider connection API (used by the PSP dashboard)

Method / path	Permission	Content
`GET /api/providers`	view	List (never includes `credentials`)
`POST /api/providers`	`provider.create` (admin / developer)	`{ providerKey, displayName (≤80), testMode (default true), credentials }`. Missing required fields → 400 `missing_required`; unknown `providerKey` → 400 `unsupported_provider`; cap 50 → 403 `demo_limit`. Audit `provider.create`
`PATCH /api/providers/{id}`	`provider.update`	`displayName` / `status` (`active` / `disabled`) / `testMode` / `credentials` (`""` on a secret field = unchanged, on a non-secret field = delete). Audit `provider.update` (records only whether credentials changed)
`DELETE /api/providers/{id}`	`provider.delete`	409 `provider_has_payments` if any transaction exists. Audit `provider.delete`
`POST /api/providers/test`	`provider.test`	Connection test on unsaved form values (required fields, URL format only)
`POST /api/providers/{id}/test`	`provider.test`	Connection test on the stored, decrypted credentials; updates `lastTestAt` / `lastTestOk`. Undecryptable (key changed) → 422 `undecryptable`

With `DEMO_READONLY=1` (public demo) `DELETE` and `PATCH /api/providers/*` answer 403 for everyone.

2.4 Not implemented / planned (chapter 2)

- Nothing calls provider APIs with the stored credentials (`secret_key`, `api_secret`, …). The connection test makes no network call.
- No registration / issuance with konbini agencies or virtual-account banks, and no cancellation notice on expiry.
- Fields such as `expiry_days`, `stores`, `webhook_url`, `callback_url`, `notify_url`, `statement_descriptor` are stored and displayed only and have no effect.

---

3. Receiving deposit and result notifications

Notifications Wire Pay receives from providers fall into three receiving interfaces. All use Wire Pay's own format and are exempt from the middleware's session, CSRF and (dashboard-oriented) IP checks.

Receiving interface	Purpose	Authentication	Implementation
`POST /api/webhooks/{providerId}`	Result notifications for card / QR / other (capture, failure, cancellation, refund)	HMAC-SHA256 signature (the connection's `webhook_secret`)	`app/api/webhooks/[providerId]/route.ts`, `lib/webhooks/verify.ts`
`POST /api/demo/deposit-notify`	Bank-transfer deposit notifications	Bearer `DEPOSIT_NOTIFY_SECRET`	`app/api/demo/deposit-notify/route.ts` → `lib/deposits/notify.ts`
`POST /api/demo/cvs-notify`	Konbini payment notifications	Bearer `DEPOSIT_NOTIFY_SECRET` (shared with the bank one)	`app/api/demo/cvs-notify/route.ts` → `lib/deposits/notify.ts`

Although the `/api/demo/*` names come from the demo, this document treats them as the specification of the receiving interfaces. For a live connection an adapter must satisfy the same contract (request / response / idempotency) — see 3.5. The demo receiver for merchant webhooks, `GET/POST /api/demo/webhook-receiver`, simulates the Wire Pay → merchant direction and is irrelevant to providers (Specification A, 12.3).

3.1 Result notifications: `POST /api/webhooks/{providerId}`

Request

Item	Specification
Path	`{providerId}` = `PaymentProvider.id` (Wire Pay's connection ID, communicated to the provider as its notification URL)
Headers	`Wirepay-Signature: t=<UNIX seconds>,v1=<hex HMAC-SHA256>`; `Content-Type: application/json`
Signature	`v1 = hex( HMAC_SHA256( key = webhook_secret, message = "<t>.<raw body>" ) )`. Stripe-compatible format. Rejected when `t` differs from now by more than ±300 seconds
Body	`{ "id": string(1–128), "type": "payment.captured" | "payment.failed" | "payment.cancelled" | "payment.refunded", "data": { "externalId": string, "amount"?: integer > 0 } }`
`id`	The provider's event ID; de-duplicated on `(providerId, id)`
`data.externalId`	The provider transaction ID (`Payment.externalId`, unique per `(providerId, externalId)`)
`data.amount`	The refund amount for `payment.refunded` (omitted = the whole remaining balance); ignored for other types

Processing

1. Load the provider by `providerId`; missing → 404 `provider_not_found`.
2. Decrypt the credentials and read `webhook_secret`; unset → 400 `webhook_not_configured`.
3. Verify the signature; failures → 400 `signature_malformed` / `signature_expired` / `signature_mismatch`.
4. Parse JSON (400 `invalid_json`) and validate the schema (400 `invalid_input`).
5. De-duplicate: an existing `(providerId, externalEventId)` answers 200 `{ received: true, duplicate: true }` without re-applying. Concurrent arrivals are resolved by the unique constraint.
6. Store the raw body in `WebhookEvent`.
7. Find the transaction by `externalId`; missing → record `error = payment_not_found` and answer 404 `not_found`.
8. Apply the action mapped by `EVENT_TO_ACTION` (`applyPaymentAction`, actor `webhook`, audit actor type `webhook`). An impossible transition (e.g. `payment.captured` on a completed transaction) answers 409 `invalid_transition` and stores the message in `WebhookEvent.error`.

type	Action	Allowed source statuses	Merchant webhook
`payment.captured`	`capture`	`pending` / `authorized` / `awaiting_transfer` / `awaiting_payment`	`payment.completed`
`payment.failed`	`fail`	`pending` / `authorized` / `awaiting_transfer` / `awaiting_payment`	`payment.failed`
`payment.cancelled`	`cancel`	`pending` / `authorized` / `awaiting_transfer` / `awaiting_payment`	`payment.cancelled`
`payment.refunded`	`refund`	`captured` / `partially_refunded`	`refund.completed` (a `Refund` row is created directly as `completed`, reason `other`)

Response

HTTP	Body	Meaning
200	`{ ok: true, data: { received: true, duplicate: false, payment: { id, status, amountRefunded, depositAmount, depositDiff } } }`	Applied
200	`{ received: true, duplicate: true }`	Event ID already processed
400	`signature_*` / `webhook_not_configured` / `invalid_json` / `invalid_input` / `refund_exceeds`	Retrying will not help
404	`provider_not_found` / `not_found`	Connection ID or transaction not found
409	`invalid_transition`	Not applicable in the current status

Wire Pay's behaviour towards provider retries

- A retry with the same `id` always answers 200 (duplicate). Providers should retry only on non-2xx. 4xx responses will not succeed until the content changes.
- The timestamp tolerance is 5 minutes; recompute `t` and the signature on retry.

Test facility

The PSP dashboard's "Simulate webhook" on a transaction detail (permission `payment.simulate_webhook` = admin / developer) builds an event of the above shape for the transaction's `externalId`, signs it with the provider's `webhook_secret` and POSTs it to Wire Pay's own **`/api/webhooks/{providerId}`** (`POST /api/payments/{id}/simulate-webhook { type, amount? }`), exercising signature verification, de-duplication and the state machine on the production path.

3.2 Bank-transfer deposit notifications: **`POST /api/demo/deposit-notify`**

Request

Item	Type	Required	Description
`Authorization`	header	when configured	`Bearer <DEPOSIT_NOTIFY_SECRET>` (constant-time compare). When the variable is unset: 404 (disabled) in production, open in development
`eventId`	string (1–128)		The sender's event ID (de-duplication key, 1.1.0). When omitted, duplicates are detected by a content hash (below)
`transferId`	string (≤20)		The transfer ID the customer prefixed to the payer name. When it does not match `^\d{7,8}$` or no transaction exists, the deposit is recorded as unmatched
`amount`	integer (1–99,999,999)	○	Amount received (yen)
`mode`	`test` | `live`	○	Environment of the sender (virtual account). Compared with the transaction's `livemode`; on a mismatch the deposit is held as unmatched instead of reconciled (1.1.0; missing → 400 `invalid_input`, `fieldErrors.mode = "required"`)
`payerName`	string (≤120)		Payer name (kept on the unmatched deposit; `(unknown)` when omitted)
`bankReference`	string (≤80)		The bank's statement reference
`receivedAt`	string (ISO date-time, ≤40)		Deposit time; defaults to now (an invalid value → 400 `invalid_input`, `fieldErrors.receivedAt = "date"`)

Processing (**`processDepositNotification`**)

1. Validate (table above). Invalid input answers 400 and records nothing (the sender fixes and resends).

2. Look the transaction up by transfer ID and decide: no transaction → unmatched / `livemode ≠ mode` → unmatched (`mode_mismatch`) / `expired` → unmatched (`late_deposit`) / `cancelled` → unmatched (`cancelled_deposit`) / awaiting transfer (`awaiting_transfer`) → apply / anything else (completed etc.) → rejected.
3. Claim the de-duplication key: `bank:evt:<eventId>` when an `eventId` is given, else `sha256(source | transfer ID | amount | receivedAt rounded to the minute | bank reference)`. A key already claimed marks the notification as a duplicate: it is recorded and answered 200 without re-applying anything (the unique constraint on `DepositNotification.claimKey` makes this race-free for concurrent arrivals).
4. Run `applyPaymentAction(deposit, actor: "bank")` (chapter 5) or `registerUnmatchedDeposit` (`source = bank`, `reason`, `candidatePaymentId` = the transaction named by the notification) according to the decision.
5. Record every notification (applied / duplicate / unmatched / rejected) in the deposit notification log `DepositNotification` (number `DN-00001`, `result`, `resultReason`, `paymentId`, `unmatchedDepositId`, `duplicateOfId`, raw body).

Response

Situation	HTTP	**`data`** (always: **`notificationId`**, **`notificationNo`**, **`duplicate: false`**, **`received`**)
Transfer ID matched, reconciliation applied	200	`{ matched: true, transferId, paymentId, amount (due), depositAmount (cumulative), depositDiff: null | "short" | "excess", status, completed: boolean }`
Transfer ID missing / malformed / unknown	202	`{ matched: false, reason: "not_found", transferId: string | null, paymentId: null, unmatchedDepositId }` (an `UnmatchedDeposit` with `source = bank`, `status = unmatched` is created; audit `deposit.register`)
`mode` differs from the transaction's environment	202	`{ matched: false, reason: "mode_mismatch", paymentId, unmatchedDepositId }` (`reason = mode_mismatch`, with `candidatePaymentId`; not selectable on the matching screen)
Transaction expired	202	`{ matched: false, reason: "late_deposit", paymentId, unmatchedDepositId }` (the PSP may apply it through "Apply as late deposit" = the `late_deposit` transition, 5.3)
Transaction cancelled	202	`{ matched: false, reason: "cancelled_deposit", paymentId, unmatchedDepositId }` (can only be dismissed as a return)
Re-sent notification (same de-duplication key)	200	`{ duplicate: true, notificationId (the first notification), notificationNo, duplicateNotificationId, paymentId, unmatchedDepositId, result }`; nothing is re-applied
Transaction completed or otherwise not awaiting transfer	409	`invalid_transition` (`details.notificationId`; logged as `rejected` / `invalid_status`)
Transaction with neither transfer ID nor receipt number	400	`not_bank_transfer`

Situation	HTTP	**data** (always: **notificationId**, **notificationNo**, **duplicate: false**, **received**)
Missing `mode` / invalid `amount` / invalid `receivedAt`	400	`invalid_input` (not recorded)
Provider connection disabled	400	`provider_disabled`

- Reconciliation is `applyPaymentAction(deposit, actor: "bank")`; audit actor type `bank`; decision rules in chapter 5.
- On completion the merchant receives `payment.completed`, the customer a "payment completed" e-mail and, depending on the merchant's setting, the merchant contact a `merchant_payment_notice` (Specification A, 11.1).
- Changed since 1.0.0: `mode` is mandatory and used for matching; deposits on expired / cancelled transactions are held with 202 instead of refused with 409 (`docs/spec/CHANGELOG.md` B-2 to B-4).

3.3 Konbini payment notifications: `POST /api/demo/cvs-notify`

Item	Type	Required	Description
`Authorization`	header	when configured	As in 3.2
`eventId`	string (1–128)		The sender's event ID (de-duplication key, 1.1.0); same rules as 3.2 (content hash when omitted; key prefix `cvs:`)
`receiptNo`	string (≤20)	○	The 13-digit receipt number; hyphens are stripped before matching (`4102-9938-27716` accepted). Malformed / unknown → 404 `receipt_not_found` (logged as `rejected`)
`amount`	integer		Amount paid at the counter; omitted = the transaction amount (treated as exact)
`receivedAt`	string (ISO date-time, ≤40)		Payment time; defaults to now
`mode`	`test` | `live`	○	Environment of the collection agency; compared with the transaction's `livemode` (1.1.0)

Situation	HTTP	**data** (common fields as in 3.2)
Applied	200	`{ matched: true, receiptNo (hyphens removed), paymentId, amount (due), depositAmount, depositDiff, status, completed }`
Environment mismatch / expired / cancelled	202	`{ matched: false, reason: "mode_mismatch" | "late_deposit" | "cancelled_deposit", receiptNo, paymentId, unmatchedDepositId }` (an unmatched deposit with `source = cvs`)
Unknown / malformed	404	`receipt_not_found` (`details.notificationId`)

Situation	HTTP	**data** (common fields as in 3.2)
Re-sent	200	`{ duplicate: true, … }` (as in 3.2)
Not awaiting payment (completed etc.)	409	`invalid_transition`

- Reconciliation is `applyPaymentAction(deposit, actor: "cvs")` with `waiting = awaiting_payment` (konbini "awaiting payment" became its own status in 1.1.0). On completion `cvsPaidAt` is stamped, the merchant receives `payment.completed` and the customer the completion e-mail.
- The payment page's "Mark as paid at the store (demo)" calls the same `deposit` with actor `cvs` (Specification A, 7.5).

3.4 Common receiving rules

Item	Specification
Response envelope	`{ ok: true, data }` / `{ ok: false, error: { code, message } }` (`x-lang` selects the language)
Idempotency	Result notifications are de-duplicated on `(providerId, id)`. Deposit notifications are de-duplicated on **`eventId`** (else a content hash); a resend answers 200 `{ duplicate: true }` and is not added to the cumulative deposit (1.1.0, 3.2)
Deposit notification log	Every deposit notification is recorded in `DepositNotification` and visible on the PSP dashboard's "Deposit notification log" (`/deposit-notifications`, `GET /api/deposit-notifications` + CSV; filters by source, result and period) and under "Related deposit notifications" on the transaction detail (1.1.0)
Environment	Deposit notifications require `mode`; a notification whose `mode` differs from the transaction's `livemode` is held as unmatched instead of reconciled (1.1.0)
Rate limit	None (the middleware passes `/api/webhooks/` and `/api/demo/*` as self-authenticating paths)
IP restriction	The dashboard block list does not apply (`ipRestricted: false`)
Audit	`AuditLog.actorType` = `webhook` / `bank` / `cvs`, with the caller IP
Status history	`PaymentEvent.actor` = `webhook` / `bank` / `cvs`

3.5 Requirements for a live connection (interfaces required of providers)

To connect the receiving interfaces of the target commit to real notifications, the provider (or an adapter) must satisfy:

Requirement	Content
R3-1 Result signature	HMAC-SHA256 in the `t=<UNIX seconds>,v1=<hex>` format, with a shared secret that fits Wire Pay's `webhook_secret` field; clock skew within 5 minutes
R3-2 Event ID	A unique, immutable provider-side event ID (≤128 chars), identical on retries
R3-3 Transaction mapping	The notification carries the `externalId` Wire Pay issued (a live design must store the provider's transaction ID instead, chapter 4)
R3-4 Event types	Mappable onto `payment.captured` / `payment.failed` / `payment.cancelled` / `payment.refunded` (vendor names translated by an adapter)
R3-5 Bank deposit notification	Carries the transfer ID (7 / 8 digits), amount, deposit time, payer name, bank reference and environment (`mode`); deposits whose transfer ID cannot be read are still notified (held as unmatched)
R3-6 Konbini payment notification	Carries the 13-digit receipt number, the amount paid and the environment (`mode`)
R3-7 Retry policy	Retry only on non-2xx and with the same **`eventId`** (Wire Pay de-duplicates; without an `eventId` a notification with the same source, number, amount, minute of receipt and bank reference is treated as a duplicate)
R3-8 Authentication	Deposit notifications use a Bearer token (`DEPOSIT_NOTIFY_SECRET`); per-provider tokens require an adapter (one shared secret today)
R3-9 Environment separation	Tag every notification with the correct environment (`mode`). Wire Pay compares `mode` with the transaction's `livemode` and holds mismatches as unmatched deposits (1.1.0). Result notifications are separated by `providerId` (per connection)
R3-10 Event ID	Give deposit notifications a unique, immutable event ID (≤128 chars) too (without it the content hash is used and two deposits of the same amount in the same minute could be mistaken for duplicates)

3.6 Not implemented / planned (chapter 3)

- No adapters translating vendor formats (Stripe `payment_intent.succeeded`, PayPay `PAYMENT_COMPLETED`, …); a mapping proposal is in Appendix C.
- No per-provider Bearer tokens, no source-IP restriction.
- Only four result types are accepted; transitions to authorized-only, partial captures and chargeback notifications are not.

---

4. Identifier mapping

4.1 Wire Pay identifiers

Identifier	Column	Format	Uniqueness	Issued	Used for
Transaction ID	`Payment.id`	cuid (about 25 alphanumerics)	System-wide	At creation (Prisma)	`id` in the merchant API, `payment_id` in webhooks, dashboards
Provider transaction ID	`Payment.externalId`	Any string; in the demo `<first 6 chars of providerKey (alphanumeric, lower case)>_<creation time base36>_<8 random chars>`	Per `(providerId, externalId)`	Generated by Wire Pay at creation (demo)	`data.externalId` of result notifications, `transaction_id` of merchant webhooks
Transfer ID	`Payment.transferId`	7 or 8 digits (merchant setting `transferIdDigits`), first digit non-zero (`^[1-9]\d{6,7}$`)	System-wide (`@unique` , across environments)	Random at bank-transfer creation, redrawn once on collision	Deposit-notification match key, customer instructions

Identifier	Column	Format	Uniqueness	Issued	Used for
Receipt number	`Payment.cvsReceiptNo`	13 digits, first digit non-zero (`^[1-9]\d{12}$`); displayed 4-4-5	System-wide (`@unique`)	Random at konbini creation, redrawn once	Payment-notification match key, customer instructions
Order number	`Payment.orderNumber`	Merchant-supplied (≤64). Payment links `LNK-<TOKEN6>-<4-digit seq>`, subscriptions `SUB-<last 6 of subscription id>-<YYYYMMDD>` (`-F` suffix for failed records)	Not unique	Merchant / Wire Pay	Display, settlement line description
Idempotency key	`Payment.idempotencyKey`	8–128 chars	System-wide	Merchant	Duplicate prevention

Identifier	Column	Format	Uniqueness	Issued	Used for
Event ID (inbound)	`WebhookEvent.externalEventId`	Provider-side ID (≤128)	Per `(providerId, externalEventId)`	Provider	De-duplication of result notifications
Connection ID	`PaymentProvider.id`	cuid	System-wide	At connection creation	Path of the result-notification URL
Merchant ID	`Merchant.merchantCode`	`MER-` + 5-digit sequence	System-wide	At merchant creation	`merchant_id` in merchant webhooks, part of the invoice number
Receipt number	`Receipt.receiptNo`	`RC-YYYYMM-00001` (monthly sequence)	System-wide	At issue (PSP dashboard / payment page / merchant portal)	Documents

Identifier	Column	Format	Uniqueness	Issued	Used for
Invoice number	`SettlementBatch.invoiceNo`	`INV-YYYYMM-<merchant number>-<2-digit sequence>` (the period's start month; the merchant's confirmation order within the month)	System-wide (`@unique`)	Assigned and stored when the batch is confirmed (1.1.0; previously computed at PDF generation as `INV-YYYYMM-<merchant number>` and duplicated across batches of one month)	Invoice PDF, `invoiceNo` in the merchant API `settlements`, global search
Deposit notification number	`DepositNotification.notificationNo`	`DN-00001` (sequence)	System-wide	When a deposit notification is received (1.1.0)	Deposit notification log
Deposit de-duplication key	`DepositNotification.dedupeKey` / `claimKey`	`<bank|cvs>:evt:<eventId>` or `<bank|cvs>:h:<sha256>`	`claimKey` system-wide (the first claiming row only)	When a deposit notification is received	Resend detection (3.2)

4.2 Mapping to provider identifiers

Provider identifier	Wire Pay counterpart	Today	Requirement for a live connection
Card / QR transaction ID (Stripe PaymentIntent ID, PayPay merchantPaymentId, …)	`Payment.externalId`	Wire Pay generates a pseudo ID and expects result notifications to return it in `data.externalId`	R4-1: overwrite `externalId` with the provider's transaction ID obtained from the authorize / capture response and match notifications on it; or pass Wire Pay's generated `externalId` to the provider as its reference (`merchantPaymentId` etc.) and have notifications echo it
Virtual account number / collection customer & confirmation numbers	None (matching by transfer ID)	The customer prefixes the transfer ID to the payer name	R4-2: when accounts / numbers are issued per order, keep an account-number → transfer ID (or transaction ID) map in the adapter and translate deposit notifications into `transferId`; respect the merchant's length setting (7 / 8)
Konbini receipt / slip number	`Payment.cvsReceiptNo`	Wire Pay generates the 13 digits	R4-3: when the agency issues the number, normalise it to 13 digits (first non-zero) into `cvsReceiptNo`, or translate through a map
Notification event ID	`WebhookEvent.externalEventId`	Stored as-is	R4-4: must be unique and immutable
Chargeback / dispute case ID	None	Entered manually by the PSP (`Chargeback` has no external ID column)	R4-5: future column (※要確認: not implemented)

4.3 Uniqueness and collisions

- Transfer IDs and receipt numbers are random; the DB unique constraint detects a collision and one redraw is attempted (two consecutive collisions answer 409 `conflict`). The 7-digit space holds 9 × 10^6 values, the 13-digit space 9 × 10^12.
- Transfer IDs and receipt numbers are unique across environments (test / live). A test deposit notification could in theory match a live transfer ID, but the mandatory `mode` is compared with the transaction's `livemode` and a mismatch is held as an unmatched deposit instead of reconciled (1.1.0, 3.2).
- `externalId` is unique per connection (`providerId`). Separate test and live connections of the same definition form separate namespaces.

4.4 Not implemented / planned (chapter 4)

- No path stores the provider transaction ID into `externalId` (no authorize / capture response ingestion).
- No columns for virtual account numbers or chargeback case IDs.

5. Reconciliation and short / excess handling


5.1 Decision logic (`reconcileDeposit`)

Deposit reconciliation is the pure function `reconcileDeposit(amount, alreadyDeposited, deposit, waiting)` in `lib/payments/transfer.ts`, shared by bank transfers (`waiting = awaiting_transfer`) and konbini (`waiting = awaiting_payment`, 1.1.0). The PSP dashboard's reconciliation dialog previews the outcome with the same function.

```
total = alreadyDeposited + deposit           # cumulative deposits
if total <  amount → status = waiting,  diff = "short"     # short: stays put; the next deposit accumulates
if total == amount → status = captured, diff = null        # exact: completed
if total >  amount → status = captured, diff = "excess"    # excess: completed + excess flag
```

Outcome	**`Payment`** update	Merchant webhook	Customer e-mail	PSP follow-up
Short	`depositAmount = total`, `depositDiff = "short"`, `depositDiffStatus = "open"`; status unchanged	None	None (the `deposit_short` mail is sent when the PSP marks "customer notified")	"Short / excess deposits" screen → notify the customer → re-evaluated by the next deposit
Exact	`status = captured`, `capturedAt`, `depositAmount = total`, `depositDiff = null`, `depositDiffStatus = null` (konbini also `cvsPaidAt`)	`payment.completed`	`payment_completed`	None
Excess	`status = captured`, `capturedAt`, `depositAmount = total`, `depositDiff = "excess"`, `depositDiffStatus = "open"`	`payment.completed`	`payment_completed`	"Short / excess deposits" → file a refund request for the excess (reason `duplicate`, amount = excess) → `refund.completed` on approval

- Preconditions: the transaction is `awaiting_transfer` (with a transfer ID) or `awaiting_payment` (with a receipt number) = `WAITING_STATUSES`. A deposit on a transaction with neither answers 400 `not_bank_transfer`.
- The deposit must be a positive integer; otherwise 400 `invalid_input`.
- Decision and update run in one transaction with a status-conditioned update, so two simultaneous (different) notifications leave one with 409 `invalid_transition` (deposits after completion are refused, 5.4). A resend of the same notification is stopped earlier by the deposit-log de-duplication (3.2).
- A late deposit (`late_deposit`, 5.3) uses the same `reconcileDeposit` but moves to `captured` even when short, keeping `depositDiff = short`.




5.2 Follow-up status of short / excess deposits (`depositDiffStatus`)

Value	Label	Transition
`open`	Open	Set automatically at reconciliation
`refund_arranged`	Refund arranged	Excess × open → PSP "Refund the difference" (`createRefundRequest`, reason `duplicate`, `reason = "excess deposit (<transfer ID>)"`)
`notified`	Customer notified	Short × open → PSP "Mark as notified" (mail `deposit_short`: transfer ID, shortfall, amount due, deadline)
`resolved`	Resolved	Any state → PSP "Resolve"

API: `GET /api/deposit-diffs`, `POST /api/deposit-diffs/{paymentId}/refund|notify|resolve` (permission `deposit_diff.update` = admin / accounting / cs; audit `payment.deposit_diff_update`).

5.3 Unmatched deposits (deposits without a usable transfer ID)



Operation	API	Permission	Errors
Register (manual)	`POST /api/unmatched-deposits { amount, payerName, receivedAt?, bankReference?, givenTransferId?, note? }`	`unmatched_deposit.register` (admin / accounting / cs)	Invalid `receivedAt` 400
Candidates	`GET /api/unmatched-deposits/{id}` → `{ deposit, candidates[] }` (up to 20, with `exact` (balance match) and `overdue` flags; the transaction named by the notification (`candidatePaymentId`) comes first with `modeMismatch` / `late` / `status` , and mismatched / expired candidates cannot be selected on the screen)	view	
Match	`POST /api/unmatched-deposits/{id}/match` `{ transferId }` → `{ deposit, payment, renotified }`	`unmatched_deposit.match` (admin / accounting)	Unknown / not a bank transfer 404 `transfer_not_found` ; environment mismatch 409 `mode_mismatch` ; not awaiting 409 `invalid_transition` ; already handled 409 `deposit_not_open`
Apply as late deposit (1.1.0)	`POST /api/unmatched-deposits/{id}/late-match` `{ reason }` (reason required) → `{ deposit, payment, renotified }` . When the named transaction (`candidatePaymentId`) is `expired` , `applyPaymentAction(late_deposit, actor dashboard)` moves it to `captured` ; it completes even when the amount differs and records the difference in `depositDiff` . On completion `payment.completed` and the completion e-mail follow. Audit `deposit.late_match` + `payment.late_deposit`	`unmatched_deposit.match` (admin / accounting)	No named transaction / not `expired` 409 `invalid_transition` ; already handled 409 `deposit_not_open` ; missing reason 400

Operation	API	Permission	Errors
Dismiss	`POST /api/unmatched-deposits/{id}/dismiss` `{ reason, kind? }` (`kind`: `returned` = return / refund arranged, `other` = default; 1.1.0). Deposits on cancelled transactions can only be dismissed	`unmatched_deposit.dismiss`	Already handled 409 `deposit_not_open`
API re-notify	`POST /api/payments/{id}/renotify` (completed bank transfers only)	`payment.renotify` (admin / cs / developer)	Not a bank transfer 409 `not_bank_transfer`; not completed 409 `invalid_transition`; no merchant 409 `no_merchant`

5.4 Deadlines

Item	Specification
Deadline	Bank: creation + `Merchant.transferDueDays` (default 7, 1–60). Konbini: creation + `Merchant.cvsDueDays` (default 3, 1–30). Both in `Payment.transferDueAt`
Automatic expiry	The cron `GET/POST /api/cron/expire-transfers` (`CRON_SECRET`) applies `expire` (actor `system`, audit `cron`) to up to 200 transactions per run with `transferDueAt < now` and a status in `WAITING_STATUSES` (`awaiting_transfer` / `awaiting_payment`). Merchant webhook `payment.expired`. The frequency is the deployment's cron definition (8.4; the demo's `vercel.json` runs it once a day, hourly is recommended in production)
Manual expiry	PSP dashboard "Expire"; before the deadline 409 `not_overdue`
Deposits after expiry	Once `expired`, a deposit notification with a matching transfer ID / receipt number is held as an unmatched deposit (**`reason = late_deposit`**, **`candidatePaymentId`** = the transaction) with 202 (1.1.0; it used to be refused with 409 and left no record). The PSP either applies it ("Apply as late deposit", the `late_deposit` transition, reason required; completes even when the amount differs and records the difference in `depositDiff`) or dismisses it (kind "return arranged" = refund handled outside the system). A deposit on a `cancelled` transaction is held as `cancelled_deposit` and can only be dismissed
Deposits near the deadline	The cron re-checks `transferDueAt` in real time, so a deposit may still reconcile until the cron runs; concurrent races are resolved by the status-conditioned update
Overdue tab	The PSP dashboard's payment-application list filters "overdue (status unchanged)" with `?overdue=1` (1.1.0); this is distinct from the `expired` status

Item	Specification
Daily digest	The notifications cron raises "overdue bank transfers: N", "overdue konbini payments: N" and "late deposits: N (unprocessed unmatched deposits)" once a day to the PSP notification centre (`transfer.overdue` / `cvs.overdue` / `deposit.late`)

5.5 Requirements for a live connection

Requirement	Content
R5-1	One notification per deposit; resend with the same `eventId` (Wire Pay de-duplicates; a resend without `eventId` relies on the content hash, and another deposit of the same amount in the same minute could be mistaken for a duplicate)
R5-2	Include the deposit time (`receivedAt`), bank reference (`bankReference`) and environment (`mode`) so unmatched deposits can be matched, environments checked and audited
R5-3	Provide a way to return money for post-expiry or unknown deposits on the provider / adapter side (Wire Pay only records the dismissal kind "return arranged" and moves no funds)
R5-4	Decide with merchants whether partial deposits (several transfers) are acceptable; Wire Pay accepts them automatically through cumulative evaluation

5.6 Not implemented / planned (chapter 5)

- Late deposits are applied only by a manual PSP action (never automatically). Returning the money happens outside the system.

---

6. Authorization, capture, void, refund, chargeback


For each operation this chapter pairs Wire Pay's status handling (implemented) with the operation required with the provider (requirement for a live connection). The transition table is identical to Specification A, 2.3 (`lib/payments/transitions.ts`) and is not repeated.

6.1 Operations and Wire Pay's handling

Operation	Wire Pay trigger (implemented)	Effect (**`applyPaymentAction`**)	Merchant webhook	Provider operation (requirement)
Authorize	Creation with `autoCapture: false` (credit / qr), payment-link checkout, test card `4000000000003220`	`authorized` (history `created` → authorized)	None	R6-1: call the authorize API and store the provider transaction ID in `externalId`

Operation	Wire Pay trigger (implemented)	Effect (**`applyPaymentAction`**)	Merchant webhook	Provider operation (requirement)
Capture	Creation with `autoCapture: true`, PSP "Complete", payment page "Complete payment", result notification `payment.captured`	`captured`, `capturedAt`	`payment.completed`	R6-2: capture API (on an authorization); a single authorize + capture call for immediate sales
Void (cancel)	PSP "Cancel", result notification `payment.cancelled`	`cancelled`, `cancelledAt`	`payment.cancelled`	R6-3: authorization reversal API; invalidate bank / konbini numbers
Fail	PSP "Fail", result notification `payment.failed`, creation-time rejection (limit, blacklist, test card)	`failed`, `failureReason`	`payment.failed` (creation-time rejections send only `limit.exceeded`)	R6-4: ingest declines and errors (`failureReason` reason codes)
Expire	The expiry cron, PSP "Expire"	`expired`	`payment.expired`	R6-5: number invalidation notice (optional)
Deposit	Deposit notification (bank / konbini), PSP "Reconcile deposit", matching an unmatched deposit	Chapter 5	`payment.completed` (on completion)	Chapters 3 and 5
Late deposit (late_deposit, 1.1.0)	"Apply as late deposit" on the unmatched-deposit screen	`expired` → `captured`, `capturedAt` (difference in `depositDiff`)	`payment.completed`	R5-3 (return facility)
Refund	Approval of a refund request (PSP), result notification `payment.refunded`	`partially_refunded` / `refunded`, `amountRefunded += amount`, `refundedAt` (full), `Refund.status = completed`	`refund.completed`	R6-6: refund API (partial / full). Today the refund completes at approval (`approved` / `processing` are skipped)
Chargeback	PSP registers → disputes → lost / confirmed	`chargeback` on lost / confirmed (from `captured` / `partially_refunded` / `refunded`)	`chargeback.opened` at registration only	R6-7: ingest dispute notifications; evidence submission API (optional)

6.2 Internal refund flow



- The result notification `payment.refunded` (3.1) bypasses the request flow and creates a `Refund` row directly as `completed` (`reasonCode = other`, no `requestedById`). It serves as the ingestion point for refunds executed on the provider side.
- The refundable balance is "amount − refunded − pending requests"; approval re-checks it.

6.3 Internal chargeback flow

Step	Wire Pay operation (PSP, permissions **`chargeback.create`** / **`chargeback.update`** = admin / accounting)	Effect
Register	`POST /api/chargebacks { paymentId, amount? (default = transaction amount), reasonCode, disputeDeadline? (default 14 days), evidenceNote? }`	`Chargeback(received)` , merchant webhook `chargeback.opened`
Dispute	`POST /api/chargebacks/{id}/dispute { evidenceNote }` (required)	`disputed`
Outcome	`POST /api/chargebacks/{id}/resolve { outcome: won | lost, note? }`	`won` (transaction unchanged) / `lost` (transaction → `chargeback` , `resolvedAt`)
Confirm	`POST /api/chargebacks/{id}/confirm` (from `received` / `disputed` / `lost`)	`confirmed` , transaction → `chargeback` , `resolvedAt` (now if unset)
Settlement deduction	`lost` / `confirmed` with `resolvedAt` in the period become `chargeback` lines	Chapter 7
Deadline	The notifications cron (minute 50) warns the PSP daily from 3 days before the deadline (`chargeback.deadline`)	

Disputes from the provider (card issuer / acquirer) are entered manually by PSP operators today. The `chargeback` status cannot be set directly on the dashboard; it results only from a lost or confirmed chargeback.

6.4 How status consistency is kept

Mechanism	Content
Status-conditioned update	`updateMany({ where: { id, status: { in: from } } })` : a transaction whose status is not an allowed source updates 0 rows → 409. Concurrent notifications and operations never apply twice
History	Every transition appended to `PaymentEvent(type, fromStatus, toStatus, amount, actor)`
Audit	`AuditLog` `payment.<action>` with before / after snapshots (actor types `admin` / `webhook` / `bank` / `cvs` / `system` / `merchant`)
Disabled provider	Operations on a transaction whose connection is `disabled` answer 400 `provider_disabled` (the ledger stays; transitions resume when the connection is re-activated)
Side effects isolated	Webhooks and e-mails are sent after commit and never fail the transition

6.5 Requirements for a live connection (summary)

Requirement	Content
R6-1 … R6-7	Rows of 6.1
R6-8	Call the provider API before the state transition and apply `applyPaymentAction` on success (the current `applyPaymentAction` has no external call; a calling layer must sit in front of the action, chapter 10)
R6-9	Operations that the provider settles asynchronously (capture after 3-D Secure, refunds confirmed later) are ingested through result notifications (3.1)
R6-10	To actually use `approved` → `processing` → `completed` / `failed`, split `approveRefund` so that `applyPaymentAction(refund)` runs after the provider's response rather than at approval


6.6 Not implemented / planned (chapter 6)

- Provider API calls for authorize, capture, void, refund and ingestion of their responses.
- Automatic chargeback registration from provider notifications and an evidence submission API.
- Real use of refund statuses `approved` / `processing` / `failed`.

---

7. Settlement and the flow of funds

7.1 Where the funds flow



Leg	Implementation at the target commit	Requirement
Customer → provider	External. Wire Pay learns of it through result / deposit notifications (chapter 3)	—
Provider → Wire Pay	None. No ingestion or matching of provider settlement deposits or provider fees	R7-1: ingest the provider's settlement statement (transactions, amounts, fees, deposit date) and match it against Wire Pay transactions
Wire Pay → merchant	Status management of settlement batches (generate, confirm, schedule, paid). No transfer is executed	R7-2: a payout API (Zengin / bank API) that moves `scheduled` batches to `paid`
Wire Pay → agent	Monthly aggregation and CSV only	—

7.2 Settlement batch calculation

Formulas, cycles, payout terms, line aggregation and status transitions are identical to Specification A, chapter 9 (same `lib/settlements/service.ts`). Only points relevant to provider connections are added here.

Aspect	Content
Nature of the fee	The fee deducted in settlement is the Wire Pay (PSP) → merchant contract rate (`MerchantFeeSchedule`, per-method `ratePercent` + `fixedFee`). Fees the provider charges Wire Pay (interchange, acquiring fees) are not modelled
Completion-date basis	Sale lines use `capturedAt`, refund lines `completedAt`, chargeback lines `resolvedAt` within the period, independent of the provider's deposit or closing dates
Environment	Separate batches per `livemode`; test batches are never paid (demo)
Qualified invoice	An invoice for the Wire Pay → merchant payment fees (tax-inclusive, per rate, rounding). Invoices between Wire Pay and providers are out of scope
Line sources	`SettlementLine.paymentId / refundId / chargebackId` are string references (no FK); the ledger survives source deletions
Invoice number	`SettlementBatch.invoiceNo` is assigned at confirmation (`confirm`) as `INV-YYYYMM-<merchant number>-<2-digit sequence>` and stored (unique; the merchant's confirmation order within the month; one retry on a uniqueness violation). The PDF, the merchant API and global search use the stored value. Batches confirmed before 1.1.0 are numbered by `npm run db:backfill` (`runPhase1Backfill`, idempotent)

7.3 Matching provider settlements (requirements)

The target commit has no tables or screens for provider settlement statements. A live connection needs adapters and tables meeting:

Requirement	Content
R7-3	Ingest the provider's statement (amount, fee, expected deposit date per transaction / `externalId`)
R7-4	Match against Wire Pay's completed transactions (`captured` and later) and report differences
R7-5	Decide whether the provider's deposit confirmation triggers `scheduled` → `paid` on merchant batches or whether they run independently (※要確認: business decision)

7.4 Not implemented / planned (chapter 7)

- Provider fee and provider statement models, funds movement (payout) API connection, automatic generation per cycle (Specification A, 9.10).


---

8. Incident operations

8.1 Payment-method suspension

For a provider-side incident (card network outage, collection agency downtime, …) the PSP can stop new checkouts only for a method. In-flight transactions (completion, refunds, deposits) are unaffected.

Item	Specification (**`lib/payments/method-controls.ts`**, **`PaymentMethodControl`**)
Scope	Global (`scope = global`, admin) / per merchant (`scope = merchant`, admin / cs)
Methods	`credit` / `qr` / `convenience` / `bank` ("other" is not controllable)
Required	A reason (`reason`)
Auto-resume	With a future `resumeAt`, the cron `GET/POST /api/cron/payment-method-controls` (minute 45) resumes it (audit `payment_method.resume`, notification `payment_method.resumed`)
Effect	The shared creation path answers 409 `method_suspended` (API, PSP dashboard, payment links, subscriptions alike); the method disappears from the payment page and the creation form
Visibility	PSP dashboard: a red banner on every page while a global suspension is active. Merchant portal: "Payment methods" with reason and resume time
Notifications	A notification centre entry on suspension (global = critical, per merchant = warning). A global suspension offers to draft an `incident` announcement
API	`GET /api/payment-method-controls[?merchantId=]`, `PUT /api/payment-method-controls { scope, merchantId?, method, suspended, reason, resumeAt? }`
Audit	`payment_method.suspend` / `payment_method.resume`


Provider
PSP operator
Wire Pay
Merchant
incident notice (today: outside the system)
PUT /api/payment-method-controls {scope: global, method, suspended: true, reason, resumeAt?}
notification centre critical / red banner / incident announcement draft
publish the announcement (incident, updates: occurred → investigating → resolved)
new transaction → 409 method_suspended / method hidden on the payment page
GET /api/merchant-api/announcements / portal
recovery notice
suspended: false (or auto-resume via resumeAt)
notification payment_method.resumed / announcement resolved → ended
Provider
PSP operator
Wire Pay
Merchant

8.2 Resending notifications

Direction	Mechanism
Wire Pay → merchant webhooks	Automatic retries 1 min → 5 min → 30 min → 2 h → 24 h (cron `/api/cron/webhook-retry`, 8.4), abandoned after 5 → notification centre critical (`webhook.abandoned`). Deliveries to an environment without a signing secret are not sent but logged as `failed` (`signing_secret_missing`) with a warning (1.1.0). Manual resend by the PSP (permission `webhook.resend` = admin / developer; a confirmation shows the transaction's current status and the last successful delivery) and by the merchant. Details in Specification A, 6.4 / 6.6
Provider → Wire Pay result notifications	Wire Pay cannot request a resend; it relies on the provider's retries (3.1; duplicates are removed by event ID)
Provider → Wire Pay deposit notifications	Same. Resends are safe because they are de-duplicated on `eventId` (or the content hash) (3.2). A missed deposit can be typed in by the PSP as an unmatched deposit and matched (5.3). Receipt is recorded in the deposit notification log
Re-notifying a bank transfer to the merchant	`POST /api/payments/{id}/renotify` (resends `payment.completed`; completed bank transfers only)

8.3 Notification centre integration

PSP notifications (`lib/notifications/*`) relevant to provider operations. Severities are defaults; e-mail / Slack delivery follows each admin's preferences.

Kind	Severity	Trigger	Roles
`payment_method.suspended`	critical (global) / warning (per merchant)	Method suspended	everyone / admin, cs
`payment_method.resumed`	info	Auto-resume	everyone
`webhook.abandoned`	critical	Merchant webhook failed 5 times	admin, developer
`batch.failed`	critical	A cron job threw (`runCron` wraps expiry, webhook retry, subscriptions, method resume, notifications, anonymisation)	admin, developer

Kind	Severity	Trigger	Roles
`transfer.overdue` / `cvs.overdue`	warning	Overdue transfers / konbini payments (once a day)	admin, accounting, cs
`deposit.late`	warning	Unprocessed deposits that arrived after expiry / cancellation (once a day, 1.1.0)	admin, accounting, cs
`webhook.signing_secret_missing`	warning	A merchant webhook that could not be sent for lack of a signing secret (once per 24 hours per merchant × environment, 1.1.0)	admin, developer
`limit.exceeded`	warning	Merchant limit exceeded	admin, accounting, cs
`blacklist.candidate`	warning	Repeated-failure detection	admin, cs
`chargeback.deadline`	critical	Dispute deadline within 3 days	admin, accounting
`subscription.payment_failed`	warning / critical	Subscription charge failed / suspended	admin, accounting, cs
`settlement.generated` / `settlement.held`	info / warning	Batch generated / held	admin, accounting
`refund.requested`	info	Refund request	admin, accounting

The same kind and target is raised at most once per 24 hours. Delivery goes to `GlobalSetting.slackWebhookUrl` (Slack Incoming Webhook, 8-second timeout, one retry, `SlackLog`) and by e-mail through the `notification` template.

8.4 Cron jobs and outages

Cron	Demo **`vercel.json`** (UTC)	Recommended in production	Work	Effect when stalled
`/api/cron/expire-transfers`	daily 01:00	hourly	Expire overdue transfers / konbini slips	Expiry is delayed (deposits still reconcile)

Cron	Demo `vercel.json` (UTC)	Recommended in production	Work	Effect when stalled
`/api/cron/webhook-retry`	daily 01:30	hourly	Send due merchant webhook retries	Retries are delayed (in the demo the 1 min → 5 min ⋯ schedule effectively becomes daily)
`/api/cron/subscriptions`	daily 02:15	hourly	Charge subscriptions	Charges are delayed
`/api/cron/payment-method-controls`	daily 02:45	hourly	Resume suspensions past `resumeAt`	Auto-resume is delayed
`/api/cron/notifications`	daily 03:50	hourly	Daily digests (overdue, late deposits, chargeback deadlines) and pending e-mail / Slack fan-out	Notifications are delayed
`/api/cron/merchant-daily-summary`	daily 00:00 (09:00 JST)	same	Merchant daily summary mail for the previous day (1.1.0)	Summaries are delayed (a re-run never duplicates)
`/api/cron/anonymize`	daily 19:00 (04:00 JST)	same	Personal-data retention	Anonymisation is delayed
`/api/demo/reset`	daily 18:00	do not register	Demo data reset (public demo only; never register on real data)	—

The demo's `vercel.json` spreads the jobs over one run a day because of the Hobby plan (`README.md`); hourly runs are recommended in production, and Docker deployments call the same URLs from any scheduler. All require `Authorization: Bearer <CRON_SECRET>` and answer 404 when it is unset. Exceptions raise `batch.failed` and the route answers 500 (recorded as a failed invocation by Vercel).

8.5 Recovery procedure (PSP operations)

1. Recognise the provider incident → suspend the method globally (reason, resume time) → publish an incident announcement (`occurred`).
2. Review result / deposit notifications that failed during the incident (400 / 409 / 5xx) in `WebhookEvent.error` and the audit log; ask the provider to resend.
3. On recovery → lift the suspension (or auto-resume) → add `investigating` / `resolved` updates → end the announcement.
4. Resend abandoned merchant webhooks from the webhook log; match missed deposits from unmatched deposits.
5. If the expiry cron was stalled, the first run after recovery processes up to 200 per run (the rest on later runs).

8.6 Requirements for a live connection

Requirement	Content
R8-1	A systematic way to receive provider outage / recovery (status API / notification). Today the PSP suspends manually
R8-2	Alignment of the provider's retry policy with Wire Pay's event-ID de-duplication (3.5)
R8-3	A policy for transactions left `authorized` during an outage (auto-void / expiry) (※要確認: `authorized` has no deadline)

8.7 Not implemented / planned (chapter 8)

- Automatic detection / suspension on provider outages, automatic voiding of `authorized` transactions, automatic retry of failed cron runs.

---

9. Security requirements

9.1 Signatures

Direction	Scheme	Implementation
Provider → Wire Pay (result notifications)	`Wirepay-Signature: t=<UNIX seconds>,v1=<hex HMAC-SHA256(secret, "<t>.<raw body>")>`. Tolerance ±300 s. Constant-time compare. The secret is the connection's `webhook_secret` (stored AES-GCM encrypted, decrypted on use)	`lib/webhooks/verify.ts`, `app/api/webhooks/[providerId]/route.ts`
Provider → Wire Pay (deposit notifications)	Bearer token `DEPOSIT_NOTIFY_SECRET` (environment variable, constant-time compare). No signature	`app/api/demo/deposit-notify/route.ts`, `cvs-notify/route.ts`

Direction	Scheme	Implementation
Wire Pay → merchant (webhooks)	`X-Signature: v1=<hex HMAC-SHA256(secret, "<X-Timestamp>.<payload>")> + X-Timestamp`, plus the compatible `Wirepay-Signature: t=..,v1=..`. Secret: the merchant's signing secret per environment. No delivery to an environment without a usable secret (fail closed; logged as `failed` / `signing_secret_missing`; the password fallback was removed in 1.1.0). The test secret is issued automatically at merchant registration	Specification A, 6.4
Cron / demo reset	Bearer `CRON_SECRET` (constant-time compare)	`app/api/cron/*`

Requirements for a live connection: R9-1 add a signature or per-provider token to deposit notifications (one shared Bearer today). R9-2 a secret rotation procedure (`webhook_secret` can be updated through the connection form on the PSP dashboard; there is no overlap period with the old secret).

9.2 IP restrictions

Target	Implementation
Provider → Wire Pay notifications	No IP restriction (`/api/webhooks/*` and `/api/demo/*` are `ipRestricted: false` and pass the middleware). Authentication by signature / token only
PSP dashboard	Callers matching `IpRestriction(target = admin, mode = deny)` are blocked from pages and APIs (403 `ip_blocked`, `details.reason = "deny"`). With the allow-list mode (`GlobalSetting.ipAllowlistAdmin`, 1.1.0) on, callers matching no enabled allow rule are blocked too (`reason = "not_in_allowlist"`). Switching it on requires at least one allow rule that covers the operator's own address, and while it is on, allow-rule changes that would drop the operator's address are refused (400 `ip_self_block`). IPv4 only
Merchant API	`IpRestriction(target = merchant_api, merchantId)` deny rules. With the allow-list mode (`ipAllowlistMerchantApi`) on, merchants that have allow rules also block non-matching callers (both `/api/merchant-api/*` and `/api/v1/*`; Specification A, 10.1)
Switch API	`GET/PUT /api/ip-restrictions/allowlist { target, enabled }` (permission `ip_restriction.update` = admin / developer; audit `global_setting.update`). No allow rule → 400 `allowlist_no_rules`

Requirement for a live connection: R9-3 when a provider's egress range is fixed, implement a per-route allow list in the adapter layer or a WAF (Wire Pay itself has no inbound allow list).

9.3 Key management

Key	Use	Specification (**`lib/crypto.ts`** etc.)
`ENCRYPTION_KEY`	AES-256-GCM encryption of provider secret fields, merchant passwords, signing-secret ciphertexts and admin TOTP secrets	base64 32 bytes (43 chars + `=`). 12-byte random IV per encryption, 16-byte auth tag; ciphertext `iv:tag:data` (base64 each). Fail-closed: in production a missing / malformed key throws at start-up / use (API 500 `encryption_key`). Development only: a fixed dev key with a warning
`SESSION_SECRET`	HMAC for the admin session cookie, the merchant session cookie (separate derivation with the `wirepay-merchant-session:` prefix) and receipt download URLs (`wirepay-receipt:` prefix)	Falls back to `ENCRYPTION_KEY`
`CRON_SECRET`	Bearer for cron / demo reset	Unset → cron routes answer 404 (expiry, retries, charges, notifications, anonymisation stop)
`DEPOSIT_NOTIFY_SECRET`	Bearer for deposit notifications	Unset → 404 in production, open in development
Provider `webhook_secret` and other secret fields	Result-notification verification etc.	Stored per connection in `PaymentProvider.credentials` (JSON) as ciphertext; displayed as `••••••••` + last 4; blank on edit = unchanged
Merchant API keys	Merchant API authentication	SHA-256 hash only; plaintext shown once at issue / rotation
Merchant signing secrets	Merchant webhook signing	Hash plus an AES-GCM ciphertext (`ApiKey.secretEnc`) decrypted at send time

Changing `ENCRYPTION_KEY` makes existing ciphertexts undecryptable: the API answers 422 `undecryptable` and the UI shows "undecryptable" (the demo database is re-seeded instead). Key rotation (key versions in ciphertexts) is not implemented.

9.4 Not holding personal data

Item	Specification
Card number (PAN) and security code	Never stored. The public API's `card.number` is used only for Luhn validation, brand detection and deriving the last 4 and the fingerprint (`sha256(brand|last4|expiry)`); `cvc` is not even validated. The PSP dashboard's creation form takes brand, last 4 and expiry only
Stored cards (`PaymentToken`)	Brand, last 4, expiry, fingerprint. No column for a provider token
Customer personal data	Name, e-mail, phone and source IP in plain columns, masked on PSP screens, masked at write time in the audit log, anonymised after the retention period (default 24 months) (Specification A, 10.5)
Data passed to providers (requirement)	R9-4: a live connection handling PANs must rely on the provider's tokenisation / hosted fields / 3-D Secure redirects so that Wire Pay's servers never receive the PAN (keeping Wire Pay out of PCI DSS scope)

9.5 Transport, authorization and audit

Item	Specification
Authorization of receiving endpoints	Result notifications: per-connection `providerId` + signature. Deposit notifications: shared token. Dashboard CSRF / session checks do not apply
Authorization of management actions	`lib/role.ts` permission matrix (complete table in Specification A, Appendix E). Creating / updating / deleting / testing provider connections: `admin` / `developer`; global method suspension: `admin`; deposit reconciliation: `admin` / `accounting`; matching unmatched deposits (including late deposits): `admin` / `accounting`; dismissing: `admin` / `accounting` / `cs`; IP restrictions and the allow-list mode: `admin` / `developer`
Audit log	Every change in `AuditLog` (actor types `admin` / `merchant` / `system` / `webhook` / `bank` / `cvs` / `cron` / `seed`; snapshots redact secret keys as `[redacted]` and mask personal-data keys)
Rate limits	None on provider inbound. PSP dashboard mutation APIs 60 / minute per IP. Merchant APIs (`/api/v1`, `/api/merchant-api`) 60 / minute per merchant × environment (counted in the database; extended to the merchant API in 1.1.0)
Security headers	Set in Next.js `next.config.js` (※要確認: the concrete header values are out of scope here)

9.6 Not implemented / planned (chapter 9)

- Signatures / per-provider tokens for deposit notifications, inbound IP allow lists, key rotation (KMS), a provider token column.

---

10. Adding a new provider

This chapter is for developers adding or implementing provider connections on the Wire Pay side. Following the structure of the target commit it separates (A) what can be done with connection settings alone (the current mechanism) from (B) the implementation steps for a live connection with real traffic (a design to meet the requirements). The repository's working rules (`CLAUDE.md`) apply.

10.1 (A) Adding connection settings (possible with the current mechanism)


1. Add the provider definition — append a `ProviderDefinition` to `PROVIDERS` in `lib/providers/registry.ts`.
   - `key` (unique, lower case + `_`), `name` / `description` (`{ ja, en }` both mandatory), `category` (`credit` / `qr` / `convenience` / `bank` / `other`), `logoColor`, `docsUrl` (optional), `supportsTestMode`.
   - `fields`: inputs. `type` (`text` / `password` / `secret` / `url` / `email` / `select` / `textarea`), `required`, `secret: true` (encrypted storage, masked display), `placeholder` (technical strings only), `helpText` (`{ ja, en }`), `options` for `select`.

    - Name the secret used to verify result notifications **`webhook_secret`** (`app/api/webhooks/[providerId]/route.ts` reads that key).
2. Dictionaries — all copy lives in the definition as `LocalizedText`. Extra UI strings go into both `lib/i18n/messages/ja.ts` and `en.ts` (one side alone is a type error).
3. Connection test — `runConnectionTest` checks required fields and URL format only. Provider-specific checks go into `lib/providers/connection.ts` (for network calls see 10.2).
4. Seed (optional) — to ship a demo connection, add a fixed-ID `upsert({ update: {} })` to `prisma/seed-data.ts`.
5. Verify — `npm run verify` (lint → typecheck → check:i18n → check:permissions → test → build). Extend `lib/providers/*.test.ts` where definitions are tested.
6. Operate — the provider appears under its category in "Payment providers → Add" on the PSP dashboard. Register separate test and live connections.

Within this scope the new provider takes part in provider selection at creation, environment separation and result-notification reception (when **`webhook_secret`** exists), but no external traffic occurs.

10.2 (B) Implementing a live connection with real traffic (design guidance)

The target commit has no adapter layer; the following is design guidance for an addition (not implemented).



Step	Content	Existing modules involved
B-1 Adapter interface	Implement a `ProviderAdapter` with `authorize(input) → { externalId }`, `capture(externalId, amount)`, `void(externalId)`, `refund(externalId, amount) → { refundId }` in `lib/providers/adapters/<key>.ts`. Obtain credentials via `readCredentialsForUse(providerKey, credentials)` (never import `lib/crypto` directly)	`lib/providers/credentials.ts`
B-2 Hook into creation	Call authorize / capture before the row is written in `createTransaction`; on success store the `externalId`, on failure record `failed` + `failureReason` (the same path as the test cards' `forcedFailure`). `Payment.externalId` is unique per `(providerId, externalId)`	`lib/payments/create.ts` (replacing `generateDemoExternalId`)
B-3 Hook into actions	Call the adapter right before `applyPaymentAction` (PSP capture / cancel, refund approval `approveRefund`). Split refunds into `approved` → provider response → `completed` / `failed` (R6-10)	`lib/payments/actions.ts`, `lib/refunds/service.ts`, `app/api/payments/[id]/[action]/route.ts`
B-4 Result-notification mapper	A route for the vendor's webhook (e.g. `/api/webhooks/stripe/{providerId}`) verifies the vendor signature → converts to `{ id, type, data: { externalId, amount } }` → reuses the existing processing (de-duplication, `EVENT_TO_ACTION`). Extend `lib/webhooks/events.ts` and `EVENT_TO_ACTION` for missing types (authorized only, partial capture, chargeback)	`lib/webhooks/verify.ts`, `lib/webhooks/events.ts`
B-5 Deposit mapper	Convert bank / agency notifications to `{ transferId, amount, payerName, bankReference, receivedAt, mode }` / `{ receiptNo, amount }` and call `applyPaymentAction(deposit)` or `registerUnmatchedDeposit`. Add event-ID de-duplication (none today)	`lib/payments/actions.ts`, `lib/deposits/service.ts`

Step	Content	Existing modules involved
B-6 Credential fields	Add the needed fields to `registry.ts` (`secret: true` for secrets). Existing connections can be extended with `PATCH /api/providers/{id}`	`lib/providers/registry.ts`
B-7 Tests	Route Handler integration tests (`tests/integration/*.test.ts`, SQLite `prisma/test.db`) with a stubbed `fetch` covering adapter → transition → merchant webhook (`WEBHOOK_DELIVERY=queue` to inspect the queue). Add screen checks to the Playwright smoke (`tests/smoke-ops.mjs`)	`tests/`
B-8 Audit and notifications	Record adapter failures with `recordAudit` and the notification centre (`emitNotification`; new kinds go into `NOTIFICATION_KINDS` and the dictionary `notificationEnums.*`)	`lib/audit.ts`, `lib/notifications/*`
B-9 Documentation	Update the admin manual `content/manual/{ja,en}/*.md`, `CLAUDE.md` and the relevant chapters of these specifications	—

10.3 Checklist when adding a provider

- ☐ The definition is in `PROVIDERS` with matching `{ ja, en }` copy (`npm run check:i18n` passes)
- ☐ Secret fields have `secret: true` and display masked
- ☐ The result-notification secret is named `webhook_secret` (when using the existing route)
- ☐ Test and live connections are registered separately with the right `testMode`
- ☐ Transaction creation picks a provider of the matching `category` (public API: the oldest active one)
- ☐ Signature verification, de-duplication and transitions of result notifications are covered by tests (`simulate-webhook` for manual checks)
- ☐ Deposit notifications (bank / konbini) translate to transfer IDs / receipt numbers and the reconciliation, short / excess and unmatched cases are verified
- ☐ Method suspension (global / per merchant) makes new checkouts answer 409

- ☐ Deleting a connection with transactions answers 409 `provider_has_payments` and disabling works instead
- ☐ `npm run verify` and the Playwright smoke pass; the manual and CLAUDE.md are updated

10.4 Not implemented / planned (chapter 10)

- The adapter layer, mappers and refund split of 10.2 are all unimplemented.

---

11. Not implemented / planned

The target commit of Wire Pay runs in demo mode; there is no "real sending" of payment processing. This chapter lists honestly what is unimplemented or still mocked with respect to provider connections.

11.1 Real sending not implemented

Item	Status
Provider API calls for authorize, capture, void, refund	None; everything is an immediate DB state transition
Ingesting the provider transaction ID	None; `Payment.externalId` is pseudo-generated by Wire Pay
Issuing virtual accounts / collection numbers, registering konbini receipt numbers with the agency	None; transfer IDs and receipt numbers are Wire Pay random numbers
Invalidation notices to providers on expiry / cancellation	None
Ingesting provider settlement statements and matching them; funds movement (merchant payouts, agent payments)	None; settlement is status management only
Automatic chargeback ingestion and evidence submission	None; PSP operators enter chargebacks manually
Real e-mail delivery	`EMAIL_PROVIDER=log` (record only) / `console`
External connectivity in the connection test	None; required fields and URL format only

11.2 Still mocked

Item	Status
Result-notification format	Wire Pay's own (`{ id, type, data: { externalId, amount } }` , Stripe-compatible signature); no vendor-format mappers
Deposit notifications	`/api/demo/deposit-notify` , `/api/demo/cvs-notify` (shared Bearer; since 1.1.0 with `eventId` de-duplication, `mode` matching and the deposit notification log; no vendor-format mappers)
Demo receiver for merchant webhooks	`/api/demo/webhook-receiver?result=ok|error|timeout`
PSP dashboard "Complete / Fail"	Manual demo actions for transitions a provider notification would perform in production

Item	Status
Payment page "Complete payment (demo)" / "Mark as paid at the store (demo)"	Substitutes for real card entry and counter payment
Subscription charge outcomes	Random failures at `RiskSetting.demoChargeFailPercent` (default 20 %)
Test card numbers	Scenario selection in test; in live the normal flow (immediate completion) because there is no network
Most connection fields	Stored and displayed only (`expiry_days`, `stores`, `webhook_url`, `callback_url`, `notify_url`, `statement_descriptor`, `api_endpoint`, `api_key`, …)

11.3 Gaps in the data model

Item	Status
Provider fees, provider statements, provider tokens (stored cards), external chargeback case IDs, virtual account numbers	No columns / tables
Per-provider deposit-notification tokens	None (`DEPOSIT_NOTIFY_SECRET` is shared; event IDs and de-duplication are implemented in `DepositNotification`)
Expiry of `authorized`	None (authorized transactions never expire)
Postgres migration history	Vercel uses `prisma db push` (the SQLite schema with the provider rewritten); the Docker path uses `migrate deploy`


11.4 Operational constraints

Item	Status
Rate limits	None on provider inbound; dashboard per-IP limits are in-process memory (best-effort across instances); merchant API limits are counted in the database
Key rotation	Changing `ENCRYPTION_KEY` makes existing ciphertexts undecryptable (no KMS / key versions)
IPv6	Not evaluated by IP restrictions
Demo caps	50 providers, 1,000 transactions, etc. (`DEMO_LIMITS`)


Appendix A: Data model (ER diagram)

Main models for payments, provider connections and settlement (`prisma/schema.prisma`), split into transactions / settlement / configuration & notifications (three diagrams since 1.1.0, one before). Enumerations are string columns validated by the application. Only the main columns are shown; see `prisma/schema.prisma` for all of them.


A.1 Transactions (transactions, result notifications, deposit notifications, refunds, chargebacks)



A.2 Settlement (batches, lines, invoice numbers, receipts, agents)



A.3 Configuration and notifications (merchant settings, API keys, IP restrictions, method suspension, global settings, merchant webhooks)



Other models (`AdminUser`, `AuditLog`, `Blacklist`, `RiskSetting`, `Notification*`, `SlackLog`, `EmailTemplate`, `EmailLog`, `Announcement*`, `ApiRateLimit`, `AnonymizeBatch`, `Plan`, `Subscription`, `PaymentLink`, `TransactionNote`) are in `prisma/schema.prisma`.

Appendix B: Configuration items

B.1 Environment variables (**`DEPLOY.md`**)

Variable	Required	Use (as relevant to provider connections)
`DATABASE_URL`	✅	SQLite (`file:`) or Postgres
`ENCRYPTION_KEY`	✅	AES-256-GCM key (base64, 32 bytes). Encrypts provider credentials, merchant passwords, signing secrets, TOTP. Fail-closed in production
`SESSION_SECRET`	optional	HMAC key for sessions and receipt URLs (falls back to `ENCRYPTION_KEY`)
`CRON_SECRET`	production ✅	Bearer for `/api/cron/*` and `/api/demo/reset`; unset → cron routes answer 404
`DEPOSIT_NOTIFY_SECRET`	optional	Bearer for `/api/demo/deposit-notify` and `/api/demo/cvs-notify`; unset → 404 in production / open in development
`APP_URL`	recommended in production	Resolves relative `notifyUrl`s, payment-link URLs and the OpenAPI `servers` (fallback `VERCEL_PROJECT_PRODUCTION_URL` → `VERCEL_URL` → `http://localhost:3000`)
`WEBHOOK_DELIVERY`	optional	`queue` queues merchant webhooks for the cron instead of sending immediately
`EMAIL_PROVIDER` / `EMAIL_DEFAULT_LANG`	optional	Mail provider (`log` / `console`) and customer mail language
`DEMO_READONLY`	optional	`1` makes DELETE and provider PATCH answer 403
`DEMO_LOGIN_HINT` / `DEMO_GENERAL_PASSWORD`	optional	Demo account display

B.2 Provider connection (**`PaymentProvider`**)

Item	Values
`providerKey`	The 15 definitions of 2.1
`category`	Set from the definition
`displayName`	1–80 characters
`status`	`active` / `disabled`
`testMode`	true / false
`credentials`	Per definition field (secrets as ciphertext)

B.3 Global settings (`GlobalSetting`, PSP dashboard "Global settings", admin)

Item	Default	Use
`viewerCsvExport`	false	Whether the viewer role may export CSV
`slackWebhookUrl`	—	Slack destination of the notification centre
`issuerName` / `issuerRegistrationNo` (`T` + 13 digits) / `issuerAddress` / `issuerTel`	—	Qualified-invoice issuer
`taxRounding`	`floor`	Consumption-tax rounding (`floor` / `round` / `ceil`)
`piiRetentionMonths`	24	Personal-data retention
`auditRetentionYears`	7	Audit-log retention
`csvPii`	`masked`	Personal data in CSV (`masked` / `full`)
`ipAllowlistAdmin` / `ipAllowlistMerchantApi`	false / false	IP allow-list mode per target (admin / merchant_api, 1.1.0; switched through `PUT /api/ip-restrictions/allowlist`)

B.4 Risk settings (`RiskSetting`, id `global`)

Item	Default	Use
`windowMinutes`	10	Window of repeated-failure detection (1–1440)
`maxFailures`	3	Failures that create a candidate (2–100)
`demoChargeFailPercent`	20	Demo subscription failure rate (0–100)

B.5 Per-merchant settings (`Merchant`, as relevant to provider connections)

Item	Default / constraints	Use
`enabledMethods`	`[]`	Enabled payment methods
`transferIdDigits`	7 (7 / 8)	Transfer ID length
`transferDueDays`	7 (1–60)	Transfer deadline
`cvsDueDays`	3 (1–30)	Konbini payment deadline
`refundWindowDays`	180 (0–365)	Refund window
`notifyUrl` / `notifyFormat` / `notifyParamSet` / `notifyIdFormat`	https / `json_post` / `standard` / `payment_id`	Merchant webhooks
`settlementCycle` / `payoutTerm` / bank account / `settlementFee` / `invoiceNumber` / `address`	`monthly` / `next_month_end` / — / 0 / — / —	Settlement
`MerchantFeeSchedule` (`plan`, `rates`, `effectiveFrom`)	—	Fees (history)
`MerchantLimit` (`perTransaction`, `daily`, `monthly`)	null = unlimited	Limits
`IpRestriction(target = merchant_api)`	—	Merchant-API IP restriction

Item	Default / constraints	Use
`PaymentMethodControl(scope = merchant)`	—	Per-merchant method suspension

B.6 Cron (`vercel.json`)

See the table in 8.4.

Appendix C: Vendor notification mapping (reference, not implemented)

Not implemented — a reference for adapter design. Wire Pay's result notification (3.1) accepts only the four types of its own format `{ id, type, data: { externalId, amount } }`, and no adapter translates vendor-specific notifications. The table proposes how the events of major vendors would map onto Wire Pay's inbound events when the notification mapper of 10.2 (B-4) is implemented. Vendor event names and payloads follow each vendor's published documentation; the table is a guide to the correspondence only (amounts may need converting from the vendor's minor unit to whole yen).

Vendor	Vendor event	Wire Pay inbound event (`type`)	Value for `data.externalId`	`data.amount`	Notes
Stripe	`payment_intent.succeeded`	`payment.captured`	`payment_intent.id` (`pi_…`)	—	With `capture_method: manual`, `amount_capturable_updated` leaves the transaction authorized (Wire Pay has no authorized-only inbound event; express it with `autoCapture: false` at creation)
Stripe	`payment_intent.payment_failed`	`payment.failed`	`payment_intent.id`	—	Design: copy `last_payment_error.decline_code` into `failureReason` (the current inbound event carries no reason)
Stripe	`payment_intent.canceled`	`payment.cancelled`	`payment_intent.id`	—	
Stripe	`charge.refunded`	`payment.refunded`	`charge.payment_intent`	The delta of `amount_refunded`	Partial refunds send the delta; a full refund may omit `amount`
Stripe	`charge.dispute.created`	(no mapping)	—	—	Automatic chargeback ingestion is not implemented (R6-7, R4-5); the PSP enters it through `POST /api/chargebacks`
PayPay	`PAYMENT_COMPLETED` (`state: COMPLETED`)	`payment.captured`	`merchantPaymentId` (pass Wire Pay's `externalId` at creation, R4-1)	—	QR completes immediately; no authorization stage
PayPay	`PAYMENT_FAILED` / `state: FAILED`	`payment.failed`	`merchantPaymentId`	—	`EXPIRED` could map to `payment.cancelled`
PayPay	`REFUND` (`status: SUCCESS`)	`payment.refunded`	`merchantPaymentId`	`amount.amount`	No column holds the refund ID
GMO Payment Gateway	Result notification (status `CAPTURE` / `SALES`)	`payment.captured`	`AccessID` (or an `OrderID` → `externalId` map)	—	The notification arrives as a form POST; the adapter rebuilds it as JSON and signs it

Vendor	Vendor event	Wire Pay inbound event (**`type`**)	Value for **`data.externalId`**	**`data.amount`**	Notes
GMO Payment Gateway	Result notification (`AUTH`)	(no mapping)	`AccessID`	—	Authorized-only notifications are not accepted (express with `autoCapture: false` at creation)
GMO Payment Gateway	Result notification with `ErrCode`	`payment.failed`	`AccessID`	—	Design: copy `ErrInfo` into `failureReason`
GMO Payment Gateway	Result notification (`VOID` / `RETURN`)	`payment.cancelled` / `payment.refunded`	`AccessID`	`Amount`	`RETURN` is a refund, `VOID` a cancellation
GMO Payment Gateway (konbini / Pay-easy)	Deposit result notification (`PAYSUCCESS`)	Translate into the deposit notification `POST /api/demo/cvs-notify` / `deposit-notify`	`ReceiptNo` → `cvsReceiptNo` , account number → `transferId` (maps of R4-2 / R4-3)	`Amount`	Goes to the deposit interface, not the result interface; put the vendor's notification ID in `eventId` and the connection's environment in `mode`

Events that cannot be mapped (3-D Secure completion, authorized-only, partial captures, chargebacks, balance enquiries, …) are listed as not implemented in 3.6 and chapter 11.

Appendix D: Requirements for a live connection (list)

All "Requirements for a live connection" of the body in one list (the full text is in each section).

Requirement	Section	Summary
R3-1	3.5	Result-notification signature: HMAC-SHA256, `t=<UNIX seconds>,v1=<hex>`, clock skew within 5 minutes
R3-2	3.5	Result-notification event ID: unique, immutable, ≤128 chars, identical on retries
R3-3	3.5	Transaction mapping: carry `externalId` (live: the provider transaction ID, chapter 4)
R3-4	3.5	Map event types onto `payment.captured` / `failed` / `cancelled` / `refunded` (Appendix C)
R3-5	3.5	Bank deposit notification: transfer ID, amount, time, payer name, bank reference, environment (`mode`); notify unreadable transfer IDs too
R3-6	3.5	Konbini payment notification: 13-digit receipt number, amount, environment (`mode`)
R3-7	3.5	Retry only on non-2xx, with the same `eventId`
R3-8	3.5	Deposit-notification authentication: Bearer (per-provider tokens through an adapter)
R3-9	3.5	Environment separation: the correct `mode` on every notification (mismatches are held as unmatched)
R3-10	3.5	A unique, immutable event ID on deposit notifications too
R4-1	4.2	Store the provider transaction ID in `externalId`, or pass Wire Pay's `externalId` as the provider reference
R4-2	4.2	Keep a virtual account number → transfer ID (transaction ID) map in the adapter
R4-3	4.2	Normalise agency receipt numbers to 13 digits, or translate through a map
R4-4	4.2	Notification event IDs are unique and immutable
R4-5	4.2	A chargeback case-ID column (future)
R5-1	5.5	One notification per deposit; resend with the same `eventId`
R5-2	5.5	Include the deposit time, bank reference and environment
R5-3	5.5	A facility to return post-expiry / unknown deposits on the provider / adapter side
R5-4	5.5	Decide with merchants whether partial deposits (several transfers) are acceptable
R6-1 to R6-7	6.1	Provider operations for authorize / capture / void / fail / expire / refund / chargeback
R6-8	6.5	Call the provider API before the state transition
R6-9	6.5	Ingest asynchronously confirmed operations through result notifications
R6-10	6.5	Split approval when `approved` → `processing` → `completed` / `failed` is used for refunds
R7-1	7.1	Ingest and reconcile provider settlement statements
R7-2	7.1	A payout API for `scheduled` → `paid`

Requirement	Section	Summary
R7-3 to R7-5	7.3	Statement ingestion, difference reports, and whether deposit confirmation drives batches
R8-1	8.6	A way to receive provider outages / recoveries
R8-2	8.6	Alignment of retry policy and de-duplication
R8-3	8.6	Handling of transactions left `authorized` during an outage
R9-1	9.1	A signature or per-provider token on deposit notifications
R9-2	9.1	A secret rotation procedure
R9-3	9.2	A per-route allow list when the provider's egress IPs are fixed
R9-4	9.4	A design in which Wire Pay's servers never receive PANs

Revision history

Version	Date	Commit	Changes
1.0.0	2026-09-06	`6b72a40`	First edition
1.1.0	2026-09-07	`cf1c153`	Reflects the implementation changes of fix phases 1–5. Breaking: `mode` mandatory on deposit notifications with environment matching (3.2 / 3.3), 202 holding of deposits on expired / cancelled transactions (3.2 / 5.4), the transaction status `awaiting_payment` (3.1 / 5.1), the invoice number format assigned at confirmation (4.1 / 7.2). Added: idempotent deposit notifications (`eventId` , content hash) and the deposit notification log (3.2 / 3.4), the `late_deposit` transition with reasons and dismissal kinds on unmatched deposits (5.3 / 5.4), the daily `deposit.late` and `webhook.signing_secret_missing` notifications (8.3), fail-closed webhook signing (9.1), the IP allow-list mode (9.2), the merchant API rate limit (9.5), the cron table split into the actual `vercel.json` schedule (daily) and the production recommendation (8.4), Appendix A split into three diagrams, Appendix C (vendor mapping) and Appendix D (requirements list). Requirements R3-5 to R3-10 and R5-1 to R5-3 revised. Details in `docs/spec/CHANGELOG.md`