Wire Pay Specification Glossary (English–Japanese)

Item	Value
Version	1.1.0
Target system	commit `cf1c153` (`main`)
Date / revised	2026-09-06 / 2026-09-07 (rows added or changed in 1.1.0 say "1.1.0" in the definition)

This glossary fixes the terminology used in Specifications A and B (Japanese and English editions). DB / API values are the literal strings used by the implementation; UI labels come from the dictionaries (`lib/i18n/messages/ja.ts` / `en.ts`). It includes the fixed term pairs from `CLAUDE.md`.

1. Parties and roles

English	Japanese	DB / API value	Definition
PSP (payment service provider)	決済代行（PSP）	—	The operator of Wire Pay that offers payment services to merchants. Written "Wire Pay" or "the PSP"
Merchant	加盟店	`Merchant`	An e-commerce business contracted with Wire Pay to accept payments
Merchant ID	加盟店ID	`merchantCode` (`MER-00001`)	Auto-numbered public identifier
Agent	代理店	`Agent` (`AGT-00001`)	A business that refers / brokers merchants
Customer	購入者（ユーザー）	`customerName` / `customerId` / `Customer`	The person paying on the merchant's site; "user" on a transaction, "customer" in the customer master
Customer id	ユーザーID	`customerId` / `Customer.externalId`	The merchant's own identifier of the customer
Admin user	管理者	`AdminUser`	An operator of the PSP dashboard
Master	マスター	`admin` (formerly `master`)	The all-permissions role; written "admin" in the specs
General	一般	`cs` (formerly `general`)	The customer-support role; written "cs" in the specs
Role	ロール	`admin` / `accounting` / `cs` / `developer` / `viewer`	Operator permission groups
Payment provider	決済プロバイダ	`PaymentProvider`	Connection settings for a party Wire Pay entrusts processing to
Downstream PSP / wallet	下位 PSP・ウォレット	—	A business that calls Wire Pay's API as a client (reader of Specification A)
Upstream PSP / wallet	上位 PSP・ウォレット	—	A business Wire Pay entrusts processing to (reader of Specification B)
Acquirer	アクワイアラ	—	Card merchant-acquiring bank

English	Japanese	DB / API value	Definition
Konbini payment collection agency	コンビニ収納代行	—	Collection business for convenience-store counter payments
Virtual account	バーチャル口座	`virtual_account`	Bank service issuing a transfer account per order

2. Transactions and lifecycle

English	Japanese	DB / API value	Definition
Transaction	取引	`Payment`	One payment record from creation to completion, refund or expiry
Payment application	決済申請	`APPLICATION_STATUSES`	Name / list of transactions not yet completed (plus failed, expired, cancelled)
Payments (sales)	決済一覧（売上）	`SALES_STATUSES`	List of completed, refunded and charged-back transactions
Transaction ID	取引ID	`Payment.id` / webhook `payment_id`	Unique identifier issued by Wire Pay
Provider transaction ID	トランザクションID（プロバイダ側）	`Payment.externalId` / webhook `transaction_id`	The provider-side identifier
Order number	注文番号	`orderNumber`	The merchant's order number
Payment method	決済手段 / 決済種別	`method`: `credit` / `qr` / `convenience` / `bank` / `other`	
Credit card payments	クレジットカード決済	`credit`	
QR code payments	QR コード決済	`qr`	
Konbini payments	コンビニ決済	`convenience`	Convenience-store counter payments

English	Japanese	DB / API value	Definition
Bank transfer payments	銀行振込決済	`bank`	
Other web payment services	その他 Web サービス決済	`other`	
Pending	申請中	`pending`	Just created (the English label changed from "Applied" to "Pending" in 1.1.0)
Awaiting payment (konbini)	支払待ち（コンビニ）	`awaiting_payment`	Receipt number issued, waiting for the counter payment (its own status since 1.1.0; previously `pending` + `cvsReceiptNo`)
Waiting for money	入金待ち	`WAITING_STATUSES`: `awaiting_transfer` / `awaiting_payment`	Statuses that carry a deadline (`transferDueAt`) (1.1.0)
Awaiting transfer	振込待ち	`awaiting_transfer`	Transfer ID issued, waiting for the deposit
Authorization / Authorized	与信 / 与信済	`authorized`	Funds reserved
Capture / Completed	売上確定 / 完了	`captured`, action `capture`	Payment settled
Partially refunded	一部返金	`partially_refunded`	
Refunded	返金済	`refunded`	
Void / Cancelled	取消 / キャンセル	`cancelled`, action `cancel`	Abandoning a transaction before completion; UI label "Cancelled"
Failed	失敗	`failed`	
Expired	期限切れ	`expired`, action `expire`	A later deposit can be applied through `late_deposit`
Late deposit	期限後入金	action `late_deposit` (`expired` → `captured`), `UnmatchedDeposit.reason = late_deposit`	A deposit that arrived after expiry, applied by the PSP with a reason (1.1.0)
Overdue	期限超過	`?overdue=1`, `overdue` flag	Past the deadline while the status is unchanged

English	Japanese	DB / API value	Definition
Chargeback (status)	チャージバック（ステータス）	`chargeback`	A lost / confirmed dispute
Failure reason	失敗理由	`failureReason`	`limit_exceeded:*` / `blocked:*` / test-card reasons / `charge_declined`
Status history	ステータス変更履歴	`PaymentEvent`	Append-only log of transitions
Actor	実行者	`dashboard` / `api` / `webhook` / `bank` / `cvs` / `system` / `seed`	Who caused a transition
Transition table	状態遷移表	`TRANSITIONS`	The single definition of allowed transitions
Auto-capture	自動売上	`autoCapture`	Complete at creation
Idempotency key	冪等キー	`Idempotency-Key` / `idempotencyKey`	Prevents duplicate creation
Test / Live (environment)	テスト / 本番（環境）	`livemode`, `mode: test | live`, key prefixes `wp_test_` / `wp_live_`	Data environment
Test card	テストカード	`TEST_CARDS`	Card numbers selecting a scenario

3. Bank transfer, konbini and deposits

English	Japanese	DB / API value	Definition
Transfer ID	振込ID	`transferId`	7- or 8-digit matching number
Transfer ID length	振込IDの桁数	`transferIdDigits`	7 or 8
Transfer deadline	振込期限	`transferDueAt` / `transferDueDays`	Default 7 days
Transfer instructions	振込案内	e-mail `transfer_guide`	
Receipt number (konbini)	受付番号	`cvsReceiptNo`	13 digits

English	Japanese	DB / API value	Definition
Store (konbini brand)	支払店舗	`cvsBrand`: `seven` / `lawson` / `familymart` / `ministop` / `other`	
Payment deadline (konbini)	支払期限（コンビニ）	`transferDueAt` / `cvsDueDays`	Default 3 days
Paid at	支払日時	`cvsPaidAt`	
Deposit	入金	action `deposit`	Money received from a bank / konbini
Deposit notification	入金通知	`/api/demo/deposit-notify`, `/api/demo/cvs-notify`	Notification from a bank / konbini network; `mode` mandatory, `eventId` optional (1.1.0)
Deposit notification log	入金通知ログ	`DepositNotification` (`DN-00001`), `/deposit-notifications`	Record of every received notification; result `applied` / `duplicate` / `unmatched` / `rejected` (1.1.0)
De-duplication key	重複排除キー	`dedupeKey` / `claimKey`	`eventId` or a content hash; a resend with the same key is not re-applied (1.1.0)
Environment mismatch	環境不一致	`mode_mismatch`	A deposit whose `mode` differs from the transaction's `livemode` (held as unmatched, 1.1.0)
Deposit reconciliation	入金消込	`reconcileDeposit`	Matching a deposit to a transaction
Deposited amount (total)	入金額（累計）	`depositAmount`	
Short / excess deposit	過不足入金	`depositDiff`: `short` / `excess`	
Short	不足	`short`	total < amount due
Excess	超過	`excess`	total > amount due
Follow-up status	対応状況（過不足）	`depositDiffStatus`: `open` / `refund_arranged` / `notified` / `resolved`	
Additional deposit request	追加入金案内	e-mail `deposit_short`	
Unmatched deposit	未消込入金	`UnmatchedDeposit`: `unmatched` / `matched` / `dismissed`; `source`: `bank` / `cvs` / `manual`	Holding place for deposits with an unknown transfer ID, late, after cancellation, or in the wrong environment

English	Japanese	DB / API value	Definition
Hold reason	保留理由	`reason`: `late_deposit` / `cancelled_deposit` / `mode_mismatch`	Why the deposit became unmatched (1.1.0)
Match (attach transfer ID)	振込IDを付与して消込	`POST .../match`	
Apply as late deposit	期限後入金として消込	`POST .../late-match` (reason required)	Runs the `late_deposit` transition (1.1.0)
Dismiss	却下	`dismissed`, `dismissKind`: `returned` / `other`	
Return (of a deposit)	組戻し	`dismissKind = returned`	Sending the money back to the payer (funds move outside the system, 1.1.0)
API re-notify	API 再通知	`POST /api/payments/{id}/renotify`	Re-send `payment.completed`
Payout	入金（PSP → 加盟店）	`SettlementBatch`	Settlement payment to the merchant

4. Refunds and chargebacks

English	Japanese	DB / API value	Definition
Refund	返金	`Refund`	Returning money on a completed transaction
Refund request	返金申請	`requested`	Filed by a merchant or the PSP
Approve / Reject	承認 / 否認	`approved` / `rejected`, `/approve` / `/reject`	PSP review
Refund window	返金可能期限	`refundWindowDays`	Default 180 days
Forced refund	強制返金	`forced`	Admin refund after the window
Refund reason	返金理由	`customer` / `defect` / `duplicate` / `other`	Customer request / Defective goods / Duplicate payment / Other
Full / Partial	全額 / 一部	`kind`: `full` / `partial`	
Refundable balance	返金可能残額	—	amount − refunded − pending requests
Chargeback	チャージバック	`Chargeback`	Payment dispute

English	Japanese	DB / API value	Definition
Received / Disputed / Won / Lost / Confirmed	受付 / 異議申立中 / 勝訴 / 敗訴 / 確定	`received` / `disputed` / `won` / `lost` / `confirmed`	
Dispute deadline	異議申立期限	`disputeDeadlineAt`	Default 14 days
Reason code (chargeback)	理由コード（CB）	`fraud` / `not_received` / `not_as_described` / `duplicate` / `other`	Fraud / Not received / Not as described / Duplicate / Other
Evidence note	証憑メモ	`evidenceNote`	

5. Settlement and invoicing

English	Japanese	DB / API value	Definition
Settlement	精算	`SettlementBatch`	Payout calculation for a merchant
Settlement batch	精算バッチ	`SettlementBatch`	One per merchant × period × environment
Settlement line	明細行	`SettlementLine`: `payment` / `refund` / `chargeback`	
Settlement cycle	締めサイクル	`settlementCycle`: `monthly` / `semimonthly` / `weekly`	Month-end / 15th and month-end / weekly
Payout term	支払サイト	`payoutTerm`: `next_month_end` / `next_month_15` / `month_after_next_15` / `next_week`	
Scheduled payout date / Paid at	振込予定日 / 振込完了日	`scheduledAt` / `paidAt`	
Collecting / Confirmed / Scheduled / Paid / Held	集計中 / 確定 / 振込予定 / 振込済 / 保留	`collecting` / `confirmed` / `scheduled` / `paid` / `held`	
Gross sales	売上総額	`grossAmount`	
Fee (total)	手数料（合計）	`feeAmount`	Wire Pay → merchant payment fees
Fee rate / Fixed fee	手数料率 / 固定手数料	`ratePercent` / `fixedFee`	
Contract plan	契約プラン	`plan`: `standard` / `premium` / `custom`	
Settlement fee (transfer fee)	精算手数料（振込手数料）	`settlementFee`	
Net payout	差引支払額	`netAmount`	
Qualified invoice	適格請求書（インボイス）	`GET .../invoice`	Invoice PDF for the payment fees

English	Japanese	DB / API value	Definition
Invoice number	請求書番号	`SettlementBatch.invoiceNo`: `INV-YYYYMM-<merchant number>-<2-digit sequence>`	Assigned and stored when the batch is confirmed (1.1.0; the old format had no sequence)
Registration number	登録番号	`issuerRegistrationNo` / `invoiceNumber` (`T` + 13 digits)	Qualified-invoice issuer number
Tax category	税区分	`taxCategory`: `standard10` / `reduced8` / `exempt`	
Tax rounding	端数処理	`taxRounding`: `floor` / `round` / `ceil`	
Receipt	領収書	`Receipt` (`RC-YYYYMM-00001`), `source`: `dashboard` / `customer` / `merchant`	Customer receipt PDF; also issued from the merchant portal (1.1.0)
Addressee / Description	宛名 / 但し書き	`recipientName` / `description`	Receipt wording (description added in 1.1.0)
Re-issue	再発行	`reissueCount`	
Agent fee	代理店手数料	—	`floor(net payout × fee rate)`

6. Webhooks, API and authentication

English	Japanese	DB / API value	Definition
Merchant webhook	Webhook（加盟店向け通知）	`WebhookDelivery`	HTTP notification Wire Pay → merchant
Webhook delivery log	Webhook 送信ログ	`WebhookDelivery` / `WebhookAttempt`	
Notification URL	システム通知先 URL	`notifyUrl`	The merchant's receiving endpoint
Notification format	通知の型	`notifyFormat`: `json_post` / `form_post` / `query_get`	
Parameter set	送信パラメータセット	`notifyParamSet`: `minimal` / `standard` / `full`	
Identifier format	決済識別子の形式	`notifyIdFormat`: `payment_id` / `transaction_id` / `both`	
Signature	署名	`X-Signature` / `Wirepay-Signature`	HMAC-SHA256
Signing secret	署名シークレット	`ApiKey.kind = signing_secret` (`wp_*_ss_`)	Webhook signing key; no delivery to an environment without one (fail closed); the test secret is issued at merchant registration (1.1.0)
Signing secret missing	署名鍵なし	`signing_secret_missing`, notification `webhook.signing_secret_missing`	A webhook that could not be sent for lack of a signing secret (1.1.0)
API key	API キー	`ApiKey.kind = api_key` (`wp_*_ak_`)	Bearer credential

English	Japanese	DB / API value	Definition
Issue / Rotate / Revoke	発行 / ローテーション / 失効	`api_key.issue` / `rotate` / `revoke`	
Grace period	猶予期間	`ROTATION_GRACE_DAYS` = 7	Overlap of old and new key
Active / Expiring / Expired / Revoked	有効 / 失効予定 / 期限切れ / 失効	`active` / `expiring` / `expired` / `revoked`	Key states
Pending / Success / Retrying / Failed / Abandoned	送信待ち / 成功 / リトライ待ち / 失敗 / 断念	`pending` / `success` / `retrying` / `failed` / `abandoned`	Delivery states
Resend / Retry	再送	`webhook.resend`	Manual resend / automatic retry
Result notification (provider webhook)	結果通知（プロバイダ → Wire Pay）	`WebhookEvent`, `/api/webhooks/{providerId}`	
Simulate webhook	Webhook をシミュレート	`/api/payments/{id}/simulate-webhook`	Signed self-delivery test
Public API	公開 API	`/api/v1`	Merchant-facing REST API
Merchant API	加盟店 API	`/api/merchant-api/*`	ping / settlements / announcements
Merchant portal	加盟店管理画面	`/merchant/*`, cookie `wirepay.merchant`	Merchant login screens
PSP dashboard (operator dashboard)	PSP 管理画面	under `/`	Operator screens
Hosted payment page	ホスト型決済ページ	`/pay/<token>`	Customer page of a payment link
Payment link	決済リンク	`PaymentLink`（`active` / `disabled`）	Fixed-amount checkout by URL / QR
Disable	無効化	`disabled`	
Used count / Max uses	利用回数 / 最大利用回数	`usedCount` / `maxUses`	
Sandbox	サンドボックス	`/merchant/sandbox`	Console calling the real API with a test key

English	Japanese	DB / API value	Definition
Rate limit	レート制限	`ApiRateLimit`, 429 `rate_limited`	60 / minute per merchant × environment, shared by the public API and the merchant API (1.1.0)
IP restriction	IP 制限	`IpRestriction`	
Block / Allow / Allow list	ブロック / 許可 / 許可リスト	`mode`: `deny` / `allow`	Block rules always enforce; allow rules enforce while the allow-list mode is on
Allow-list mode	許可リストモード	`GlobalSetting.ipAllowlistAdmin` / `ipAllowlistMerchantApi`, `PUT /api/ip-restrictions/allowlist`	Blocks callers matching no enabled allow rule (per target, default off, 1.1.0)
Self-lockout prevention	自己ロックアウト防止	400 `ip_self_block`, `allowlist_no_rules`	Refuses settings that would lock the operator out
Target (IP restriction)	対象（IP 制限）	`target`: `admin` / `merchant_api`	
Lockout	ロックアウト	`merchant_locked` (423)	15 minutes after 5 failures
Two-factor (TOTP)	二段階認証	`totpEnabled`	PSP admin users only
Invite	招待	`invited`	Admin accounts
Audit log	操作ログ	`AuditLog`	
Actor type	操作者種別	`admin` / `merchant` / `system` / `webhook` / `bank` / `cvs` / `cron` / `seed`	

7. Risk, limits and notifications

English	Japanese	DB / API value	Definition
Transaction limit	限度額	`MerchantLimit`: `perTransaction` / `daily` / `monthly`	
Limit exceeded	限度額超過	`limit_exceeded:*`, webhook `limit.exceeded`	
Payment method suspension	決済手段の停止（一時停止）	`PaymentMethodControl`	Stops new checkouts only

English	Japanese	DB / API value	Definition
Global / Per-merchant suspension	全体停止 / 加盟店別停止	`scope`: `global` / `merchant`	
Auto-resume	自動再開	`resumeAt`	
Blacklist	ブラックリスト	`Blacklist`: `card` / `ip` / `email`	
Candidate / Active / Disabled / Rejected	候補 / 有効 / 無効 / 却下	`candidate` / `active` / `disabled` / `rejected`	
Repeated-failure detection	連続失敗検知	`RiskSetting.windowMinutes` / `maxFailures`	
Card fingerprint	カード識別ハッシュ	`cardHash`	`sha256(brand|last4|expiry)`
Source IP	接続元 IP	`clientIp`	
Stored card (payment token)	保存カード（トークン）	`PaymentToken`	Brand, last 4, expiry
Customer master	顧客マスタ	`Customer`	Merchant × customer id

English	Japanese	DB / API value	Definition
Masking / Unmask	マスク表示 / マスク解除	`pii.unmask`	
Anonymisation	匿名化	`anonymizedAt`, `AnonymizeBatch`	
Retention period	保持期間	`piiRetentionMonths` / `auditRetentionYears`	
Notification centre	通知センター	`Notification`	Operator notifications
Severity	重要度	`info` / `warning` / `critical`	
Announcement	お知らせ	`Announcement`: `notice` / `maintenance` / `incident`	Notice / Maintenance / Incident
Occurred / Investigating / Resolved	発生 / 対応中 / 復旧	`occurred` / `investigating` / `resolved`	Incident timeline
Draft / Published / Ended	下書き / 公開 / 終了	`draft` / `published` / `ended`	
E-mail template	メールテンプレート	`EmailTemplate` (`transfer_guide`, `cvs_guide`, `payment_completed`, `refund_completed`, `deposit_short`, `statement`, `admin_invite`, `subscription_failed`, `subscription_suspended`, `notification`, `merchant_payment_notice`, `merchant_daily_summary`)	12 keys × 2 languages
E-mail notification setting	メール通知設定	`emailNotification`: `per_payment` / `daily` / `none`	Merchant-facing payment mail, sent to the contact e-mail (implemented in 1.1.0)

English	Japanese	DB / API value	Definition
Merchant payment notice / Daily summary	加盟店宛決済通知 / 日次サマリー	`merchant_payment_notice` / `merchant_daily_summary`, `/api/cron/merchant-daily-summary`	Per completion / previous-day digest (09:00 JST, 1.1.0)
E-mail log	送信ログ	`EmailLog`: `sent` / `failed` / `demo`	

8. Subscriptions

English	Japanese	DB / API value	Definition
Plan	課金プラン	`Plan`: `monthly` / `yearly` / `weekly`	
Subscription	定期課金（契約）	`Subscription`	
Trial	無料期間	`trialDays`, `trialing`	
Active / Past due / Suspended / Cancelled	有効 / 未払い / 停止 / 解約	`active` / `past_due` / `suspended` / `cancelled`	
Next charge date	次回課金日	`nextChargeAt`	
Retry	再試行	`RETRY_DAYS` = [3, 7]	
Charge now / Pause / Resume / Cancel	今すぐ課金 / 一時停止 / 再開 / 解約	`charge` / `pause` / `resume` / `cancel`	
Demo charge failure rate	デモの課金失敗率	`demoChargeFailPercent`	

9. Operations and system

English	Japanese	DB / API value	Definition
Cron job	cron	`/api/cron/*`	Scheduled processing
Demo mode	デモモード	—	No calls to external payment networks
Demo limit	デモ上限	`DEMO_LIMITS`, `demo_limit`	
Read-only demo	読み取り専用デモ	`DEMO_READONLY`	
Encryption key	暗号鍵	`ENCRYPTION_KEY`	AES-256-GCM
Fail-closed	fail-closed	—	Production refuses to run without the key
Global settings	全体設定	`GlobalSetting`	
Mode indication (live stripe)	モード表示（本番ストライプ）	`data-testid="current-mode"` / `live-stripe`	The mode badge next to page titles and the red stripe in live mode (1.1.0)

English	Japanese	DB / API value	Definition
Admin manual	管理画面マニュアル	`/manual/*`	
API docs	API ドキュメント	`/docs/api/*`	
Business time zone	業務タイムゾーン	`Asia/Tokyo`	Date boundaries