

Apply filters to SQL queries

Project description

SQL stands for Structured Query Language, is used to create, interact with, and request information from a database. As a security professional it is my job to investigate security issues to help keep the system secure. As we recently discovered some potential security issues that involve login attempts and employee machines. So, we need to examine the organization's data in their employees and log_in_attempts tables by using SQL filters to retrieve records from different datasets and investigate the potential security issues.

Retrieve after hours failed login attempts

A potential security incident that occurred after business hours need to be investigated by querying the log_in_attempts table. I need to review the failed logins (marked as 0 or False in the table) after 18:00.

```
MariaDB [organization]> select * from log_in_attempts where login_time > '18:00' AND success = FALSE;
```

event_id	username	login_date	login_time	country	ip_address	success
2	apatel	2022-05-10	20:27:27	CAN	192.168.205.12	0
18	pwashing	2022-05-11	19:28:50	US	192.168.66.142	0
20	tshah	2022-05-12	18:56:36	MEXICO	192.168.109.50	0
28	astrada	2022-05-09	19:28:12	MEXICO	192.168.27.57	0
34	drosas	2022-05-11	21:02:04	US	192.168.45.93	0
42	cgriffin	2022-05-09	23:04:05	US	192.168.4.157	0
52	cjackson	2022-05-10	22:07:07	CAN	192.168.58.57	0
69	wjaffrey	2022-05-11	19:55:15	USA	192.168.100.17	0
82	abernard	2022-05-12	23:38:46	MEX	192.168.234.49	0
87	apatel	2022-05-08	22:38:31	CANADA	192.168.132.153	0
96	ivelasco	2022-05-09	22:36:36	CAN	192.168.84.194	0
104	asundara	2022-05-11	18:38:07	US	192.168.96.200	0
107	bisles	2022-05-12	20:25:57	USA	192.168.116.187	0
111	astrada	2022-05-10	22:00:26	MEXICO	192.168.76.27	0
127	abellmas	2022-05-09	21:20:51	CANADA	192.168.70.122	0
131	bisles	2022-05-09	20:03:55	US	192.168.113.171	0
155	cgriffin	2022-05-12	22:18:42	USA	192.168.236.176	0
160	jclark	2022-05-10	20:49:00	CANADA	192.168.214.49	0
199	yappiah	2022-05-11	19:34:48	MEXICO	192.168.44.232	0

```
19 rows in set (0.001 sec)
```

In the command 'select * from log_in_attempts' is used to select the whole log_in_attempts table. The 'where' clause is used to select the particular event, here 'login_time > 18:00' which means details after 6pm or 18:00 and 'success = FALSE' meaning failed attempts. In this query, both the conditions should be met to show the data of the table, this is the way 'AND' operator is used.

Retrieve login attempts on specific dates

A suspicious event has occurred on 22-05-09, as a result I need to review all login attempts which occurred on this day and the day before.

```
MariaDB [organization]> select * from log_in_attempts where login_date = '2022-05-09' OR login_date = '2022-05-08';
```

event_id	username	login_date	login_time	country	ip_address	success
1	jrafael	2022-05-09	04:56:27	CAN	192.168.243.140	1
3	dkot	2022-05-09	06:47:41	USA	192.168.151.162	1
4	dkot	2022-05-08	02:00:39	USA	192.168.178.71	0
8	bisles	2022-05-08	01:30:17	US	192.168.119.173	0
12	dkot	2022-05-08	09:11:34	USA	192.168.100.158	1
15	lyamamot	2022-05-09	17:17:26	USA	192.168.183.51	0
24	arusso	2022-05-09	06:49:39	MEXICO	192.168.171.192	1
25	sbaelish	2022-05-09	07:04:02	US	192.168.33.137	1
26	apatel	2022-05-08	17:27:00	CANADA	192.168.123.105	1
28	aestrada	2022-05-09	19:28:12	MEXICO	192.168.27.57	0
30	yappiah	2022-05-09	03:22:22	MEX	192.168.124.48	1
32	acook	2022-05-09	02:52:02	CANADA	192.168.142.239	0
36	asundara	2022-05-08	09:00:42	US	192.168.78.151	1
38	sbaelish	2022-05-09	14:40:01	USA	192.168.60.42	1
39	yappiah	2022-05-09	07:56:40	MEXICO	192.168.57.115	1
42	cgriffin	2022-05-09	23:04:05	US	192.168.4.157	0
43	mcouliba	2022-05-08	02:35:34	CANADA	192.168.16.208	0
44	daquino	2022-05-08	07:02:35	CANADA	192.168.168.144	0
47	dkot	2022-05-08	05:06:45	US	192.168.233.24	1

The 'select * from employees' shows the whole log_in_attempts table, putting the 'where' clause to select a particular event, here the 'login_date' of 22-05-09 or 'login_date' of 22-05-08, if either of the query is true then the data of the table will be shown, this is how 'OR' operator is used.

Retrieve login attempts outside of Mexico

There's been suspicious activity with login attempts, but the team has determined that this activity didn't originate in Mexico. So I need to investigate login attempts that occurred outside Mexico.

```
MariaDB [organization]> select * from log_in_attempts where NOT country LIKE 'MEX%';
```

event_id	username	login_date	login_time	country	ip_address	success
1	jrafael	2022-05-09	04:56:27	CAN	192.168.243.140	1
2	apatel	2022-05-10	20:27:27	CAN	192.168.205.12	0
3	dkot	2022-05-09	06:47:41	USA	192.168.151.162	1
4	dkot	2022-05-08	02:00:39	USA	192.168.178.71	0
5	jrafael	2022-05-11	03:05:59	CANADA	192.168.86.232	0
7	eraab	2022-05-11	01:45:14	CAN	192.168.170.243	1
8	bisles	2022-05-08	01:30:17	US	192.168.119.173	0
10	jrafael	2022-05-12	09:33:19	CANADA	192.168.228.221	0
11	sgilmore	2022-05-11	10:16:29	CANADA	192.168.140.81	0
12	dkot	2022-05-08	09:11:34	USA	192.168.100.158	1
13	mrhah	2022-05-11	09:29:34	USA	192.168.246.135	1
14	sbaelish	2022-05-10	10:20:18	US	192.168.16.99	1
15	lyamamot	2022-05-09	17:17:26	USA	192.168.183.51	0

In this query, the 'NOT' operator is used to focus on all the other countries except Mexico. Since, in some places 'MEX' is written, hence we are using the 'LIKE' clause to select both 'MEX' and 'MEXICO'.

Retrieve employees in Marketing

My team wants to perform security updates on specific employee machines in the Marketing department and the office is in EAST building, hence I need to gather information on these employee machines from the employees table.

```
MariaDB [organization]> select * from employees where department = 'Marketing' AND office LIKE 'EAST%';
```

employee_id	device_id	username	department	office
1000	a320b137c219	elarson	Marketing	East-170
1052	a192b174c940	jdarosa	Marketing	East-195
1075	x573y883z772	fbautist	Marketing	East-267
1088	k865l965m233	rgosh	Marketing	East-157
1103	NULL	randerss	Marketing	East-460
1156	a184b775c707	dellery	Marketing	East-417
1163	h679i515j339	cwilliam	Marketing	East-216

```
7 rows in set (0.002 sec)
```

Here, the department 'Marketing' is selected using the 'where' clause and since there are different offices of EAST building, examples: EAST-170, EAST-195 etc, hence we are using 'LIKE' clause to select the offices of EAST building. 'AND' operator is used to show the data of only those which satisfy both the conditions.

Retrieve employees in Finance or Sales

My team needs to perform a different security update on machines for employees in the Sales and Finance departments, so I need to gather information on all employees in the Sales or Finance departments.

```
MariaDB [organization]> select * from employees where department = 'Finance' OR department = 'Sales';
```

employee_id	device_id	username	department	office
1003	d394e816f943	sgilmore	Finance	South-153
1007	h174i497j413	wjaffrey	Finance	North-406
1008	i858j583k571	abernard	Finance	South-170
1009	NULL	lrodriqu	Sales	South-134
1010	k242l212m542	jlansky	Finance	South-109
1011	l748m120n401	drosas	Sales	South-292
1015	p611q262r945	jsoto	Finance	North-271
1017	r550s824t230	jclark	Finance	North-188
1018	s310t540u653	abellmas	Finance	North-403
1022	w237x430y567	arusso	Finance	West-465
1024	y976z753a267	iuduike	Sales	South-215
1025	z381a365b233	ihill	Sales	North-115

The department for Finance or Sales have been selected using the 'where' clause and 'OR' operator, so that if either the conditions are met, the data of the table will be shown.

Retrieve all employees not in IT

Only the IT department has a certain update that the other departments don't have, hence I need to gather information of all other departments who need it.

```
MariaDB [organization]> select * from employees where NOT department = 'Information Technology';
```

employee_id	device_id	username	department	office
1000	a320b137c219	elarson	Marketing	East-170
1001	b239c825d303	bmoreno	Marketing	Central-276
1002	c116d593e558	tshah	Human Resources	North-434
1003	d394e816f943	sgilmore	Finance	South-153
1004	e218f877g788	eraab	Human Resources	South-127
1005	f551g340h864	gesparza	Human Resources	South-366
1007	h174i497j413	wjaffrey	Finance	North-406
1008	i858j583k571	abernard	Finance	South-170
1009	NULL	lrodriqu	Sales	South-134
1010	k242l212m542	jlsansky	Finance	South-109
1011	l748m120n401	drosas	Sales	South-292
1015	p611q262r945	jsoto	Finance	North-271
1016	q793r736s288	sbaelish	Human Resources	North-229
1017	r550s824t230	jclark	Finance	North-188
1018	s310t540u653	abellmas	Finance	North-403
1020	u899v381w363	arutley	Marketing	South-351
1022	w237x430y567	arusso	Finance	West-465
1024	y976z753a267	iuduike	Sales	South-215
1025	z381a365b233	jhill	Sales	North-115
1026	a998b568c863	apatel	Human Resources	West-320
1027	b806c503d354	mrah	Marketing	West-246
1028	c603d749e374	aestrada	Human Resources	West-121
1029	d336e475f676	ivelasco	Finance	East-156
1030	e391f189g913	mabadi	Marketing	West-375
1031	f419g188h578	dkot	Marketing	West-408
1034	i679j565k940	bsand	Human Resources	East-484
1035	j236k303l245	higley	Sales	South-171

This query has the 'NOT' operator which selects all other departments except the 'Information Technology' department.

Summary

By using the SQL query, it was very easy to gather the information needed by the department. I have used AND, OR, NOT operators with the 'LIKE', 'WHERE' clauses and listed the data that was needed from the Table of employees or log_in_attempts. Every query has been written and explained.