

Chapter 4 - Lists, tables & forms

Lists

Lists are used to display content which represents a list

Unordered list: Used to list unordered items

``

` Home `

` About `

`⋮`

``

Ordered list: used to list ordered items

``

` Phone `

` PC `

` Laptop `

``

Tables

The `<table>` tag is used to define tables in HTML. It is used to format & display tabular data.

tr tag: used to display table row

td tag: used to display table data

th tag: used in place of table data for displaying table headers

We can define as many table rows as we want.

To add a caption to the table, we use `<caption>` tag inside table.

`thead` tag: Used to wrap table head (caption & `tr` with `th`)

`tbody` tag: Used to wrap the table body.

Colspan attribute

This attribute is used to create cells spanning multiple columns.

`<th colspan="3"> Harry </th>`

↳ Spans 3 columns

HTML forms

An HTML form is used to collect input from the user. `form` tag is used for the same.

`<form>`

-- Element of the form --

`</form>`

There are different form elements for different kinds of user input.

→ `input` element: Can be of type text, checkbox, radio, button and submit. We also have a 'file' type.

→ `textarea` element: Defines a multi line text input. `cols` and `rows` attributes can be used to size the `textarea`.

→ `select` element: Defines a drop down list.

Note : you don't have to remember all the tags, you will automatically memorize them with practice

Embedding Videos

Video tag is used to play videos in HTML

```
<Video src = 'harry.mp4' > Error </video>
```

Attributes for video

We can use :

- Width : To adjust width of a video (Height automatically adjusts)
- We can use autoplay/loop to autoplay or loop the video.