Understanding subqueries

- ➤ What is Subquery?
- Need of Subquery

Understanding Subquery


Subqueries – Queries that are embedded into other queries.


```
☐select FIRST_NAME, LAST_NAME, CITY from AUTHOR


 WHERE CITY='Toronto'
                    select FirstName, LastName
                     from [Person].[Person]
                     where BusinessEntityID IN (select PersonID
                                                    from [Sales].[Customer]
                                                    where CustomerID IN
                                                            select CustomerID
                                                                    [Sales].[SalesOrderHeader]
                                                            from
                                                            where SalesOrderID in
                                                                 (select SalesOrderID as Order id
                                                                from [Sales].[SalesOrderDetail]
                                                                where ProductID = '710'
```

Need of Subqueries

First Understand these tables:










П												
П	select * from [Person].[Person]											
П												
П	109 % - 4											
П	■ Results № Messages											
П		BusinessEntityID	PersonType	NameStyle	Title	FirstName	MiddleName	LastName	Suffix	EmailPromotion	AdditionalC	
П	1	1	EM	0	NULL	Ken	J	Sánchez	NULL	0	NULL	
П	2	2	EM	0	NULL	Terri	Lee	Duffy	NULL	1	NULL	
П	3	3	EM	0	NULL	Roberto	NULL	Tamburello	NULL	0	NULL	
П	4	4	EM	0	NULL	Rob	NULL	Walters	NULL	0	NULL	
П	5	5	EM	0	Ms.	Gail	Α	Erickson	NULL	0	NULL	
П	6	6	EM	0	Mr.	Jossef	Н	Goldberg	NULL	0	NULL	
П	7	7	EM	0	NULL	Dylan	Α	Miller	NULL	2	NULL	
П	8	8	EM	0	NULL	Diane	L	Margheim	NULL	0	NULL	
П	9	9	EM	0	NULL	Gigi	N	Matthew	NULL	0	NULL	
П	10	10	FM	n	NULL	Michael	NULL	Rahoom	NULL	2	NI II I	

Need of Subqueries


First Understand these tables:








First Get the Order Id & Customer Id for a Product



Get the PersonID and Customer Details



Get the PersonID and Customer Details

```
select SalesOrderID as Order_id from [Sales].[SalesOrderDetail] where ProductID ='710'
  select CustomerID from [Sales].[SalesOrderHeader] where SalesOrderID in ('43667','43670','43676')
select PersonID from [Sales].[Customer] where CustomerID IN ('29974','29566','29811')
select FirstName,LastName from [Person].[Person] where BusinessEntityID IN ('487','1017','1373')
  Results Messages
    FirstName LastName
    Mae
            Black
            Hanson
    Mark
    Scott
            MacDonald
```

Subqueries

```
iselect FirstName, LastName
 from [Person].[Person]
 where BusinessEntityID IN (select PersonID
                                 from [Sales].[Customer]
                                 where CustomerID IN
                                        (select CustomerID
                                        from
                                                 [Sales].[SalesOrderHeader]
                                        where SalesOrderID in
                                              (select SalesOrderID as Order_id
                                             from [Sales].[SalesOrderDetail]
                                             where ProductID = '710'
                                                   Results Messages
                                                     FirstName LastName
                                                           Black
                                                     Mark
                                                           Hanson
                                                           MacDonald
                                                     Scott
```