Advanced Networking Lab

Thomas Hendriks   Jakob Struye

February 27, 2017

Lab 2

Frequencies and Channels

In the IEEE 802.11 standards, various channels are defined. Two main frequency bands are used, namely 2.4 GHz and 5GHz. IEEE 802.11a networks use the 5 GHz band, while IEEE 802.11b/g networks operate in the 2.4 GHz band. In both bands, various "channels" have been defined. However, channel separation is not as clean cut as one might expect. In the following setups, you will illustrate this using some simple tests.

2.1 Available channels

Exercise 1: Frequencies

Within the IEEE 802.11 specification, various channels are defined. Depending on the local authorities (Belgisch Instituut voor Postdiensten en Telecommunicatie - Belgian Institute for Postal services and Telecommunications (BIPT) in Belgium [**?**]), the list of allowed channels can vary. Using `iw` you can get the list of available channels.

The wireless drivers we use make a difference between the logical interface (`wlan0` as we have used it so far) and the actual physical radio interface. All things related to physical characteristics are actually handled by the physical interface, which is called `phy0` or `phy1`, respectively.

1. To get a correct overview of which frequencies/channels are available in Belgium, use the command `iw phy1 info`.

2. List all frequencies/channels that the `phy1` interface supports.
   L2-1-1

Using the command iw phy1 info, we got a lot of output, filtering for Frequencies rendered the following result, showing which frequencies the physical interface supports (though some are disabled):
Frequencies:

- 2412 MHz [1] (20.0 dBm)
- 2417 MHz [2] (20.0 dBm)
- 2422 MHz [3] (20.0 dBm)
- 2427 MHz [4] (20.0 dBm)
- 2432 MHz [5] (20.0 dBm)
- 2437 MHz [6] (20.0 dBm)
- 2442 MHz [7] (20.0 dBm)
- 2447 MHz [8] (20.0 dBm)
- 2452 MHz [9] (20.0 dBm)
- 2457 MHz [10] (20.0 dBm)
- 2462 MHz [11] (20.0 dBm)
- 2467 MHz [12] (20.0 dBm)
- 2472 MHz [13] (20.0 dBm)
- 2484 MHz [14] (disabled)

Frequencies:

- 5180 MHz [36] (20.0 dBm)
- 5190 MHz [38] (20.0 dBm)
- 5200 MHz [40] (20.0 dBm)
- 5220 MHz [44] (20.0 dBm)
- 5230 MHz [46] (20.0 dBm)
- 5240 MHz [48] (20.0 dBm)
- 5260 MHz [52] (20.0 dBm) (radar detection)
- 5270 MHz [54] (20.0 dBm) (radar detection)
- 5280 MHz [56] (20.0 dBm) (radar detection)
- 5300 MHz [60] (20.0 dBm) (radar detection)
- 5310 MHz [62] (20.0 dBm) (radar detection)

- 5320 MHz [64] (20.0 dBm) (radar detection)
- 5500 MHz [100] (27.0 dBm) (radar detection)
- 5510 MHz [102] (27.0 dBm) (radar detection)
- 5520 MHz [104] (27.0 dBm) (radar detection)
- 5540 MHz [108] (27.0 dBm) (radar detection)
- 5550 MHz [110] (27.0 dBm) (radar detection)
- 5560 MHz [112] (27.0 dBm) (radar detection)
- 5580 MHz [116] (27.0 dBm) (radar detection)
- 5590 MHz [118] (27.0 dBm) (radar detection)
- 5600 MHz [120] (27.0 dBm) (radar detection)
- 5620 MHz [124] (27.0 dBm) (radar detection)
- 5630 MHz [126] (27.0 dBm) (radar detection)
- 5640 MHz [128] (27.0 dBm) (radar detection)
- 5660 MHz [132] (27.0 dBm) (radar detection)
- 5670 MHz [134] (27.0 dBm) (radar detection)
- 5680 MHz [136] (27.0 dBm) (radar detection)
- 5700 MHz [140] (27.0 dBm) (radar detection)
- 5745 MHz [149] (disabled)
- 5755 MHz [151] (disabled)
- 5765 MHz [153] (disabled)
- 5785 MHz [157] (disabled)
- 5795 MHz [159] (disabled)
- 5805 MHz [161] (disabled)
- 5825 MHz [165] (disabled)
- 5835 MHz [167] (disabled)
- 5845 MHz [169] (disabled)
- 5855 MHz [171] (disabled)
- 5865 MHz [173] (disabled)
- 4920 MHz [-16] (disabled)
- 4940 MHz [-12] (disabled)
- 4960 MHz [-8] (disabled)
- 4980 MHz [-4] (disabled)

- 6040 MHz [208] (disabled)
- 6060 MHz [212] (disabled)
- 6080 MHz [216] (disabled)

You should observe several frequencies that are marked *disabled*. This indicates that the card supports these frequencies, but cannot use them because of Belgian regulations. Also, several frequencies should be marked with *radar detection*. These can be used, but special mechanisms must be put in place in order to avoid interference with radar installatiuons (e.g. airport radar).

Exercise 2: Available UA hotspots

Figure 2.1: Channel separation setup 1

1. Start by building the setup as illustrated in figure 2.1.

   Remark that it is not necessary to configure the SSID or channel, but bring up the interface to activate it.

2. Find out which access points (APs) are active using `iw wlan0 scan`. This command provides an interface to list various settings from the wireless network interface card (wnic). The manpage or command line help should be self-explanatory.

3. Fill in the following table:
   L2-2-1

SSID	frequency(MHz)	BSS
UA-guest	2412	84:d4:7e:27:c0:61
mosaic	2412	08:76:ff:b4:09:c3
eduroam	2412	84:d4:7e:27:b5:80
UA-guest	2412	84:d4:7e:27:b5:81
UAntwerpen	2412	84:d4:7e:27:b5:82
Wireless Antwerpen PATS test	2437	00:1d:7e:1b:11:83
mosaic	2437	08:76:ff:4c:0e:9e
G233	2462	04:1e:64:f2:13:b1
UAntwerpen	2462	00:0b:86:a6:25:75
eduroam	2462	84:d4:7e:27:bc:00
UA-guest	2462	84:d4:7e:27:bc:01
UAntwerpen	2462	84:d4:7e:27:bc:02
eduroam	2462	84:d4:7e:27:a3:e0
UA-guest	2462	84:d4:7e:27:a3:e1
UAntwerpen	2462	84:d4:7e:27:a3:e2
Jan's Wi-Fi Network	2462	f0:99:bf:0c:be:38
TelenetWiFree	2462	06:53:7c:31:a4:85
eduroam	5180	84:d4:7e:27:c2:10
UA-guest	5180	84:d4:7e:27:c2:11
UAntwerpen	5180	84:d4:7e:27:c2:12
community-lab.net	5180	02:ca:ff:ee:ba:be
G233	5220	04:1e:64:f2:13:b2
eduroam	5260	84:d4:7e:27:b5:90
UA-guest	5260	84:d4:7e:27:b5:91
UAntwerpen	5260	84:d4:7e:27:b5:92
eduroam	5300	84:d4:7e:27:c0:70
UA-guest	5300	84:d4:7e:27:c0:71
UAntwerpen	5300	84:d4:7e:27:c0:72
CONFINE-J	5500	dc:9f:db:48:ba:ee
CONFINE-I	5520	dc:9f:db:48:b8:eb
eduroam	5580	84:d4:7e:27:a3:f0
UA-guest	5580	84:d4:7e:27:a3:f1
UAntwerpen	5580	84:d4:7e:27:a3:f2
CONFINE-H	5660	00:0c:42:c3:97:a2
CONFINE-K	5660	dc:9f:db:48:ed:51

2.2 Channel Separation

Exercise 3: Channel overhearing


```
No. ▾   Time        Source             Destination     Protocol  Info
     1  0.000000    ArubaNet_a6:26:80   Broadcast       IEEE 80:  Beacon frame,SN=2648,FN=0,BI=100, SSID: "UA-vpn"
     2  0.001109    ArubaNet_a6:26:81   Broadcast       IEEE 80:  Beacon frame,SN=2649,FN=0,BI=100, SSID: "UA-visit"
     3  0.001684    ArubaNet_a6:26:82   Broadcast       IEEE 80:  Beacon frame,SN=2650,FN=0,BI=100, SSID: "UA-dwep"
     4  0.002089    ArubaNet_a6:26:83   Broadcast       IEEE 80:  Beacon frame,SN=2651,FN=0,BI=100, SSID: "UA-tkip"
     5  0.002511    ArubaNet_a6:26:84   Broadcast       IEEE 80:  Beacon frame,SN=2652,FN=0,BI=100, SSID: "UA-aes"

▷ Frame 1 (126 bytes on wire, 126 bytes captured)
▽ Radiotap Header v0, Length 26
      Header revision: 0
      Header pad: 0
      Header length: 26
    ▷ Present flags: 0x0000186f
      MAC timestamp: 7916884150
    ▷ Flags: 0x12
      Data Rate: 1.0 Mb/s
      Channel: 5
      Channel frequency: 2432
      Channel type: 802.11g (0x0480)
      SSI Signal: -73 dBm
      SSI Noise: -96 dBm
      Antenna: 1
      SSI Signal: 23 dB
▷ IEEE 802.11
▽ IEEE 802.11 wireless LAN management frame
    ▷ Fixed parameters (12 bytes)
    ▽ Tagged parameters (60 bytes)
      ▷ SSID parameter set: "UA-vpn"
      ▷ Supported Rates: 1.0(B) 2.0(B) 5.5 11.0
      ▷ DS Parameter set: Current Channel: 6
      ▷ (TIM) Traffic Indication Map: DTIM 0 of 1 bitmap empty
      ▷ Country Information: Country Code: BE, Any Environment
      ▷ Power Constraint: Tag 32 Len 1
      ▷ ERP Information: no Non-ERP STAs, do not use protection, short or long preambles
      ▷ Extended Supported Rates: 6.0 9.0 12.0 18.0 24.0 36.0 48.0 54.0
      ▷ Reserved tag number: Tag 171 Len 11
```

Figure 2.2: Channels in a captured beacon frame.

In the previous exercise, you made an overview of a lot of access points. The next exercise will illustrate the channel overhearing. The information about which channel an AP is working on, is provided in the beacon frames the AP periodically transmits. In figure 2.2, a Wireshark [**?**] screen shot shows a beacon frame. The Radiotap header indicates the frame was received on channel 5, while the beacon's content shows the AP sending this beacon only operates at channel 6. Channels are thus not cleanly separated. In the next exercise you'll create an overview of the channel overhearing.

1. Start from the setup as shown in figure 2.3.

Figure 2.3: Setup for exercise 3.

Note that the AP should be configured in channel 4 from the b/g range. To be able to do this, you should change the line `hw_mode=a` to `hw_mode=b` in the hostapd.conf file.

2. On station (STA)1, on every channel, make a capture `/mnt/L2-3-1.chanID.pcap`

3. Use the following wireshark display filter to only show beacons:
   `wlan.fc.type_subtype == 8`

4. Fill out the following table using the obtained information.

   L2-3-1

Selected channels	Observed channels in received beacons
1	1,4
2	1,4
3	1,4,6
4	4,6
5	4,6
6	4,6
7	6
8	4,6
9	11,4,6
10	11,4
11	11,4

From this exercise, it should be clear that the channels within the IEEE 802.11b/g range are not strictly separated. Figure 2.4[1] gives you an idea why: the consecutive

---

[1]By Michael Gauthier, Wireless Networking in the Developing World [CC-BY-SA-3.0 (http://creativecommons.org/licenses/by-sa/3.0)], via Wikimedia Commons

Figure 2.4: 2.4 GHz channels

channels overlap to a certain extent. Therefore, a careful channel planning is crucial in building and deploying wireless networks on these frequencies. In the next exercise, we will take a look at the channel separation in the IEEE 802.11a band.

Exercise 4: Channel separation in IEEE 802.11a

1. Now, change the AP so that it is on channel `x`.

2. Using `tcpdump` as in the previous exercise, find out in which channels IEEE 802.11a the beacons of this AP can be seen. Save your traces in `/mnt/L2-4-1.chanID.pcap`

   L2-4-1

   The beacons from our channel could be found in channel 36 and not anymore in channel 40.

## 2.3   Using the Wireless Channel

Figure 2.5: Basic ad-hoc network.

Exercise 5: Beacons

In the next few exercises, we will again use an ad-hoc network setup. It is best to reboot the devices before proceeding.

1. Create the network setup as shown in figure 2.5. Perform the following commands on all three stations. Substitute `nodeNumber` with a different number (e.g. 1, 2 and 3) on each node.
   ```
   wmn:~# iw dev wlan0 set type ibss
   wmn:~# ip addr add fc00:grID::nodeNumber/64 dev wlan0
   wmn:~# ifconfig wlan0 up
   wmn:~# iw dev wlan0 ibss join wmn-grID-A <frequency>
   ```

2. Put interface wlan1 of STA1 in monitor mode on the same frequency.
   ```
   STA1:~# iw dev wlan1 set type monitor
   STA1:~# ifconfig wlan1 up
   STA1:~# iw dev wlan1 set freq <frequency>
   ```

3. Check if all stations can reach each other.

4. Perform a `tcpdump` on the monitor interface. Save it to `/mnt/L2-5-1.STA1.pcap` Let it run for a few seconds and then stop the trace.

5. In your trace file, you should observe beacon frames. Carefully inspect one of the beacon frames in this trace and compare it to a beacon frame captured in the previous exercise (exercise 4). Give the packet IDs of the beacon frames you are comparing and identify the differences in the management frame part.

   L2-5-1

   For this exercise, we will be comparing packet 2 from traces/L2-4-1.36.pcap and packet 2 from traces/L2-5-1.STA1.pcap. For the purpose of comparing the WLAN management frames, I have included them below:

   For the beacon frame captured in exercise 4:

   ```
 1 IEEE 802.11 wireless LAN management frame
       Fixed parameters (12 bytes)
 3         Timestamp: 0x00000000082f503b
           Beacon Interval: 0,102400 [Seconds]
 5         Capabilities Information: 0x0001
               .... .... .... ...1 = ESS capabilities: Transmitter is an
                   AP
 7             .... .... .... ..0. = IBSS status: Transmitter belongs to a
                   BSS
               .... ..0. .... 00.. = CFP participation capabilities: No
                   point coordinator at AP (0x0000)
   ```

```
9        .... .... ...0 .... = Privacy : AP/STA cannot support WEP
         .... .... ..0. .... = Short Preamble : Not Allowed
11       .... .... .0.. .... = PBCC : Not Allowed
         .... .... 0... .... = Channel Agility : Not in use
13       .... ...0 .... .... = Spectrum Management : Not Implemented
         .... .0.. .... .... = Short Slot Time : Not in use
15       .... 0... .... .... = Automatic Power Save Delivery : Not
            Implemented
         ...0 .... .... .... = Radio Measurement : Not Implemented
17       ..0. .... .... .... = DSSS-OFDM : Not Allowed
         .0.. .... .... .... = Delayed Block Ack : Not Implemented
19       0... .... .... .... = Immediate Block Ack : Not Implemented
     Tagged parameters (28 bytes )
21      Tag : SSID parameter set : wmn-1-A
            Tag Number : SSID parameter set (0)
23          Tag length : 7
            SSID : wmn-1-A
25      Tag : Supported Rates 6(B) , 9, 12(B) , 18, 24(B) , 36, 48, 54, [
            Mbit / sec ]
            Tag Number : Supported Rates (1)
27          Tag length : 8
            Supported Rates : 6(B) (0x8c)
29          Supported Rates : 9 (0x12)
            Supported Rates : 12(B) (0x98)
31          Supported Rates : 18 (0x24)
            Supported Rates : 24(B) (0xb0)
33          Supported Rates : 36 (0x48)
            Supported Rates : 48 (0x60)
35          Supported Rates : 54 (0x6c)
        Tag : DS Parameter set : Current Channel : 36
37          Tag Number : DS Parameter set (3)
            Tag length : 1
39          Current Channel : 36
        Tag : Traffic Indication Map (TIM) : DTIM 1 of 0 bitmap
41          Tag Number : Traffic Indication Map (TIM) (5)
            Tag length : 4
43          DTIM count : 1
            DTIM period : 2
45          Bitmap control : 0x00
                .... ...0 = Multicast : False
47              0000 000. = Bitmap Offset : 0x00
            Partial Virtual Bitmap : 00
```

for the beacon frame captured in exercise 5:

```
IEEE 802.11 wireless LAN management frame
2    Fixed parameters (12 bytes )
         Timestamp : 0x000000000a53c0aa
4        Beacon Interval : 0,102400 [Seconds ]
         Capabilities Information : 0x0002
```

```
 6          .... .... .... ...0 = ESS capabilities: Transmitter is a
                STA
            .... .... .... ..1. = IBSS status: Transmitter belongs to
                an IBSS
 8          .... ..0. .... 00.. = CFP participation capabilities:
                Station is not CF-Pollable (0x0000)
            .... .... ...0 .... = Privacy: AP/STA cannot support WEP
10          .... .... ..0. .... = Short Preamble: Not Allowed
            .... .... .0.. .... = PBCC: Not Allowed
12          .... .... 0... .... = Channel Agility: Not in use
            .... ...0 .... .... = Spectrum Management: Not Implemented
14          .... .0.. .... .... = Short Slot Time: Not in use
            .... 0... .... .... = Automatic Power Save Delivery: Not
                Implemented
16          ...0 .... .... .... = Radio Measurement: Not Implemented
            ..0. .... .... .... = DSSS-OFDM: Not Allowed
18          .0.. .... .... .... = Delayed Block Ack: Not Implemented
            0... .... .... .... = Immediate Block Ack: Not Implemented
20      Tagged parameters (32 bytes)
            Tag: SSID parameter set: wmn-1-A
22              Tag Number: SSID parameter set (0)
                Tag length: 7
24              SSID: wmn-1-A
            Tag: Supported Rates 6(B), 9, 12(B), 18, 24(B), 36, 48, 54, [
                Mbit/sec]
26              Tag Number: Supported Rates (1)
                Tag length: 8
28              Supported Rates: 6(B) (0x8c)
                Supported Rates: 9 (0x12)
30              Supported Rates: 12(B) (0x98)
                Supported Rates: 18 (0x24)
32              Supported Rates: 24(B) (0xb0)
                Supported Rates: 36 (0x48)
34              Supported Rates: 48 (0x60)
                Supported Rates: 54 (0x6c)
36          Tag: IBSS Parameter set: ATIM window 0x0
                Tag Number: IBSS Parameter set (6)
38              Tag length: 2
                Atim Windows: 0x0000
40          Tag: Vendor Specific: Microsof: WMM/WME: Information Element
                Tag Number: Vendor Specific (221)
42              Tag length: 7
                OUI: 00-50-f2
44              Vendor Specific OUI Type: 2
                Type: WMM/WME (0x02)
46              WME Subtype: Information Element (0)
                WME Version: 1
48              WME QoS Info: 0x00
                    0... .... = U-APSD: Disabled
50                  .... 0000 = Parameter Set Count: 0x00
                    .000 .... = Reserved: 0x00
```

6. Start a new trace on the monitor interface and save it to `/mnt/L2-5-2.STA1.pcap`

7. While the trace is running, perform two ping tests. You may perform the simultaneously, but it will be easier to answer the next question if you perform them consecutively.
```
STA2:~# ping6 -c 5 fc00:grID::3
STA3:~# ping6 -s 1400 -c 5 fc00:grID::1
```

8. Open your trace file and filter out the beacon frames with the following display filter: `!(wlan.fc.type_subtype == 0x08)`. Apart from the data frames, which kind of frames do you observe?

   L2-5-2

9. Explain the purpose of those frames.

   L2-5-3

Exercise 6: Request to Send (RTS)/Clear to Send (CTS)

For this exercise, you will study the RTS/CTS mechanism. This mechanism will clear the channel for each transmission, minimizing the chance of collisions in the channel. A threshold value is used to determine if RTS/CTS should be used. Larger packets will receive RTS/CTS protections while smaller packet will not. Using RTS/CTS for small packets adds a lot of overhead and hence degrades performance.

1. Start from the setup as for the previous exercise.

2. The RTS/CTS threshold will be set with `iwconfig wlan0 rts 1000`. Perform this command on all nodes.

3. Performing the same `ping6` commands as in the previous exercise. Start a capture session on the monitor interface and save it to `/mnt/L2-6-1.STA1.pcap`

4. You should observe RTS/CTS packets. Which packets are protected by this mechanism? Give an example (packet ID).

L2-6-1

_____

_____

5. Compare an RTS and CTS frame. How do they differ? Illustrate using frames from your last trace file. **L2-6-2**

_____

_____

As you can see in the RTS/CTS frames, they do not contain any information about the network on which they are transmitted. The RTS/CTS is meant to avoid collisions on the wireless medium, so any node that receives a CTS frame is required to remain silent for the duration included in the CTS frame. The only exception, for obvious reasons, is the node to which the CTS frame is sent. Capturing RTS/CTS frames (or acknowledgement frames) on a certain channel is always a good indication that some activity is going on in that channel, even if it is impossible to overhear the actual data transmission.

2.4   IEEE 802.11n

Until now, we have only used the wnics in IEEE 802.11a or b/g mode. "b" is the oldest mode. "g" improves upon "b" by offering significantly higher maximal throughput (54 Mbps versus 11 Mbps) ."a" operates at different frequencies and offers the same throughput as "g".

Another mode of operation is called "n". IEEE 802.11n is an amendment to the IEEE 802.11 standard in order to improve throughput over both "a" and "g". It operates at both frequency bands and is defined for bit rates up to 600 Mbps, but very few setups will be able to obtain these speeds.

IEEE 802.11n can use different optimizations, such as the multiple-input, multiple-output (MIMO) principle, 40 MHz wide channels (versus 20 MHz in IEEE 802.11a/b/g), and frame aggregation to improve throughput. The following exercise will demonstrate that IEEE 802.11n channels can indeed be twice as wide as those in IEEE 802.11a, and thus interfere with adjacent IEEE 802.11a channels.

Exercise 7: IEEE 802.11n

Figure 2.6: IEEE 802.11n ad-hoc network.

As this exercise will use both channels allocated to the mobile and wireless lab, two groups cannot perform this exercise at the same time! Check if no other group is currently working on this course!

1. Reboot all devices. In order to enable IEEE 802.11n mode without any problems, we will start from a blank setup.

2. After they have been rebooted, perform the following on all devices in order to create an ad-hoc network with IEEE 802.11n support in the 5 GHz band:
   ```
   STA:~# iw dev wlan0 set type ibss
   STA:~# ip addr add fc00:grID::nodeNumber/64 dev wlan0
   STA:~# ifconfig wlan0 up
   STA:~# iw dev wlan0 ibss join wmn-grID-A 5180 HT20
   ```

3. Check that all nodes can reach each other.

4. Set up a monitor interface on channel 36 (5180 MHz) on STA1.

5. Start a trace on the monitor interface and save it to `/mnt/L2-7-1.STA1.pcap`

6. Start a ping from STA2 to STA3 and from STA3 to STA1. Like before, use different ping sizes:
   ```
   STA2:~# ping6 -c 5 fc00:grID::3
   STA3:~# ping6 -s 1400 -c 5 fc00:grID::1
   ```

7. Filter out the beacon frames from your trace. Do you observe packets from both ping sessions? Did you see all packets from these sessions? Why or why not?
   L2-7-1

   _____

   _____

8. Set the monitor interface to channel 40 (5200 MHz).

14

9. Perform the same ping test again, but now save your trace to `/mnt/L2-7-2.STA1.pcap`

10. Did you capture any packets?
    L2-7-2

    _____

    _____

Exercise 8: 40 MHz channels

In the previous exercise, we enabled IEEE 802.11n, but we did not enable 40 MHz wide channels yet. We will do that now.

1. Deconfigure all `wlan0` interfaces.
   ```
   STA:~# iw dev wlan0 ibss leave
   ```

2. Now, create an ad-hoc network that uses 40 MHz wide channels:
   ```
   STA:~# iw dev wlan0 ibss join wmn-0-A 5180 HT40+
   ```

3. As in the previous exercise, set the monitor interface of STA1 on channel 36 and perform a capture while sending both pings. Save it to `/mnt/L2-8-1.STA1.36.pcap`

4. Do the same again, but this time monitor channel 40.
   Save your trace in `/mnt/L2-8-1.STA1.40.pcap`

5. Do you observe any different behaviour in the trace file on channel 36, compared to the previous exercise?
   L2-8-1

   _____

   _____

6. In the trace file on channel 40, which packets have you captured? Why?
   L2-8-2

   _____

   _____

Acronyms

AP access point

BIPT Belgisch Instituut voor Postdiensten en Telecommunicatie - Belgian Institute for Postal services and Telecommunications

CTS Clear to Send

grID group ID

MIMO multiple-input, multiple-output

nic network interface card

RTS Request to Send

STA station

wmn wireless mesh node

wnic wireless network interface card