



Advance Care Directive Custodian Record
CDA Implementation Guide

11 September 2019 v2.0.0

Draft for internal use

Document ID: DH-XXXX:2019

Draft Version 002

**THIS SPECIFICATION IS AN UNTESTED DRAFT AND IS NOT SUITABLE
FOR IMPLEMENTATION.**

DRAFT



Disclaimer

The Australian Digital Health Agency (“the Agency”) makes the information and other material (“Information”) in this document available in good faith but without any representation or warranty as to its accuracy or completeness. The Agency cannot accept any responsibility for the consequences of any use of the Information. As the Information is of a general nature only, it is up to any person using or relying on the Information to ensure that it is accurate, complete and suitable for the circumstances of its use.

Document control

This document is maintained in electronic form and is uncontrolled in printed form. It is the responsibility of the user to verify that this copy is the latest revision.

Security

The information contained herein must only be used for the purpose for which it is supplied and must not be disclosed other than explicitly agreed in writing with the Australian Digital Health Agency.

Copyright © 2019 Australian Digital Health Agency

This document contains information which is protected by copyright. All Rights Reserved. No part of this work may be reproduced or used in any form or by any means – graphic, electronic, or mechanical, including photocopying, recording, taping, or information storage and retrieval systems – without the permission of the Australian Digital Health Agency. All copies of this document must include the copyright and other information contained on this page.

OFFICIAL

Document Information

Key Information

| | |
|-----------------------|--|
| Owner | National Health Chief Information Officer, Infrastructure Operations |
| Contact for enquiries | Australian Digital Health Agency Help Centre |
| t: | 1300 901 001 |
| e: | help@digitalhealth.gov.au |

Product Version History

| Product ver- sion | Date | Release comments |
|----------------------|-------------|--|
| 1.0 | 1 NaN | Initial release. |
| 2.0.0 | 11 Sep 2019 | This version implements terminology updates and transitions from openEHR based models to FHIR-based models. This is a backwards incompatible release |

Related Documents

| Name | Version/Release Date |
|--|---|
| Australian Base Profiles Implementation Guide | v1.0.0 (Standard for Trial Use), Continuous Integration Build |
| FHIR | Release 3 (STU), Issued 19 April 2017 |
| Participant Model Specification | Version 1.0, Issued 01 November 2018 |
| Common - Clinical Document | Version 1.5.2, Issued 28 February 2019 |
| CDA Rendering Specification | Version 1.0, Issued 07 March 2012 |
| Advance Care Directive Record Information Requirements | Version 1.0, Issued 12 December 2011 |
| Representing Coding in CDA Documents Implementation Guidance | Version 1.0, Issued 10 October 2011 |
| Clinical Documents Common Conformance Profile | Version 1.7, Issued 21 December 2017 |

DRAFT

Acknowledgements

Council of Australian Governments

The Australian Digital Health Agency is jointly funded by the Australian Government and all state and territory governments.

Regenstrief Institute (LOINC)

This material contains content from [LOINC™](#). The LOINC table, LOINC codes, LOINC panels and forms file, and LOINC linguistic variants file are copyright © 1995-2015, Regenstrief Institute, Inc. and the Logical Observation Identifiers Names and Codes (LOINC) Committee and available at no cost under the license at the [LOINC Terms of Use](#). LOINC is a trademark of Regenstrief Institute, Inc., registered in the United States.

IHTSDO (SNOMED CT)

This material includes SNOMED Clinical Terms™ (SNOMED CT®) which is used by permission of the International Health Terminology Standards Development Organisation (IHTSDO). All rights reserved. SNOMED CT® was originally created by The College of American Pathologists. "SNOMED" and "SNOMED CT" are registered trademarks of the [IHTSDO](#).

HL7 FHIR

This product includes all or a portion of material that is HL7 FHIR Copyright © 2011+ HL7 licensed under Creative Commons "No Rights Reserved".

HL7 International

This document includes excerpts of HL7™ International standards and other HL7 International material. HL7 International is the publisher and holder of copyright in the excerpts. The publication, reproduction and use of such excerpts is governed by the [HL7 IP Policy](#) and the HL7 International License Agreement. HL7 and CDA are trademarks of Health Level Seven International and are registered with the United States Patent and Trademark Office. FHIR is a registered trademark of Health Level Seven International.

This product includes all or a portion of the HL7 Vocabulary, or is derived from the HL7 Vocabulary, subject to a license from Health Level Seven International. Your use of the HL7 Vocabulary also is subject to this license, a copy of which is accessible through the following link: <http://www.hl7.org/permalink/?VocabTables>. The current complete HL7 Vocabulary is also available through this link. The HL7 Vocabulary is copyright © 1989-2010, Health Level Seven International. All rights reserved. THE HL7 VOCABULARY IS PROVIDED "AS IS." ANY EXPRESS OR IMPLIED WARRANTIES ARE DISCLAIMED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

DRAFT

Table of Contents

| | |
|---|----|
| 1. Introduction | 1 |
| 1.1. Document purpose and scope | 1 |
| 1.2. Context and use | 1 |
| 1.3. How to read this document | 2 |
| 1.4. Editorial note | 2 |
| 1.5. Intended audience | 2 |
| 1.6. Known issues | 2 |
| 2. Guidance | 5 |
| 2.1. Clinical Document Architecture Release 2 | 5 |
| 2.2. Australian Digital Health Agency CDA extensions | 6 |
| 2.3. Conformance conventions | 7 |
| 2.4. Mapping presentation and structure | 10 |
| 3. Conformance | 13 |
| 3.1. Conformance requirements | 13 |
| 3.2. CDA narratives | 14 |
| 4. Advance Care Directive Custodian Record hierarchy | 15 |
| 4.1. Hierarchy | 15 |
| 4.2. Expanded hierarchy | 16 |
| 5. CDA Header templates | 23 |
| 5.1. ClinicalDocument | 23 |
| 5.2. LegalAuthenticator | 26 |
| 5.3. Administrative Observations | 27 |
| 6. Document CDA templates | 29 |
| 6.1. Composition (Advance Care Directive Custodian Record) | 29 |
| 7. Participation CDA templates | 31 |
| 7.1. recordTarget (Patient with Mandatory Identifier) | 31 |
| 7.2. participant (Patient contact) | 36 |
| 7.3. participant (generalPractitioner Base Organization) | 37 |
| 7.4. participant (generalPractitioner Base Practitioner) | 39 |
| 7.5. participant (Base Organization) | 41 |
| 7.6. participant (Base Patient) | 43 |
| 7.7. participant (Base Practitioner) | 46 |
| 7.8. participant (Base RelatedPerson) | 48 |
| 7.9. author (Patient with Mandatory Identifier) | 50 |
| 7.10. author (RelatedPerson with Mandatory Identifier) | 52 |
| 7.11. author (PractitionerRole with Practitioner with Mandatory Identifier) | 54 |
| 7.12. custodian (Organization with Mandatory Identifier) | 56 |
| 8. Entity CDA templates | 59 |
| 8.1. providerOrganization (Base Organization) | 59 |
| 8.2. participant (Organization contact) | 61 |
| 8.3. representedOrganization (Base Organization) | 62 |
| 8.4. assignedPerson (Practitioner with Mandatory Identifier) | 64 |
| 9. Section CDA templates | 67 |
| 9.1. section (Advance Care Directive Custodians) | 67 |
| 10. Act CDA templates | 69 |
| 10.1. act (Advance Care Directive Custodian Entry) | 69 |
| 10.2. ext:coverage (Practitioner qualification) | 70 |
| 11. Common patterns | 73 |
| 11.1. code | 73 |
| 11.2. id | 76 |
| 11.3. time | 78 |
| 11.4. Entity Identifier | 80 |
| 11.5. Personal Relationship | 82 |
| 11.6. Qualification | 84 |
| A. Complex data type mappings to CDA (R2) | 85 |
| A.1. Identifier | 86 |
| A.2. HumanName | 91 |

| | |
|--|------------|
| A.3. Address | 93 |
| A.4. Address as Australian Address | 95 |
| A.5. ContactPoint | 97 |
| B. Examples | 99 |
| B.1. Advance Care Directive Custodian Record example 1 | 100 |
| B.2. Advance Care Directive Custodian Record example 2 | 103 |
| C. Mapping from requirements | 105 |
| References | 109 |

DRAFT

List of Examples

| | |
|--|-----|
| 11.1. code | 74 |
| 11.2. id | 77 |
| 11.3. Simple timestamp | 78 |
| 11.4. Low time | 78 |
| 11.5. Interval timestamp 1 | 78 |
| 11.6. Interval timestamp 2 | 79 |
| 11.7. Width time | 79 |
| 11.8. Entity Identifier | 81 |
| 11.9. Personal Relationship | 83 |
| A.1. Identifier | 88 |
| A.2. HumanName | 92 |
| A.3. Address | 94 |
| A.4. Address | 96 |
| A.5. ContactPoint | 98 |
| B.1. Advance Care Directive Custodian Record example 1 | 100 |
| B.2. Advance Care Directive Custodian Record example 2 | 103 |

DRAFT

1 Introduction

1.1 Document purpose and scope

The primary aim of the implementation guide is to take implementers step by step through mapping each element of the Advance Care Directive Custodian Record (ACDCR) model (*Advance Care Records FHIR Implementation Guide [DH2019e]*) to a corresponding CDA attribute or element. The resulting CDA document can be used for the electronic exchange of ACDCR information between healthcare providers.

This implementation guide is not to be used as a guide to presentation (or rendering) of the data. Beyond defining conformance requirements on CDA narratives it contains no information as to how the data described by it should be displayed and no such guidance should be inferred from This implementation guide.

Reference has been made to International and Australian Standards, and to Standards from Health Level Seven. The following standard is referred to in the text in such a way that some or all of its content constitutes requirements for the purposes of this specification: *HL7 Clinical Document Architecture [HL7CDAR2]*.

Wherever possible, material in this specification is based on existing standards. All efforts have been made to minimise divergence from the HL7 Australia profiles of HL7 International standards (*Australian Base Profiles Implementation Guide [HL7AUBIG]*) to provide for system interoperability and compatibility with other profiles. Issues of an editorial nature in the source material (such as spelling or punctuation errors) are intentionally reproduced.

1.2 Context and use

A CDA implementation guide is part of a package of documents and files that support the development of software to exchange a type of clinical document, a specification package.

An Agency clinical document specification package supports software developers to create and interpret instances of a clinical document. The core of each package is a specification of the information content of instances of the clinical document.

Supplementary contents of the package include statements of scenarios for which the specification is appropriate, guidance on implementing the specification, and guidance on testing purported instances.

The contents may include:

- statement of requirements
- CDA implementation guide (CDA IG) – a statement of constraints and custom extensions on *HL7 Clinical Document Architecture [HL7CDAR2]*
- FHIR implementation guide (FHIR IG) – a statement of constraints and custom extensions on *FHIR [HL7FHIR3]*
- template package library – a set of Schematron schema to test conformance of CDA documents with the specification
- conformance profile – a statement of conformance requirements for exchanging documents within a particular scenario such as the My Health Record
- A set of release notes

Specification packages contain only files relevant to the particular clinical document. Specifications that are common to many clinical documents and should be considered part of the specification package, as directed by the relevant release note and conformance profile, are contained in the *Common - Clinical Document [DH2019a]*.

1.3 How to read this document

This implementation guide contains descriptions of both constraints on the CDA and, where necessary, custom extensions to the CDA, for the purposes of fulfilling the requirements for Australian implementations of ACDCR.

These descriptions are defined as a set of CDA templates (see [Conformance conventions](#)) presented in CDA mapping tables (see [Mapping presentation and structure](#)). The mapping tables take implementers step by step through mapping each element of the ACDCR model to a corresponding CDA attribute or element.

A logical view of the ACDCR model ([FHIR \[HL7FHIR3\] StructureDefinitions](#)) is presented as a tree structure in a hierarchical table (see [4 Advance Care Directive Custodian Record hierarchy](#)). The ACDCR model is published as a set of [FHIR \[HL7FHIR3\]](#) profiles in [Advance Care Records FHIR Implementation Guide \[DH2019e\]](#).

The starting point for the CDA templates is the clinical document model template defined in [Composition \(Advance Care Directive Custodian Record\)](#), which references the additional templates necessary to assert conformance for this implementation guide.

1.4 Editorial note

This implementation guide is an early working specification that is available for comment and review. It may be used to solicit feedback and to provide insight as to the expected content in a forthcoming stable and approved version of the specification.

This implementation guide may not be considered to be complete enough or sufficiently reviewed to be safe for implementation and use in production systems. It may have known issues and still be in development.

It is intended to supersede [Advance Care Directive Custodian Record Structured Content Specification \[NEHT2011ax\]](#) and [Advance Care Directive Custodian Record CDA Implementation Guide \[NEHT2011bg\]](#). This new, backwards incompatible version, is intended to address alignment to HL7 FHIR and is the result of work undertaken in conjunction with HL7 Australia.

1.5 Intended audience

This implementation guide is aimed at software development teams, architects, designers, clinicians and informatics researchers who are responsible for the delivery of clinical applications, infrastructure components and messaging interfaces, and also for those who wish to evaluate the clinical suitability of the Agency-endorsed specifications.

This implementation guide and related artefacts are technical in nature and the audience is expected to be familiar with the language of health data specifications and to have some familiarity with health information standards and specifications, such as CDA and Standards Australia IT-014 documents. Definitions and examples are provided to clarify relevant terminology usage and intent.

1.6 Known issues

This section lists known issues with this specification at the time of publishing. We are working on solutions to these issues and encourage comments to help us develop these solutions.

| Reference | Description |
|-------------------------|---|
| Terminology publication | <p>The following value sets are not yet available in NCTS:</p> <ul style="list-style-type: none">• Healthcare Identifier Geographic Area• Composition Status FHIR to Australian CDA Document Life-cycle Status |

| Reference | Description |
|--|--|
| Advance Care Records FHIR Implementation Guide [DH2019e] | The corresponding Advance Care Directive Custodian Record FHIR IG is currently in progress; draft content is available from https://github.com/AuDigitalHealth/ci-fhir-stu3 (public) https://stash.digitalhealth.gov.au/projects/CIL/repos/-/ci-fhir-stu3/browse (internal). |

DRAFT

DRAFT

2 Guidance

2.1 Clinical Document Architecture Release 2

A CDA document is an XML document built following the rules described in the CDA specification, which conforms to the HL7 CDA schema provided by HL7. The CDA document is based on the semantics provided by the [HL7 V3 RIM, Data types and Vocabulary \[HL7V3DT\]](#).

A CDA document has two main parts: the header and the body.

The CDA document header is consistent across all CDA documents, regardless of document type. The header identifies and classifies the document and provides information on authentication, the encounter, the patient, and the involved providers.

The body contains the clinical report. The body can be marked-up text (narrative, renderable text) or a combination of both marked-up text and structured data. The marked-up text can be transformed to XHTML and displayed to a human. The structured data allows machine processing of the information shown in the narrative section.

All clinical information is required to be marked up in CDA narratives. These narratives are CDA-defined hypertext, able to be rendered in web browsers with only a standard accompanying transformation. This transformation is produced and distributed by HL7.

The rendered narrative can stand alone as a source of authenticated information for consuming parties. Content from the CDA body is not to be omitted from the narrative.

Further information and conformance requirements on the CDA narrative is available in [CDA narratives](#).

The following references are recommended to gain a better understanding of CDA:

- [HL7 Clinical Document Architecture \[HL7CDAR2\]](#)
- [HL7 V3 RIM, Data types and Vocabulary \[HL7V3DT\]](#)
- [CDA Examples \[RING2009\]](#)
- [CDA Validation Tools: infoway_release_2_2X_18.zip \[INFO2009\]](#)

2.2 Australian Digital Health Agency CDA extensions

As part of the CDA, standard extensions are allowed as follows:

Locally-defined markup may be used when local semantics have no corresponding representation in the CDA specification. CDA seeks to standardize the highest level of shared meaning while providing a clean and standard mechanism for tagging meaning that is not shared. In order to support local extensibility requirements, it is permitted to include additional XML elements and attributes that are not included in the CDA schema. These extensions should not change the meaning of any of the standard data items, and receivers must be able to safely ignore these elements. Document recipients must be able to faithfully render the CDA document while ignoring extensions.

Extensions may be included in the instance in a namespace other than the HL7v3 namespace, but must not be included within an element of type ED (e.g., <text> within <procedure>) since the contents of an ED datatype within the conformant document may be in a different namespace. Since all conformant content (outside of elements of type ED) is in the HL7 namespace, the sender can put any extension content into a foreign namespace (any namespace other than the HL7 namespace). Receiving systems must not report an error if such extensions are present. [HL7 Clinical Document Architecture \[HL7CDAR2\]](#)

A number of extensions to CDA have been defined in this implementation guide. To maintain consistency, the same development paradigm has been used as CDA.

These Australian Digital Health Agency CDA extensions have been added to the Australian Digital Health Agency CDA schema and are incorporated in the namespace <http://ns.electronichealth.net.au/Ci/Cda/Extensions/3.0> as shown in [Appendix B, Examples](#). Future versions of CDA extensions will be versioned as per the following example:

<http://ns.electronichealth.net.au/Ci/Cda/Extensions/4.0>

The Australian Digital Health Agency CDA schema therefore differs from the base HL7 CDA W3C XML Schema (referred to in this document as the HL7 CDA Schema). CDA documents which include extensions will fail to validate against the HL7 CDA Schema – this is a known limitation.

An Advance Care Directive Custodian Record document that conforms to this specification will validate against the Australian Digital Health Agency CDA schema that accompanies this specification, and will validate against the HL7 CDA Schema once the extensions have been removed. Note that merely passing schema validation does not ensure conformance. For more information, refer to [Conformance requirements](#).

2.3 Conformance conventions

Templates

This implementation guide specifies the CDA templates for implementing the document model that is the subject of this implementation guide, i.e. Advance Care Directive Custodian Record.
A CDA template is a set of constraints, and where necessary, custom extensions to [HL7 Clinical Document Architecture \[HL7CDAR2\]](#).

In this implementation guide CDA templates are presented in a CDA mapping table and indicated by the presence of a `templateId`.

Template identifiers (`templateId`) are unique to each CDA template. When valued in an instance, the template identifier signals the imposition of a set of template-defined constraints. The root value of this attribute (e.g. `@root="1.2.36.1.2001.1001.1002.226"`) provides a unique identifier for the template in question. The extension value of this attribute (e.g. `@extension="1.0"`) provides the version identifier for the template in question.

Open and closed templates

A CDA template may be either an open template or a closed template. In an open template all of the features of the CDA R2 base specification [HL7 V3 RIM, Data types and Vocabulary \[HL7V3DT\]](#) are allowed except as constrained by explicitly specified constraints. In a closed template everything that is allowed must be explicitly specified and nothing further may be allowed.

For example if a specification of a CDA template says nothing about the use of the `id` element:

- In an open template context this means that `id` is allowed as specified in the schema
- In a closed template context this means that no use of `id` is allowed

The template context in this implementation guide is that of an open template unless otherwise stated.

Terminology binding

Vocabulary is specified in this implementation guide, in some cases binding an element to a value set or binding an attribute to a single fixed code. For guidance on coding common clinical concepts in CDA documents see [Representing Coding in CDA Documents Implementation Guidance \[NEHT2011bv\]](#).

A value set binding, if present in this specification, will be specified in the "Constraints and comments" column of a CDA mapping table as the title of the value set (hyperlinked to its definition) followed by identification of the binding strength (hyperlinked to its definition), e.g. [v3 Code System ParticipationFunction \(required\)](#).

Conformance verbs

Where used in this document, the keywords **SHALL**, **SHOULD**, **MAY**, **SHALL NOT** and **SHOULD NOT** from [Key Words for Use in RFCs to Indicate Requirement Levels \[RFC2119\]](#) are to be interpreted as described in the table below.

Conformance verbs

| Conformance verb | Interpretation |
|------------------|---|
| SHALL | <p>An absolute requirement.</p> <p>Where SHALL appears in any conformance constraint it indicates a mandatory requirement.</p> <p>Where SHALL is applied to the occurrences of an element or attribute then that element or attribute must be present but can be null if the value is not known and the value has not been constrained to not allow a null value.</p> |
| SHOULD | <p>A requirement that is considered best practice or recommendation for inclusion. There may be valid reasons to ignore an item, but the full implications must be understood and carefully weighed before choosing a different course.</p> <p>Where SHOULD appears in an conformance constraint that constrains the allowed occurrences of an item it indicates that the item may not be present but does not override the upper bound of the cardinality range.</p> <p>For a sending application where SHOULD is applied to the occurrences of an item then that item must be present if a sending application has the data for that data element. If the value is not known the element or attribute does not need to be included.</p> <p>Implementers must support an optional requirement.</p> |
| MAY | <p>A requirement that can be included or omitted as the author decides with no implications.</p> <p>Where MAY appears in a conformance constraint that constrains the allowed occurrences of an item it indicates that the item may not be present but does not override the upper bound of the cardinality range.</p> <p>Implementers must support an optional requirement.</p> |
| SHALL NOT | <p>An absolute prohibition.</p> <p>Where SHALL NOT appears in any conformance constraint it indicates a mandatory prohibition requirement.</p> |

| Conformance verb | Interpretation |
|-------------------|---|
| SHOULD NOT | A requirement that is considered best practice or recommendation for against inclusion. There may be valid reasons to ignore an item, but the full implications must be understood and carefully weighed before choosing a different course. Where SHOULD NOT appears in a conformance constraint that constrains the allowed occurrences of an item it indicates that the item may not be present but does not override the upper bound of the cardinality range. For a sending application where SHOULD NOT is applied to the occurrences of then that element or attribute must be present if a sending application has the data for that data element. If the value is not known the element or attribute does not need to be included. Implementers must support an optional requirement. |

Cardinality

The cardinality range specifies the allowable occurrences within a document instance. Cardinality range is specified in the format "m..n" where m is the minimum allowed members of the set (lower bound) and n is the maximum allowed members of the set (upper bound). The allowed values for m and n are 0, any positive integer, and *.

The table below demonstrates a representative set of examples of cardinality range and how to interpret that cardinality range; p is positive integer greater than the minimum allowed members of the set.

| Cardinality range | Interpretation |
|-------------------|----------------------------------|
| 0..0 | zero (explicitly prohibited) |
| 0..1 | zero or one |
| 1..1 | exactly one |
| 0..* | zero or more |
| 1..* | at least one |
| 2..* | at least two |
| 1..p | at least one and not more than p |
| 2..p | at least two and not more than p |

2.4 Mapping presentation and structure

The content of this implementation guide is a set of CDA templates that are presented as a mapping from the logical view of a set of models (i.e. [FHIR \[HL7FHIR3\]](#) StructureDefinitions) to CDA. These models are published as [FHIR \[HL7FHIR3\]](#) profiles in [Advance Care Records FHIR Implementation Guide \[DH2019e\]](#).

CDA templates are located within a templates chapter, e.g. [9 Section CDA templates](#). The heading for each child section identifies the CDA schema element that is templated, and may also identify the name of part of the ACDCR model that template corresponds to, e.g. observation (Summary Statement of Allergy or Intolerance) defines the CDA template of the observation CDA schema element to represent the model for Summary Statement of Allergy or Intolerance.

A CDA mapping table aims to take implementers step by step through mapping each element of the ACDCR model to a corresponding CDA attribute or element. The following section describes in more detail the fields used to present the mapping content in this implementation guide.

x.x CDA schema element (model / element)

Implementation guidance specific to the usage scenarios expected to be supported by this implementation guide may be present above the mapping table. This content is informative; there may be valid reasons not to follow this guidance, but the full implications must be understood and carefully weighed before choosing a different course.

CDA mapping

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|---|--|--|--|---|---|
| CDA conformance level, e.g. CDA Header, CDA Body Level 3 Data Elements | | | | | |
| The logical hierarchical path in the ACDCR model expressed using names of the elements in the ACDCR model. If there is a name in round brackets after the path, this is the label for that element or resource. The text in bold (the last in the path) is the subject for this row. i.e. Parent (Label) > Child e.g. AllergyIntolerance (Summary Statement of Allergy or Intolerance) > patient | The description of the element in the ACDCR model. (See Conformance conventions) | The cardinality of the element in the ACDCR model. (See Conformance conventions) | The type of the element (hyper-linked to the definition of the [HL7FHIR3] type) in the ACDCR model. This may be expressed as a type that is further constrained by a model in the convention <type> as <model name>, e.g. Patient as Patient with Mandatory Identifier. | Context: The root context that is applied as a prefix to the CDA schema element paths in the mapping rows below The CDA schema element(s) in the CDA template that correspond to the model element. The syntax for this is similar to XPath: {/name{[index]}}n Where: <ul style="list-style-type: none">{ } indicates optional{ }n means a section that may repeat[index] differentiates two similar mappings Example: participant[location] participant[location]/@typeCode="ORG" participant[location]/associatedEntity participant[location]/associatedEntity/@classCode="SDLOC" participant[location]/associatedEntity/code A sequence of names refers to the XML path in the CDA document. The path always starts from the context as defined in the grey header row above each group of mapping rows. The last name is shown in bold to make the path easier to read. The last name may be a reference to an attribute or an element, as defined in the Australian Digital Health Agency CDA schema. An index after the name, such as "participation[location]" implies that there can be two or more templates of a participation CDA schema element or that the CDA schema element name may be repeated in one or more templates. The indexes differentiate which CDA schema element is referenced in the path. It is possible for one model element to map to more than one CDA schema element. | Constraints on the CDA schema element(s). Terminology binding, identified by a hyperlinked value set title followed by the terminology binding strength (hyperlinked to the definition of the binding strength). When applicable, followed by a reference to a footnote that provides a hyperlink to related concept map. e.g. Address Type HL7 v3 (required) ¹ Additional information about the mapping and/or constraints which are identified by conformance verbs (See Conformance conventions). e.g. See < code > for available attributes. |

¹Note: The source terminology binding on address type[\[DH2019e\]](#) and the terminology binding in the representation of the model in this specification are different. Mappings between the set of concepts are defined in [v3 map for AddressType](#) concept map.

3 Conformance

3.1 Conformance requirements

This document describes how the ACDCR model is implemented as a CDA document. Conformance claims are not made against this implementation guide directly; rather, they are made against additional conformance profiles documented elsewhere. Any document that claims conformance to any derived conformance profile **SHALL** meet these base requirements:

- It **SHALL** be a valid HL7 CDA instance. In particular:
 - It **SHALL** be valid against the HL7 CDA schema (once extensions have been removed).
 - It **SHALL** conform to the HL7 V3 R1 data type specification.
 - It **SHALL** conform to the semantics of the RIM and Structural Vocabulary.
- It **SHALL** be valid against the Australian Digital Health Agency CDA schema that accompanies this implementation guide after any additional extensions not in the Australian Digital Health Agency extension namespace have been removed, along with any other CDA content not described by this implementation guide.
- It **SHALL** use the mappings as they are stated in this document.
- It **SHALL** use all fixed values specified in the mappings (e.g. @attribute="FIXED_VALUE").
- It **SHALL** be valid against the additional conformance requirements that are established in this document (i.e. any normative use of the word 'shall' identified by the term presented in uppercase and bold typeface).
- The narrative **SHALL** conform to the requirements described in this implementation guide.
- The document **SHALL** conform to the requirements specified in the CDA Rendering Specification [\[NEHT2012s\]](#).
- Any additional content included in the CDA document that is not described by this implementation guide **SHALL NOT** qualify or negate content described by this implementation guide and it **SHALL** be clinically safe for receivers of the document to ignore the non-narrative additions when interpreting the existing content.

A system that *consumes* ACDCR CDA documents may claim conformance if it correctly processes conformant instance documents, including correctly understanding all the information in the header. It may, but is not required to, reject non-conformant documents. Conformant systems that consume ACDCR CDA documents are not required to process any or all of the structured data entries in the CDA document, but they **SHALL** be able to correctly render the document for end-users when appropriate (see [Clinical Document Architecture Release 2](#)).

Conformance profiles of this document **MAY** make additional rules that override this document in regard to:

- Allowing the use of alternative value sets in place of the value sets specified in this document.
- Allowing the use of alternative identifiers in place of the Healthcare Identifiers Service identifiers.
- Making required data elements and section divisions optional.

3.2 CDA narratives

CDA requires that each section in its body include a narrative block, containing a clinically complete version of the section's encoded content using custom hypertext markup defined by HL7. The narrative is the human-readable and attestable part of a CDA document, and can stand alone as an accurate representation of the content of the document without any need to consult entries in the body.

It is a [HL7 Clinical Document Architecture \[HL7CDAR2\]](#) requirement that all clinical information **SHALL** be marked up in CDA narratives.

It is a [HL7 Clinical Document Architecture \[HL7CDAR2\]](#) requirement that the rendered narrative **SHALL** be able to stand alone as a source of authenticated information for consuming parties. Content from the CDA body **SHALL NOT** be omitted from the narrative.

There is no canonical markup for specific CDA components, but some conformance requirements apply:

- The narrative block **SHALL** be encapsulated within the text component of the CDA section.
- The narrative contents **SHALL** conform to the requirements specified in the CDA Rendering Specification.
 - In accordance with the requirement to completely represent section contents, elements of type [CodeableConcept](#) **SHALL** include an originalText or a displayName attribute (or both). Where available, the originalText **SHOULD** be found in the narrative, otherwise the displayName **SHOULD** be found in the narrative.
- The narrative contents **SHALL** completely and accurately represent the clinical information encoded in the section. Content **SHALL NOT** be omitted from the narrative.
- The narrative **SHALL** conform to the content requirements of the CDA specification [\[HL7CDAR2\]](#) and the XML schema.

Clinical judgement is required to determine the appropriate presentation for narrative. We may release additional guidance in this regard. The examples provided in sections of this document offer some guidance for narrative block markup and may be easily adapted as boilerplate markup.

4 Advance Care Directive Custodian Record hierarchy

An advance care directive custodian record document is defined as:

A record of the custodians of an individual's advance care directive. [Advance Care Records FHIR Implementation Guide \[DH2019e\]](#)

4.1 Hierarchy

The hierarchy below provides a logical view of the Advance Care Directive Custodian Record model as a tree structure in a hierarchical table; it is not intended to represent how the data contents are represented in a CDA document.

Each row contains information about a single element. The top level row contains two occupied cells: Name of the document model, and the Type (hyperlinked to the definition of the type).

Each following row contains three occupied cells: Name of the child element in the model, Cardinality (the lower and upper bounds on how many times this element is allowed to appear in the resource), and the Type (hyperlinked to the definition of the type). Type may be expressed as a type that is further constrained by a referenced model, e.g. Patient as Base Patient.

| Name | Cardinality | Type |
|---|-------------|---|
| Composition (Advance Care Directive Custodian Record) | | DomainResource |
| composition-author-role | 0..1 | Reference(PractitionerRole as PractitionerRole with Practitioner with Mandatory Identifier) |
| identifier | 0..1 | Identifier |
| status | 1..1 | code |
| type | 1..1 | CodeableConcept |
| subject | 1..1 | Reference(Patient as Patient with Mandatory Identifier) |
| date | 1..1 | dateTime |
| author | 1..1 | Reference(RelatedPerson as RelatedPerson with Mandatory Identifier Patient as Patient with Mandatory Identifier Practitioner as Practitioner with Mandatory Identifier) |
| title | 1..1 | string |
| attester (Legal Attester) | 0..1 | BackboneElement |
| mode | 1..1 | code |
| time | 1..1 | dateTime |
| party | 0..1 | Reference(Patient as Patient with Mandatory Identifier Practitioner as Practitioner with Mandatory Identifier) |
| attester-related-party | 0..1 | Reference(RelatedPerson as RelatedPerson with Mandatory Identifier) |
| custodian | 1..1 | Reference(Organization as Organization with Mandatory Identifier) |
| section (Advance Care Directive Custodians) | 1..1 | BackboneElement |
| title | 1..1 | string |
| code | 1..1 | CodeableConcept |
| text | 1..1 | Narrative |
| entry (Advance Care Directive Custodian Entry) | 1..* | Reference(Practitioner as Base Practitioner Patient as Base Patient RelatedPerson as Base RelatedPerson Organization as Base Organization) |

4.2 Expanded hierarchy

The hierarchy below provides an expanded logical view of the Advance Care Directive Custodian Record model as a tree structure in a hierarchical table that includes the structure of the first level of referenced models; it is not intended to represent how the data contents are represented in a CDA document.

Each row contains information about a single element. The top level row contains two occupied cells: Name of the document model, and the Type (hyperlinked to the definition of the type).

Each following row contains three occupied cells: Name of the child element in the model, Cardinality (the lower and upper bounds on how many times this element is allowed to appear in the resource), and the Type (hyperlinked to the definition of the type). Type may be expressed as a type that is further constrained by a referenced model, e.g. Patient as Base Patient.

| Name | | Cardinality | Type |
|---|------------------------------|-------------|---|
| Composition (Advance Care Directive Custodian Record) | | | DomainResource |
| | composition-author-role | 0..1 | Reference(PractitionerRole as PractitionerRole with Practitioner with Mandatory Identifier) |
| | identifier | 0..* | Identifier |
| | active | 0..1 | boolean |
| | period | 0..1 | Period |
| | practitioner | 1..1 | Reference(Practitioner as Practitioner with Mandatory Identifier) |
| | organization | 0..1 | Reference(Organization as Base Organization) |
| | code | 0..* | CodeableConcept |
| | specialty | 0..* | CodeableConcept |
| | location | 0..* | Reference(Location) |
| | healthcareService | 0..* | Reference(HealthcareService) |
| | telecom | 0..* | ContactPoint |
| | availableTime | 0..* | BackboneElement |
| | daysOfWeek | 0..* | code |
| | allDay | 0..1 | boolean |
| | availableStartTime | 0..1 | time |
| | availableEndTime | 0..1 | time |
| | notAvailable | 0..* | BackboneElement |
| | description | 1..1 | string |
| | during | 0..1 | Period |
| | availabilityExceptions | 0..1 | string |
| | identifier | 0..1 | Identifier |
| | status | 1..1 | code |
| | type | 1..1 | CodeableConcept |
| | subject | 1..1 | Reference(Patient as Patient with Mandatory Identifier) |
| | birthPlace | 0..1 | Address |
| | indigenous-status | 0..1 | Coding |
| | closing-the-gap-registration | 0..1 | boolean |
| | patient-mothersMaidenName | 0..1 | string |
| | identifier | 1..* | Identifier |
| | active | 0..1 | boolean |
| | name | 0..* | HumanName |
| | telecom | 0..* | ContactPoint |
| | gender | 0..1 | code |

| Name | | | Cardinality | Type |
|--------|------------------------------|-------------------------|-------------|--|
| | birthDate | | 0..1 | date |
| | | date-accuracy-indicator | 0..1 | Coding |
| | | birthTime | 0..1 | dateTime |
| | deceased[x] | | 0..1 | boolean dateTime |
| | | date-accuracy-indicator | 0..1 | Coding |
| | address | | 0..* | Address |
| | maritalStatus | | 0..1 | CodeableConcept |
| | multipleBirth[x] | | 0..1 | boolean integer |
| | contact | | 0..* | BackboneElement |
| | | relationship | 0..* | CodeableConcept |
| | | name | 0..1 | HumanName |
| | | telecom | 0..* | ContactPoint |
| | | address | 0..1 | Address |
| | | gender | 0..1 | code |
| | | organization | 0..1 | Reference(Organization as Base Organization) |
| | | period | 0..1 | Period |
| | communication | | 0..* | BackboneElement |
| | | communication.language | 1..1 | CodeableConcept |
| | | communication.preferred | 0..1 | boolean |
| | generalPractitioner | | 0..* | Reference(Practitioner as Base Practitioner Organization as Base Organization) |
| | managingOrganization | | 0..1 | Reference(Organization as Base Organization) |
| date | | | 1..1 | dateTime |
| author | | | 1..1 | Reference(Patient as Patient with Mandatory Identifier) |
| | birthPlace | | 0..1 | Address |
| | indigenous-status | | 0..1 | Coding |
| | closing-the-gap-registration | | 0..1 | boolean |
| | patient-mothersMaidenName | | 0..1 | string |
| | identifier | | 1..* | Identifier |
| | active | | 0..1 | boolean |
| | name | | 0..* | HumanName |
| | telecom | | 0..* | ContactPoint |
| | gender | | 0..1 | code |
| | birthDate | | 0..1 | date |
| | | date-accuracy-indicator | 0..1 | Coding |
| | | birthTime | 0..1 | dateTime |
| | deceased[x] | | 0..1 | boolean dateTime |
| | | date-accuracy-indicator | 0..1 | Coding |
| | address | | 0..* | Address |
| | maritalStatus | | 0..1 | CodeableConcept |
| | multipleBirth[x] | | 0..1 | boolean integer |
| | contact | | 0..* | BackboneElement |
| | | relationship | 0..* | CodeableConcept |
| | | name | 0..1 | HumanName |
| | | telecom | 0..* | ContactPoint |
| | | address | 0..1 | Address |
| | | gender | 0..1 | code |

| Name | | | | Cardinality | Type |
|------|---------------------------|----------------------|------------------------------|-------------|--|
| | | organization | | 0..1 | Reference(Organization as Base Organization) |
| | | period | | 0..1 | Period |
| | | communication | | 0..* | BackboneElement |
| | | language | | 1..1 | CodeableConcept |
| | | preferred | | 0..1 | boolean |
| | | generalPractitioner | | 0..* | Reference(Practitioner as Base Practitioner Organization as Base Organization) |
| | | managingOrganization | | 0..1 | Reference(Organization as Base Organization) |
| | author | | | 1..1 | Reference(RelatedPerson as RelatedPerson with Mandatory Identifier) |
| | | identifier | | 0..* | Identifier |
| | | active | | 0..1 | boolean |
| | | patient | | 1..1 | Reference(Patient as Base Patient) |
| | | relationship | | 0..1 | CodeableConcept |
| | | name | | 0..* | HumanName |
| | | telecom | | 0..* | ContactPoint |
| | | gender | | 0..1 | code |
| | | birthDate | | 0..1 | date |
| | | address | | 0..* | Address |
| | | period | | 0..1 | Period |
| | author | | | 0..1 | Reference(Practitioner as Practitioner with Mandatory Identifier) |
| | | identifier | | 1..* | Identifier |
| | | active | | 0..1 | boolean |
| | | name | | 0..* | HumanName |
| | | telecom | | 0..* | ContactPoint |
| | | address | | 0..* | Address |
| | | gender | | 0..1 | code |
| | | birthDate | | 0..1 | date |
| | | qualification | | 0..* | BackboneElement |
| | | | identifier | 0..* | Identifier |
| | | | code | 1..1 | CodeableConcept |
| | | | period | 0..1 | Period |
| | | | issuer | 0..1 | Reference(Organization as Base Organization) |
| | | | communication | 0..* | CodeableConcept |
| | title | | | 1..1 | string |
| | attester (Legal Attester) | | | 1..1 | BackboneElement |
| | | mode | | 1..1 | code |
| | | time | | 1..1 | dateTime |
| | | party | | 0..1 | Reference(Patient as Patient with Mandatory Identifier) |
| | | | birthPlace | 0..1 | Address |
| | | | indigenous-status | 0..1 | Coding |
| | | | closing-the-gap-registration | 0..1 | boolean |
| | | | patient-mothersMaidenName | 0..1 | string |
| | | | identifier | 1..* | Identifier |
| | | | active | 0..1 | boolean |
| | | | name | 0..* | HumanName |
| | | | telecom | 0..* | ContactPoint |

| Name | Cardinality | | Type |
|-------|------------------------|------|--|
| | | 0..1 | code |
| | | 0..1 | date |
| | | 0..1 | Coding |
| | | 0..1 | dateTime |
| | deceased[x] | 0..1 | boolean dateTime |
| | | 0..1 | Coding |
| | address | 0..* | Address |
| | maritalStatus | 0..1 | CodeableConcept |
| | multipleBirth[x] | 0..1 | boolean integer |
| | contact | 0..* | BackboneElement |
| | | 0..* | CodeableConcept |
| | | 0..1 | HumanName |
| | telecom | 0..* | ContactPoint |
| | | 0..1 | Address |
| | | 0..1 | code |
| | | 0..1 | Reference(Organization as Base Organization) |
| | | 0..1 | Period |
| | communication | 0..* | BackboneElement |
| | | 1..1 | CodeableConcept |
| | | 0..1 | boolean |
| | generalPractitioner | 0..* | Reference(Practitioner as Base Practitioner Organization as Base Organization) |
| | managingOrganization | 0..1 | Reference(Organization as Base Organization) |
| party | | 0..1 | Reference(Practitioner as Practitioner with Mandatory Identifier) |
| | identifier | 1..* | Identifier |
| | active | 0..1 | boolean |
| | name | 0..* | HumanName |
| | telecom | 0..* | ContactPoint |
| | address | 0..* | Address |
| | gender | 0..1 | code |
| | birthDate | 0..1 | date |
| | qualification | 0..* | BackboneElement |
| | | 0..* | Identifier |
| | | 1..1 | CodeableConcept |
| | | 0..1 | Period |
| | issuer | 0..1 | Reference(Organization as Base Organization) |
| | communication | 0..* | CodeableConcept |
| | attester-related-party | 0..1 | Reference(RelatedPerson as RelatedPerson with Mandatory Identifier) |
| | identifier | 0..* | Identifier |
| | active | 0..1 | boolean |
| | patient | 1..1 | Reference(Patient as Base Patient) |
| | relationship | 0..1 | CodeableConcept |
| | name | 0..* | HumanName |
| | telecom | 0..* | ContactPoint |
| | gender | 0..1 | code |
| | birthDate | 0..1 | date |

| Name | | | | | Cardinality | Type |
|------|---|--|------------------------------|-------------------------|-------------|---|
| | | address | | 0..* | | Address |
| | | period | | 0..1 | | Period |
| | custodian | | | | 1..1 | Reference(Organization as Organization with Mandatory Identifier) |
| | | identifier | | | 1..* | Identifier |
| | | active | | | 0..1 | boolean |
| | | type | | | 0..* | CodeableConcept |
| | | name | | | 0..1 | string |
| | | alias | | | 0..* | string |
| | | telecom | | | 0..* | ContactPoint |
| | | address | | | 0..* | Address |
| | | partOf | | | 0..1 | Reference(Organization as Base Organization) |
| | | contact | | | 0..* | BackboneElement |
| | | | purpose | | 0..1 | CodeableConcept |
| | | | name | | 0..1 | HumanName |
| | | | telecom | | 0..* | ContactPoint |
| | | | address | | 0..1 | Address |
| | section (Advance Care Directive Custodians) | | | | 1..1 | BackboneElement |
| | | title | | | 1..1 | string |
| | | code | | | 1..1 | CodeableConcept |
| | | text | | | 1..1 | Narrative |
| | | entry (Advance Care Directive Custodian Entry) | | | 1..* | Reference(Practitioner as Base Practitioner) |
| | | | identifier | | 1..* | Identifier |
| | | | active | | 0..1 | boolean |
| | | | name | | 0..* | HumanName |
| | | | telecom | | 0..* | ContactPoint |
| | | | address | | 0..* | Address |
| | | | gender | | 0..1 | code |
| | | | birthDate | | 0..1 | date |
| | | | qualification | | 0..* | BackboneElement |
| | | | | identifier | 0..* | Identifier |
| | | | | code | 1..1 | CodeableConcept |
| | | | | period | 0..1 | Period |
| | | | | issuer | 0..1 | Reference(Organization as Base Organization) |
| | | | communication | | 0..* | CodeableConcept |
| | | entry (Advance Care Directive Custodian Entry) | | | 1..* | Reference(Patient as Base Patient) |
| | | | birthPlace | | 0..1 | Address |
| | | | indigenous-status | | 0..1 | Coding |
| | | | closing-the-gap-registration | | 0..1 | boolean |
| | | | patient-mothersMaidenName | | 0..1 | string |
| | | | identifier | | 1..* | Identifier |
| | | | active | | 0..1 | boolean |
| | | | name | | 0..* | HumanName |
| | | | telecom | | 0..* | ContactPoint |
| | | | gender | | 0..1 | code |
| | | | birthDate | | 0..1 | date |
| | | | | date-accuracy-indicator | 0..1 | Coding |

| Name | Cardinality | Type |
|--|-------------|--|
| | 0..1 | dateTime |
| deceased[x] | 0..1 | boolean dateTime |
| | 0..1 | Coding |
| address | 0..* | Address |
| maritalStatus | 0..1 | CodeableConcept |
| multipleBirth[x] | 0..1 | boolean integer |
| contact | 0..* | BackboneElement |
| | 0..* | CodeableConcept |
| | 0..1 | HumanName |
| telecom | 0..* | ContactPoint |
| | 0..1 | Address |
| | 0..1 | code |
| | 0..1 | Reference(Organization) as Base Organization |
| | 0..1 | Period |
| | 0..* | BackboneElement |
| | 1..1 | CodeableConcept |
| | 0..1 | boolean |
| generalPractitioner | 0..* | Reference(Practitioner) as Base Practitioner Organization as Base Organization |
| managingOrganization | 0..1 | Reference(Organization) as Base Organization |
| entry (Advance Care Directive Custodian Entry) | 1..* | Reference(RelatedPerson) as Base RelatedPerson |
| identifier | 0..* | Identifier |
| active | 0..1 | boolean |
| patient | 1..1 | Reference(Patient) as Base Patient |
| relationship | 0..1 | CodeableConcept |
| name | 0..* | HumanName |
| telecom | 0..* | ContactPoint |
| gender | 0..1 | code |
| birthDate | 0..1 | date |
| address | 0..* | Address |
| period | 0..1 | Period |
| entry (Advance Care Directive Custodian Entry) | 1..* | Reference(Organization) as Base Organization |
| identifier | 1..* | Identifier |
| active | 0..1 | boolean |
| type | 0..* | CodeableConcept |
| name | 0..1 | string |
| alias | 0..* | string |
| telecom | 0..* | ContactPoint |
| address | 0..* | Address |
| partOf | 0..1 | Reference(Organization) as Base Organization |
| contact | 0..* | BackboneElement |
| | 0..1 | CodeableConcept |
| | 0..1 | HumanName |
| | 0..* | ContactPoint |
| | 0..1 | Address |

DRAFT

5 CDA Header templates

This chapter contains the CDA Header requirements for this implementation guide; these are infrastructure or control requirements that are not sourced from the Advance Care Directive Custodian Record model.

All the definitions in this chapter are sourced from HL7 Clinical Document Architecture, Release 2 [\[HL7CDAR2\]](#).

5.1 ClinicalDocument

CDA mapping

| CDA schema element | Definition | Card | Constraints and comments |
|---|---|------|--|
| CDA Header Data Elements | Context: / | | |
| ClinicalDocument | The ClinicalDocument class is the entry point into the CDA R-MIM, and corresponds to the <ClinicalDocument> XML element that is the root element of a CDA document. | 1..1 | <p>This template SHALL be a closed template.</p> <p>All attributes of the ClinicalDocument element defined by the Australian Digital Health Agency CDA schema SHALL be allowed.</p> <p>The CDA document SHALL be valid against the Australian Digital Health Agency CDA schema after any additional extensions not in the Australian Digital Health Agency extension namespace have been removed.</p> |
| ClinicalDocument/realmCode | A realmCode signals the imposition of realm-specific constraints. The value identifies the realm in question. | 0..* | All attributes of the //realmCode element defined by the Australian Digital Health Agency CDA schema SHALL be allowed. |
| ClinicalDocument/typeId | A technology-neutral explicit reference to the CDA Release 2 specification. | 1..1 | |
| ClinicalDocument/typeId/@extension="POCD_HD000040" | | 1..1 | The unique identifier for the CDA Release 2 Hierarchical Description. |
| ClinicalDocument/typeId/@root="2.16.840.1.113883.1.3" | | 1..1 | The OID for HL7 Registered models. |

| CDA schema element | Definition | Card | Constraints and comments |
|---|---|------|--|
| ClinicalDocument/templateId | A templateId signals the imposition of a set of template-defined constraints. The value provides a unique identifier for the templates in question. | 1..* | <p>All attributes of the //templateId element defined by the Australian Digital Health Agency CDA schema SHALL be allowed.</p> <p>Exactly one template identifier SHALL indicate the constraints defined in this mapping table and have @root="1.2.36.1.2001.1001.102.101.100033" and @extension="1.0".</p> <p>Exactly one template identifier SHALL indicate the constraints defined in the CDA Rendering Specification [NEHT2012s] and have @root="1.2.36.1.2001.1001.100.226" and @extension="1.0".</p> <p>In addition to the template identifiers above, a template identifier is expected for the clinical document model as per Composition (Advance Care Directive Custodian Record). Additional template identifiers may be required by other specifications.</p> <p>Systems are not required to recognise any other template identifiers than the clinical document model templateId in order to understand the document as a [type] but these identifiers may influence how the document must be handled.</p> |
| ClinicalDocument/id | Represents the unique instance identifier of a clinical document. | 1..1 | <p>All attributes of the //id element defined by the Australian Digital Health Agency CDA schema SHALL be allowed with the exception that @nullFlavor SHALL NOT be present.</p> <p>See <id> for available attributes.</p> |
| ClinicalDocument/effectiveTime | Signifies the document creation time, when the document first came into being. Where the CDA document is a transform from an original document in some other format, the ClinicalDocument.effectiveTime is the time the original document is created. | 1..1 | <p>All attributes of the //effectiveTime element defined by the Australian Digital Health Agency CDA schema SHALL be allowed with the exception that @nullFlavor SHALL NOT be present.</p> <p>See <time> for available attributes.</p> |
| ClinicalDocument/confidentialityCode/@nullFlavor="NA" | Codes that identify how sensitive a piece of information is and/or that indicate how the information may be made available or disclosed. | 1..1 | |
| ClinicalDocument/languageCode | Specifies the human language of character data (whether they be in contents or attribute values). | 0..1 | |
| ClinicalDocument/languageCode/@code | | 1..1 | <p><Language Code> – <DIALECT> The <Language Code> SHALL be "en". The <DIALECT> SHOULD be "AU".</p> |
| ClinicalDocument/setId | Represents an identifier that is common across all document revisions. | 0..1 | <p>All attributes of the //setId element defined by the Australian Digital Health Agency CDA schema SHALL be allowed.</p> <p>See <id> for available attributes.</p> |
| ClinicalDocument/versionNumber | An integer value used to version successive replacement documents. | 0..1 | |
| ClinicalDocument/versionNumber/@value | | 1..1 | |
| ClinicalDocument/ext:completionCode | The lifecycle status of a document. | 1..1 | <p>All attributes of the //completionCode element defined by the Australian Digital Health Agency CDA schema SHALL be allowed with the exception that @nullFlavor SHALL NOT be present.</p> <p>See <code> for available attributes.</p> <p>Australian Healthcare Clinical Document Architecture Document Lifecycle Status (required)</p> |
| ClinicalDocument/recordTarget | Represents the medical record that this document belongs to. | 1..1 | All attributes and elements of the //recordTarget element defined by the Australian Digital Health Agency CDA schema SHALL be allowed. |

| CDA schema element | Definition | Card | Constraints and comments |
|---------------------------------------|---|------|---|
| ClinicalDocument/author | Represents the humans and/or machines that authored the document. | 1..1 | All attributes and elements of the //author element defined by the Australian Digital Health Agency CDA schema SHALL be allowed. |
| ClinicalDocument/dataEnterer | Represents the participant who has transformed a dictated note into text. | 0..1 | All attributes and elements of the //dataEnterer element defined by the Australian Digital Health Agency CDA schema SHALL be allowed. |
| ClinicalDocument/informant | Represents an informant (or source of information) who provides relevant information, such as the parent of a comatose patient who describes the patient's behavior prior to the onset of coma. Unless otherwise stated, the patient is implicitly the informant. | 0..* | All attributes and elements of the //informant element defined by the Australian Digital Health Agency CDA schema SHALL be allowed. |
| ClinicalDocument/custodian | Represents the organization from which the document originates and that is in charge of maintaining the document. The custodian is the steward that is entrusted with the care of the document. Every CDA document has exactly one custodian. | 1..1 | All attributes and elements of the //custodian element defined by the Australian Digital Health Agency CDA schema SHALL be allowed. |
| ClinicalDocument/informationRecipient | Represents a recipient who should receive a copy of the document. | 0..* | All attributes and elements of the //informationRecipient element defined by the Australian Digital Health Agency CDA schema SHALL be allowed. |
| ClinicalDocument/legalAuthenticator | Represents a participant who has legally authenticated the document. | 0..1 | All attributes and elements of the //legalAuthenticator element defined by the Australian Digital Health Agency CDA schema SHALL be allowed. |
| ClinicalDocument/authenticator | Represents a participant who has attested to the accuracy of the document, but who does not have privileges to legally authenticate the document. An example would be a resident physician who sees a patient and dictates a note, then later signs it. | 0..* | All attributes and elements of the //authenticator element defined by the Australian Digital Health Agency CDA schema SHALL be allowed. |
| ClinicalDocument/participant | Represents a participant not explicitly mentioned by other classes that was somehow involved. | 0..* | All attributes and elements of the //participant element defined by the Australian Digital Health Agency CDA schema SHALL be allowed. |
| ClinicalDocument/inFulfillmentOf | Relates the current document to an order this document fulfills (in whole or in part). | 0..* | All attributes and elements of the //inFulfillmentOf element defined by the Australian Digital Health Agency CDA schema SHALL be allowed. |
| ClinicalDocument/documentationOf | Relates the current document to the related event that this document is documentation of. | 0..* | All attributes and elements of the //documentationOf element defined by the Australian Digital Health Agency CDA schema SHALL be allowed. |
| ClinicalDocument/relatedDocument | Relates the current document to a parent document. | 0..* | All attributes and elements of the //relatedDocument element defined by the Australian Digital Health Agency CDA schema SHALL be allowed. |
| ClinicalDocument/authorization | Relates the current document to consents associated with this document. The consent authorizes or certifies acts specified in the current document. | 0..* | All attributes and elements of the //authorization element defined by the Australian Digital Health Agency CDA schema SHALL be allowed. |
| ClinicalDocument/componentOf | Relates the current document to the encounter. The current document is a documentation of events that occurred during the encounter. | 0..1 | All attributes and elements of the //componentOf element defined by the Australian Digital Health Agency CDA schema SHALL be allowed. |
| ClinicalDocument/component | Relates the associated document body as a component of the document. | 1..1 | All attributes and elements of the //component element defined by the Australian Digital Health Agency CDA schema SHALL be allowed. |

5.2 LegalAuthenticator

CDA mapping

| CDA schema element | Definition | Card | Constraints and comments |
|--|--|------|---|
| CDA Header Data Elements | | | Context: /ClinicalDocument/ |
| legalAuthenticator/templateId | The use of templateId signals the imposition of a set of template-defined constraints. | 1..1 | |
| legalAuthenticator/templateId/@root="1.2.36.1.2001.1001.102.101.100012" | | 1..1 | |
| legalAuthenticator/templateId/@extension="1.0" | | 1..1 | |
| legalAuthenticator/time/@value | Indicates the time of authentication. | 1..1 | |
| legalAuthenticator/signatureCode/@code="S" | Indicates that the signature has been affixed and is on file. | 1..1 | |
| legalAuthenticator/assignedEntity | A legalAuthenticator is a person in the role of an assigned entity (AssignedEntity class). An assigned entity is a person assigned to the role by the scoping organization. The entity playing the role is a person (Person class). The entity scoping the role is an organization (Organization class). | 1..1 | |
| legalAuthenticator/assignedEntity/code | The specific kind of role. | 0..1 | See < code > for available attributes. |
| legalAuthenticator/assignedEntity/id | A unique identifier for the player entity in this role. | 1..1 | See < id > for available attributes. |
| legalAuthenticator/assignedEntity/assignedPerson | The entity playing the role (assignedEntity) is a person. | 1..1 | |
| legalAuthenticator/assignedEntity/assignedPerson/ext:asEntityIdentifier | The entity identifier of the person. | 0..* | See < Entity Identifier > for available attributes. Recommended mappings for the complex data type to CDA (R2): Identifier . |
| legalAuthenticator/assignedEntity/addr | A postal address for the entity (assignedPerson) while in the role (assignedEntity). | 0..* | Recommended mappings for the complex data type to CDA (R2): Address . |
| legalAuthenticator/assignedEntity/telecom | A telecommunication address for the entity (assignedPerson) while in the role (assignedEntity). | 0..* | Recommended mappings for the complex data type to CDA (R2): ContactPoint . |
| legalAuthenticator/assignedEntity/assignedPerson/name | A non-unique textual identifier or moniker for the entity (assignedPerson). | 0..* | Recommended mappings for the complex data type to CDA (R2): HumanName . |
| legalAuthenticator/assignedEntity/representedOrganization | The entity scoping the role (assignedEntity). | 0..1 | |
| legalAuthenticator/assignedEntity/representedOrganization/ext:asEntityIdentifier | A unique identifier for the scoping entity (represented organization) in this role (assignedEntity). | 0..* | See < Entity Identifier > for available attributes. Recommended mappings for the complex data type to CDA (R2): Identifier . |
| legalAuthenticator/assignedEntity/representedOrganization/name | A non-unique textual identifier or moniker for the entity (representedOrganization). | 0..* | |

5.3 Administrative Observations

CDA mapping

| CDA schema element | Definition | Card | Constraints and comments |
|---|---|---|---|
| Conformance level comes from linking elements | Context: /ClinicalDocument/component/structuredBody/ | | |
| component[admin_obs] | The ACDCR document model contains a number of elements for which there are no equivalent elements at that point in the hierarchical structure of the model mapped into CDA. These elements are considered to be "Administrative Observations" about the encounter, the patient or some other participant. | Cardinality comes from linking elements | ClinicalDocument SHALL contain at most one Administrative Observation section. The Administrative Observations section SHALL NOT be populated if there are no entries or text to go in it. |
| component[admin_obs]/section | | 1..1 | |
| component[admin_obs]/section/templateId | | 1..1 | The use of templateId signals the imposition of a set of template-defined constraints. |
| component[admin_obs]/section/templateId/@root="1.2.36.1.2001.1001.102.101.100000" | | 1..1 | |
| component[admin_obs]/section/templateId/@extension="1.0" | | 1..1 | |
| component[admin_obs]/section/id | | 0..1 | See <id> for available attributes. |
| component[admin_obs]/section/code | | 1..1 | |
| component[admin_obs]/section/code/@code="102.16080" | | 1..1 | |
| component[admin_obs]/section/code/@codeSystem="1.2.36.1.2001.1001.101" | | 1..1 | |
| component[admin_obs]/section/code/@codeSystemName | | 0..1 | Optional CDA element. The value SHOULD be "NCTIS Data Components". |
| component[admin_obs]/section/code/@displayName | | 0..1 | Optional CDA element. The value SHOULD be "Administrative Observations". |
| component[admin_obs]/section/title="Administrative Observations" | | 0..1 | |
| component[admin_obs]/section/text | | 0..1 | See CDA narratives . |

6 Document CDA templates

This chapter contains mapping from the Composition (Advance Care Directive Custodian Record) model to a CDA clinical document class, expressed as a series of CDA templates that describe how the CDA document is composed.

CDA templates are expected to be reused from one document type (or Composition model) to another. Each CDA template is presented under a heading in the format of "CDA schema element" ("model name") where "CDA schema element" is the root element for a CDA template and "model name" is the name of a model that constrains an element in the Advance Care Directive Custodian Record hierarchy.

6.1 Composition (Advance Care Directive Custodian Record)

CDA mapping

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|---------------------------------|---|------|---|---|--|
| Context: / | | | | | |
| Composition | A record of the custodians of an individual's advance care directive. | 1..1 | DomainResource | ClinicalDocument | In addition to the template defined in this mapping table, ClinicalDocument SHALL conform to the template defined in ClinicalDocument . |
| | | | | ClinicalDocument/templateId | The use of templateId signals the imposition of a set of template-defined constraints. |
| | | | | ClinicalDocument/templateId/@root="1.2.36.1.2001.1001.102.101.100044" | |
| | | | | ClinicalDocument/templateId/@extension="1.0" | |
| Composition > identifier | Logical identifier for the composition, assigned when created. This identifier stays constant as the composition is changed over time. | 0..1 | Identifier | ClinicalDocument/setId | |
| Composition > status | The workflow/clinical status of this composition. The status is a marker for the clinical standing of the document. | 1..1 | code | ClinicalDocument/ext:completionCode | Australian Healthcare Clinical Document Architecture Document Lifecycle Status (required)¹ |
| Composition > subject | Who or what the composition is about. The composition can be about a person, (patient or healthcare practitioner), a device (e.g. a machine) or even a group of subjects (such as a document about a herd of livestock, or a set of patients that share a common exposure). | 1..1 | Reference(Patient) as Patient with Mandatory Identifier | ClinicalDocument/recordTarget | recordTarget SHALL conform to the template defined in recordTarget (Patient with Mandatory Identifier) . |
| Composition > date | The composition editing time, when the composition was last logically changed by the author. | 1..1 | dateTime | ClinicalDocument/author/time | |

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|---|--|------|---|--|---|
| Composition > author | Identifies who is responsible for the information in the composition, not necessarily who typed it in. | 1..1 | Reference(Patient) as Patient with Mandatory Identifier Practitioner as Practitioner with Mandatory Identifier RelatedPerson as RelatedPerson with Mandatory Identifier | ClinicalDocument/author | In CDA an author (Practitioner) is part of composition-author-role (PractitionerRole); therefore if the author is a practitioner then composition-author-role SHALL be instantiated. author SHALL conform to a template defined in author (Patient with Mandatory Identifier) or author (RelatedPerson with Mandatory Identifier) or author (PractitionerRole with Practitioner with Mandatory Identifier) . |
| Composition > title | Official human-readable label for the composition. | 1..1 | string | ClinicalDocument/title="Advance Care Directive Custodian Record" | |
| Composition > attester (Legal Attester) | A participant who has attested to the accuracy of the composition/document. | 0..1 | BackboneElement | ClinicalDocument/legalAuthenticator | A legal attester SHALL have a party or an attester-related-party but not both. legalAuthenticator SHALL conform to the template defined in LegalAuthenticator . |
| Composition > attester (Legal Attester) > mode | The type of attestation the authenticator offers. | 1..1 | code | n/a | Not mapped separately, the logical mode of "legal" is implicit in legalAuthenticator. |
| Composition > attester (Legal Attester) > time | When the composition was attested by the party. | 1..1 | dateTime | n/a | Not mapped separately, implicit in legalAuthenticator/time/@value. |
| Composition > attester (Legal Attester) > party | Who attested the composition in the specified way. | 1..1 | Reference(Patient) as Patient with Mandatory Identifier Practitioner as Practitioner with Mandatory Identifier | n/a | Not mapped separately, implicit in legalAuthenticator/as-signedEntity. |
| Composition > attester (Legal Attester) > attester-related-party | A related person that attested this composition. | 0..1 | Reference(RelatedPerson) as RelatedPerson with Mandatory Identifier | n/a | Not mapped separately, implicit in legalAuthenticator/as-signedEntity. |
| Composition > custodian | Identifies the organization or group who is responsible for ongoing maintenance of and access to the composition/document information. | 1..1 | Reference(Organization) as Organization with Mandatory Identifier | ClinicalDocument/custodian | custodian SHALL conform to the template defined in custodian (Organization with Mandatory Identifier) . |
| Composition > section (Advance Care Directive Custodians) | A section that contains details pertaining to the custodians of an individual's advance care directive. | 1..1 | BackboneElement | ClinicalDocument/component/structuredBody/component[acd] | |
| | | | | ClinicalDocument/component/structuredBody/component[acd]/section | section SHALL conform to the template defined in section (Advance Care Directive Custodians) . |

¹Note: Mappings between the set of concepts in the terminology binding on status in Advance Care Directive Custodian Record [DH2019e] and in the CDA model are defined in [Composition Status FHIR to Australian CDA Document Lifecycle Status concept map](#).

7 Participation CDA templates

This chapter contains mapping from the Individual (e.g. Patient with Mandatory Identifier) and Entity (e.g. Organization with Mandatory Identifier) models to CDA participation classes, expressed as a series of CDA templates that describe how each CDA participation is composed.

CDA templates are expected to be reused from one document type (or Composition model) to another. Each CDA template is presented under a heading in the format of "CDA schema element" ("model name") where "CDA schema element" is the root element for a CDA template and "model name" is the name of a model that constrains an element in the Advance Care Directive Custodian Record hierarchy.

7.1 recordTarget (Patient with Mandatory Identifier)

CDA mapping

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|-----------------------------|--|---|--------------------------------|--|---|
| CDA Header Data Elements | | | | | |
| Patient | Demographics and other administrative information about an individual receiving care or other health-related services. | Cardinality comes from linking elements | DomainResource | Context: /ClinicalDocument/ | |
| | | | | recordTarget[pat] | |
| | | | | recordTarget[pat]/templateId | The use of templateId signals the imposition of a set of template-defined constraints. |
| | | | | recordTarget[pat]/templateId/@root="1.2.36.1.2001.1001.102.101.100004" | |
| | | | | recordTarget[pat]/templateId/@extension="1.0" | |
| | | | | recordTarget[pat]/patientRole/id | See <id> for available attributes. |
| Patient > birthPlace | The registered place of birth of the patient. A system may use the address.text if they don't store the birthPlace address in discrete elements. | 0..1 | Address | recordTarget[pat]/patientRole/patient/birthplace | |
| | | | | recordTarget[pat]/patientRole/patient/birthplace/place | |
| | | | | recordTarget[pat]/patientRole/patient/birthplace/place/addr | Recommended mappings for the complex data type to CDA (R2): Address Address as Australian Address . |
| Patient > indigenous-status | National Health Data Dictionary (NHDD) based indigenous status for a patient. | 0..1 | Coding | recordTarget[pat]/patientRole/patient/ethnicGroupCode | <p>When sending to the My Health Record this element is expected to be sent.</p> <p>See <code> for available attributes.</p> <p>Australian Indigenous Status (required)</p> |

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|--|---|------|-------------------------|--|--|
| CDA Header Data Elements | | | | | |
| Patient > closing-the-gap-registration | Indication for eligibility for the Closing the Gap program. | 0..1 | boolean | entry[close_gap] entry[close_gap]/observation entry[close_gap]/observation/@classCode="OBS" entry[close_gap]/observation/@moodCode="EVN" entry[close_gap]/observation/id entry[close_gap]/observation/code entry[close_gap]/observation/code/@code="103.32011" entry[close_gap]/observation/code/@codeSystem="1.2.36.1.2001.1001.101" entry[close_gap]/observation/code/@codeSystemName entry[close_gap]/observation/code/@displayName entry[close_gap]/observation/value | Optional CDA element. See <id> for available attributes. codeSystemName SHOULD be "NCTIS Data Components". displayName SHOULD be "Closing the Gap Copayment Eligibility Indicator". The value is "true" if eligible for Closing the Gap co-payment. //value/@xsi:type SHALL be "BL". |
| Patient > patient-mothersMaidenName | Mother's maiden (unmarried) name, commonly collected to help verify patient identity. | 0..1 | string | entry[mothers_name] entry[mothers_name]/observation entry[mothers_name]/observation/@classCode="OBS" entry[mothers_name]/observation/@moodCode="EVN" entry[mothers_name]/observation/id entry[mothers_name]/observation/code entry[mothers_name]/observation/code/@code="103.10245" entry[mothers_name]/observation/code/@codeSystem="1.2.36.1.2001.1001.101" entry[mothers_name]/observation/code/@codeSystemName entry[mothers_name]/observation/code/@displayName entry[mothers_name]/observation/value | Optional CDA element. See <id> for available attributes. codeSystemName SHOULD be "NCTIS Data Components". displayName SHOULD be "Mother's Original Family Name". //value/@xsi:type SHALL be "ST". |

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|--|--|------|------------------------------|---|--|
| CDA Header Data Elements | | | | Context: /ClinicalDocument/ | |
| Patient > identifier | An identifier for this patient. | 1..* | Identifier | recordTarget[pat]/patientRole/patient/ext:asEntityIdentifier | When sending to the My Health Record an IHI is expected. See < Entity Identifier > for available attributes. Recommended mappings for the complex data type to CDA (R2): Identifier . |
| Patient > active | Whether this patient record is in active use. | 0..1 | boolean | n/a | This logical element has no mapping to CDA. |
| Patient > name | A name associated with the individual. | 0..* | HumanName | recordTarget[pat]/patientRole/patient/name | Recommended mappings for the complex data type to CDA (R2): HumanName . |
| Patient > telecom | A contact detail (e.g. a telephone number or an email address) by which the individual may be contacted. | 0..* | ContactPoint | recordTarget[pat]/patientRole/telecom | Recommended mappings for the complex data type to CDA (R2): ContactPoint . |
| Patient > gender | Administrative Gender - the gender that the patient is considered to have for administration and record keeping purposes. | 0..1 | code | recordTarget[pat]/patientRole/patient/administrativeGenderCode | See < code > for available attributes. AdministrativeGender (required) |
| Patient > birthDate | The date of birth for the individual. | 0..1 | date | recordTarget[pat]/patientRole/patient/birthTime | See < time > for available attributes. |
| CDA Header Data Elements | | | | Context: /ClinicalDocument/component/structuredBody/component[admin_obs]/section/ See Administrative Observations . | |
| Patient > birthDate > date-accuracy-indicator | General date accuracy indicator coding. | 0..1 | Coding | entry[dob_acc] entry[dob_acc]/observation entry[dob_acc]/observation/@classCode="OBS" entry[dob_acc]/observation/@moodCode="EVN" entry[dob_acc]/observation/id entry[dob_acc]/observation/code entry[dob_acc]/observation/code/@code="102.16234" entry[dob_acc]/observation/code/@codeSystem="1.2.36.1.2001.1001.101" entry[dob_acc]/observation/code/@codeSystemName entry[dob_acc]/observation/code/@displayName entry[dob_acc]/observation/value | Optional CDA element. See < id > for available attributes. Optional CDA element. codeSystemName SHOULD be "NCTIS Data Components". Optional CDA element. displayName SHOULD be "Date of Birth Accuracy Indicator". //value/@xsi:type SHALL be "CS". Date Accuracy Indicator (required) |
| CDA Header Data Elements | | | | Context: /ClinicalDocument/ | |
| Patient > birthDate > patient-birthTime | The time of day that the Patient was born. This includes the date to ensure that the timezone information can be communicated effectively. | 0..1 | dateTime | n/a | Not mapped separately, encompassed in patientRole/patient/birthTime. |

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|---|---|------|--------------------|---|---|
| Patient > deceased[x] | Indicates if the individual is deceased or not. Deceased date accuracy indicator is optional. | 0..1 | boolean dateTime | recordTarget[pat]/patientRole/patient/ext:deceasedInd recordTarget[pat]/patientRole/patient/ext:deceasedTime | Only one of patientRole/patient/ext:deceasedInd or patientRole/patient/ext:deceasedTime SHOULD be instantiated. |
| CDA Header Data Elements | | | | | Context: /ClinicalDocument/component/structuredBody/component[admin_obs]/section/ See Administrative Observations |
| Patient > deceased[x] > date-accuracy-indicator | General date accuracy indicator coding. | 0..1 | Coding | entry[dod_acc] entry[dod_acc]/observation entry[dod_acc]/observation/@classCode="OBS" entry[dod_acc]/observation/@moodCode="EVN" entry[dod_acc]/observation/id entry[dod_acc]/observation/code entry[dod_acc]/observation/code/@code="102.16252" entry[dod_acc]/observation/code/@codeSystem="1.2.36.1.2001.1001.101" entry[dod_acc]/observation/code/@codeSystemName entry[dod_acc]/observation/code/@displayName entry[dod_acc]/observation/value | <p>Optional CDA element. See <id> for available attributes.</p> <p>Optional CDA element. codeSystemName SHOULD be "NCTIS Data Components".</p> <p>Optional CDA element. displayName SHOULD be "Date of Death Accuracy Indicator".</p> <p>//value/@xsi:type SHALL be "CS". Date Accuracy Indicator (required)</p> |
| CDA Header Data Elements | | | | | Context: /ClinicalDocument/ |
| Patient > address | Addresses for the individual. | 0..* | Address | recordTarget[pat]/patientRole/addr | <p>When sending to the My Health Record this element is not expected to be sent.</p> <p>Recommended mappings for the complex data type to CDA (R2): Address Address as Australian Address.</p> |
| Patient > maritalStatus | This field contains a patient's most recent marital (civil) status. | 0..1 | CodeableConcept | recordTarget[pat]/patientRole/patient/maritalStatusCode | <p>See <code> for available attributes.</p> <p>Marital Status Codes (extensible)</p> |
| Patient > multipleBirth[x] | Indicates whether the patient is part of a multiple (bool) or indicates the actual birth order (integer). | 0..1 | boolean integer | recordTarget[pat]/patientRole/patient/ext:multipleBirthInd recordTarget[pat]/patientRole/patient/ext:multipleBirthOrderNumber | Only one of patientRole/patient/ext:multipleBirthInd or patientRole/patient/ext:multipleBirthOrderNumber SHOULD be instantiated. |
| Patient > contact | A contact party (e.g. guardian, partner, friend) for the patient. | 0..* | BackboneElement | participant[pat_contact] | participant[pat_contact] SHALL conform to the template defined in participant (Patient contact) . |
| Patient > communication | Languages which may be used to communicate with the patient about his or her health. | 0..* | BackboneElement | recordTarget[pat]/patientRole/patient/languageCommunication | |

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|--|---|------|--|---|--|
| Patient > communication > language | The ISO-639-1 alpha 2 code in lower case for the language, optionally followed by a hyphen and the ISO-3166-1 alpha 2 code for the region in upper case; e.g. 'en' for English, or 'en-US' for American English versus 'en-EN' for England English. | 1..1 | CodeableConcept | recordTarget[pat]/patientRole/patient/languageCommunication/languageCode | See < code > for available attributes. Common Languages in Australia (extensible) |
| Patient > communication > preferred | Indicates whether or not the patient prefers this language (over other languages he masters up a certain level). | 0..1 | boolean | recordTarget[pat]/patientRole/patient/languageCommunication/preferenceInd | |
| Patient > generalPractitioner | Patient's nominated care provider. | 0..* | Reference(Organization as Base Organization Practitioner as Base Practitioner) | participant | participant SHALL conform to the template defined in participant (generalPractitioner Base Organization) or participant (generalPractitioner Base Practitioner) . |
| Patient > managingOrganization | Organization that is the custodian of the patient record. | 0..1 | Reference(Organization as Base Organization) | recordTarget[pat]/patientRole/providerOrganization[manag_org] | providerOrganization SHALL conform to the template defined in providerOrganization (Base Organization) . |

7.2 participant (Patient contact)

CDA mapping

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|---|--|---|--|---|---|
| CDA Header Data Elements | | | | | |
| Patient > contact | A contact party (e.g. guardian, partner, friend) for the patient. | Cardinality comes from linking elements | BackboneElement | Context: /ClinicalDocument/ | |
| | | | | participant[pat_contact] | contact SHALL have at least name, or telecom, or address, or organization instantiated. |
| | | | | participant[pat_contact]/@typeCode="IND" | |
| | | | | participant[pat_contact]/templateId | The use of templateId signals the imposition of a set of template-defined constraints. |
| | | | | participant[pat_contact]/templateId/@root="1.2.36.1.2001.1001.102.101.100056" | |
| | | | | participant[pat_contact]/templateId/@extension="1.0" | |
| | | | | participant[pat_contact]/associatedEntity | |
| | | | | participant[pat_contact]/associatedEntity/@typeCode="CON" | |
| | | | | participant[pat_contact]/associatedEntity/id | Patient > contact is represented in CDA by a participant. |
| Patient > contact > relationship | The nature of the relationship between the patient and the contact person. | 0..* | CodeableConcept | participant[pat_contact]/associatedEntity/associatedPerson/ext:personalRelationship | See Personal Relationship for available attributes. ContactEntityType (extensible) |
| Patient > contact > name | A name associated with the contact person. | 0..1 | HumanName | participant[pat_contact]/associatedEntity/associatedPerson/name | Recommended mappings for the complex data type to CDA (R2): HumanName . |
| Patient > contact > telecom | A contact detail for the person, e.g. a telephone number or an email address. | 0..* | ContactPoint | participant[pat_contact]/associatedEntity/telecom | Recommended mappings for the complex data type to CDA (R2): ContactPoint . |
| Patient > contact > address | Address for the contact person. | 0..1 | Address | participant[pat_contact]/associatedEntity/addr | Recommended mappings for the complex data type to CDA (R2): Address Address as Australian Address . |
| Patient > contact > gender | Administrative Gender - the gender that the contact person is considered to have for administration and record keeping purposes. | 0..1 | code | participant[pat_contact]/associatedEntity/associatedPerson/ext:administrativeGenderCode | See code for available attributes. AdministrativeGender (required) |
| Patient > contact > organization | Organization on behalf of which the contact is acting or for which the contact is working. | 0..1 | Reference(Organization as Base Organization) | participant[pat_contact]/associatedEntity/scopingOrganization | contact > organization template is not currently defined. |
| Patient > contact > period | The period during which this contact person or organization is valid to be contacted relating to this patient. | 0..1 | Period | n/a | |

7.3 participant (generalPractitioner Base Organization)

CDA mapping

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|----------------------------------|---|---|---------------------------------|--|--|
| CDA Header Data Elements | | | | | Context: /ClinicalDocument/ |
| Organization | A formally or informally recognized grouping of people or organizations formed for the purpose of achieving some form of collective action. Includes companies, institutions, corporations, departments, community groups, healthcare practice groups, etc. | Cardinality comes from linking elements | DomainResource | <code>participant[gen_prac_org]</code> | The organization SHALL at least have an identifier (particpant[gen_prac_org]/associatedEntity/scopingOrganization/ext:asEntityIdentifier) or a name (partcipant[gen_prac_org]/associatedEntity/scopingOrganization/name). |
| | | | | <code>participant[gen_prac_org]/@typeCode="PART"</code> | |
| | | | | <code>participant[gen_prac_org]/templateId</code> | The use of templateId signals the imposition of a set of template-defined constraints. |
| | | | | <code>participant[gen_prac_org]/templateId/@root="1.2.36.1.2001.1001.102.101.100036"</code> | |
| | | | | <code>participant[gen_prac_org]/templateId/@extension="1.0"</code> | |
| | | | | <code>participant[gen_prac_org]/functionCode/@code="PCP"</code> | |
| | | | | <code>participant[gen_prac_org]/associatedEntity</code> | |
| | | | | <code>participant[gen_prac_org]/associatedEntity/@classCode="PROV"</code> | |
| | | | | <code>participant[gen_prac_org]/associatedEntity/id</code> | Optional CDA element. See < id > for available attributes. |
| Organization > identifier | Identifier for the organization that is used to identify the organization across multiple disparate systems. | 0..* | Identifier | <code>participant[gen_prac_org]/associatedEntity/scopingOrganization/ext:asEntityIdentifier</code> | See < Entity Identifier > for available attributes. Recommended mappings for the complex data type to CDA (R2): Identifier . |
| Organization > active | Whether the organization's record is still in active use. | 0..1 | boolean | n/a | This logical element has no mapping to CDA. |
| Organization > type | The kind(s) of organization that this is. | 0..1 | CodeableConcept | <code>participant[gen_prac_org]/associatedEntity/code</code> | See < code > for available attributes. OrganizationType (example) |
| Organization > name | A name associated with the organization. | 0..1 | string | <code>participant[gen_prac_org]/associatedEntity/scopingOrganization/name</code> | In CDA name and alias are represented by //scopingOrganization/name. |
| Organization > alias | A list of alternate names that the organization is known as, or was known as in the past. | 0..* | string | <code>participant[gen_prac_org]/associatedEntity/scopingOrganization/name</code> | In CDA name and alias are represented by //scopingOrganization/name. |
| Organization > telecom | A contact detail for the organization. | 0..* | ContactPoint | <code>participant[gen_prac_org]/associatedEntity/telecom</code> | <code>telecom/@use</code> is Organization Telecom Use HL7 V3 (required) . Recommended mappings for the complex data type to CDA (R2): ContactPoint . |

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|---------------------------------|---|------|--|--|--|
| Organization > address | An address for the organization. | 0..* | Address | participant[gen_prac_org]/associatedEntity/addr | addr/@use is Organization Address Use HL7 V3 (required) . Recommended mappings for the complex data type to CDA (R2): Address Address as Australian Address . |
| Organization > partOf | The organization of which this organization forms a part. | 0..1 | Reference(Organization as Base Organization) | participant[gen_prac_org]/asOrganizationPartOf participant[gen_prac_org]/asOrganizationPartOf/wholeOrganization | The organization SHALL have at least a name (/wholeOrganization/name) or an identifier (/wholeOrganization/ext:asEntityIdentifier). Organization > partOf template is not currently defined. |
| CDA Header Data Elements | | | | | Context: /ClinicalDocument/ |
| Organization > contact | Contact for the organization for a certain purpose. | 0..* | BackboneElement | participant[org_contact] | participant[org_contact] SHALL conform to the template defined in participant (Organization contact) . |

7.4 participant (generalPractitioner Base Practitioner)

CDA mapping

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|----------------------------------|--|---|--------------------------------|--|--|
| CDA Header Data Elements | | | | Context: /ClinicalDocument/ | |
| Practitioner | A person who is directly or indirectly involved in the provisioning of healthcare. | Cardinality comes from linking elements | DomainResource | <code>participant[gen_prac_prac]</code> | The practitioner SHALL at least have an identifier (<code>participant[gen_prac_prac]/associatedEntity/associatedPerson/ext:asEntityIdentifier</code>) or a name (<code>participant[gen_prac_prac]/associatedEntity/associatedPerson/name</code>). |
| | | | | <code>participant[gen_prac_prac]/@typeCode="PART"</code> | |
| | | | | <code>participant[gen_prac_prac]/templateId</code> | The use of templateId signals the imposition of a set of template-defined constraints. |
| | | | | <code>participant[gen_prac_prac]/templateId/@root="1.2.36.1.2001.1001.102.101.100037"</code> | |
| | | | | <code>participant[gen_prac_prac]/templateId/@extension="1.0"</code> | |
| | | | | <code>participant[gen_prac_prac]/functionCode/@code="PCP"</code> | |
| | | | | <code>participant[gen_prac_prac]/associatedEntity</code> | |
| | | | | <code>participant[gen_prac_org]/associatedEntity/@classCode="PROV"</code> | |
| | | | | <code>participant[gen_prac_prac]/associatedEntity/id</code> | Optional CDA element. See < id > for available attributes. |
| | | | | <code>participant[gen_prac_prac]/associatedEntity/code</code> | Optional CDA element. Australian and New Zealand Standard Classification of Occupations (preferred) |
| Practitioner > identifier | An identifier that applies to this person in this role. | 0..* | Identifier | <code>participant[gen_prac_prac]/associatedEntity/associatedPerson/ext:asEntityIdentifier</code> | See < Entity Identifier > for available attributes. Recommended mappings for the complex data type to CDA (R2): Identifier . |
| Practitioner > active | Whether this practitioner's record is in active use. | 0..1 | boolean | n/a | This logical element has no mapping to CDA. |
| Practitioner > name | The name(s) associated with the practitioner. | 0..* | HumanName | <code>participant[gen_prac_prac]/associatedEntity/associatedPerson/name</code> | Recommended mappings for the complex data type to CDA (R2): HumanName . |
| Practitioner > telecom | A contact detail for the practitioner, e.g. a telephone number or an email address. | 0..* | ContactPoint | <code>participant[gen_prac_prac]/associatedEntity/telecom</code> | Recommended mappings for the complex data type to CDA (R2): ContactPoint . |
| Practitioner > address | Address(es) of the practitioner that are not role specific (typically home address). Work addresses are not typically entered in this property as they are usually role dependent. | 0..* | Address | <code>participant[gen_prac_prac]/associatedEntity/addr</code> | Recommended mappings for the complex data type to CDA (R2): Address Address as Australian Address . |

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|-------------------------------------|--|------|---------------------------------|--|--|
| Practitioner > gender | Administrative Gender - the gender that the person is considered to have for administration and record keeping purposes. | 0..1 | code | participant[gen_prac_prac]/associatedEntity/associatedPerson/ ext:administrativeGenderCode | See < code > for available attributes. AdministrativeGender (required) |
| Practitioner > birthDate | The date of birth for the practitioner. | 0..1 | date | participant[gen_prac_prac]/associatedEntity/associatedPerson/ ext:birthTime | |
| Practitioner > qualification | Qualifications obtained by training and certification. | 0..* | BackboneElement | See: instantiation choices | <p>It is possible that the qualification may be able to be captured as a complex structure or as a text list.</p> <p>instantiation choices:</p> <p>If the qualification or list of qualifications is the result of capturing a text field then this element is expected to be as //ext:Qualifications/@classCode="QUAL". See <Qualification> for available attributes.</p> <p>If more information can be captured than a narrative list then this logical element is expected to be instantiated as ext:coverage2[prac_qual] and SHALL conform to the template defined in ext:coverage (Practitioner qualification).</p> |
| Practitioner > communication | A language the practitioner is able to use in patient communication. | 0..* | CodeableConcept | participant[gen_prac_prac]/associatedEntity/associatedPerson/ ext:languageCommunication | See < code > for available attributes. Common Languages in Australia (extensible) |

7.5 participant (Base Organization)

CDA mapping

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|---|---|---|---------------------------------|--|--|
| CDA Header Data Elements | | | | | Context: /ClinicalDocument/ |
| Organization | A formally or informally recognized grouping of people or organizations formed for the purpose of achieving some form of collective action. Includes companies, institutions, corporations, departments, community groups, healthcare practice groups, etc. | Cardinality comes from linking elements | DomainResource | <code>participant[org]</code> | The organization SHALL at least have an identifier (<code>participant[org]/participantRole/scopingEntity/ext:asEntityIdentifier</code>) or a name (<code>participant[org]/participantRole/scopingEntity/name</code>). |
| | | | | <code>participant[org]/@type="PART"</code> | |
| | | | | <code>participant[org]/templateId</code> | The use of templateId signals the imposition of a set of template-defined constraints. |
| | | | | <code>participant[org]/templateId/@root="1.2.36.1.2001.1001.102.101.100047"</code> | |
| | | | | <code>participant[org]/templateId/@extension="1.0"</code> | |
| | | | | <code>participant[org]/participantRole</code> | |
| | | | | <code>participant[org]/participantRole/@classCode="ASSIGNED"</code> | |
| | | | | <code>participant[org]/participantRole/id</code> | Optional CDA element. See <id> for available attributes. |
| | | | | <code>participant[org_contact]/participantRole/scopingEntity</code> | |
| | | | | <code>participant[org_contact]/participantRole/scopingEntity/typeCode="ORG"</code> | |
| Organization > <code>identifier</code> | Identifier for the organization that is used to identify the organization across multiple disparate systems. | 0..* | Identifier | <code>participant[org]/participantRole/scopingEntity/ext:asEntityIdentifier</code> | See <Entity Identifier> for available attributes. Recommended mappings for the complex data type to CDA (R2): Identifier . |
| Organization > <code>active</code> | Whether the organization's record is still in active use. | 0..1 | boolean | n/a | This logical element has no mapping to CDA. |
| Organization > <code>type</code> | The kind(s) of organization that this is. | 0..1 | CodeableConcept | <code>participant[org]/participantRole/code</code> | See <code> for available attributes. OrganizationType (example) |
| Organization > <code>name</code> | A name associated with the organization. | 0..1 | string | <code>participant[org]/participantRole/scopingEntity/name</code> | In CDA name and alias are represented by //scopingEntity/name. |
| Organization > <code>alias</code> | A list of alternate names that the organization is known as, or was known as in the past. | 0..* | string | <code>participant[org]/participantRole/scopingEntity/name</code> | In CDA name and alias are represented by //scopingEntity/name. |
| Organization > <code>telecom</code> | A contact detail for the organization. | 0..* | ContactPoint | <code>participant[org]/participantRole/telecom</code> | telecom/@use is Organization Telecom Use HL7 V3 (required) . Recommended mappings for the complex data type to CDA (R2): ContactPoint . |

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|---------------------------------|---|------|--|--|--|
| Organization > address | An address for the organization. | 0..* | Address | participant[org]/participantRole/ addr | addr/@use is Organization Address Use HL7 V3 (required) . Recommended mappings for the complex data type to CDA (R2): Address . |
| Organization > partOf | The organization of which this organization forms a part. | 0..1 | Reference(Organization as Base Organization) | participant[org]/asOrganizationPartOf participant[org]/asOrganizationPartOf/wholeOrganization | The organization SHALL have at least a name (/wholeOrganization/name) or an identifier (/wholeOrganization/ext:asEntityIdentifier). Organization > partOf template is not currently defined. |
| CDA Header Data Elements | | | | | Context: /ClinicalDocument/ |
| Organization > contact | Contact for the organization for a certain purpose. | 0..* | BackboneElement | participant[org_contact] | participant[org_contact] SHALL conform to the template defined in participant (Organization contact) . |

7.6 participant (Base Patient)

CDA mapping

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|---|--|---|--------------------------------|---|---|
| Conformance level comes from linking elements | | Context: Comes from linking elements | | | |
| Patient | Demographics and other administrative information about an individual receiving care or other health-related services. | Cardinality comes from linking elements | DomainResource | participant[pat] | The patient SHALL at least have an identifier (participant[pat]/participantRole/playingEntity/ext:asEntityIdentifier) or a name (participant[pat]/participantRole/playingEntity/name). |
| | | | | participant[pat]/@type="PART" | |
| | | | | participant[pat]/templateId | The use of templateId signals the imposition of a set of template-defined constraints. |
| | | | | participant[pat]/templateId/@root="1.2.36.1.2001.1001.102.101.100048" | |
| | | | | participant[pat]/templateId/@extension="1.0" | |
| | | | | participant[pat]/participantRole | |
| | | | | participant[pat]/participantRole/id | information-recipient (patient) is represented in CDA by an information recipient with the same id as the patient that is the subject of this document. |
| | | | | participant[pat]/participantRole/code | This SHALL hold the same value as /ClinicalDocument/recordTarget/patientRole/id. |
| | | | | participant[pat]/participantRole/code/@code="ONESELF" | |
| | | | | participant[pat]/participantRole/code/@codeSystem="2.16.840.1.113883.5.111" | |
| | | | | participant[pat]/participantRole/playingEntity | |
| | | | | participant[pat]/participantRole/playingEntity/@classCode=PSN" | |
| Patient > birthPlace | The registered place of birth of the patient. A system may use the address.text if they don't store the birthPlace address in discrete elements. | 0..1 | Address | n/a | Not mapped directly for this participant; this is implicit in //patient/languageCommunication/birthPlace/place/addr. |
| Patient > indigenous-status | National Health Data Dictionary (NHDD) based indigenous status for a patient. | 0..1 | Coding | n/a | Not mapped directly for this participant; this is implicit in //patient/ethnicGroupCode. |
| Patient > closing-the-gap-registration | Indication for eligibility for the Closing the Gap program. | 0..1 | boolean | n/a | closing-the-gap-registration is not currently mapped. |
| Patient > patient-mothers-MaidenName | Mother's maiden (unmarried) name, commonly collected to help verify patient identity. | 0..1 | string | n/a | Not mapped directly for this participant; this is implicit in //entry[mothers_name]/observation/value. |

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|--|--|------|---|---|---|
| Patient > identifier | An identifier for this patient. | 0..* | Identifier | participant[pat]/participantRole/playingEntity/ext:asEntityIdentifier | See < Entity Identifier > for available attributes. Recommended mappings for the complex data type to CDA (R2): Identifier . |
| Patient > active | Whether this patient record is in active use. | 0..1 | boolean | n/a | This logical element has no mapping to CDA. |
| Patient > name | A name associated with the individual. | 0..* | HumanName | participant[pat]/participantRole/playingEntity/name | Recommended mappings for the complex data type to CDA (R2): HumanName . |
| Patient > telecom | A contact detail (e.g. a telephone number or an email address) by which the individual may be contacted. | 0..* | ContactPoint | participant[pat]/participantRole/playingEntity/telecom | Recommended mappings for the complex data type to CDA (R2): ContactPoint . |
| Patient > gender | Administrative Gender - the gender that the patient is considered to have for administration and record keeping purposes. | 0..1 | code | participant[pat]/participantRole/playingEntity/ext:administrativeGenderCode | See < code > for available attributes. AdministrativeGender (required) |
| Patient > birthDate | The date of birth for the individual. | 0..1 | date | n/a | Not mapped directly for this participant; this is implicit in //patient/birthTime. |
| Patient > birthDate > date-accuracy-indicator | General date accuracy indicator coding. | 0..1 | Coding | n/a | not mapped directly for this participant. |
| Patient > birthDate > patient- birthTime | The time of day that the Patient was born. This includes the date to ensure that the timezone information can be communicated effectively. | 0..1 | dateTime | n/a | Not mapped directly for this participant; this is implicit in //patient/birthTime. |
| Patient > deceased | Indicates if the individual is deceased or not. Deceased date accuracy indicator is optional. | 0..1 | boolean dateTime | n/a | Not mapped directly for this participant; this is implicit in //patient/ext:deceasedTime or //patient/ext:deceasedInd. |
| Patient > deceased > date-accuracy-indicator | General date accuracy indicator coding. | 0..1 | Coding | n/a | not mapped directly for this participant. |
| Patient > address | Addresses for the individual. | 0..* | Address | participant[pat]/participantRole/playingEntity/addr | Recommended mappings for the complex data type to CDA (R2): Address . |
| Patient > maritalStatus | This field contains a patient's most recent marital (civil) status. | 0..1 | CodeableConcept | n/a | Not mapped directly for this participant; this is implicit in //patient/ext:deceasedTime or //patient/maritalStatusCode. |
| Patient > multipleBirth | Indicates whether the patient is part of a multiple (bool) or indicates the actual birth order (integer). | 0..1 | boolean integer | n/a | Not mapped directly for this participant; this is implicit in //patient/ext:multipleBirthInd or //patient/multipleBirthOrderNumber. |
| Patient > photo | Image of the patient. | 0..0 | Attachment | participant[pat]/participantRole/playingEntity/desc | |
| Patient > contact | A contact party (e.g. guardian, partner, friend) for the patient. | 0..* | BackboneElement | n/a | This logical element has no mapping to CDA. |
| Patient > communication | Languages which may be used to communicate with the patient about his or her health. | 0..* | BackboneElement | n/a | Not mapped directly for this participant; this is implicit in //patient/languageCommunication. |

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|--|---|------|---|--------------------|--|
| Patient > communication > language | The ISO-639-1 alpha 2 code in lower case for the language, optionally followed by a hyphen and the ISO-3166-1 alpha 2 code for the region in upper case; e.g. 'en' for English, or 'en-US' for American English versus 'en-EN' for England English. | 1..1 | CodeableConcept | n/a | Not mapped directly for this participant; this is implicit in //patient/languageCommunication/languageCode. |
| Patient > communication > preferred | Indicates whether or not the patient prefers this language (over other languages he masters up a certain level). | 0..1 | boolean | n/a | Not mapped directly for this participant; this is implicit in //patient/languageCommunication/preferenceInd. |
| Patient > generalPractitioner | Patient's nominated care provider. | 0..* | Reference(Organization as Base Organization Practitioner as Base Practitioner) | n/a | This logical element has no mapping to CDA. |
| Patient > managingOrganization | Organization that is the custodian of the patient record. | 0..1 | Reference(Organization as Base Organization) | n/a | This logical element has no mapping to CDA. |

7.7 participant (Base Practitioner)

CDA mapping

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|---|--|---|--------------------------------|---|--|
| Conformance level comes from linking elements | | Context: Comes from linking elements | | | |
| Practitioner | A person who is directly or indirectly involved in the provisioning of healthcare. | Cardinality comes from linking elements | DomainResource | participant[prac] | The practitioner SHALL at least have an identifier (participant[prac]/participantRole/playingEntity/ext:asEntityIdentifier) or a name (participant[prac]/participantRole/playingEntity/name). |
| | | | | participant[prac]/@type="PART" | |
| | | | | participant[prac]/templateId | The use of templateId signals the imposition of a set of template-defined constraints. |
| | | | | participant[prac]/templateId/@root="1.2.36.1.2001.1001.102.101.100049" | |
| | | | | participant[prac]/templateId/@extension="1.0" | |
| | | | | participant[prac]/functionCode | Optional CDA element. TBD some help on this |
| | | | | participant[prac]/participantRole | |
| | | | | participant[gen_prac_org]/participantRole/@classCode="PROV" | |
| | | | | participant[prac]/participantRole/id | Optional CDA element. See < id > for available attributes. |
| | | | | participant[prac]/participantRole/code | Optional CDA element. Australian and New Zealand Standard Classification of Occupations (preferred) |
| Practitioner > identifier | An identifier that applies to this person in this role. | 0..* | Identifier | participant[prac]/participantRole/playingEntity/ext:asEntityIdentifier | See < Entity Identifier > for available attributes. Recommended mappings for the complex data type to CDA (R2): Identifier . |
| | | | | | This logical element has no mapping to CDA. |
| Practitioner > active | Whether this practitioner's record is in active use. | 0..1 | boolean | n/a | |
| Practitioner > name | The name(s) associated with the practitioner. | 0..* | HumanName | participant[prac]/participantRole/playingEntity/name | Recommended mappings for the complex data type to CDA (R2): HumanName . |

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|-------------------------------------|--|------|---------------------------------|--|---|
| Practitioner > telecom | A contact detail for the practitioner, e.g. a telephone number or an email address. | 0..* | ContactPoint | participant[prac]/participantRole/ telecom | Recommended mappings for the complex data type to CDA (R2): ContactPoint . |
| Practitioner > address | Address(es) of the practitioner that are not role specific (typically home address). Work addresses are not typically entered in this property as they are usually role dependent. | 0..* | Address | participant[prac]/participantRole/ addr | Recommended mappings for the complex data type to CDA (R2): Address . |
| Practitioner > gender | Administrative Gender - the gender that the person is considered to have for administration and record keeping purposes. | 0..1 | code | participant[prac]/participantRole/playingEntity/ ext:administrativeGenderCode | See code for available attributes. AdministrativeGender (required) |
| Practitioner > birthDate | The date of birth for the practitioner. | 0..1 | date | participant[prac]/participantRole/playingEntity/ ext:birthTime | |
| Practitioner > photo | Image of the person. | 0..0 | Attachment | participant[prac]/participantRole/playingEntity/ desc | |
| Practitioner > qualification | Qualifications obtained by training and certification. | 0..* | BackboneElement | See: instantiation choices | <p>It is possible that the qualification may be able to be captured as a complex structure or as a text list.</p> <p>instantiation choices:</p> <p>If the qualification or list of qualifications is the result of capturing a text field then this element is expected to be as //ext:Qualifications/@classCode="QUAL". See Qualification for available attributes.</p> <p>If more information can be captured than a narrative list then this logical element is expected to be instantiated as ext:coverage2[prac_qual] and SHALL conform to the template defined in ext:coverage (Practitioner qualification).</p> |
| Practitioner > communication | A language the practitioner is able to use in patient communication. | 0..* | CodeableConcept | n/a | <p>This logical element is not currently mapped into CDA.</p> <p>This may be supported in future by an entry in Administrative Observations or by the addition of an extension to add the languageCommunication element to the Person class.</p> |

7.8 participant (Base RelatedPerson)

CDA mapping

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|---|--|---|--|---|--|
| Conformance level comes from linking elements | | Context: Comes from linking elements | | | |
| RelatedPerson | Information about a person that is involved in the care for a patient, but who is not the target of healthcare, nor has a formal responsibility in the care process. | Cardinality comes from linking elements | DomainResource | participant[relper]/ | The related person SHALL have at least a name (participant[relper]/participantRole/playingEntity/name), or an identifier(participant[relper]/participantRole/playingEntity/ext:asEntityIdentifier), or a relationship instantiated (participant[relper]/participantRole/playingEntity/ext:personalRelationship). |
| | | | | participant[relper]/@typeCode="PART" | |
| | | | | participant[relper]/templateId | The use of templateId signals the imposition of a set of template-defined constraints. |
| | | | | participant[relper]/templateId/@root="1.2.36.1.2001.1001.102.101.100050" | |
| | | | | participant[relper]/templateId/@extension="1.0" | |
| | | | | participant[relper]/participantRole | Optional CDA element. See < id > for available attributes. |
| | | | | participant[relper]/participantRole/id | Optional CDA element. See < id > for available attributes. |
| | | | | participant[relper]/participantRole/playingEntity | |
| | | | | participant[relper]/participantRole/playingEntity/@classCode=PSN" | |
| RelatedPerson > identifier | Identifier for a person within a particular scope. | 1..* | Identifier | participant[relper]/participantRole/playingEntity/ext:asEntityIdentifier | See < Entity Identifier > for available attributes. Recommended mappings for the complex data type to CDA (R2): Identifier . |
| RelatedPerson > active | Whether this related person record is in active use. | 0..1 | boolean | n/a | This logical element has no mapping to CDA. |
| RelatedPerson > patient | The patient this person is related to. | 1..1 | Reference(Patient as Base Patient) | n/a | Not mapped directly for this participant; this is implicit in //patient. |
| RelatedPerson > relationship | The nature of the relationship between a patient and the related person. | 0..1 | string | participant[relper]/participantRole/playingEntity/ext:personalRelationship | Related Person Relationship Type (extensible) See < Personal Relationship > for available attributes. |
| RelatedPerson > name | A name associated with the person. | 0..* | HumanName | participant[relper]/participantRole/playingEntity/name | Recommended mappings for the complex data type to CDA (R2): HumanName . |

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|----------------------------------|---|------|---|---|---|
| RelatedPerson > telecom | A contact detail for the person, e.g. a telephone number or an email address. | 0..* | ContactPoint participant[relper]/participantRole/playingEntity/ telecom | | |
| RelatedPerson > gender | Administrative Gender - the gender that the person is considered to have for administration and record keeping purposes. | 0..1 | code | participant[relper]/participantRole/playingEntity/ ext:administrativeGenderCode | See < code > for available attributes. AdministrativeGender (required) |
| RelatedPerson > birthDate | The date on which the related person was born. | 0..1 | date | participant[relper]/participantRole/playingEntity/ ext:birthTime | See < time > for available attributes. |
| RelatedPerson > address | Address where the related person can be contacted or visited. | 0..* | Address | participant[relper]/participantRole/playingEntity/ addr | Recommended mappings for the complex data type to CDA (R2): Address . |
| RelatedPerson > photo | Image of the person. | 0..0 | Attachment | participant[relper]/participantRole/playingEntity/ desc | |
| RelatedPerson > period | The period of time that this relationship is considered to be valid. If there are no dates defined, then the interval is unknown. | 0..1 | Period | participant[relper]/participantRole/playingEntity/ ext:personalRelationship[related]/ext:effectiveTime | See < time > for available attributes. |

7.9 author (Patient with Mandatory Identifier)

CDA mapping

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|---|--|---|--------------------------------|--|---|
| Conformance level comes from linking elements | | | | Context: Comes from linking elements | |
| Patient | Demographics and other administrative information about an individual receiving care or other health-related services. | Cardinality comes from linking elements | DomainResource | author[pat] | |
| | | | | author[pat]/templateId | The use of templateId signals the imposition of a set of template-defined constraints. |
| | | | | author[pat]/templateId/@root="1.2.36.1.2001.1001.102.101.100003" | |
| | | | | author[pat]/templateId/@extension="1.0" | |
| | | | | author[pat]/assignedAuthor/id | |
| | | | | author[pat]/assignedAuthor/code | |
| | | | | author[pat]/assignedAuthor/code/@code="ONESELF" | |
| | | | | author[pat]/assignedAuthor/code/@codeSystem="2.16.840.1.113883.5.111" | |
| | | | | author[pat]/assignedAuthor/assignedPerson | |
| Patient > birthPlace | The registered place of birth of the patient. A system may use the address.text if they don't store the birthPlace address in discrete elements. | 0..1 | Address | n/a | Not mapped directly for this participant; this is implicit in //recordTarget/patientRole/patient/birthPlace/place/addr. |
| Patient > indigenous-status | National Health Data Dictionary (NHDD) based indigenous status for a patient. | 0..1 | Coding | n/a | Not mapped directly for this participant; this is implicit in //recordTarget/patientRole/patient/ethnic-GroupCode. |
| Patient > closing-the-gap-registration | Indication for eligibility for the Closing the Gap program. | 0..1 | boolean | n/a | Not mapped directly for this participant; this is implicit in //entry[close_gap]/observation/value. |
| Patient > patient-mothersMaiden-Name | Mother's maiden (unmarried) name, commonly collected to help verify patient identity. | 0..1 | string | n/a | Not mapped directly for this participant; this is implicit in //entry[mothers_name]/observation/value. |
| Patient > active | Whether this patient record is in active use. | 0..1 | boolean | n/a | This logical element has no mapping to CDA. |
| Patient > name | A name associated with the individual. | 0..* | HumanName | author[pat]/assignedAuthor/assignedPerson/name | Recommended mappings for the complex data type to CDA (R2): HumanName . |
| Patient > telecom | A contact detail (e.g. a telephone number or an email address) by which the individual may be contacted. | 0..* | ContactPoint | author[pat]/assignedAuthor/telecom | Recommended mappings for the complex data type to CDA (R2): ContactPoint . |
| Patient > gender | Administrative Gender - the gender that the patient is considered to have for administration and record keeping purposes. | 0..1 | code | author[pat]/assignedAuthor/assignedPerson/ext:administrativeGenderCode | See < code > for available attributes. AdministrativeGender (required) |
| Patient > birthDate | The date of birth for the individual. | 0..1 | date | n/a | Not mapped directly for this participant; this is implicit in //recordTarget/patientRole/patient/birthTime. |

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|---------------------------------------|---|------|---|---------------------------------|---|
| Patient > deceased[x] | Indicates if the individual is deceased or not. Deceased date accuracy indicator is optional. | 0..1 | boolean dateTime | n/a | Not mapped directly for this participant; this is implicit in //recordTarget/patientRole/patient/ext:deceasedTime or //recordTarget/patientRole/patient/ext:deceasedInd. |
| Patient > address | Addresses for the individual. | 0..* | Address | author[pat]/assignedAuthor/addr | Recommended mappings for the complex data type to CDA (R2): Address . |
| Patient > maritalStatus | This field contains a patient's most recent marital (civil) status. | 0..1 | CodeableConcept | n/a | Not mapped directly for this participant; this is implicit in //recordTarget/patientRole/patient/maritalStatusCode. |
| Patient > multipleBirth[x] | Indicates whether the patient is part of a multiple (bool) or indicates the actual birth order (integer). | 0..1 | boolean integer | n/a | Not mapped directly for this participant; this is implicit in //recordTarget/patientRole/patient/ext:multipleBirthInd or //recordTarget/patientRole/patient/multipleBirthOrderNumber. |
| Patient > contact | A contact party (e.g. guardian, partner, friend) for the patient. | 0..* | BackboneElement | n/a | This logical element has no mapping to CDA. |
| Patient > communication | Languages which may be used to communicate with the patient about his or her health. | 0..* | BackboneElement | n/a | Not mapped directly for this participant; this is implicit in //recordTarget/patientRole/patient/languageCommunication. |
| Patient > generalPractitioner | Patient's nominated care provider. | 0..* | Reference(Organization as Base Organization Practitioner as Base Practitioner) | n/a | This logical element has no mapping to CDA. |
| Patient > managingOrganization | Organization that is the custodian of the patient record. | 0..1 | Reference(Organization as Base Organization) | n/a | This logical element has no mapping to CDA. |

7.10 author (RelatedPerson with Mandatory Identifier)

CDA mapping

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|---|--|---|--|--|---|
| Conformance level comes from linking elements | | Context: Comes from linking elements | | | |
| RelatedPerson | Information about a person that is involved in the care for a patient, but who is not the target of healthcare, nor has a formal responsibility in the care process. | Cardinality comes from linking elements | DomainResource | author[relper] | |
| | | | | author[relper]/templateId | The use of templateId signals the imposition of a set of template-defined constraints. |
| | | | | author[relper]/templateId/@root="1.2.36.1.2001.1001.102.101.100030" | |
| | | | | author[relper]/templateId/@extension="1.0" | |
| | | | | author[relper]/assignedAuthor | |
| | | | | author[relper]/assignedAuthor/id | Optional CDA element. See < id > for available attributes. |
| | | | | author[relper]/assignedAuthor/code | |
| | | | | author[relper]/assignedAuthor/code/@code="AGNT" | |
| | | | | author[relper]/assignedAuthor/code/@codeSystem="2.16.840.1.113883.5.110" | |
| | | | | author[relper]/assignedAuthor/assignedPerson | |
| RelatedPerson > identifier | Identifier for a person within a particular scope. | 1..* | Identifier | author[relper]/assignedAuthor/assignedPerson/ext:asEntityIdentifier | See < Entity Identifier > for available attributes. Recommended mappings for the complex data type to CDA (R2): Identifier . |
| RelatedPerson > active | Whether this related person record is in active use. | 0..1 | boolean | n/a | |
| RelatedPerson > patient | The patient this person is related to. | 1..1 | Reference(Patient as Base Patient) | n/a | Not mapped directly for this participant; this is implicit in //recordTarget/patientRole/patient. |
| RelatedPerson > relationship | The nature of the relationship between a patient and the related person. | 0..1 | CodeableConcept | author[relper]/assignedAuthor/assignedPerson/ext:personalRelationship | Related Person Relationship Type (extensible) See < Personal Relationship > for available attributes. |
| RelatedPerson > name | A name associated with the person. | 0..* | HumanName | author[relper]/assignedAuthor/assignedPerson/name | |
| RelatedPerson > telecom | A contact detail for the person, e.g. a telephone number or an email address. | 0..* | ContactPoint | author[relper]/assignedAuthor/telecom | Recommended mappings for the complex data type to CDA (R2): ContactPoint . |
| RelatedPerson > gender | Administrative Gender - the gender that the person is considered to have for administration and record keeping purposes. | 0..1 | code | author[relper]/assignedAuthor/assignedPerson/ext:administrativeGenderCode | See < code > for available attributes. AdministrativeGender (required) |
| RelatedPerson > birthDate | The date on which the related person was born. | 0..1 | date | author[relper]/assignedAuthor/assignedPerson/ext:birthTime | |

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|--------------------------------|---|------|-------------------------|--|---|
| RelatedPerson > address | Address where the related person can be contacted or visited. | 0..* | Address | author[relper]/assignedAuthor/addr | Recommended mappings for the complex data type to CDA (R2): Address . |
| RelatedPerson > period | The period of time that this relationship is considered to be valid. If there are no dates defined, then the interval is unknown. | 0..1 | Period | author[relper]/assignedAuthor/assignedPerson/ext:personalRelationship[related]/ext:effectiveTime | See <time> for available attributes. |

7.11 author (PractitionerRole with Practitioner with Mandatory Identifier)

CDA mapping

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|---|---|---|--|--|--|
| Conformance level comes from linking elements | | | | | Context: Comes from linking elements |
| PractitionerRole | A specific set of Roles/Locations/specialties/services that a practitioner may perform at an organization for a period of time. | Cardinality comes from linking elements | DomainResource | author[prac_rol] | |
| | | | | author[prac_rol]/templateId | The use of templateId signals the imposition of a set of template-defined constraints. |
| | | | | author[prac_rol]/templateId/@root="1.2.36.1.2001.1001.102.101.100006" | |
| | | | | author[prac_rol]/templateId/@extension="1.0" | |
| | | | | author[prac_rol]/assignedAuthor | The use of templateId signals the imposition of a set of template-defined constraints. |
| | | | | author[prac_rol]/assignedAuthor/id | |
| PractitionerRole > identifier | Business identifiers for practitioner in a role. | 0..* | Identifier | author[prac_rol]/assignedAuthor/assignedPerson/ext:asEntityIdentifier | In CDA the identifier for both PractitionerRole and Practitioner for an author participation are expected to be included in /assignedPerson/ext:asEntityIdentifier. |
| | | | | | When sending to the My Health Record an HPI-I is expected. |
| | | | | | Cardinality of this element SHALL be interpreted as 1..*. |
| | | | | | See <Entity Identifier> for available attributes. |
| | | | | | Recommended mappings for the complex data type to CDA (R2): Identifier . |
| | | | | | |
| PractitionerRole > active | Whether this practitioner's record is in active use. | 0..1 | boolean | n/a | This logical element has no mapping to CDA. |
| Practitioner > period | The period during which the person is authorized to act as a practitioner in these role(s) for the organization. | 0..1 | Period | n/a | This logical element has no mapping to CDA. |
| PractitionerRole > practitioner | Practitioner that is able to provide the defined services for the organization. | 1..1 | DomainResource | author[prac_rol]/assignedAuthor/assignedPerson | assignedPerson SHALL conform to the template defined in assignedPerson (Practitioner with Mandatory Identifier) . |
| PractitionerRole > organization | The organization where the Practitioner performs the roles associated. | 0..1 | Reference(Organization as Base Organization) | author[prac_rol]/assignedAuthor/representedOrganization | representedOrganization SHALL conform to the template defined in representedOrganization (Base Organization) . |
| PractitionerRole > code | Roles which this practitioner is authorized to perform for the organization. | 0..* | code | author[prac_rol]/assignedAuthor/code | A code equivalent to the provider's professional role, e.g. 159011008 Community pharmacist is expected. See <code> for available attributes. Australian and New Zealand Standard Classification of Occupations (preferred) or Practitioner Role (preferred) ¹ |

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|---|---|------|---|---|--|
| PractitionerRole > specialty | Specific specialty of the practitioner. | 0..* | code | n/a | specialty is not currently mapped. |
| PractitionerRole > location | The location(s) at which this practitioner provides care. | 0..* | Reference(Location) | n/a | location is not currently mapped. |
| PractitionerRole > healthcareService | The list of healthcare services that this worker provides for this role's Organization/Location(s). | 0..* | Reference(Health-careService) | n/a | healthcareService is not currently mapped. |
| PractitionerRole > telecom | Contact details that are specific to the role/location/service. | 0..* | ContactPoint | author[prac_rol]/assignedAuthor/telecom | In CDA the telecom for both PractitionerRole and Practitioner for an author participation are expected to be included in //assignedAuthor/telecom. Recommended mappings for the complex data type to CDA (R2): ContactPoint . |
| PractitionerRole > availableTime | A collection of times that the Service Site is available. | 0..* | BackboneElement | n/a | availableTime is not currently mapped. |
| PractitionerRole > notAvailable | The HealthcareService is not available during this period of time due to the provided reason. | 0..* | string | n/a | notAvailable is not currently mapped. |
| PractitionerRole > availabilityExceptions | A description of site availability exceptions, e.g. public holiday availability. Succinctly describing all possible exceptions to normal site availability as details in the available Times and not available Times. | 0..1 | CodeableConcept | n/a | availabilityExceptions is not currently mapped. |

¹Note: The source representation of this terminology binding on code in PractitionerRole with Practitioner with Mandatory Identifier [DH2019e] is as an optional slice on the [coding](#) part of the code element. In the representation of the model presented in this specification it is normalised as a set of preferred bindings.

7.12 custodian (Organization with Mandatory Identifier)

CDA mapping

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|---|---|---|---------------------------------|--|--|
| Conformance level comes from linking elements | | | | | |
| Organization | A formally or informally recognized grouping of people or organizations formed for the purpose of achieving some form of collective action. Includes companies, institutions, corporations, departments, community groups, healthcare practice groups, etc. | Cardinality comes from linking elements | DomainResource | Context: Comes from linking elements | |
| | | | | custodian[org] | |
| | | | | custodian[org]/templateId | The use of templateId signals the imposition of a set of template-defined constraints. |
| | | | | custodian[org]/templateId/@root="1.2.36.1.2001.1001.102.101.100002" | |
| | | | | custodian[org]/templateId/@extension="1.0" | |
| | | | | custodian[org]/assignedCustodian | |
| | | | | custodian[org]/assignedCustodian/representedCustodianOrganization | |
| Organization > identifier | Identifier for the organization that is used to identify the organization across multiple disparate systems. | 1..* | Identifier | custodian[org]/assignedCustodian/representedCustodianOrganization/id | Optional CDA element. See <id> for available attributes. |
| | | | | | When sending to the My Health Record an HPI-O is expected. |
| | | | | | See <Entity Identifier> for available attributes. |
| Organization > active | Whether the organization's record is still in active use. | 0..1 | boolean | n/a | This logical element has no mapping to CDA. |
| Organization > type | The kind(s) of organization that this is. | 0..1 | CodeableConcept | n/a | This logical element has no mapping to CDA. |
| Organization > name | A name associated with the organization. | 0..1 | string | custodian[org]/assignedCustodian/representedCustodianOrganization/name | In CDA name and alias are represented by //represented-CustodianOrganization/name. |
| Organization > alias | A list of alternate names that the organization is known as, or was known as in the past. | 0..* | string | n/a | This logical element has no mapping to CDA. |
| Organization > telecom | A contact detail for the organization. | 0..* | ContactPoint | custodian[org]/assignedCustodian/representedCustodianOrganization/telecom | In CDA the maximum occurrences of representedCustodianOrganization/telecom is 1. Although the model indicates that telecom is 0..*, in a CDA implementation this is limited to 0..1. telecom/@use is Organization Telecom Use HL7 V3 (required) . Recommended mappings for the complex data type to CDA (R2): ContactPoint . |

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|---------------------------------|---|------|--|--|--|
| Organization > address | An address for the organization. | 0..* | Address | custodian[org]/assignedCustodian/representedCustodianOrganization/addr | <p>addr/@use is Organization Address Use HL7 V3 (required).</p> <p>In CDA the maximum occurrences of representedCustodianOrganization/addr is 1. Although the model indicates that address is 0..*, in a CDA implementation this is limited to 0..1.</p> <p>Recommended mappings for the complex data type to CDA (R2): Address Address as Australian Address.</p> |
| Organization > partOf | The organization of which this organization forms a part. | 0..1 | Reference(Organization as Base Organization) | n/a | This logical element has no mapping to CDA. |
| CDA Header Data Elements | | | | | Context: /ClinicalDocument/ |
| Organization > contact | Contact for the organization for a certain purpose. | 0..* | BackboneElement | participant[org_contact] | participant[org_contact] SHALL conform to the template defined in participant (Organization contact) . |

8 Entity CDA templates

This chapter contains mapping from the Individual (e.g. Patient with Mandatory Identifier) and Entity (e.g. Organization with Mandatory Identifier) models to CDA entity classes, expressed as a series of CDA templates that describe how each CDA entity is composed.

CDA templates are expected to be reused from one document type (or Composition model) to another. Each CDA template is presented under a heading in the format of "CDA schema element" ("model name") where "CDA schema element" is the root element for a CDA template and "model name" is the name of a model that constrains an element in the Advance Care Directive Custodian Record hierarchy.

8.1 providerOrganization (Base Organization)

CDA mapping

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|---|---|---|---------------------------------|--|--|
| Conformance level comes from linking elements | | | | Context: Comes from linking elements | |
| Organization | A formally or informally recognized grouping of people or organizations formed for the purpose of achieving some form of collective action. Includes companies, institutions, corporations, departments, community groups, healthcare practice groups, etc. | Cardinality comes from linking elements | DomainResource | providerOrganization[manag_org] | The organization SHALL at least have an identifier (providerOrganization[manag_org]/ext:asEntityIdentifier) or a name (providerOrganization[manag_org]/name). |
| | | | | providerOrganization[manag_org]/templateId | The use of templateId signals the imposition of a set of template-defined constraints. |
| | | | | providerOrganization[manag_org]/templateId/@root="1.2.36.1.2001.1001.102.101.100034" | |
| | | | | providerOrganization[manag_org]/templateId/@extension="1.0" | |
| | | | | providerOrganization[manag_org]/id | Optional CDA element. See <id> for available attributes. |
| Organization > identifier | Identifier for the organization that is used to identify the organization across multiple disparate systems. | 0..* | Identifier | providerOrganization[manag_org]/ext:asEntityIdentifier | See <Entity Identifier> for available attributes. Recommended mappings for the complex data type to CDA (R2): Identifier . |
| Organization > active | Whether the organization's record is still in active use. | 0..1 | boolean | n/a | This logical element has no mapping to CDA. |
| Organization > type | The kind(s) of organization that this is. | 0..1 | CodeableConcept | providerOrganization[manag_org]/standardIndustryClassCode | See <code> for available attributes. OrganizationType (example) |
| Organization > name | A name associated with the organization. | 0..1 | string | providerOrganization[manag_org]/name | In CDA name and alias are represented by //representedOrganization/name. |

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|---------------------------------|---|------|--|--|--|
| Organization > alias | A list of alternate names that the organization is known as, or was known as in the past. | 0..* | string | providerOrganization[manag_org]/name | In CDA name and alias are represented by //representedOrganization/name. |
| Organization > telecom | A contact detail for the organization. | 0..* | ContactPoint | providerOrganization[manag_org]/telecom | telecom/@use is Organization Telecom Use HL7 V3 (required) . Recommended mappings for the complex data type to CDA (R2): ContactPoint . |
| Organization > address | An address for the organization. | 0..* | Address | providerOrganization[manag_org]/addr | addr/@use is Organization Address Use HL7 V3 (required) . Recommended mappings for the complex data type to CDA (R2): Address Address as Australian Address . |
| Organization > partOf | The organization of which this organization forms a part. | 0..1 | Reference(Organization as Base Organization) | providerOrganization[manag_org]/asOrganizationPartOf providerOrganization[manag_org]/asOrganizationPartOf/wholeOrganization | The organization SHALL have at least a name (//wholeOrganization/name) or an identifier (//wholeOrganization/ext:asEntityIdentifier). Organization > partOf template is not currently defined. |
| CDA Header Data Elements | | | | Context: /ClinicalDocument/ | |
| Organization > contact | Contact for the organization for a certain purpose. | 0..* | BackboneElement | participant[org_contact] | participant[org_contact] SHALL conform to the template defined in participant (Organization contact) . |

8.2 participant (Organization contact)

CDA mapping

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|---|---|---|---------------------------------|--|---|
| CDA Header Data Elements | | | | Context: /ClinicalDocument/ | |
| Organization > contact | Contact for the organization for a certain purpose. | Cardinality comes from linking elements | BackboneElement | participant[org_contact] | |
| | | | | participant[org_contact]/@typeCode="IND" | |
| | | | | participant[org_contact]/templateId | The use of templateId signals the imposition of a set of template-defined constraints. |
| | | | | participant[org_contact]/templateId/@root="1.2.36.1.2001.1001.102.101.100035" | |
| | | | | participant[org_contact]/templateId/@extension="1.0" | |
| | | | | participant[org_contact]/associatedEntity | |
| | | | | participant[org_contact]/associatedEntity/@classCode="CON" | |
| | | | | participant[org_contact]/associatedEntity/scopingOrganization | |
| | | | | participant[org_contact]/associatedEntity/scopingOrganization/@classCode="ORG" | Optional CDA element. |
| | | | | participant[org_contact]/associatedEntity/scopingOrganization/id | Organization > contact is represented in CDA by a participant that is scoped by the Organization for which they are a contact. This SHALL hold the same value as the organization this is a contact for (the value in this id element SHALL be present in a separate participation). |
| Organization > contact > purpose | Indicates a purpose for which the contact can be reached. | 0..1 | CodeableConcept | participant[org_contact]/associatedEntity/code | See code for available attributes. ContactEntityType (extensible) |
| Organization > contact > name | A name associated with the contact. | 0..1 | HumanName | participant[org_contact]/associatedEntity/associatedPerson | |
| | | | | participant[org_contact]/associatedEntity/associatedPerson/name | Recommended mappings for the complex data type to CDA (R2): HumanName . |
| Organization > contact > telecom | A contact detail (e.g. a telephone number or an email address) by which the party may be contacted. | 0..* | ContactPoint | participant[org_contact]/associatedEntity/telecom | telecom/@use is Organization Telecom Use HL7 V3 (required) . Recommended mappings for the complex data type to CDA (R2): ContactPoint . |
| Organization > contact > address | Visiting or postal addresses for the contact. | 0..1 | Address | participant[org_contact]/associatedEntity/addr | Recommended mappings for the complex data type to CDA (R2): Address Address as Australian Address . |

8.3 representedOrganization (Base Organization)

CDA mapping

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|---|---|---|--|---|--|
| Conformance level comes from linking elements | | Context: Comes from linking elements | | | |
| Organization | A formally or informally recognized grouping of people or organizations formed for the purpose of achieving some form of collective action. Includes companies, institutions, corporations, departments, community groups, healthcare practice groups, etc. | Cardinality comes from linking elements | DomainResource | representedOrganization | The organization SHALL have at least name (//representedOrganization/name) or an identifier (//representedOrganization/ext:asEntityIdentifier) instantiated. |
| | | | | representedOrganization/templateId | The use of templateId signals the imposition of a set of template-defined constraints. |
| | | | | representedOrganization/templateId/@root="1.2.36.1.2001.1001.102.101.100039" | |
| | | | | representedOrganization/templateId/@extension="1.0" | |
| | | | | representedOrganization/id | See < id > for available attributes. |
| Organization > identifier | Identifier for the organization that is used to identify the organization across multiple disparate systems. | 0..* | Identifier | representedOrganization/ext:asEntityIdentifier | See < Entity Identifier > for available attributes. Recommended mappings for the complex data type to CDA (R2): Identifier . |
| Organization > active | Whether the organization's record is still in active use. | 0..1 | boolean | n/a | This logical element has no mapping to CDA. |
| Organization > type | The kind(s) of organization that this is. | 0..1 | CodeableConcept | representedOrganization/standardIndustryClassCode | See < code > for available attributes. OrganizationType (example) |
| Organization > name | A name associated with the organization. | 0..1 | string | representedOrganization/name | In CDA name and alias are represented by //representedOrganization/name. |
| Organization > alias | A list of alternate names that the organization is known as, or was known as in the past. | 0..* | string | representedOrganization/name | In CDA name and alias are represented by //representedOrganization/name. |
| Organization > telecom | A contact detail for the organization. | 0..* | ContactPoint | representedOrganization/telecom | telecom/@use is Organization Telecom Use HL7 V3 (required) . Recommended mappings for the complex data type to CDA (R2): ContactPoint . |
| Organization > address | An address for the organization. | 0..* | Address | representedOrganization/addr | addr/@use is Organization Address Use HL7 V3 (required) . Recommended mappings for the complex data type to CDA (R2): Address Address as Australian Address . |
| Organization > partOf | The organization of which this organization forms a part. | 0..1 | Reference(Organization as Organization Base) | representedOrganization/asOrganizationPartOf | The organization SHALL have at least a name (//wholeOrganization/name) or an identifier (//wholeOrganization/ext:asEntityIdentifier). |
| | | | | representedOrganization/asOrganizationPartOf/wholeOrganization | Organization > partOf template is not currently defined. |

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|--|---|-----------------------------|---------------------------------|--|--|
| CDA Header Data Elements | | Context: /ClinicalDocument/ | | | |
| Organization > contact | Contact for the organization for a certain purpose. | 0..* | BackboneElement | participant[org_contact] | participant[org_contact] SHALL conform to the template defined in participant (Organization contact) . |

8.4 assignedPerson (Practitioner with Mandatory Identifier)

CDA mapping

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|---|--|---|--------------------------------|---|---|
| Conformance level comes from linking elements | | Context: Comes from linking elements | | | |
| Practitioner | A person who is directly or indirectly involved in the provisioning of healthcare. | Cardinality comes from linking elements | DomainResource | assignedPerson[prac] | |
| | | | | assignedPerson[prac]/templateId | The use of templateId signals the imposition of a set of template-defined constraints. |
| | | | | assignedPerson[prac]/templateId/@root="1.2.36.1.2001.1001.102.101.100040" | |
| | | | | assignedPerson[prac]/templateId/@extension="1.0" | |
| | | | | assignedPerson[prac]/id | See < id > for available attributes. |
| Practitioner > identifier | An identifier that applies to this person in this role. | 1..* | Identifier | assignedPerson[prac]/ext:asEntityIdentifier | When sending to the My Health Record an HPI-I is expected. See < Entity Identifier > for available attributes. Recommended mappings for the complex data type to CDA (R2): Identifier . |
| Practitioner > active | Whether this practitioner's record is in active use. | 0..1 | boolean | n/a | This logical element has no mapping to CDA. |
| Practitioner > name | The name(s) associated with the practitioner. | 0..* | HumanName | assignedPerson[prac]/name | Recommended mappings for the complex data type to CDA (R2): HumanName . |
| Practitioner > telecom | A contact detail for the practitioner, e.g. a telephone number or an email address. | 0..* | ContactPoint | telecom | Recommended mappings for the complex data type to CDA (R2): ContactPoint . |
| Practitioner > address | Address(es) of the practitioner that are not role specific (typically home address). Work addresses are not typically entered in this property as they are usually role dependent. | 0..* | Address | addr | Recommended mappings for the complex data type to CDA (R2): Address Address as Australian Address . |
| Practitioner > gender | Administrative Gender - the gender that the person is considered to have for administration and record keeping purposes. | 0..1 | code | assignedPerson[prac]/ext:administrativeGenderCode | See < code > for available attributes. AdministrativeGender (required) |
| Practitioner > birthDate | The date of birth for the practitioner. | 0..1 | date | assignedPerson[prac]/ext:birthTime | See < time > for available attributes. |

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|-------------------------------------|--|------|---------------------------------|--|--|
| Practitioner > qualification | Qualifications obtained by training and certification. | 0..* | BackboneElement | See: instantiation choices | <p>It is possible that the qualification may be able to be captured as a complex structure or as a text list.</p> <p>instantiation choices:</p> <p>If the qualification or list of qualifications is the result of capturing a text field then this element is expected to be as //assignedPerson[prac]/ext:Qualifications/@classCode="QUAL". See <Qualification> for available attributes.</p> <p>If more information can be captured than a narrative list then this logical element is expected to be instantiated as ext:coverage2[prac_qual] and SHALL conform to the template defined in ext:coverage (Practitioner qualification).</p> |
| Practitioner > communication | A language the practitioner is able to use in patient communication. | 0..* | CodeableConcept | assignedPerson[prac]/ext:languageCommunication | <p>See <code> for available attributes.</p> <p>Common Languages in Australia (extensible)</p> |

9 Section CDA templates

This chapter contains mapping from the section (e.g.) models to CDA section classes, expressed as a series of CDA templates that describe how each CDA section is composed.

CDA templates are expected to be reused from one document type (or Composition model) to another. Each CDA template is presented under a heading in the format of "CDA schema element" ("model name") where "CDA schema element" is the root element for a CDA template and "model name" is the name of a model that constrains an element in the Advance Care Directive Custodian Record hierarchy.

9.1 section (Advance Care Directive Custodians)

CDA mapping

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|--|--|------|---------------------------------|--|---|
| CDA Body Level 3 Data Elements | | | | | |
| section (Advance Care Directive Custodians) | A section that contains details pertaining to the custodians of an individual's advance care directive. | 1..1 | BackboneElement | section | The use of templateId signals the imposition of a set of template-defined constraints. |
| | | | | section/templateId | |
| | | | | section/templateId/@root="1.2.36.1.2001.1001.102.101.100045" | |
| | | | | section/templateId/@extension="1.0" | |
| section (Advance Care Directive Custodians) > title | The label for this particular section. This will be part of the rendered content for the document, and is often used to build a table of contents. | 1..1 | string | section/title | |
| section (Advance Care Directive Custodians) > code | A code identifying the kind of content contained within the section. This must be consistent with the section title. | 1..1 | CodeableConcept | section/code | |
| | | | | section/code/@code="101.16694" | |
| | | | | section/code/@codeSystem="1.2.36.1.2001.1001.101" | |
| | | | | section/code/@codeSystemName | Optional CDA element. codeSystemName SHOULD be "NCTIS Data Components". |
| | | | | section/code/@displayName | Optional CDA element. displayName SHOULD be "Advance Care Directive Custodian Entries". |

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|---|--|------|---|--|--|
| section (Advance Care Directive Custodians) > text | A human-readable narrative that contains the attested content of the section, used to represent the content of the resource to a human. The narrative need not encode all the structured data, but is required to contain sufficient detail to make it 'clinically safe' for a human to just read the narrative. | 1..1 | narrative | section/text | See CDA narratives . |
| section (Advance Care Directive Custodians) > entry (Advance Care Directive Custodian Entry) | A reference to the actual resource from which the narrative in the section is derived. | 1..* | Reference(Practitioner as Base Practitioner Patient as Base Patient RelatedPerson as Base RelatedPerson Organization as) | section/entry[acdr] section/entry[acdr]/act | act SHALL conform to the template defined in act (Advance Care Directive Custodian Entry) . |

10 Act CDA templates

This chapter contains mapping from the Composition (Advance Care Directive Custodian Record) model and entry (e.g. Advance Care Directive Custodian Entry) models to CDA act classes, expressed as a series of CDA templates that describe how each CDA act is composed.

CDA templates are expected to be reused from one document type (or Composition model) to another. Each CDA template is presented under a heading in the format of "CDA schema element" ("model name") where "CDA schema element" is the root element for a CDA template and "model name" is the name of a model that constrains an element in the Advance Care Directive Custodian Record hierarchy.

10.1 act (Advance Care Directive Custodian Entry)

CDA mapping

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|--------------------------------|--|---|---|--|---|
| CDA Body Level 3 Data Elements | | | | Context: Comes from linking elements | |
| entry | A reference to the actual resource from which the narrative in the section is derived. | Cardinality comes from linking elements | Reference(Practitioner Patient as Base Patient RelatedPerson as Base RelatedPerson) | act | |
| | | | | act/templateId | The use of templateId signals the imposition of a set of template-defined constraints. |
| | | | | act/templateId/@root="1.2.36.1.2001.1001.102.101.100046" | |
| | | | | act/templateId/@extension="1.0" | |
| | | | | act/id | Optional CDA element. |
| | | | | act/code | |
| | | | | act/code/@code | |
| | | | | act/code/@codeSystem="1.2.36.1.2001.1001.101" | |
| | | | | act/code/@codeSystemName | Optional CDA element. codeSystemName SHOULD be "NCTIS Data Components". |
| | | | | act/code/@displayName | Optional CDA element. displayName SHOULD be "Advance Care Directive Custodian Entries". |
| | | | | act/participant | At least one (1..*) advance care directive custodians (act/participant) SHALL be instantiated. participant SHALL conform to the template defined in participant (Base Practitioner) or participant (Base Patient) or participant (Base RelatedPerson) or participant (Base Organization) . |

10.2 ext:coverage (Practitioner qualification)

CDA mapping

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|--|---|---|---------------------------------|--|--|
| CDA Header Data Elements | | | | | Context: /ClinicalDocument/component/structuredBody/component[admin_obs]/section/ See Administrative Observations . |
| Practitioner > qualification | Qualifications obtained by training and certification. | Cardinality comes from linking elements | BackboneElement | ext:coverage2[prac_qual] | |
| | | | | ext:coverage2[prac_qual]/@typeCode="COVBY" | |
| | | | | ext:coverage2[prac_qual]/templateId | The use of templateId signals the imposition of a set of template-defined constraints. |
| | | | | ext:coverage2[prac_qual]/templateId/@root="1.2.36.1.2001.1001.102.101.100038" | |
| | | | | ext:coverage2[prac_qual]/templateId/@extension="1.0" | |
| | | | | ext:coverage2[prac_qual]/ext:entitlement | |
| | | | | ext:coverage2[prac_qual]/ext:entitlement/@classCode="COV" | |
| | | | | ext:coverage2[prac_qual]/ext:entitlement/@moodCode="EVN" | |
| | | | | ext:coverage2[prac_qual]/ext:entitlement/ext:participant[prac] | |
| | | | | ext:coverage2[prac_qual]/ext:entitlement/ext:participant[prac]/@typeCode="HLD" | |
| | | | | ext:coverage2[prac_qual]/ext:entitlement/ext:participant[prac]/ext:participantRole | |
| | | | | ext:coverage2[prac_qual]/ext:entitlement/ext:participant[prac]/ext:participantRole/@classCode="ASSIGNED" | |
| | | | | ext:coverage2[prac_qual]/ext:entitlement/ext:participant[prac]/ext:participantRole/ext:id | Practitioner > qualification is represented in CDA by an entitlement (qualification) held by a participant (practitioner). This SHALL hold the same value as practitioner that this qualification is associated with (the value in this id element SHALL be present in separate participation). |
| Practitioner > qualification > identifier | An identifier that applies to this person's qualification in this role. | 0..* | Identifier | ext:coverage2[prac_qual]/ext:entitlement/ext:id | |
| Practitioner > qualification > code | Coded representation of the qualification. | 1..1 | CodeableConcept | ext:coverage2[prac_qual]/ext:entitlement/ext:code | See <code> for available attributes. v2 table 0360, Version 2.7 (example) |
| Practitioner > qualification > period | Period during which the qualification is valid. | 0..1 | Period | ext:coverage2[prac_qual]/ext:entitlement/ext:effectiveTime | |

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|--|---|------|--|--|---|
| Practitioner > qualification > issuer | Organization that regulates and issues the qualification. | 0..1 | Reference(Organization as Base Organization) | ext:coverage2[prac_qual]/ext:entitlement/ext:participant[issuer] | ext:participant[issuer]/@typeCode SHALL be "AUT". ext:participant[issuer]/ext:participantRole SHALL be "COMPAR". |

11 Common patterns

11.1 code

The <code> element pattern refines the kind of act being recorded. It is of data type CD CWE (Concept Descriptor, Coded With Extensibility). It may have:

- a null attribute (*nullFlavor*)
- *originalText*
- *code* and *codeSystem*
- *qualifier* (CD)
- *translation* (CD)
- any combination of the above.

A *displayName* is highly recommended.

Where used, the *code* attribute **SHALL** contain a code from the relevant vocabulary.

Where used, the *codeSystem* attribute **SHALL** contain the OID for the relevant vocabulary. Values for coding systems can be obtained from the HL7 OID registry accessible from the HL7 home web page at www.hl7.org.

Where used, the *displayName* attribute **SHALL** contain a human-readable description of the code value that is provided by the code system; *displayName* is a case insensitive value except where explicitly stated otherwise by the code system. A preferred interface term for display that is not a member of the description set supplied by the code system **SHALL NOT** be used to populate the *displayName* attribute.

The *codeSystemName* **MAY** be present and, where used, **SHALL** contain a human-readable name for the coding system.

Where used, the *originalText* element **SHALL** be used to carry the full text associated with this code as selected by, typed by or displayed to the author of this statement including the contents of the *qualifier* if present.

Where used, the *qualifier* element **SHALL** carry a code from the same code system as the code; for example if the main concept code is from SNOMED CT the *qualifier* also has to be taken from SNOMED CT as the use of a different code system for a *qualifier* is not allowed. The use of the *qualifier* element is governed by the code system used and cannot be used with code systems that do not provide for qualifiers (e.g. pre-coordinated systems).

Codes can be obtained from a variety of sources. Additional vocabularies are also available from the HL7 Version 3 Vocabulary tables, available to HL7 members through the HL7 web site. In some cases, the vocabularies have been specified; in others, a particular code has been fixed or there is no vocabulary specified. For guidance on coding common clinical concepts in CDA documents see [Representing Coding in CDA Documents Implementation Guidance \[NEHT2011bv\]](#).

Where a code is used from a different code system to that specified, or where the code lies outside the reference set specified, or where a code system or reference set is not specified, the code value **SHALL** be consistent with the meaning of the associated element of the Advance Care Directive Custodian Record model.

If a vocabulary is specified in this implementation guide and no suitable code can be found, the *originalText* element **SHALL** be used to carry the full text as selected by, typed by or displayed to the author of this statement.

If a vocabulary is specified in this implementation guide and it is not possible to use this vocabulary, but an alternate vocabulary is in use, the *originalText* element **SHALL** be used to carry the full text as selected by, typed by or displayed to the author of this statement. The *code* element **SHALL** be used to carry the relevant information from the alternate vocabulary and the alternate vocabulary **SHALL** be registered with HL7 and allocated an appropriate OID.

If an alternate vocabulary is in use and a translation into the specified code system is available, the *originalText* element **SHALL** be used to carry the full text as selected by, typed by or displayed to the author of this statement. The *code* element **SHALL** be used to carry the relevant information from the alternate vocabulary and the alternate vocabulary **SHALL** be registered with HL7 and allocated an appropriate OID. The *translation* element **SHALL** be used to indicate the translation code from the specified vocabulary.

Example 11.1. code

```
<!-- Specified code system in use -->
<code
  code="271807003"
  codeSystem="2.16.840.1.113883.6.96"
  codeSystemName="SNOMED CT"
  codeSystemVersion="20101130"
  displayName="Skin rash" />

<!-- Specified code system in use with a qualifier -->
<code
  code="23986001"
  codeSystem="2.16.840.1.113883.6.96"
  codeSystemName="SNOMED CT"
  displayName="Glaucoma" >
  <originalText>Glaucoma, left</originalText>
  <qualifier>
    <name
      code="272741003"
      codeSystem="2.16.840.1.3883.6.96"
      codeSystemName="SNOMED CT"
      displayName="Laterality" />
    <value
      code="7771000"
      codeSystem="2.16.840.1.113883.6.96"
      codeSystemName="SNOMED CT"
      displayName="Left"
      xsi:type="CD" />
  </qualifier>
</code>
```

```
<!-- Alternate code system in use and a translation into the specified code system is available -->
<code
  code="J45.9"
  codeSystem="2.16.840.1.113883.6.135"
  codeSystemName="icd10am"
  displayName="Asthma, unspecified">
  <originalText>Asthma</originalText>
  <translation
    code="195967001"
    codeSystem="2.16.840.1.113883.6.96"
    codeSystemName="SNOMED CT"
    displayName="Asthma"/>
</code>

<!-- Alternate code system in use and no translation into the specified code system is available -->
<code
  code="J45.9"
  codeSystem="2.16.840.1.113883.6.135"
  codeSystemName="icd10am"
  displayName="Asthma, unspecified">
  <originalText>Asthma</originalText>
</code>

<!-- No suitable code can be found or there is no code system in use -->
<code
  <originalText>Asthma</originalText>
</code>
```

11.2 id

The <id> element pattern is of data type II (Instance Identifier). The II data type may have:

- a null attribute (*nullFlavor*)
- a *root*
- a *root* and an *extension*
- a *root* and an *extension* and an *assigningAuthorityName*
- a *root* and an *assigningAuthorityName*
- a *root* and an *assigningAuthorityName* and a *displayable*
- a *root* and an *extension* and a *displayable*
- a *root* and an *extension* and an *assigningAuthorityName* and a *displayable*
- a *root* and a *displayable*

The root attribute is **REQUIRED** and is a unique identifier that guarantees the global uniqueness of the instance identifier. The root alone **MAY** be the entire instance identifier. The root attribute **SHALL** be a UUID or OID.

The extension attribute **MAY** be present, and is a character string as a unique identifier within the scope of the identifier root.

In the case of business or technical identifier an *assigningAuthorityName* is **RECOMMENDED**.

Identifiers appear in this implementation guide for two different reasons. The first is that the identifier has been identified as relevant to the business process or clinical workflow. These identifiers are documented in mapping tables in the Element column, e.g. Composition > identifier or Medication Statement (Prescription) > identifier, which make clear the meaning of this identifier.

In addition, the implementation makes clear that identifiers may also be found on many other parts of the CDA structure. These identifiers, often referred to as technical identifiers, are allowed to facilitate record matching across multiple versions of related documents, so that the same record can consistently be identified, in spite of variations in the information as the record passes through time or between systems. These identifiers have no meaning in the business specification. If senders provide one of these identifiers, it **SHALL** always be the same identifier in all versions of the record, and it **SHALL** be globally unique per the rules of the II data type.

Example 11.2. id

```
<id root="2.16.840.1.113883.19" extension="123A45" />  
<ext:id assigningAuthorityName="HPI-O" root="1.2.36.1.2001.1003.0.8003621566684455" />
```

11.3 time

When a time value is supplied it **SHALL** include hours and minutes.

When a time value is supplied it **MAY** include seconds and fractions of seconds.

When a time value is supplied it **SHALL** include a time zone.

The <time> element pattern is of data type TS (Point in Time) and can also be an interval between two times (IVL_TS), representing a period of time. Both forms can either have a nullFlavor attribute or child components following allowed patterns.

A simple timestamp (point in time) will only contain a value attribute containing the time value, expressed as a series of digits as long as required or as available.

Example 11.3. Simple timestamp

```
<time value="20091030" />
```

This represents "October 30, 2009" to calendar day precision. In cases where the containing element is defined in the CDA schema as "ANY" data type, it is useful to provide an xsi:type attribute, set to the value "TS".

The period of time pattern is defined in terms of one or both of its lowest and highest values. The low and high elements are instances of the timestamp pattern described above. More complex time period concepts can be expressed by combining a high, low, or centre element with a width element.

Example 11.4. Low time

```
<period>
  <low value="20091030" />
</period>
```

This represents "a period after October 30, 2009". In cases where the containing element is defined in the CDA schema as "ANY" data type, it is useful to provide an xsi:type attribute, set to the value "IVL_TS", as in the next example.

Example 11.5. Interval timestamp 1

```
<period xsi:type="IVL_TS">
  <high value="200910301030+1000" />
</period>
```

This represents "a period before 10:30 a.m. UTC+10, October 30, 2009". A discretionary xsi:type attribute has been provided to explicitly cast the pattern to "IVL_TS".

Example 11.6. Interval timestamp 2

```
<period xsi:type="IVL_TS">
  <low value="2007" />
  <high value="2009" />
</period>
```

This represents "the calendar years between 2007 and 2009". The low element **SHALL** precede the high element. As per the previous example, a discretionary xsi:type attribute has been provided to explicitly cast the pattern to "IVL_TS".

Example 11.7. Width time

```
<period>
  <high value="20091017" />
  <width value="2" unit="wk" />
</period>
```

This expresses "two weeks before October 17th, 2009". A low value can be derived from this.

11.4 Entity Identifier

CDA mapping

| Element | Definition | Card | CDA schema element | Constraints and comments |
|--------------------------|--|---|---|--|
| CDA Data Elements | | | | |
| Entity Identifier | A number or code issued for the purpose of identifying a participant within a health-care context. | The cardinality of the element comes from the linking parent. | //ext:asEntityIdentifier | |
| | | 1..1 | //ext:asEntityIdentifier/@classCode="IDENT" | |
| | | 1..1 | //ext:asEntityIdentifier/ext:id | |
| | | 1..1 | //ext:asEntityIdentifier/ext:id/@root | @root SHALL be an OID and SHALL NOT be a UUID. @root SHALL be a globally unique object identifier (i.e. OID) that identifies the combination of geographic area, issuer and type. If no such OID exists, it SHALL be defined before any identifiers can be created. |
| | | 0..1 | //ext:asEntityIdentifier/ext:id/@extension | If present, @extension SHALL be a unique identifier within the scope of the root that is populated directly from the designation. |
| | | 0..1 | //ext:asEntityIdentifier/ext:id/@assigningAuthorityName | @assigningAuthorityName SHOULD be used and, if it is used, SHALL be a human-readable name for the namespace represented in the root that is populated with the issuer, or identifier type, or a concatenation of both as appropriate. This SHOULD NOT be used for machine readability purposes. |
| | | 0..1 | //ext:asEntityIdentifier/ext:code | See < code > for available attributes. |
| | | 0..1 | //ext:asEntityIdentifier/ext:assigningGeographicArea | |
| | | 1..1 | //ext:asEntityIdentifier/ext:assigningGeographicArea/@classCode="PLC" | |
| | | 0..1 | //ext:asEntityIdentifier/ext:assigningGeographicArea/ext:name | If present, ext:name SHALL be the range and extent that the identifier applies to the object with which it is associated that is populated directly from the geographic area. This SHOULD NOT be used for machine readability purposes. Healthcare Identifier Geographic Area (preferred) This element is expected to be populated with the display, e.g. "National Identifier". |

Example 11.8. Entity Identifier

```
<!-- These example fragments are illustrative only. They cannot be treated as clinically valid.  
While every effort has been taken to ensure that the examples are consistent with the message specification, where  
there are conflicts with the written message specification or schema, the specification or schema will take precedence. -->  
  
<!-- person -->  
<x:asEntityIdentifier classCode="IDENT">  
  <x:id root="1.2.36.1.2001.1003.0.8003608833357361" assigningAuthorityName="IHI" />  
  <x:assigningGeographicArea classCode="PLC">  
    <x:name>National Identifier</x:name>  
  </x:assigningGeographicArea>  
</x:asEntityIdentifier>  
  
<x:asEntityIdentifier classCode="IDENT">  
  <x:id root="1.2.36.1.2001.1005.29.8003621566684455" extension="542181" assigningAuthorityName="Croydon GP Centre" />  
  <x:code code="MP" codeSystem="2.16.840.1.113883.12.203" codeSystemName="Identifier Type (HL7)" />  
</x:asEntityIdentifier>  
  
<!-- organisation -->  
<ext:asEntityIdentifier classCode="IDENT">  
  <ext:id assigningAuthorityName="HPI-O" root="1.2.36.1.2001.1003.0.8003621566684455" />  
  <ext:assigningGeographicArea classCode="PLC">  
    <ext:name>National Identifier</ext:name>  
  </ext:assigningGeographicArea>  
</ext:asEntityIdentifier>
```

11.5 Personal Relationship

CDA mapping

| Element | Definition | Card | CDA schema element | Constraints and comments |
|--------------------------|---|---|---|---|
| CDA Data Elements | | | | |
| Personal Relationship | The relationship of a participant to a subject of care (patient). | The cardinality of the element comes from the linking parent. | //ext:personalRelationship | This logical data component SHALL NOT be instantiated if the participant is a healthcare provider. If ext:personalRelationship is instantiated the value of Entity Identifier SHALL NOT be a HPI-I. |
| | | 0..1 | //ext:personalRelationship/@classCode="PRS" | |
| | | 0..1 | //ext:personalRelationship/ext:id | |
| | | 1..1 | //ext:personalRelationship/ext:code | See <code> for available attributes. Related Person Relationship Type (extensible) |
| | | 0..1 | //ext:personalRelationship/ext:statusCode | See <code> for available attributes. v3 Code System RoleStatus (required) |
| | | 0..1 | //ext:personalRelationship/ext:effectiveTime | See <time> for available attributes. |
| | | 1..1 | //ext:personalRelationship/ext:asPersonalRelationship | |
| | | 0..1 | //ext:personalRelationship/ext:asPersonalRelationship/@classCode="PSN" | |
| | | 0..1 | //ext:personalRelationship/ext:asPersonalRelationship/@determinerCode="INSTANCE" | |
| | | 1..1 | //ext:personalRelationship/ext:asPersonalRelationship/id | This SHALL hold the same value as /ClinicalDocument/recordTarget/patientRole/id. |
| | | 1..1 | //ext:personalRelationship/ext:asPersonalRelationship/administrativeGenderCode/@nullFlavor="NA" | Included for CDA conformance only. |

Example 11.9. Personal Relationship

```
<!-- These example fragments are illustrative only. They cannot be treated as clinically valid.  
While every effort has been taken to ensure that the examples are consistent with the message specification, where  
there are conflicts with the written message specification or schema, the specification or schema will take precedence. -->  
  
<!-- patient -->  
<recordTarget>  
  <patientRole>  
    <!-- patient identifier-->  
    <id extension="100543" root="2.16.840.1.113883.19.1.2.3.4"/>  
  </patientRole>  
</recordTarget>  
  
<!-- author with personal relationship -->  
<author>  
  <time value="200911031647+1000"/>  
  <assignedAuthor>  
    <!-- author identifier-->  
    <id root="86d729b8-72d2-460a-a64c-489a51607450"/>  
    <assignedPerson>  
      <!-- personal relationship -->  
      <ext:personalRelationship>  
        <!--relationship-->  
        <ext:code code="SIGOTHR" codeSystem="2.16.840.1.113883.5.111" codeSystemName="v3 Code System RoleCode" displayName="significant other" />  
        <!--patient-->  
        <ext:asPersonalRelationship>  
          <!-- patient identifier-->  
          <id extension="100543" root="2.16.840.1.113883.19.1.2.3.4"/>  
          <administrativeGenderCode nullFlavor="NA" />  
        </ext:asPersonalRelationship>  
      </ext:personalRelationship>  
    </assignedPerson>  
  </assignedAuthor>  
</author>  
  
<!-- participant performer with personal relationship -->  
<participant typeCode="PRF">  
  <associatedEntity classCode="ASSIGNED">  
    <!--participant performer identifier-->  
    <id root="f3351b5c-8a6c-437c-a55c-a6c121873456"/>  
    <!-- personal relationship -->  
    <associatedPerson>  
      <ext:personalRelationship>  
        <!--relationship-->  
        <ext:code code="FAMMEMB" codeSystem="2.16.840.1.113883.5.111" codeSystemName="v3 Code System RoleCode" displayName="Family Member" />  
        <!--patient-->  
        <ext:asPersonalRelationship>  
          <!-- patient identifier-->  
          <id extension="100543" root="2.16.840.1.113883.19.1.2.3.4"/>  
          <administrativeGenderCode nullFlavor="NA" />  
        </ext:asPersonalRelationship>  
      </ext:personalRelationship>  
    </associatedPerson>  
  </associatedEntity>  
</participant>
```

11.6 Qualification

CDA mapping

| Element | Definition | Card | CDA schema element | Constraints and comments |
|--------------------------|---|------|--|--|
| CDA Data Elements | | | | |
| Qualification | A list of professional certifications, and certificates recognising having passed a course. | 0..1 | //ext:asQualifications | |
| | | 1..1 | //ext:asQualifications/@classCode="QUAL" | |
| | | 1..1 | //ext:asQualifications/ext:code | Qualifications is a text field, so the text list is entered in the originalText of this element. |

Appendix A. Complex data type mappings to CDA (R2)

This informative appendix provides some guidance on how complex data types referred to in the body of this specification can map to CDA (R2). The mappings provided are a set of preferred mappings and do not represent conformance requirements.

A.1 Identifier

This informative appendix provides some guidance on how the complex data type [Identifier](#), referenced in the body of this specification can map to CDA (R2). The mappings provided are a set of preferred mappings and do not represent conformance requirements.

In addition to examples provided in this implementation guide some guidance on representation of common identifiers in CDA is provided by [Representation of Common Australian Identifiers in v2 and CDA \[HI2011\]](#) and [Common - Clinical Document \[DH2019a\]](#).

CDA mapping

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|-------------------------------|--|--|-------------------------|-----------------------------------|---|
| Identifier | A technical identifier - identifies some entity uniquely and unambiguously. | Cardinality comes from linking parent. | Element | See: instantiation choices | <p>In CDA it is possible that the identifier is formed such that the system and value are both part of the value of the root attribute. In this circumstance the extension attribute should not be instantiated.</p> <p>instantiation choices:</p> <p>If the identifier element is for a Patient, Practitioner, PractitionerRole, Organization, RelatedPerson or Device it is expected to be instantiated as //ext:asEntityIdentifier/@classCode="IDENT". See <Entity Identifier> for available attributes.</p> <p>The identifier element may be instantiated as //id.</p> |
| Identifier > use | The purpose of this identifier. | 0..1 | code | n/a | This logical element has no mapping to CDA. |
| Identifier > type | A coded type for the identifier that can be used to determine which identifier to use for a specific purpose. | 0..1 | code | //ext:asEntityIdentifier/ext:code | <p>Identifier Type Codes (extensible)</p> <p>This element is only available if the identifier is instantiated as //ext:asEntityIdentifier/@classCode="IDENT".</p> |
| Identifier > system | Establishes the namespace for the value - that is, a URL that describes a set values that are unique. | 0..1 | uri | See: instantiation choices | <p>instantiation choices:</p> <p>If the identifier element is for a Patient, Practitioner, PractitionerRole, Organization, RelatedPerson or Device this is expected to be instantiated as //ext:asEntityIdentifier/ext:id/@root.</p> <p>The identifier system may be instantiated as //id/@root.</p> |
| Identifier > value | The portion of the identifier typically relevant to the user and which is unique within the context of the system. | 0..1 | string | See: instantiation choices | <p>instantiation choices:</p> <p>If the identifier element is for a Patient, Practitioner, PractitionerRole, Organization, RelatedPerson or Device this is expected to be instantiated as //ext:asEntityIdentifier/ext:id/@extension.</p> <p>The identifier value may be instantiated as //id/@extension.</p> |
| Identifier > period | Time period during which identifier is/was valid for use. | 0..1 | Period | n/a | This logical element has no mapping to CDA. |

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|-----------------------|--|------|--|----------------------------|---|
| Identifier > assigner | Organization that issued/manages the identifier. | 0..1 | Reference (Organization) | See: instantiation choices | instantiation choices: If the identifier element is for a Patient, Practitioner, PractitionerRole, Organization, RelatedPerson or Device this is expected to be instantiated as //ext:asEntityIdentifier/ext:id/@assigningAuthorityName. The identifier value may be instantiated as //id/@assigningAuthorityName. |

Example A.1. Identifier

```
<!-- These example fragments are illustrative only. They cannot be treated as clinically valid.  
While every effort has been taken to ensure that the examples are consistent with the message specification, where  
there are conflicts with the written message specification or schema, the specification or schema will take precedence. -->  
  
<!-- subject -->  
<recordTarget>  
  <!-- subject (Patient) -->  
  <patientRole>  
    <patient>  
      <administrativeGenderCode></administrativeGenderCode>  
  
      <!-- Patient.identifier as an Australian IHI -->  
      <ext:asEntityIdentifier classCode="IDENT">  
        <!-- identifier.type.text=IHI,  
        identifier.value=8003600200002222,  
        identifier.system=http://ns.electronichealth.net.au/id/hi/ih/1.0 -->  
        <ext:id assigningAuthorityName="IHI" root="1.2.36.1.2001.0.8003600200002222" />  
        <ext:assigningGeographicArea classCode="PLC">  
          <ext:name>National Identifier</ext:name>  
        </ext:assigningGeographicArea>  
      </ext:asEntityIdentifier>  
  
      <!-- Patient.identifier as an Institution Medical Record-->  
      <ext:asEntityIdentifier classCode="IDENT">  
        <!-- identifier.assigner=Croydon GP Centre,  
        identifier.value=542181,  
        identifier.system=urn:oid:1.2.36.1.2001.1005.29.8003621566684455 -->  
        <ext:id root="1.2.36.1.2001.29.8003621566684455" extension="542181" assigningAuthorityName="Croydon GP Centre" />  
        <!-- Patient.identifier.type -->  
        <ext:code code="MR" codeSystem="2.16.840.1.113883.12.203" codeSystemName="Identifier Type (HL7)" />  
      </ext:asEntityIdentifier>  
  
      <!-- Patient.identifier as a Medicare Number -->  
      <ext:asEntityIdentifier classCode="IDENT">  
        <!-- identifier.system=urn:oid:1.2.36.1.5001.1.0.7,  
        identifier.value=123456789,  
        identifier.assigner=Medicare Card Number -->  
        <ext:id assigningAuthorityName="Medicare Card Number"  
          root="1.2.36.1.5001.1.0.7" extension="1234567892" />  
        <ext:code code="MO" codeSystem="2.16.840.1.113883.12.203"  
          codeSystemName="Identifier Type (HL7)" displayName="Patient's Medicare number" />  
        <!-- Identifier.period is not available in an asEntityIdentifier class -->  
      </ext:asEntityIdentifier>  
  
      <!-- Patient.identifier as a DVA Number -->  
      <ext:asEntityIdentifier classCode="IDENT">  
        <!-- identifier.system=urn:oid:2.16.840.1.113883.3.879.270091,  
        identifier.value=NBUR9080,  
        identifier.assigner=Department of Veterans' Affairs -->  
        <ext:id assigningAuthorityName="Department of Veterans' Affairs"  
          root="2.16.840.1.113883.3.879.270091" extension="NBUR9080" />  
        <ext:code code="DVG" codeSystem="2.16.840.1.113883.2.3.4.1.1.203"  
          codeSystemName="HL7V2Table0203IdentifierTypeAUExtended" displayName="DVA Gold Card Number" />  
        <!-- Identifier.period is not available in an asEntityIdentifier class -->  
      </ext:asEntityIdentifier>  
  
      <!-- Patient.identifier as a Healthcare card number -->  
      <ext:asEntityIdentifier classCode="IDENT">  
        <!-- identifier.system=urn:oid:2.16.840.1.113883.3.879.270098,
```

```
        identifier.value=307111942H,
        identifier.assigner=Centrelink customer reference number -->
<ext:id assigningAuthorityName="Centrelink customer reference number"
root="2.16.840.1.113883.3.879.270098" extension="307111942H"/>
<ext:code code="HC" codeSystem="2.16.840.1.113883.12.203"
codeSystemName="Identifier Type (HL7)" displayName="Health Card Number"/>
</ext:asEntityIdentifier>

    </patient>
</patientRole>
</recordTarget>

<author>
<time value="200911031647+1000"/>
<!-- author (PractitionerRole) --&gt;
&lt;assignedAuthor&gt;
    &lt;!-- PractitionerRole.id --&gt;
    &lt;id root="86d729b8-72d2-460a-a64c-489a51607450"/&gt;
    &lt;!-- PractitionerRole.practitioner(Practitioner) --&gt;
    &lt;assignedPerson&gt;
        &lt;!-- Practitioner.identifier as an Australian HPI-I --&gt;
        &lt;ext:asEntityIdentifier classCode="IDENT"&gt;
            &lt;!-- identifier.value=8003610537409456,
            identifier.system=urn:oid:1.2.36.1.2001.1003.0,
            identifier.assigner=HPI-I --&gt;
            &lt;ext:id assigningAuthorityName="HPI-I"
root="1.2.36.1.2001.1003.0.8003610537409456"/&gt;
            &lt;ext:assigningGeographicArea classCode="PLC"&gt;
                &lt;ext:name&gt;National Identifier&lt;/ext:name&gt;
            &lt;/ext:assigningGeographicArea&gt;
        &lt;/ext:asEntityIdentifier&gt;
    &lt;/assignedPerson&gt;
    &lt;!-- PractitionerRole.identifier as an ABN scoped provider identifier --&gt;
    &lt;ext:asEntityIdentifier classCode="IDENT"&gt;
        &lt;!-- identifier.value=8003610537409456,
        identifier.system=urn:oid:1.2.36.1.2001.1003.0,
        identifier.assigner=HPI-I --&gt;
        &lt;ext:id assigningAuthorityName="Albion Hospital",
root="1.2.36.1.2001.1005.70.51824753556"
extension="peterwinslow44"/&gt;
        &lt;!-- identifier.type --&gt;
        &lt;ext:code code="EI"
codeSystem="2.16.840.1.113883.18.108"
codeSystemName="v2 Identifier Type"
displayName="Employee number"/&gt;
    &lt;/ext:asEntityIdentifier&gt;
    &lt;/assignedPerson&gt;
&lt;/assignedAuthor&gt;
<!--PractitionerRole.organization (Organization)--&gt;
&lt;representedOrganization&gt;
    &lt;!-- Organization.name --&gt;
    &lt;name&gt;Albion Hospital&lt;/name&gt;
    &lt;!--Organization.identifier as an ABN--&gt;
    &lt;ext:asEntityIdentifier classCode="IDENT"&gt;
        &lt;!-- identifier.value=51824754455,
        identifier.system=urn:oid:1.2.36,
        identifier.assigner=ABN --&gt;
        &lt;ext:id root="1.2.36.51824754455" assigningAuthorityName="ABN"/&gt;
        &lt;!-- identifier.type --&gt;
        &lt;ext:code code="XX"
codeSystem="2.16.840.1.113883.12.203" /&gt;
    &lt;/ext:asEntityIdentifier&gt;
&lt;/representedOrganization&gt;</pre>
```

```
</author>

<custodian>
  <!-- custodian (Organization)-->
  <assignedCustodian>
    <representedCustodianOrganization>
      <!-- Organization.id-->
      <id root="d0455def-ff37-4ebe-97fb-52db7224b148"/>
      <!-- Organization.identifier as a Laboratory NATA Identifier -->
      <ext:asEntityIdentifier classCode="IDENT">
        <!-- identifier.system.value=urn:oid:1.2.36.1.2001.1005.12,
        identifier.value=2184,
        identifier.assigner=NATA -->
        <ext:id assigningAuthorityName="NATA"
          root="1.2.36.1.2001.1005.12" extension="2184"/>
        <!-- identifier.type -->
        <ext:code code="XX" codeSystem="2.16.840.1.113883.12.203"/>
      </ext:asEntityIdentifier>
    </representedCustodianOrganization>
  </assignedCustodian>
</custodian>

<!--DiagnosticReport.basedOn-->
<inFulfillmentOf typeCode="FLFS">
  <!--ProcedureRequest-->
  <order classCode="ACT" moodCode="RQO">
    <!-- ProcedureRequest.identifier
    identifier.system=urn:oid:1.2.36.1.2001.1005.52.8003621566684455, identifier.value=123451 -->
    <id extension="123451" root="1.2.36.1.2001.1005.52.8003621566684455" />
  </order>
</inFulfillmentOf>
```

A.2 HumanName

This informative appendix provides some guidance on how the complex data type [HumanName](#), referenced in the body of this specification can map to CDA (R2). The mappings provided are a set of preferred mappings and do not represent conformance requirements.

CDA mapping

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|------------------------------|---|--|-------------------------|--------------------|---|
| HumanName | A human's name with the ability to identify parts and usage. | Cardinality comes from linking parent. | Element | //name | Name SHALL have at least text or family or given instantiated. In CDA a full text representation of a name is not to be included in the same instance as a structured representation with the same name parts. Either the free text representation or a name with structure (e.g. name/family or name/given) should be provided but not both. |
| HumanName > use | Identifies the purpose for this name. | 0..1 | code | //name/@use | Common Person Name Use (required) |
| HumanName > text | A full text representation of the name. | 0..1 | string | //name | |
| HumanName > family | The part of a name that links to the genealogy. In some cultures (e.g. Eritrea) the family name of a son is the first name of his father. | 0..1 | string | //name/family | |
| HumanName > given | Given name. | 0..* | string | //name/given | |
| HumanName > prefix | Part of the name that is acquired as a title due to academic, legal, employment or nobility status, etc. and that appears at the start of the name. | 0..* | string | //name/prefix | Prefix values can be populated as described in AS 4846 (2014) – Person and provider identification in healthcare [SA2014a] , 4.4.2 Name Title. |
| HumanName > suffix | Part of the name that is acquired as a title due to academic, legal, employment or nobility status, etc. and that appears at the end of the name. | 0..* | string | //name/suffix | Suffix values can be populated as described in AS 4846 (2014) – Person and provider identification in healthcare [SA2014a] , 4.5.3.2 Name Suffix. |
| HumanName > period | Indicates the period of time when this name was valid for the named person. | 0..1 | Period | //name/validTime | See <time> for available attributes. |

Example A.2. HumanName

```
<!-- These example fragments are illustrative only. They cannot be treated as clinically valid.  
While every effort has been taken to ensure that the examples are consistent with the message specification, where  
there are conflicts with the written message specification or schema, the specification or schema will take precedence. -->  
  
<!-- HumanName where use=official -->  
<name use="C">  
  <!-- HumanName.given -->  
  <given>Adam</given>  
  <!-- HumanName.given -->  
  <given>A.</given>  
  <!-- HumanName.family -->  
  <family>Everyman</family>  
</name>  
  
<!-- HumanName where use=official -->  
<name use="C">  
  <!-- HumanName.text -->  
  Adam A. Everyman  
</name>  
  
<!-- HumanName where use=usual -->  
<name use="I">  
  <!-- HumanName.given -->  
  <given>Damo</given>  
</name>  
  
<!-- HumanName where use=old -->  
<name use="DN">  
  <!-- HumanName.given -->  
  <given>Adam</given>  
  <!-- HumanName.given -->  
  <given>A.</given>  
  <!-- HumanName.family -->  
  <family>Adamson</family>  
  <!-- HumanName.period -->  
  <validTime xsi:type="IVL_TS">  
    <low value="01012001" />  
    <high value="01012012" />  
  </validTime>  
</name>
```

A.3 Address

This informative appendix provides some guidance on how the complex data type [Address](#), referenced in the body of this specification can map to CDA (R2). The mappings provided are a set of preferred mappings and do not represent conformance requirements.

CDA mapping

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|-----------------------------|---|--|-------------------------|--------------------------|--|
| Address | An address expressed using postal conventions (as opposed to GPS or other location definition formats). This data type may be used to convey addresses for use in delivering mail as well as for visiting locations which might not be valid for mail delivery. There are a variety of postal address formats defined around the world. | Cardinality comes from linking parent. | Element | //addr | |
| Address > use | The purpose of this address. | 0..1 | code | //addr/@use | Address Use HL7 v3 (required) addr/@use may be used to carry more than one value by a space separated list of codes. |
| Address > type | Distinguishes between physical addresses (those you can visit) and mailing addresses (e.g. PO Boxes and care-of addresses). Most addresses are both. | 0..1 | code | //addr/@use | Address Type HL7 v3 (required) addr/@use may be used to carry more than one value by a space separated list of codes. |
| Address > text | A full text representation of the address. | 0..1 | string | //addr | The expectation is that this is free text. |
| Address > line | This component contains the house number, apartment number, street name, street direction, P.O. Box number, delivery hints, and similar address information. | 0..* | string | //addr/streetAddressLine | |
| Address > city | The name of the city, town, village or other community or delivery center. | 0..1 | string | //addr/city | |
| Address > district | The name of the administrative area (county). | 0..1 | string | //addr/county | |
| Address > state | Sub-unit of a country with limited sovereignty in a federally organized country. A code may be used if codes are in common use (i.e. US 2 letter state codes). | 0..1 | string | //addr/state | |
| Address > postalCode | A postal code designating a region defined by the postal service. | 0..1 | string | //addr/postalCode | |
| Address > country | Country - a nation as commonly understood or generally accepted. | 0..1 | string | //addr/country | Iso 3166 Part 1: 2 Letter Codes (preferred) |
| Address > period | Time period when address was/is in use. | 0..1 | Period | //addr/useablePeriod | |

Example A.3. Address

```
<!-- These example fragments are illustrative only. They cannot be treated as clinically valid.  
While every effort has been taken to ensure that the examples are consistent with the message specification, where  
there are conflicts with the written message specification or schema, the specification or schema will take precedence. -->  
  
<!-- Address where use=work and type=postal -->  
<addr use="PST WP">  
  <!--Address.text-->  
  1050 W Wishard Blvd  
  RG  
  5th floor  
  Indianapolis, IN 46240  
  <!--Address.line-->  
  <streetAddressLine>1050 W Wishard Blvd</streetAddressLine>  
  <!--Address.line-->  
  <streetAddressLine>RG 5th floor</streetAddressLine>  
  <!--Address.city-->  
  <city>Indianapolis</city>  
  <!--Address.state-->  
  <state>IN</state>  
  <!--Address.postalCode-->  
  <postalCode>46240</postalCode>  
</addr>  
  
<!-- Address where use=home and type=physical -->  
<addr use="PHYS H">  
  <!--Address.text-->  
  1 Back Lane&#13;&#10;Holmfirth&#13;&#10;HUDDERSFIELD&#13;&#10;HD7 1HQ  
  <!--Address.line-->  
  <streetAddressLine>1 Back Lane</streetAddressLine>  
  <!--Address.city-->  
  <city>Holmfirth</city>  
  <!--Address.district-->  
  <county>HUDDERSFIELD</county>  
  <!--Address.postalCode-->  
  <postalCode>HD7 1HQ</postalCode>  
</addr>  
  
<!-- Address where use=old -->  
<addr use="TMP">  
  <!--Address.line-->  
  <streetAddressLine>Rue Lougoraïa 12, app. 10</streetAddressLine>  
  <!--Address.city-->  
  <city>Korolevo</city>  
  <!--Address.state-->  
  <state>Minsk</state>  
  <!--Address.country-->  
  <country>BELARUS</country>  
  <!--Address.period-->  
  <useablePeriod xsi:type="IVL_TS">  
    <low value="01012001" />  
    <high value="01012012" />  
  </useablePeriod>  
</addr>
```

A.4 Address as Australian Address

This informative appendix provides some guidance on the constrained form of complex data type [Address as Australian Address](#) published by HL7 Australia. The mappings provided are a set of preferred mappings and do not represent conformance requirements.

CDA mapping

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|---------------------------------|--|--|-------------------------|--------------------------|--|
| Address | An Australian address expressed using postal conventions (as opposed to GPS or other location definition formats). | Cardinality comes from linking parent. | Element | //addr | addr SHALL have text or one or more line (addr/streetAddressLine). |
| Address > use | The purpose of this address. | 0..1 | code | //addr/@use | Address Use HL7 v3 (required) //addr/@use may be used to carry more than one value by a space separated list of codes. |
| Address > type | Distinguishes between physical addresses (those you can visit) and mailing addresses (e.g. PO Boxes and care-of addresses). Most addresses are both. | 0..1 | code | //addr/@use | Address Type HL7 v3 (required) //addr/@use may be used to carry more than one value by a space separated list of codes. |
| Address > text | A full text representation of the address. | 0..1 | string | //addr | The expectation is that this is free text. |
| Address > line | This component contains the house number, apartment number, street name, street direction, P.O. Box number, delivery hints, and similar address information. | 0..* | string | //addr/streetAddressLine | |
| Address > city | The name of the city, town, village or other community or delivery center. | 0..1 | string | //addr/city | |
| Address > district | The name of the administrative area (county). | 0..1 | string | //addr/county | |
| Address > state | Sub-unit of a country with limited sovereignty in a federally organized country. A code may be used if codes are in common use (i.e. US 2 letter state codes). | 0..1 | string | //addr/state | Australian States and Territories (required) This element SHALL be populated with the code e.g. "NT". |
| Address > postalCode | A postal code designating a region defined by the postal service. | 0..1 | string | //addr/postalCode | The maximum length of postalCode SHALL be 4. |
| Address > country | Fixed value if present otherwise assumed to be Australia in this context. | 0..1 | string | //addr/country | This element SHALL be populated with "AU". |
| Address > period | Time period when address was/is in use. | 0..1 | Period | //addr/useablePeriod | |
| Address > nofixedaddress | No fixed address indicator. | 0..1 | boolean | n/a | Not mapped directly, if true, addr SHOULD be equal to "NO FIXED ADDRESS" and addr/@use SHOULD be "PHYS". |

Example A.4. Address

```
<!-- These example fragments are illustrative only. They cannot be treated as clinically valid.  
While every effort has been taken to ensure that the examples are consistent with the message specification, where  
there are conflicts with the written message specification or schema, the specification or schema will take precedence. -->  
  
<!-- Australian Address with no fixed address in Melbourne, VIC-->  
<addr use="PHYS">  
<!--Address.text-->  
NO FIXED ADDRESS  
<!--Address.city-->  
<city>Melbourne</city>  
<!--Address.state-->  
<state>VIC</state>  
</addr>  
  
<!-- Australian Address with only text-->  
<addr use="PHYS">  
<!--Address.text-->  
Level 1, 300 George St, Brisbane, QLD 4000  
</addr>  
  
<!-- Australian Address where use=work and type=postal -->  
<addr use="PST WP">  
<!--Address.line-->  
<streetAddressLine>Northern Territory Office, Department of Addresses, GPO Box 19132110</streetAddressLine>  
<!--Address.city-->  
<city>Darwin</city>  
<!--Address.state-->  
<state>NT</state>  
<!--Address.postalCode-->  
<postalCode>0801</postalCode>  
<!--Address.country-->  
<country>AU</country>  
<!--Address.period-->  
<useablePeriod xsi:type="IVL_TS">  
<low value="200311031647+1000" />  
</useablePeriod>  
</addr>  
  
<!-- Australian Address where use=work and type=physical -->  
<addr use="PHYS WP">  
<!--Address.line-->  
<streetAddressLine>5th Floor, Northern Territory House, 223 Mitchell Street</streetAddressLine>  
<!--Address.city-->  
<city>Darwin</city>  
<!--Address.state-->  
<state>NT</state>  
<!--Address.postalCode-->  
<postalCode>0800</postalCode>  
<!--Address.country-->  
<country>AU</country>  
</addr>
```

A.5 ContactPoint

This informative appendix provides some guidance on how the complex data type [ContactPoint](#), referenced in the body of this specification can map to CDA (R2). The mappings provided are a set of preferred mappings and do not represent conformance requirements.

CDA mapping

| Element | Element description | Card | Element type | CDA schema element | Constraints and comments |
|------------------------------|---|--|-----------------------------|------------------------|---|
| ContactPoint | A human's name with the ability to identify parts and usage. | Cardinality comes from linking parent. | Element | //telecom | If value is present, system SHALL be present. |
| ContactPoint > system | Telecommunications form for contact point - what communications system is required to make use of the contact. | 0..1 | code | //telecom/@value | HL7 URLScheme (required) Makes up part of the attribute: "system:value", e.g. "tel:phone number", "mailto:email address", "http:URL", etc. |
| ContactPoint > value | The actual contact point details, in a form that is meaningful to the designated communication system (i.e. phone number or email address). | 0..1 | string | //telecom/@value | Makes up the part of the attribute: "system:value", e.g. "tel:phone number", "mailto:email address", "http:URL", etc. |
| ContactPoint > use | Identifies the purpose for the contact point. | 0..1 | code | //telecom/@use | HL7 TelecommunicationAddressUse (required) |
| ContactPoint > rank | Specifies a preferred order in which to use a set of contacts. Contacts are ranked with lower values coming before higher values. | 0..1 | positiveInt | n/a | This logical element has no mapping to CDA. |
| ContactPoint > period | Time period when the contact point was/is in use. | 0..1 | Period | //telecom/usablePeriod | See < time > for available attributes. |

Example A.5. ContactPoint

```
<!-- These example fragments are illustrative only. They cannot be treated as clinically valid.  
While every effort has been taken to ensure that the examples are consistent with the message specification, where  
there are conflicts with the written message specification or schema, the specification or schema will take precedence. -->  
  
<!-- ContactPoint where system=phone, value=+1-(555)555-1212, use=home -->  
<telecom value="tel:+1-(555)555-1212" use="H">  
  <!-- ContactPoint.period -->  
  <useablePeriod xsi:type="IVL_TS">  
    <low value="01012001" />  
    <high value="01012012" />  
  </useablePeriod>  
</telecom>  
  
<!-- ContactPoint where system=phone, value=0712341234, use=home -->  
<telecom use="H" value="tel:0712341234" />  
  
<!-- ContactPoint where system=email, value=sfranklin@mail.com.au, use=work -->  
<telecom use="WP" value="mailto:sfranklin@mail.com.au" />
```

Appendix B. Examples

This informative appendix provides some examples that conform to the conformance requirements specified within this implementation guide.

DRAFT

B.1 Advance Care Directive Custodian Record example 1

This informative appendix provides an example CDA instance that conforms to the requirements of this implementation guide.

Example B.1. Advance Care Directive Custodian Record example 1

```
<!-- This example is illustrative only. This fragment cannot be treated as clinically valid.  
While every effort has been taken to ensure that the examples are consistent with the message specification, where  
there are conflicts with the written message specification or schema, the specification or schema will take precedence. -->  
  
<ClinicalDocument classCode="DOCLIN" moodCode="EVN" xmlns="urn:hl7-org:v3"  
  xmlns:ex="urn:hl7-org:v3-example"  
  xmlns:ext="http://ns.electronichealth.net.au/Ci/Cda/Extensions/3.0"  
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"  
  xsi:schemaLocation="urn:hl7-org:v3 ../../library/schema_au_published/CDA-AU-V1_0.xsd">  
  <typeId root="2.16.840.1.113883.1.3" extension="POCD_HD000040"/>  
  <!-- ClinicalDocument templateId -->  
  <templateId root="1.2.36.1.2001.1001.102.101.100033" extension="1.0"/>  
  <!--Advance Care Directive Custodian Record document model templateId -->  
  <templateId root="1.2.36.1.2001.1001.102.101.100044" extension="1.0"/>  
  <!--CDA Rendering Specification templateId-->  
  <tempalteId root="1.2.36.1.2001.100.226" extension="1.0"/>  
  <id root="10a31fe6-fcd6-4109-80c6-b1411495a2b7"/>  
  <code code="100.16696" codeSystem="1.2.36.1.2001.1001.101"  
    codeSystemName="NCTIS Data Components" displayName="Advance Care Directive Custodian Record"/>  
  <title>Advance Care Directive Custodian Record</title>  
  <effectiveTime value="20180621090015+1000"/>  
  <confidentialityCode nullFlavor="NA"/>  
  <languageCode code="en-AU"/>  
  <ext:completionCode code="F" codeSystem="1.2.36.1.2001.1001.101.104.20104"  
    codeSystemName="NCTIS Document Status Values" displayName="Final"/>  
  <!-- subject (Patient with mandatory identifier) -->  
  <recordTarget typeCode="RCT">  
    <templateId root="1.2.36.1.2001.1001.102.101.100004" extension="1.0"/>  
    <patientRole classCode="PAT">  
      <id root="5b64239f-0254-45f5-b02d-e3dba30743bf"/>  
      <!-- Patient.address -->  
      <addr>1 Australia Lane, North Adelaide, SA, 5006, Australia</addr>  
      <!-- Patient.telecom -->  
      <telecom value="tel:0755886699"/>  
      <patient>  
        <!-- Patient.name -->  
        <name use="C">Mr Frank HARDING</name>  
        <!-- Patient.gender -->  
        <administrativeGenderCode code="male" codeSystem="2.16.840.1.113883.4.642.1.2"  
          codeSystemName="AdministrativeGender" displayName="Male"/>  
        <!-- Patient.birthDate -->  
        <birthTime value="19491004"/>  
        <!-- Patient.indigenous-status -->  
        <ethnicGroupCode code="4" codeSystems="1.2.36.1.2001.1004.200.10012"  
          codeSystemName="Australian Indigenous Status"  
          displayName="Neither Aboriginal nor Torres Strait Islander origin"/>  
        <!-- Patient.identifier -->  
        <ext:asEntityIdentifier classCode="IDENT">  
          <ext:id root="1.2.36.1.2001.1003.0.8003608833357361"  
            assigningAuthorityName="IHI"/>  
          <ext:assigningGeographicArea classCode="PLC">  
            <ext:name>National Identifier</ext:name>  
          </ext:assigningGeographicArea>  
        </ext:asEntityIdentifier>  
        <ext:asEntityIdentifier classCode="IDENT">  
          <ext:id assigningAuthorityName="Medicare Card Number"  
            root="1.2.36.1.5001.1.0.7.1" extension="3950302571"/>  
          <ext:code code="MC" codeSystem="2.16.840.1.113883.12.203"/>  
        </ext:asEntityIdentifier>  
      </patient>  
    </patientRole>  
  </recordTarget>  
  <!-- composition-author-role :: author (PractitionerRole with practitioner) -->  
  <author typeCode="AUT">  
    <templateId root="1.2.36.1.2001.1001.102.101.100006" extension="1.0"/>  
    <!-- Composition.date -->  
    <time value="20170621090015+1000"/>  
    <assignedAuthor>  
      <id root="6bd143fd-1811-46a9-9bc4-e15afdd7174c"/>  
      <!-- PractitionerRole.code -->  
      <code code="253111" codeSystem="2.16.840.1.113883.13.62"  
        displayName="General Practitioner">  
        <originalText>GP</originalText>  
      </code>  
      <!-- Practitioner.address -->  
      <addr use="WP">3 HENRI PL, 80 Stamford Road, PEARCE, SA, 5006, Australia</addr>  
      <!-- Practitioner.telecom -->  
      <telecom use="WP" value="tel:0737202801"/>  
      <!-- PractitionerRole.practitioner -->  
      <assignedPerson>  
        <!-- assignedPerson (Practitioner with mandatory identifier) -->  
        <templateId root="1.2.36.1.2001.1001.102.101.100040" extension="1.0"/>  
        <!-- Practitioner.name -->  
        <name>Dr Charley Fletcher</name>  
        <!-- Practitioner.identifier -->  
        <ext:asEntityIdentifier classCode="IDENT">
```

```
<ext:id root="1.2.36.1.2001.1003.0.8003612033304560"  
assigningAuthorityName="HPI-I"/>  
<ext:assigningGeographicArea classCode="PLC">  
  <ext:name>National Identifier</ext:name>  
  </ext:assigningGeographicArea>  
  </ext:asEntityIdentifier>  
  </assignedPerson>  
  </assignedAuthor>  
</author>  
<!-- custodian (Organization with mandatory identifier) -->  
<custodian>  
  <templatId root="1.2.36.1.2001.1001.102.101.100002" extension="1.0"/>  
  <assignedCustodian>  
    <representedCustodianOrganization>  
      <id root="987d6a7e-6264-43b0-8666-a14e1d1bfff91"/>  
    <!-- Organization.identifier -->  
    <ext:asEntityIdentifier classCode="IDENT">  
      <ext:id root="1.2.36.1.2001.1007.1.8003640001000036"  
        assigningAuthorityName="PAI-O"/>  
    <ext:assigningGeographicArea classCode="PLC">  
      <ext:name>National Identifier</ext:name>  
    </ext:assigningGeographicArea>  
    </ext:asEntityIdentifier>  
    </representedCustodianOrganization>  
  </assignedCustodian>  
</custodian>  
  
<component>  
  <structuredBody>  
    <!-- section (Advance Care Directive Custodians) -->  
    <component>  
      <section>  
        <templatId root="1.2.36.1.2001.1001.102.101.100045" extension="1.0"/>  
        <id root="9df11e58-5a28-479d-86b4-3ffe823b77aa"/>  
        <!-- section.code -->  
        <code code="101.16694" codeSystems="1.2.36.1.2001.1001.101"  
          displayName="Advance Care Directive Custodian Entries"/>  
        <!-- section.title -->  
        <title>Advance Care Directive Custodians</title>  
        <!-- section.text -->  
        <text mediaType="text/x-hl7-text+xml">  
          <table>  
            <tbody>  
              <tr>  
                <th>Custodian</th>  
                <td/>  
              </tr>  
              <tr>  
                <th>Name</th>  
                <td>Mr Frank HARDING</td>  
              </tr>  
              <tr>  
                <th>Address</th>  
                <td>1 Australia Lane, North Adelaide, SA, 5006, Australia</td>  
              </tr>  
              <tr>  
                <th>Phone</th>  
                <td>0755886699</td>  
              </tr>  
              <tr>  
                <th>Email</th>  
                <td></td>  
              </tr>  
            </tbody>  
          </table>  
          <table>  
            <tbody>  
              <tr>  
                <th>Custodian</th>  
                <td/>  
              </tr>  
              <tr>  
                <th>Name</th>  
                <td>Dr Charley Fletcher</td>  
              </tr>  
              <tr>  
                <th>Address</th>  
                <td>3 HENRI PL, 80 Stamford Road, PEARCE, SA, 5006, Australia  
                  (Workplace)</td>  
              </tr>  
              <tr>  
                <th>Phone</th>  
                <td>(07) 3720 2801 (Workplace)</td>  
              </tr>  
              <tr>  
                <th>Email</th>  
                <td></td>  
              </tr>  
            </tbody>  
          </table>  
          <table>  
            <tbody>  
              <tr>  
                <th>Custodian</th>  
                <td/>  
              </tr>  
              <tr>  
                <th>Name</th>  
                <td>Dr Matthew Kessler</td>  
              </tr>  
            </tbody>  
          </table>  
        </text>  
      </component>  
    </section>  
  </structuredBody>  
</component>
```

```
</tr>
<tr>
<th>Address</th>
<td>12 Yamba Ave, Garran, ACT, 2605, Australia (Workplace)</td>
</tr>
<tr>
<th>Phone</th>
<td>0245754566 (Workplace)</td>
</tr>
<tr>
<th>Email</th>
<td>-</td>
</tr>
</tbody>
</table>
</text>

<!-- entry (Advance Care Directive Custodian Entry) -->
<entry>
<act classCode="ACT" moodCode="EVN">
<templateId root="1.2.36.1.2001.1001.102.101.100046" extension="1.0"/>
<id root="9c049b63-37f0-45a2-b447-8e5bb5747170"/>
<code code="102.16690" codeSystem="1.2.36.1.2001.1001.101"
displayName="Advance Care Directive Custodian Entry"/>
<!--participant (Base Patient)-->
<participant typeCode="PART">
<templateId root="1.2.36.1.2001.1001.102.101.100048" extension="1.0"/>
<participantRole>
<id root="5b64239f-0254-45f5-b02d-e3dba30743bf"/>
<code code="ONESELF" codeSystem="2.16.840.1.113883.5.111"/>
<addr>1 Australia Lane, North Adelaide, SA, 5006,
Australia</addr>
<telecom value="tel:0755886699"/>
<playingEntity classCode="PSN">
<name>Mr Frank HARDING</name>
</playingEntity>
</participantRole>
</participant>
<!--participant (Base Practitioner)-->
<participant typeCode="PART">
<templateId root="1.2.36.1.2001.1001.102.101.100049" extension="1.0"/>
<participantRole>
<id root="692a0819-b240-4acf-95ae-fd02d214bc90"/>
<addr use="WB">12 Yamba Ave, Garran, ACT, 2605, Australia</addr>
<telecom use="WB" value="tel:0245754566"/>
<playingEntity classCode="PSN">
<name>Dr Matthew Kessler</name>
</playingEntity>
</participantRole>
</participant>
<!--participant (Base Practitioner)-->
<participant typeCode="PART">
<templateId root="1.2.36.1.2001.1001.102.101.100049" extension="1.0"/>
<participantRole>
<id root="6bd143fd-1811-46a9-9bc4-e15afdd7174c"/>
<addr use="WB">3 HENRI PL, 80 Stamford Road, PEARCE, SA, 5006,
Australia</addr>
<telecom use="WP" value="tel:0737202801"/>
<playingEntity classCode="PSN">
<name>Dr Charley Fletcher</name>
</playingEntity>
</participantRole>
</participant>
</act>
</entry>
</section>
</component>

</structuredBody>
</component>
</clinicalDocument>
```

B.2 Advance Care Directive Custodian Record example 2

This informative appendix provides an example CDA instance that conforms to the requirements of this implementation guide.

Example B.2. Advance Care Directive Custodian Record example 2

```
<!-- This example is illustrative only. This fragment cannot be treated as clinically valid.  
While every effort has been taken to ensure that the examples are consistent with the message specification, where  
there are conflicts with the written message specification or schema, the specification or schema will take precedence. -->  
<ClinicalDocument classCode="DOCLIN" moodCode="EVN" xmlns="urn:hl7-org:v3"  
xmlns:xsi="urn:hl7-org/v3-example"  
xmlns:ext="http://ns.electronichealth.net.au/Ci/Cda/Extensions/3.0"  
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"  
xsi:schemaLocation="urn:hl7-org:v3 ../../library/schema_au_published/CDA-AU-V1_0.xsd">  
<typeId root="2.16.840.1.113883.1.3" extension="POCD_HD000040"/>  
<!-- ClinicalDocument templateId -->  
<templateId root="1.2.36.1.2001.1001.102.101.100033" extension="1.0"/>  
<!-- Advance Care Directive Custodian Record document model templateId -->  
<templateId root="1.2.36.1.2001.1001.102.101.100044" extension="1.0"/>  
<!-- CDA Rendering Specification templateId-->  
<templateId root="1.2.36.1.2001.1001.100.226" extension="1.0"/>  
<id root="ffd1533c-27c8-4bb7-b32b-981b77d03329"/>  
<code code="100.16696" codeSystem="1.2.36.1.2001.1001.101"  
codeSystemName="NCTIS Data Components" displayName="Advance Care Directive Custodian Record"/>  
<title>Advance Care Directive Custodian Record</title>  
<effectiveTime value="20180921090015+1000"/>  
<confidentialityCode nullFlavor="NA"/>  
<languageCode code="en-AU"/>  
<ext:completionCode code="F" codeSystem="1.2.36.1.2001.1001.101.104.20104"  
codeSystemName="NCTIS Document Status Values" displayName="Final"/>  
<!-- subject (Patient with mandatory identifier) -->  
<recordTarget typeCode="RCT">  
<templateId root="1.2.36.1.2001.1001.102.101.100004" extension="1.0"/>  
<patientRole classCode="PAT">  
  <id root="70fcefa0-dc27-445a-b2d1-a17fac5a7d0c"/>  
  <!-- Patient.telecom -->  
  <telecom value="tel:0755876699"/>  
  <patient>  
    <!-- Patient.name -->  
    <name>  
      <prefix>Ms</prefix>  
      <given>Faye</given>  
      <family>Ferris</family>  
    </name>  
    <!-- Patient.gender -->  
    <administrativeGenderCode code="female" codeSystem="2.16.840.1.113883.4.642.1.2"  
    codeSystemName="AdministrativeGender" displayName="Male"/>  
    <!-- Patient.indigenous-status -->  
    <ethnicGroupCode code="4" codeSystem="1.2.36.1.2001.1004.200.10012"  
    codeSystemName="Australian Indigenous Status"  
    displayName="Neither Aboriginal nor Torres Strait Islander origin"/>  
    <!-- Patient.identifier -->  
    <ext:asEntityIdentifier classCode="IDENT">  
      <ext:id assigningAuthorityName="Medicare Card Number"  
      root="1.2.36.1.5001.1.0.7.1" extension="3950302571"/>  
      <ext:code code="MC" codeSystem="2.16.840.1.113883.12.203"/>  
    </ext:asEntityIdentifier>  
  </patient>  
  </patientRole>  
</recordTarget>  
<!-- composition-author-role :: author (PractitionerRole with practitioner) -->  
<author typeCode="AUT">  
<templateId root="1.2.36.1.2001.1001.102.101.100006" extension="1.0"/>  
<!-- Composition.date -->  
  <time value="20170621090015+1000"/>  
  <assignedAuthor>  
    <id root="1be2ab6e-ed2f-448b-8cf2-ed2172ad9c17"/>  
    <!-- PractitionerRole.code -->  
    <code code="253111" codeSystem="2.16.840.1.113883.13.62"  
    displayName="General Practitioner">  
      <originalText>GP</originalText>  
    </code>  
    <!-- Practitioner.telecom -->  
    <telecom use="WP" value="mailto:bhelpman@example.devonportgp.com.au"/>  
    <!-- PractitionerRole.practitioner -->  
    <assignedPerson>  
      <!-- assignedPerson (Base Practitioner) -->  
      <templateId root="1.2.36.1.2001.1001.102.101.100040" extension="1.0"/>  
      <!-- Practitioner.name -->  
      <name>  
        <given>Barry</given>  
        <family>Helpman</family>  
        <suffix qualifier="AC">M.D.</suffix>  
      </name>  
      <!-- Practitioner.identifier -->  
      <ext:asEntityIdentifier classCode="IDENT">  
        <ext:id root="1.2.36.1.2001.1003.0.8003610000000000"  
        assigningAuthorityName="HPI-I"/>  
        <ext:assigningGeographicArea classCode="PLC">  
          <ext:name>National Identifier</ext:name>  
        </ext:assigningGeographicArea>
```

```
</ext:asEntityIdentifier>
<!-- Practitioner.qualification -->
<ext:asQualifications classCode="QUAL">
<ext:code>
<originalText>Bachelor of Medicine</originalText>
</ext:code>
</ext:asQualifications>
</assignedPerson>
</assignedAuthor>
</author>
<!-- custodian (Organization with mandatory identifier) -->
<custodian>
<templateId root="1.2.36.1.2001.1001.102.101.100002" extension="1.0"/>
<assignedCustodian>
<representedCustodianOrganization>
<id root="94ff0fbc-0454-47d4-bc8c-7d945f3c6ab3"/>
<!-- Organization.identifier -->
<ext:asEntityIdentifier classCode="IDENT">
<ext:id root="1.2.36.1.2001.1007.1.8003640001000036"
assigningAuthorityName="PAI-O"/>
<ext:assigningGeographicArea classCode="PLC">
<ext:name>National Identifier</ext:name>
</ext:assigningGeographicArea>
</ext:asEntityIdentifier>
</representedCustodianOrganization>
</assignedCustodian>
</custodian>

<component>
<structuredBody>
<!-- section (Advance Care Directive Custodians) -->
<component>
<section>
<templateId root="1.2.36.1.2001.1001.102.101.100045" extension="1.0"/>
<id root="0007b6dc-0cf3-4f08-a87c-097defb5a01a"/>
<!-- section.code -->
<code code="101.16694" codeSystem="1.2.36.1.2001.1001.101"
displayName="Advance Care Directive Custodian Entries"/>
<!-- section.title -->
<title>Advance Care Directive Custodians</title>
<!-- section.text -->
<text mediaType="text/x-hl7-text+xml">
<table>
<tbody>
<tr>
<th>Custodian</th>
<td></td>
</tr>
<tr>
<th>Name</th>
<td>Dr Sarah Tonin</td>
</tr>
<tr>
<th>Phone</th>
<td>0849754566</td>
</tr>
<tr>
<th>Email</th>
<td>sarah.tonin@example.com.au</td>
</tr>
</tbody>
</table>
</text>
<!-- entry (Advance Care Directive Custodian Entry) -->
<entry>
<act classCode="ACT" moodCode="EVN">
<templateId root="1.2.36.1.2001.1001.102.101.100046" extension="1.0"/>
<id root="8dd3234c-cab7-48ef-851d-b432616aaeab"/>
<code code="102.16690" codeSystem="1.2.36.1.2001.1001.101"
displayName="Advance Care Directive Custodian Entry"/>
<!-- participant (Base Practitioner)-->
<participant typeCode="PART">
<templateId root="1.2.36.1.2001.1001.102.101.100049" extension="1.0"/>
<participantRole>
<id root="f400ce46-9ff1-4885-baab-13fd8774c5d0"/>
<telecom use="WP" value="mailto:sarah.tonin@example.com.au"/>
<telecom use="WP" value="tel:0849754566"/>
<playingEntity classCode="PSN">
<name>Dr Sarah Tonin</name>
</playingEntity>
</participantRole>
</participant>
</act>
</entry>
</section>
</component>
</structuredBody>
</component>
</ClinicalDocument>
```

Appendix C. Mapping from requirements

This informative appendix provides mapping from the data items (i.e. requirements) in *Advance Care Directive Record Information Requirements [NEHT2011by]*.

The table below matches the data items to the elements of the Advance Care Directive Custodian Record (ACDCR) model as shown in the Element column of the CDA Mapping table in the relevant template, and their corresponding CDA schema element(s) path from the root CDA schema element ClinicalDocument.

| Requirement section | Data item | Element | CDA schema element |
|---------------------|-----------------------|---|--|
| Individual | Component | Composition > subject Composition > author (Patient) | /ClinicalDocument/recordTarget[pat]/ /ClinicalDocument/author[pat]/assignedAuthor/ |
| | Person Name | Patient > name | /ClinicalDocument/recordTarget[pat]/patientRole/patient/name /ClinicalDocument/author[pat]/assignedAuthor/assignedPerson/name |
| | Person Identifier | Patient > identifier | /ClinicalDocument/recordTarget[pat]/patientRole/patient/ext:asEntityIdentifier /ClinicalDocument/author[pat]/assignedAuthor/assignedPerson/ext:asEntityIdentifier |
| | Date of Birth | Patient > birthDate | /ClinicalDocument/recordTarget[pat]/patientRole/patient/birthTime |
| | Sex | Patient > gender | /ClinicalDocument/recordTarget[pat]/patientRole/patient/administrativeGenderCode |
| | Address | Patient > address | /ClinicalDocument/recordTarget[pat]/patientRole/addr /ClinicalDocument/author[pat]/assignedAuthor/addr |
| | Communication Details | Patient > telecom | /ClinicalDocument/recordTarget[pat]/patientRole/telecom /ClinicalDocument/author[pat]/assignedAuthor/telecom |
| | Indigenous Status | Patient > indigenous-status | /ClinicalDocument/recordTarget[pat]/patientRole/patient/ext:asEntityIdentifier /ClinicalDocument/author[pat]/assignedAuthor/assignedPerson/ext:asEntityIdentifier |

| Requirement section | Data item | Element | CDA schema element |
|-----------------------------|---------------------------|--------------------------------------|---|
| ACD Custodian Record Author | Component | Composition > author (Patient) | |
| | | Composition > author (RelatedPerson) | /ClinicalDocument/author/assignedAuthor/assignedPerson |
| | | Composition > author (Practitioner) | |
| | Person Name | Patient > name | |
| | | RelatedPerson > name | /ClinicalDocument/author/assignedAuthor/assignedPerson/name |
| | | Practitioner > name | |
| | Person Identifier | Patient > identifier | |
| | | RelatedPerson > identifier | /ClinicalDocument/author/assignedAuthor/assignedPerson/ext:asEntityIdentifier |
| | | Practitioner > identifier | |
| | Address | Patient > address | |
| | | RelatedPerson > address | /ClinicalDocument/author/assignedAuthor/addr |
| | | Practitioner > address | |
| | Communication Details | Patient > telecom | |
| | | RelatedPerson > telecom | /ClinicalDocument/author/assignedAuthor/assignedPerson/telecom |
| | | Practitioner > telecom | |
| | Authorised Representative | Not directly supported | /ClinicalDocument/effectiveTime/high/@value where /ClinicalDocument/author[relper] |
| | Expiry Date | Not directly supported | /ClinicalDocument/effectiveTime/high/@value |

| Requirement section | Data item | Element | CDA schema element |
|---------------------|-----------------------------|---|--|
| ACD Custodian | Component | Composition > section (Advance Care Directive Custodians) > entry (Practitioner) | |
| | | Composition > section (Advance Care Directive Custodians) > entry (Patient) | /ClinicalDocument/component/structuredBody/component[acd]/section/entry[acd-cr]/act/participant |
| | | Composition > section (Advance Care Directive Custodians) > entry (RelatedPerson) | |
| | | Composition > section (Advance Care Directive Custodians) > entry (Organization) | |
| | Person or Organisation Name | Practitioner > name | /ClinicalDocument/component/structuredBody/component[acd]/section/entry[acd-cr]/act/participant[prac]/participantRole/playingEntity/name |
| | | Patient > name | /ClinicalDocument/component/structuredBody/component[acd]/section/entry[acd-cr]/act/participant[pat]/participantRole/playingEntity/name |
| | | RelatedPerson > name | /ClinicalDocument/component/structuredBody/component[acd]/section/entry[acd-cr]/act/participant[relper]/participantRole/playingEntity/name |
| | | Organisation > name | /ClinicalDocument/component/structuredBody/component[acd]/section/entry[acd-cr]/act/participant[org]/participantRole/scopingEntity/name |
| | Custodian Relationship | Not directly supported | /ClinicalDocument/component/structuredBody/component[acd]/section/entry[acd-cr]/act/participant/participantRole/code |
| | Address | Practitioner > address | |
| | | Patient > address | /ClinicalDocument/component/structuredBody/component[acd]/section/entry[acd-cr]/act/participant/participantRole/addr |
| | | RelatedPerson > address | |
| | | Organisation > address | |
| | Communication Details | | /ClinicalDocument/component/structuredBody/component[acd]/section/entry[acd-cr]/act/participant/participantRole/telecom |

| Requirement section | Data item | Element | CDA schema element |
|---------------------|-------------------|--|-------------------------------|
| | | Practitioner > telecom Patient > telecom RelatedPerson > telecom Organisation > telecom | |
| Document Control | Component | n/a | n/a |
| | DateTime Attested | Composition > date | /ClinicalDocument/author/time |

References

- [DH2017o] Australian Digital Health Agency, 21 December 2017, *Clinical Documents Common Conformance Profile*, Version 1.7.
<https://developer.digitalhealth.gov.au/resources-and-documentation/clinical-documents/ep-2563-2017-dh-2481-2017>
- [DH2018d] Australian Digital Health Agency, 01 November 2018, *Participant Model Specification*, Version 1.0.
<https://www.digitalhealth.gov.au/implementation-resources/clinical-documents/participant-model-specification>
- [DH2019a] Australian Digital Health Agency, 28 February 2019, *Common - Clinical Document*, Version 1.5.2.
<https://developer.digitalhealth.gov.au/specifications/clinical-documents/ep-2807-2019>
- [DH2019e] Australian Digital Health Agency, Not yet published, *Advance Care Records FHIR Implementation Guide*, Version 1.0.0.
<https://www.digitalhealth.gov.au/implementation-resources/clinical-documents/common-clinical-document>
- [HI2011] Health Intersections, 2011, *Representation of Common Australian Identifiers in v2 and CDA*, accessed 28 November 2011.
<http://www.healthintersections.com.au/?p=721>
- [HL7AUBIG] HL7 Australia, Continuous Integration Build, *Australian Base Profiles Implementation Guide*, v1.0.0 (Standard for Trial Use), accessed 07 March 2019.
<http://build.fhir.org/ig/hl7au/au-fhir-base/index.html>
- [HL7CDAR2] Health Level Seven, Inc., January 2010, *HL7 Clinical Document Architecture*, Release 2.
http://www.hl7.org/implement/standards/product_brief.cfm?product_id=7
- [HL7FHIR3] Health Level Seven, Inc., 19 April 2017, *FHIR*, Release 3 (STU), accessed 10 Mar 2019.
<http://hl7.org/fhir/STU3/index.html>
- [HL7RIM] Health Level Seven, Inc., January 2010, *HL7 Version 3 Standard – Reference Information Model*.
http://www.hl7.org/implement/standards/product_brief.cfm?product_id=77
- [HL7V3] Health Level Seven, Inc., January 2010, *HL7 Version 3 Standard*.
http://www.hl7.org/implement/standards/product_brief.cfm?product_id=186
- [HL7V3DT] Health Level Seven, Inc., January 2010, *HL7 V3 RIM, Data types and Vocabulary*.
<http://www.hl7.org/memonly/downloads/v3edition.cfm>
- [IHTS2010] International Health Terminology Standards Development Organisation, January 2010, *SNOMED CT*, accessed 15 March 2010.
<http://www.ihtsdo.org/snomed-ct>
- [INFO2009] Canada Health Infoway, *CDA Validation Tools: infoway_release_2_2X_18.zip*.
<http://www.hl7.org/memonly/downloads/v3edition.cfm>
- [NEHT2011ax] National E-Health Transition Authority, *Advance Care Directive Custodian Record Structured Content Specification*, Version 1.0.
<https://www.digitalhealth.gov.au/implementation-resources/clinical-documents/EP-1745-2014>
- [NEHT2011bg] National E-Health Transition Authority, 09 December 2011, *Advance Care Directive Custodian Record CDA Implementation Guide*, Version 1.0.
<https://www.digitalhealth.gov.au/implementation-resources/clinical-documents/EP-1745-2014>
- [NEHT2011bv] National E-Health Transition Authority, 10 October 2011, *Representing Coding in CDA Documents Implementation Guidance*, Version 1.0.
<https://developer.digitalhealth.gov.au/resources-and-documentation/clinical-documents/ep-1094-2011-nehta-1097-2011>
- [NEHT2011by] National E-Health Transition Authority, 12 December 2011, *Advance Care Directive Record Information Requirements*, Version 1.0.

<https://www.digitalhealth.gov.au/implementation-resources/clinical-documents/EP-1745-2014>

- [NEHT2012s] National E-Health Transition Authority, 07 March 2012, *CDA Rendering Specification*, Version 1.0.
<https://developer.digitalhealth.gov.au/resources-and-documentation/clinical-documents/ep-1094-2011-nehta-1199-2012>
- [RFC2119] Network Working Group, 1997, *Key Words for Use in RFCs to Indicate Requirement Levels*, accessed 05 March 2019.
<https://tools.ietf.org/html/rfc2119>
- [RING2009] Ringholm, 2009, *CDA Examples*, accessed 15 March 2010.
http://www.ringholm.de/download/CDA_R2_examples.zip
- [SA2014a] Standards Australia, 2014, *AS 4846 (2014) – Person and provider identification in healthcare*.
<http://infostore.saiglobal.com/store/details.aspx?ProductID=1753860>
- [UCUM] The Unified Code for Units of Measure, 2009, *The Unified Code for Units of Measure*, accessed 01 November 2012.
<http://unitsofmeasure.org/trac/>

DRAFT