



Chapter 5: Advanced SQL

Modified by hzd@zju.edu.cn

Database System Concepts, 7th Ed.

©Silberschatz, Korth and Sudarshan
See www.db-book.com for conditions on re-use



Chapter 5: Advanced SQL

- Accessing SQL From a Programming Language
 - Embedded SQL
 - ODBC and JDBC
- Functions and Procedural Constructs
- Triggers
- Advanced Aggregation Features
- OLAP



Embedded SQL

- The SQL standard defines embeddings of SQL in a variety of programming languages such as C, Java, and Cobol.
- A language to which SQL queries are embedded is referred to as a **host language**, and the SQL structures permitted in the host language comprise *embedded SQL*.
- The basic form of these languages follows that of the System R embedding of SQL into PL/I.
- **EXEC SQL** statement is used to identify embedded SQL request to the preprocessor

EXEC SQL <embedded SQL statement > END_EXEC

Note: this varies by language (for example, the Java embedding uses # SQL { };)

- Main issues: exchange of parameters and results between the host language and SQL statements; sets vs. variables; get the execution status of the SQL statements; compile to host language;



Embedded SQL (Cont.)

- Example 1: Salary promotion:
EXEC SQL update *instructor* set *salary* = *salary* * 1.05
where *salary* < :*some_amount* END_EXEC
- Example 2: From within a host language, find the ID and name of students who have completed more than the number of credits stored in variable *credit_amount*.

Specify the query in SQL and declare a *cursor* for it

EXEC SQL

declare *c* **cursor for**

select *ID, name*

from *student*

where *tot_cred* > :*credit_amount*

END_EXEC



Embedded SQL (Cont.)

- The **open** statement causes the query to be evaluated

EXEC SQL open c END_EXEC

- The **fetch** statement causes the values of one tuple in the query result to be placed on host language variables.

EXEC SQL fetch c into :si, :sn END_EXEC

Repeated calls to **fetch** get successive tuples in the query result

- A variable called SQLSTATE in the SQL communication area (SQLCA) gets set to '02000' to indicate no more data is available
- The **close** statement causes the database system to delete the temporary relation that holds the result of the query.

EXEC SQL close c END_EXEC

Note: above details vary with language. For example, the Java embedding defines Java iterators to step through result tuples.



Embedded SQL (Cont.)

```
void getStudentInfo()
{
    int credit_amount;
    char sId[16];
    char sName[16];
    EXEC SQL declare c cursor select id, name from student where tot_cred > :credit_amount END EXEC;
    printf("Please input the credit amount: ");
    scanf("%d",&credit_amount);
    EXEC SQL open c END_EXEC;
    while (1)
    {
        EXEC SQL fetch c into :sId, :sName END_EXEC;
        if (!strcmp(SQLSTATE,"02000"))
            break;
        printf("%s %s\n",sId,sName);
    }
    EXEC SQL close c END_EXEC;
}
```



Updates Through Cursors

- Can update tuples fetched by cursor by declaring that the cursor is for update

```
declare c cursor for  
select *  
from instructor  
where dept_name = 'Music'  
for update
```

- To update tuple at the current location of cursor *c*, usually when the application has complicated logic. For example, before an instructor is promoted, some specific information may be required, such as the number of courses he/she taught in the pervious years, the average grades of his/her classes, etc. After the specific conditions are met, the update can be executed as follows:

```
update instructor  
set salary = salary + 100  
where current of c
```



ODBC and JDBC

- API (application-program interface) for a program to interact with a database server
- Application makes calls to
 - Connect with the database server
 - Send SQL commands to the database server
 - Fetch tuples of result one-by-one into program variables
- ODBC (Open Database Connectivity) works with C, C++, C#, and Visual Basic
 - Other API's such as ADO.NET sit on top of ODBC
- JDBC (Java Database Connectivity) works with Java




ODBC

- Open DataBase Connectivity(ODBC) standard
 - standard for application program to communicate with a database server.
 - application program interface (API) to
 - ▶ open a connection with a database,
 - ▶ send queries and updates,
 - ▶ get back results.
- Applications such as GUI, spreadsheets, etc. can use ODBC
- Was defined originally for Basic and C, versions available for many languages.



ODBC – Client Side Architecture



- Each database system supporting ODBC provides a "driver" library that must be linked with the client program.
- ODBC Manager determine to load which driver and connect to which server based on the data source name (DSN) configuration
- When client program makes an ODBC API call, the code in the library communicates with the server to carry out the requested action, and fetch results.



ODBC – Driver and DSN Configuration

- Driver configuration example in odbcinst.ini:
 - [PostgreSQL]
 - Description=PostgreSQL driver for Mac
 - Driver=/usr/local/Cellar/psqlodbc/12.01.0000/lib/psqlodbcw.so
 - Setup=/usr/local/Cellar/psqlodbc/12.01.0000/lib/psqlodbcw.so
- DSN configuration example in odbc.ini
 - [Mike] //Data Source Name
 - Description=Mike
 - Driver=PostgreSQL
 - Database=mike
 - Servername=localhost
 - UserName=mike
 - Password=
 - Port=5432



ODBC – Prepare to Connect

- ODBC program first allocates an SQL environment, then a database connection handle.
- Opens database connection using `SQLConnect()`. Parameters for `SQLConnect`:
 - connection handle,
 - data source name
 - the user identifier,
 - password
- Must also specify types of arguments:
 - `SQL_NTS` denotes previous argument is a null-terminated string.



ODBC– Connect – Code Example

```
■ int ODBCexample()  
{  
    RETCODE error;  
    HENV  env;   /* environment */  
    HDBC  conn; /* database connection */  
    SQLAllocEnv(&env);  
    SQLAllocConnect(env, &conn);  
    SQLConnect(conn, "Mike", SQL_NTS, "avi", SQL_NTS, "avipasswd",  
               SQL_NTS);  
    { .... Do actual work , usually use a statement handle to do the query... }  
  
    SQLDisconnect(conn);  
    SQLFreeConnect(conn);  
    SQLFreeEnv(env);  
}
```




ODBC – Execute Stmt & Fetch Results

- After successful connection, program allocates a stmt handle, then sends SQL commands to database by using `SQLExecDirect` or `SQLExecute`
- After stmt execution, using `SQLBindCol()` to bind C language variables to attributes of the query result
 - Arguments to `SQLBindCol()`
 - ▶ ODBC stmt variable,
 - ▶ attribute position in query result,
 - ▶ The data type,
 - ▶ The address of the variable,
 - ▶ For variable-length types like character arrays,
 - The maximum length of the variable
 - Location to store actual length when a tuple is fetched.
 - Note: A negative value returned for the length field indicates null value
 - When a tuple is fetched, its attribute values are automatically stored in corresponding C variables.
- Result tuples are fetched using `SQLFetch()` in a loop
- Good programming requires checking results of every function call for errors; we have omitted most checks for brevity.



ODBC - Statement Handle Internal


- Statement
- Metadata



- Value



- Host variables address:





ODBC – Stmt Execution Example

```
int getStudentInfo(HDBC conn)
{
    int creditAmount;
    char sId[24];
    char sName[24];
    int totalCredit;
    SQLELEN lenOut1,lenOut2,lenOut3;
    HSTMT stmt;
    RETCODE error;
    char sqlquery[1024], sCreditAmount[24];
    printf("Please input the credit amount: ");
    scanf("%d",&creditAmount);
    sprintf(sCreditAmount, "%d", creditAmount);
    strcpy(sqlquery,"select id, name, tot_cred from student where tot_cred>");
    strcat(sqlquery,sCreditAmount); //Usually do not use strcat directly, use prepared stmt instead
    // to be continue
}
```




ODBC – Stmt Execution Example – Cont.

//follow the previous slide

```
SQLAllocStmt(conn, &stmt);
```

```
error = SQLExecDirect(stmt, (SQLCHAR *)sqlquery, SQL_NTS);
```

```
if (error == SQL_SUCCESS) {
```

```
    SQLBindCol(stmt, 1, SQL_C_CHAR, sId , 80, &lenOut1);
```

```
    SQLBindCol(stmt, 2, SQL_C_CHAR, sName , 80 , &lenOut2);
```

```
    SQLBindCol(stmt, 3, SQL_C_SLONG, &totalCredit , 0 , &lenOut3);
```

```
    while (SQLFetch(stmt) == SQL_SUCCESS) {
```

```
        printf (" %s %s %d\n", sId, sName, totalCredit);
```

```
    }
```

```
}
```

```
SQLFreeStmt(stmt, SQL_DROP);
```

```
return 0;
```

```
}
```

```
// end of getStudentInfo
```



Chance of SQL Injection

- getStudentInfo version 2

```
int getStudentInfo(HDBC conn) {
    char sId[24];
    char sName[24];
    int totalCredit;
    SQLLEN lenOut1, lenOut2, lenOut3;
    HSTMT stmt;
    RETCODE error;
    char sqlquery[1024], sCreditAmount[1024];
    printf("Please input the credit amount: ");
    gets(sCreditAmount); //dangerous
    strcpy(sqlquery, "select id, name, tot_cred from student where tot_cred>");
    strcat(sqlquery, sCreditAmount); //dangerous
    SQLAllocStmt(conn, &stmt);
    SQLExecDirect(stmt, (SQLCHAR *)sqlquery, SQL_NTS);
    .....
```

- If user input is "3; update student set tot_cred=200 where ID = '19001' ", then the overall query will be "select id, name, tot_cred from student where tot_cred> 3; update student set tot_cred=200 where ID = '19001' ". The total credit of student with ID '19001' will be updated to 200



ODBC Prepared Statements

■ Prepared Statement

- Can have placeholders when preparing: E.g. insert into account values(?,?,?)
- Bind the host variables with those placeholders
- Construct the complete statement with these information
- Can repeatedly executed with different values for the placeholders

■ To prepare a statement

`SQLPrepare(stmt, <SQL String>);`

■ To bind parameters

`SQLBindParameter(stmt, <parameter#>, ... type information and value omitted for simplicity..)`

■ To execute the statement

`retcode = SQLExecute(stmt);`

■ To avoid SQL injection security risk, do not create SQL strings directly using user input; instead use prepared statements to bind user inputs



Prepared Statements - getStudentInfo V3

```
int getStudentInfo(HDBC conn)
{
    int creditAmount;
    char sId[24];
    char sName[24];
    int totalCredit;
    SQLELEN lenOut1, lenOut2, lenOut3;
    HSTMT stmt;
    RETCODE error;
    char* sqlquery = "select id, name, tot_cred from student where tot_cred> ? ";
    printf("Please input the credit amount: ");
    scanf("%d",&creditAmount);
    SQLAllocStmt(conn, &stmt);
    SQLPrepare(stmt,(SQLCHAR* )sqlquery,SQL_NTS);
    SQLBindParameter(stmt,1,SQL_PARAM_INPUT, SQL_C_SLONG, SQL_INTEGER, 0,
0,(SQLPOINTER)&creditAmount, sizeof(int), NULL); //safer way
    error = SQLExecute(stmt);
    .....
```



More ODBC Features

■ Metadata features

- finding all the relations in the database and
- finding the names and types of columns of a query result or a relation in the database.

■ By default, each SQL statement is treated as a separate transaction that is committed automatically.

- Can turn off automatic commit on a connection
 - ▶ `SQLSetConnectOption(conn, SQL_AUTOCOMMIT, 0)`
- Transactions must then be committed or rolled back explicitly by
 - ▶ `SQLTransact(conn, SQL_COMMIT)` or
 - ▶ `SQLTransact(conn, SQL_ROLLBACK)`



ODBC Conformance Levels

- Conformance levels specify subsets of the functionality defined by the standard.
 - Core
 - Level 1 requires support for metadata querying
 - Level 2 requires ability to send and retrieve arrays of parameter values and more detailed catalog information.
- SQL Call Level Interface (CLI) standard similar to ODBC interface, but with some minor differences.



ADO.NET

- API designed for Visual Basic .NET and C#, providing database access facilities similar to JDBC/ODBC

- Partial example of ADO.NET code in C#
using System, System.Data, System.Data.SqlClient;
SqlConnection conn = new SqlConnection(
 "Data Source=<IPaddr>, Initial Catalog=<Catalog>");
conn.Open();
SqlCommand cmd = new SqlCommand("select * from students",
 conn);

SqlDataReader rdr = cmd.ExecuteReader();
while(rdr.Read()) {
 Console.WriteLine(rdr[0], rdr[1]); /* Prints result attributes 1 & 2 */
}
rdr.Close(); conn.Close();

- Can also access non-relational data sources such as
 - OLE-DB, XML data, Entity framework



JDBC

- **JDBC** is a Java API for communicating with database systems supporting SQL.
- JDBC supports a variety of features for querying and updating data, and for retrieving query results.
- JDBC also supports metadata retrieval, such as querying about relations present in the database and the names and types of relation attributes.
- Model for communicating with the database:
 - Open a connection
 - Create a “statement” object
 - Execute queries using the Statement object to send queries and fetch results
 - Exception mechanism to handle errors



JDBC Code

```
public static void JDBCexample(String dbid, String userid, String passwd)
{
    try {
        Class.forName ("oracle.jdbc.driver.OracleDriver");
        Connection conn = DriverManager.getConnection(
            "jdbc:oracle:thin:@db.yale.edu:2000:univdb", userid, passwd);
        Statement stmt = conn.createStatement();
        ... Do Actual Work ....
        stmt.close();
        conn.close();
    }
    catch (SQLException sqle) {
        System.out.println("SQLException : " + sqle);
    }
}
```



JDBC Code (Cont.)

- Update to database

```
try {  
    stmt.executeUpdate(  
        "insert into instructor values('77987', 'Kim', 'Physics', 98000)");  
} catch (SQLException sqle)  
{  
    System.out.println("Could not insert tuple. " + sqle);  
}
```

- Execute query and fetch and print results

```
ResultSet rset = stmt.executeQuery(  
    "select dept_name, avg (salary)  
    from instructor  
    group by dept_name");  
while (rset.next()) {  
    System.out.println(rset.getString("dept_name") + " " +  
        rset.getFloat(2));  
}
```



JDBC Code Details

- Getting result fields:
 - **`rs.getString("dept_name")` and `rs.getString(1)` equivalent if `dept_name` is the first argument of select result.**
- Dealing with Null values
 - **`int a = rs.getInt("a");`
`if (rs.isNull()) Systems.out.println("Got null value");`**



Prepared Statement

- `PreparedStatement pstmt = conn.prepareStatement("insert into instructor values(?,?,?,?)");`
`pstmt.setString(1, "88877"); pstmt.setString(2, "Perry");`
`pstmt.setString(3, "Finance"); pstmt.setInt(4, 125000);`
`pstmt.executeUpdate();`
`pstmt.setString(1, "88878");`
`pstmt.executeUpdate();`
- For queries, use `pstmt.executeQuery()`, which returns a `ResultSet`
- WARNING: always use prepared statements when taking an input from the user and adding it to a query
 - **NEVER create a query by concatenating strings which you get as inputs**
 - `"insert into instructor values(' " + ID + " ', ' " + name + " ', " +`
`" ' + dept name + " ', " ' balance + ")"`
 - What if name is "D'Souza"?



SQL Injection

- Suppose query is constructed using
 - "select * from instructor where name = '" + name + "'"
- Suppose the user, instead of entering a name, enters:
 - X' or 'Y' = 'Y
- then the resulting statement becomes:
 - "select * from instructor where name = '" + "X' or 'Y' = 'Y" + "'"
 - which is:
 - ▶ select * from instructor where name = 'X' or 'Y' = 'Y'
 - User could have even used
 - ▶ X'; update instructor set salary = salary + 10000; --
- Prepared statement internally uses:
"select * from instructor where name = 'X\' or \'Y\' = \'Y'"
 - **Always use prepared statements, with user inputs as parameters**



Metadata Features

- ResultSet metadata
- E.g., after executing query to get a ResultSet rs:
 - `ResultSetMetaData rsmd = rs.getMetaData();`
 `for(int i = 1; i <= rsmd.getColumnCount(); i++) {`
 `System.out.println(rsmd.getColumnName(i));`
 `System.out.println(rsmd.getColumnTypeName(i));`
 `}`
- How is this useful?



Metadata (Cont)

- Database metadata

- `DatabaseMetaData dbmd = conn.getMetaData();`

```
ResultSet rs = dbmd.getColumns(null, "univdb", "department", "%");
```

```
// Arguments to getColumns: Catalog, Schema-pattern, Table-pattern,  
// and Column-Pattern
```

```
// Returns: One row for each column; row has a number of attributes
```

```
// such as COLUMN_NAME, TYPE_NAME
```

```
while( rs.next()) {
```

```
    System.out.println(rs.getString("COLUMN_NAME"),
```

```
                        rs.getString("TYPE_NAME");
```

```
}
```

- And where is this useful?



Finding Primary Keys

■ DatabaseMetaData dmd = connection.getMetaData();

// Arguments below are: Catalog, Schema, and Table

// The value "" for Catalog/Schema indicates current catalog/schema

// The value null indicates all catalogs/schemas

ResultSet rs = dmd.getPrimaryKeys("", "", tableName);

while(rs.next()){

 // KEY_SEQ indicates the position of the attribute in

 // the primary key, which is required if a primary key has multiple

 // attributes

 System.out.println(rs.getString("KEY_SEQ"),
 rs.getString("COLUMN_NAME");

}



Transaction Control in JDBC

- By default, each SQL statement is treated as a separate transaction that is committed automatically
 - bad idea for transactions with multiple updates
- Can turn off automatic commit on a connection
 - `conn.setAutoCommit(false);`
- Transactions must then be committed or rolled back explicitly
 - `conn.commit();` or
 - `conn.rollback();`
- `conn.setAutoCommit(true)` turns on automatic commit.



Other JDBC Features

- Calling functions and procedures
 - `CallableStatement cStmt1 = conn.prepareCall("{? = call some function(?)})");`
 - `CallableStatement cStmt2 = conn.prepareCall("{call some procedure(?,?)})");`
- Handling large object types
 - `getBlob()` and `getClob()` that are similar to the `getString()` method, but return objects of type `Blob` and `Clob`, respectively
 - get data from these objects by `getBytes()`
 - associate an open stream with Java `Blob` or `Clob` object to update large objects
 - ▶ `blob.setBlob(int parameterIndex, InputStream inputStream).`



SQLJ

- JDBC is overly dynamic, errors cannot be caught by compiler
- SQLJ: embedded SQL in Java

- ```
#sql iterator deptInfolter (String dept name, int avgSal);
deptInfolter iter = null;
#sql iter = { select dept_name, avg(salary) from instructor
 group by dept name };
while (iter.next()) {
 String deptName = iter.dept_name();
 int avgSal = iter.avgSal();
 System.out.println(deptName + " " + avgSal);
}
iter.close();
```



# Procedural Constructs in SQL



# Procedural Extensions and Stored Procedures

- SQL provides a **module** language
  - Permits definition of procedures in SQL, with if-then-else statements, for and while loops, etc.
- Stored Procedures
  - Can store procedures in the database
  - then execute them using the **call** statement
  - permit external applications to operate on the database without knowing about internal details
  - separate the business logic and user interface logic
  - decrease back and forth of command and data over the network
  - compile and recompile of the procedure before execution, highly increase the efficiency of the application



# Functions and Procedures

- SQL:1999 supports functions and procedures
  - Functions/procedures can be written in SQL itself, or in an external programming language.
  - Functions are particularly useful with specialized data types such as images and geometric objects.
    - ▶ Example: functions to check if polygons overlap, or to compare images for similarity.
  - Some database systems support **table-valued functions**, which can return a relation as a result.
- SQL:1999 also supports a rich set of imperative constructs, including
  - Loops, if-then-else, assignment
- Many databases have proprietary procedural extensions to SQL that differ from SQL:1999.



# SQL Functions

- Define a function that, given the name of a department, returns the count of the number of instructors in that department.

```
create function dept_count (dept_name varchar(20))
returns integer
begin
 declare d_count integer;
 select count (*) into d_count
 from instructor
 where instructor.dept_name = dept_name
 return d_count;
end
```

- Find the department name and budget of all departments with more than 12 instructors.

```
select dept_name, budget
from department
where dept_count (dept_name) > 12
```



# Table Functions

- SQL:2003 added functions that return a relation as a result
- Example: Return all instructors of one department

**create function** *instructors\_of* (*dept\_name* **char**(20)

**returns table** ( *ID* **varchar**(5),  
*name* **varchar**(20),  
*dept\_name* **varchar**(20),  
*salary* **numeric**(8,2))

**return table**

(**select** *ID, name, dept\_name, salary*  
**from** *instructor*  
**where** *instructor.dept\_name = instructors\_of.dept\_name*)

- Usage

**select** \*  
**from table** (*instructors\_of* ('Music'))



# SQL Procedures

- The `dept_count` function could instead be written as procedure:  

```
create procedure dept_count_proc (in dept_name varchar(20),
 out d_count integer)
begin
 select count(*) into d_count
 from instructor
 where instructor.dept_name = dept_count_proc.dept_name
end
```
- Procedures can be invoked either from an SQL procedure or from embedded SQL, using the **call** statement.  

```
declare d_count integer;
call dept_count_proc('Physics', d_count);
```

Procedures and functions can be invoked also from dynamic SQL

- SQL:1999 allows more than one function/procedure of the same name (called name **overloading**), as long as the number of arguments differ, or at least the types of the arguments differ



# Stored Procedure Example (pgSQL)

- Find the number of students with tot\_cred greater than some amount. Create a procedure with one "in" parameter creditAmount and one "inout" parameter numOfStudent

```
CREATE OR REPLACE PROCEDURE findNumOfStudent(creditAmount in INT,
numOfStudent inout INT)
LANGUAGE plpgsql
AS $$
BEGIN
 select count(*) into numOfStudent from student where tot_cred >
 creditAmount;
END;
$$;
```



# Stored Procedure Example (pgSQL) - Cont.

- Call from another procedure

```
CREATE OR REPLACE PROCEDURE callExample(cAmount in INT)
LANGUAGE plpgsql
AS $$
DECLARE
 noStudent INT := 0;
BEGIN
 call findNumOfStudent(cAmount,noStudent);
 RAISE NOTICE '%', noStudent; //output to screen
END;
$$;
```



# Procedural Constructs

- Warning: most database systems implement their own variant of the standard syntax below
  - read your system manual to see what works on your system
- Compound statement: **begin ... end**,
  - May contain multiple SQL statements between **begin** and **end**.
  - Local variables can be declared within a compound statement

- **While** and **repeat** statements :

```
declare n integer default 0;
```

```
while $n < 10$ do
```

```
 set $n = n + 1$
```

```
end while
```

```
repeat
```

```
 set $n = n - 1$
```

```
until $n = 0$
```

```
end repeat
```



# Procedural Constructs (Cont.)

## ■ **For** loop

- Permits iteration over all results of a query, like cursor
- Example:

```
declare n integer default 0;
for r as
 select budget from department
 where dept_name = 'Music'
do
 set n = n + r.budget
end for
```



# Procedural Constructs (cont.)

- Conditional statements (**if-then-else**)  
SQL:1999 also supports a **case** statement similar to C case statement
- Example procedure: registers student after ensuring classroom capacity is not exceeded
  - Returns 0 on success and -1 if capacity is exceeded
  - See book for details
- Signaling of exception conditions, and declaring handlers for exceptions

```
declare out_of_classroom_seats condition
declare exit handler for out_of_classroom_seats
begin
...
.. signal out_of_classroom_seats
end
```

  - The handler here is **exit** -- causes enclosing **begin..end** to be exited
  - Other actions possible on exception



# Procedural Constructs (PG example)

- Find number of students whose tot\_cred is greater than some number and who have at least one advisor
- Can do with one SQL query. Illustrate cursor and loop here in a function

```
CREATE OR REPLACE FUNCTION findStudentsWithAdvisor(credAmount Integer)
 RETURNS Integer
LANGUAGE plpgsql
AS $$
DECLARE
 num Integer DEFAULT 0;
 numOfAdvisor Integer DEFAULT 0;
 sld char(12) DEFAULT "";
 curStudent CURSOR (cAmount Integer)
 FOR SELECT ID
 FROM student
 WHERE tot_cred > cAmount;
BEGIN
-- to be continued
```



# Procedural Constructs (PG example, Cont.)

```
-- Open the cursor
OPEN curStudent(credAmount);
LOOP
 -- fetch row
 FETCH curStudent INTO sld;
 -- exit when no more row to fetch
 EXIT WHEN NOT FOUND;
 -- just for example, simple logic below, can have much complicated logic
 select count(*) into numOfAdvisor from advisor where s_id = sld;
 -- if have advisor, num++
 IF numOfAdvisor > 0 THEN
 num := num + 1;
 END IF;
END LOOP;
-- Close the cursor
CLOSE curStudent;
RETURN num;
END; $$
```





# Stored Procedure Example (Transfer Fund)

```
CREATE OR REPLACE PROCEDURE transfer_funds(source_account_id INT, destination_account_id INT, amount DECIMAL)
LANGUAGE plpgsql
AS $$
BEGIN
 -- Check if source account has enough funds
 IF (SELECT balance FROM accounts WHERE id = source_account_id) < amount THEN
 RAISE EXCEPTION 'Insufficient funds';
 END IF;
 -- Deduct amount from source account
 UPDATE accounts SET balance = balance - amount WHERE id = source_account_id;
 -- Add amount to destination account
 UPDATE accounts SET balance = balance + amount WHERE id = destination_account_id;
 -- Record the transaction
 INSERT INTO transfers (source_id, destination_id, amount, transaction_date) VALUES (source_account_id, destination_account_id, amount,
CURRENT_TIMESTAMP);
 -- If everything is successful, commit the transaction
 COMMIT;
EXCEPTION
 WHEN OTHERS THEN
 ROLLBACK;
 RAISE;
END;
$$;
```



# External Language Functions/Procedures

- SQL:1999 permits the use of functions and procedures written in other languages such as C or C++
- Declaring external language procedures and functions

```
create procedure dept_count_proc(in dept_name varchar(20),
 out count integer)
```

```
language C
```

```
external name ' /usr/avi/bin/dept_count_proc'
```

```
create function dept_count(dept_name varchar(20))
```

```
returns integer
```

```
language C
```

```
external name '/usr/avi/bin/dept_count'
```



# External Language Routines (Cont.)

- Benefits of external language functions/procedures:
  - more efficient for many operations, and more expressive power.
- Drawbacks
  - Code to implement function may need to be loaded into database system and executed in the database system's address space.
    - ▶ risk of accidental corruption of database structures
    - ▶ security risk, allowing users access to unauthorized data
  - There are alternatives, which give good security at the cost of potentially worse performance.
  - Direct execution in the database system's space is used when efficiency is more important than security.



# Security with External Language Routines

- To deal with security problems
  - Use **sandbox** techniques
    - ▶ that is use a safe language like Java, which cannot be used to access/damage other parts of the database code.
  - Or, run external language functions/procedures in a separate process, with no access to the database process' memory.
    - ▶ Parameters and results communicated via inter-process communication
- Both have performance overheads
- Many database systems support both above approaches as well as direct executing in database system address space.



# Triggers



# Triggers

- A **trigger** is a statement that is executed automatically by the system as a side effect of a modification to the database.
- To design a trigger mechanism, we must:
  - Specify the conditions under which the trigger is to be executed.
  - Specify the actions to be taken when the trigger executes.
- Triggers introduced to SQL standard in SQL:1999, but supported even earlier using non-standard syntax by most databases.
  - Syntax illustrated here may not work exactly on your database system; check the system manuals



# Trigger Example

- E.g. *time\_slot\_id* is not a primary key of *timeslot*, so we cannot create a foreign key constraint from *section* to *timeslot*.
- Alternative: use triggers on *section* and *timeslot* to enforce integrity constraints

```
create trigger timeslot_check1 after insert on section
referencing new row as nrow
for each row
when (nrow.time_slot_id not in (
 select time_slot_id
 from time_slot)) /* time_slot_id not present in time_slot */
begin
 rollback
end;
```



## Trigger Example Cont.

```
create trigger timeslot_check2 after delete on timeslot
 referencing old row as orow
 for each row
 when (orow.time_slot_id not in (
 select time_slot_id
 from time_slot)
 /* last tuple for time slot id deleted from time slot */
 and orow.time_slot_id in (
 select time_slot_id
 from section)) /* and time_slot_id still referenced from section */
 begin
 rollback
 end;
```





# Triggering Events and Actions in SQL

- Triggering event can be **insert**, **delete** or **update**
- Triggers on update can be restricted to specific attributes
  - **E.g., after update of *takes* on *grade***
- Values of attributes before and after an update can be referenced
  - **referencing old row as** : for deletes and updates
  - **referencing new row as** : for inserts and updates
- Triggers can be activated before an event, which can serve as extra constraints. E.g. convert blank grades to null.

```
create trigger setnull_trigger before update of takes
referencing new row as nrow
for each row
when (nrow.grade = ' ')
begin atomic
 set nrow.grade = null;
end;
```



# Trigger to Maintain `credits_earned` value

- **create trigger *credits\_earned* after update of *takes* on (*grade*)**  
**referencing new row as *nrow***  
**referencing old row as *orow***  
**for each row**  
**when *nrow.grade* <> 'F' and *nrow.grade* is not null**  
**and (*orow.grade* = 'F' or *orow.grade* is null)**  
**begin atomic**  
**update *student***  
**set *tot\_cred* = *tot\_cred* +**  
**(select *credits***  
**from *course***  
**where *course.course\_id* = *nrow.course\_id*)**  
**where *student.id* = *nrow.id*;**  
**end;**



# Statement Level Triggers

- Instead of executing a separate action for each affected row, a single action can be executed for all rows affected by a transaction
  - Use **for each statement** instead of **for each row**
  - Use **referencing old table** or **referencing new table** to refer to temporary tables (called *transition tables*) containing the affected rows
  - Can be more efficient when dealing with SQL statements that update a large number of rows



# When Not To Use Triggers

- Triggers were used earlier for tasks such as
  - maintaining summary data (e.g., total salary of each department)
  - Replicating databases by recording changes to special relations (called **change** or **delta** relations) and having a separate process that applies the changes over to a replica
- There are better ways of doing these now:
  - Databases today provide built in materialized view facilities to maintain summary data
  - Databases provide built-in support for replication
- Encapsulation facilities can be used instead of triggers in many cases
  - Define methods to update fields
  - Carry out actions as part of the update methods instead of through a trigger



# When Not To Use Triggers

- Risk of unintended execution of triggers, for example, when
  - loading data from a backup copy
  - replicating updates at a remote site
  - Trigger execution can be disabled before such actions.
- Other risks with triggers:
  - Error leading to failure of critical transactions that set off the trigger
  - Cascading execution



# Recursive Queries



# Recursion in SQL

- SQL:1999 permits recursive view definition
- Example: find which courses are a prerequisite, whether directly or indirectly, for a specific course

```
with recursive rec_prereq(course_id, prereq_id) as (
 select course_id, prereq_id
 from prereq
 union
 select rec_prereq.course_id, prereq.prereq_id,
 from rec_rereq, prereq
 where rec_prereq.prereq_id = prereq.course_id
)
select *
from rec_prereq;
```

This example view, *rec\_prereq*, is called the *transitive closure* of the *prereq* relation

Note: 1<sup>st</sup> printing of 6<sup>th</sup> ed erroneously used *c\_prereq* in place of *rec\_prereq* in some places



# The Power of Recursion

- Recursive views make it possible to write queries, such as transitive closure queries, that cannot be written without recursion or iteration.
  - Intuition: Without recursion, a non-recursive non-iterative program can perform only a fixed number of joins of *prereq* with itself
    - ▶ This can give only a fixed number of levels of managers
    - ▶ Given a fixed non-recursive query, we can construct a database with a greater number of levels of prerequisites on which the query will not work
    - ▶ Alternative: write a procedure to iterate as many times as required
      - See procedure *findAllPrereqs* in book





# The Power of Recursion

- Computing transitive closure using iteration, adding successive tuples to *rec\_prereq*
  - The next slide shows a *prereq* relation
  - Each step of the iterative process constructs an extended version of *rec\_prereq* from its recursive definition.
  - The final result is called the *fixed point* of the recursive view definition.
- Recursive views are required to be **monotonic**. That is, if we add tuples to *prereq* the view *rec\_prereq* contains all of the tuples it contained before, plus possibly more



# Example of Fixed-Point Computation

| <i>course_id</i> | <i>prereq_id</i> |
|------------------|------------------|
| BIO-301          | BIO-101          |
| BIO-399          | BIO-101          |
| CS-190           | CS-101           |
| CS-315           | CS-101           |
| CS-319           | CS-101           |
| CS-347           | CS-101           |
| EE-181           | PHY-101          |

| Iteration Number | Tuples in cl                 |
|------------------|------------------------------|
| 0                |                              |
| 1                | (CS-301)                     |
| 2                | (CS-301), (CS-201)           |
| 3                | (CS-301), (CS-201)           |
| 4                | (CS-301), (CS-201), (CS-101) |
| 5                | (CS-301), (CS-201), (CS-101) |



# Advanced Aggregation Features



# Ranking

- Ranking is done in conjunction with an order by specification.

- Suppose we are given a relation  
*student\_grades*(*ID*, *GPA*)  
giving the grade-point average of each student

- Find the rank of each student.

```
select ID, rank() over (order by GPA desc) as s_rank
from student_grades
```

- An extra **order by** clause is needed to get them in sorted order

```
select ID, rank() over (order by GPA desc) as s_rank
from student_grades
order by s_rank
```

- Ranking may leave gaps: e.g. if 2 students have the same top GPA, both have rank 1, and the next rank is 3
  - **dense\_rank** does not leave gaps, so next dense rank would be 2



# Ranking

- Ranking can be done using basic SQL aggregation, but resultant query is very inefficient

```
select ID, (1 + (select count(*)
 from student_grades B
 where B.GPA > A.GPA)) as s_rank
from student_grades A
order by s_rank;
```



## Ranking (Cont.)

- Ranking can be done within partition of the data.
- “Find the rank of students within each department.”

```
select ID, dept_name,
 rank () over (partition by dept_name order by GPA desc)
 as dept_rank
from dept_grades
order by dept_name, dept_rank;
```

- Multiple **rank** clauses can occur in a single **select** clause.
- Ranking is done *after* applying **group by** clause/aggregation
- Can be used to find top-n results
  - More general than the **limit** *n* clause supported by many databases, since it allows top-n within each partition



# Ranking (Cont.)

- Other ranking functions:
  - **percent\_rank** (within partition, if partitioning is done)
  - **cume\_dist** (cumulative distribution)
    - ▶ fraction of tuples with preceding values
  - **row\_number** (non-deterministic in presence of duplicates)
- SQL:1999 permits the user to specify **nulls first** or **nulls last**  
**select** *ID*,  
          **rank ( ) over (order by GPA desc nulls last) as s\_rank**  
**from** *student\_grades*



## Ranking (Cont.)

- For a given constant  $n$ , the ranking the function  $ntile(n)$  takes the tuples in each partition in the specified order, and divides them into  $n$  buckets with equal numbers of tuples.

- E.g.,

```
select ID, ntile(4) over (order by GPA desc) as quartile
from student_grades;
```





# Windowing

- Used to smooth out random variations.
- E.g., **moving average**: “Given sales values for each date, calculate for each date the average of the sales on that day, the previous day, and the next day”
- **Window specification** in SQL:
  - Given relation *sales(date, value)*  
**select date, *sum*(value) over**  
    **(order by date between rows 1 preceding and 1 following)**  
**from sales**



# Windowing

- Examples of other window specifications:
  - **between rows unbounded preceding and current**
  - **rows unbounded preceding**
  - **range between 10 preceding and current row**
    - ▶ All rows with values between current row value –10 to current value
  - **range interval 10 day preceding**
    - ▶ Not including current row



## Windowing (Cont.)

- Can do windowing within partitions
- E.g., Given a relation *transaction* (*account\_number*, *date\_time*, *value*), where *value* is positive for a deposit and negative for a withdrawal
  - “Find total balance of each account after each transaction on the account”

```
select account_number, date_time,
 sum (value) over
 (partition by account_number
 order by date_time
 rows unbounded preceding)
 as balance
from transaction
order by account_number, date_time
```



**OLAP\*\***





# Data Analysis and OLAP

## ■ Online Analytical Processing (OLAP)

- Interactive analysis of data, allowing data to be summarized and viewed in different ways in an online fashion (with negligible delay)
- Data that can be modeled as dimension attributes and measure attributes are called **multidimensional data**.
  - **Measure attributes**
    - ▶ measure some value
    - ▶ can be aggregated upon
    - ▶ e.g., the attribute *number* of the *sales* relation
  - **Dimension attributes**
    - ▶ define the dimensions on which measure attributes (or aggregates thereof) are viewed
    - ▶ e.g., attributes *item\_name*, *color*, and *size* of the *sales* relation



## Example sales relation

| <i>item_name</i> | <i>color</i> | <i>clothes_size</i> | <i>quantity</i> |
|------------------|--------------|---------------------|-----------------|
| skirt            | dark         | small               | 2               |
| skirt            | dark         | medium              | 5               |
| skirt            | dark         | large               | 1               |
| skirt            | pastel       | small               | 11              |
| skirt            | pastel       | medium              | 9               |
| skirt            | pastel       | large               | 15              |
| skirt            | white        | small               | 2               |
| skirt            | white        | medium              | 5               |
| skirt            | white        | large               | 3               |
| dress            | dark         | small               | 2               |
| dress            | dark         | medium              | 6               |
| dress            | dark         | large               | 12              |
| dress            | pastel       | small               | 4               |
| dress            | pastel       | medium              | 3               |
| dress            | pastel       | large               | 3               |
| dress            | white        | small               | 2               |
| dress            | white        | medium              | 3               |
| dress            | white        | large               | 0               |
| shirt            | dark         | small               | 2               |
| shirt            | dark         | medium              | 4               |

...

...



# Cross Tabulation of sales by *item\_name* and color

*clothes\_size* **all**

*color*

| <i>item_name</i> |       | dark | pastel | white | total |
|------------------|-------|------|--------|-------|-------|
|                  | skirt | 8    | 35     | 10    | 53    |
|                  | dress | 20   | 10     | 5     | 35    |
|                  | shirt | 14   | 7      | 28    | 49    |
|                  | pants | 20   | 2      | 5     | 27    |
|                  | total | 62   | 54     | 48    | 164   |


- The table above is an example of a **cross-tabulation** (**cross-tab**), also referred to as a **pivot-table**.
  - Values for one of the dimension attributes form the row headers
  - Values for another dimension attribute form the column headers
  - Other dimension attributes are listed on top
  - Values in individual cells are (aggregates of) the values of the dimension attributes that specify the cell.





# Data Cube


- A **data cube** is a multidimensional generalization of a cross-tab
- Can have  $n$  dimensions; we show 3 below
- Cross-tabs can be used as views on a data cube






# Hierarchies on Dimensions

- **Hierarchy** on dimension attributes: lets dimensions to be viewed at different levels of detail
  - 👉 E.g., the dimension DateTime can be used to aggregate by hour of day, date, day of week, month, quarter or year



a) Time Hierarchy



b) Location Hierarchy



# Cross Tabulation With Hierarchy

- Cross-tabs can be easily extended to deal with hierarchies
  - Can drill down or roll up on a hierarchy

*clothes\_size:* **all**

|                 |                  | <i>color</i> |        |       |       |     |
|-----------------|------------------|--------------|--------|-------|-------|-----|
| <i>category</i> | <i>item_name</i> | dark         | pastel | white | total |     |
| womenswear      | skirt            | 8            | 8      | 10    | 53    | 88  |
|                 | dress            | 20           | 20     | 5     | 35    |     |
|                 | subtotal         | 28           | 28     | 15    |       |     |
| menswear        | pants            | 14           | 14     | 28    | 49    | 76  |
|                 | shirt            | 20           | 20     | 5     | 27    |     |
|                 | subtotal         | 34           | 34     | 33    |       |     |
| total           |                  | 62           | 62     | 48    |       | 164 |



# Relational Representation of Cross-tabs

- Cross-tabs can be represented as relations
  - We use the value **all** is used to represent aggregates.
  - The SQL standard actually uses null values in place of **all** despite confusion with regular null values.

| <i>item_name</i> | <i>color</i> | <i>clothes_size</i> | <i>quantity</i> |
|------------------|--------------|---------------------|-----------------|
| skirt            | dark         | <b>all</b>          | 8               |
| skirt            | pastel       | <b>all</b>          | 35              |
| skirt            | white        | <b>all</b>          | 10              |
| skirt            | <b>all</b>   | <b>all</b>          | 53              |
| dress            | dark         | <b>all</b>          | 20              |
| dress            | pastel       | <b>all</b>          | 10              |
| dress            | white        | <b>all</b>          | 5               |
| dress            | <b>all</b>   | <b>all</b>          | 35              |
| shirt            | dark         | <b>all</b>          | 14              |
| shirt            | pastel       | <b>all</b>          | 7               |
| shirt            | White        | <b>all</b>          | 28              |
| shirt            | <b>all</b>   | <b>all</b>          | 49              |
| pant             | dark         | <b>all</b>          | 20              |
| pant             | pastel       | <b>all</b>          | 2               |
| pant             | white        | <b>all</b>          | 5               |
| pant             | <b>all</b>   | <b>all</b>          | 27              |
| <b>all</b>       | dark         | <b>all</b>          | 62              |
| <b>all</b>       | pastel       | <b>all</b>          | 54              |
| <b>all</b>       | white        | <b>all</b>          | 48              |
| <b>all</b>       | <b>all</b>   | <b>all</b>          | 164             |



# Extended Aggregation to Support OLAP

- The **cube** operation computes union of **group by**'s on every subset of the specified attributes
- Example relation for this section  
*sales(item\_name, color, clothes\_size, quantity)*
- E.g. consider the query

```
select item_name, color, size, sum(number)
from sales
group by cube(item_name, color, size)
```

This computes the union of eight different groupings of the *sales* relation:

```
{ (item_name, color, size), (item_name, color),
 (item_name, size), (color, size),
 (item_name), (color),
 (size), () }
```

where ( ) denotes an empty **group by** list.

- For each grouping, the result contains the null value for attributes not present in the grouping.



# Online Analytical Processing Operations

- Relational representation of cross-tab that we saw earlier, but with *null* in place of **all**, can be computed by

```
select item_name, color, sum(number)
from sales
group by cube(item_name, color)
```

- The function **grouping()** can be applied on an attribute
  - Returns 1 if the value is a null value representing all, and returns 0 in all other cases.

```
select item_name, color, size, sum(number),
 grouping(item_name) as item_name_flag,
 grouping(color) as color_flag,
 grouping(size) as size_flag,
from sales
group by cube(item_name, color, size)
```



# Online Analytical Processing Operations

- Can use the function **decode()** in the **select** clause to replace such nulls by a value such as **all**
  - E.g., replace *item\_name* in first query by  
**decode( grouping(*item\_name*), 1, 'all', *item\_name*)**



## Extended Aggregation (Cont.)

- The **rollup** construct generates union on every prefix of specified list of attributes
- E.g.,

```
select item_name, color, size, sum(number)
from sales
group by rollup(item_name, color, size)
```

Generates union of four groupings:

{ (*item\_name*, *color*, *size*), (*item\_name*, *color*), (*item\_name*), ( ) }

- Rollup can be used to generate aggregates at multiple levels of a hierarchy.
- E.g., suppose table *itemcategory*(*item\_name*, *category*) gives the category of each item. Then

```
select category, item_name, sum(number)
from sales, itemcategory
where sales.item_name = itemcategory.item_name
group by rollup(category, item_name)
```

would give a hierarchical summary by *item\_name* and by *category*.





# Extended Aggregation (Cont.)

- Multiple rollups and cubes can be used in a single group by clause
  - Each generates set of group by lists, cross product of sets gives overall set of group by lists
- E.g.,

```
select item_name, color, size, sum(number)
from sales
group by rollup(item_name), rollup(color, size)
```

generates the groupings

$$\{item\_name, ()\} \times \{(color, size), (color), ()\}$$
$$= \{ (item\_name, color, size), (item\_name, color), (item\_name), (color, size), (color), ( ) \}$$



# Online Analytical Processing Operations

- **Pivoting:** changing the dimensions used in a cross-tab is called
- **Slicing:** creating a cross-tab for fixed values only
  - Sometimes called **dicing**, particularly when values for multiple dimensions are fixed.
- **Rollup:** moving from finer-granularity data to a coarser granularity
- **Drill down:** The opposite operation - that of moving from coarser-granularity data to finer-granularity data



# OLAP Implementation

- The earliest OLAP systems used multidimensional arrays in memory to store data cubes, and are referred to as **multidimensional OLAP (MOLAP)** systems.
- OLAP implementations using only relational database features are called **relational OLAP (ROLAP)** systems
- Hybrid systems, which store some summaries in memory and store the base data and other summaries in a relational database, are called **hybrid OLAP (HOLAP)** systems.



# OLAP Implementation (Cont.)

- Early OLAP systems precomputed *all* possible aggregates in order to provide online response
  - Space and time requirements for doing so can be very high
    - ▶  $2^n$  combinations of **group by**
  - It suffices to precompute some aggregates, and compute others on demand from one of the precomputed aggregates
    - ▶ Can compute aggregate on  $(item\_name, color)$  from an aggregate on  $(item\_name, color, size)$ 
      - For all but a few “non-decomposable” aggregates such as *median*
      - is cheaper than computing it from scratch
- Several optimizations available for computing multiple aggregates
  - Can compute aggregate on  $(item\_name, color)$  from an aggregate on  $(item\_name, color, size)$
  - Can compute aggregates on  $(item\_name, color, size)$ ,  $(item\_name, color)$  and  $(item\_name)$  using a single sorting of the base data



## **End of Chapter Exercises in the book : 6, 15**

### **Additional:**

1) 写一个嵌入SQL/ODBC程序或Stored Procedure，保存一位同学的一门选课信息，需检查不能有冲突的上课时间；所有先修课必须通过；教室容量必须够。如果以上条件不满足则失败

**Database System Concepts, 7<sup>th</sup> Ed.**

©Silberschatz, Korth and Sudarshan  
See [www.db-book.com](http://www.db-book.com) for conditions on re-use



## Figure 5.22

| <i>item_name</i> | <i>clothes_size</i> | <i>dark</i> | <i>pastel</i> | <i>white</i> |
|------------------|---------------------|-------------|---------------|--------------|
| skirt            | small               | 2           | 11            | 2            |
| skirt            | medium              | 5           | 9             | 5            |
| skirt            | large               | 1           | 15            | 3            |
| dress            | small               | 2           | 4             | 2            |
| dress            | medium              | 6           | 3             | 3            |
| dress            | large               | 12          | 3             | 0            |
| shirt            | small               | 2           | 4             | 17           |
| shirt            | medium              | 6           | 1             | 1            |
| shirt            | large               | 6           | 2             | 10           |
| pant             | small               | 14          | 1             | 3            |
| pant             | medium              | 6           | 0             | 0            |
| pant             | large               | 0           | 1             | 2            |



## Figure 5.23

| <i>item_name</i> | <i>quantity</i> |
|------------------|-----------------|
| skirt            | 53              |
| dress            | 35              |
| shirt            | 49              |
| pant             | 27              |



## Figure 5.24

| <i>item_name</i> | <i>color</i> | <i>quantity</i> |
|------------------|--------------|-----------------|
| skirt            | dark         | 8               |
| skirt            | pastel       | 35              |
| skirt            | white        | 10              |
| dress            | dark         | 20              |
| dress            | pastel       | 10              |
| dress            | white        | 5               |
| shirt            | dark         | 14              |
| shirt            | pastel       | 7               |
| shirt            | white        | 28              |
| pant             | dark         | 20              |
| pant             | pastel       | 2               |
| pant             | white        | 5               |





# Another Recursion Example

- Given relation  
*manager(employee\_name, manager\_name)*
- Find all employee-manager pairs, where the employee reports to the manager directly or indirectly (that is manager's manager, manager's manager's manager, etc.)  

```
with recursive empl (employee_name, manager_name) as (
 select employee_name, manager_name
 from manager
 union
 select manager.employee_name, empl.manager_name
 from manager, empl
 where manager.manager_name = empl.employee_name)
select *
from empl
```

This example view, *empl*, is the *transitive closure* of the *manager* relation



# Merge statement (now in Chapter 24)

- Merge construct allows batch processing of updates.
- Example: relation *funds\_received* (*account\_number*, *amount* ) has batch of deposits to be added to the proper account in the *account* relation

```
merge into account as A
 using (select *
 from funds_received as F)
 on (A.account_number = F.account_number)
 when matched then
 update set balance = balance + F.amount
```