# DC192_PC192 Command Set

**Revisions**

| No | Issue Date | Version | Description | Apply Firmware |
|----|-----------|---------|-------------|----------------|
| 1 | 2013/07/02 | 1.0 | First version. | |
| 2 | 2014/01/06 | 1.1 | 1. Set Audio Microphone Volume: Add command<br>2. Call Audio Microphone Volume: Add command<br>3. Set Audio Out Volume/ Call Audio Out Volume: Revise the comment | DGA106 |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |

*Notice:

1.  The RS-232 command list is for DC192_PC192.
2.  The Yellow highlight [      ] means the latest update
3.  The Blue highlight [≡≡≡] means the deleted item.

## 1. Communication Protocol

Transmit Method: Asynchronous Interface Half
Duplex Serial Communication.

- Transmit Speed: 9600bps
- Start bit: 1Bit
  Parity Check: NA
- Data Bit: 8Bit
- Stop Bit: 1Bit

## 2. The wire diagram

The RS232 wire diagram between presenter and remote controller as below



Female

1 2 3 4 5 6 7 8 9

| CONNECTIONS | | |
|---|---|---|
| DB 9F | COLOUR | DB 9F |
| 2 | - | 3 |
| 3 | - | 2 |
| 5 | - | 5 |
| SHELL | DRAIN | SHELL |

## 3. Communication Program



Host Controller                    Camera Module

Command

Return Command    ACK    Normal End

NACK    Errors In Command Packet

IGNORE    Unsupported Command

Focus Status
Zoom Status
Digital Zoom Status

## 4. Command Format

### 4.1 Command Packet Format

| 1Byte | STX | Start Of Command | : A0h |
|-------|-----|------------------|-------|
| 2Byte | Command | Command | : 00~FFh |
| 3Byte | Parameter1 | Data | : 00~FFh |
| 4Byte | Parameter2 | Data | : 00~FFh |
| 5Byte | Parameter3 | Data | : 00~FFh |
| 6Byte | ETX | End Of Command | : AFh |

### 4.2 Return Packet Format

| 1Byte | STX | Start Of Command | : A0h | | |
|-------|-----|------------------|-------|---|---|
| 2Byte | Command | Command | : 00~ FFh | | |
| 3Byte | Parameter1 | Data | : 00~FFh | | |
| 4Byte | Parameter2 | Data | : 00~FFh | | |
| 5Byte | Status | <Bit> | <Contents> | | |
| | | 7 | (0) | | |
| | | 6 | Iris | Moving Status (1)/(0)Stop Status | |
| | | 5 | Zoom | Moving Status (1)/(0)Stop Status | |
| | | 4 | Focus | Moving Status (1)/(0)Stop Status | |
| | | 3 | (0) | | |
| | | 2 | (0) | | |
| | | 1 | Communication Response 0=ACK/1=NAK/2=IGNORE/3=Not Used | | |
| | | 0 | Communication Response | | |
| 6Byte | ETX | End Of Command | : AFh | | |
| Communication Response | | Bit1 | Bit0 | Status | |

| ACK | 0 | 0 | Capable Of Normal End Or Normal Operation |
|---|---|---|---|
| NAK | 0 | 1 | Detecting Errors In Command Packet(STX, ETX Byte) |
| | | | Parity Error ,Framing Error, Overrun Error |
| | | | Data in out of specified range |
| IGNORE | 1 | 0 | Cannot execute the transmitted command for other operations |
| | | | Unsupported command |
| Not Used | 1 | 1 | |

## 5. Command Packet

| Item | Function | PC AP to DC192 Master command format | | | | | | Comment |
|---|---|---|---|---|---|---|---|---|
| | | 1B | 2B | 3B | 4B | 5B | 6B | |
| 1 | Preset/Factory Reset | A0h | 03h | P1 | P2 | 00h | AFh | P1=0, P2=00/01:Preset Load/Save<br>P1=1:Factory Reset |
| 2 | Slide show On/Off | A0h | 04h | P1 | 00h | 00h | AFh | P1=00/01:Off/On |
| 3 | Slide show Delay | A0h | 06h | P1 | 00h | 00h | AFh | P1=0~5:0.5sec/1sec/3sec/5sec/10sec/Manual |
| 4 | Image/Record Quality | A0h | 07h | P1 | 00h | 00h | AFh | P1=00/01/02:High/Medium/Low |
| 5 | Copy From Nand to SD | A0h | 08h | 00h | 00h | 00h | AFh | |
| 6 | Zoom Stop | A0h | 10h | 00h | 00h | 00h | AFh | |
| 7 | Zoom Start (No AF) | A0h | 11h | P1 | P2 | 00h | AFh | P1=00/01:Tele/Wide |
| 8 | Zoom Direct (No AF) | A0h | 11h | P1 | P2 | 00h | AFh | p1:low byte p2:high byte Value:0~855<br>Optical Zoom:<br>XGA:805<br>SXGA:802<br>WXGA:802<br>1080P:795<br>NTSC:810<br>PAL:810 |
| 9 | Auto Erase | A0h | 14h | P1 | 00h | 00h | AFh | P1=00/01:Auto Erase off/on |
| 10 | Focus Stop | A0h | 19h | 00h | 00h | 00h | AFh | |
| 11 | Focus Start | A0h | 1Ah | P1 | P2 | 00h | AFh | P1=00/01:Near/Far        P2=00~06:Speed |
| 12 | Focus Direct | A0h | 1Bh | P1 | P2 | P3 | AFh | P1(LowByte)P2(HighByte)=0~160(Dec),<br>P3=00~06:Speed |
| 13 | Zoom Start (with AF) | A0h | 1Dh | P1 | P2 | 00h | AFh | P1=00/01:Tele/Wide |
| 14 | Zoom Direct(with AF) | A0h | 1Dh | P1 | P2 | 00h | AFh | p1:low byte p2:high byte Value:0~855 |

| Item | Function | PC AP to DC192 Master command format | | | | | | Comment |
|---|---|---|---|---|---|---|---|---|
| | | 1B | 2B | 3B | 4B | 5B | 6B | |
| | | | | | | | | Optical Zoom:<br>XGA:805<br>SXGA:802<br>WXGA:802<br>1080P:795<br>NTSC:810<br>PAL:810 |
| 15 | White Balance (AWB, Auto Tune) | A0h | 22h | P1 | 00h | 00h | AFh | P1=00/01:Auto Tune/AWB |
| 16 | Set Pan Mode | A0h | 26h | P1 | 00h | 00h | AFh | P1=00/01 : off/on |
| 17 | Mask Mode | A0h | 27h | P1 | 00h | 00h | AFh | p1=0:Disable 1:Mask 2:Spolight |
| 18 | Freeze | A0h | 2Ch | P1 | 00h | 00h | AFh | P1=00/01:Off/On |
| 19 | Brightness Contorl | A0h | 30h | P1 | 00h | 00h | AFh | P1=00/01:Auto/Manua<br>P2=60/50Hz: 00~147 |
| 20 | LogoDelay | A0h | 34h | P1 | 00h | 00h | AFh | P1=4~30 (sec) |
| 21 | Language Select | A0h | 38h | P1 | 00h | 00h | AFh | P1=0~20(Dec):<br>0:English/ 1:Traditional Chinese/ 2:Simplified Chinese/ 3:German/ 4:French/ 5:Spanish/ 6:Russian/ 7:Dutch/ 8:Finnish/ 9:Polish/ 10:Italian/ 11:Portuguese/ 12:Swedish/ 13:Danish/ 14:Czech/ 15:Arabic/ 16:Japanese/ 17:Korean/ 18:Greek/ 19:Reserved/ 20:Latvia |
| 22 | Brightness Step | A0h | 39h | P1 | 00h | 00h | AFh | P1=00/01:-1/+1 |
| 23 | Source live/PC | A0h | 3Ah | P1 | 00h | 00h | AFh | 00    : Camera<br>01    : PC |

| Item | Function | PC AP to DC192 Master command format | | | | | | Comment |
|---|---|---|---|---|---|---|---|---|
| | | 1B | 2B | 3B | 4B | 5B | 6B | |
| | | | | | | | | 02　　　: Source OFF |
| 24 | Disable Digital Zoom After Optical Zoom | A0h | 40h | P1 | 00h | 00h | AFh | P1=00/01:Disable/Enable |
| 25 | Call Master Version | A0h | 45h | 00h | 00h | 00h | AFh | Version code:　P1 P2 P3(ASCII) |
| 26 | Call AE Status | A0h | 46h | 00h | 00h | 00h | AFh | P1=00/01:Off/On |
| 27 | Enable/Disable LOGO Image | A0h | 47h | P1 | 00h | 00h | AFh | p1=00/01:default logo/user logo |
| 28 | Playback Image Index Change Page | A0h | 4Ah | P1 | 00h | 00h | AFh | P1=00/01:Page Up/Page Down |
| 29 | All OSD On/Off | A0h | 4Bh | P1 | 00h | 00h | AFh | P1=00/01:Off/On |
| 30 | Call Slave Version | A0h | 4Dh | 00h | 00h | 00h | AFh | Version code:　P1 P2 P3(ASCII) |
| 31 | Frame Average | A0h | 4Eh | P1 | 00h | 00h | AFh | P1=00/01:LCD/DLP |
| 32 | Call lamp Status | A0h | 50h | 00h | 00h | 00h | AFh | 00　　　: Lamp + Head Led OFF<br>01　　　: Lamp + Head Led ON<br>02　　　: Lamp ON<br>03　　　: Head Led ON |
| 33 | Call Text/Photo Status | A0h | 51h | 00h | 00h | 00h | AFh | P1=00/01/02:Photo/Text/Gray |
| 34 | reg1 | A0h | 52h | P1 | P2 | 00h | AFh | P1=00/01:Read/Write　　P2=0x00~0xff |
| 34 | reg2 | A0h | 53h | P1 | P2 | 00h | AFh | |
| 36 | reg3 | A0h | 54h | P1 | P2 | 00h | AFh | |
| 37 | Error Code | A0h | 55h | P1 | 00h | 00h | AFh | p1=00/01:Show Error Code/Clear Error Code<br>AWB Correction<br>Call AC 50/60 Hz power State. |
| 38 | AWB Correction | A0h | 56h | 00h | 00h | 00h | AFh | |
| 39 | Call AC 50/60Hz power state | A0h | 58h | 00h | 00h | 00h | AFh | |

| Item | Function | PC AP to DC192 Master command format | | | | | | Comment |
|------|----------|-----|-----|-----|-----|-----|-----|---------|
| | | 1B | 2B | 3B | 4B | 5B | 6B | |
| 40 | Keypad Detect | A0h | 59h | P1 | 00h | 00h | AFh | p1:00/01 :Keypad Detect Stop/Start. (Enable the Debug message at this time, the detection message will be sent via RS232.) |
| 41 | Call Zoom Position | A0h | 60h | 00h | 00h | 00h | AFh | p1:low byte p2:high byte<br>XGA:805<br>SXGA:802<br>WXGA:802<br>1080P:795<br>NTSC:810<br>PAL:810 |
| 42 | Call Digital Zoom Position | A0h | 62h | 00h | 00h | 00h | AFh | p1:low byte p2:high byte<br>XGA:50<br>SXGA:53<br>WXGA:53<br>1080P:60<br>NTSC:45<br>PAL:45 |
| 43 | Call Focus Position | A0h | 64h | 00h | 00h | 00h | AFh | P1(LowByte)P2(HighByte)=0~160(Dec) |
| 44 | Call Freeze Status | A0h | 78h | 00h | 00h | 00h | AFh | P1=00/01:Off/On |
| 45 | Call Brightness Position | A0h | 89h | 00h | 00h | 00h | AFh | P1=60/50Hz: 00~147(dec) |
| 46 | Call Mix Zoom Position | A0h | 8Ah | 00h | 00h | 00h | AFh | p1:low byte p2:high byte 0~855<br>Optical Zoom:<br>XGA:805<br>SXGA:802<br>WXGA:802 |

| Item | Function | PC AP to DC192 Master command format | | | | | | Comment |
|------|----------|-----|-----|-----|-----|-----|-----|---------|
| | | 1B | 2B | 3B | 4B | 5B | 6B | |
| | | | | | | | | 1080P:795<br>NTSC:810<br>PAL:810 |
| 47 | Call Menu Status | A0h | 8Bh | 00h | 00h | 00h | AFh | P1=00/01:Off/On |
| 48 | Capture Action | A0h | 96h | P1 | 00h | 00h | AFh | 00      : Single Capture<br>01      : Time Lapse<br>02      : Record<br>03      : Disabled |
| 49 | Capture time | A0h | 97h | P1 | 00h | 00h | AFh | P1=00/01/02/03/04/05/06:1hr/2hr/4hr/<br>8hr/24hr/48hr/72hr |
| 50 | Capture interval | A0h | 98h | P1 | 00h | 00h | AFh | 00      : 3 sec.<br>01      : 5 sec.<br>02      : 10 sec.<br>03      : 30 sec.<br>04      : 1 min.<br>05      : 2 min.<br>06      : 5 min. |
| 51 | Key Function | A0h | A0h | P1 | 00h | 00h | AFh | P1=01/02/03/04/05/06=Enter/Up/Down/Left/Right/Menu |
| 52 | Set R/B Gain | A0h | A1h | P1 | P2 | P3 | AFh | P1=01/02:Red Gain/Blue Gain<br>P2(LowByte)P3(HighByte)=0x100~0xFFF(hex):Gain |
| 53 | Call R/B Gain | A0h | A2h | P1 | 00h | 00h | AFh | Send : P1=01/02:Red Gain/Blue Gain<br>Return :<br>P1(LowByte)P2(HighByte)=0x100~0xFFF(Dec):G |

| Item | Function | PC AP to DC192 Master command format | | | | | | Comment |
|------|----------|-----|-----|-----|-----|-----|-----|---------|
| | | 1B | 2B | 3B | 4B | 5B | 6B | |
| | | | | | | | | ain |
| 54 | AF One Push Trigger | A0h | A3h | 01h | 00h | 00h | AFh | |
| 55 | Set Gamma Mode | A0h | A7h | P1 | 00h | 00h | AFh | P1=00/01/02:Photo/Text/Gray |
| 56 | Set Image Mode | A0h | A9h | P1 | 00h | 00h | AFh | P1=00/01/02/03:Normal/Slide/Film/Microscope |
| 57 | System ON/OFF | A0h | B0h | P1 | 00h | 00h | AFh | P1=00/01:Off/On |
| 58 | Power | A0h | B1h | P1 | 00h | 00h | AFh | P1=00/01:Off/On |
| 59 | Capture | A0h | B2h | P1 | 00h | 00h | AFh | P1=00/01:Capture/Record |
| 60 | Playback thumbnail | A0h | B3h | P1 | 00h | 00h | AFh | P1=00:Thumbnail |
| 61 | Preview rotation | A0h | B4h | P1 | 00h | 00h | AFh | P1=00/01/02/03:Rotate 0/180/Flip/Mirror |
| 62 | Delete | A0h | B6h | P1 | 00h | 00h | AFh | P1=00/01/02: Delete one/Delete all/Format |
| 63 | call system status | A0h | B7h | 00h | 00h | 00h | AFh | P1(system status)=00/01: not ready/ Read to receive the command<br>P2(Power Status)=00/01:Off/On |
| 64 | Lamp On/Off | A0h | C1h | P1 | 00h | 00h | AFh | 00 : Lamp + Head Led OFF<br>01 : Lamp + Head Led ON<br>02 : Lamp ON<br>03 : Head Led ON |
| 65 | Firmware Upgrade | A0h | CBh | P1 | 00h | 00h | AFh | P1=00/01:osd/no osd |
| 66 | Set Audio Microphone Volume | A0h | D4h | P1 | 00h | 00h | AFh | P1=0~16(Dec):Volume |
| 67 | Call Audio Microphone Volume | A0h | D5h | 00h | 00h | 00h | AFh | P1=0~16(Dec):Volume |

| Item | Function | PC AP to DC192 Master command format | | | | | | Comment |
|------|----------|------|------|------|------|------|------|---------|
| | | 1B | 2B | 3B | 4B | 5B | 6B | |
| 68 | Set Audio Out Volume | A0h | D6h | P1 | 00h | 00h | AFh | P1=0~31(Dec):Volume |
| 69 | Call Audio Out Volume | A0h | D7h | 00h | 00h | 00h | AFh | P1=0~31(Dec):Volume |

## 6. Return Packet

| Item | Function | PC AP to DC192 Master command format | | | | | | Comment |
|------|----------|----|----|----|----|----|----|---------|
| | | 1B | 2B | 3B | 4B | 5B | 6B | |
| 1 | Preset/Factory Reset | A0h | 03h | P1 | P2 | St. | AFh | P1=0, P2=00/01:Preset Load/Save<br>P1=1:Factory Reset |
| 2 | Slide show On/Off | A0h | 04h | P1 | 00h | St. | AFh | P1=00/01:Off/On |
| 3 | Slide show Delay | A0h | 06h | P1 | 00h | St. | AFh | P1=0~5:0.5sec/1sec/3sec/5sec/10sec/Manual |
| 4 | Image/Record Quality | A0h | 07h | P1 | 00h | St. | AFh | P1=00/01/02:High/Medium/Low |
| 5 | Copy From Nand to SD | A0h | 08h | 00h | 00h | St. | AFh | |
| 6 | Zoom Stop | A0h | 10h | 00h | 00h | St. | AFh | |
| 7 | Zoom Start (No AF) | A0h | 11h | P1 | P2 | St. | AFh | P1=00/01:Tele/Wide |
| 8 | Zoom Direct (No AF) | A0h | 11h | P1 | P2 | St. | AFh | p1:low byte p2:high byte Value:0~855<br>Optical Zoom:<br>XGA:805<br>SXGA:802<br>WXGA:802<br>1080P:795<br>NTSC:810<br>PAL:810 |
| 9 | Auto Erase | A0h | 13h | P1 | 00h | St. | AFh | P1=00/01:Auto Erase off/on |
| 10 | Focus Stop | A0h | 19h | 00h | 00h | St. | AFh | |
| 11 | Focus Start | A0h | 1Ah | P1 | P2 | St. | AFh | P1=00/01:Near/Far    P2=00~06:Speed |
| 12 | Focus Direct | A0h | 1Bh | P1 | P2 | St. | AFh | P1(LowByte)P2(HighByte)=0~160(Dec),<br>P3=00~06:Speed |
| 13 | Zoom Start (with AF) | A0h | 1Dh | P1 | P2 | St. | AFh | P1=00/01:Tele/Wide |
| 14 | Zoom Direct(with AF) | A0h | 1Dh | P1 | P2 | St. | AFh | p1:low byte p2:high byte Value:0~855<br>Optical Zoom: |

| Item | Function | PC AP to DC192 Master command format | | | | | | Comment |
|---|---|---|---|---|---|---|---|---|
| | | 1B | 2B | 3B | 4B | 5B | 6B | |
| | | | | | | | | XGA:805<br>SXGA:802<br>WXGA:802<br>1080P:795<br>NTSC:810<br>PAL:810 |
| 15 | White Balance (AWB, Auto Tune) | A0h | 22h | P1 | 00h | St. | AFh | P1=00/01:Auto Tune/AWB |
| 16 | Set Pan Mode | A0h | 26h | P1 | 00h | St. | AFh | P1=00/01 : off/on |
| 17 | Mask Mode | A0h | 27h | P1 | 00h | St. | AFh | p1=0:Disable 1:Mask 2:Spolight |
| 18 | Freeze | A0h | 2Ch | P1 | 00h | St. | AFh | P1=00/01:Off/On |
| 19 | Brightness Contorl | A0h | 30h | P1 | 00h | St. | AFh | P1=00/01:Auto/Manua<br>P2=60/50Hz: 00~147 |
| 20 | LogoDelay | A0h | 32h | P1 | 00h | St. | AFh | P1=4~30 (sec) |
| 21 | Language Select | A0h | 38h | P1 | 00h | St. | AFh | P1=0~18(Dec): English/ Traditional Chinese/ Simplified Chinese/ German/ French/ Spanish/ Russian/ Dutch/ Finnish/ Polish/ Italian/ Portuguese/ Swedish/ Danish/ Czech/ Arabic/ Japanese/ Korean/ Greek |
| 22 | Brightness Step | A0h | 39h | P1 | 00h | St. | AFh | P1=00/01:-1/+1 |
| 23 | Source live/PC | A0h | 3Ah | P1 | 00h | St. | AFh | 00    : Camera<br>01    : PC<br>02    : Source OFF |
| 24 | Disable Digital Zoom After Optical Zoom | A0h | 40h | P1 | 00h | St. | AFh | P1=00/01:Disable/Enable |

| Item | Function | PC AP to DC192 Master command format | | | | | | Comment |
|---|---|---|---|---|---|---|---|---|
| | | 1B | 2B | 3B | 4B | 5B | 6B | |
| 25 | Call Master Version | A0h | 45h | P1 | P2 | P3 | AFh | Version code:   P1 P2 P3(ASCII) |
| 26 | Call AE Status | A0h | 46h | P1 | 00h | St. | AFh | P1=00/01:Off/On |
| 27 | Enable/Disable LOGO Image | A0h | 47h | P1 | 00h | St. | AFh | p1=00/01:default logo/user logo |
| 28 | Playback Image Index Change Page | A0h | 4Ah | P1 | 00h | St. | AFh | P1=00/01:Page Up/Page Down |
| 29 | All OSD On/Off | A0h | 4Bh | P1 | 00h | St. | AFh | P1=00/01:Off/On |
| 30 | Call Slave Version | A0h | 4Dh | P1 | P2 | P3 | AFh | Version code:   P1 P2 P3(ASCII) |
| 31 | Frame Average | A0h | 4Eh | P1 | 00h | St. | AFh | P1=00/01:LCD/DLP |
| 32 | Call lamp Status | A0h | 50h | P1 | 00h | St. | AFh | 00    : Lamp + Head Led OFF<br>01    : Lamp + Head Led ON<br>02    : Lamp ON<br>03    : Head Led ON |
| 33 | Call Text/Photo Status | A0h | 51h | P1 | 00h | St. | AFh | P1=00/01/02:Photo/Text/Gray |
| 34 | reg1 | A0h | 52h | P1 | P2 | St. | AFh | P1=00/01:Read/Write        P2=0x00~0xff |
| 34 | reg2 | A0h | 53h | P1 | P2 | St. | AFh | |
| 36 | reg3 | A0h | 54h | P1 | P2 | St. | AFh | |
| 37 | Error Code | A0h | 55h | 00h | 00h | St. | AFh | p1=00/01:Show Error Code/Clear Error Code |
| 38 | AWB Correction | A0h | 56h | 00h | 00h | St. | AFh | AWB Correction |
| 39 | Call AC 50/60 Hzpower state | A0h | 58h | 00h | 00h | St. | AFh | Call AC 50/60 Hz power State. |
| 40 | Keypad Detect | A0h | 59h | 00h | 00h | St. | AFh | p1:00/01 :Keypad Detect Stop/Start. (Enable the Debug message at this time, the detection message will be sent via RS232.) |
| 41 | Call Zoom Position | A0h | 60h | P1 | P2 | St. | AFh | p1:low byte p2:high byte<br>XGA:805<br>SXGA:802 |

| Item | Function | PC AP to DC192 Master command format | | | | | | Comment |
|---|---|---|---|---|---|---|---|---|
| | | 1B | 2B | 3B | 4B | 5B | 6B | |
| | | | | | | | | WXGA:802<br>1080P:795<br>NTSC:810<br>PAL:810 |
| 42 | Call Digital Zoom Position | A0h | 62h | P1 | 00h | St. | AFh | p1:low byte p2:high byte<br>XGA:50<br>SXGA:53<br>WXGA:53<br>1080P:60<br>NTSC:45<br>PAL:45 |
| 43 | Call Focus Position | A0h | 64h | P1 | P2 | St. | AFh | P1(LowByte)P2(HighByte)=0~160(Dec) |
| 44 | Call Freeze Status | A0h | 78h | P1 | 00h | St. | AFh | P1=00/01:Off/On |
| 45 | Call Brightness Position | A0h | 89h | P1 | 00h | St. | AFh | P1=60/50Hz: 00~147(dec) |
| 46 | Call Mix Zoom Position | A0h | 8Ah | P1 | P2 | St. | AFh | p1:low byte p2:high byte 0~855<br>Optical Zoom:<br>XGA:805<br>SXGA:802<br>WXGA:802<br>1080P:795<br>NTSC:810<br>PAL:810 |
| 47 | Call Menu Status | A0h | 8Bh | P1 | 00h | St. | AFh | P1=00/01:Off/On |
| 48 | Capture Action | A0h | 96h | P1 | 00h | St. | AFh | 00　　: Single Capture<br>01　　: Time Lapse |

| Item | Function | PC AP to DC192 Master command format | | | | | | Comment |
|------|----------|----|----|----|----|----|----|---------|
| | | 1B | 2B | 3B | 4B | 5B | 6B | |
| | | | | | | | | 02    : Record<br>03    : Disabled |
| 49 | Capture time | A0h | 97h | P1 | 00h | St. | AFh | P1=00/01/02/03/04/05/06:1hr/2hr/4hr/<br>8hr/24hr/48hr/72hr |
| 50 | Capture interval | A0h | 98h | P1 | 00h | St. | AFh | 00    : 3 sec.<br>01    : 5 sec.<br>02    : 10 sec.<br>03    : 30 sec.<br>04    : 1 min.<br>05    : 2 min.<br>06    : 5 min. |
| 51 | Key Function | A0h | A0h | P1 | 00h | St. | AFh | P1=01/02/03/04/05/06=Enter/Up/Down/Left/Right/Menu |
| 52 | Set R/B Gain | A0h | A1h | P1 | P2 | St. | AFh | P1=01/02:Red Gain/Blue Gain<br>P2(LowByte)P3(HighByte)=0x100~0xFFF(hex):Gain |
| 53 | Call R/B Gain | A0h | A2h | P1 | P2 | St. | AFh | Send : P1=01/02:Red Gain/Blue Gain<br>Return :<br>P1(LowByte)P2(HighByte)=0x100~0xFFF(Dec):Gain |
| 54 | AF One Push Trigger | A0h | A3h | 01h | 00h | St. | AFh | |
| 55 | Set Gamma Mode | A0h | A7h | P1 | 00h | St. | AFh | P1=00/01/02:Photo/Text/Gray |
| 56 | Set Image Mode | A0h | A9h | P1 | 00h | St. | AFh | P1=00/01/02/03:Normal/Slide/Film/Microscope |
| 57 | System ON/OFF | A0h | B0h | P1 | 00h | St. | AFh | P1=00/01:Off/On |
| 58 | Power | A0h | B1h | P1 | 00h | St. | AFh | P1=00/01:Off/On |

| Item | Function | PC AP to DC192 Master command format | | | | | | Comment |
|------|----------|----|----|----|----|----|----|---------|
| | | 1B | 2B | 3B | 4B | 5B | 6B | |
| 59 | Capture | A0h | B2h | P1 | 00h | St. | AFh | P1=00/01:Capture/Record |
| 60 | Playback thumbnail | A0h | B3h | P1 | 00h | St. | AFh | P1=00:Thumbnail |
| 61 | Preview rotation | A0h | B4h | P1 | 00h | St. | AFh | P1=00/01/02/03:Rotate 0/180/Flip/Mirror |
| 62 | Delete | A0h | B6h | P1 | 00h | St. | AFh | P1=00/01/02: Delete one/Delete all/Format |
| 63 | call system status | A0h | B7h | P1 | P2 | St. | AFh | P1(system status)=00/01: not ready/ Read to receive the command<br>P2(Power Status)=00/01:Off/On |
| 64 | Lamp On/Off | A0h | C1h | P1 | 00h | St. | AFh | 00     : Lamp + Head Led OFF<br>01     : Lamp + Head Led ON<br>02     : Lamp ON<br>03     : Head Led ON |
| 65 | Firmware Upgrade | A0h | CBh | P1 | 00h | St. | AFh | P1=00/01:osd/no osd |
| 66 | Set Audio Microphone Volume | A0h | D4h | P1 | 00h | St. | AFh | P1=0~16(Dec):Volume |
| 67 | Call Audio Microphone Volume | A0h | D5h | P1 | P2 | St. | AFh | P1=0~16(Dec):Volume |
| 68 | Set Audio Out Volume | A0h | D6h | P1 | 00h | St. | AFh | P1=0~31(Dec):Volume |
| 69 | Call Audio Out Volume | A0h | D7h | P1 | P2 | St. | AFh | P1=0~31(Dec):Volume |

** St : 0 =Action Succeed, 1= NAK (No Action), 2 = Ignore (Command is not in the command list.)