

Machine Learning

Neural Network

Dr. Shuang LIANG

Today's Topics

- Neural Network Introduction
- Neural Network Structure
- How Neural Network Works
- Backpropagation

Today's Topics

- *Neural Network Introduction*
- Neural Network Structure
- How Neural Network Works
- Backpropagation

Neural networks are a hot topic



A bit of history

The **Mark I Perceptron** machine was the first implementation of the perceptron algorithm.


The machine was connected to a camera that used 20×20 cadmium sulfide photocells to produce a 400-pixel image.

recognized
letters of the alphabet

update rule:

$$w_i(t+1) = w_i(t) + \alpha(d_j - y_j(t))x_{j,i}$$



$$f(x) = \begin{cases} 1 & \text{if } w \cdot x + b > 0 \\ 0 & \text{otherwise} \end{cases}$$



This image by Rocky Acosta is licensed under [CC-BY 3.0](https://creativecommons.org/licenses/by/3.0/)

Frank Rosenblatt, ~1957: Perceptron

A bit of history



Widrow and Hoff, ~1960: Adaline/Madaline

These figures are reproduced from [Widrow 1960, Stanford Electronics Laboratories Technical Report](#) with permission from [Stanford University Special Collections](#).

A bit of history




Illustration of Rumelhart et al., 1986 by
Lane McIntosh, copyright CS231n 2017

Rumelhart et al., 1986: First time back-propagation became popular

A bit of history

[Hinton and Salakhutdinov 2006]

Reinvigorated research in
Deep Learning




Illustration of Hinton and Salakhutdinov
2006 by Lane McIntosh, copyright
CS231n 2017

A bit of history

First strong results

Acoustic Modeling using Deep Belief Networks

Abdel-rahman Mohamed, George Dahl, Geoffrey Hinton, 2010

Context-Dependent Pre-trained Deep Neural Networks for Large Vocabulary Speech Recognition

George Dahl, Dong Yu, Li Deng, Alex Acero, 2012

Imagenet classification with deep convolutional neural networks

Alex Krizhevsky, Ilya Sutskever, Geoffrey E Hinton, 2012






Illustration of Dahl et al. 2012 by Lane McIntosh, copyright CS231n 2017



Figures copyright Alex Krizhevsky, Ilya Sutskever, and Geoffrey Hinton, 2012. Reproduced with permission.

Ups and downs of Neural Networks

- 1958: Perceptron (linear model)
- 1969: Perceptron has limitation
- 1980s: Multi-layer perceptron
 - 1986: Backpropagation
- 1989: 1 hidden layer is “good enough”, why deep?
 - 2006: RBM initialization

Ups and downs of Neural Networks

- 2009: GPU
- 2011: Start to be popular in speech recognition
 - 2012: win ILSVRC image competition
- 2015.2: Image recognition surpassing human-level performance
 - 2016.3: Alpha GO beats Lee Sedol
- 2016.10: Speech recognition system as good as humans
 - Now: Transformer, BERT, Autopilot...


Neural Networks

(**Before**) Linear score function

$$f = Wx$$

(**Now**) 2-layer Neural Network

$$f = W_2 \max(0, W_1 x)$$




Biological neuron



This image by Fotis Bobotas is
licensed under [CC-BY 2.0](#)


Artificial neuron



Activation Function


Sigmoid

$$\sigma(x) = \frac{1}{1+e^{-x}}$$




tanh

$$\tanh(x)$$



ReLU

$$\max(0, x)$$



commonly used

Leaky ReLU

$$\max(0.1x, x)$$




Maxout

$$\max(w_1^T x + b_1, w_2^T x + b_2)$$



ELU

$$\begin{cases} x & x \geq 0 \\ \alpha(e^x - 1) & x < 0 \end{cases}$$




Biological v.s. Artificial

- From biological neuron to artificial neuron (perceptron)



Biological v.s. Artificial

- From biological neuron network to artificial neuron networks



Be very careful with your brain analogies!

- **Biological Neurons**


- Many different types
 - Dendrites can perform complex non-linear computations
 - Synapses are not a single weight but a complex non-linear dynamical system
 - Rate code may not be adequate
- We can ignore whether the neural network actually simulates a biological neural network, and just think of a neural network as **a mathematical model with many parameters**

Today's Topics

- Neural Network Introduction
- ***Neural Network Structure***
- How Neural Network Works
- Backpropagation


Perceptron

- It consists of two layers of neurons, the **input layer** and the **output layer**.




- Can realize logical AND, OR, NOT operation
- Only the neurons in the output layer perform activation function processing, and the learning ability is very limited
- Can't solve problems that are not linear separable, like XOR.

Multi-layer Network



Hidden layer and output layer neurons are
functional neurons with activation functions

Multi-layer Network



The learning process of the neural network is to adjust the **"connection weight"** between neurons and the **threshold** of each functional neuron according to the training data

Deep Neural Network

Deep = Many hidden layers


Now the commonly used
ResNet has reached **152** layers

8 layers


16.4%

7.3%

http://cs231n.stanford.edu/slides/winter1516_lecture8.pdf



AlexNet (2012)



19 layers

VGG (2014)



22 layers


6.7%

GoogleNet (2014)

Today's Topics


- Neural Network Introduction
- Neural Network Structure
- *How Neural Network Works*
- Backpropagation

Matrix Operation




$$\sigma\left(\underbrace{\begin{bmatrix} 1 & -2 \\ -1 & 1 \end{bmatrix} \begin{bmatrix} 1 \\ -1 \end{bmatrix} + \begin{bmatrix} 1 \\ 0 \end{bmatrix}}_{\begin{bmatrix} 4 \\ -2 \end{bmatrix}} \right) = \begin{bmatrix} 0.98 \\ 0.12 \end{bmatrix}$$

Function Nesting



Function Nesting




$$y = f(x)$$

Using parallel computing techniques
to speed up matrix operation


$$= \sigma(W^L \dots \sigma(W^2 \sigma(W^1 x + b^1) + b^2) \dots + b^L)$$

As a multi-class classifier



Case study


Handwriting Digit Recognition



Case study

Handwriting Digit Recognition


Input



Ink \rightarrow 1

No ink \rightarrow 0


Output



Each dimension represents the confidence of a digit.


Case study

Handwriting Digit Recognition



Case study

Handwriting Digit Recognition



You need to decide the network structure to let a good function in your function set.

Case study


Handwriting Digit Recognition

- How many layers? How many neurons for each layer?

Trial and Error

+

Intuition



Today's Topics

- Neural Network Introduction
- Neural Network Structure
- How Neural Network Works
- *Backpropagation*

Neural Network Optimization

- We have already learned to optimize the learner using the gradient descent method
- Can neural networks also be optimized using gradient descent?

Case: CNN (AlexNet)




Figure copyright Alex Krizhevsky, Ilya Sutskever, and Geoffrey Hinton, 2012. Reproduced with permission.

Case: Neural Turing Machine

input image

loss




Figure reproduced with permission from a [Twitter post](#) by Andrej Karpathy.

Why we need BP

- If we use gradient descent directly

Network parameters $\theta = \{w_1, w_2, \dots, b_1, b_2, \dots\}$

Starting Parameters $\theta^0 \longrightarrow \theta^1 \longrightarrow \theta^2 \longrightarrow \dots$

$$\nabla L(\theta) = \begin{bmatrix} \partial L(\theta) / \partial w_1 \\ \partial L(\theta) / \partial w_2 \\ \vdots \\ \partial L(\theta) / \partial b_1 \\ \partial L(\theta) / \partial b_2 \\ \vdots \end{bmatrix}$$

Compute $\nabla L(\theta^0)$ $\theta^1 = \theta^0 - \eta \nabla L(\theta^0)$

Compute $\nabla L(\theta^1)$ $\theta^2 = \theta^1 - \eta \nabla L(\theta^1)$


Millions of parameters

To compute the gradients efficiently,
we use **backpropagation**.

BP: A simple example

$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$



BP: A simple example


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



BP: A simple example


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



BP: A simple example


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



BP: A simple example


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



BP: A simple example


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



BP: A simple example


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



BP: A simple example


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial y}$$

BP: A simple example


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



Chain rule:

$$\frac{\partial f}{\partial y} = \frac{\partial f}{\partial q} \frac{\partial q}{\partial y}$$

$$\frac{\partial f}{\partial y}$$

BP: A simple example


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial x}$$

BP: A simple example


$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$




$$\frac{\partial f}{\partial x}$$


Chain rule:

$$\frac{\partial f}{\partial x} = \frac{\partial f}{\partial q} \frac{\partial q}{\partial x}$$


Backpropagation




Backpropagation




Backpropagation




Backpropagation



Backpropagation




Backpropagation



BP: Another example

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$$



$$f(x) = e^x$$

→

$$\frac{df}{dx} = e^x$$

$$f(x) = \frac{1}{x}$$

→

$$\frac{df}{dx} = -1/x^2$$

$$f_a(x) = ax$$

→

$$\frac{df}{dx} = a$$


$$f_c(x) = c + x$$

→

$$\frac{df}{dx} = 1$$

BP: Another example

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$$



$$f(x) = e^x$$

→

$$\frac{df}{dx} = e^x$$

$$f_a(x) = ax$$

→

$$\frac{df}{dx} = a$$

$$f(x) = \frac{1}{x}$$

→

$$\frac{df}{dx} = -1/x^2$$


$$f_c(x) = c + x$$

→

$$\frac{df}{dx} = 1$$

BP: Another example

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$$



$$f(x) = e^x$$

→

$$\frac{df}{dx} = e^x$$

$$f_a(x) = ax$$

→

$$\frac{df}{dx} = a$$

$$f(x) = \frac{1}{x}$$

→

$$\frac{df}{dx} = -1/x^2$$


$$f_c(x) = c + x$$

→

$$\frac{df}{dx} = 1$$

BP: Another example

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$$



$$f(x) = e^x$$

→

$$\frac{df}{dx} = e^x$$

$$f(x) = \frac{1}{x}$$

→

$$\frac{df}{dx} = -1/x^2$$

$$f_a(x) = ax$$

→

$$\frac{df}{dx} = a$$


$$f_c(x) = c + x$$

→

$$\frac{df}{dx} = 1$$

BP: Another example

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$$



$$f(x) = e^x$$

→

$$\frac{df}{dx} = e^x$$

$$f(x) = \frac{1}{x}$$

→

$$\frac{df}{dx} = -1/x^2$$

$$f_a(x) = ax$$

→

$$\frac{df}{dx} = a$$


$$f_c(x) = c + x$$

→

$$\frac{df}{dx} = 1$$

BP: Another example

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$$



$$f(x) = e^x \rightarrow \frac{df}{dx} = e^x$$


$$f_a(x) = ax \rightarrow \frac{df}{dx} = a$$

$$f(x) = \frac{1}{x} \rightarrow \frac{df}{dx} = -1/x^2$$

$$f_c(x) = c + x \rightarrow \frac{df}{dx} = 1$$

BP: Another example

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$$



$$f(x) = e^x \rightarrow \frac{df}{dx} = e^x$$


$$f_a(x) = ax \rightarrow \frac{df}{dx} = a$$

$$f(x) = \frac{1}{x} \rightarrow \frac{df}{dx} = -1/x^2$$

$$f_c(x) = c + x \rightarrow \frac{df}{dx} = 1$$

BP: Another example

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$$



$$f(x) = e^x$$

→

$$\frac{df}{dx} = e^x$$

$$f(x) = \frac{1}{x}$$

→

$$\frac{df}{dx} = -1/x^2$$

$$f_a(x) = ax$$

→

$$\frac{df}{dx} = a$$


$$f_c(x) = c + x$$

→

$$\frac{df}{dx} = 1$$

BP: Another example

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$$



$$f(x) = e^x$$

→

$$\frac{df}{dx} = e^x$$

$$f(x) = \frac{1}{x}$$

→

$$\frac{df}{dx} = -1/x^2$$

$$f_a(x) = ax$$

→

$$\frac{df}{dx} = a$$


$$f_c(x) = c + x$$

→

$$\frac{df}{dx} = 1$$

BP: Another example

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$$



$$f(x) = e^x$$

→

$$\frac{df}{dx} = e^x$$

$$f(x) = \frac{1}{x}$$

→

$$\frac{df}{dx} = -1/x^2$$

$$f_a(x) = ax$$

→

$$\frac{df}{dx} = a$$

$$f_c(x) = c + x$$

→

$$\frac{df}{dx} = 1$$


BP: Another example

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$$

[local gradient] x [upstream gradient]

$$[1] \times [0.2] = 0.2$$

$$[1] \times [0.2] = 0.2 \text{ (both inputs!)}$$



$$f(x) = e^x$$

→

$$\frac{df}{dx} = e^x$$

$$f(x) = \frac{1}{x}$$

→

$$\frac{df}{dx} = -1/x^2$$

$$f_a(x) = ax$$

→

$$\frac{df}{dx} = a$$


$$f_c(x) = c + x$$

→

$$\frac{df}{dx} = 1$$

BP: Another example

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$$



$$f(x) = e^x$$

→

$$\frac{df}{dx} = e^x$$

$$f(x) = \frac{1}{x}$$

→

$$\frac{df}{dx} = -1/x^2$$

$$f_a(x) = ax$$

→

$$\frac{df}{dx} = a$$


$$f_c(x) = c + x$$

→

$$\frac{df}{dx} = 1$$

BP: Another example

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$$



[local gradient] x [upstream gradient]

$$x_0: [2] \times [0.2] = 0.4$$

$$w_0: [-1] \times [0.2] = -0.2$$

$$f(x) = e^x$$

→

$$\frac{df}{dx} = e^x$$

$$f(x) = \frac{1}{x}$$

→

$$\frac{df}{dx} = -1/x^2$$

$$f_a(x) = ax$$

→

$$\frac{df}{dx} = a$$

$$f_c(x) = c + x$$


→

$$\frac{df}{dx} = 1$$

BP: Another example

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}} \quad \sigma(x) = \frac{1}{1 + e^{-x}} \text{ sigmoid function}$$


$$\frac{d\sigma(x)}{dx} = \frac{e^{-x}}{(1 + e^{-x})^2} = \left(\frac{1 + e^{-x} - 1}{1 + e^{-x}} \right) \left(\frac{1}{1 + e^{-x}} \right) = (1 - \sigma(x)) \sigma(x)$$



BP: Another example

$$f(w, x) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}} \quad \sigma(x) = \frac{1}{1 + e^{-x}} \text{ sigmoid function}$$

$$\frac{d\sigma(x)}{dx} = \frac{e^{-x}}{(1 + e^{-x})^2} = \left(\frac{1 + e^{-x} - 1}{1 + e^{-x}} \right) \left(\frac{1}{1 + e^{-x}} \right) = (1 - \sigma(x)) \sigma(x)$$



Summary

- **Neuron**
 - Input and output
- **Neural Networks**
 - Perceptron
 - Multi-layer network
 - Deep neural networks
- **How Neural Network Works**
 - Calculation process
 - Work as a multi-class classifier
- **Backpropagation**

Thinking

- Are more layers in a neural network better?
- Why shouldn't we use linear function as activation function of neural network?