

Contents

Basic Information

Overview:2

Installation:3

Input:4

DPMJET:7

Output.....9

Extended Information

Class Diagram11

File Descriptions.....12

Overview:

The STARlight Monte Carlo models 2-photon and photon-Pomeron interactions in ultra-peripheral heavy ion collisions. The physics approach for the photon-Pomeron interactions is described in Klein and Nystrand, Phys. Rev. C60, 014903 (1999), with the p_t spectrum (including vector meson interference) discussed in Phys. Rev. Lett. 84, 2330 (2000). The 2-photon interactions are described in Baltz, Gorbunov, Klein, Nystrand, Phys.Rev. C80 044902 (2009).

STARlight has several input files, all of which are expected to be in the same directory as the starlight code. User-specified input parameters are read from a file named "slight.in"; these parameters are described below in [Input](#).

The simulated events are written to an ASCII file named "slight.out", which is described below in [Output](#).

Installation:

To obtain the latest version:

```
-svn co http://starlight.hepforge.org/svn/trunk
```

Alternatively:

```
-Visit https://starlight.hepforge.org/trac/browser
```

```
-Download the trunk [click on the download symbol in the Size column]
```

```
-Unpackage the zip file. The trunk/ represents <PathToSource>
```

To build Starlight:

```
- First create your build directory <BUILDDIR> (e.g. mkdir bin)
```

```
- $ cd <BUILDDIR>
```

```
- $ cmake <PathToSource>
```

```
- $ make
```

This creates an executable file, `starlight`, in the build directory.

To clean the build:

```
- $ make clean
```

To run `starlight`, a configuration file, `slight.in`, is needed. Examples of `slight.in` may be found in the `config/` directory.

To run:

```
$ ./starlight
```

Enabling Pythia:

To simulate the η , η' , and η_c channels, you need Pythia v8.2 or higher to handle their decays. To enable Pythia support you need to run `cmake` with the option `-DENABLE_PYTHIA=ON` and have `$PYTHIADIR` pointing to the top directory of Pythia8. [Note: when building Pythia, be sure to enable shared libraries(.so). `./configure --enable-shared` before compiling Pythia.]

```
$ setenv PYTHIADIR /my/local/pythia8
```

```
$ cmake <PathToSource> -DENABLE_PYTHIA=ON
```

Note: v8.2+ is necessary since the Pythia directory structure changed[trunk/cmake_modules/FindPythia8.cmake depends on the structure layout], `liblhpdfdummy` was removed, and `Standalone:allowResDec` was removed.

To enable DPMJET, please see the passage on [DPMJET](#)

Input:

The contents of a sample slight.in file are listed below, with explanation. The user should modify this file according to his or her needs.

```
baseFileName          #The output file name. STARlight will copy the
                        input slight.in to baseFileName.in, and produce
                        output files baseFileName.txt and baseFileName.out
                        (formerly known as slight.txt and slight.out)

BEAM_1_Z = 82          #Z of projectile
BEAM_1_A = 208         #A of projectile
BEAM_2_Z = 82          #Z of target
BEAM_2_A = 208         #A of target
BEAM_GAMMA = 1470      #Gamma of the colliding ions
BEAM_1_GAMMA = 1470.0  #Gamma of the colliding ions in beam 1
BEAM_2_GAMMA = 1470.0  #Gamma of the colliding ions in beam 2
W_MAX = 12.0           #Max value of w-Maximum value for the gamma-gamma
                        center of mass energy,  $W = 4E_1E_2$ , in GeV. Setting
                        W_MAX = -1 tells STARlight to use the default
                        value specified in inputParameters.cpp
                        (recommended for single meson production). For
                        single mesons, the default W_MAX is the particle
                        mass plus five times the width. For lepton pairs,
                        the default W_MAX is given by  $2\hbar c \sqrt{\frac{Y_1 Y_2}{R_1 R_2}}$ . For other
                        definitions, please check src/inputParameters.cpp.

W_MIN = -1             #Min value of w. Minimum value for the gamma-gamma
                        center of mass energy,  $W = 4E_1E_2$ , in GeV. Setting
                        W_MIN = -1 tells STARlight to use the default
                        value specified in inputParameters.cpp
                        (recommended for single meson production). The
                        default W_MIN is the larger of the kinematic limit
                        ( e.g.  $2m_\pi$  for  $\rho$  decays) or the particle mass
                        minus five times the width.

W_N_BINS = 40          #Bins w maximum and minimum values for w (the
                        gamma-gamma center of mass energy,  $w = 4(E_1)(E_2)$ ,
                        and the number of w bins in the lookup tables

RAP_MAX = 8.           # max rapidity
RAP_N_BINS = 80        # Number of y bins used in the cross section
                        calculation

CUT_PT = 0             #Cut in pT? 0 = (no, 1 = yes)
PT_MIN = 1.0           #Minimum pT in GeV
PT_MAX = 3.0           #Maximum pT in GeV
CUT_ETA = 0            #Cut in pseudorapidity (0 = no, 1 = yes)
ETA_MIN = -10          #Minimum pseudorapidity
ETA_MAX = 10           #Maximum pseudorapidity
PROD_MODE = 2          #gg or gP switch (1 = Two-photon interaction. 2 =
                        Coherent photonuclear vector meson production.
                        This option should also be used for exclusive
                        vector meson production in pp collision. In pA
                        collisions, this option means that the proton
```

```

emits the photon and that the gamma-A interaction
is coherent. 4 = Incoherent photonuclear vector
meson production. In pA collisions, this option
means that the nucleus emits the photon. 5 =
Photonuclear one photon exchange uses DPMJET
single. 6 = Photonuclear two photon exchange (both
nuclei excited) uses DPMJET double. 7 =
Photonuclearsinglepa uses DPMJET Single, proton
mode)
N_EVENTS = 10      #Number of events produced
PROD_PID = 443013  #Channel of interest (in PDG notation); currently
                   #supported options listed below
RND_SEED = 34533   #Random number seed
BREAKUP_MODE = 5   #Controls the nuclear breakup
                   #This option only works for lead or gold-not pp or
                   #pA
                   # 1 = hard sphere nuclei (b>2R)
                   # 2 = require that both nuclei break up (Xn,Xn)
                   # 3 = a single neutron from each nucleus (1n,1n)
                   # 4 = require that neither nucleus breaks
                   # up(0n,0n)
                   # 5 = require that there be no hadronic
                   # interactions (This is similar to option 1, but
                   # with the actual hadronic interaction probability)
                   # 6 = require break up of one or both nuclei with
                   # no restriction on the number of neutrons emitted.
                   # (XnXn+0nXn+Xn0n)
                   # 7 = require break up of one nucleus (Xn,0n)

INTERFERENCE = 0   #Interference (0 = off, 1 = on)
IF_STRENGTH = 1.   #% of interference (0.0 - 0.1)
INT_PT_MAX = 0.24  #Maximum pt considered, when interference is
                   #turned on
INT_PT_N_BINS =120 #Number of pt bins when interference is turned on

```

Channels of Interest:

2-Photon Channels

Currently supported 2-photon (prod. mode = 1) channel options:

jetset id	particle
221	eta
331	eta-prime
441	eta-c
9010221	f0(975)
225	f2(1270)
115	a2(1320)
335	f2(1525)
33	rho0 pair
11	e+/e- pair
13	mu+/mu- pair
15	tau+/tau- pair

Pomeron-Photon Channels

Currently supported vector meson (prod. mode = 2/3/4) options:

jetset id	particle
-----------	----------

113	rho0
223	omega
333	phi
443011	J/psi --> e+e-
443013	J/Psi --> mu+mu-
444011	Psi(2S) --> e+e-
444013	Psi(2S) --> mu+mu-
553011	Upsilon(1S) --> e+e-
553013	Upsilon(1S) --> mu+mu-
554011	Upsilon(2S) --> e+e-
554013	Upsilon(2S) --> mu+mu-
555011	Upsilon(3S) --> e+e-
555013	Upsilon(3S) --> mu+mu-
913	rho0 + direct pi+pi- (with interference). The direct pi+pi- fraction is from the ZEUS results, EPJ C2 p247 (1998)
999	four-prong final states (rho'-like to pi+pi-pi+pi-)

DPMJET:

Simulation of photonuclear interactions with STARlight is possible through an interface with DPMJet. These interfaces can be enabled through options passed to cmake during the configuration process. [Deprecated: Using Pythia 6 as a substitute for DPMJet]

The gfortran compiler is required to use the photonuclear interfaces.

===== 1. Photonuclear interactions with DPMJet =====

----- 1.1. Obtaining and installing DPMJet -----

The DPMJet package can be obtained by contacting the authors as explained here: <http://sroesler.web.cern.ch/sroesler/dpmjet3.html>

Once you have the code proceed with these steps:

Change the line containing the OPT variable in the DPMJet Makefile:

```
OPT = -c -C -std=legacy -O -O3 -g -fexpensive-optimizations
      -funroll-loops -fno-automatic -fbounds-check -v -fPIC
```

----- 64-bit -----

Make sure that all -m32 options are removed from the Makefile.

Unfortunately, the DPMJet package depends on a floating point exception trap implementation, and only a 32-bit version of that is included in the package, which needs to be replaced. An example implementation can be found here:

<http://www.arsc.edu/arsc/support/news/hpcnews/hpcnews376/>

Under "Fortran Floating Point Traps for Linux" there is a code example. A file based on this, fpe.c, can be found in the external/ directory in STARlight. Move that to your DPMJet directory to replace the original file and run:

```
$ gcc -o fpe.o fpe.c
```

Note: if the above command returns the following error:
*/usr/lib/../../lib64/crt1.o: In function `_start':
(.text+0x20): undefined reference to `main'
/tmp/ccs2CQsd.o: In function `enable_exceptions':
fpe.c:(.text+0xe): undefined reference to `feenableexcept'*

collect2: error: ld returned 1 exit status

Try: gcc fpe.c -Wall -g -c

feenableexcept is a gcc extension and gcc may need all of the headers present.

----- End 64-bit -----

Then in the DPMJet directory run:

\$ make

Note: When compiling at RCAS(BNL), needed to change g77 → gfortran, needed to install fluka and setenv FLUPRO /path/to/fluka, and modify phojet before compiling. The changes for phojet is at line 29875, from:

```
PRINT LO,'PHO_DIFSLP:ERROR: this option is not installed !'
```

to:

```
WRITE(LO,'(/1X,A,I2)')  
& 'PHO_DIFSLP:ERROR: this option is not installed  
& !',ISWMDL(13)
```

----- 1.2. Compiling Starlight with DPMJet interface -----

To enable the compilation of the DPMJet interface please follow these steps:

CMake uses an environment variable \$DPMJETDIR to locate the DPMJet object files, so define it.

\$ export DPMJETDIR=<path to dpmjet>

Then create a build directory for STARlight

\$ mkdir <build-dir>

and change into it

\$ cd <build-dir>

Run CMake with the option to enable DPMJet

\$ cmake <path-to-starlight-source> -DENABLE_DPMJET=ON

Then build it

\$ make

Note: When compiling at RCAS(BNL), needed to add the gfortran library to the CMakeLists.txt and left it there.

----- 1.3. Running Starlight with DPMJet interface -----

To run Starlight with the DPMJet interface a couple of files are needed in the directory where you want to run Starlight.

The files needed are:

- slight.in** (Starlight config file. An example suitable for DPMJet can be found in config/slight.in.dpmjet)
- my.input** (DPMJet config file. An example can be found in config/my.input)
- dpmjet.dat** (Can be found in the DPMJet source directory)

In the slight.in file the relevant production modes (PROD_MODE) for DPMJET is:

- 5: A+A single excitation
- 6: A+A double excitation
- 7: p+A single excitation

In addition the minimum and maximum gamma energies must be set. These must be within the interval set in the my.input file.

To run:

```
$ ./starlight < my.input
```

```
[DPMJET reads from direct input/interactive]
```

Output

STARlight outputs an ASCII file named slight.out.

For each event, a summary line is printed, with the format

EVENT: n ntracks nvertices ,

where n is the event number (starting with 1), ntracks is the number of tracks in the event, and nvertices is the number of vertices in the event (STARlight does not currently produce events with more than one vertex).

EVENT line is followed by a description of the vertex, with the format

VERTEX: x y z t nv nproc nparent ndaughters ,


where x , y , z and t are the 4-vector components of the vertex location, nv is the vertex number, $nproc$ is a number intended to represent physical process (always set to 0), $nparent$ is the track number of parent track (0 for primary vertex) and $ndaughters$ is the number of daughter tracks from this vertex.

This is followed by a series of lines describing each of the daughter tracks emanating from this vertex. Each track line has the format

TRACK: GPID px py pz nev ntr stopv PDGPID ,

where GPID is the Geant particle id code, px , py and pz are the three vector components of the track's momentum, nev is the event number, ntr is the number of this track within the vertex (starting with 0), $stopv$ is the vertex number where track ends (0 if track does not terminate within the event), and PDGPID is the Monte Carlo particle ID code endorsed by the Particle Data Group.

Class Diagram



File Descriptions

Readme.pdf

[This file.] provides information on the installation, operation, and construction of STARlight.

CMakeLists.txt

controls STARlight compilation. For details, please see above in [Installation](#). This is the default/supported compilation method.

Makefile

A sample Makefile for compilation on *nix systems. This file is not actively supported. Please use CMake.

starlightconfig.h.in

passes on some compiler settings; such as enabling the Pythia/DPMJet sections within the source code.

starlightDoxyfile.conf

Doxygen configuration file.

CMake Modules:

FindPythia8.cmake

used by CMake to find the Pythia 8 files needed to compile STARlight with Pythia 8 dependent options enabled. It searches for: Pythia.h, Index.xml, libpythia8

FindPythia6.cmake

used by CMake to find the Pythia 6 files needed to compile STARlight with Pythia 6 dependent options enabled. It searches for: libPythia6. *Pythia 6 functionality has been deprecated.*

FindDPMJet.cmake

used by CMake to find the DPMJET files needed to compile STARlight with DPMJET dependent options enabled. It searches for: dpmjet3.0-5.o, pythia6l15dpm3v1.o, and phojet1.12-35c4.o

FindROOT.cmake

used by CMake to find the ROOT files needed to compile STARlight with ROOT dependent options enabled. It searches for: root-config. root-config is then used to set the rest of the paths/options needed to enable ROOT within STARlight.

CommonMacros.cmake

A collection of useful cmake macros.

FindLHAPDF.cmake

used by CMake to find the LHAPDF dependent options enabled. This was necessary for older versions of Pythia8, but this is no longer the case. However, this file is being kept in the

distribution for users that would like to re-enable it. It searches for: Pythia.h and liblhpdfdummy

Config files:

my.input

A sample DPMJET configuration file.

slight.in

A sample STARlight input file, to select the desired final state and associated options. The section [Input](#) has more information.

slight.in.dpmjet

A sample slight.in file to use the DPMJET options (eg: PROD_MODE = 5, 6, 7, and MIN_GAMMA_ENERGY, and MAX_GAMMA_ENERGY.).

slight.in.ee_rhic

A sample slight.in file for e+e- production by Au-Au at top RHIC energies

slight.in.jpsi_lhc

A sample slight.in file for J/ψ production by Pb-Pb at the LHC.

slight.in.pPb_lhc

A sample slight.in file for J/ψ production by p-Pb at the LHC.

slight.in.rho_rhic

A sample slight.in file for ρ production by Au-Au at top RHIC energies.

dpmjet:

dpmjetint.f

This is a DPMJET library, used in the CMakeLists.txt file to link when enabling DPMJET.

external:

fpe.c

corrects for the floating point trap differences between 32 and 64-bit. The [DPMJET section](#) has more information.

pythia6:

pythiainterface.h

interfaces Pythia6 with STARlight. *Pythia 6 functionality has been deprecated.*

utils:

Ana.C

This macro runs Analyze.cxx, which takes as input an ASCII STARlight output file, slight.out, and creates a standard set of histograms, which are stored in histograms.root

Analyze.cxx

This macro reads in a starlight output file and creates histograms of the p_T and rapidity of the daughters, as well as the p_T , rapidity and mass of the parent. It assumes there are only 2 daughter tracks that are electrons, muons, or pions. The histograms for the daughter particles are called fPt2, fPt2, fRap1, and fRap2. Parent histograms are created for each possible daughter species (e.g., parent p_T histograms are created with the names fPtEl, fPtMu, and fPtPi), but only the ones corresponding to the actual daughter particle are filled. The histograms are saved in a file called histograms.root.

To use this Analyze.cxx, modify the file Ana.C to call your input file (as downloaded, it calls slight.out) and the number of events you wish to process (as downloaded, it processes 20 events). Then open root and type ".x Ana.C" .

Analyze.h

The header file for Analyze.cxx and Ana.C.

AnalyzeTree.cxx

This macro reads the starlight.root file produced by ConvertStarlightAsciiToTree.C, which contains TLorentzVectors for the parents and a TClonesArray of TLorentzVectors for the daughters. It creates histograms of the p_T and rapidity of the daughters, as well as the p_T , rapidity and mass of the parent. While the parents may have been created as the vector sum of any number of daughter particles, this macro currently produces histograms for only the first two daughter particles. The daughter histograms are called D1Pt, D2Pt, D1Rapidity, and D1Rapidity. Parent histograms are named ParentPt, ParentRapidity, and ParentMass. The histograms are stored in starlight_histos.root.

To use Analyzetree.cxx, first run ConvertStarlightAsciiToTree.C to produce the starlight.root file. If needed, modify the file AnalyzeTree.h to call your input file (as downloaded, it calls starlight.root). Then open root and type .x AnaTree.C .

AnalyzeTree.h

The header file for AnalyzeTree.cxx.

AnaTree.C

compiles and runs AnalyzeTree.cxx, which takes as input the starlight.root file produced by ConvertStarlightAsciiToTree.cxx output histograms are stored in starlight_histos.root

ConvertStarlightAsciiToTree.C

reads a starlight output file (default name slight.out) and creates a root file with TLorentzVectors for the parent and a TClonesArray of TLorentzVectors for the daughter particles. The output is stored in a root file (default name starlight.root) with one branch labeled "parent" and the other labeled "daughters". Any number of daughter tracks can be accommodated. Daughter species currently accommodated are: electrons, muons, charged or neutral pions, charged or neutral kaons, and protons.

To use AnaTree.C, open root and then type `.x ConvertStarlightAsciiToTree.C("inputfilename", "outputfilename")` The root file produced can be examined in a root TBrowser.

A macro to read this root file and make some standard plots is also provided. This macro is called AnalyzeTree.cxx; it can be compiled and run with the AnaTree.C macro by opening root and typing `.x AnaTree.C()`

Source Files:

beam.cpp

generates the beam class, which inherits from the nucleus class (cf. [nucleus.cpp](#)). The object represents an accelerated nucleus, or a beam.

Functions:

```
beam::beam
beam::~~beam
beam::photonFlux // calculates the "photon density" given
                  the impact parameter and energy.
```

beambeamsystem.cpp

represents the colliding system of interest.

Functions:

```
beamBeamSystem::beamBeamSystem
beamBeamSystem::~~beamBeamSystem
beamBeamSystem::probabilityOfBreakup
beamBeamSystem::generateBreakupProbabilities
beamBeamSystem::probabilityOfHadronBreakup
beamBeamSystem::probabilityOfPhotonBreakup
```

bessel.cpp

calculate modified Bessel functions of the first and second kind.

Functions:

```
bessel::besI0
bessel::dbesk0
bessel::dbesk1
bessel::besI1
```

eventchannel.cpp

inherits from readLuminosity. It is a base for class for functions to produce events that is overloaded by other classes (Gammagammaleptonpair, Gammagammasingle, Gammaavectormeson, starlightDpmJet, and starlightPythia).

Functions:

```
eventChannel::eventChannel
eventChannel::~~eventChannel
eventChannel::transform // Lorentz Tranforms the frame
eventChannel::pseudoRapidity // calculates the
    pseudorapidity with the input from px, py, and pz
```

eventfilewriter.cpp

writes event information in the output file.

Functions:

```
eventFileWriter::eventFileWriter
eventFileWriter::~~eventFileWriter
eventFileWriter::writeEvent
```

filewriter.cpp

The base class for eventFileWriter, which is writes event information in the output file.

Functions:

```
fileWriter::fileWriter()
fileWriter::~~fileWriter()
fileWriter::open
fileWriter::open(filename)
fileWriter::close
```

gammaaluminosity.cpp

contains the photonNucleusLuminosity class, which inherits from photonNucleusCrossSection. It calculates the differential cross-section for gamma-A interactions.

Functions:

```
photonNucleusLuminosity::photonNucleusLuminosity
photonNucleusLuminosity::~~photonNucleusLuminosity
photonNucleusLuminosity::photonNucleusDifferentialLuminosity //Calculates and outputs the differential luminosity
photonNucleusLuminosity::pttablegen // Calculates the pt spectra for VM production with interference per S. Klein and J. Nystrand, Phys. Rev Lett. 84, 2330 (2000).
photonNucleusLuminosity::vmsigmapt //calculates th effect of the nuclear form factor on the pt spectrum, for use in interference calculations. It calculates the cross section suppression SIGMAPT(PT) as a function of pt. The input pt values come from pttable.inc
photonNucleusLuminosity::nofe //calculates the 'photon density'd^2N_gamma/db^2
```

gammaavm.cpp

is responsible for classes Gammaavectormeson, Gammaanarrowvm, and Gammaawidevm. Both Gammaanarrowvm and Gammaawidevm inherit from Gammaavectormeson, which inherits from eventChannel. The classes are responsible for generating and decaying the vector mesons produced by photon-nucleus interactions.

Functions:

```

Gammaavectormeson::Gammaavectormeson
Gammaavectormeson::~~Gammaavectormeson
Gammaavectormeson::pickwy //responsible for selecting the
events center of mass energy and rapidity
Gammaavectormeson::twoBodyDecay // This routine decays a
particle into two particles of mass mdec, taking spin into
account
Gammaavectormeson::fourBodyDecay // decays a particle into
four particles with isotropic angular distribution
Gammaavectormeson::getDaughterMass //returns the daughter
particles mass, & the final particles id...
Gammaavectormeson::getTheta //This depends on the decay
angular distribution
Gammaavectormeson::getWidth
Gammaavectormeson::getMass
Gammaavectormeson::getSpin //it's a VM, returns 1
Gammaavectormeson::momenta // calculates momentum and
energy of vector meson given W and Y, without
interference.
Gammaavectormeson::pTgamma //finds the photon pT
Gammaavectormeson::vmpt // calculates momentum and energy
of a vector meson given W and Y, including interference.
It gets the pt distribution from a lookup table.
produceEvent
pseudorapidity
Gammaanarrowvm::Gammaanarrowvm
Gammaanarrowvm::~~Gammaanarrowvm
Gammaanarrowvm::gammaaincoherentvm
Gammaawidevm::Gammaawidevm
Gammaawidevm::~~Gammaawidevm

```

gammagammaleptonpair.cpp

inherits from eventChannel. It calculates the lepton pair's cross-section and generates and decays the lepton pairs.

Functions:

```

Gammagammaleptonpair::Gammagammaleptonpair
Gammagammaleptonpair::~~Gammagammaleptonpair
Gammagammaleptonpair::twoLeptonCrossSection // calculates
section for 2-particle decay, per, see STAR Note 243, Eq.
9. It calculates the 2-lepton differential cross section
Gammagammaleptonpair::twoMuonCrossSection // gives the
two muon cross section as a function of Y&W, per G.Soff
et. al Nuclear Equation of State, part B, 579
Gammagammaleptonpair::pickw // Picks a w for the 2- photon
calculation.
Gammagammaleptonpair::picky // Picks a y given a W
Gammagammaleptonpair::pairMomentum // calculates
px,py,pz,and E given w and y
Gammagammaleptonpair::pp_1 // For beam 1, returns a
random momentum drawn from from pp_1(E) distribution
Gammagammaleptonpair::pp_2 // For beam 2, returns a
random momentum drawn from from pp_2(E) distribution
Gammagammaleptonpair::twoBodyDecay //decays a particle
into two particles of mass mdec, taking spin into account

```

```

Gammagammaleptonpair::thetalep // calculates the cross-
section as a function of angle for a given W and Y, for
the production of two muons or taus, per Brodsky et al.
PRD 1971, 1532 equation 5.7
Gammagammaleptonpair::produceEvent //returns the vector
with the decay particles inside
Gammagammaleptonpair::calculateTable //calculates the
tables that are used elsewhere in the Monte Carlo the tau
decay follows V-A theory,  $1 - 1/3 \cos(\theta)$  the energy of
each of the two leptons in tau decay is calculated using
formula 10.35 in "Introduction to elementary particles by
D. Griffiths," which assumes that the mass of the electron
is 0. The maximum electron energy in in such a system is
 $0.5 * \text{mass of the tau}$ 
Gammagammaleptonpair::tauDecay // assumes that the
taus decay to electrons and calculates the directions of
the decays
Gammagammaleptonpair::getMass
Gammagammaleptonpair::getWidth
Gammagammaleptonpair::getSpin

```

gammagammasingle.cpp

inherits from eventChannel. It calculates the cross-section for single mesons and generates and decays the single mesons from gamma-gamma interactions. It also generates single mesons which are then decayed by Pythia 8.

Functions:

```

Gammagammasingle::Gammagammasingle
Gammagammasingle::~~Gammagammasingle
Gammagammasingle::singleCrossSection // calculates the
cross-section in the narrow-width approximation, per STAR
Note 243, Eq. 8
Gammagammasingle::pickw // picks a w for the 2-photon
calculation.
Gammagammasingle::picky
Gammagammasingle::parentMomentum // calculates
px,py,pz,and E given w and y
Gammagammasingle::pp_1 // For beam 1, returns a random
momentum drawn from from pp(E) distribution
Gammagammasingle::pp_2 // For beam 2, returns a random
momentum drawn from from pp(E) distribution
Gammagammasingle::twoBodyDecay //decays a particle into
two particles of mass mdec, taking spin into account
Gammagammasingle::produceEvent
Gammagammasingle::getMass
Gammagammasingle::getSpin

```

incoherentPhotonNucleusLuminosity.cpp

is responsible for the incoherentPhotonNucleusLuminosity class and inherits from photonNucleusCrossSection. It houses the differential luminosity calculation for incoherent gamma-A interactions.

Functions:

```

incoherentPhotonNucleusLuminosity::incoherentPhotonNucleus
Luminosity

```

```

        incoherentPhotonNucleusLuminosity::~~incoherentPhotonNucleu
        sLuminosity
        incoherentPhotonNucleusLuminosity::incoherentPhotonNucleu
        sDifferentialLuminosity
        incoherentPhotonNucleusLuminosity::nofe //Function for the
        calculation of the "photon density".

incoherentVMCrossSection.cpp
    inherits from photonNucleusCrossSection. It calculates the
    cross-section for incoherent photon-nucleus interactions.
Functions:
    incoherentVMCrossSection::incoherentVMCrossSection
    incoherentVMCrossSection::~~incoherentVMCrossSection
    incoherentVMCrossSection::crossSectionCalculation //
    calculates the vector meson cross section assuming a
    narrow resonance. For reference, see STAR Note 386.

inputParameters.cpp
    sets and stores STARlight's input parameters.
Functions:
    inputParameters::inputParameters
    inputParameters::~~inputParameters
    inputParameters::init
    inputParameters::configureFromFile
    inputParameters::print
    inputParameters::write
    inputParameters::parameterValueKey

inputParser.cpp
    parses the input files and stores the information in the
    inputParameters.
Functions:
    inputParser::inputParser()
    inputParser::~~inputParser()
    inputParser::parseFile
    inputParser::parseString
    inputParser::addIntParameter
    inputParser::addUIntParameter
    inputParser::addFloatParameter
    inputParser::addDoubleParameter
    inputParser::addBoolParameter
    inputParser::addStringParameter
    inputParser::printParameterInfo
    inputParser::validateParameters

lorentzvector.cpp
    holds Lorentz 4-vectors.
Functions:
    lorentzVector::lorentzVector
    lorentzVector::~~lorentzVector
    SetXYZT

main.cpp
    the "main" file/function—where the program starts.

narrowResonanceCrossSection.cpp

```

inherits from photonNucleusCrossSection. It calculates the cross-section for narrow resonance vector mesons.

Functions:

```
narrowResonanceCrossSection::narrowResonanceCrossSection  
narrowResonanceCrossSection::~~narrowResonanceCrossSection  
narrowResonanceCrossSection::crossSectionCalculation //  
calculates the vector meson cross section assuming a  
narrow resonance, per STAR Note 386.
```

nBodyPhaseSpaceGen.cpp

is responsible for the kinematics used in the four-prong decays.

Functions:

```
nBodyPhaseSpaceGen::nBodyPhaseSpaceGen  
nBodyPhaseSpaceGen::~~nBodyPhaseSpaceGen  
nBodyPhaseSpaceGen::setDecay // sets decay constants and  
prepares internal variables  
nBodyPhaseSpaceGen::generateDecay// generates event with  
certain n-body mass and momentum and returns event weight  
general purpose function  
nBodyPhaseSpaceGen::generateDecayAccepted// generates full  
event with certain n-body mass and momentum only, when  
event is accepted (return value = true) this function is  
more efficient, if only weighted events are needed  
nBodyPhaseSpaceGen::pickMasses// randomly chooses the (n -  
2) effective masses of the respective (i + 1)-body systems  
nBodyPhaseSpaceGen::calcWeight// computes event weight (=   
integrand value) and breakup momenta uses vector of  
intermediate two-body masses prepared by pickMasses()  
nBodyPhaseSpaceGen::calcEventKinematics// calculates  
complete event from the effective masses of the (i + 1)-  
body systems, the Lorentz vector of the decaying system,  
and the decay angles uses the break-up momenta calculated  
by calcWeight()  
nBodyPhaseSpaceGen::estimateMaxWeight// calculates maximum  
weight for given n-body mass  
nBodyPhaseSpaceGen::print
```

nucleus.cpp

defines the basis properties of a nucleus such as radius, form factor, and thickness.

Functions:

```
nucleus::nucleus  
nucleus::~~nucleus  
nucleus::init  
nucleus::nuclearRadius  
nucleus::formFactor  
nucleus::dipoleFormFactor  
nucleus::thickness// calculates the nuclear thickness  
function per Eq. 4 in Klein and Nystrand, PRC 60
```

photonNucleusCrossSection.cpp

calculates the cross-section for coherent photon-Nucleus interactions.

Functions:

```
photonNucleusCrossSection::photonNucleusCrossSection
```

```

photonNucleusCrossSection::~photonNucleusCrossSection
photonNucleusCrossSection::getcsgA // returns the cross-
section for photon-nucleus interaction producing vector
mesons
photonNucleusCrossSection::photonFlux // gives the
photon flux as a function of energy Egamma for arbitrary
nuclei and gamma. The first time it is called, it
calculates a lookup table which is used on subsequent
calls. It returns dN_gamma/dE (dimensions 1/E), not dI/dE
energies are in GeV, in the lab frame
photonNucleusCrossSection::nepoint// gives the spectrum of
virtual photons, dn/dEgamma, for a point charge q=Ze
sweeping past the origin with velocity gamma, integrated
over impact parameter from bmin to infinity, per Eq. 15.54
of Jacksons Classical Electrodynamics
photonNucleusCrossSection::sigmagp// gives the gamma-
proton --> VectorMeson cross section. Wgp is the gamma-
proton CM energy. Unit for cross section: fm**2
photonNucleusCrossSection::sigma_A// Nuclear Cross Section
sig_N,sigma_A in (fm**2)
photonNucleusCrossSection::sigma_N// Nucleon Cross Section
in (fm**2)
photonNucleusCrossSection::breitWigner// uses simple
fixed-width s-wave Breit-Wigner without coherent
background for rho' (PDG '08 eq. 38.56)

```

pythiadecayer.cpp

links Pythia 8 and STARlight, and initializes Pythia 8.

Functions:

```

pythiaDecayer::pythiaDecayer
pythiaDecayer::~pythiaDecayer
pythiaDecayer::init
pythiaDecayer::addParticle
pythiaDecayer::execute

```

randomgenerator.cpp

STARlight's random number generator, using the same algorithm as ROOTs TRANDOM3 class. It is based on M. Matsumoto and T. Nishimura, Mersenne Twistor: A 623-dimensionally equidistributed uniform pseudorandom number generator. For more information see

<http://www.math.keio.ac.jp/~matumoto/emt.html>

Functions:

```

randomGenerator::SetSeed
randomGenerator::Rndom

```

readinluminosity.cpp

reads in the luminosity tables from slight.txt, which is generated in the early stages of the program.

Functions:

```

readLuminosity::readLuminosity
readLuminosity::~readLuminosity
readLuminosity::read

```

spectrum.cpp

sets up functions needed to make cross-section calculations for general photonuclear interactions modeled with DPMJET.

Functions:

- spectrum::spectrum
- spectrum::generateKsingle
- spectrum::generateKdouble
- spectrum::drawKsingle
- spectrum::drawKdouble
- spectrum::generateBreakupProbabilities
- spectrum::getFnSingle
- spectrum::getFnDouble
- spectrum::getTransformedNofe

sppectrumprotonnucleus.cpp

sets up functions needed to make cross-section calculations for general photonuclear interactions modeled with DPMJET.

Functions:

- spectrumProtonNucleus::spectrumProtonNucleus
- spectrumProtonNucleus::generateBreakupProbabilities
- spectrumProtonNucleus::getSigma

starlight.cpp

initializes and then produces and decays events.

Functions:

- starlight::starlight
- starlight::~~starlight
- starlight::init
- starlight::produceEvent
- starlight::luminosityTableIsValid
- starlight::createEventChannel

starlightdpmjet.cpp

hosts the class starlightDpmJet which inherits from the eventChannel class. It includes methods to generate diffractive events with DPMJET.

Functions:

- starlightDpmJet::starlightDpmJet
- starlightDpmJet::init
- starlightDpmJet::produceEvent
- starlightDpmJet::produceSingleEvent
- starlightDpmJet::produceDoubleEvent

starlightparticle.cpp

is a container to store particle information.

Functions:

- starlightParticle::starlightParticle
- starlightParticle::~~starlightParticle

starlightparticlecodes.cpp

converts jetset particle numbers to the corresponding GEANT code.

Functions:

- starlightParticleCodes::jetsetToGeant

starlightpythia.cpp

inherits from the eventChannel class. It includes methods to calculate diffractive events with Pythia6. *Pythia 6 functionality has been deprecated.*

Functions:

```
starlightPythia::starlightPythia
starlightPythia::~~starlightPythia
starlightPythia::init
starlightPythia::produceEvent
```

starlightStandalone.cpp

is used by Main.cpp and in turn calls methods from the starlight class.

Functions:

```
starlightStandalone::starlightStandalone
starlightStandalone::~~starlightStandalone
starlightStandalone::init
starlightStandalone::run
starlightStandalone::boostEvent
```

twophotonluminosity.cpp

inherits from beamBeamSystem, and is responsible for calculating the two photon luminosity table based on W and Y.

Functions:

```
twoPhotonLuminosity::twoPhotonLuminosity
twoPhotonLuminosity::~~twoPhotonLuminosity
twoPhotonDifferentialLuminosity
twoPhotonLuminosity::D2LDMDY
twoPhotonLuminosity::D2LDMDY_Threaded
twoPhotonLuminosity::integral
twoPhotonLuminosity::radmul
twoPhotonLuminosity::integrand
twoPhotonLuminosity::Nphoton
```

upcevent.cpp

stores the final event information.

Functions:

```
upcEvent::upcEvent
upcEvent::operator=
upcEvent::operator+
upcEvent::boost
```

vector3.cpp

is a container for 3D-vectors.

Functions:

```
vector3::vector3
vector3::~~vector3
vector3::SetVector
```

wideResonanceCrossSection.cpp

inherits from photnNucleusCrossSection. It is responsible for calculating the cross-section of vector mesons with a wide resonance (eg. Rho).

Functions:

```
wideResonanceCrossSection::wideResonanceCrossSection
wideResonanceCrossSection::~~wideResonanceCrossSection
```

```
wideResonanceCrossSection::crossSectionCalculation //
calculates the cross-section assuming a wide(Breit-Wigner)
resonance.
```

Include Files:

```
beam.h //This class includes a single beam of nucleons
```

Included in files

```
beambeamsystem.h
twophotonluminosity.h
beam.cpp
gammaaluminosity.cpp
incoherentPhotonNucleusLuminosity.cpp
spectrumprotonnucleus.cpp
twophotonluminosity.cpp
```

Functions

```
beam
~beam
rapidity
photonFlux
setBeamLorentzGamma
```

```
beambeamsystem.h //This class covers a coliding beam system
```

Included in files

```
eventchannel.h
gammaaluminosity.h
gammaaavm.h
gammagammasingle.h
incoherentPhotonNucleusLuminosity.h
photonNucleusCrossSection.h
starlightpythia.h
twophotonluminosity.h
beambeamsystem.cpp
gammaaluminosity.cpp
incoherentPhotonNucleusLuminosity.cpp
spectrum.cpp
spectrumprotonnucleus.cpp
twophotonluminosity.cpp
```

Functions

```
beamBeamSystem
~beamBeamSystem
cmsBoost
beamLorentzGamma
beam1
beam2
probabilityOfBreakup
init
generateBreakupProbabilities
probabilityOfHadronBreakup
probabilityOfPhotonBreakup
```

```
bessel.h
```

Included in files

```
beam.cpp
beambeamsystem.cpp
```


[bessel.cpp](#)
[gammaaluminosity.cpp](#)
[incoherentPhotonNucleusLuminosity.cpp](#)
[photonNucleusCrossSection.cpp](#)
[twophotonluminosity.cpp](#)

Functions

besI0
dbesk0
dbesk1
besI1

eventchannel.h

Included in files

[gammaavm.h](#)
[gammagammaleptonpair.h](#)
[gammagammasingle.h](#)
[starlight.h](#)
[starlightdpmjet.h](#)
[starlightpythia.h](#)
[eventchannel.cpp](#)
[starlight.cpp](#)

Functions

eventChannel
~eventChannel
nmbAttempts ///< returns number of attempted events
nmbAccepted ///< returns number of accepted events
produceEvent
transform ///< Lorentz-transforms given 4-vector
pseudoRapidity ///< calculates pseudorapidity for
given 3-momentum

eventfilewriter.h

Included in files

[eventfilewriter.cpp](#)
[main.cpp](#)
[starlight.cpp](#)
[starlightStandalone.cpp](#)

Functions

eventFileWriter
writeEvent /** Write an UPC event to file */
writeFullPythiaInfo /** Set if we want to write full
pythia information */

filewriter.h

Included in files

[eventfilewriter.h](#)
[eventfilewriter.cpp](#)
[filewriter.cpp](#)
[main.cpp](#)
[starlight.cpp](#)
[starlightStandalone.cpp](#)

Functions

fileWriter
~fileWriter
open //opens the file
setFileName//set the filename we're writing to

gammaaluminosity.h

Included in files

[gammaaluminosity.cpp](#)
[starlight.cpp](#)

Functions

photonNucleusLuminosity
~photonNucleusLuminosity
photonNucleusDifferentialLuminosity
vmsigmapt
nofe
pttablegen

gammaavm.h

Included in files

[gammaavm.cpp](#)
[starlight.cpp](#)

Functions

Gammaavectormeson
~Gammaavectormeson
produceEvent
pickwy
momenta
pTgamma
vmpt
twoBodyDecay
fourBodyDecay
getMass
getWidth
getTheta
getSpin
getDaughterMass
pseudoRapidity
Gammaanarrowvm
~Gammaanarrowvm
Gammaawidevm
~Gammaawidevm
Gammaaincoherentvm
~Gammaaincoherentvm

gammagammaleptonpair.h

Included in files

[gammagammaleptonpair.cpp](#)
[starlight.cpp](#)

Functions

Gammagammaleptonpair
~Gammagammaleptonpair
twoLeptonCrossSection
calculateTable
produceEvent
twoMuonCrossSection
pickw
picky
pairMomentum
pp_1
pp_2

twoBodyDecay
thetalep
tauDecay
getMass
getWidth
getSpin

gammagammasingle.h

Included in files

[gammagammasingle.cpp](#)
[starlight.cpp](#)

Functions

Gammagammasingle
~Gammagammasingle
singleCrossSection
produceEvent
pickw
picky
parentMomentum
pp
twoBodyDecay
thephi
getMass
getWidth
getSpin

incoherentPhotonNucleusLuminosity.h

Included in files

[incoherentPhotonNucleusLuminosity.cpp](#)
[starlight.cpp](#)

Functions

incoherentPhotonNucleusLuminosity
~incoherentPhotonNucleusLuminosity
incoherentPhotonNucleusDifferentialLuminosity
nofe

incoherentVMCrossSection.h

Included in files

[gammaavm.cpp](#)
[incoherentVMCrossSection.cpp](#)

Functions

incoherentVMCrossSection
~incoherentVMCrossSection
crossSectionCalculation

inputParameters.h

Included in files

[beam.h](#)
[gammaaluminosity.h](#)
[incoherentPhotonNucleusLuminosity.h](#)
[readinluminosity.h](#)
[starlightpythia.h](#)
[beam.cpp](#)
[beambeamsystem.cpp](#)
[gammaaluminosity.cpp](#)
[incoherentPhotonNucleusLuminosity.cpp](#)

[inputParameters.cpp](#)
[nucleus.cpp](#)
[readinluminosity.cpp](#)
[starlight.cpp](#)
[starlightStandalone.cpp](#)
[twophotonluminosity.cpp](#)

Functions

parameterlist
add
validationKey
parameterbase
toString
operator<<
parameter
operator=
ptr
value
name
required
setValue
setName
setRequired
inputParameters
~inputParameters
init
configureFromFile
baseFileName
beam1Z
beam1A
beam2Z
beam2A
beamLorentzGamma
beam1LorentzGamma
beam2LorentzGamma
maxW
minW
nmbWBins
maxRapidity
nmbRapidityBins
ptCutEnabled
ptCutMin
ptCutMax
etaCutEnabled
etaCutMin
etaCutMax
productionMode
nmbEvents
prodParticleId
randomSeed
beamBreakupMode
interferenceEnabled
interferenceStrength
maxPtInterference
nmbPtBinsInterference
ptBinWidthInterference
coherentProduction
incoherentFactor

```

minGammaEnergy
maxGammaEnergy
pythiaParams
pythiaFullEventRecord
xsecCalcMethod
prodParticleType
prodParticleDecayType
interactionType
protonEnergy
setBaseFileName
setBeam1Z
setBeam1A
setBeam2Z
setBeam2A
setBeamLorentzGamma
setBeam1LorentzGamma
setBeam2LorentzGamma
setMaxW
setMinW
setNmbWBins
setMaxRapidity
setNmbRapidityBins
setPtCutEnabled
setPtCutMin
setPtCutMax
setEtaCutEnabled
setEtaCutMin
setEtaCutMax
setProductionMode
setNmbEvents
setProdParticleId
setRandomSeed
setBeamBreakupMode
setInterferenceEnabled
setInterferenceStrength
setMaxPtInterference
setNmbPtBinsInterference
setPtBinWidthInterference
setCoherentProduction
setIncoherentFactor
setMinGammaEnergy
setMaxGammaEnergy
setPythiaParams
setPythiaFullEventRecord
setXsecCalcMethod
setProdParticleType
setProdParticleDecayType
setInteractionType
setProtonEnergy
setParameter
print
write
parameterValueKey
instance

```

inputParser.h

Included in files

[inputParameters.h](#)
[inputParameters.cpp](#)
[inputParser.cpp](#)

Functions

inputParser
inputParser
parseFile/** Parse a file */
parseString
addIntParameter
addUIntParameter
addFloatParameter
addDoubleParameter
addBoolParameter
addStringParameter
printParameterInfo
validateParameters
_parameter
operator==
operator<
printParameterInfo
addParameter

lorentzvector.h

Included in files

[nBodyPhaseSpaceGen.h](#)
[starlightparticle.h](#)
[lorentzvector.cpp](#)

Functions

lorentzVector
~lorentzVector
SetXYZT
SetPxPyPzE
GetPx
GetPy
GetPz
GetE
operator +=
operator -=
M2
M
BoostVector
Boost
operator <<

narrowResonanceCrossSection.h

Included in files

[narrowResonanceCrossSection.cpp](#)
[gammaavm.cpp](#)

Functions

narrowResonanceCrossSection
~narrowResonanceCrossSection
crossSectionCalculation

nBodyPhaseSpaceGen.h

Included in files

[gammaavm.h](#)

[nBodyPhaseSpaceGen.cpp](#)

Functions

Factorial
breakupMomentum
nBodyPhaseSpaceGen
~nBodyPhaseSpaceGen
setDecay
random
generateDecay
generateDecayAccepted
setMaxWeight
maxWeight
normalization
eventWeight
maxWeightObserved
resetMaxWeightObserved
estimateMaxWeight
eventAccepted
daughter
daughters
nmbOfDaughters
daughterMass
intermediateMass
breakupMom
cosTheta
phi
print
operator <<
pickMasses
calcWeight
pickAngles
calcEventKinematics
eventAccepted

nucleus.h

Included in files

[beam.h](#)
[beambeamsystem.h](#)
[twophotonluminosity.h](#)
[gammaaluminosity.h](#)
[incoherentPhotonNucleusLuminosity.cpp](#)
[nucleus.cpp](#)
[spectrumprotonnucleus.cpp](#)
[starlightdpmjet.cpp](#)
[starlightpythia.cpp](#)
[twophotonluminosity.cpp](#)

Functions

nucleus
~nucleus
init
Z
A
nuclearRadius
formFactor
dipoleFormFactor
thickness

```
Q0
rho0
woodSaxonSkinDepth
fritiofR0
rws
```

photonNucleusCrossSection.h

Included in files

```
gammaaluminosity.h
incoherentPhotonNucleusLuminosity.h
incoherentVMCrossSection.h
narrowResonanceCrossSection.h
wideResonanceCrossSection.h
gammaavm.cpp
photonNucleusCrossSection.cpp
```

Functions

```
photonNucleusCrossSection
~photonNucleusCrossSection
slopeParameter///< returns slope of t-distribution
[(GeV/c)^{-2}]
getChannelMass ///< returns mass of the produced
system [GeV/c^2]
getBNORM
luminosity///< returns luminosity [10^{26} cm^{-2}
sec^{-1}]
getbbs///< returns beamBeamSystem
vmPhotonCoupling ///< vectormeson-photon coupling
constant f_v / 4 pi (cf. Eq. 10 in KN PRC 60 (1999)
014903)
getDefaultC
maxPhotonEnergy///< returns max photon energy in lab
frame [GeV] (for vectormesons only)
crossSectionCalculation
getcsgA
photonFlux
sigmagp
sigma_A
sigma_N
breitWigner
nepoint
```

pythiadecayer.h

Included in files

```
gammagammasingle.h
pythiadecayer.cpp
```

Functions

```
pythiaDecayer
~pythiaDecayer
init// Initialize
addParticle// Add particle to current event
execute// Execute event and return starlight type
event
pythiaDecayer
operator==
```

PythiaStarlight.h

Included in files

[starlight.cpp](#)

Functions

pythiaStarlight
init
getPythia

randomgenerator.h

Included in files

[eventchannel.h](#)
[gammaavm.h](#)
[gammagammasingle.h](#)
[nBodyPhaseSpaceGen.h](#)
[inputParameters.cpp](#)
[randomgenerator.cpp](#)
[spectrum.cpp](#)

Functions

SetSeed
Rndom
randomGenerator
instance

readinluminosity.h

Included in files

[eventchannel.h](#)
[gammaavm.h](#)
[gammagammaleptonpair.h](#)
[gammagammasingle.h](#)
[readinluminosity.cpp](#)

Functions

readLuminosity
~readLuminosity
read

reportingUtils.h

Included in files

[inputParser.h](#)
[nBodyPhaseSpaceGen.h](#)
[beam.cpp](#)
[beambeamsystem.cpp](#)
[inputParameters.cpp](#)
[main.cpp](#)
[nucleus.cpp](#)
[photonNucleusCrossSection.cpp](#)
[pythiadecayer.cpp](#)
[starlight.cpp](#)
[starlightStandalone.cpp](#)

Functions

getClassMethod__
printErr
printWarn
printInfo
svnVersion
printSvnVersion
compileDir
printCompilerInfo

```

operator <<
progressIndicator
trueFalse
yesNo
onOff
enDisabled

```

spectrum.h

Included in files

```

spectrumprotonnucleus.h
starlightdpmjet.h
spectrum.cpp
starlightdpmjet.cpp

```

Functions

```

spectrum // Spectrum must be constructed with beam-
beam system, default constructor disallowed
generateKsingle // Generate a table of photon energy
probabilities. Use NK+1 logarithmic steps between
Et_min and Eg_max
generateKdouble // Generate a 2-D table of photon
energy probabilities. Use NK+1 x NK+1 logarithmic
steps between Et_min and Eg_max
drawKsingle // Get the energy of a single gamma
@return energy of the gamma
drawKdouble // Get the energy of a single gamma
@param egamma1 variable passed by reference to get
the energy of the first gamma @param egamma2 variable
passed by reference to get the energy of the second
gamma @return energy of the gamma
setBeamBeamSystem // Set the beam beam system
setMinGammaEnergy //Set the minimum gamma energy
setMaxGammaEnergy / Set the maximum gamma energy
setBmin //Set minimum impact parameter
setBMax //Set maximum impact parameter
generateBreakupProbabilities //Generate the hadron
breakup probability table
getSigma ---1.05?
getTransformedNofe
getFnSingle
getFnDouble

```

spectrumprotonnucleus.h

Included in files

```

spectrumprotonnucleus.cpp
starlightdpmjet.cpp
starlightpythia.cpp

```

Functions

```

spectrumProtonNucleus
getNucleonNucleonSigma --- 7.35?
generateBreakupProbabilities
getSigma

```

starlight.h

Included in files

```

main.cpp
starlight.cpp

```

[starlightStandalone.cpp](#)

Functions

starlight
~starlight
init
produceEvent
configFileName
nmbAttempts
nmbAccepted
luminosityTableIsValid
createEventChannel

starlightconstants.h

Included in files

[eventchannel.h](#)
[gammaavm.h](#)
[gammagammaingle.h](#)
[gammagammaleptonpair.h](#)
[inputParameters.h](#)
[nBodyPhaseSpaceGen.h](#)
[photonNucleusCrossSection.h](#)
[upcevent.h](#)
[beam.cpp](#)
[beambeamsystem.cpp](#)
[gammaaluminosity.cpp](#)
[gammagammaleptonpair.cpp](#)
[gammagammaingle.cpp](#)
[incoherentPhotonNucleusLuminosity.cpp](#)
[incoherentVMCrossSection.cpp](#)
[inputParameters.cpp](#)
[narrowResonanceCrossSection.cpp](#)
[nucleus.cpp](#)
[photonNucleusCrossSection.cpp](#)
[readinluminosity.cpp](#)
[twophotonluminosity.cpp](#)
[wideResonanceCrossSection.cpp](#)

Functions

N/A

starlightdpmjet.h

Included in files

[starlight.cpp](#)
[starlightdpmjet.cpp](#)

Functions

starlightDpmJet
init
produceEvent
produceSingleEvent
produceDoubleEvent
setSingleMode
setDoubleMode
setMinGammaEnergy
setMaxGammaEnergy
setProtonMode

starlightlimits.h

Included in files

[gammagammaleptonpair.h](#)
[readinluminosity.h](#)
[twophotonluminosity.h](#)

Functions

N/A

starlightparticle.h

Included in files

[pyhthiadcayer.h](#)
[upcevent.h](#)
[starlightparticle.cpp](#)

Functions

starlightParticle
~starlightParticle
setPdgCode
getPdgCode
setCharge
getCharge
setFirstParent
getFirstParent
setLastParent
getLastParent
setFirstDaughter
getFirstDaughter
setLastDaughter
getLastDaughter
getStatus
setStatus
setVertex
getVertex

starlightparticlecodes.h

Included in files

[eventfilewriter.cpp](#)
[starlightparticlescodes.cpp](#)

Functions

jetsetToGeant//Converts a jetset code into a GEANT
codes

starlightpythia.h

Included in files

[starlight.cpp](#)
[starlightpythia.cpp](#)

Functions

starlightPythia
~starlightPythia
init
produceSingleEvent
produceDoubleEvent
produceEvent
setSingleMode
setDoubleMode
setMinGammaEnergy
setMaxGammaEnergy
setFullEventRecord

starlightStandalone.h

Included in files

[main.cpp](#)

[starlightStandalone.cpp](#)

Functions

starlightStandalone
~starlightStandalone
init
run
configFileName
eventDataFileName
setConfigFileName
setEventDataFileName
boostEvent

twophotonluminosity.h

Included in files

[starlight.cpp](#)

[twophotonluminosity.cpp](#)

Functions

twoPhotonLuminosity
~twoPhotonLuminosity
twoPhotonDifferentialLuminosity
D2LDMDY
D2LDMDY_Threaded
integral
radmul
integrand
Nphoton

upcevent.h

Included in files

[eventchannel.h](#)

[filewriter.h](#)

[gammaavm.h](#)

[pythiadecayer.h](#)

[starlight.h](#)

[starlightpythia.h](#)

[starlight.cpp](#)

[upcevent.cpp](#)

Functions

upcEvent
~upcEvent
addParticle
addVertex
addGamma
getParticles
getVertices
getGammaEnergies
operator=
operator+
boost

vector3.h

Included in files

[lorentzvector.h](#)
[vector3.cpp](#)

Functions

vector3
~vector3
GetVector
SetVector
operator +=
operator =
operator -=
X
Y
Z
Mag2
Mag
operator <<

wideResonanceCrossSection.h

Included in files

[gammaavm.cpp](#)
[wideResonanceCrossSection.cpp](#)

Functions

wideResonanceCrossSection
~wideResonanceCrossSection
crossSectionCalculation