

FamilyOS — PostgreSQL Schema v0.1

****Status:**** Draft

****Database:**** PostgreSQL 17

****Backend:**** Supabase

****Author:**** FamilyOS Team

****Based on:****

- Vision & Product Definition v0.1
- Knowledge Model v0.1
- Event Model v0.1
- Data Dictionary v0.3
- Knowledge Graph Schema v0.1

Objetivo

Este documento define o schema físico inicial do banco PostgreSQL utilizado pelo FamilyOS.

O modelo segue uma arquitetura relacional normalizada, preservando a representação do Knowledge Graph através de chaves estrangeiras e tabelas de relacionamento.

Nesta fase o documento descreve a estrutura lógica das tabelas.

A implementação SQL será gerada automaticamente na versão 0.2.

Convenções

Chaves primárias

Todos os registros utilizam:

UUID

```text

id UUID PRIMARY KEY

```

Auditoria

Todas as tabelas possuem:

```text

created\_at TIMESTAMP

updated\_at TIMESTAMP

deleted\_at TIMESTAMP NULL

```

Status

Sempre que possível utilizar ENUM.

Exemplo:

```text

ACTIVE

INACTIVE

PENDING

EXPIRED

ARCHIVED

```

1. families

Representa uma família cadastrada no FamilyOS.

Campos

Campo	Tipo	Observação
-------	------	------------

id	UUID	PK
----	------	----

name	VARCHAR(200)	Nome da família
------	--------------	-----------------

description	TEXT	Opcional
-------------	------	----------

created_at	TIMESTAMP	
------------	-----------	--

updated_at	TIMESTAMP	
------------	-----------	--

deleted_at	TIMESTAMP	
------------	-----------	--

2. people

Representa uma pessoa.

Campos

Campo	Tipo
id	UUID
family_id	UUID FK -> families.id
first_name	VARCHAR(100)
last_name	VARCHAR(100)
birth_date	DATE
cpf	VARCHAR(20)
nationality	VARCHAR(50)
email	VARCHAR(200)
phone	VARCHAR(50)
created_at	TIMESTAMP
updated_at	TIMESTAMP
deleted_at	TIMESTAMP

3. documents

Representa qualquer documento.

Campos

Campo	Tipo
id	UUID
person_id	UUID FK
document_type	VARCHAR(50)
number	VARCHAR(100)
issue_date	DATE
expiration_date	DATE
issuing_authority	VARCHAR(200)
country	VARCHAR(100)
storage_path	TEXT
status	VARCHAR(30)
created_at	TIMESTAMP
updated_at	TIMESTAMP

4. properties

Representa um imóvel.

Campos

Campo	Tipo
id	UUID
family_id	UUID
title	VARCHAR(200)
address	TEXT
city	VARCHAR(100)
state	VARCHAR(50)
country	VARCHAR(50)
property_type	VARCHAR(50)
registry_number	VARCHAR(100)
created_at	TIMESTAMP
updated_at	TIMESTAMP

5. property_owners

Relacionamento N:N

Pessoa ↔ Imóvel

Campos

Campo	Tipo
property_id	UUID
person_id	UUID
ownership_percentage	NUMERIC(5,2)

6. expenses

Campos

Campo	Tipo
id	UUID
family_id	UUID
supplier_id	UUID
description	TEXT
category	VARCHAR(50)
amount	NUMERIC(14,2)
due_date	DATE
status	VARCHAR(30)

| recurrence_rule | TEXT |

7. payments

Campos

| Campo | Tipo |

|-----|-----|

| id | UUID |

| expense_id | UUID |

| account_id | UUID |

| payment_date | DATE |

| amount | NUMERIC(14,2) |

| receipt_document_id | UUID |

| status | VARCHAR(30) |

8. suppliers

Campos

| Campo | Tipo |

|-----|-----|

| id | UUID |

| name | VARCHAR(200) |

| document | VARCHAR(50) |

| email | VARCHAR(200) |

| phone | VARCHAR(50) |

9. accounts

Campos

| Campo | Tipo |

|-----|-----|

| id | UUID |

| owner_person_id | UUID |

| bank | VARCHAR(100) |

| account_type | VARCHAR(50) |

| currency | VARCHAR(10) |

10. trips

Campos

Campo	Tipo
id	UUID
family_id	UUID
destination	VARCHAR(200)
departure_date	DATE
return_date	DATE
status	VARCHAR(30)

11. trip_participants

Relacionamento N:N

Viagem ↔ Pessoas

12. travel_readiness

Resultado da avaliação da viagem.

Campos

Campo	Tipo
id	UUID
trip_id	UUID
person_id	UUID
passport_ok	BOOLEAN
visa_ok	BOOLEAN
esta_ok	BOOLEAN
vaccine_ok	BOOLEAN
insurance_ok	BOOLEAN
readiness_score	INTEGER
status	VARCHAR(30)

13. alerts

Campos

Campo	Tipo
id	UUID
related_entity_type	VARCHAR(50)
related_entity_id	UUID
severity	VARCHAR(20)
title	VARCHAR(200)
description	TEXT
due_date	DATE
status	VARCHAR(30)

14. tasks

Campos

Campo	Tipo
id	UUID
assigned_person_id	UUID
alert_id	UUID
title	VARCHAR(200)
due_date	DATE
status	VARCHAR(30)

15. events

Implementação física do Event Model.

Campos

Campo	Tipo
id	UUID
event_type	VARCHAR(80)
source	VARCHAR(50)
affected_entity_type	VARCHAR(50)
affected_entity_id	UUID
related_person_id	UUID
previous_state	JSONB
new_state	JSONB
priority	VARCHAR(20)
evidence_document_id	UUID
automation_status	VARCHAR(30)
occurred_at	TIMESTAMP

Índices

Criar índices para:

- person_id
- family_id
- property_id
- document_type
- expiration_date
- due_date
- status
- event_type

Próxima Versão

A versão v0.2 deste documento irá gerar automaticamente:

- PostgreSQL SQL Script
- Supabase Migration
- TypeScript Types
- OpenAPI Models
- Prisma Schema (opcional)