

နည်းပညာတက္ကသိုလ်(မန္တလေး)
လျှပ်စစ်စွမ်းအားအင်ဂျင်နီယာဌာန
ပရောဂျက်အကျဉ်းချုပ်

၁။	ပရောဂျက်အမည်	(မြန်မာဘာသာဖြင့်)	ပရိုဂရမ်မေဘယ်လ် လောဂျစ် ကွန်ထရိုလာ (PLC) ကို အသုံးပြုထားသော အလိုအလျောက် လက်ဆေးစက်
		(အင်္ဂလိပ်ဘာသာဖြင့်)	Automatic Hand-Washing Machine Using PLC
၂။	ပရောဂျက်ရည်ရွယ်ချက်	1. To design and construct a PLC-based automatic hand-washing machine for touchless and hygienic hand washing. 2. To automatically control soapy-water dispensing, clean-water supply, hand drying and hand-gel dispensing by using photoelectric sensors and PLC ladder logic. 3. To provide reliable operation by using timer functions, mutual interlocking and an automatic battery backup system.	
၃။	ပရောဂျက်ပါဝင်ပစ္စည်း	1. Programmable Logic Controller (PLC Unit), 2. 24 V DC Switching Power Supply, 3. Photoelectric Sensors. 4. Electromagnetic Relays, 5. Pilot Lights, 6. Terminal Blocks, 7. AC and DC Circuit Breakers, 8. 24 V to 12 V DC Converters 9. Backup Battery. 10. 12 V DC Pump Motors, 11. Water Tank, 12. Soapy-Water Container,	

		13. Hand-Gel Container 14. 220 V AC Hand Dryer and 15. PLC Ladder Logic Programming Software GX Works2.
၄။	ပရောဂျက်အကျဉ်းချုပ်	This project focuses on the design and implementation of a PLC-based automatic hand washing machine. Photoelectric sensors are used to detect the user's hands without physical contact, and the PLC controls the corresponding washing operations. The system automatically performs soapy-water dispensing, clean-water supply, hand drying and hand-gel dispensing. Timer functions are used to control the dispensing periods, while mutual interlocking prevents more than one operating stage from operating at the same time. An automatic power-supply changeover system is also included to provide battery backup for selected DC circuits when the normal AC mains supply fails.
၅။	ပရောဂျက်အကျိုးကျေးဇူး	Provides touchless hand-washing operation and reduces physical contact with commonly shared surfaces. Controls the use of water, soapy water and hand gel automatically, reducing unnecessary liquid consumption. Improves system reliability by using PLC control, timer functions and mutual interlocking. Provides battery backup for selected DC

		circuits during an AC mains-power failure. Promotes the application of PLC and industrial automation technology in hygiene systems.
၆။	ဘာသာရပ်နယ်ပယ်	PLC Control and Industrial Automation Field
၇။	ပရောဂျက်အရွယ်အစား	၂.၄ ပေ x ၁.၅ ပေ x ၄.၅ ပေ
၈။	ပါဝါ (Power Supply)	The system normally operates from a 220–230 V AC mains supply with a 24 V DC control power supply. A battery backup system is also provided for selected DC circuits.
၉။	ပရောဂျက်တွင်ပါဝင်ဆောင်ရွက်မည့်သူများ၏ အမည်/ရာထူး/ဌာန/ဖုန်းနံပါတ်/အီးလ်မေးလိပ်စာ	ဒေါ်ကြူကြူညွန့်(တွဲဖက်ပါမောက္ခ) လျှပ်စစ်စွမ်းအားအင်ဂျင်နီယာဌာန ၀၉.၉၇၄၅၁၅၂၅၀ kyukyunyunt9@gmail.com နည်းပညာတက္ကသိုလ်(မန္တလေး) မောင်ကျော်ဇင်(အဖွဲ့ဝင်) လျှပ်စစ်စွမ်းအားအင်ဂျင်နီယာဌာန ၀၉.၉၆၂၀၀၀၀၃၂ 252kywzn@gmail.com နည်းပညာတက္ကသိုလ်(မန္တလေး) မမြင့်မြတ်မိုး(အဖွဲ့ဝင်) လျှပ်စစ်စွမ်းအားအင်ဂျင်နီယာဌာန ၀၉.၆၇၀၀၀၁၀၄ mntmtmoe@gmail.com နည်းပညာတက္ကသိုလ်(မန္တလေး)

၁၀။ မှတ်တမ်းဓာတ်ပုံများ

