tblBooking
bookingId (int, PK)
userId (int, FK)
userName (string)
classId (int, FK)
className (string)
statusId (int, FK)
statusName (string)
upId (int, FK)
totalHour (datetime)
bookedAt (datetime)
cancelAt (datetime)
dateCreated (datetime)
dateUpdated (datetime)
ssCheckedIn (boolean)

tblPackage
packageId (int, PK)
packageName (string)
countryId (int, FK)
countryName (string)
credits (int)
packagePrice (decimal)
packageDescription (string)
expiryDays (int)
dateCreated (datetime)
dateUpdated (datetime)

tblClass
classId (int, PK)
className (string)
countryId (int, FK)
countryName (string)
creditToBuy (int)
startTime (datetime)
endTime (datetime)
classDuration (int)
maxSlots (int)
dateCreated (datetime)
dateUpdated (datetime)

tblStatus
statusId (int, PK)
statusName (string)
dateCreated (datetime)
dateUpdated (datetime)

tblCountry
countryId (int, PK)
countryName (string)
dateCreated (datetime)
dateUpdated (datetime)

tblTransactionHistory
thId (int, PK)
upId (int, FK)
classId (int, FK)
className (string)
usedCredits (int)
refundCredits (int)
transactionType (string)
transactionDate (datetime)
dateCreated (datetime)
dateUpdated (datetime)

tblWaitlist
wailistId (int, PK)
bookingId (int, FK)
classId (int, FK)
statusId (int, FK)
statusName (string)
addAt (datetime)
dateCreated (datetime)
dateUpdated (datetime)

tblUser
userId (int, PK)
userName (string)
userEmail (string)
userPassword (string)
verifyPassword (string)
countryId (int, FK)
countryName (string)
isVarify (boolean)
dateCreated (datetime)
dateUpdated (datetime)

tblUserPackage
upId (int, PK)
userId (int, FK)
userName (string)
packageId (int, FK)
packagename (string)
creditRemain (int)
isExpire (boolean)
purchaseDate (datetime)
expiryDate (datetime)
dateCreated (datetime)
dateUpdated (datetime)