Frontend with React JS (7062) – IMP. FOR SEM-END

Q.1 How do you pass data from a parent component to a child component in JSX?	
A. By using the props attribute in the child component	B By using the state attribute in the child component
C. By using the render() method in the parent component	D. By using the create Component() method in the parent component
Correct Answer: A	
Reference: Heading 2.5 Page no. 35	

Q.2 What is the role of Babel in JSX?	
A Babel is used to compile JSXcode into JavaScript code that can be executed by the browser.	B. Babel is used to optimize the performance of React components that use JSX
C. Babel is used to convert JSX code into HTML code for better browser compatibility.	D. Babel is not related to JSX in any way.
Correct Answer: A	
Reference: Table 1.1 page no. 10	

Q.3 What is the difference between props and state in ReactJS?	
A. Props are immutable and passed from parent components, while state is mutable and managed within a component.	B. Props are mutable and managed within a component, while state is immutable and passed from parent
C. Props and state are the same thing in ReactJS.	D. None of these
Correct Answers : A	
Reference : Table 1.3 Page No.13	

Q.4 What is the purpose of the "key" attribute in ReactJS?	
A. To specify the type of element being rendered.	B. To specify the type of element being rendered.
C. To control the behavior of a component.	D. None of these
Correct Answers : Both A & C	

Q.5 How do you create a new component React functional in a project?	
A. By defining a function that returns JSX	B. By extending the React.Component class.
C.By using the createComponent function from the React library.	D. By defining a function that returns a string.
Correct Answers : A	
Reference : Heading 2.3 Page No.32	

Q.6 How should parameters be passed to a route in React Router?	
A. By using the query string in the URL.	B. By defining a custom prop for the component being rendered.
C. By using the useParams hook.	D. By passing them as a second argument to the Route component.
Correct Answers : C	
Reference : Book Page No. 103	

Q.7 Which one of the following is an example of a synthetic event in ReactJS?	
A. onClick	B. onChange
C. onBlur	D. All of these
Correct Answers : D	
Reference : HEADING 4.4 PAGE NO 66	

Q.8 What is the purpose of event.stopPropagation() method in ReactJS?	
A. To stop the event from bubbling up the DOM tree.	B. To stop the event from propagating to child elements.
C. To stop the default browser behavior.	D. To stop the event from firing multiple times.
Correct Answers : A	

Frontend with React JS (7062) – IMP. FOR SEM-END

Q.9 Which React hook is used for managing component styles?	
A useState	C. useEffect
C. useMemo	D. useRef
Correct Answers : A	
Reference : Code Snippet 9, Page No.71	

Q.10 What is ReactJS?	
A. A programming language	B A front-end Web development library
C. A server-side scripting languagex	D. A serA database management system
Correct Answers : B	
Reference : HEADING 1.1 PAGE NO.5	

Q.11 What is a React component?	
A. A reusable piece of code that represents part of a user interface	B. A function that returns a string
C. A database table	D. A file containing CSS styles
Correct Answers : A	
Reference : Heading 1.1 PAGE NO.9	

Q.12 Which one of the following statements about React functional components is true?	
A. They are deprecated in favor of class components.	B. They cannot have state or lifecycle methods.
C. They cannot receive props from a parent component.	D. They are defined using a function that returns JSX
Correct Answers : D	
Reference : Heading 2.3 Page No. 32	

Q.13 Which one of the following statements is true about JSX in React?	
A. JSXis a new language that replaces HTML in React.	B JSXis used to write templates for React components.
B. JSXis used to define the structure of a React component's state.	D. JSXis used to define the structure of a React component's props.
Correct Answers : B	
Reference : Heading 3.3 Page No. 51	

Q.14. Can inline styles be used with JSX?	
A.Yes, by passing a style object to the style attribute in JSX	B.No, inline styles are not supported in JSX
C.Yes, by using the class Name attribute in JSX	D.Yes, by using the style attribute with CSS class es in JSX
Correct Answer: A	
Reference: heading 6.1.1 page no.117	

Q.15 What is the purpose of curly braces ({}) In JSX?	
A. To indicate the beginning and end of JSX Syntax	C. To define the component's props
C. To write JavaScript expressions inside JSX	D. To escape special characters in JSX
Correct Answer: C	
Reference: Heading 3.3 Page No. 51	

Q.16 What is the purpose of the "onChange" attribute in an HTML input element?	
A. It specifies the default value of the input field.	B.It specifies the name of the input field.
C. It specifies the type of the input field.	D. It specifies the function to be called when the input value changes.
Correct Answer: D	

Q.17 What is Yup?	
A. A popular JavaScript library for building user interfces	B. A tool for checking the syntax of JavaScript code
C. A validation library for JavaScript	D. None of these
Correct Answer: C	

Q.18 Which one of the following is a Yup validation method for checking if a string matches a regular expression?	
A. required()	B. email()
C. matches()	D. None of these
Correct Answer: C	

Q.19 Which CSS-in-JS library is commonly used for styling React components?	
A. jQuery	B. Bootstrap
C. Styled Components	D. Material UI
Correct Answer: C	
Reference: PAGE NO. 10	

Q.20 Which one of the following is a benefit of using inline styles in React?	
A. Greater modularity and reusability of CSS code	B. Faster page loading times
C. Improved browser compatibility	D. Greater ease of debugging
Correct Answer: D	
Reference: HEADING 6.1.1 PAGE NO. 117	

Q.21 Which CSS property can be used to create a gradient background in a React component?	
A. background-color	B. background-image
C. background-position	D. background-size
Correct Answer: B	

Q.22 Which one of the following is a popular CSS framework for styling React components?	
A. Tailwind CSS	B. Material UI
C. Semantic UI	D. All of these
Correct Answer: D	

Q.23 How do you pass query parameters in a Fetch API request?	
A. By appending them to the URL as a string	B. By including them in the request body
C. By adding them to the "headers" parameter.	D. By using the "URLSearchParams" object.
Correct Answer: A	

Q.24 Which one of the following is the correct way to initialize a Formik form?	
A. <Formik initialValues={initialValues} onSubmit={handleSubmit}>	B. <Formik values={initialValues} handleSubmit={handleSubmit}>
C. <Formik initialValues={initialValues} handleSubmit={handleSubmit}>	D. None of these
Correct Answer: A	

Q.25 Which lifecycle method is commonly used to handle form submission in ReactJS?	
A. componentWillMount	B. componentWillUnmount
C. componentDidMount	D. onSubmit
Correct Answer: D	
Reference: PAGE NO. 75	

Q.26 What is the purpose of the "value" attribute in an HTML input element?	
A. It specifies the default value of the input field.	B. It specifies the name of the input field.
C. It specifies the type of the input field.	D. It specifies the placeholder text of the input field.
Correct Answer: A	
Reference: PAGE NO 73	

Q.27 Which CSS selector is used to target the first child element of a parent element in React?	
A. :first-child	B. :nth-child(1)
D. :last-child	D. :only-child
Correct Answer: A	

Q.28 Which CSS property is used to adjust the opacity of a React component?	
A. Opacity	B. Visibility
C. Display	D. Filter
Correct Answer: A	

Q.29 Which of the following is a CSS property that can be used to adjust the size of a React component?	
A. Height	B. Width
C. Font-size	D. Line-height
Correct Answer: A, B	

Q.30 Which of the following CSS selectors is used to target all elements with a specific class name in React?	
A. #	B. .
C. *	D. &
Correct Answer: B	
Reference: HEADING 6.2.3 PAGE 125	

Q.31 What is the purpose of the <Switch> component in React Router?	
A. To define routes	B. To render the first matching route
C. To render all matching routes	D. To handle server-side rendering
Correct Answer: B	

Q.32 What is the purpose of the useParams hook in React Router?	
A. To access the current URL path parameters	B. To navigate to a new route
C. To render the first matching route	D. To handle server-side rendering
Correct Answer: A	
Reference: PAGE NO. 103	

Q.33 What is the purpose of the CSS modules in React?	
A. To create reusable components	B. To manage state in React components
C. To import CSS styles into a React component	D. To provide animation effects in React components
Correct Answer: C	
Reference: HEADING 6.2.3 PAGE NO. 125	

Q.34 What is the main purpose of Formik?	
A. To manage component state.	B. To manage server-side state.
C. To handle form data in React.	D. None of these
Correct Answer: C	
Reference: PAGE NO. 195	

Q.35 How does Formik handle form validation?	
A. It does not support form validation.	B. It provides a set of built-in validation functions.
C. It helps define one's own validation functions.	D. None of these
Correct Answer: C	
Reference: HEADING 8.3.2 PAGE NO. 172	

Q.36 Which one of the following is a Yup validation method for checking if a value is a valid date?	
A. date()	B. required()
C. email()	D. None of these
Correct Answer: A	

Q.37 Which one of the following is a Yup validation method for checking if a value is a valid integer?	
A. integer()	B. positive()
C. min()	D. None of these
Correct Answer: A	

Q.38 Which of the following are valid ways to conditionally render content in a React component?	
A. {condition && Content to be rendered }	B. {condition ? Content to be rendered : null}
C. {condition || Content to be rendered }	D. {condition && Content to be rendered } || Default content
Correct Answer: A, B	

Q.39 Which of the following methods can be used to handle mouse events in a React component?	
A. onMouseEnter	B. onMouseLeave
C. onMouseDown	D. onMouseUp
Correct Answer: A, B, C, D	

Q.40 What is the purpose of the React useEffect hook?	
A. To handle side effects in a React component.	B. To optimize the performance of a React component.
C. To replace the componentDidMount, componentDidUpdate, and componentWillUnmount lifecycle methods.	D. To manage global state in a React application.
Correct Answer: A	
Reference: HEADING 7.2 PAGE NO. 136	