

SSVE White Balance Data Visualization

20 Dec 2021, SSVE started a trial which is an activity to write White Balance data into Pmod T-Con board.

To ensure effectiveness, PE wanna check log data compared with JND.

This small VBA project helps to accelerate the whole process.

Author

SSVE TVQA member @Zhang Liang, 20211220


Changelog

- v0.01, initial build
- v0.02, fix visualization bug (screw non-standard charts..)
- v0.03, resize `named range` dynamically
- v0.04, create `Python3` + `Rlang` solution for scaling data and workload;

Diagram

the following the diagram of the whole process

SSVE White Balance Visualization @ZL, 20211221



Solution 01

toolkits: VB.NET + Excel + VBA;

using this approach when workload and dataset are small ($\leq 1,000$);

Implementation

some core functionality as follows.

```
Private Sub read_PBM_csv(ByVal csv_path As String, ByRef dstWB As Workbook)
    ''' read data from a PBM csv log files at SSVE @ZL, 20211220
    Const col_x As Integer = 5
    Const col_y As Integer = 6
    Const idx_x As Integer = 0
    Const idx_y As Integer = 1
    Const sheet_no As Integer = 1
    Dim cool, neutral, warm, expert1, color_temps

    cool = Array(47, 58, 69, 80)
```

```

neutral = Array(107, 118, 129, 140)
warm = Array(167, 178, 189, 200)
expert1 = Array(227, 238, 249, 260)

color_temps = Array(cool, neutral, warm, expert1)

Dim src_wb As Workbook
Dim src_ws As Worksheet

Set src_wb = GetObject(csv_path)
Set src_ws = src_wb.Worksheets(sheet_no)

Dim i As Integer
Const wsn_cool As String = "Cool"
Const wsn_neutral As String = "Neutral"
Const wsn_warm As String = "Warm"
Const wsn_expert1 As String = "Expert1"
Dim dstWS_cool As Worksheet: Set dstWS_cool = dstWB.Sheets(wsn_cool)
Dim dstWS_neutral As Worksheet: Set dstWS_neutral = dstWB.Sheets(wsn_neutral)
Dim dstWS_warm As Worksheet: Set dstWS_warm = dstWB.Sheets(wsn_warm)
Dim dstWS_expert1 As Worksheet: Set dstWS_expert1 = dstWB.Sheets(wsn_expert1)

Const lb As Integer = 0
Const ub As Integer = 3
Dim dstRow As Integer
Const dstCol_dt As Integer = 2
Const dstCol_ser As Integer = 3
Const dstCol_u As Integer = 7
Const dstCol_v As Integer = 8

For i = lb To ub
    dstRow = GetLastRow(dstWS_cool, dstCol_u) + 1
    dstWS_cool.Cells(dstRow, dstCol_ser).Value = dstWS_cool.Cells(dstRow,
dstCol_ser).Value & parse_pbm_fp(csv_path)
    dstWS_cool.Cells(dstRow, dstCol_u).Resize(1, 2) =
ConvXY_to_uv(src_ws.Cells(cool(i), col_x), src_ws.Cells(cool(i), col_y))
' cool

    dstWS_neutral.Cells(dstRow, dstCol_ser).Value =
dstWS_neutral.Cells(dstRow, dstCol_ser).Value & parse_pbm_fp(csv_path)
    dstWS_neutral.Cells(dstRow, dstCol_u).Resize(1, 2) =
ConvXY_to_uv(src_ws.Cells(neutral(i), col_x), src_ws.Cells(neutral(i), col_y))
' neutral

    dstWS_warm.Cells(dstRow, dstCol_ser).Value = dstWS_warm.Cells(dstRow,
dstCol_ser).Value & parse_pbm_fp(csv_path)
    dstWS_warm.Cells(dstRow, dstCol_u).Resize(1, 2) =
ConvXY_to_uv(src_ws.Cells(warm(i), col_x), src_ws.Cells(warm(i), col_y))
' warm

    dstWS_expert1.Cells(dstRow, dstCol_ser).Value =
dstWS_expert1.Cells(dstRow, dstCol_ser).Value & parse_pbm_fp(csv_path)
    dstWS_expert1.Cells(dstRow, dstCol_u).Resize(1, 2) =
ConvXY_to_uv(src_ws.Cells(expert1(i), col_x), src_ws.Cells(expert1(i), col_y))
'

```

```

expert1
    Next i

    src_wb.Close False
    Set src_wb = Nothing
End Sub

```

Visualization

using some tricks to make dynamic charts.



Dynamic Chart

```


''' Dynamic Chart
' [ trick ]
' step1: using Formula -> Define Name to customize target series + offset()
function
' step2: using Click Chart -> select data series -> target series

' ref: https://support.microsoft.com/en-us/office/offset-function-c8de19ae-dd79-4b9b-a14e-b4d906d11b66
' syntax: OFFSET(reference, rows, cols, [height], [width])

```



Gallery



Solution 02

toolkits: **Python3** + **Pandas** + **Rlang** + **ggplot2**;

using this approach when workload and dataset are enormous ($>=1,000$);

Implementation

```
class PBM_Wrangler:
    fn_prefix:str      = 'PBM_'
    fn_ext:str         = 'CSV'
    head_x:str         = 'x(calc)'
    head_y:str         = 'y(calc)'
    head_xy:List[str]  = [head_x, head_y]
    head_picmode:str   = 'picmode'
    head_level:str     = 'LEVEL'
    head_u:str         = 'u'
    head_v:str         = 'v'
```

```

head_uv:List[str]      = [head_u, head_v]
dummy_rows:List[int]   = [i for i in range(33)] + [92, 93] + [152, 153] + [212,
213] + [272, 273] # may change overtime..
levels:int             = 57
temps:List[str]        = ['COOL'] * levels + ['NEUTRAL'] * levels + ['WARM'] *
levels + ['EXPERT1'] * levels + ['PHOTO'] * levels
ires:List[int]         = [12, 23, 34, 45]
color_temps:List[str] = ['COOL', 'NEUTRAL', 'WARM', 'EXPERT1']

df_temp:DataFrame      = None
df_cools:List[DataFrame] = []
df_neutrals:List[DataFrame] = []
df_warms:List[DataFrame] = []
df_expert1s:List[DataFrame] = []
df_cts:List[List[DataFrame]] = [df_cools, df_neutrals, df_warms, df_expert1s]
# note: match with color_temps

def __init__(self, src_folder:Path) -> None:
    """initialize an instance with a given folder with source PBM_*.CSV log
files inside

    Args:
        src_folder (Path): a given folder with source PBM_*.CSV log files
inside
    """
    self._src_folder = src_folder

def _filter(self)->Path:
    for path in sorted(pathlib.Path(self._src_folder).rglob(f'*.
{self.fn_ext}')):
        if path.name.startswith(self.fn_prefix):
            yield path.absolute()

@staticmethod
def xy2uv(x:float, y:float)->Tuple:
    u = (4 * x) / (12 * y - 2 * x + 3)
    v = (9 * y) / (12 * y - 2 * x + 3)
    return u, v

def xy2u(self, x:float, y:float, offset:float=.0)->float:
    return (4 * x) / (12 * y - 2 * x + 3) + offset

def xy2v(self, x:float, y:float, offset:float=.0)->float:
    return (9 * y) / (12 * y - 2 * x + 3) + offset

def __read(self, pbm_file:Path)->None:
    df:DataFrame = pd.read_csv(pbm_file, skiprows=self.dummy_rows,
engine='python')
    df[self.head_picmode] = self.temps
    self.df_temp = df[np.isin(df[self.head_level], self.ires)]

def __categorize(self, color_temp:str, dst_df:List[DataFrame])->None:
    df:DataFrame = self.df_temp[self.df_temp[self.head_picmode] ==
color_temp].loc[:, [self.head_x, self.head_y]]

```

```

        df[self.head_u] = df.apply(lambda df: self.xy2u(df[self.head_x],
df[self.head_y]), axis=1)
        df[self.head_v] = df.apply(lambda df: self.xy2v(df[self.head_x],
df[self.head_y]), axis=1)
        fixed_df = df.loc[:, self.head_uv]
        dst_df.append(fixed_df)

    def __reset(self, how:str=None)->None:
        self.df_temp = None
        if how == 'all':
            for df in self.df_cts:
                df.clear()

    def __wrangle(self)->None:
        for color_temp, df_ct in zip(self.color_temps, self.df_cts):
            if df_ct: self.__categorize(color_temp, df_ct)
        self.__reset()

    def __concat(self, color_temp:str, src_df:List[DataFrame])->None:
        df:DataFrame = pd.concat(src_df, ignore_index=True, sort=False)
        df.to_csv(f'./src/{color_temp}.csv', index=False)

    def __tocsv(self)->None:
        for color_temp, df_ct in zip(self.color_temps, self.df_cts):
            if df_ct: self.__concat(color_temp, df_ct)

    @timer
    def work(self)->None:
        logging.info('start working..')
        for pbm_file in self._filter():
            self.__read(pbm_file)
            self.__wrangle()
        self.__tocsv()
        self.__reset(how='all')
        logging.info('succeeded.')

```

Visualization

```

### plot
plot.wb <- function(df.temp, temp,
                    temp.breaks.x, temp.breaks.y,
                    temp.minor.x, temp.minor.y,
                    temp.jnd1, temp.jnd2, temp.jnd3) {

    p <- ggplot(df.temp) +
        geom_point(aes(x=u,
                        y=v),
                    colour = "purple",
                    shape = 21,

```

```


        fill = 'white',
        stroke = .5,
        alpha = 0.9,
        size = 2) +
# coord_cartesian(xlim=c(0.1771, 0.1991),
#                 ylim=c(0.4247, 0.4467)) +
scale_x_continuous(breaks = temp.breaks.x,
                   minor_breaks = temp.minor.x) +
scale_y_continuous(breaks = temp.breaks.y,
                   minor_breaks = temp.minor.y) +
labs(title=gsub(' ', '', paste('WB::', temp)),
     x="u\\'",
     y="v\\'") +
theme(plot.title = element_text(size=8),
      #panel.grid.major.x = element_blank(),
      #panel.grid.major.y = element_blank(),
      panel.grid.minor.x = element_blank(),
      panel.grid.minor.y = element_blank(),
      axis.title.x = element_text(size=8),
      axis.title.y = element_text(angle=0, size=8, vjust=0.5),
      axis.text.x = element_text(angle=90, size=5),
      axis.text.y = element_text(size=5)) +
geom_path(data=temp.jnd1,
          aes(x=du,
              y=dv),
          size = 0.2,
          color = 'blue'
          ) +
geom_path(data=temp.jnd2,
          aes(x=du,
              y=dv),
          size = 0.2,
          color = 'blue'
          ) +
geom_path(data=temp.jnd3,
          aes(x=du,
              y=dv),
          size = 0.2,
          color = 'red'
          )
# dev.print(file = gsub(' ', '', paste('Rplot_', temp, '.png')),
#           device = png,
#           width = 800,
#           height = 800)
return(p)
}

```

Gallery

【SSVE Pmod/SET】 White Balance Confirmation

規格: $u'v'$, 0.010 (3JND)



Disclaimer: Non of these plots are insightful @ZL

About

MIT License

Copyright (c) 2021 ZL

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.