
Software Requirements Specification

for
RouteRunner

Version 1.0 approved

Prepared by:

Gay Ming Kai, U2320596C
Low Kan Yui (Liu Gengrui), U2322359G
Khoo An Xian, U2322918F
Tan Hsuen Yin Andria, U2320699F
Aung Aung Pyae Phyo, U2320039C

Nanyang Technology University

30 October 2024

Table of Contents

Introduction	3
Purpose	3
Product Scope	3
References	3
Overall Description	5
Product Perspective	5
Product Functions	5
User Classes and Characteristics	5
Operating Environment	6
External Interface Requirements	7
Software Interfaces	7
System Features	9
Login	9
Manage Runners (for Operator)	9
Manage Jobs (for Operator)	10
View Active Runners (for Operator)	11
View Route (for Runner)	11
View Carpark Availability (for Runner)	12
View Job (for Runner)	12
Job Allocation	12
Non-Functional Requirements	14
Performance Requirements	14
Security Requirements	14
Software Quality Attributes	14
Appendix A: Data Dictionary	16
Appendix B: Use Case Diagram and Descriptions	17
Login (for All)	18
For Operators	19
For Runners	27
Appendix C: User Interfaces	29
Appendix D: Dialog Map	34
Appendix E: Sequence Diagrams	35

Introduction

○ Purpose

This SRS document details the requirements for the "RouteRunner" application, designed to help small and medium-sized enterprises (SMEs) efficiently track their runners on-the-ground and assign jobs. This document outlines the functional and non-functional requirements of the system, specifying how operators and runners will manage job assignments and location tracking. This SRS covers version 1.0 of the application, encompassing the core features required for effective job management, route optimization, and real-time location tracking of runners.

○ Product Scope

RouteRunner is a web application designed to streamline the job allocation process for SMEs by enabling operators to assign jobs to runners effectively. The system optimizes job allocation based on priority levels and route proximity, reducing idle time and improving efficiency. It provides real-time location tracking of runners, ensuring operators have up-to-date information on job statuses and runner locations. The primary objective of RouteRunner is to enhance the coordination of task management, reduce operational inefficiencies, and support businesses in managing their field operations more effectively. The application aligns with business strategies focused on improving productivity and customer satisfaction.

○ References

Our team referenced the following documentation.

Google Maps API Documentation

- **Author:** Google LLC
- **Version Number:** Latest stable version
- **Source/Location:** <https://developers.google.com/maps/documentation>
- **Description:** This documentation provides detailed information on integrating Google Maps services, including geolocation, route optimization, map visualization, and traffic updates, which are essential for RouteRunner's route planning and real-time navigation features.

GovTech Carpark Availability API Documentation

- **Author:** Government Technology Agency of Singapore (GovTech)
- **Version Number:** Latest version as available on Data.gov.sg
- **Source/Location:** <https://data.gov.sg/collections/85/view>

- **Description:** This documentation outlines the use of the Carpark Availability API, which provides real-time data on carpark availability across various locations in Singapore. It is integrated into RouteRunner to assist runners in finding available parking near their job locations.

OneMap API Documentation

- **Author:** Singapore Land Authority (SLA)
- **Version Number:** 3.0
- **Source/Location:** <https://www.onemap.gov.sg/apidocs/apidocs>
- **Description:** The OneMap API is Singapore's government geospatial data API, providing access to various map-based services, including geolocation, reverse geocoding, route calculation, and property searches. This API is primarily used to access detailed Singapore map data, which can be incorporated into web or mobile applications to enhance spatial awareness and services tailored to specific locations within Singapore.

Firebase Authentication API Documentation

- **Author:** Google LLC
- **Version Number:** Latest stable version
- **Source/Location:** <https://firebase.google.com/docs/auth>
- **Description:** This documentation provides comprehensive details on implementing Firebase Authentication for secure user login and identity management. It is used in our application to streamline the login process and ensure user data security.


HDB Carpark Info

- **Author:** HDB (Housing and Development Board)
- **Version Number:** 1st October (Updated start of every month)
- **Source/Location:** https://data.gov.sg/datasets/d_23f946fa557947f93a8043bbef41dd09/view
- **Description:** Information about HDB car parks such as operating hours, car park location (in SVY21), type of parking system, etc.

Overall Description

- **Product Perspective**


RouteRunner is a self-contained product belonging to the on-demand service family.



3-Layered Architecture Diagram


○ Product Functions

○ Boundary Class Diagram



Software Requirements Specification for RouteRunner

Entity Class Diagram



For All	For Operators	For Runners	System
<ul style="list-style-type: none"> ● Login ● View Job 	<ul style="list-style-type: none"> ● Manage Runners ● Manage Jobs ● View Active Runners 	<ul style="list-style-type: none"> ● View Route ● View Carpark Availability 	<ul style="list-style-type: none"> ● Job Allocation

○ User Classes and Characteristics

RouteRunner has 2 main user classes: Operator and Runner.

Operator:

- **Frequency of Use:** High; operators are expected to use the application throughout the day to manage job assignments and monitor runner activity.
- **Functions Used:** Operators will have access to functionalities related to job creation, allocation, route management, and runner tracking. They can also view and modify job statuses, manage runner accounts, and set priorities for tasks.
- **Privilege Levels:** High; operators have access to sensitive data, including runner information, job details, and real-time location tracking. Role-based access control ensures that only authorized personnel can modify job allocations and view certain data.

Runner:

- **Frequency of Use:** Moderate; runners interact with the system primarily to receive job assignments, update job statuses, and view their planned routes.
- **Functions Used:** Runners can log in to view their daily job list, check the priority and details of each task, update job completion statuses, and access route maps. They will also receive notifications about new assignments and changes to their routes.
- **Privilege Levels:** Low; runners have limited access to the system, primarily restricted to viewing and updating their own job-related information. They cannot modify job allocations or access the data of other runners.

○ Operating Environment

The application is built on the FMERN stack (Firebase, MongoDB, Express.js, React, Node.js), which provides a full-stack JavaScript environment.

External Interface Requirements

○ Software Interfaces

RouteRunner integrates with several external software components to enhance its functionality and provide real-time, accurate information for users. The key software interfaces are described below:

Google Maps API

- **Name and Version:** Google Maps Platform (latest stable version)
- **Purpose:** The API uses the Google Maps API for route optimization, geolocation services, and map visualization. This interface helps operators and runners view the most efficient routes for job assignments and display maps for navigating between job locations
- **Data In/Out:**
 - **Input:** Job locations (addresses), runner current locations, and destination addresses.
 - **Output:** Optimized routes, real-time map visualizations.
- **Nature of Communication:** RouteRunner sends location data and receives routing information through RESTful API calls. It uses secure HTTPS connections to ensure data privacy and integrity.

GovTech Carpark Availability API

- **Name and Version:** GovTech Carpark Availability API (latest version as available on <https://data.gov.sg/>)
- **Purpose:** This API provides real-time carpark availability data to assist runners in finding parking spots near job locations, reducing the time spent searching for parking. This feature is especially useful in busy urban areas where parking can be a challenge.
- **Data In/Out:**
 - **Input:** Location coordinates
 - **Output:** Address, capacity and real-time availability of parking spots at nearest carpark
- **Nature of Communication:** RouteRunner makes HTTPS requests to the GovTech Carpark Availability API endpoint, retrieving real-time data. The application processes this information to display available carparks near job destinations on the runner's route map.

Firebase Authentication API

- **Name and Version:** Firebase Authentication

- **Purpose:** The API is used to facilitate secure login for users in our application. It supports email verification.
- **Data In/Out:**
 - **Input:** User credentials (email and password) for login and registration.
 - **Output:** User ID tokens, session management information, and error responses if authentication fails.
- **Nature of Communication:** The application sends HTTPS requests to Firebase Authentication endpoints.

Database Management System

- **Name and Version:** MongoDB (version 7.0.14, hosted at AWS Singapore)
- **Purpose:** The database stores all essential data, including user credentials, job details, runner information, and historical job logs. It also manages real-time updates on job statuses and route information for operators and runners.
- **Data In/Out:**
 - **Input:** User account information, job creation data, runner location updates, and status changes.
 - **Output:** Job lists for runners, route updates, job history records, and operator dashboard information.
- **Nature of Communication:** The application communicates with the database via NoSQL queries for MongoDB. Data transactions are secured with encryption protocols to ensure data integrity and security.

System Features

Login

A. Description and Priority

The Login feature allows the System to authenticate the actor (either an Operator or Runner) and bring them to their respective homepages. It is of high priority.

B. Stimulus/Response Sequences

Users must visit the RouteRunner web application.

C. Functional Requirements

1. User shall be able to log in by inputting his email and password.
 - 1.1. System must verify the email and password inputted.
 - 1.2. If the email is invalid, System must display an error message and allow User to input it again.
 - 1.3. If the password is invalid, System must display an error message and allow User to input it again.

Manage Runners (*for Operator*)

A. Description and Priority

The Manage Runners feature allows the Operator to view all Runners and their activity status, location and assigned jobs. It also allows the Operator to create or delete Runners. It is of high priority.

B. Stimulus/Response Sequences

The Operator should log in, click on the burger menu at the top right corner, then click the Manage Runners button to stimulate this feature.

C. Functional Requirements

1. Operator shall be able to manage Runners
 - 1.1. Operator shall be able to view the list of all Runners and their respective activity status
 - 1.2. Operator shall be able to search for a Runner by username
 - 1.3. Operator shall be able to **view individual Runner's details**
 - 1.3.1. Operator shall be able to view his last and next destination
 - 1.3.2. Operator shall be able to delete the Runner
 - 1.3.3. Operator shall be able to reset password for the Runner
 - 1.3.3.1. System must ensure that the password conforms to character restrictions*

- 1.3.3.1.1. If the password is not valid, System must prompt Operator until a valid password is inputted
- 1.4. Operator shall be able to **create a new Runner**
 - 1.4.1. Operator shall be able register a new Runner by inserting his username, password and email
 - 1.4.2. System must ensure that the username is unique (ie. does not currently exist in User database)
 - 1.4.2.1. If the username is not unique, System must prompt Operator until a unique username is inputted
 - 1.4.3. System must ensure that the password conforms to character restrictions*
 - 1.4.3.1. If the password is not valid, System must prompt Operator until a valid password is inputted
 - 1.4.4. System must ensure that the email is unique (i.e. does not exist in user User database)
 - 1.4.4.1. If the email is not unique, System must prompt Operator until a unique email is inputted
 - 1.4.5. System must ensure the email address is valid
 - 1.4.5.1. If the email is not valid, System must prompt Operator until a valid email is inputted
 - 1.4.6. System must trigger a verification email upon registration that will be sent to the Runner's email

*Password character restrictions: at least 8 characters long, contain at least a number, upper and lower case letters, and a special character

Manage Jobs (*for Operator*)

A. Description and Priority

The Manage Jobs feature allows the Operator to perform Create, Read, Update and Delete (CRUD) operations on the Job database. It is of high priority.

B. Stimulus/Response Sequences

The Operator should log in, click on the burger menu at the top right corner, then click the Manage Jobs button to stimulate this feature.

C. Functional Requirements

1. Operator shall be able to manage jobs
 - 1.1. Operator shall be able to view a list of all ongoing and pending jobs
 - 1.2. Operator shall be able to search for a job by Job ID
 - 1.3. Operator shall be able to delete a job
 - 1.4. Operator shall be able to **view individual job's details**
 - 1.4.1. System shall display the job ID, Runner assigned and job status
 - 1.5. Operator shall be able to **view a history log** of completed jobs

- 1.5.1. System shall display the job ID, address, Runner assigned, job status, and date of each job
- 1.5.2. System shall be able to filter by job ID, address, runner username, and the completed date.
- 1.5.3. System shall be able to search for a specific archived job using the job ID
- 1.6. Operator shall be able to **create a new job**
 - 1.6.1. Operator shall be able to input the postal code of the job location
 - 1.6.1.1. Operator shall be able to verify if the postal code is mappable
 - 1.6.1.1.1. If the postal code is unmappable, System must prompt Operator until a mappable postal code is inputted
 - 1.6.1.1.2. If postal code is valid, System autofills the remaining location details (street name and block number)
 - 1.6.2. Operator shall be able to input the additional notes for the job
 - 1.6.3. Operator shall be able to input the priority level for the job
 - 1.6.4. System must add this new job into the Job database with its status marked as ‘pending’

View Active Runners (*for Operator*)

A. Description and Priority

The View Active Runners feature allows the Operator to view all active Runners and their location, both in a list and on a map. It is of medium priority.

B. Stimulus/Response Sequences

The Operator should log in to stimulate this feature (on the Home Page)

C. Functional Requirements

- 1. Operator shall be able to track active Runners
 - 1.1. Operator shall be able to view all active Runners and their locations
 - 1.2. Operator shall be able to view individual Runner’s details

View Route (*for Runner*)

A. Description and Priority

The View Route feature allows the Runner to view his route on a map and indicate completion of jobs to generate a new route. It is of high priority.

B. Stimulus/Response Sequences

The Runner should log in to stimulate this feature (on the Home Page)

C. Functional Requirements

1. Runner shall be able to view the route from his previous job to his next job on a map
2. Runner shall be able to indicate completion of a job
 - 2.1. System shall update the status of the job from ‘ongoing’ to ‘completed’ on the Job database
 - 2.2. System shall allocate a new job to the Runner
 - 2.3. System shall update the route on the map

View Carpark Availability (*for Runner*)

A. Description and Priority

The View Carpark Availability feature allows the Runner to check for vacancies in carparks nearest to the Runner’s next job destination. It is of low priority.

B. Stimulus/Response Sequences

The Runner should log in, then click ‘View Carpark’ on the Homepage to stimulate this feature

C. Functional Requirements

1. Runner shall be able to view the carpark number, address, free capacity and last updated timing for the car park nearest to his job location.

View Job (*for Runner*)

A. Description and Priority

The View Job feature allows the Runner to view details for the current job he is assigned. It is of high priority.

B. Stimulus/Response Sequences

The Runner should log in, then click the burger menu and ‘View Job’ to stimulate this feature.

C. Functional Requirements

1. Runner shall be able to view the job ID, address, notes and priority level for each job

Job Allocation

A. Description and Priority

The Job Allocation feature allocates newly created jobs to the most suitable Runner. Jobs are of high or low priority.

B. Stimulus/Response Sequences

The Operator should create a new job to stimulate this feature.

C. Functional Requirements

1. System must allocate a ‘pending’ job based on its priority level
 - 1.1. If job is high priority, System must allocate the job to the next available Runner
 - 1.2. If job is low priority, System must allocate the job to the Runner whose next destination is closest to the job
 - 1.3. System must update the status of the job from ‘pending’ to ‘ongoing’ in the Job database once it is allocated
 - 1.4. System must update the assigned Runner’s route and locations once the job is allocated

Non-Functional Requirements

○ Performance Requirements

- System must allocate jobs to Runners within 3 seconds of the operator submitting the job.
- Location tracking updates must have a latency of no more than 2 seconds.

○ Security Requirements

- Users must have an account in order to use the application.
- Operators and Runners must log into the system with a password consisting of at least 8 characters, and at least a number, a lowercase letter, an uppercase letter and a special character.
- Sensitive data, such as the user's account password , must be encrypted in transit and at rest.

○ Software Quality Attributes

- Scalability
 - System must support up to 500 concurrent users without significant performance degradation to response time and service availability
 - The real-time locating system shall be able to scale from managing up to IoT devices without loss of data fidelity or monitoring capabilities.
- Reliability
 - System must ensure 99.9% uptime, ensuring availability during peak business hours.
 - After a failed operation (e.g. job allocation or notification delivery), System must retry operation within 2 seconds for up to 3 times, before reporting an error.
 - After a system reboot, the full system functionality must be restored within 5 minutes.
- Usability
 - User interface must have a clean and consistent design, with easy-to-understand icons and clear labels.
 - System must be displayed in the local language according to the user's locale.
 - System must display date, time, and address formats according to the user's locale settings.
- Compliance
 - System must comply with relevant data protection regulations, such as the general data protection regulation (GDPR).
 - System must log all user actions related to job allocation and location tracking for audit purposes.
- Maintainability
 - The codebase shall adhere to best practices for clean code, including modular design, well-documented functions, and consistent naming conventions.
 - System must be designed with ease of maintenance in mind, allowing for quick updates and bug fixes within 1 hour of downtime.


Software Requirements Specification for RouteRunner

- Automated testing shall cover at least 80% of the codebase to ensure reliability during updates.
- Portability & Compatibility
 - System must be compatible with both iOS and Android devices.
 - System shall be able to operate and maintain a consistent user experience across various mobile devices, including different screen sizes and resolutions.
- Interoperability
 - System shall be able to integrate seamlessly with external APIs, such as mapping services (e.g. Google Maps) for route optimization.

Appendix A: Data Dictionary

Term	Definition
Operator	Human user of the system that is responsible for entering location and managing Runners.
Runner	Person that moves between assigned locations to complete tasks (eg. repair worker). Runner follows routes created by the system based on the allocated location. A Runner is either active or non-active.
Active Runner	A Runner that is logged into the system, and can be assigned a job.
Job	A task assigned to a Runner, consisting of a delivery or action at a specific location, and can be marked as high or low priority.
Completion status	Indicates whether the job is “waiting”, “ongoing” or “completed”.

Appendix B: Use Case Diagram and Descriptions



Login (for All)

Use Case ID:	SYS.ALL.1		
Use Case Name:	Login		
Created By:	Alvin & Kan Yui	Last Updated By:	An Xian
Date Created:	8/9/24	Date Last Updated:	28/10/24

Actor:	Runner / Operator
Description:	This use case allows System to authenticate the actor and bring them to their respective homepages.
Preconditions:	1. The users have their accounts with username and password.
Postconditions:	1. Actor has been authenticated. 2. Actors gain access to the respective System's functions.
Priority:	High
Frequency of Use:	High
Flow of Events:	<ol style="list-style-type: none"> User keys in username and password System validates username and password against User database System returns a successful login if username and password are valid System routes the actor to their respective homepage
Alternative Flows:	<p>SYS.ALL.1.AC.1: If the actor's username does not exist in the database,</p> <ol style="list-style-type: none"> System displays an error message and allows the actor to key in again. <p>SYS.ALL.1.AC.2: If the actor's username exists but the password is wrong,</p> <ol style="list-style-type: none"> System displays an error message and allows the actor to key in again.
Exceptions:	<p>SYS.ALL.1.EX.1: Database storing the actor credentials is not available.</p> <ol style="list-style-type: none"> System displays message: "System is down temporarily. Please contact service desk at +65 XXXXXXXX"
Includes:	NIL
Special Requirements:	<ol style="list-style-type: none"> Sensitive data such as users' passwords must be encrypted in transit and at rest.
Assumptions:	<ol style="list-style-type: none"> Operators' accounts must be created by developers of RouteRunner Runners' account must be created by Operators (see CreateRunner use case for Operators) If Operators forget their password, they must contact developers of RouteRunner to reset their password If Runners forget their password, they must contact their Operators to reset their password (see ViewRunner use case for Operators)
Notes and Issues:	NIL

For Operators

Use Case ID:	SYS.OP.1		
Use Case Name:	ManageJobs		
Created By:	Alvin & Kan Yui	Last Updated By:	An Xian
Date Created:	10/9/24	Date Last Updated:	28/10/24

Actor:	Operator
Description:	This use case allows the Operator to perform Create, Read, Update and Delete (CRUD) operations on the jobs database.
Preconditions:	1. Operator must be authenticated.
Postconditions:	1. Jobs database is accessed by the Operator.
Priority:	High
Frequency of Use:	High
Flow of Events:	<ol style="list-style-type: none"> 1. Operator clicks on the burger menu on the Home page 2. Operator selects Manage Jobs 3. System displays a list of all pending and ongoing jobs, a search bar, and options to Create Job and View History Log 4. If Operator enters a Job ID in search bar, System displays the selected job 5. If Operator clicks a specific job, System routes Operator to View Job interface (see included ViewJob use case) 6. If Operator clicks 'Create Job', System routes Operator to Create Job interface (see included CreateJob use case) 7. If Operator clicks 'History Log', System routes Operator to History Log interface (see included HistoryLog use case) <p>*pending job = yet to be assigned, ongoing job = assigned and in progress</p>
Alternative Flows:	SYS.OP.1.AC.1: If Operator enters invalid Job ID in search bar, <ol style="list-style-type: none"> 1. System displays blank list of jobs
Exceptions:	SYS.OP.1.EX.1. Database storing the jobs is not available <ol style="list-style-type: none"> 1. System displays message: "System is down temporarily. Please contact service desk at +65 XXXXXXXX"
Includes:	<ol style="list-style-type: none"> 1. CreateJob 2. ViewJob 3. HistoryLogs
Special Requirements:	1. System must ensure 99.9% uptime, ensuring availability during peak business hours.
Assumptions:	<ol style="list-style-type: none"> 1. Alterations to the database are transactional only.
Notes and Issues:	NIL

Use Case ID:	SYS.OP.1.1		
Use Case Name:	CreateJob		
Created By:	Alvin & Kan Yui	Last Updated By:	An Xian
Date Created:	8/9/24	Date Last Updated:	28/10/24

Actor:	Operator
Description:	This use case allows the operator to create new jobs which will later be allocated by the System.
Preconditions:	<ol style="list-style-type: none"> 1. The Operator must be authenticated. 2. The database must be accessible to add jobs.
Postconditions:	<ol style="list-style-type: none"> 1. A new job is created in the Job database. 2. A new job is allocated to a suitable Runner.
Priority:	High
Frequency of Use:	High
Flow of Events:	<ol style="list-style-type: none"> 1. Operator clicks on Create Job on the Manage Job interface 2. Operator enters the postal code of the job location 3. System verifies if postal code is mappable 4. System autfills the remaining job location details (street name, block number) if postal code is mappable 5. Operator adds additional notes and indicates priority level of the job 6. Operator clicks Create Job 7. System adds this new job into the Job database with its status marked as ‘pending’ 8. System allocates the job to the most suitable Runner 9. System updates the status of the job from ‘pending’ to ‘ongoing’ when the job is allocated
Alternative Flows:	<p>SYS.OP.1.1.AC.1: If postal code is unmappable,</p> <ol style="list-style-type: none"> 1. System displays error message and allows Operator to input again
Exceptions:	<p>SYS.OP.1.1.EX.1. Database storing the jobs is not available</p> <ol style="list-style-type: none"> 2. System displays message: “System is down temporarily. Please contact service desk at +65 XXXXXXXX”
Includes:	NIL
Special Requirements:	<ol style="list-style-type: none"> 1. System must ensure 99.9% uptime, ensuring availability during peak business hours. 2. System must log all user actions related to job allocation and location tracking for audit purposes.
Assumptions:	NIL
Notes and Issues:	When new jobs are added, an ID should be assigned for easy reference.

Use Case ID:	SYS.OP.1.2		
Use Case Name:	HistoryLogs		
Created By:	Alvin & Kan Yui	Last Updated By:	An Xian
Date Created:	8/9/24	Date Last Updated:	28/10/24

Actor:	Operator
Description:	This use case allows the operator to view history logs of all completed jobs.
Preconditions:	<ul style="list-style-type: none"> 1. The Operator must be authenticated. 2. The Jobs database must be accessible and updated
Postconditions:	1. System displays history logs
Priority:	Low
Frequency of Use:	Mid
Flow of Events:	<ul style="list-style-type: none"> 1. Operator clicks on History Logs on the Manage Job interface 2. System displays list of all completed jobs and their details (including job ID, address, Runner assigned, job status, and date)
Alternative Flows:	NIL
Exceptions:	<p>SYS.OP.1.2.EX.1. Database storing the jobs is not available</p> <p>3. System displays message: "System is down temporarily. Please contact service desk at +65 XXXXXXXX"</p>
Includes:	NIL
Special Requirements:	NIL
Assumptions:	NIL
Notes and Issues:	This history logs is for audit purposes

Use Case ID:	SYS.ALL.2		
Use Case Name:	ViewJob		
Created By:	Alvin & Kan Yui	Last Updated By:	An Xian
Date Created:	8/9/24	Date Last Updated:	28/10/24

Actor:	Operator / Runner
Description:	This use case allows the Operator or Runner to browse details of specific jobs.
Preconditions:	1. The Operator/Runner must be authenticated
Postconditions:	1. System displays details of selected job 2. For Operators, System displays an option to Delete Job
Priority:	High
Frequency of Use:	High
Flow of Events:	<p>If Operator</p> <ol style="list-style-type: none"> 1. Operator clicks on a specific Job on the Manage Job interface 2. System displays the details of the job and an option to Delete Job. 3. If Operator clicks ‘Delete Job’, System deletes the job from the Job database <p>If Runner</p> <ol style="list-style-type: none"> 1. Runner clicks on the burger menu in his home page 2. Runner clicks on View Job 3. System displays the details of the job
Alternative Flows:	NIL
Exceptions:	<p>SYS.ALL.2.EX.1. If Operator tries to Delete Job for that is ongoing,</p> <ol style="list-style-type: none"> 1. The Delete Job button is disabled and Operator is unable to click it <p>SYS.ALL.2.EX.2. Database storing the jobs is not available</p> <ol style="list-style-type: none"> 4. System displays message: “System is down temporarily. Please contact service desk at +65 XXXXXXXX”
Includes:	NIL
Special Requirements:	<ol style="list-style-type: none"> 1. System must enforce role-based access control (RBAC) to limit access to sensitive functionalities based on user roles. The Delete Job option should only be accessible for Operators 2. System must support up to 500 concurrent users without significant performance degradation to response time and service availability 1. System must ensure 99.9% uptime, ensuring availability during peak business hours. 2. System must be compatible with both iOS and Android devices.
Assumptions:	NIL
Notes and Issues:	

Use Case ID:	SYS.OP.2		
Use Case Name:	ManageRunners		
Created By:	Alvin & Kan Yui	Last Updated By:	An Xian
Date Created:	8/9/24	Date Last Updated:	28/10/24

Actor:	Operator
Description:	This use case allows the Operator to perform Create, Read, Update and Delete (CRUD) operations on the Runners database.
Preconditions:	1. Operator must be authenticated
Postconditions:	1. Runners database is accessed by the Operator.
Priority:	Medium
Frequency of Use:	Low
Flow of Events:	<p>If Operator wants to view list of all Runners,</p> <ol style="list-style-type: none"> 1. Operator clicks on the burger menu on the Home page 2. Operator selects Manage Runners 3. System displays a list of all Runners and their activity status, a search bar, and an option to ‘Create New Runner’ 4. If Operator enters a name in search bar, System displays the respective Runner and his activity status 5. If Operator clicks on a Runner, System routes Operator to View Runner interface (see included ViewRunner use case) 6. If Operator clicks ‘Create New Runner’, System routes Operator to Create Runner interface (see included CreateRunner use case)
Alternative Flows:	<p>SYS.OP.2.AC.1: If Operator enters invalid Job ID in search bar,</p> <ol style="list-style-type: none"> 2. System displays blank list of Runners
Exceptions:	<p>SYS.OP.2.EX.1. Database storing the Runners’ information is not available.</p> <ol style="list-style-type: none"> 1. System displays message: “System is down temporarily. Please contact service desk at +65 XXXXXXXX”
Includes:	<ol style="list-style-type: none"> 1. CreateRunner 2. ViewRunner
Special Requirements:	<ol style="list-style-type: none"> 1. System must ensure 99.9% uptime, ensuring availability during peak business hours. 2. System must be compatible with both iOS and Android devices.
Assumptions:	NIL
Notes and Issues:	NIL

Use Case ID:	SYS.OP.2.1		
Use Case Name:	CreateRunner		
Created By:	Alvin & Kan Yui	Last Updated By:	An Xian
Date Created:	10/9/24	Date Last Updated:	28/10/24

Actor:	Operator
Description:	This use case allows the Operator to create new Runner profiles to be inserted into the Runner database.
Preconditions:	1. Operator must be authenticated.
Postconditions:	1. A new Runner record is created in the Runner database.
Priority:	Medium
Frequency of Use:	Low
Flow of Events:	<ol style="list-style-type: none"> 1. Operator clicks Create New Runner on Manage Runners Interface 2. Operator fills in the username, password and email for the Runner 3. Operator clicks Register 4. System validates the inputs 5. System creates a new Runner account in the User database
Alternative Flows:	<p>SYS.OP.2.1.AC.1: If password does not conform to character restrictions,</p> <ol style="list-style-type: none"> 1. System displays error message and allows Operator to input new password <p>SYS.OP.2.1.AC.2: If email is invalid,</p> <ol style="list-style-type: none"> 1. System displays error message and allows Operator to input email again <p>SYS.OP.2.1.AC.3: If username already exists,</p> <ol style="list-style-type: none"> 1. System displays error message and allows Operator to input username again <p>SYS.OP.2.1.AC.4: If email already exists,</p> <ol style="list-style-type: none"> 1. System displays error message and allows Operator to input email again
Exceptions:	<p>SYS.OP.2.1.EX.1: An input field is left blank.</p> <ol style="list-style-type: none"> 1. System does not allow Operator to click Register
Includes:	NIL
Special Requirements:	<p>New account passwords should be fulfill the following character restrictions:</p> <ul style="list-style-type: none"> • at least 8 characters long, • a mixture of upper and lower case letters, • a special case character • a number
Assumptions:	NIL
Notes and Issues:	NIL

Use Case ID:	SYS.OP.2.2		
Use Case Name:	ViewRunner		
Created By:	Alvin & Kan Yui	Last Updated By:	An Xian
Date Created:	10/9/24	Date Last Updated:	28/10/24

Actor:	Operator
Description:	This use case allows the Operator to view details of a specific Runner, as well as delete the Runner or reset his password.
Preconditions:	<ul style="list-style-type: none"> 1. The Operator must be authenticated 2. The Runner account exists in the database
Postconditions:	<ul style="list-style-type: none"> 1. System displays details of selected Runner (including his last and next destination)
Priority:	Mid
Frequency of Use:	Low
Flow of Events:	<ul style="list-style-type: none"> 1. Operator clicks on a specific Runner 2. System displays the details of the Runner and an option to Delete Runner or Reset Password for the Runner 3. If Operator clicks ‘Delete Runner’, System deletes the Runner from the User database. 4. If Operator clicks ‘Reset Password’, Operator can input a new password for the runner and System resets the Runner’s password in the User database.
Alternative Flows:	NIL
Exceptions:	NIL
Includes:	NIL
Special Requirements:	<ul style="list-style-type: none"> 1. System must ensure 99.9% uptime, ensuring availability during peak business hours. 2. System must be compatible with both iOS and Android devices.
Assumptions:	NIL
Notes and Issues:	

Use Case ID:	SYS.OP.3		
Use Case Name:	ViewActiveRunners		
Created By:	Alvin & Kan Yui	Last Updated By:	An Xian
Date Created:	10/9/24	Date Last Updated:	28/10/24

Actor:	Operator
Description:	This use case allows the Operator and Runner to view locations for active Runners.
Preconditions:	<ol style="list-style-type: none"> 1. The Operator must be authenticated 2. There are active Runners (Runners who are logged into their accounts)
Postconditions:	<ol style="list-style-type: none"> 1. System displays a list of the active Runners' names and their locations 2. System displays the location of active Runners on a map
Priority:	Mid
Frequency of Use:	High
Flow of Events:	<ol style="list-style-type: none"> 1. Operator logs into his account 2. System displays a list of the active Runners' names and their locations, and visualizes all their locations on a map 3. If Operator clicks on a Runner in the list, System routes Operator to View Runner interface (see included ViewRunner use case)
Alternative Flows:	NIL
Exceptions:	<p>SYS.OP.2.2.EX.1.. Database storing the Runners is not available</p> <ol style="list-style-type: none"> 1. System displays message: "System is down temporarily. Please contact service desk at +65 XXXXXXXX"
Includes:	NIL
Special Requirements:	<ol style="list-style-type: none"> 1. System shall be able to integrate seamlessly with Google Maps API for location visualization. 2. System must ensure 99.9% uptime, ensuring availability during peak business hours. 3. System must be compatible with both iOS and Android devices.
Assumptions:	NIL
Notes and Issues:	NIL

For Runners

Use Case ID:	SYS.RN.1		
Use Case Name:	ViewRoute		
Created By:	Alvin & Kan Yui	Last Updated By:	An Xian
Date Created:	10/9/24	Date Last Updated:	28/10/24

Actor:	Runner
Description:	This use case allows the Runner to view the route to the next job and indicate completion when the job is done.
Preconditions:	<ol style="list-style-type: none"> 1. The Runner must be authenticated. 2. The Runner must be active. 3. The Runner must have a job allocated.
Postconditions:	<ol style="list-style-type: none"> 1. System displays the route to the Runner's next job location (the route originates from his last job location)
Priority:	High
Frequency of Use:	High
Flow of Events:	<ol style="list-style-type: none"> 1. Runner logs into his account 2. System displays the route to his next allocated job on a map in the Home page 3. Runner clicks Complete Job when he has completed the job 4. System changes the job status from 'ongoing' to 'completed' in the Job database 5. System allocates next Job to Runner 6. System displays the updated route to his next allocated job on the map
Alternative Flows:	NIL
Exceptions:	<p>SYS.RN.1.EX.1.. No job is available for allocation</p> <ol style="list-style-type: none"> 1. System does not update the route displayed on the map after Runner clicks Complete Job
Includes:	NIL
Special Requirements:	<ol style="list-style-type: none"> 1. System shall be able to integrate seamlessly with Google Maps API for route visualization. 2. System must support up to 500 concurrent users without significant performance degradation to response time and service availability 3. System must ensure 99.9% uptime, ensuring availability during peak business hours. 4. System must be compatible with both iOS and Android devices.
Assumptions:	NIL
Notes and Issues:	NIL


Use Case ID:	SYS.RN.2		
Use Case Name:	ViewCarparkAvailability		
Created By:	Alvin & Kan Yui	Last Updated By:	An Xian

Date Created:	10/9/24	Date Last Updated:	28/10/24
----------------------	---------	---------------------------	----------


Actor:	Runner
Description:	This use case allows the Runner to view the capacity of the carpark nearest to their next job location.
Preconditions:	<ul style="list-style-type: none"> 1. The Runner must be authenticated. 2. The Runner must be active. 3. The Runner must have a job allocated.
Postconditions:	1. System displays the relevant information of the carpark nearest to the Runner's next job location
Priority:	Medium
Frequency of Use:	Medium
Flow of Events:	<ul style="list-style-type: none"> 1. Runner clicks View Carpark on the Runner Main Interface page 2. System displays the carpark number, address, free capacity, and last updated timing of the carpark nearest to the Runner's destination
Alternative Flows:	NIL
Exceptions:	<p>SYS.RN.2.EX.2 Carpark cannot be found due to issues with API connection</p> <ul style="list-style-type: none"> 1. System displays message: "System is temporarily down. Please try again in 5 minutes"
Includes:	NIL
Special Requirements:	<ul style="list-style-type: none"> 1. System must support up to 500 concurrent users without significant performance degradation to response time and service availability 2. System must ensure 99.9% uptime, ensuring availability during peak business hours. 3. System must be compatible with both iOS and Android devices.
Assumptions:	NIL
Notes and Issues:	NIL

Appendix C: User Interfaces

Login




Runner Main Menu Scenario 1




Runner Main Menu Scenario 2



Runner Main Menu Misc




Operator Main Menu




ManageJobs




CreateJobs




ManageRunners




HistoryLogs




Appendix D: Dialog Map




Appendix E: Sequence Diagrams




Software Requirements Specification for RouteRunner




Software Requirements Specification for RouteRunner




Software Requirements Specification for RouteRunner



Software Requirements Specification for RouteRunner



Software Requirements Specification for RouteRunner



Software Requirements Specification for RouteRunner

