

3GPP TS 36.213 V19.3.0 (2026-03)

Technical Specification

3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Evolved Universal Terrestrial Radio Access (E-UTRA); Physical layer procedures (Release 19)



The present document has been developed within the 3rd Generation Partnership Project (3GPP™) and may be further elaborated for the purposes of 3GPP. The present document has not been subject to any approval process by the 3GPP Organizational Partners and shall not be implemented. This Specification is provided for future development work within 3GPP only. The Organizational Partners accept no liability for any use of this Specification. Specifications and Reports for implementation of the 3GPP™ system should be obtained via the 3GPP Organizational Partners' Publications Offices.

3GPP

Postal address

3GPP support office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet

<http://www.3gpp.org>

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© 2026, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI, TTA, TTC).
All rights reserved.

UMTS™ is a Trade Mark of ETSI registered for the benefit of its members
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners
LTE™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners
GSM® and the GSM logo are registered and owned by the GSM Association

Contents

Foreword	8
1 Scope	9
2 References	9
3 Symbols and abbreviations	10
3.1 Symbols	10
3.2 Abbreviations	10
4 Synchronization procedures	12
4.1 Cell search	12
4.2 Timing synchronization	12
4.2.1 Radio link monitoring	12
4.2.2 Inter-cell synchronization	12
4.2.3 Transmission timing adjustments	12
4.3 Timing for Secondary Cell Activation / Deactivation	14
5 Power control	16
5.1 Uplink power control	16
5.1.1 Physical uplink shared channel	17
5.1.1.1 UE behaviour	17
5.1.1.2 Power headroom	32
5.1.2 Physical uplink control channel	35
5.1.2.1 UE behaviour	36
5.1.3 Sounding Reference Symbol (SRS)	41
5.1.3.1 UE behaviour	41
5.1.3.2 Power headroom for Type3 report	44
5.1.4 Power allocation for EUTRA dual connectivity	45
5.1.4.1 Dual connectivity power control Mode 1	45
5.1.4.2 Dual connectivity power control Mode 2	52
5.1.4a Power allocation for dual active protocol stack	57
5.1.5 Power allocation for PUCCH-SCell	57
5.2 Downlink power allocation	58
5.2.1 eNodeB Relative Narrowband TX Power (RNTP) restrictions	61
6 Random access procedure	62
6.1 Physical non-synchronized random access procedure	62
6.1.1 Timing	63
6.2 Random Access Response Grant	64
7 Physical downlink shared channel related procedures	69
7.1 UE procedure for receiving the physical downlink shared channel	71
7.1.1 Single-antenna port scheme	90
7.1.2 Transmit diversity scheme	90
7.1.3 Large delay CDD scheme	91
7.1.4 Closed-loop spatial multiplexing scheme	91
7.1.5 Multi-user MIMO scheme	91
7.1.5A Dual layer scheme	91
7.1.5B Up to 8 layer transmission scheme	91
7.1.6 Resource allocation	91
7.1.6.1 Resource allocation type 0	93
7.1.6.2 Resource allocation type 1	94
7.1.6.3 Resource allocation type 2	95
7.1.6.4 PDSCH starting position	98
7.1.6.4A PDSCH starting position for BL/CE UEs	100
7.1.6.5 Physical Resource Block (PRB) bundling	100
7.1.7 Modulation order and transport block size determination	102
7.1.7.1 Modulation order and redundancy version determination	105
7.1.7.2 Transport block size determination	111

7.1.7.2.1	Transport blocks not mapped to two or more layer spatial multiplexing	116
7.1.7.2.2	Transport blocks mapped to two-layer spatial multiplexing	125
7.1.7.2.3	Transport blocks mapped for DCI Format 1C and DCI Format 6-2	125
7.1.7.2.4	Transport blocks mapped to three-layer spatial multiplexing	126
7.1.7.2.5	Transport blocks mapped to four-layer spatial multiplexing	126
7.1.7.2.6	Transport blocks mapped for BL/CE UEs configured with CEModeB and PDSCH bandwidth up to 1.4MHz	127
7.1.7.2.7	Transport blocks mapped for BL/CE UEs <i>SystemInformationBlockType1-BR</i>	128
7.1.7.2.8	Transport blocks mapped for UEs configured with <i>ce-pdsch-maxBandwidth-config</i> value of 5 MHz or with <i>pdsch-MaxBandwidth-SC-MTCH</i> value of 24 PRBs	128
7.1.7.3	Redundancy Version determination for Format 1C	128
7.1.8	Storing soft channel bits	129
7.1.9	PDSCH resource mapping parameters	129
7.1.10	Antenna ports quasi co-location for PDSCH	131
7.1.11	PDSCH subframe assignment for BL/CE UE	132
7.2	UE procedure for reporting Channel State Information (CSI)	134
7.2.1	Aperiodic CSI Reporting using PUSCH	144
7.2.2	Periodic CSI Reporting using PUCCH	170
7.2.3	Channel Quality Indicator (CQI) definition	211
7.2.4	Precoding Matrix Indicator (PMI) definition	225
7.2.5	Channel-State Information – Reference Signal (CSI-RS) definition	253
7.2.6	Channel-State Information – Interference Measurement (CSI-IM) Resource definition	255
7.2.7	Zero Power CSI-RS Resource definition	255
7.2.8	CSI-RS Activation / Deactivation	255
7.3	UE procedure for reporting HARQ-ACK	256
7.3.1	FDD HARQ-ACK reporting procedure	261
7.3.2	TDD HARQ-ACK reporting procedure	266
7.3.2.1	TDD HARQ-ACK reporting procedure for same UL/DL configuration	266
7.3.2.2	TDD HARQ-ACK reporting procedure for different UL/DL configurations	281
7.3.3	FDD-TDD HARQ-ACK reporting procedure for primary cell frame structure type 1	289
7.3.4	FDD-TDD HARQ-ACK reporting procedure for primary cell frame structure type 2	290
8	Physical uplink shared channel related procedures	292
8.0	UE procedure for transmitting the physical uplink shared channel	293
8.0.1	Single-antenna port scheme	320
8.0.2	Closed-loop spatial multiplexing scheme	320
8.1	Resource allocation for PDCCH/EPDCCH/SPDCCH with uplink DCI format	321
8.1.1	Uplink resource allocation type 0	321
8.1.2	Uplink resource allocation type 1	322
8.1.3	Uplink resource allocation type 2	322
8.1.4	Uplink resource allocation type 3	323
8.1.5	Uplink resource allocation type 4	324
8.1.5.1	UL Resource Block Groups	324
8.1.6	Uplink resource allocation type 5	325
8.2	UE sounding procedure	327
8.3	UE HARQ-ACK procedure	339
8.3A	Autonomous uplink feedback procedure	341
8.4	UE PUSCH hopping procedure	341
8.4.1	Type 1 PUSCH hopping	342
8.4.2	Type 2 PUSCH hopping	342
8.5	UE Reference Symbol (RS) procedure	343
8.6	Modulation order, redundancy version and transport block size determination	344
8.6.1	Modulation order and redundancy version determination	344
8.6.2	Transport block size determination	352
8.6.3	Control information MCS offset determination	359
8.7	UE transmit antenna selection	363
8.8	Transmission timing adjustments	363
9	Physical downlink control channel procedures	363
9.1	UE procedure for determining physical downlink control channel assignment	364
9.1.1	PDCCH assignment procedure	364
9.1.2	PHICH assignment procedure	368

9.1.3	Control Format Indicator (CFI) assignment procedure	371
9.1.4	EPDCCH assignment procedure	372
9.1.4.1	EPDCCH starting position	379
9.1.4.2	Antenna ports quasi co-location for EPDCCH	379
9.1.4.3	Resource mapping parameters for EPDCCH	380
9.1.4.4	PRB-pair indication for EPDCCH	380
9.1.5	MPDCCH assignment procedure	381
9.1.5.1	MPDCCH starting position	389
9.1.5.2	Antenna ports quasi co-location for MPDCCH	389
9.1.5.3	Preconfigured Uplink Resource ACK/fallback procedure	389
9.1.6	SPDCCH assignment procedure	389
9.1.6.1	Resource mapping parameters for SPDCCH	391
9.1.6.2	PRB-pair indication for SPDCCH	391
9.1.6.3	Physical Resource Block (PRB) bundling for DMRS-based SPDCCH	392
9.1.6.4	Antenna ports quasi co-location for DMRS-based SPDCCH	392
9.2	PDCCH/EPDCCH/MPDCCH/SPDCCH validation for semi-persistent scheduling	393
9.2A	PDCCH/EPDCCH validation for autonomous uplink transmissions	395
9.3	PDCCH/EPDCCH/MPDCCH/SPDCCH control information procedure	396
10	Physical uplink control channel procedures	397
10.1	UE procedure for determining physical uplink control channel assignment	398
10.1.1	PUCCH format information	403
10.1.2	FDD HARQ-ACK feedback procedures	410
10.1.2.1	FDD HARQ-ACK procedure for one configured serving cell	410
10.1.2.2	FDD HARQ-ACK procedures for more than one configured serving cell	414
10.1.2.2.1	PUCCH format 1b with channel selection HARQ-ACK procedure	414
10.1.2.2.2	PUCCH format 3 HARQ-ACK procedure	418
10.1.2.2.3	PUCCH format 4 HARQ-ACK procedure	420
10.1.2.2.4	PUCCH format 5 HARQ-ACK procedure	424
10.1.3	TDD HARQ-ACK feedback procedures	424
10.1.3.1	TDD HARQ-ACK procedure for one configured serving cell	426
10.1.3.2	TDD HARQ-ACK procedure for more than one configured serving cell	440
10.1.3.2.1	PUCCH format 1b with channel selection HARQ-ACK procedure	440
10.1.3.2.2	PUCCH format 3 HARQ-ACK procedure	456
10.1.3.2.3	PUCCH format 4 HARQ-ACK procedure	464
10.1.3.2.4	PUCCH format 5 HARQ-ACK procedure	480
10.1.3A	FDD-TDD HARQ-ACK feedback procedures for primary cell frame structure type 2	480
10.1.4	HARQ-ACK Repetition procedure	482
10.1.5	Scheduling Request (SR) procedure	483
10.2	Uplink HARQ-ACK timing	485
11	Physical Multicast Channel (PMCH) related procedures	492
11.1	UE procedure for receiving the PMCH	492
11.2	UE procedure for receiving MCCH and system information change notification	495
12	Assumptions independent of physical channel	495
13	Uplink/Downlink configuration determination procedure for Frame Structure Type 2	496
13.1	UE procedure for determining eIMTA-uplink/downlink configuration	497
13A	Subframe configuration for Frame Structure Type 3	498
14	UE procedures related to Sidelink	501
14.1	Physical Sidelink Shared Channel related procedures	502
14.1.1	UE procedure for transmitting the PSSCH	502
14.1.1.1	UE procedure for determining subframes for transmitting PSSCH for sidelink transmission mode 1	504
14.1.1.1.1	Determination of subframe indicator bitmap	504
14.1.1.2	UE procedure for determining resource blocks for transmitting PSSCH for sidelink transmission mode 1	507
14.1.1.2.1	PSSCH resource allocation for sidelink transmission mode 1	507
14.1.1.2.2	PSSCH frequency hopping for sidelink transmission mode 1	508
14.1.1.3	UE procedure for determining subframes for transmitting PSSCH for sidelink transmission mode 2	508

14.1.1.4	UE procedure for determining resource blocks for transmitting PSSCH for sidelink transmission mode 2	509
14.1.1.4A	UE procedure for determining subframes and resource blocks for transmitting PSSCH for sidelink transmission mode 3	509
14.1.1.4B	UE procedure for determining subframes and resource blocks for transmitting PSSCH and reserving resources for sidelink transmission mode 4	510
14.1.1.4C	UE procedure for determining subframes and resource blocks for PSSCH transmission associated with an SCI format 1	510
14.1.1.5	UE procedure for PSSCH power control	511
14.1.1.6	UE procedure for determining the subset of resources to be reported to higher layers in PSSCH resource selection in sidelink transmission mode 4 and in sensing measurement in sidelink transmission mode 3	513
14.1.1.7	Conditions for selecting resources when the number of HARQ transmissions is two in sidelink transmission mode 4	516
14.1.2	UE procedure for receiving the PSSCH	516
14.1.3	UE procedure for determining resource block pool and subframe pool for sidelink transmission mode 2	517
14.1.5	UE procedure for determining resource block pool and subframe pool for sidelink transmission mode 3 and 4	518
14.2	Physical Sidelink Control Channel related procedures	519
14.2.1	UE procedure for transmitting the PSCCH	519
14.2.1.1	UE procedure for determining subframes and resource blocks for transmitting PSCCH for sidelink transmission mode 1	522
14.2.1.2	UE procedure for determining subframes and resource blocks for transmitting PSCCH for sidelink transmission mode 2	522
14.2.1.3	UE procedure for PSCCH power control	523
14.2.2	UE procedure for receiving the PSCCH	524
14.2.3	UE procedure for determining resource block pool and subframe pool for PSCCH	524
14.2.4	UE procedure for determining resource block pool for PSCCH in sidelink transmission mode 3 and 4	525
15	Void	529
16	UE Procedures related to narrowband IoT	529
16.1	Synchronization procedures	529
16.1.1	Cell search	529
16.1.2	Timing synchronization	529
16.2	Power control	530
16.2.1	Uplink power control	530
16.2.1.1	Narrowband physical uplink shared channel	530
16.2.1.1.1	UE behaviour	530
16.2.1.1.2	Power headroom	531
16.2.1.2	SR	532
16.2.1.2.1	UE behaviour	532
16.2.2	Downlink power allocation	532
16.3	Random access procedure	533
16.3.1	Physical non-synchronized random access procedure	533
16.3.2	Timing	534
16.3.3	Narrowband random access response grant	535
16.4	Narrowband physical downlink shared channel related procedures	536
16.4.1	UE procedure for receiving the narrowband physical downlink shared channel	537
16.4.1.1	Single-antenna port scheme	541
16.4.1.2	Transmit diversity scheme	541
16.4.1.3	Resource allocation	541
16.4.1.4	NPDSCH starting position	544
16.4.1.5	Modulation order and transport block size determination	545
16.4.1.5.1	Transport blocks not mapped for <i>SystemInformationBlockType1-NB</i>	546
16.4.1.5.2	Transport blocks mapped for <i>SystemInformationBlockType1-NB</i>	546
16.4.2	UE procedure for reporting ACK/NACK	547
16.5	Narrowband physical uplink shared channel related procedures	549
16.5.1	UE procedure for transmitting format 1 narrowband physical uplink shared channel	549
16.5.1.1	Resource allocation	552

16.5.1.2	Modulation order, redundancy version and transport block size determination	554
16.5.2	UE procedure for NPUSCH retransmission	556
16.5.3	UE procedure for transmitting SR	556
16.6	Narrowband physical downlink control channel related procedures	556
16.6.1	NPDCCH starting position	563
16.6.2	NPDCCH control information procedure	563
16.6.3	NPDCCH validation for semi-persistent scheduling	563
16.6.4	Preconfigured uplink resource ACK/fallback procedure	564
16.7	Assumptions independent of physical channel related to narrowband IoT	564
16.8	UE procedure for acquiring cell-specific reference signal sequence and raster offset	564
16.9	UE procedure for receiving narrowband wake up signal	565
16.10	GNSS measurement gap related procedures	566
17	Wake-up signal related procedures for BL/CE UE	566
18	GNSS measurement gap related procedures for BL/CE UE	567
Annex A (informative): Change history		568