

Q1 Instructions

0 Points

To receive full credit on this quiz, you must score at least 50%.

The Github repo for Lecture 14 is at:

<https://github.com/ucsd-cse12-f20/ucsd-cse12-f20.github.io/tree/master/lectures/lecture-14>

Q2 QuickSort

1 Point

Which of the following descriptions of pivot selection will result in the best case quicksort runtime?

- ☐ Randomly choosing the pivot
- ☐ Choosing the first value as the pivot
- ☐ Choosing the median index as the pivot
- ☒ Choosing the median value as the pivot
- ☐ There is no definite pivot selection method that will always result in best case runtime

Q3 MergeSort

1 Point

Consider the merge sort from class. How many times will the element at index 0 be copied when sorting an array of length n over the entire run of the algorithm?

- ☐ 1
- ☐ $\lg(n)$
- ☒ $2 \cdot \lg(n)$
- ☐ $n/2$
- ☐ n

Q4 Sorting

1 Point

Which of the following statements about sorting are true?

☐ The best case time of all sorts is $O(1)$ because of the case when an array is length 1

☒ Merge sort has best and worst cases of $O(n \lg(n))$

☒ If arrays are split into thirds instead of halves in merge sort, the best case would still be $O(n \lg(n))$ {HINT: look up the rules of logs!}

☐ Quicksort is $O(n^2)$ only when an array is in reversed order

☒ The worst cases for selection sort and insertion sort occur when an array is in reversed order