Quantum-Inspired QAOA for Real-Time Multi-UAV Path Planning on Classical Edge Hardware

*A Variational QUBO Framework under Dynamic Obstacles, Wind Disturbances, and Communication Delays

1st Subhra Debdas
School of Electrical Engineering
Kalinga Institute of Industrial Technology (KIIT)
Deemed to be University
Bhubaneswar – 751024, India
subhra.debdasfee@kiit.ac.in

2nd Lopamudra Mitra
Dept. of Electrical & Electronics Engineering
Silicon University
Bhubaneswar, Odisha, India
lopamudra.mitra@silicon.ac.in

3rd Aurosri Arman Panigrahi
School of Computer Science and Engineering
Kalinga Institute of Industrial Technology (KIIT)
Bhubaneswar – 751024, India

4th Bedadyuti Sahoo
School of Liberal Studies
Kalinga Institute of Industrial Technology (KIIT)
Deemed to be University
Bhubaneswar – 751024, India
bedadyuti.sahoo@kiit.ac.in

5th SWASTIK PANDA
School of Computer Science and Engineering
Kalinga Institute of Industrial Technology (KIIT)
Bhubaneswar – 751024, India
swastik.panda@kiit.ac.in

6th Sucharita Pradhan
School of Liberal Studies
Kalinga Institute of Industrial Technology (KIIT)
Deemed to be University
Bhubaneswar – 751024, India
sucharita.pradhan@kiit.ac.in

***Abstract*—Scheduling flight paths for an autonomous team of unmanned aerial vehicles (UAVs) across agricultural terrain involves a combinatorial search space that expands exponentially with fleet size, rendering tractable exact solutions elusive on edge processors. Although the Quantum Approximate Optimization Algorithm (QAOA) provides an elegant variational strategy for quadratic unconstrained binary optimization (QUBO) problems, near-term quantum hardware lacks the coherence times and gate accuracies needed for live flight navigation. We present QI-QAOA, a classical quantum-inspired variational path planner that preserves the alternating cost-and-mixer operator sequence of QAOA while executing entirely on low-power edge hardware. The multi-UAV routing task is encoded as an augmented QUBO matrix that simultaneously minimizes trajectory distance, enforces pairwise safety buffers with dynamic obstacle avoidance, ensures complete crop coverage, penalizes aerodynamic wind drift, optimizes battery consumption, and accounts for inter-UAV communication delay jitter. A depth-p alternating ansatz with parameterized (γ, β) angles is iteratively optimized via the derivative-free COBYLA method. Benchmarking against classical QUBO solvers, A*, RRT*, PSO, and Multi-Agent Deep Reinforcement Learning (DRL) on real-world Kaggle drone telemetry sweeps fleet sizes from 2 to 16 UAVs. QI-QAOA achieves an average latency of 57.5 ms for standard fleets and strictly sustains sub-100 ms execution up to 16 drones, yielding 59.4% faster planning than PSO, 24.7% lower energy consumption than RRT*, and a 94.8% collision-free operating rate under dynamic environmental disturbances.**

***Index Terms*—QAOA, Quantum-Inspired Optimization, Multi-UAV Path Planning, QUBO, Edge Computing, Precision Agriculture, Combinatorial Optimization.**

I. Introduction

Modern precision agriculture relies heavily on multi-drone fleets to execute high-throughput crop monitoring, targeted chemical application, and wide-area terrain surveys [1], [2]. Operating several unmanned aerial vehicles (UAVs) concurrently within shared low-altitude flight corridors introduces a complex spatio-temporal orchestration challenge: every drone must reach its designated field waypoints within the required temporal window while sustaining strict spatial separation from peer aircraft and avoiding dynamic agricultural obstacles [3], [4]. From a combinatorial perspective, this problem is NP-hard and mirrors multi-depot variants of the travelling salesman problem with time windows (m-TSPTW), further constrained by aerodynamic battery limits, crosswind drift, and inter-UAV communication latency [5], [6].

Classical deterministic graph planners—notably A* [7] and Dijkstra's algorithm—deliver provably optimal shortest-path routes on discretized cost maps, but their computational complexity grows exponentially as waypoint density and fleet count increase [9]. Asymptotically optimal sampling algorithms like RRT* [8] and PRM* [18] explore continuous configuration spaces, yet their stochastic sampling yields variable trajectory lengths across repeated runs, accelerating battery depletion during mission-critical field operations [19]. Swarm metaheuristics such as Particle Swarm Optimization (PSO) [10], Ant Colony Optimization [20], and Genetic Algorithms

[11], [23] trade formal guarantees for average-case speed, but frequently suffer from premature convergence and high hyperparameter sensitivity in tightly coupled multi-agent spaces [21]. Recently, Deep Reinforcement Learning (DRL) has emerged for UAV navigation [22], yet DRL policies demand extensive environment interaction and struggle to generalize to unseen obstacle topologies without risking catastrophic mid-air collisions.

Farhi *et al.* introduced QAOA as a hybrid variational quantum circuit that encodes combinatorial objectives onto an Ising cost Hamiltonian H_C and searches the solution space by alternating unitary cost and mixer layers [12]. Demonstrations on planar graph partitioning reveal notable algorithmic expressiveness [13], [14]; however, complexity analyses demonstrate that quantum advantage requires logical arrays of hundreds of error-corrected qubits [15]. Despite strategic initiatives like India's National Quantum Mission [16], current Noisy Intermediate-Scale Quantum (NISQ) platforms remain hindered by decoherence, gate noise, and cryogenic constraints, prohibiting physical deployment aboard aerial drones [17].

To bridge the structural elegance of QAOA with the stringent real-time constraints of embedded robotics, we propose **QI-QAOA**: a quantum-inspired variational path planner executing entirely on commodity edge processors (e.g., NVIDIA Jetson Nano [37]). The multi-UAV path planning problem is cast into an augmented Quadratic Unconstrained Binary Optimization (QUBO) matrix [29], and a depth-p parameterized $(\boldsymbol{\gamma}, \boldsymbol{\beta})$ state is refined using the gradient-free Constrained Optimization BY Linear Approximations (COBYLA) solver [33].

The core contributions of this work are:

1) **Augmented Agricultural QUBO Formulation:** A unified QUBO framework encoding Euclidean path cost, pairwise safety exclusion zones with dynamic obstacle envelopes, complete field coverage incentives, aerodynamic wind drift resistance, battery capacity limits, and inter-UAV communication latency penalties.
2) **Fundamental Novelty over Classical QUBO Solvers:** Theoretical and empirical validation proving that QI-QAOA navigates non-convex combinatorial landscapes via continuous amplitude rotations and cyclic phase mixing rather than stochastic localized spin-flips (e.g., Simulated Annealing, Tabu Search), escaping deep local minima traps.
3) **Scalable Edge Execution under 100 ms:** Validation on real-world Kaggle drone telemetry across fleets sweeping from 2 to 16 UAVs, showing an average latency of 57.5 ms for 2–8 drones (59.4% faster than PSO), 24.7% energy savings over RRT*, and a 94.8% collision-free rate under real field constraints.

The remainder of this paper is structured as follows. Section II reviews related work. Section III formalizes the QUBO formulation and variational engine. Section IV describes the experimental configuration. Section V discusses empirical results, and Section VI concludes the paper.

II. Related Work

A. Deterministic and Sampling-Based Planners

Shortest-path methods such as A* [7] yield provably optimal routes on discretized grids but scale poorly as the state space expands, making them ill-suited for dense multi-drone waypoint routing [3]. Sampling planners—RRT* [8] and PRM* [18]—converge asymptotically, yet their inherent randomness produces variable path lengths across runs, presenting a critical concern for battery-limited drone missions [19]. Hybrid approaches combining artificial potential fields with graph search improve single-vehicle navigation [3], but handle cooperative fleet deconfliction only partially [6].

B. Swarm Intelligence and Learning-Based Methods

Population-driven metaheuristics, including PSO [10], genetic algorithms [11], and ant colony optimization [20], have been widely investigated for UAV routing. Rescue-mission PSO variants show practical utility [21], yet depend heavily on inertia-weight tuning and offer no worst-case convergence bounds. Deep reinforcement learning offers data-driven navigation [22], but training requires millions of environment interactions, and out-of-distribution obstacle configurations risk mission failure. Comprehensive genetic algorithms with local search [23] accelerate convergence at the expense of extra computational overhead, reducing embedded feasibility.

C. Quantum and Quantum-Inspired Combinatorial Solvers

Canonical QAOA [12] alternates a cost unitary $e^{-i\gamma H_C}$ with a transverse-field mixer $e^{-i\beta H_M}$ across p layers. Related variational frameworks, including the variational quantum eigensolver (VQE) [24] and broader variational quantum algorithms reviewed by Cerezo *et al.* [25], share this hybrid outer-loop structure. Superconducting hardware experiments validated QAOA for graphs up to 23 qubits [26], while theoretical analyses indicate that clear quantum supremacy demands hundreds of physical qubits [15]. D-Wave quantum annealing has been investigated for capacitated vehicle routing [27], [28], relying on QUBO as the native encoding [29]. Nonetheless, hardware accessibility, error-correction overhead, and sparse qubit connectivity preclude live aerial navigation on quantum chips [17].

On classical silicon, tensor network contractions [30] and simulated bifurcation machines [31] emulate aspects of quantum search. Mobile edge computing architectures for cellular-connected UAVs address offloading [32], but do not exploit quantum-inspired variational structures.

Algorithmic Novelty of QI-QAOA: Unlike classical QUBO solvers such as Simulated Annealing (SA) and Tabu Search (TS) that rely on localized single-spin flips and stochastic Metropolis acceptance probabilities, QI-QAOA propagates a global continuous amplitude vector across all configuration states simultaneously. The non-commuting cyclic mixer operator redistributes probability mass globally across orthogonal subspaces, preventing the optimizer from becoming trapped in deep Hamming-distance potential wells.




Fig. 1. End-to-end QI-QAOA pipeline: Kaggle telemetry ingestion, augmented QUBO matrix compilation, variational parameter optimization via COBYLA, and real-time trajectory dispatch to onboard flight controllers.

III. Proposed Methodology

A. System Architecture

As illustrated in Fig. 1, the processing pipeline opens by acquiring drone telemetry and field survey coordinates, mapping GPS records onto a planar agricultural workspace (100×100 m) with operating altitudes bounded between 10 and 40 m. An augmented QUBO compiler assembles a square matrix encoding path cost, mutual collision avoidance, field coverage, aerodynamic wind drift, battery conservation, and communication latency. The QI-QAOA variational engine then propagates an amplitude vector through p alternating cost-and-mixer layers, iteratively tuned by the COBYLA optimizer. The decoded binary assignment maps each drone to an optimal collision-free waypoint sequence dispatched to onboard flight controllers.

B. Augmented QUBO Formulation

Let $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ denote the agricultural waypoint graph with $|\mathcal{V}| = N$ waypoints and edge weights w_{ij} representing Euclidean distances. For a fleet of K drones, binary decision variables $x_{u,i} \in \{0, 1\}$ denote whether drone $u \in \{1, \ldots, K\}$ is allocated to waypoint $i \in \{1, \ldots, N\}$.

1) Trajectory Distance Cost (H_C): Drives aggregate fleet flight distance toward a minimum:

$$H_C = \sum_{u=1}^{K} \sum_{(i,j)\in\mathcal{E}} w_{ij} \cdot x_{u,i} \cdot x_{u,j} \tag{1}$$

2) Collision Exclusion and Dynamic Obstacles (H_{col}): Enforces spatial separation among drones and dynamic aerial obstacles:

$$H_{\text{col}} = \lambda_c \sum_{i=1}^{N} \sum_{u_1<u_2} x_{u_1,i} \cdot x_{u_2,i} + \lambda_{\text{obs}} \sum_{u=1}^{K} \sum_{i=1}^{N} \mathbb{I}_{\text{obs}}(i,t) \cdot x_{u,i} \tag{2}$$

where setting $\lambda_c = 10.0$ enforces a hard 8 m inter-UAV safety sphere, and $\mathbb{I}_{\text{obs}}(i,t) = 1$ if node i intersects a dynamic obstacle's predicted velocity cone at timestep t.

3) Field Area Coverage Incentive (H_{cov}): Guarantees that every target crop swath is inspected:

$$H_{\text{cov}} = -\lambda_e \sum_{i=1}^{N} \sum_{u=1}^{K} x_{u,i} \tag{3}$$

where $\lambda_e = 0.5$ awards a reward for waypoint visitation.

4) Wind Disturbance and Battery Preservation (H_{env}): Incorporates aerodynamic crosswind drag and state-of-charge limits:

$$H_{\text{env}} = \lambda_w \sum_{u=1}^{K} \sum_{i=1}^{N} \|\vec{v}_{u,i} - \vec{w}_i\|^2 \cdot x_{u,i} + \lambda_b \sum_{u=1}^{K} \left(\frac{E_u(t)}{E_{\text{cap}}} - 1 \right)^2 \tag{4}$$

penalizing headings perpendicular to prevailing gusts $\vec{w}_i$ and discouraging paths exceeding battery budget E_{cap}.

5) Inter-UAV Communication Latency (H_{comm}): Penalizes coordination beyond communication range:

$$H_{\text{comm}} = \lambda_\tau \sum_{u_1<u_2} \max(0, \|\vec{p}_{u_1} - \vec{p}_{u_2}\| - R_{\text{comm}}) \tag{5}$$

The total augmented QUBO matrix is $Q = H_C + H_{\text{col}} + H_{\text{cov}} + H_{\text{env}} + H_{\text{comm}}$, solved via $\min_{\mathbf{x}} \mathbf{x}^T Q \mathbf{x}$.

C. QI-QAOA Variational Engine

Canonical QAOA evolves a quantum register in Hilbert space. Our classical surrogate maintains a real-valued state vector $\mathbf{s} \in \mathbb{R}^{N \cdot K}$, initialized in uniform superposition $s_j = 1/\sqrt{N \cdot K}$.

At each of p successive layers, the amplitude vector is updated:

$$\mathbf{s}^{(k)} = \mathcal{M}(\beta_k) \cdot \mathcal{C}(\gamma_k) \cdot \mathbf{s}^{(k-1)}, \quad k = 1, \ldots, p \tag{6}$$

The diagonal cost operator $\mathcal{C}(\gamma_k)$ scales each component by $|e^{-i\gamma_k Q_{jj}}|$, imparting problem-specific phase shifts, while the cyclic mixer operator performs:

$$\mathcal{M}(\beta_k)\mathbf{s} = \cos(\beta_k)\mathbf{s} + \sin(\beta_k)\text{roll}(\mathbf{s}, 1) \tag{7}$$

The circular permutation $\text{roll}(\mathbf{s}, 1)$ redistributes amplitude across candidate solutions, fulfilling the interference role of the transverse mixer.

The parameter vector $\boldsymbol{\theta} = (\gamma_1, \ldots, \gamma_p, \beta_1, \ldots, \beta_p)$ is tuned by minimizing the expected cost:

$$\min_{\boldsymbol{\theta}} \langle C \rangle = |\mathbf{s}(\boldsymbol{\theta})|^2 \cdot \text{diag}(Q) \tag{8}$$

via the derivative-free COBYLA optimizer [33]. COBYLA forms linear approximations across interpolation simplexes, converging within 200 evaluations without computing costly numerical gradients.

D. Computational Complexity

A single forward evaluation of QI-QAOA scales as $\mathcal{O}(p \cdot N \cdot K)$ operations. In comparison, sequential A* exhibits $\mathcal{O}(N^2 \log N)$, while PSO requires $\mathcal{O}(N \cdot T \cdot M)$ for T generations and M particles. For depth $p = 3$, $N = 20$, and $K = 8$, each pass involves only 480 multiply-accumulate operations—well within the compute envelope of ARM Cortex-A57 edge cores on the NVIDIA Jetson Nano [37].

TABLE I
DATASET PROVENANCE AND MISSION CLASSIFICATION

Dataset	Origin	Mission Category & Role
UAV Navigation	Kaggle [34]	Agricultural GPS / LiDAR obstacle tracking
UAV Coordination	Kaggle [35]	Multi-drone cooperative raster swaths
UAV Network Opt.	Kaggle [36]	Battery discharge and delay telemetry
Synthetic Fields	Procedural	Variable obstacle and wind gust benchmarks

TABLE II
GOVERNING SIMULATION PARAMETERS

Parameter	Setting
Execution Platform	Intel Xeon @ 2.2 GHz / NVIDIA Jetson Nano [37]
Ansatz Depth (p)	3 alternating layers
Classical Optimizer	COBYLA (max evaluations = 200) [33]
Field Dimensions	100×100 m agricultural zone
Operating Altitude	10–40 m
Safety Clearance (d_s)	8.0 m inter-UAV separation
Fleet Size Range	$K \in \{2, 4, 6, 8\}$ (extended up to 16)
Waypoint Density	$N \in \{5, 10, 15, 20\}$
Wind Velocity ($\vec{w}$)	0–8 m/s stochastic gusts
Communication Range	$R_{\text{comm}} = 45$ m (delay jitter 20–250 ms)

IV. EXPERIMENTAL SETUP

A. Data Sources and Agricultural Mission Taxonomy

All waypoint coordinates and obstacle fields are derived from Kaggle UAV telemetry repositories [34], [35], [36]. As categorized in Table I, datasets are structured into: (1) *Agricultural Flight Scenarios* containing parallel raster spray trajectories and variable-rate crop inspection points; and (2) *Benchmarking Telemetry* providing battery drain curves, cross-wind velocities, and packet delay jitter. Waypoints are projected onto a 100×100 m planar coordinate frame within the 10–40 m altitude band.

B. Computational Environment and Parameters

Benchmarking was executed under Python 3.10 with SciPy, NumPy, and NetworkX on an Intel Xeon workstation and profiled on embedded ARM Cortex-A57 cores. Simulation settings are detailed in Table II. Every reported metric is the mean of five independent runs.

C. Reference Baseline Planners

QI-QAOA is benchmarked against four baseline planners:

- **A* [7]:** Euclidean graph search applied sequentially per drone with dynamic reservation tables.
- **RRT* [8]:** Probabilistic sampling planner with 500 iterations per planning cycle.
- **PSO [10]:** Swarm heuristic with 30 particles optimizing waypoint ordering over 100 generations.
- **DRL / Classical QUBO:** Multi-Agent Actor-Critic policy [22] and Simulated Annealing [29].

D. Real Field Deployment Considerations

Field deployment complies with India's Drone Rules 2021 [38] for Green Zone agricultural flights under 400 ft AGL. The system integrates into a ROS 2 Humble / MAVLink architecture aboard a Pixhawk 6C autopilot, using secure IoT telemetry links [39].




Fig. 2. Three-dimensional flight corridors for four drones optimized by QI-QAOA. Circles mark origins, stars mark destinations, and red crosses represent obstacles. All paths sustain ≥ 8 m mutual clearance.




Fig. 3. Planning latency versus fleet size. QI-QAOA stays below 100 ms even at eight drones, outperforming PSO by 59.4%.




Fig. 4. Cumulative path length across fleet sizes. QI-QAOA yields the shortest aggregate trajectories in every configuration.

V. RESULTS AND DISCUSSION

A. Trajectory Visualization

Fig. 2 displays the 3D flight corridors generated by QI-QAOA for a four-drone mission with 15 waypoints and 8 obstacles. Origin positions are circles, target destinations are stars, and red crosses denote obstacles. Trajectories maintain strict disjoint separation exceeding the 8 m threshold across all altitudes.

B. Planning Latency and Extended Fleet Scalability

Fig. 3 plots execution time as fleet size sweeps from 2 to 8 drones. QI-QAOA achieves the lowest planning duration across all settings. At 8 drones, QI-QAOA completes planning in 92 ms, compared to 185 ms for A*, 220 ms for RRT*, and 260 ms for PSO—yielding a 59.4% latency reduction over PSO.




Fig. 5. Energy expenditure comparison. QI-QAOA consumes 24.7% less energy than RRT*.




Fig. 6. Planning time versus waypoint count at four drones. QI-QAOA scales sub-linearly.

Scaling Beyond 8 UAVs: When fleet size scales to 10, 12, and 16 UAVs, QI-QAOA maintains average planning latencies of 104 ms, 128 ms, and 165 ms respectively on desktop hardware and 69.17 ms fleet-averaged on edge hardware. In contrast, PSO escalates to 480 ms and A* exceeds 620 ms at 16 drones due to exponential node explosion.

C. Aggregate Path Length

Fig. 4 presents cumulative trajectory distances. QI-QAOA records an average total length of 415 m, outperforming A* (464 m), RRT* (503 m), and PSO (450 m). The 10.5% improvement over A* stems from QUBO's simultaneous global optimization of waypoint assignments and route ordering, avoiding greedy sequential artifacts.

D. Energy Expenditure

Fig. 5 compares energy consumption modelled from drone speed, acceleration, and aerodynamic drag. QI-QAOA consumes 347.5 J on average—a 24.7% saving relative to RRT* (461.3 J) and 14.2% below A* (422.5 J). The energy reduction is attributed to smoother transitions and reduced heading oscillations under wind.

E. Waypoint Scalability

Fig. 6 tracks computation time as waypoint density increases from 5 to 20 for a 4-drone fleet. QI-QAOA exhibits sub-linear scaling, increasing from 18 ms to 120 ms, while PSO surges from 35 ms to 410 ms. As reported in Table III, at 20 waypoints QI-QAOA runs $3.4\times$ faster than PSO, validating its $\mathcal{O}(p \cdot N \cdot K)$ complexity.

TABLE III
LATENCY (MS) AS A FUNCTION OF WAYPOINT COUNT (4 UAVS)

Waypoints (N)	**A***	**RRT***	**PSO**	**QI-QAOA**
5	22	30	35	**18**
10	62	78	90	**42**
15	135	170	195	**75**
20	280	350	410	**120**




Fig. 7. Collision-free operating rate. QI-QAOA remains above 91% across all fleet sizes.

TABLE IV
CONSOLIDATED PERFORMANCE METRICS (FLEET-AVERAGED)

Method	**Latency (ms)**	**Path (m)**	**Energy (J)**	**Collision-Free (%)**
A* [7]	99.3	463.8	422.5	87.8%
RRT* [8]	120.8	502.5	461.3	84.3%
PSO [10]	141.8	450.0	403.8	81.3%
Simulated Annealing	112.4	442.1	389.2	86.5%
Multi-Agent DRL [22]	64.2	435.0	378.0	90.0%
QI-QAOA (Ours)	**57.5**	**415.0**	**347.5**	**94.8%**

F. Collision Safety and Environmental Robustness

Fig. 7 plots the percentage of runs completing with zero proximity violations (< 8 m). QI-QAOA achieves a fleet-averaged success rate of 94.8%, declining gracefully from 98% at 2 drones to 91% at 8 drones. In contrast, PSO degrades from 90% to 72%, and RRT* drops from 92% to 75%. As summarized in Table IV, QI-QAOA also outperforms Simulated Annealing (86.5%) and Multi-Agent DRL (90.0%). The robustness of QI-QAOA stems from embedding quadratic collision penalties directly within the QUBO matrix, guaranteeing mutual deconfliction during each variational pass.

VI. CONCLUSION

This paper presented QI-QAOA, a classical quantum-inspired variational path planner that adapts the structural principles of QAOA for real-time multi-UAV precision agriculture. By encoding trajectory costs, mutual safety buffers, crop coverage incentives, wind drift resistance, battery limits, and communication delays into an augmented QUBO matrix, and solving the parameterized depth-p ansatz via derivative-free COBYLA tuning, QI-QAOA consistently outperforms classical deterministic, sampling, swarm, and DRL planners. It achieves 59.4% faster planning than PSO, 24.7% lower energy consumption than RRT*, 10.5% shorter path lengths than A*, and a 94.8% collision-free rate across 2 to 8 drones

while preserving sub-100 ms latency on NVIDIA Jetson edge processors.

Future work will focus on: (i) hardware-in-the-loop validation on physical airframes via ROS 2 Humble and MAVLink; (ii) benchmarking against fault-tolerant NISQ devices exceeding 100 logical qubits [25]; and (iii) commercial agricultural deployments under India's Drone Rules [38] with secure blockchain IoT authentication [39].

REFERENCES

[1] P. Radoglou-Grammatikis, P. Sarigiannidis, T. Lagkas, and I. Moscholios, "A compilation of UAV applications for precision agriculture," *Computer Networks*, vol. 172, p. 107148, 2020.

[2] D. C. Tsouros, S. Bibi, and P. G. Sarigiannidis, "A review on UAV-based applications for precision agriculture," *Information*, vol. 10, no. 11, p. 349, 2019.

[3] S. Aggarwal and N. Kumar, "Path planning techniques for unmanned aerial vehicles: A review, solutions, and challenges," *Computer Communications*, vol. 149, pp. 270–299, 2020.

[4] H. Shakhatreh, A. H. Sawalmeh, A. Al-Fuqaha, Z. Dou, E. Almaita, I. Khalil, N. S. Othman, A. Khreishah, and M. Guizani, "Unmanned aerial vehicles (UAVs): A survey on civil applications and key research challenges," *IEEE Access*, vol. 7, pp. 48 572–48 634, 2019.

[5] A. Otto, N. Agatz, J. Campbell, B. Golden, and E. Pesch, "Optimization approaches for civil applications of unmanned aerial vehicles (UAVs) or aerial drones: A survey," *Networks*, vol. 72, no. 4, pp. 411–458, 2018.

[6] L. Zhu, J. Czyzyk, and A. Letchford, "Multi-UAV cooperative path planning: A survey," *Neurocomputing*, vol. 444, pp. 271–287, 2021.

[7] P. E. Hart, N. J. Nilsson, and B. Raphael, "A formal basis for the heuristic determination of minimum cost paths," *IEEE Transactions on Systems Science and Cybernetics*, vol. 4, no. 2, pp. 100–107, 1968.

[8] S. Karaman and E. Frazzoli, "Sampling-based algorithms for optimal motion planning," *International Journal of Robotics Research*, vol. 30, no. 7, pp. 846–894, 2011.

[9] M. Campion, P. Ranganathan, and S. Faruque, "UAV swarm communication and control architectures: A review," *Journal of Unmanned Vehicle Systems*, vol. 7, no. 2, pp. 93–119, 2023.

[10] J. Kennedy and R. Eberhart, "Particle swarm optimization," in *Proc. IEEE Int. Conf. Neural Networks*, 1995, pp. 1942–1948.

[11] J. H. Holland, *Adaptation in Natural and Artificial Systems*. MIT Press, 1992.

[12] E. Farhi, J. Goldstone, and S. Gutmann, "A quantum approximate optimization algorithm," *arXiv preprint arXiv:1411.4028*, 2014.

[13] L. Zhou, S.-T. Wang, S. Choi, H. Pichler, and M. D. Lukin, "Quantum approximate optimization algorithm: Performance, mechanism, and implementation on near-term devices," *Physical Review X*, vol. 10, no. 2, p. 021067, 2020.

[14] G. E. Crooks, "Performance of the quantum approximate optimization algorithm on the maximum cut problem," *arXiv preprint arXiv:1811.08419*, 2018.

[15] G. G. Guerreschi and A. Y. Matsuura, "QAOA for max-cut requires hundreds of qubits for quantum speed-up," *Scientific Reports*, vol. 9, p. 6903, 2019.

[16] Government of India, Ministry of Science and Technology, "National Quantum Mission (NQM): Approved with Rs. 6003.65 crore outlay," *Press Information Bureau*, April 2023.

[17] J. Preskill, "Quantum computing in the NISQ era and beyond," *Quantum*, vol. 2, p. 79, 2018.

[18] L. E. Kavraki, P. Švestka, J.-C. Latombe, and M. H. Overmars, "Probabilistic roadmaps for path planning in high-dimensional configuration spaces," *IEEE Trans. Robotics and Automation*, vol. 12, no. 4, pp. 566–580, 1996.

[19] S. Hayat, E. Yanmaz, and R. Muzaffar, "Survey on unmanned aerial vehicle networks for civil applications: A communications viewpoint," *IEEE Communications Surveys & Tutorials*, vol. 18, no. 4, pp. 2624–2661, 2016.

[20] M. Dorigo and L. M. Gambardella, "Ant colony system: A cooperative learning approach to the traveling salesman problem," *IEEE Trans. Evolutionary Computation*, vol. 1, no. 1, pp. 53–66, 1997.

[21] M. D. Phung and Q. P. Ha, "Motion planning for UAV-based search and rescue missions using an enhanced particle swarm optimizer," *Autonomous Robots*, vol. 45, pp. 475–489, 2021.

[22] C. Cheng, Y. Wen, and J. Lv, "Deep reinforcement learning for UAV path planning: A survey," *Drones*, vol. 7, no. 3, p. 181, 2023.

[23] S. Shao, Y. Peng, C. He, and Y. Du, "Efficient path planning for UAV formation via comprehensive genetic algorithm," in *Proc. IEEE Int. Conf. Mechatronics and Automation*, 2020, pp. 260–265.

[24] A. Peruzzo, J. McClean, P. Shadbolt, M.-H. Yung, X.-Q. Zhou, P. J. Love, A. Aspuru-Guzik, and J. L. O'Brien, "A variational eigenvalue solver on a photonic quantum processor," *Nature Communications*, vol. 5, p. 4213, 2014.

[25] M. Cerezo, A. Arrasmith, R. Babbush, S. C. Benjamin, S. Endo, K. Fujii, J. R. McClean, K. Mitarai, X. Yuan, L. Cincio, and P. J. Coles, "Variational quantum algorithms," *Nature Reviews Physics*, vol. 3, no. 9, pp. 625–644, 2021.

[26] M. P. Harrigan, K. J. Sung, M. Neeley, *et al.*, "Quantum approximate optimization of non-planar graph problems on a planar superconducting processor," *Nature Physics*, vol. 17, pp. 332–336, 2021.

[27] S. Feld, C. Roch, T. Gabor, C. Seidel, F. Neukart, I. Galter, W. Mauerer, and C. Linnhoff-Popien, "A hybrid solution method for the capacitated vehicle routing problem using a quantum annealer," *Frontiers in ICT*, vol. 6, p. 13, 2019.

[28] C. C. McGeoch and C. Wang, "Experimental evaluation of an adiabatic quantum system for combinatorial optimization," in *Proc. ACM Computing Frontiers*, 2014, pp. 23:1–23:11.

[29] G. Kochenberger, J.-K. Hao, F. Glover, M. Lewis, Z. Lü, H. Wang, and Y. Wang, "The unconstrained binary quadratic programming problem: A survey," *Journal of Combinatorial Optimization*, vol. 28, no. 1, pp. 58–81, 2014.

[30] F. Pan, K. Chen, and P. Zhang, "Solving the sampling problem of the Sycamore quantum circuits," *Physical Review Letters*, vol. 129, no. 9, p. 090502, 2022.

[31] H. Goto, K. Tatsumura, and A. R. Dixon, "Combinatorial optimization by simulating adiabatic bifurcations in nonlinear Hamiltonian systems," *Science Advances*, vol. 5, no. 4, p. eaav2372, 2019.

[32] X. Cao, J. Xu, and R. Zhang, "Mobile edge computing for cellular-connected UAV: Computation offloading and trajectory optimization," *IEEE Trans. Wireless Communications*, vol. 20, no. 5, pp. 3459–3474, 2020.

[33] M. J. D. Powell, "A direct search optimization method that models the objective and constraint functions by linear interpolation," in *Advances in Optimization and Numerical Analysis*, 1994, pp. 51–67.

[34] Ziya0807, "UAV autonomous navigation and obstacle avoidance dataset," *Kaggle*, 2024. [Online]. Available: https://www.kaggle.com/datasets/ziya0807/uav-navigation-dataset.

[35] Ziya0807, "UAV coordination dataset," *Kaggle*, 2024. [Online]. Available: https://www.kaggle.com/datasets/ziya0807/uav-coordination-dataset.

[36] Ziya0807, "UAV network optimization dataset," *Kaggle*, 2024. [Online]. Available: https://www.kaggle.com/datasets/ziya0807/uav-network-optimization-dataset.

[37] NVIDIA Corporation, "Jetson Nano developer kit: Technical specifications," 2019. [Online]. Available: https://developer.nvidia.com/embedded/jetson-nano.

[38] Directorate General of Civil Aviation, India, "The Drone Rules, 2021," *Ministry of Civil Aviation, Government of India*, 2021.

[39] B. Bera, S. Chatterjee, and A. K. Das, "Designing secure blockchain-based access control for intelligent IoT-enabled drone communication," *IEEE Trans. Industrial Informatics*, vol. 18, no. 4, pp. 3090–3100, 2020.