

[illegible]

1. U3 S1T5155: water-soluble flux only. No no-clean flux.
No ultrasonic or megasonic cleaning (SiTime).
2. Reflow: IPC/JEDEC J-STD-020 profile.
3. J2 SMA (132134): hand-solder after reflow. J3-J10 SMP (SMP-MSSB-PCT10T):
remove the cap, insert loose, mate the SDRs, solder the legs from the
back (self-align), then remove the SDRs and solder the tab on top.
4. Outputs: J3-J6 10 MHz ~ j7 4dBm/50R, j7-J10 PPS 3.3 V CMOS.

PPS_IN J2

R23 49.9R

R22 100R

D8 TPD1E05U06

R21 10k

U5 SN74LVC1G17DBVR

PPS_BUF

+3V3_CLK

C28 100nF

R24 1k

D9 YEL PPS

PPS_BUF

U6 SN74LVC125APWR

+3V3_CLK

PPS_BUF 1A 2A 3A 4A

VCC 1Y 2Y 3Y 4Y

PPS1_Y PPS2_Y PPS3_Y PPS4_Y

R25 22R

D10 TPD1E05U06

PPS1_Y

R26 22R

D11 TPD1E05U06

PPS2_Y

R27 22R

D12 TPD1E05U06

PPS3_Y

R28 22R

D13 TPD1E05U06

PPS4_Y

PPS_B210_1 J7

PPS_B210_2 J8

PPS_B200_1 J9

PPS_B200_2 J10

+3V3_CLK

C29 100nF

Size: A3	Date: 2026-10-07	Rev: C
KiCad E.D.A. 10.0.6		Id: 1/1