

FOR STAINLESS STEEL

TEMP.°F

CORRECTION FACTORS											
TEMP.	TP304	TP316	TP347	TEMP.	TP304	TP316	TP347	TEMP.	TP304	TP316	TP347
-325 TO 200	1.00	0.89	0.89	750	1.60	0.99	1.13	1150	2.90	1.96	2.08
				800	1.67	0.99	1.14	1200	3.70	2.45	3.33
300	1.11	0.93	0.98	850	1.72	1.01	1.16	1250	5.12	3.14	4.63
400	1.22	0.95	1.05	900	1.77	1.04	1.18	1300	6.80	4.16	6.17
500	1.33	0.97	1.10	950	1.83	1.10	1.20	1350	9.25	5.55	8.32
600	1.44	0.97	1.12	1000	1.89	1.19	1.23	1400	11.89	7.09	10.74
650	1.49	0.98	1.12	1050	1.96	1.36	1.27	1450	16.65	9.00	13.88
700	1.54	0.98	1.13	1100	2.22	1.60	1.33	1500	22.20	11.10	16.65

DIMENSION (mm)

		TRUNNION – NOMINAL PIPE SIZE																	
		2”		3”		4”		6”		8”		10”		12”		14”			
		MIN. SCH. SAME AS HEADER																	
		Y		80		110		140		190		240		290		340			
NOM. PIPE SIZE	PIPE SCH.	PAD REQUIREMENTS																PAD TH’K MIN. ”E”	DIM. ”D”
		NO PAD	PAD	NO PAD	PAD	NO PAD	PAD	NO PAD	PAD	NO PAD	PAD	NO PAD	PAD	NO PAD	PAD	NO PAD	PAD		
		MOMENT CAPACITY OF ONE TRUNNION. (INCH–KIPS)																	
3”	5S	1	3															2.0	30
4”	5S	1	2	2	5													2.0	40
6”	5S	1	3	2	6	4	10											3.0	45
8”	5S	1	3	2	5	3	9	7	20									3.0	60
10”	5S			2	7	4	11	8	24	14	41							3.5	65
12”	5S			2	8	5	14	11	30	18	51	28	79					4.0	75
14”	5S					4	12	9	26	16	45	25	70	35	98			4.0	75
16”	5S					4	12	10	27	16	46	25	71	35	100	42	120	4.0	85
18”	5S							9	25	15	43	24	67	33	94	40	113	4.0	90
20”	5S							10	29	18	50	27	77	39	108	47	131	5.0	100
24”	5S							12	33	20	57	31	88	44	124	53	149	5.5	120
30”	5S									22	62	34	97	48	136	58	164	6.5	145
3”	10S	2	5															3.0	30
4”	10S	1	4	3	9													3.0	40
6”	10S	1	4	3	9	5	14											3.5	45
8”	10S	1	4	3	9	5	14	11	31									4.0	60
10”	10S			3	9	5	15	12	33	20	55							4.0	65
12”	10S			3	10	6	16	12	34	21	58	32	90					4.5	75
14”	10S					6	16	12	35	21	59	33	92	46	130			5.0	75
16”	10S					5	15	12	33	20	55	30	86	43	121	52	146	5.0	85
18”	10S							11	31	18	52	29	81	40	114	49	138	5.0	90
20”	10S							13	37	22	62	34	96	48	135	58	163	5.5	100
24”	10S							14	41	25	70	38	108	54	152	65	183	6.5	120
30”	10S									31	87	48	135	67	189	81	228	8.0	145

中威工程顧問股份有限公司 CHUNG WEI ENGINEERING CONSULTING CO., LTD.						DETAIL OF PIPE SUPPORT TYPE-61 (3 OF 3)						ENGINEERING STANDARD	
												HP6-DSD-A4-500-001	
BY	SHIH		CHK.	YANG								D-74	REV.
DATE	7/15/'24		APPR.	CHEN									1

FILE: D-74M.DWG