



LINE SIZE	A	B	C (NOTE 1)	D (NOTE 4)	E
1/2"	100	—	CUT FROM H-200X100X5.5X8	150	—
3/4"	100	—		150	—
1"	100	—		150	—
1 1/2"	100	—		150	—
2"	100	—		150	50
2 1/2"	100	—		150	50
3"	100	—		250	50
4"	100	—		250	50
5"	100	—		250	50
6"	100	—		250	50
8"	100	—		250	50
10"	130	9	CUT FROM H-200X200X8X12	—	50
12"	130	9		—	50
14"	130	9		—	50
16"	250	12	FAB. FROM 12 ^t PLATE	—	50
18"	250	12		—	50
20"	250	12		—	50
24"	300	12		—	50

1. SHOES FOR PIPES 1 1/2" & SMALLER MAY BE FABRICATED FROM 6 T₁ PLATE, 2" THRU. 14" FROM 9 PLATE, 16" THRU. 24" FROM 12 T₁ PLATE

66-1 1/2B(P)-A(A)-130-500

DENOTE LINE SIZE

DENOTE REIN. PAD IS REQ'D

MODIFY LOPS=500 (IN mm) IF ANY

MODIFY HOPS=130 (IN mm) IF ANY

SEE SH'T D-80A TABLE "A"

SEE SH'T D-80A TABLE "B"

3. FOR PADS MATERIAL USE PIPE MATERIAL THAT CUT FROM THE PIPE OR EQUIVALENT TO THE PIPE.

4. LONGITUDINAL LENGTH OF PIPE SHOE (SAY LOPS)
SHALL BE CALCULATED IN THE CASE WITH PIPE STOP.

5. HOPS=HEIGHT OF PIPE SHOE, LOPS=LENGTH OF PIPE SHOE.

中威工程顧問股份有限公司 CHUNG WEI ENGINEERING CONSULTING CO., LTD.						ENGINEERING STANDARD		
								HP6-DSD-A4-500-001
DETAIL OF PIPE SUPPORT TYPE-66 (1 OF 3)						D-80		REV. 1