

Technical drawing of a circular manhole cover assembly, showing two views: a top elevation (left) and a side elevation (right).

Top Elevation (Left):

- Shows a circular cover with a diameter dimension $d1$.
- Angular dimensions of 90° and 120° are indicated for the cover's profile.
- Radial dimensions of 50 and 16 are shown.
- A dimension ϕ indicates the height of the cover from the base.
- Base dimensions C and b are shown.

Side Elevation (Right):

- Shows the cover (1) mounted on a frame (2) with vertical supports (3).
- Horizontal dimensions of 12 and 12 are shown between the supports.
- A dimension m is shown from the center to the edge of the frame.
- Overall height dimensions H and h are indicated.
- Base dimensions L and 3 (TYP.) are shown.
- Callouts 4, 5, 6, and 7 point to specific components or features.

Callouts:

- 1: Cover
- 2: Frame
- 3: Vertical supports
- 4: Top flange
- 5: Side flange
- 6: Gasket/seal
- 7: Base

Text:

- 3 SIDES TYP. 6
- (TYP.)
- TYP.
- ELEV.

NO.	6	7
PIECE	2	6
PIPE SIZE	STOP ANGLE	PLATE
26"	L100X10	6 TH'K
28"		
30"		
32"		
36"		
40"		
42"		

1. FOR DIMENSIONS AND INFORMATION NOT SHOWN ON THIS DWG. SEE SH'T D-80B.

$$80 - 30B - A(A) - 130 - 500$$

DENOTE TYPE NO.	MODIFY LOPS=500 (IN mm) IF ANY
DENOTE LINE SIZE	MODIFY HOPS=130 (IN mm) IF ANY
SEE NOTE 3	SEE SH'T D-80A TABLE "B"

3. TYPE-A FOR INSULATION THICKNESS < 100
TYPE-B FOR INSULATION THICKNESS > 100 < 150

4. LOADING CONDITION : CARBON STEEL SADDLE WITH MAX. PIPE TEMPERATURE 700°F & PRESSURE 300 PSI.

5. HOPS=HEIGHT OF PIPE SHOE, LOPS=LENGTH OF PIPE SHOE.

中威工程顧問股份有限公司 CHUNG WEI ENGINEERING CONSULTING CO., LTD. DETAIL OF PIPE SUPPORT TYPE-80 (2 OF 2) ENGINEERING STANDARD HP6-DSD-A4-500-001 D-96 REV. 1					
BY	SHIH		CHK.	YANG	
DATE	7/15/'24		APPR.	CHEN	