



DIMENSION (mm)

TYPE	D	C	MAX.RECOM. LOAD (Kg)	
			650°F	750°F
MTR - 3/8	3/8"	152	270	240
MTR - 1/2	1/2"	152	510	460
MTR - 5/8	5/8"	152	820	730
MTR - 3/4	3/4"	152	1230	1100
MTR - 7/8	7/8"	152	1710	1520
MTR - 1	1"	152	2250	2000
MTR - 1 1/4	1 1/4"	152	3630	3240
MTR - 1 1/2	1 1/2"	152	5280	4700
MTR - 1 3/4	1 3/4"	178	7120	6350
MTR - 2	2"	203	9390	8370
MTR - 2 1/4	2 1/4"	229	12430	11000
MTR - 2 1/2	2 1/2"	254	15200	13560

NOTES :

1. MATERIAL : CARBON STEEL
2. DESIGNATION NUMBER DENOTE AS FOLLOWS :

MTRL-3/8-600

DENOTE DIM. "L" (IN MM)

DENOTE DIM. "D"

DENOTE W/LH THREAD

DENOTE MACHINE THREADED ROD
3. LENGTH MAY CUT & THREAD TO SUIT IN FIELD .
4. REF. GRINNELL CATALOG FIG. 140 & FIG. 253 OR EQ.
5. FURNISHED WITH "UNC" THREADS.
6. MTR : MACHINE THREAD ROD W/RIGHT HAND THREAD FOR BOTH ENDS,
MTRL: MACHINE THREAD ROD W/RIGHT HAND THREAD FOR ONE END
& LEFT HAND THREAD FOR OTHER END.

FILE: M-22M.DWG

中威工程顧問股份有限公司 CHUNG WEI ENGINEERING CONSULTING CO., LTD.						ENGINEERING STANDARD	
						HP6-DSD-A4-500-001	
BY	SHIH		CHK.	YANG		M-22	REV. 1
DATE	7/15/'24		APPR.	CHEN			