




DIMENSIONS (mm)

TYPE	MEMBER	A	B	C	D	E	F	G	H	ØJ	K	T
LGP-C-1	L50X50X6	150	100	50	30	30	60	—	—	19	5/8"	9
LGP-C-2	L65X65X6	160	130	65	35	30	70	—	—	22	3/4"	9
LGP-C-3	L75X75X9	160	140	75	40	30	70	—	—	22	3/4"	9
LGP-C-4	C100X50X5	170	160	100	50	30	80	—	—	22	3/4"	10
LGP-C-5	C100X50X5	170	160	100	—	30	80	25	50	19	5/8"	10
LGP-C-6	C125X65X6	170	180	125	—	30	80	35	55	22	3/4"	10
LGP-C-7	C150X75X9	190	220	150	—	30	100	40	70	22	3/4"	12
LGP-C-8	C180X75X7	210	260	180	—	35	110	45	90	22	3/4"	12
LGP-C-9	C200X90X8	220	300	200	—	35	120	50	100	22	3/4"	12
LGP-C-10	C250X90X9	250	350	250	—	40	140	60	130	25	7/8"	16

NOTES :

1. DESIGNATION NUMBER DENOTE AS FOLLOWS :



2. MATERIAL: SAME AS THE METAL TO WHICH IT IS CONNECTED

3. IF REINFORCING PAD IS ADDED, NOTE THAT THE PAD THICKNESS IS INCLUDED IN THE DIMENSION A OR A+t.

FILE: M-34M.DWG

中威工程顧問股份有限公司 CHUNG WEI ENGINEERING CONSULTING CO., LTD.						ENGINEERING STANDARD	
BY	SHIH		CHK.	YANG		HP6-DSD-A4-500-001	
DATE	7/15/'24		APPR.	CHEN			
LUG PLATE TYPE-C						M-34	
						REV. 1	