

NOTES :

1. FOR ALLOY STEEL, STAINLESS STEEL & STRESS RELIEF LINES, THE MATERIALS SHALL BE THE SAME AS MAIN LINES.
2. DIMENSION "H" SHALL BE CUT TO SUIT IN FIELD.
3. THIS TYPE SHALL BE USED WITH M-42 TO DETERMINE THE LOWER COMPONENT TYPE.
4. DESIGNATION NUMBER DENOTE AS FOLLOWS :

10-6B-05B

— DENOTE THE LOWER COMPONENT TYPE SEE M-42

— DENOTE DIMENSION "H" (IN 100mm)

— DENOTE SUPPORTED LINE SIZE "A"

— DENOTE TYPE NO.
5. DIMENSION "L" IS BASED ON LONG RADIUS ELBOW TO WHICH DUMMY PIPE IS WELDED.
6. THIS SUPPORT SHALL NOT BE USED IN THE FOLLOWING CONDITIONS:
 - A. DESIGN TEMPERATURE $\leq 10^{\circ}$ OR $\geq 400^{\circ}$
 - B. DESIGN PRESSURE $\geq 70 \text{ Kg/cm}^2 \text{ G}$

中威工程顧問股份有限公司 CHUNG WEI ENGINEERING CONSULTING CO., LTD.						DETAIL OF PIPE SUPPORT TYPE-10		ENGINEERING STANDARD	
								HP6-DSD-A4-500-001	
BY	SHIH		CHK.	YANG				D-10A	
DATE	7/15/'24		APPR.	CHEN					